




Description Automatic reclosing device  
 Code ReStart Rm PRO 4P  
 Suitable for RCBO's MDC - 1P+N/2P/4P - 30 mA  
 Rated voltage AC 230 V  
 Rated current 6 - 10 - 13 - 16 - 20 -25 - 32 A  
 No. modules 3  
 Standard IEC EN 63024  
 Rated frequency (Hz) 50 Hz

|                                                         |                                                      |                                                                   |                                   |
|---------------------------------------------------------|------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------|
| Distribution system                                     | TT - TN-S                                            | Rated non-operating resistance between live parts and earth (Rdo) | 8 kΩ                              |
| Insulation voltage (Ui)                                 | 500 V                                                | Rated operating resistance between live parts and earth (Rd)      | 16 kΩ                             |
| Rated impulse withstand voltage (Uimp)                  | 4 kV                                                 | Maximum operating frequency                                       | 30 oper./h                        |
| Overvoltage category                                    | III                                                  | Mechanical endurance                                              | 4000                              |
| Dielectric strength test voltage between pole and earth | 2500 V ac for 1 minute                               | Type of residual current protection                               | AC - A - A[IR]                    |
| Rated residual operating current                        | 30 mA                                                | Operating temperature                                             | -25 +60 °C                        |
| Stocking temperature                                    | -40°C ÷ +70°C                                        | Type of contacts                                                  | Photomos (potential free)         |
| Voltage operating                                       | 5-230 V ac/dc                                        | Current operating                                                 | 0.6 mA (min)-100 mA cosφ= 1 (max) |
| Operating frequency                                     | 50 Hz                                                | Use category                                                      | AC12                              |
| Operating modes                                         | NO/NC/NO with handle position signalling function    | Rated tightening torque                                           | 0.4 Nm                            |
| Terminal section                                        | ≤ 2.5 mm²                                            | Automatic reclosure for untimely tripping                         | Yes                               |
| Earth failure test                                      | Yes                                                  | Continuous system monitoring                                      | Yes                               |
| Completeable with                                       | GWD0951 Auxiliary contact - GW90992 RS485 BUS Module | Electrocod                                                        | 1413                              |

## DIMENSIONAL



## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
 24069 Cenate Sotto - Bergamo - Italy  
 tel. +39 035 94 61 11 fax +39 035 94 69 09  
 Company subject to the management and  
 coordination of Polifin S.p.A.

www.gewiss.com  
 sat@gewiss.com  
 Last update 11/09/2026

Data, measures, designs and pictures are shown  
 only as informative purposes,  
 and could be changed without previous notice