



#### Description MINIATURE CIRCUIT BREAKER

Code MT 100

No. of poles 2P

No. modules 2


Rated current 40 A

Curve D

Rated voltage 230-400 V

|                                             |                                               |                                             |                        |
|---------------------------------------------|-----------------------------------------------|---------------------------------------------|------------------------|
| Standard                                    | IEC EN 60898-1                                | Rated frequency (Hz)                        | 50/60 Hz               |
| Breaking capacity EN 60898 230V (Icn)       | 10000 A                                       | Breaking capacity EN 60898 400V (Icn)       | 10000 A                |
| Breaking capacity EN 60898 (Ics)            | 0.75 x Icn                                    | Breaking capacity IEC/EN 60947-2 230V (Icu) | 25 kA                  |
| Breaking capacity IEC/EN 60947-2 400V (Icu) | 15 kA                                         | Breaking capacity IEC/EN 60947-2 (Ics)      | 50% Icu                |
| Insulation voltage (Ui)                     | 500 V                                         | Rated impulse withstand voltage (Uimp)      | 4 kV                   |
| Minimum operating voltage                   | 12 V ac/dc                                    | Maximum operating voltage                   | 440 V AC / 220 V DC    |
| Electrical endurance                        | 10.000                                        | Mechanical endurance                        | 20.000                 |
| Section rigid cable                         | <=1x35 - <=2x16 - <=1x16+2x10 mm <sup>2</sup> |                                             | Section flexible cable |
| Rated tightening torque                     | 2 Nm                                          | Operating temperature                       | -25 +70 °C             |
| Stocking temperature                        | -40°C ÷ +70°C                                 | Electrocod                                  | 1411                   |

## DIMENSIONAL



## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09  
Company subject to the management and  
coordination of Polifin S.p.A.

www.gewiss.com  
sat@gewiss.com  
Last update 11/09/2026

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice