



Description HIGH PERFORMANCE MINIATURE CIRCUIT BREAKER

Code MTHP 250

No. of poles 3P

No. modules 4.5


Rated current 25 A

Curve C

Rated voltage 230-400 V

|   |   |   |  |
|---|---|---|--|
| Standard                                    | IEC/EN 60898-1, IEC/EN 60947-2                | Rated frequency (Hz)                        | 50/60 Hz                                 |
| Breaking capacity EN 60898 230V (Icn)       | 25000 A                                       | Breaking capacity EN 60898 400V (Icn)       | 25000 A                                  |
| Breaking capacity EN 60898 (Ics)            | 0.75 x Icn                                    | Breaking capacity IEC/EN 60947-2 230V (Icu) | 30 kA                                    |
| Breaking capacity IEC/EN 60947-2 400V (Icu) | 25 kA   | Breaking capacity IEC/EN 60947-2 (Ics)      | 75% Icu                                  |
| Insulation voltage (Ui)                     | 500 V   | Rated impulse withstand voltage (Uimp)      | 6 kV                                     |
| Minimum operating voltage                   | 12 V ac/dc                                    | Maximum operating voltage                   | 440 V ac                                 |
| Electrical endurance                        | 10.000  | Mechanical endurance                        | 20.000                                   |
| Section rigid cable                         | <=1x70 - <=2x25 - <=2x25+1x10 mm <sup>2</sup> | Section flexible cable                      | <=1x50 - <=2x25 - <=3x16 mm <sup>2</sup> |
| Rated tightening torque                     | 3.5 / 3 (terminals)                           | Operating temperature                       | -25 +70 °C                               |
| Stocking temperature                        | -40°C ÷ +70°C                                 | Electrocod                                  | 1411                                     |

### DIMENSIONAL



### STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09  
Company subject to the management and  
coordination of Polifin S.p.A.

www.gewiss.com  
sat@gewiss.com  
Last update 02/07/2026

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice