Product Data Sheet

GW95458


90 RCD Range




Description	**HIGH PERFORMANCE RESIDUAL CURRENT DEVICE**
Code	**BDHP**
No. of poles	**4P**
No. modules	**6**
Rated current	**100 A**
Rated residual operating current	**300 mA**
Type	**A**
Rated voltage (IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G)	**400 V**

Standard	**IEC/EN 61009-1 app. G, IEC/EN 61009-2-1 app. G**	**Rated frequency (Hz)**	**50/60 Hz**
Insulation voltage (Ui)	**500 V**	**Rated impulse withstand voltage (Uimp)**	**4 kV**
Overvoltage category	**III**	**Level of immunity (8/20 µs)**	**250 A**
Section rigid cable	**Max 70 mm²**	**Section flexible cable**	**Max 50 mm²**
Operating temperature	**-25 +40 °C**	**Stocking temperature**	**-40°C ÷ +70°C**
Rated tightening torque	**3.5 / 3 (terminals)**	**Assembly position**	**Any**

DIMENSIONAL



WIRING DIAGRAM



STANDARDS/APPROVALS

CE UKCA Reach Declaration

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com

Last update 03/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice