Product Data Sheet

GW95809


90 RCD Range




Description	**RCCB WITH OVERCURRENT PROTECTION**
Code	**MDC 60**
No. of poles	**2P**
No. modules	**2**
Rated current	**25 A**
Rated residual operating current	**30 mA**
Type	**A[IR]**
Curve	**C**
Rated voltage (IEC/EN 61009-1, 61009-2-1)	**230/240 V**
Energy limiting class	**3**

Standard	**IEC/EN 61009-1, IEC/EN 61009-2-1**	**Rated frequency (Hz)**	**50/60 Hz**
Breaking capacity IEC/EN 61009-1 230V (Icn)	**6000 A**	**Breaking capacity IEC/EN 61009-1 (Ics)**	**1 x Icn**
Breaking capacity IEC/EN 60947-2 230V (Icu)	**10 kA**	**Breaking capacity IEC/EN 60947-2 (Ics)**	**75% Icu**
Insulation voltage (Ui)	**500 V**	**Level of immunity (8/20 µs)**	**3000 A**
Rated impulse withstand voltage (Uimp)	**4 kV**	**Overvoltage category**	**III**
Electrical endurance	**10.000**	**Mechanical endurance**	**20.000**
Section rigid cable	**<=1x35 - <=2x16 - <=1x16+2x10 mm²**	**Section flexible cable**	**<=1x35 - <=2x16 - <=1x16+2x10 mm²**
Double connection	**YES (only down stream)**	**Rated tightening torque**	**2 Nm**
Operating temperature	**-25 +60° C (derating of In with T>30° C)**	**Stocking temperature**	**-40°C ÷ +70°C**
Auxiliaries compatibility	**Yes**	**ReStart compatibility**	**Yes**
Assembly position	**Any**		

DIMENSIONAL



WIRING DIAGRAM



STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com

Last update 03/11/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice