






The IP40 protected decorative enclosures are available in sizes from 8 to 72M. They provide superior aesthetic integration. They are available with smoked transparent doors or with blank doors that can be equipped with safety lock, characterized by the "PUSH" opening and closing. They can be equipped with bipolar and unipolar terminal blocks, 80 A and 125 A, with screw wiring; they allow to create simple and neat wiring reducing the set-up time of the enclosure.

Isolatie-klasse	II (conform de norm IEC 61140)	Kleur	Wit RAL 9016
Buitenafm. LxHxD (mm)	400x850x150	IP-graad	IP40
Vermogen-verspreiding (W)	75	Stootbestendigheid	IK08
Nominale spanning	400 V	Deur kleur	Blind
Aantal modules EN 50022	72 (18x4)	Nominale stroom	125 A
Gloedraadproef	650 °C	Bedrijfstemperatuur	-25 +60 °C
Type materiaal	Halogeenvrij conform EN 60754-2	Electrocod	0321
Thermospanning met kogel	70 °C	Accessoires voor isolatieherstelling	Schroefdroppen (GW44623) of bevestigingsbeugels uit hars (GW44621)
Standaard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Isolatie-spanning	750 V
Max. installeerbare klemmenblokken	4 x 18 modules		



## DIMENSIONAL

### TECHNICAL SYMBOLOGY

	<b>IP</b>	<b>IK</b>	<b>GWT</b>		<b>HF</b> HALOGEN FREE	
II (conform de norm IEC 61140)	IP40	IK08	650 °C	-25 +60 °C	Halogeenvrij conform EN 60754-2	70 °C

### STANDARDS/APPROVALS

