




IP65 range of watertight enclosures from 8 to 72M with smoked transparent door and equipped with screw wiring multipolar terminal blocks, 80 A and IP20. The main technical features are: reversible front and back panel, removable frames and panels with windows and detachable doors with up to 180° opening and lock accessory. The terminal blocks allow to create simple and neat wiring reducing the set-up time of the enclosure.

| | | | | |
|---------------------------------------------|-------------------------------------------------------------------|---------------------------|----------------------------------------------|----------------|
| Isolatie-klasse | II (conform de norm IEC 61140) | | Kleur | Grijs RAL 7035 |
| Buitenafm. LxHxD (mm) | 410x463x140 | IP-graad | IP65 | |
| Vermogen-verspreiding (W) | 43 | Stootbestendigheid | IK09 | |
| Nominale spanning | 400 V | Deur kleur | Transparant fumé | |
| Klemmenblokken | 80 A - IP20 tweepolige gaten met schroeven | Aantal modules EN 50022 | 36 (18x2) | |
| Nominale stroom | 125 A | Gloeidraadproof | 650 °C | |
| Bedrijfstemperatuur | -25 +60 °C | Type materiaal | Halogeenvrij conform EN 60754-2 | |
| Electrocod | 0321 | Thermospanning met kogel | 70 °C | |
| Accessoires voor isolatieherstelling | Schroefdoppen (GW44623) of bevestigingsbeugels uit hars (GW44621) | Standaard | EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49 | |
| Isolatie-spanning Pool 2 (mm ²) | 1000 V conform EN 62208 zowel bij AC als DC | Pool 1 (mm ²) | N/E 2x[(3x16) + (17x10)] | |



DIMENSIONAL

TECHNICAL SYMBOLOGY



IP

IP65

IK

IK09


GWT

650 °C



HF

Halogeenvrij conform EN 60754-2



70 °C



EN 62208
1000 V conform EN 62208 zowel bij AC als DC

STANDARDS/APPROVALS



