



Behuizing voor wandbevestiging conform de Duitse norm met tweepolige klemmenblokken en twee verwisselbare flenzen (2 flenzen met doordrukelementen).

Isolatie-klasse	II	Kleur	Grijs RAL 7035
Buitenafm. LxHxD (mm)	298x570x140	IP-graad	IP65
Installatie	Wandmontage	Stootbestendigheid	IK07
Deur kleur	Transparant fumé	Klemmenblok N (mm ²)	(6x25)+(20x10)
Klemmenblok T (mm ²)	(6x25)+(20x10)	Aantal modules EN 50022	36 (12x3)
Gloedraadproef	750 °C	Standaard	IEC EN 60670-1; IEC EN 60670-24; DIN VDE 0603-1
Bedrijfstemperatuur	-25 +60 °C	Electrocod	0321
Thermospanning met kogel	70 °C	Pool 1 (mm ²)	N (6x35)+(20x10)
Pool 2 (mm ²)	E (6x35)+(20x10)		



DIMENSIONAL

TECHNICAL SYMBOLOGY



II

IP

IP65

IK

IK07

GWT

750 °C



-25 +60 °C



70 °C

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 25/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice