


Light pliable conduits FK9 range, made of PVC, classification 22212, available in six diameters, from 16 to 50 mm, with or without cable puller, colour grey RAL 7035. Suitable for electrical and/or data transmission systems. Recommended for concealed installation in vertical walls or ceilings. The FK9 conduits comply with the standards EN 61386-1 and EN 61386-22.

Kleur	Grijs RAL 7035	Materiaal	PVC
Type	zonder trekdraad	Ø leidingen (mm)	16
Gloeidraadproef	960 °C	Bestendigheid tegen druk	2 (licht - 320 N)
Bestendigheid tegen impacten	2 (Light - 320 N)	Bestendigheid tegen buigen	2 (soepel)
Elektrische eigenschappen	2 (met elektrische isolerende eigenschappen)	Bescherming tegen binnendringen van vaste voorwerpen zonder accessoires	0
Bescherming tegen binnendringen van water	0	Bestendigheid tegen corrosie	PVC natuurlijk bestand tegen corrosie
Vuurvastheid	1 (niet-vlamverspreidend)	Bescherming tegen binnendringen van vaste voorwerpen met GF-koppeling	4
Standaard	EN 61386-1 EN 61386-22	Classificering	22212

DIMENSIONAL



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

