




The range consists of seven different sizes of connection and junction boxes made of die-cast aluminium alloy. Suitable for every application, they are particularly recommended in industrial environments and on machinery (for particular applications is necessary contact GEWISS Service Technical Assistance). The boxes can be surface-mounted from both the inside and outside. The earth terminal (for protection against indirect contact) is on both the bottom and the lid. The outside of the box is covered with epoxy-polyester paint to ensure the maximum resistance with perfect design integration. There are also unpainted versions and ATEX versions for Zone 2 (G) and Zone 22 (D). The stainless steel fixing screws of the cover are unlosable, the bottom of the box has an insert for the earth connection and is prepared for the assembly of the DIN rail. Accessories include back-mounting plates in galvanised steel (available from the second dimension).

Materiaal	Painted aluminium alloy	Kleur	Metaalgrijs
IP- graad	IP66	Binnenafm. LxHxD (mm)	178x156x75
Stoot- bestendigheid	IK08	Buitenafm. LxHxD (mm)	189x167x80
Max. Ø gaten mogelijk	37 mm	Dekselschroeven (aantal en type)	4 - Stainless steel with double slotted head
Deksel	Laag geschroefd	Bedrijfstemperatuur	-60 +100 °C
Wanden	Egale	Electrocod	0230



## DIMENSIONAL



## TECHNICAL SYMBOLOGY

**IP**

IP66

**IK**

IK08

## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 09/04/2024

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice