



The floor-standing I-ON charging stations are the JOINON solutions for public and semi-public access, designed for charging electric vehicles and to withstand any wear including impacts, stress, vandalism and atmospheric agents. They are the first and only on the market able to guarantee the IP55 level of protection. The special hexagonal design allows the units to be adapted into any urban context and parking configuration, with a targeted focus on the User Experience for the Driver. They are available with standard JoinOn graphics, which may be customised on request.

INPUT		-	Socket/Connector Nr. (Type)	2 (Type 2 socket, with shutters)
Terminal blocks	5 x 16 mm ²		Charging activation	Free access
Nominale stroom	32 A		Human Interface	LED RGB and TFT Display
Total power	22 Kilowatt		Connectivity	Neer
OUTPUT		-	MECHANICAL FACTS	-
Nominale spanning	400 V		Mounting and installation	Floor mounting
Kleur	Grey, Headboard RAL 7011		Voeding max.	11 kW per socket
Materiaal	Steel sheet		Thermal-magnetic protection	20A - 4P - Curve D
External treatments	Anti-corrosion and anti-graffiti		Type aardlekbeveiliging	20 A - 4P - Type B
IP-graad	IP55		Power meter	Neer
Stootbestendigheid	IK10		DC Leakage check	Not needed
Bedrijfstemperatuur	-25 +50 °C		(Auto)restart electrical protections	Neer
Customizations	Yes (front)			

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS

