


Flush-mounting auxiliary touch module with two commands. Two axial touch areas on the front; this product can be used in combination with the auxiliary wired inputs of the following devices of the Chorusmart range: connected commands, connected 1- channel On/Off actuator, connected movement sensors, TOUCH and EVO commands, or as a wired command for a connected 2-channel ZigBee interface. The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol.

Omschrijving	Auxiliary touch 2-commands module	Voeding	100 ÷ 240 V ac - 50/60 Hz
Aantal modules	1	Aantal ingangskanalen	-
Local control	Via 2 frontal touch areas (must be completed with ICE Touch plate)	Auxiliary input channel voltage	-
Opslagtemperatuur	-25 ÷ +70 °C	Aantal uitgangskanalen	2
Bedrijfstemperatuur	-5 ÷ +45 °C	Uitgang contacten	-
Relative humidity (non-condensative)	Max 93%	240 V ac Incandescent-halogen lamps	-
Front light signaling	Blauwe led	240 V ac LED lamps	-
Aansluitklemmen voor bekabeling	Met schroef	Loads piloted from electronic transf. 240 V ac	-
Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5	240 V Fluorescent lamps	-
Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5	Load control	-
Context	Dry indoor places	Acoustic signalling element	Buzzer
IP-graad	IP20 (with plate fitted)	Standaard	2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863 (RoHS), EN 60669-2-1, EN 60669-1, EN IEC 63000

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with plate fitted)

STANDARDS/APPROVALS

