


Britse norm



Wiring devices system characterized by its profile and shape inspired to the Chorus family feeling. Wide range of plates with an Italian design, articulated into two families, GEO and LUX cover plates, available in many materials and finishes. The range is available in three colors: glossy white, satin black, painted titanium and fits in 3x3 inches (1-gang) and 3x6 inches (2-gang) British Standard boxes. Range expandable thanks to the Chorus modular devices.

| | | | |
|--|-------------------------------------|---|---------------------------------|
| Categorie | 3 gang one-way switch | Type | 3 gang |
| Knop | Neutraal | Kleur | Wit |
| Omschrijving | 1P - 10AX | Spanning | 250 V AC |
| Rated power of 230V LED lamps | 100 W | Standaard | EN 60669-1 |
| Bestendigheid bij testspanning | 2000 V bij 50 Hz gedurende 1 minuut | Isolatieweerstand | > 5 MOhm |
| Aansluitklemmen voor bekabeling | Met schroef | Verlengd bedrijf (aantal positiewijzigingen) | 40.000 bij In 250 V AC cosφ=0,6 |
| Thermospanning met kogel | 125 °C | Gloeidraadproef | 850 °C |
| Klemgreep op kabeltractie | > 50 N | Aanspanvermogen aansluitklem flexibele kabels (mm²) | min. 1,5 - max. 2,5 |
| Aanspanvermogen aansluitklem starre kabels (mm²) | min. 1,5 - max. 2,5 | | |

DIMENSIONAL

TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

