

# Product Data Sheet

## GW10339M

Chorus - Residentiële serie  
Britse norm



Wiring devices system characterized by its profile and shape inspired to the Chorus family feeling. Wide range of plates with an Italian design, articulated into two families, GEO and LUX cover plates, available in many materials and finishes. The range is available in three colors: glossy white, satin black, painted titanium and fits in 3x3 inches (1-gang) and 3x6 inches (2-gang) British Standard boxes. Range expandable thanks to the Chorus modular devices.

Categorie	Switched socket	Omschrijving	2P+E - 13 A
Kleur	Wit	Type	Achtergrondverlichting
Spanning	250 V AC	Standaard	Britse norm
Eigenschappen	Met veiligheidsplaten	Voor stekkerpennen	Platte
Aansluitklemmen voor bekabeling	Met schroef	Standaard	BS 1363-2
Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut	Isolatiweerstand	> 5 MOhm
Thermospanning met kogel	125 °C	Gloeidraadproef	850 °C
Klemgreep op kabeltractie	> 50 N	Aanspanvermogen aansluitklem flexibele kabels (mm <sup>2</sup> )	min. 1,5 - max. 2,5
Aanspanvermogen aansluitklem starre kabels (mm <sup>2</sup> )	min. 1,5 - max. 2,5	Verlengd bedrijf (aantal positiewijzigingen)	40.000 bij In 250 V AC cosφ=0,6
Prolonged operation socket (no.of position changes)	10.000 bij In 250 V AC cosφ=0,8		

## DIMENSIONAL

## TECHNICAL SYMBOLOGY



## STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1  
24069 Cenate Sotto - Bergamo - Italy  
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com  
sat@gewiss.com  
Last update 29/04/2024

Data, measures, designs and pictures are shown  
only as informative purposes,  
and could be changed without previous notice