


Britse norm



Wiring devices system characterized by its profile and shape inspired to the Chorus family feeling. Wide range of plates with an Italian design, articulated into two families, GEO and LUX cover plates, available in many materials and finishes. The range is available in three colors: glossy white, satin black, painted titanium and fits in 3x3 inches (1-gang) and 3x6 inches (2-gang) British Standard boxes. Range expandable thanks to the Chorus modular devices.

Categorie	3 gang one-way switch	Type	3 gang
Knop	Neutraal	Kleur	Titaan
Omschrijving	1P - 10AX	Spanning	250 V AC
Rated power of 230V LED lamps	100 W	Standaard	EN 60669-1
Bestendigheid bij testspanning	2000 V bij 50 Hz gedurende 1 minuut	Isolatieweerstand	> 5 MOhm
Aansluitklemmen voor bekabeling	Met schroef	Verlengd bedrijf (aantal positiewijzigingen)	40.000 bij In 250 V AC cosφ=0,6
Thermospanning met kogel	125 °C	Gloeidraadproef	850 °C
Klemgreep op kabeltractie	> 50 N	Aanspanvermogen aansluitklem flexibele kabels (mm²)	min. 1,5 - max. 2,5
Aanspanvermogen aansluitklem starre kabels (mm²)	min. 1,5 - max. 2,5		

DIMENSIONAL

TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

