




Wireless connected device with Zigbee protocol from the ChoruSmart system that can be with Home Gateway for "CONNECTED SMART HOME" solutions, for residential and small offices, both for new builds and renovations. Zigbee technology is a secure and reliable technology in which data is encrypted and every node in the network ensures reachability across all devices (mesh network).

Kleur	Glossy Titanium	Uitgang contacten	1 NO 2 A (AC1) 240 Vac
Voeding	100 ÷ 240 V ac - 50/60 Hz	Aantal modules	1
Aantal uitgangskanalen	1	Radio connections	Zigbee (IEEE 802.15.4)
Standaard	2014/53/EU, 2011/65/EU + 2015/863, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000	Bedrijfstemperatuur	-5 ÷ +45 °C
Relative humidity (non-condensative)	Max 93%	Power output Zigbee	10 dBm
Aansluitklemmen voor bekabeling	Met schroef	Aanspanvermogen aansluitklem flexibele kabels (mm ²)	Max. 1,5
Aanspanvermogen aansluitklem starre kabels (mm ²)	Max. 1,5	Categorie	Bewegingsdetector
Aantal ingangskanalen	2 (for local command replication or sending additional Zigbee commands)	Ingangsspanning	Mains supply voltage
IP-graad	IP20	240 V ac Incandescent-halogen lamps	500W
240 V ac LED lamps	100 W	Loads piloted from electronic transf. 240 V ac	250 VA
Technologie	Infrarood	Licht sensor	1-600 lux
Horizontal bearing angle	±48°	Vertical bearing angle	±10°

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20

STANDARDS/APPROVALS

