


Complete system for the connection and distribution of LAN networks in residential and tertiary sector environments.

The range includes fibre optic solutions, wall panels, floor cabinets and copper wiring products.

The Data Center series provides all the products necessary to create a multi-service fibre optic infrastructure for residential buildings, in full compliance with all the indications dictated by the new CEI Guidelines 306-2 and Law 164/14.

Categorie	Optical cable reel	Cable colour	Zwart
No. optical fibers	8	Lengte	500 m
Ø sheath	3 mm	Gebruik	Buitenshuis
Classificering	G.657.A2 / B6_a2 Bend Insensitive	Ø core	9 µm
Ø cladding	125 µm	Strength member	Kevlar
Outer jacket	LSZH	Cable	Loose - OS2
CPR class	Eca	Tension	100 N
Crush	500 N/10cm	Minimum bend radius (Dynamic)	20x cable diameter
Minimum bend radius (Static)	10x cable diameter	Max attenuation (@1310 nm / @1550 nm)	0.35 dB/Km (@1310 nm) / 0.2 dB/Km (@1550 nm)
Bedrijfs-temperatuur	From -20°C to +60°C		

DIMENSIONAL



STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 23/04/2024

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice