


AVENUE 1 serie  
Straatverlichtingssysteem



Street lighting in injection-moulded thermoplastic. The pole coupling base can be tilted for whip pole or pole head installation. Made of die-cast aluminium painted with polyester powders (grey graphite) after trivalent passivation. Equipped with graduated goniometric scale to facilitate pointing operations. Possibility of continuous regulation  $\pm 15^\circ$  installation on side bracket;  $0\pm 15^\circ$  pole head installation. Optic in 99.85% polished and anodised aluminium. Anti-aging silicone gasket. Anti-condensation device in felt. Case containing electric components. Made of completely removable polyamide and equipped with a handle to facilitate assembly/disassembly operations and transport. Bipolar power supply terminal in double insulation for 2.5 mm<sup>2</sup> cables. PG 13.5 for cables with a diameter of 6.5÷11.5 mm. Flat glass 4 mm thick tempered and serigraphed. Ceramic lamp-holder fixed on components case.

Toepassing	Extern	IP- graad	IP65
Stoot- bestendigheid	IK08	Gloeidraadproef	650 °C
Maximaal oppervlak blootgesteld aan de wind	0.23 m <sup>2</sup>	Kantelhoek instelbaar	+15° -15°
Gewicht (kg)	8.199999999999999	Kleur	Grafiet/parelmoer
Max. lamp- vermogen	125 W	Lamp- houder	E27
Optiek	Afgesneden		

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION

### TECHNICAL SYMBOLOGY



IP  
IP65

IK  
IK08

GWT  
650 °C

  
0.23 m<sup>2</sup>

