


AVENUE 1 serie Straatverlichtingssysteem



Street lighting in injection-moulded thermoplastic. The pole coupling base can be tilted for whip pole or pole head installation. Made of die-cast aluminium painted with polyester powders (grey graphite) after trivalent passivation. Equipped with graduated goniometric scale to facilitate pointing operations. Possibility of continuous regulation $\pm 15^\circ$ installation on side bracket; $0\text{--}15^\circ$ pole head installation. Optic in 99.85% polished and anodised aluminium. Anti-aging silicone gasket. Anti-condensation device in felt. Case containing electric components. Made of completely removable polyamide and equipped with a handle to facilitate assembly/disassembly operations and transport. Bipolar power supply terminal in double insulation for 2.5 mm² cables. PG 13.5 for cables with a diameter of 6.5÷11.5 mm. Flat glass 4 mm thick tempered and serigraphed. Ceramic lamp-holder fixed on components case.

Toepassing	Extern	IP- graad	IP65
Stoot- bestendigheid	IK08	Gloeidraadproof	650 °C
Maximaal oppervlak blootgesteld aan de wind	0.23 m ²	Kantelhoek instelbaar	+15° -15°
Gewicht (kg)	8.199999999999999	Kleur	Grafiet/parelmoer
Max. lamp- vermogen	250 W	Lamp- houder	E40
Optiek	Afgesneden		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY



IP

IP65

IK

IK08

GWT

650 °C



0.23 m²



STANDARDS/APPROVALS



DS.686