


ESALITE HB Industriële toestellen




Industrial LED lighting fixture made of die-cast EN AB 46100 aluminum with polyester powder coating. Correct lighting is provided by an optical system composed of different versions of lenses. Silicone gaskets, breathing and anti-condensation device in Goretex, waterproof connector for 1.5 mm² cables and stainless steel external screws. Integrated suspension fixing system thanks to a ring made directly in the die-cast aluminum. The die-cast aluminum structure guarantees optimal performance conditions both @ Ta25 ° and @ Ta50 ° thanks to specific thermal sizing tests. The correct heat dispersion inside ESALITE is guaranteed by the special passive heat sink with a very low copper content that offers high qualitative and quantitative performances.

Serie	Esalite HB - 16K	Toepassing	Intern
Bedrijfstemperatuur	-30°C ÷ +50 °C	IP- graad	IP65
Stoot- bestendigheid	IK07	Bevestiging	-
Isolatie- klasse	I	Spanning	220-240 V - 50/60 Hz
Gewicht (kg)	7.5	Electrocod	2444

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



IP

IP65

IK

IK07



STANDARDS/APPROVALS

**UK
CA**



CE