


### ESALITE HB Industriële toestellen




Industrial LED lighting fixture made of die-cast EN AB 46100 aluminum with polyester powder coating. Correct lighting is provided by an optical system composed of different versions of lenses. Silicone gaskets, Goretex breathing and anti-condensation device, 2 waterproof connectors for 1.5 mm<sup>2</sup> cables and stainless steel external screws. Integrated suspension fixing system thanks to a ring made directly in the die-cast aluminum. The die-cast aluminum structure guarantees optimal performance conditions both @ Ta25 ° and @ Ta50 ° thanks to specific thermal sizing tests. The correct heat dispersion inside ESALITE is guaranteed by the special passive heat sink with a very low copper content that offers high qualitative and quantitative performances.

GENERAL INFORMATION		OPTIC AND ILLUMINATING FEATURES	
Context	Logistics and industrial manufacturing lighting	Optiek	Narrow 30°
Luminaire Toepassing	LED Industrial Reflector Intern	Unified Glare Rating	UGR ≤ 25
Unique digital code (Datamatrix)	Datamatrix	Lumen-vermogen (lm)	47200
Kleur	Grey RAL 9006	Efficacy (lm/W)	112
Type lichtbron	LED	Kleur temperatuur	5700 K
System vermogen	420 W	Colour Rendering Index	CRI>80
LED Lifetime	L90B10 (Tq 25°) 100000 h; L90B10 (Tq 50°) 55000 h	Standard Deviation Colour Matching	SDCM = 3
Gewicht (kg)	22.5	Photobiological Risk Class	RG0
Garantie	5 jaar	Standaard	EN60598-1; IEC 62778; IEC62471
Opslagtemperatuur	-25°C ÷ +70°C / HR 10% ÷ 85%	ELETRICAL AND LIGHTING FEATURES	
Operating temperature	-25°C ÷ +50°C	Voedings-spanning	220-240 V
MATERIALS		Nominale frequentie (Hz)	50/60 Hz
Body	Gietaluminium	Driver	Included
Type plaat	High transparency PMMA	Driver failure rate	F10 = 100.000h Tq25°C/50.000h Tq40°C
Optic	PMMA lens	Overvoltage protection	DM 6KV / CM 8KV
Gasket	Silicon	Control System	DALI
Locking Hook	-	INSTALLATION AND MAINTENANCE	
External screw	Stainless steel	Mounting and installation	Suspended
Colour	Polyester powder coated	Tilt	Not possible
STANDARDS AND APPROVALS		Wiring	With watertight connector
Classificering	-	Bevestiging	-
Toestel met verlaagde oppervlaktetemperatuur	-	Light source replaceability	Non-replaceable
DIN 18032-3-certificering	Nee	Controlgear replaceability	By professional
IPEA	-	Driver Box	Ingebouwd
Isolatie-klasse	I	Maximum surface exposed to the wind	0,42 m <sup>2</sup>
IP-graad	IP65		-
Stootbestendigheid	IK07		-
Glow Wire Test	650 °C		-

### DIMENSIONAL



### PHOTOMETRIC DISTRIBUTION



ESALITE HB  
Industriële toestellen

### TECHNICAL SYMBOLOGY



0,42 m<sup>2</sup>



**IP**  
IP65

**IK**  
IK07

**GWT**  
650 °C

### STANDARDS/APPROVALS

