


SMART[3] serie
Waterdichte ledarmaturen



Dedicated emergency kit made in grey PC (RAL 7035) for Smart[3] through wiring version. Equipped with Ni-Mh batteries for 3h autonomy. Can be fitted on the unit itself using fixing springs or mounted on the wall/ceiling, using 4mm screws.

Gewicht (kg)	1.3	Autonomie	3 h
Isolatie-klasse	II	IP-graad	IP66
Voeding batterijen	Replaceable	Stootbestendigheid	IK08
Type	Kit	Spanning	220-240 V - 50/60 Hz
Bevestiging	On the fixture body/on wall/on ceiling	Omschrijving	Smart [3] emergency kit - through wiring
Serie	SMART [3]	Toepassing	Intern
Bedrijfstemperatuur	+5 +25 °C	Oplaadtijd	24 h
Charging status feedback	Green LED	Garantie	5 jaar
Gloedraadproef	850 °C	Power inlet	H07RN-F 4x1mm ² cable
Power outlet	4P female GW connector	Electrocod	2434

DIMENSIONAL

PHOTOMETRIC DISTRIBUTION

TECHNICAL SYMBOLOGY



IP
IP66

IK
IK08



GWT
850 °C

STANDARDS/APPROVALS

