

Product Environmental Profile

IRL RAL 9010 Rigid conduits

GEWISS S.p.A.



Registration number: GWGS-00014-V01.01-EN	Drafting rules: PCR-ed4-EN-2021 09 06 Supplemented by PSR-0003-ed2.1-EN-2023 12 08
Vérifier accreditation n°: VH51	Information and reference documents: www.pep-ecopassport.org
Date of issue: 12-2025	Validity period: 5 years
Indipendent verification of the declaration and data, in compliance with ISO 14025: 2010	
Internal : ☐	External : ☒
The PCR review was conducted by a panel of experts chaired by Julie Orgelet (DDemain)	
PEPs are compliant with XP C08-100-1:2016 and EN 50693:2019	
The components of the present PEP may not be compared with components from any other program.	
Document in compliance with ISO 14025: 2010 « Environmental labels and declarations. Type III environmental declarations »	



GEWISS Sustainability commitment

GEWISS mission is to create value for our customer and our staff providing innovative and scalable solutions for building, industries and infrastructures, connecting people and things, while improving the safety and the quality of life, driven by **integrity**, culture of **excellence** and **sustainability**.

GEWISS is strongly convinced that being sustainable is essential, and therefore has decided to develop a responsible business model, which promotes respectful conduct towards people and the environment in developing products, solutions and services.

Disclaimer

The information contained in this declaration is provided under the responsibility of GEWISS in accordance with standard UNI EN ISO 14025, PCR-ed4-EN-2021 09 06 and PSR-0003-ed2.1-EN-2023 12 08.

The information contained in this document is updated as of the date of its issuance. Such information is the property of GEWISS. Any inappropriate use that alters its meaning and/or damages GEWISS's reputation is strictly prohibited.

Reading instructions

The following display rules are used:

- Values are expressed in simplified scientific notation: $0.0038 = 3.80 \times 10^{-3} = 3.80E-3$;
- When the result of the inventory calculation is zero, the value zero is displayed;
- Non-zero values are expressed with three significant figures.

General background

This declaration is an individual declaration covering the life cycle from cradle to grave.

The declaration is available at the following address:

www.pep-ecopassport.org/

Person responsible for this declaration

QHSE & Sustainability Director

sustainability@gewiss.com - www.gewiss.com



Address:

Via Domenico Bosatelli 1 - 24069 CENATE SOTTO BG, Italy
Phone +39 035 946111

General information

Product category

Product family: "Trunking systems and conduit systems"

Sub-family: "Rigid conduit systems"

Main function: Lengths and accessories intended to accommodate and protect cables

Relevant standards groups and standards: EN 61386-1 and EN 61386-21 standards

Functional Unit

"Accommodate and protect the wiring along 1 meter for a Reference Service Life of the product of 20 years". The surface-mounted or embedded flexible conduit system IRL/16 RAL 9010 white (AS04678) with cross-section 132.73 mm² includes the profile and accessories that are representative of standard use.

Reference product

The reference product trade name is: IRL/16 RAL 9010 white (AS04678).

Products belonging to the same environmental family:

Description	Commercial name
IRL/16 RAL 9010	AS04678
IRL/20 RAL 9010	AS04679; AS04681
IRL/25 RAL 9010	AS04680

Reference product characteristics

Product family	Trunking systems and conduit systems
Sub-family	Rigid conduit systems
Main function	Accommodate and protect the wiring
Relevant standard	EN 61386-1 and EN 61386-21 standards
Manufacturing site	Castel san Giovanni, Piacenza, Italy
Cable management system type	Rigid conduit
Range	RK range
Reference product	AS04678
Dimension	16 mm internal diameter
Main constituents (per 1 m of rigid conduit)	PVC rigid conduit Packaging

Mass of the reference product

Item	Quantity
<i>Total mass (product + packaging) [kg]</i>	<i>0.101</i>
<i>Product mass [kg]</i>	<i>0.098</i>
<i>Packaging mass [kg]</i>	<i>0.003</i>

Constituent materials

Constituent materials of the reference product and packaging are:

Plastic	%	Metal	%	Other	%
Total	98.2%	-	-	Total	1.8%
PVC	97.5%	-	-	Wood	1.8%
LDPE	0.5%	-	-		
PP	0.1%	-	-		
PET	< 0.1%	-	-		

Biogenic carbon content

Biogenic carbon content in the reference product	0 kg C
Biogenic carbon content in the packaging	8.86E-04 kg C

Life Cycle Assessment Methodology

The Life Cycle Assessment (LCA) on which this Product Environmental Profile (PEP) is based, complies with the criteria set out in PCR-ed4-EN-2021 09 06 of the PEP ecopassport® program. The life cycle analysis was carried out using SIMAPRO software version V9.5.0 and Ecoinvent V3.9.1 - system model: allocation, cut-off by classification. The reference service life has been modelled according to the provisions of PSR-0003-ed2-EN-2023 08 12. The end-of-life modelling follows the default scenarios proposed in PSR-0003-ed2-EN-2023 08 12.

Geographical representativeness	The scenarios are representative of the manufacturing stage in Italy and the installation, use and end-of-life treatment in Europe.
Technological representativeness	The PEP is representative of white rigid conduits in PVC. The covered range of products includes IRL (medium rigid conduit) RAL 9010 conduits with internal diameters of 16, 20 and 25 mm.

Life Cycle stages

Manufacturing stage, A1-A3

The product consists of the following elements:

- Product: 1 m PVC rigid conduit
- Components: none
- Packaging: (73.5% wood, 20.4%, LDPE, 5.6% PP, 0.4% PET)

The production of all these elements was included in the study.
Inbound transport was included in the study.
Manufacturing waste has been taken into account in this stage.

The dataset used to determine the impacts of the electricity used during the manufacturing stage has been modelled on the basis of the production mix as declared by the electricity supplier for year 2024, which includes the following sources: 67% natural gas, 12% coal, 8% renewable, 5% nuclear, 1% oil products, 7% other sources.

Distribution stage, A4

The distribution stage includes transport of the packaged product by an average lorry from the manufacturer's last logistics platform to the installation site.
The product is distributed and installed in Europe and worldwide.
No reconditioning of the packaging has been considered.

Installation stage, A5

- The installation phase includes:
- Manufacturing, distribution and end-of-life of installation scrap (3%);
 - Manufacturing and distribution of the accessories required for the installation of the conduit (1.27 unit of wall mounting element per meter of rigid conduit installed and 0.36 units of 90°angle in the plane per meter of rigid conduit installed).
 - Management of packaging waste.

Use stage, B1-B7

The use phase of the reference products is modeled as per the PSR-0003-ed2.1-EN-2023 12 08, resulting in no impact.

End-of-life stage, C1-C4

The end-of-life of the product is modelled according to the default scenario provided by the PSR-0003-ed2.1-EN-2023 12 08.

No energy consumption is considered for uninstalling the product.

The rigid conduit is transported over 100km before 100% incinerated without energy recovery.

The boundaries of this stage consider the processes up to the point of substitution in accordance with the rules of PCR-ed4-EN-2021 09 06.

Benefits and loads beyond the system boundaries (module D)

Module D includes the net benefits and loads beyond system boundaries, which have been modelled according to the PCR-ed4-EN-2021 09 06. The treatment of wood and plastic waste generates net benefits and loads, as for the impacts prevented by recycling the material and the impacts prevented by waste-to-energy recovery. The internal recycling of PVC generates is accounted as a load in this stage.

The dataset used to determine the avoided impacts for electricity is « Electricity, medium voltage {RER}| market group for | Cut-off, U».

Environmental impacts

The results presented below were obtained using the methods defined in PCR-ed4-EN-2021 09 06, and are referred to the Functional Unit.

Indicator	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Total use B1-B7	End of Life C1-C4	Total Life cycle	Module D
Acidification	mol H+ eq	3.26E-03	5.34E-05	2.98E-04	0.00	1.59E-04	3.77E-03	-7.67E-05
Climate change	kg CO2 eq	5.34E-01	1.15E-02	7.26E-02	0.00	2.09E-01	8.27E-01	-1.25E-02
Climate change - Biogenic	kg CO2 eq	-2.11E-04	9.60E-06	8.14E-04	0.00	3.30E-04	9.44E-04	-5.36E-05
Climate change - Fossil	kg CO2 eq	5.34E-01	1.14E-02	7.18E-02	0.00	2.09E-01	8.26E-01	-1.24E-02
Climate change - Land use and LU change	kg CO2 eq	1.92E-05	5.59E-06	1.59E-05	0.00	2.69E-05	6.76E-05	-3.75E-07
Ecotoxicity, freshwater - part 1	CTUe	1.42E+01	6.00E-02	7.96E-01	0.00	1.09E+01	2.60E+01	-3.34E-01
Ecotoxicity, freshwater - part 2	CTUe	1.60E-01	2.13E-02	3.08E-02	0.00	6.43E-02	2.77E-01	-3.67E-03
Ecotoxicity, freshwater - inorganics	CTUe	1.43E+01	7.83E-02	8.17E-01	0.00	1.10E+01	2.62E+01	-3.35E-01
Ecotoxicity, freshwater - organics - p.1	CTUe	3.10E-03	6.10E-04	2.22E-03	0.00	5.08E-03	1.10E-02	-6.18E-05
Ecotoxicity, freshwater - organics - p.2	CTUe	1.05E-01	2.44E-03	7.02E-03	0.00	5.88E-03	1.20E-01	-2.44E-03
Particulate matter	disease inc.	9.09E-08	1.13E-09	4.91E-09	0.00	1.44E-09	9.84E-08	-2.14E-09
Eutrophication, marine	kg N eq	4.06E-04	2.12E-05	5.82E-05	0.00	4.83E-05	5.34E-04	-9.36E-06
Eutrophication, freshwater	kg P eq	4.81E-05	8.25E-07	6.71E-06	0.00	9.03E-06	6.46E-05	-1.11E-06
Eutrophication, terrestrial	mol N eq	4.38E-03	2.27E-04	5.86E-04	0.00	4.45E-04	5.64E-03	-1.01E-04
Human toxicity, cancer	CTUh	3.39E-09	6.16E-12	1.10E-10	0.00	4.08E-11	3.54E-09	-7.97E-11
Human toxicity, cancer - inorganics	CTUh	3.28E-10	2.51E-12	1.57E-11	0.00	3.42E-11	3.81E-10	-7.74E-12
Human toxicity, cancer - organics	CTUh	3.06E-09	3.65E-12	9.42E-11	0.00	6.56E-12	3.16E-09	-7.20E-11
Human toxicity, non-cancer	CTUh	1.06E-08	1.28E-10	4.87E-10	0.00	1.32E-09	1.25E-08	-2.49E-10
Human toxicity, non-cancer - inorganics	CTUh	1.04E-08	1.10E-10	4.59E-10	0.00	1.30E-09	1.22E-08	-2.44E-10
Human toxicity, non-cancer - organics	CTUh	2.28E-10	1.84E-11	2.77E-11	0.00	1.44E-11	2.89E-10	-5.38E-12
Ionising radiation	kBq U-235 eq	2.93E-03	2.29E-04	2.06E-03	0.00	1.47E-03	6.69E-03	-5.25E-05
Land use	Pt	3.84E-01	1.24E-01	8.80E-02	0.00	1.81E-01	7.77E-01	-2.10E-03
Ozone depletion	kg CFC11 eq	3.35E-09	2.51E-10	4.81E-10	0.00	4.07E-09	8.15E-09	-6.17E-11

Product Environmental Profile



Indicator	Unit	Manufacturing	Distribution	Installation	Total use	End of Life	Total Life cycle	Module D
		A1-A3	A4	A5	B1-B7	C1-C4		
Photochemical ozone formation	kg NMVOC eq	1.69E-03	7.93E-05	2.13E-04	0.00	1.42E-04	2.12E-03	-3.92E-05
Resource use, fossils	MJ	7.95E+00	1.65E-01	1.00E+00	0.00	3.46E-01	9.47E+00	-1.97E-01
Resource use, minerals and metals	kg Sb eq	1.52E-07	3.57E-08	2.96E-07	0.00	1.53E-07	6.37E-07	-5.23E-09
Water use	m3 depriv.	2.49E-01	7.20E-04	3.08E-02	0.00	2.90E-01	5.70E-01	-6.14E-03
Total use of primary energy during the life cycle	MJ	3.31E-01	3.24E-03	4.39E-02	0.00	4.18E-02	4.20E-01	-5.91E-03
Net use of fresh water	m3	5.85E-03	2.49E-05	8.13E-04	0.00	8.86E-03	1.56E-02	-1.40E-04
Use of renewable primary energy, excluding renewable primary energy resources used as raw materials	MJ	2.21E-01	2.62E-03	4.05E-02	0.00	3.10E-02	2.95E-01	4.55E-03
Use of renewable primary energy resources used as raw materials	MJ	3.00E-02	0.00E+00	-8.58E-03	0.00	0.00E+00	2.14E-02	-9.47E-03
Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	2.51E-01	2.62E-03	3.19E-02	0.00	3.10E-02	3.17E-01	-4.92E-03
Use of non-renewable primary energy, excluding non-renewable primary energy resources used as raw materials	MJ	-1.96E+00	6.23E-04	2.20E-02	0.00	-1.95E+00	-3.88E+00	1.13E-02
Use of non-renewable primary energy resources used as raw materials	MJ	2.04E+00	0.00E+00	-1.00E-02	0.00	1.96E+00	3.99E+00	-1.23E-02
Total use of non renewable primary energy resources (primary energy and primary energy resources used as raw materials)	MJ	8.01E-02	6.23E-04	1.20E-02	0.00	1.08E-02	1.03E-01	-9.95E-04
Use of secondary materials	kg	0.00	0.00	0.00	0.00	0.00E+00	0.00	0.00
Use of renewable secondary fuels	MJ	0.00	0.00	0.00	0.00	0.00E+00	0.00	0.00
Use of non-renewable secondary fuels	MJ	0.00	0.00	0.00	0.00	0.00E+00	0.00	0.00
Hazardous waste disposed of	kg	1.25E-04	4.29E-06	1.01E-04	0.00	2.67E-03	2.90E-03	0.00
Non-hazardous waste disposed of	kg	5.06E-02	1.04E-02	6.61E-03	0.00	5.76E-02	1.25E-01	0.00
Radioactive waste disposed of	kg	7.80E-07	5.55E-08	5.24E-07	0.00	3.75E-07	1.73E-06	0.00
Components for reuse	kg	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Product Environmental Profile



Indicator	Unit	Manufacturing A1-A3	Distribution A4	Installation A5	Total use B1-B7	End of Life C1-C4	Total Life cycle	Module D
Materials for recycling	kg	0.00	0.00	8.74E-04	0.00	0.00	8.74E-04	0.00
Materials for energy recovery	kg	0.00	0.00	8.46E-04	0.00	0.00	8.46E-04	0.00
Exported energy	MJ	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Biogenic carbon content in the reference product	kg	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Biogenic carbon content in packaging	kg	8.86E-04	0.00	0.00	0.00	0.00	8.86E-04	-2.79E-04

Extrapolation rules

According to this environmental analysis, proportionality rules can be used to evaluate the impacts of other products belonging to the same environmental family.

The technical characteristics of these references are shown in the table below:

Technical characteristics of the homogeneous environmental family	
Product	<i>PVC rigid conduit</i>
Function	<i>Accommodate and protect the wiring</i>
Type	<i>White rigid conduits made in PVC, with the following internal diameters (mm): 16, 20, 25.</i>
Manufacturing site	<i>Castel san Giovanni, Piacenza, Italy</i>
Constituent materials	<i>Rigid conduit (1m) Packaging</i>

The extrapolation parameters have been calculated following the method provided by PSR -0003-ed2.1-EN-2023 08 12 and are shown in the table below. Users can multiply the indicators at any stage or for the whole life cycle by these coefficients, to use the environmental data provided in this PEP for cable protection systems belonging to the same environmental family as the reference product.

Description	Commercial name	Internal diam. (mm)	Cross-section (mm ²)	Parameter
IRL/16 RAL 9010	AS04678	16	132.73	1.00
IRL/20 RAL 9010	AS04679; AS04681	20	224.32	1.38
IRL/25 RAL 9010	AS04680	25	359.68	1.79