
























3000 K												
Lowbay-Highbay Models												
TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED Controlgear	Communication module	Rated Voltage	Input power	Rendering	
GW S4 001GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	487 x 163 x 71	Spotlight 10°	2 LED 3000 K	66253642	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	GEWISS cod. 66398181	220-240 V - 50/60 Hz	26 W		
GW S4 002GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	488 x 163 x 71	Restricted 30°	2 LED 3000 K	66257254	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 003GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	489 x 163 x 71	Medium 60°	2 LED 3000 K	66257262	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 004GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	490 x 163 x 71	Diffused 100°	2 LED 3000 K	66253634	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 005GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	491 x 163 x 71	Elliptical	2 LED 3000 K	66256835	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 006GD30K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	492 x 163 x 71	Asymmetrical	2 LED 3000 K	66256843	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 011GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Spotlight 10°	2+2 LED 3000 K	66253642	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	51 W		
GW S4 012GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Restricted 30°	2+2 LED 3000 K	66257254	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 013GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Medium 60°	2+2 LED 3000 K	66257262	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 014GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Diffused 100°	2+2 LED 3000 K	66253634	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 015GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Elliptical	2+2 LED 3000 K	66256835	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 016GD30K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Asymmetrical	2+2 LED 3000 K	66256843 66256850	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 021GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	4 LED 3000 K	66257270	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	51 W		
GW S4 022GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	4 LED 3000 K	66255803	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 023GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	4 LED 3000 K	66257288	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 024GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	4 LED 3000 K	66257296	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 025GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	4 LED 3000 K	66257304	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 026GD30K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	4 LED 3000 K	66257320	Max. 950 mA			220-240 V - 50/60 Hz	51 W		
GW S4 031GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	5 LED 3000 K	66257353	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	61 W		
GW S4 032GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	61 W		
GW S4 033GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	61 W		
GW S4 034GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	61 W		
GW S4 035GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	5 LED 3000 K	66257379	Max. 950 mA			220-240 V - 50/60 Hz	61 W		
GW S4 036GD30K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	5 LED 3000 K	66257387	Max. 950 mA			220-240 V - 50/60 Hz	61 W		
GW S4 041GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	4+4 LED 3000 K	66257270	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	100 W		
GW S4 042GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Restricted 30°	4+4 LED 3000 K	66255803	Max. 950 mA			220-240 V - 50/60 Hz	100 W		
GW S4 043GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Medium 60°	4+4 LED 3000 K	66257288	Max. 950 mA			220-240 V - 50/60 Hz	100 W		
GW S4 044GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Diffused 100°	4+4 LED 3000 K	66257296	Max. 950 mA			220-240 V - 50/60 Hz	100 W		
GW S4 045GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Elliptical	4+4 LED 3000 K	66257379	Max. 950 mA			220-240 V - 50/60 Hz	100 W		
GW S4 046GD30K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Asymmetrical	4+4 LED 3000 K	66257338 66257346	Max. 950 mA			220-240 V - 50/60 Hz	100 W		
GW S4 051GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	5+5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	121 W		
GW S4 052GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	701 x 254 x 75	Restricted 30°	5+5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	121 W		
GW S4 053GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	702 x 254 x 75	Medium 60°	5+5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	121 W		
GW S4 054GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	703 x 254 x 75	Diffused 100°	5+5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	121 W		
GW S4 055GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	704 x 254 x 75	Elliptical	5+5 LED 3000 K	66257379	Max. 950 mA			220-240 V - 50/60 Hz	121 W		
GW S4 056GD30K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	705 x 254 x 75	Asymmetrical	5+5 LED 3000 K	66255647 66255654	Max. 950 mA			220-240 V - 50/60 Hz	121 W		
GW S4 061GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x4 LED 3000 K	66257270	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	203 W		
GW S4 062GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x4 LED 3000 K	66255803	Max. 950 mA			220-240 V - 50/60 Hz	203 W		
GW S4 063GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x4 LED 3000 K	66257288	Max. 950 mA			220-240 V - 50/60 Hz	203 W		
GW S4 064GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x4 LED 3000 K	66257296	Max. 950 mA			220-240 V - 50/60 Hz	203 W		
GW S4 065GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x4 LED 3000 K	66257379	Max. 950 mA			220-240 V - 50/60 Hz	203 W		
GW S4 066GD30K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x4 LED 3000 K	66257338 66257346	Max. 950 mA			220-240 V - 50/60 Hz	203 W		
GW S4 071GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	245 W		
GW S4 072GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 073GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 074GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 075GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x5 LED 3000 K	66257379	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 076GD30K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x5 LED 3000 K	66255647 66255654	Max. 950 mA			220-240 V - 50/60 Hz	245 W		

Floodlight Models											
TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED Controlgear	Communication module	Rated Voltage	Input power	Rendering
GW S4 101GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Spotlight 10°	2 LED 3000 K	66253642	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	GEWISS cod. 66398181	220-240 V - 50/60 Hz	26 W	
GW S4 102GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Restricted 30°	2 LED 3000 K	66257254	Max. 950 mA			220-240 V - 50/60 Hz	26 W	
GW S4 103GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Medium 60°	2 LED 3000 K	66257262	Max. 950 mA			220-240 V - 50/60 Hz	26 W	
GW S4 104GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Diffused 100°	2 LED 3000 K	66253634	Max. 950 mA			220-240 V - 50/60 Hz	26 W	
GW S4 105GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Elliptical	2 LED 3000 K	66256835	Max. 950 mA			220-240 V - 50/60 Hz	26 W	
GW S4 106GD30K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Asymmetrical	2 LED 3000 K	66256843	Max. 950 mA			220-240 V - 50/60 Hz	26 W	
GW S4 111GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Spotlight 10°	2+2 LED 3000 K	66253642	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	53 W	
GW S4 112GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Restricted 30°	2+2 LED 3000 K	66257254	Max. 950 mA			220-240 V - 50/60 Hz	53 W	
GW S4 113GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Medium 60°	2+2 LED 3000 K	66257262	Max. 950 mA			220-240 V - 50/60 Hz	53 W	
GW S4 114GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Diffused 100°	2+2 LED 3000 K	66253634	Max. 950 mA			220-240 V - 50/60 Hz	53 W	
GW S4 115GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Elliptical	2+2 LED 3000 K	66256835	Max. 950 mA			220-240 V - 50/60 Hz	53 W	
GW S4 116GD30K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Asymmetrical	2+2 LED 3000 K	66256843 66256850	Max. 950 mA			220-240 V - 50/60 Hz	53 W	
GW S4 131GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Spotlight 10°	5 LED 3000 K	66257353	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	63 W	
GW S4 132GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Restricted 30°	5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	63 W	
GW S4 133GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Medium 60°	5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	63 W	
GW S4 134GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Diffused 100°	5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	63 W	
GW S4 135GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Elliptical	5 LED 3000 K	66255720	Max. 950 mA			220-240 V - 50/60 Hz	63 W	
GW S4 136GD30K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Asymmetrical	5 LED 3000 K	66257387	Max. 950 mA			220-240 V - 50/60 Hz	63 W	
GW S4 151GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Spotlight 10°	5+5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	124 W	
GW S4 152GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Restricted 30°	5+5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	124 W	
GW S4 153GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Medium 60°	5+5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	124 W	
GW S4 154GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Diffused 100°	5+5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	124 W	
GW S4 155GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Elliptical	5+5 LED 3000 K	66255720	Max. 950 mA			220-240 V - 50/60 Hz	124 W	
GW S4 156GD30K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Asymmetrical	5+5 LED 3000 K	66255647 66255654	Max. 950 mA			220-240 V - 50/60 Hz	124 W	
GW S4 171GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Spotlight 10°	4x5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	245 W	
GW S4 172GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Restricted 30°	4x5 LED 3000 K	66257361	Max. 950 mA			220-240 V - 50/60 Hz	245 W	
GW S4 173GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Medium 60°	4x5 LED 3000 K	66255282	Max. 950 mA			220-240 V - 50/60 Hz	245 W	
GW S4 174GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Diffused 100°	4x5 LED 3000 K	66256355	Max. 950 mA			220-240 V - 50/60 Hz	245 W	
GW S4 175GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Elliptical	4x5 LED 3000 K	66255720	Max. 950 mA			220-240 V - 50/60 Hz	245 W	
GW S4 176GD30K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Asymmetrical	4x5 LED 3000 K	66255647 66255654	Max. 950 mA			220-240 V - 50/60 Hz	245 W	

5700 K													
Lowbay-Highbay Models													
TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED Controlgear	Communication module	Rated Voltage	Input power	Rendering		
GW S4 001GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	487 x 163 x 71	Spotlight 10°	2 LED 5700 K	66257197	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	GEWISS cod. 66398181	220-240 V - 50/60 Hz	26 W			
GW S4 002GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	488 x 163 x 71	Restricted 30°	2 LED 5700 K	66257205	Max. 950 mA			220-240 V - 50/60 Hz	26 W			
GW S4 003GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	489 x 163 x 71	Medium 60°	2 LED 5700 K	66257213	Max. 950 mA			220-240 V - 50/60 Hz	26 W			
GW S4 004GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	490 x 163 x 71	Diffused 100°	2 LED 5700 K	66253253	Max. 950 mA			220-240 V - 50/60 Hz	26 W			
GW S4 005GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	491 x 163 x 71	Elliptical	2 LED 5700 K	66257221	Max. 950 mA			220-240 V - 50/60 Hz	26 W			
GW S4 006GD57K	SMART [4] 2.0 LB - DALI - 2L - IP66 - Class I - Grey RAL 7037	492 x 163 x 71	Asymmetrical	2 LED 5700 K	66257239	Max. 950 mA			220-240 V - 50/60 Hz	26 W			
GW S4 011GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Spotlight 10°	2+2 LED 5700 K	66257197	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	51 W			
GW S4 012GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Restricted 30°	2+2 LED 5700 K	66257205	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 013GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Medium 60°	2+2 LED 5700 K	66257213	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 014GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Diffused 100°	2+2 LED 5700 K	66253253	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 015GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Elliptical	2+2 LED 5700 K	66257221	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 016GD57K	SMART [4] 2.0 LB - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Asymmetrical	2+2 LED 5700 K	66257239	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 021GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	4 LED 5700 K	66257122	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	51 W			
GW S4 022GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	4 LED 5700 K	66257130	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 023GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	4 LED 5700 K	66256637	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 024GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	4 LED 5700 K	66256579	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 025GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	4 LED 5700 K	66257148	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 026GD57K	SMART [4] 2.0 LB - DALI - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	4 LED 5700 K	66257163	Max. 950 mA			220-240 V - 50/60 Hz	51 W			
GW S4 031GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	5 LED 5700 K	66257064	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	61 W			
GW S4 032GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	61 W			
GW S4 033GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	61 W			
GW S4 034GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	61 W			
GW S4 035GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	5 LED 5700 K	66257080	Max. 950 mA			220-240 V - 50/60 Hz	61 W			
GW S4 036GD57K	SMART [4] 2.0 LB - DALI - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	5 LED 5700 K	66256389	Max. 950 mA			220-240 V - 50/60 Hz	61 W			
GW S4 041GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	4+4 LED 5700 K	66257122	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	100 W			
GW S4 042GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Restricted 30°	4+4 LED 5700 K	66257130	Max. 950 mA			220-240 V - 50/60 Hz	100 W			
GW S4 043GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Medium 60°	4+4 LED 5700 K	66256637	Max. 950 mA			220-240 V - 50/60 Hz	100 W			
GW S4 044GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Diffused 100°	4+4 LED 5700 K	66256579	Max. 950 mA			220-240 V - 50/60 Hz	100 W			
GW S4 045GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Elliptical	4+4 LED 5700 K	66257148	Max. 950 mA			220-240 V - 50/60 Hz	100 W			
GW S4 046GD57K	SMART [4] 2.0 HB - DALI - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Asymmetrical	4+4 LED 5700 K	66257171	Max. 950 mA			220-240 V - 50/60 Hz	100 W			
GW S4 051GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	5+5 LED 5700 K	66257064	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	121 W			
GW S4 052GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	701 x 254 x 75	Restricted 30°	5+5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	121 W			
GW S4 053GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	702 x 254 x 75	Medium 60°	5+5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	121 W			
GW S4 054GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	703 x 254 x 75	Diffused 100°	5+5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	121 W			
GW S4 055GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	704 x 254 x 75	Elliptical	5+5 LED 5700 K	66257080	Max. 950 mA			220-240 V - 50/60 Hz	121 W			
GW S4 056GD57K	SMART [4] 2.0 HB - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	705 x 254 x 75	Asymmetrical	5+5 LED 5700 K	66257106	Max. 950 mA			220-240 V - 50/60 Hz	121 W			
GW S4 061GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x4 LED 5700 K	66257122	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	203 W			
GW S4 062GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x4 LED 5700 K	66257130	Max. 950 mA			220-240 V - 50/60 Hz	203 W			
GW S4 063GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x4 LED 5700 K	66256637	Max. 950 mA			220-240 V - 50/60 Hz	203 W			
GW S4 064GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x4 LED 5700 K	66256579	Max. 950 mA			220-240 V - 50/60 Hz	203 W			
GW S4 065GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x4 LED 5700 K	66257148	Max. 950 mA			220-240 V - 50/60 Hz	203 W			
GW S4 066GD57K	SMART [4] 2.0 HB - DALI - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x4 LED 5700 K	66257171	Max. 950 mA			220-240 V - 50/60 Hz	203 W			
GW S4 071GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x5 LED 5700 K	66257064	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	245 W			
GW S4 072GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	245 W			
GW S4 073GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	245 W			
GW S4 074GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	245 W			
GW S4 075GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x5 LED 5700 K	66257080	Max. 950 mA			220-240 V - 50/60 Hz	245 W			
GW S4 076GD57K	SMART [4] 2.0 HB - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x5 LED 5700 K	66257106	Max. 950 mA			220-240 V - 50/60 Hz	245 W			

Floodlight Models												
TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED Controlgear	Communication module	Rated Voltage	Input power	Rendering	
GW S4 101GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Spotlight 10°	2 LED 5700 K	66257197	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	GEWISS cod. 66398181	220-240 V - 50/60 Hz	26 W		
GW S4 102GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Restricted 30°	2 LED 5700 K	66257205	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 103GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Medium 60°	2 LED 5700 K	66257213	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 104GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Diffused 100°	2 LED 5700 K	66253253	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 105GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Elliptical	2 LED 5700 K	66257221	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 106GD57K	SMART [4] 2.0 FL - DALI - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Asymmetrical	2 LED 5700 K	66257239	Max. 950 mA			220-240 V - 50/60 Hz	26 W		
GW S4 111GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Spotlight 10°	2+2 LED 5700 K	66257197	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	53 W		
GW S4 112GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Restricted 30°	2+2 LED 5700 K	66257205	Max. 950 mA			220-240 V - 50/60 Hz	53 W		
GW S4 113GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Medium 60°	2+2 LED 5700 K	66257213	Max. 950 mA			220-240 V - 50/60 Hz	53 W		
GW S4 114GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Diffused 100°	2+2 LED 5700 K	66253253	Max. 950 mA			220-240 V - 50/60 Hz	53 W		
GW S4 115GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Elliptical	2+2 LED 5700 K	66257221	Max. 950 mA			220-240 V - 50/60 Hz	53 W		
GW S4 116GD57K	SMART [4] 2.0 FL - DALI - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Asymmetrical	2+2 LED 5700 K	66257239 66257247	Max. 950 mA			220-240 V - 50/60 Hz	53 W		
GW S4 131GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Spotlight 10°	5 LED 5700 K	66257064	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	GEWISS cod. 66398181	220-240 V - 50/60 Hz	63 W		
GW S4 132GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Restricted 30°	5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	63 W		
GW S4 133GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Medium 60°	5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	63 W		
GW S4 134GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Diffused 100°	5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	63 W		
GW S4 135GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Elliptical	5 LED 5700 K	66257098	Max. 950 mA			220-240 V - 50/60 Hz	63 W		
GW S4 136GD57K	SMART [4] 2.0 FL - DALI - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Asymmetrical	5 LED 5700 K	66256389	Max. 950 mA			220-240 V - 50/60 Hz	63 W		
GW S4 151GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Spotlight 10°	5+5 LED 5700 K	66257064	Max. 950 mA	GEWISS 160W cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	124 W		
GW S4 152GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Restricted 30°	5+5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	124 W		
GW S4 153GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Medium 60°	5+5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	124 W		
GW S4 154GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Diffused 100°	5+5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	124 W		
GW S4 155GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Elliptical	5+5 LED 5700 K	66257098	Max. 950 mA			220-240 V - 50/60 Hz	124 W		
GW S4 156GD57K	SMART [4] 2.0 FL - DALI - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Asymmetrical	5+5 LED 5700 K	66257106 66257114	Max. 950 mA			220-240 V - 50/60 Hz	124 W		
GW S4 171GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Spotlight 10°	4x5 LED 5700 K	66257064	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	GEWISS cod. 66398181	220-240 V - 50/60 Hz	245 W		
GW S4 172GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Restricted 30°	4x5 LED 5700 K	66257072	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 173GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Medium 60°	4x5 LED 5700 K	66255290	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 174GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Diffused 100°	4x5 LED 5700 K	66253220	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 175GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Elliptical	4x5 LED 5700 K	66257098	Max. 950 mA			220-240 V - 50/60 Hz	245 W		
GW S4 176GD57K	SMART [4] 2.0 FL - DALI - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Asymmetrical	4x5 LED 5700 K	66257106 66257114	Max. 950 mA			220-240 V - 50/60 Hz	245 W		