cosign

3000 K

Lowbay-Highbay Models

TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED controlgear	Rated Voltage	Input power	Rendering
GW S4 001GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	487 x 163 x 71	Spotlight 10°	2 LED 3000 K	66253642	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	220-240 V - 50/60 Hz	25 W	
GW S4 002GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	488 x 163 x 71	Restricted 30°	2 LED 3000 K	66257254	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 003GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	489 x 163 x 71	Medium 60°	2 LED 3000 K	66257262	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 004GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	490 x 163 x 71	Diffused 100°	2 LED 3000 K	66253634	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 005GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	491 x 163 x 71	Elliptical	2 LED 3000 K	66256835	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 006GS30K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	492 x 163 x 71	Asymmetrical	2 LED 3000 K	66256843	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 011GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Spotlight 10°	2+2 LED 3000 K	66253642	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	50 W	
GW S4 012GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Restricted 30°	2+2 LED 3000 K	66257254	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 013GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Medium 60°	2+2 LED 3000 K	66257262	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 014GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Diffused 100°	2+2 LED 3000 K	66253634	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 015GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Elliptical	2+2 LED 3000 K	66256835	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 016GS30K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Asymmetrical	2+2 LED 3000 K	66256843 66256850	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 021GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	4 LED 3000 K	66257270	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	50 W	
GW S4 022GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	4 LED 3000 K	66255803	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 023GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	4 LED 3000 K	66257288	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 024GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	4 LED 3000 K	66257296	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 025GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	4 LED 3000 K	66257304	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 026GS30K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	4 LED 3000 K	66257320	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 031GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	5 LED 3000 K	66257353	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	60 W	
GW S4 032GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 033GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 034GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 035GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	5 LED 3000 K	66257379	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 036GS30K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	5 LED 3000 K	66257387	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 041GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	4+4 LED 3000 K	66257270	Max. 950 mA	GEWISS 160W cod. 66225566	220-240 V - 50/60 Hz	97 W	
GW S4 042GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Restricted 30°	4+4 LED 3000 K	66255803	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 043GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Medium 60°	4+4 LED 3000 K	66257288	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 044GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Diffused 100°	4+4 LED 3000 K	66257296	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 045GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Elliptical	4+4 LED 3000 K	66257379	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 046GS30K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Asymmetrical	4+4 LED 3000 K	66257338 66257346	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 051GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	5+5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W cod. 66225566	220-240 V - 50/60 Hz	118 W	
GW S4 052GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	701 x 254 x 75	Restricted 30°	5+5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 053GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	702 x 254 x 75	Medium 60°	5+5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 054GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	703 x 254 x 75	Diffused 100°	5+5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 055GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	704 x 254 x 75	Elliptical	5+5 LED 3000 K	66257379	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 056GS30K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	705 x 254 x 75	Asymmetrical	5+5 LED 3000 K	66255647 66255654	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 061GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x4 LED 3000 K	66257270	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	220-240 V - 50/60 Hz	194 W	
GW S4 062GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x4 LED 3000 K	66255803	Max. 950 mA		220-240 V - 50/60 Hz	194 W	
GW S4 063GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x4 LED 3000 K	66257288	Max. 950 mA		220-240 V - 50/60 Hz	194 W	
GW S4 064GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x4 LED 3000 K	66257296	Max. 950 mA		220-240 V - 50/60 Hz	194 W	
GW S4 065GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x4 LED 3000 K	66257379	Max. 950 mA		220-240 V - 50/60 Hz	194 W	
GW S4 066GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x4L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x4 LED 3000 K	66257338 66257346	Max. 950 mA		220-240 V - 50/60 Hz	194 W	
GW S4 071GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Spotlight 10°	4x5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	220-240 V - 50/60 Hz	236 W	
GW S4 072GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Restricted 30°	4x5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 073GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Medium 60°	4x5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 074GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Diffused 100°	4x5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 075GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Elliptical	4x5 LED 3000 K	66257379	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 076GS30K	SMART [4] 2.0 HB - Stand-Alone - 4x5L - IP66 - Class I - Grey RAL 7037	700 x 504 x 85	Asymmetrical	4x5 LED 3000 K	66255647 66255654	Max. 950 mA		220-240 V - 50/60 Hz	236 W	

Floodlight Models

TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED controlgear	Rated Voltage	Input power	Rendering
GW S4 101GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Spotlight 10°	2 LED 3000 K	66253642	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	220-240 V - 50/60 Hz	26 W	
GW S4 102GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Restricted 30°	2 LED 3000 K	66257254	Max. 950 mA		220-240 V - 50/60 Hz	26 W	
GW S4 103GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Medium 60°	2 LED 3000 K	66257262	Max. 950 mA		220-240 V - 50/60 Hz	26 W	
GW S4 104GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Diffused 100°	2 LED 3000 K	66253634	Max. 950 mA		220-240 V - 50/60 Hz	26 W	
GW S4 105GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Elliptical	2 LED 3000 K	66256835	Max. 950 mA		220-240 V - 50/60 Hz	26 W	
GW S4 106GS30K	SMART [4] 2.0 FL - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	532 x 191 x 73	Asymmetrical	2 LED 3000 K	66256843	Max. 950 mA		220-240 V - 50/60 Hz	26 W	
GW S4 111GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Spotlight 10°	2+2 LED 3000 K	66253642	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	50 W	
GW S4 112GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Restricted 30°	2+2 LED 3000 K	66257254	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 113GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Medium 60°	2+2 LED 3000 K	66257262	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 114GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Diffused 100°	2+2 LED 3000 K	66253634	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 115GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Elliptical	2+2 LED 3000 K	66256835	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 116GS30K	SMART [4] 2.0 FL - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	767 x 191 x 73	Asymmetrical	2+2 LED 3000 K	66256843 66256850	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 131GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Spotlight 10°	5 LED 3000 K	66257353	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	60 W	
GW S4 132GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Restricted 30°	5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 133GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Medium 60°	5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 134GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Diffused 100°	5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 135GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Elliptical	5 LED 3000 K	66255720	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 136GS30K	SMART [4] 2.0 FL - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	425 x 294 x 77	Asymmetrical	5 LED 3000 K	66257387	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 151GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Spotlight 10°	5+5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W cod. 66225566	220-240 V - 50/60 Hz	118 W	
GW S4 152GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Restricted 30°	5+5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 153GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Medium 60°	5+5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 154GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Diffused 100°	5+5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 155GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Elliptical	5+5 LED 3000 K	66255720	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 156GS30K	SMART [4] 2.0 FL - 5+5L - IP66 - Class I - Grey RAL 7037	741 x 282 x 77	Asymmetrical	5+5 LED 3000 K	66255647 66255654	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 171GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Spotlight 10°	4x5 LED 3000 K	66257353	Max. 950 mA	GEWISS 160W 2 x cod. 66225566	220-240 V - 50/60 Hz	236 W	
GW S4 172GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Restricted 30°	4x5 LED 3000 K	66257361	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 173GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Medium 60°	4x5 LED 3000 K	66255282	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 174GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Diffused 100°	4x5 LED 3000 K	66256355	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 175GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Elliptical	4x5 LED 3000 K	66255720	Max. 950 mA		220-240 V - 50/60 Hz	236 W	
GW S4 176GS30K	SMART [4] 2.0 FL - 4x5L - IP66 - Class I - Grey RAL 7037	751 x 533 x 99	Asymmetrical	4x5 LED 3000 K	66255647 66255654	Max. 950 mA		220-240 V - 50/60 Hz	236 W	

5700 K

Lowbay-Highbay Models

TypeRef.	Description	External dimensions (mm)	Type of optics	Light source	LED module	LED drive current	LED controlgear	Rated Voltage	Input power	Rendering
GW S4 001GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	487 x 163 x 71	Spotlight 10°	2 LED 5700 K	66257197	Max. 950 mA	GEWISS 40W SLIM cod. 66239682	220-240 V - 50/60 Hz	25 W	
GW S4 002GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	488 x 163 x 71	Restricted 30°	2 LED 5700 K	66257205	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 003GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	489 x 163 x 71	Medium 60°	2 LED 5700 K	66257213	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 004GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	490 x 163 x 71	Diffused 100°	2 LED 5700 K	66253253	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 005GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	491 x 163 x 71	Elliptical	2 LED 5700 K	66257221	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 006GS57K	SMART [4] 2.0 LB - Stand-Alone - 2L - IP66 - Class I - Grey RAL 7037	492 x 163 x 71	Asymmetrical	2 LED 5700 K	66257239	Max. 950 mA		220-240 V - 50/60 Hz	25 W	
GW S4 011GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Spotlight 10°	2+2 LED 5700 K	66257197	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	50 W	
GW S4 012GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Restricted 30°	2+2 LED 5700 K	66257205	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 013GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Medium 60°	2+2 LED 5700 K	66257213	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 014GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Diffused 100°	2+2 LED 5700 K	66253253	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 015GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Elliptical	2+2 LED 5700 K	66257221	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 016GS57K	SMART [4] 2.0 LB - Stand-Alone - 2+2L - IP66 - Class I - Grey RAL 7037	717 x 163 x 71	Asymmetrical	2+2 LED 5700 K	66257239	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 021GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	4 LED 5700 K	66257122	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	50 W	
GW S4 022GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	4 LED 5700 K	66257130	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 023GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	4 LED 5700 K	66256637	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 024GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	4 LED 5700 K	66256579	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 025GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	4 LED 5700 K	66257148	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 026GS57K	SMART [4] 2.0 LB - Stand-Alone - 4L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	4 LED 5700 K	66257163	Max. 950 mA		220-240 V - 50/60 Hz	50 W	
GW S4 031GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Spotlight 10°	5 LED 5700 K	66257064	Max. 950 mA	GEWISS 80W SLIM cod. 66239690	220-240 V - 50/60 Hz	60 W	
GW S4 032GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Restricted 30°	5 LED 5700 K	66257072	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 033GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Medium 60°	5 LED 5700 K	66255290	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 034GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Diffused 100°	5 LED 5700 K	66253220	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 035GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Elliptical	5 LED 5700 K	66257080	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 036GS57K	SMART [4] 2.0 LB - Stand-Alone - 5L - IP66 - Class I - Grey RAL 7037	383 x 253 x 74	Asymmetrical	5 LED 5700 K	66256389	Max. 950 mA		220-240 V - 50/60 Hz	60 W	
GW S4 041GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	4+4 LED 5700 K	66257122	Max. 950 mA	GEWISS 160W cod. 66225566	220-240 V - 50/60 Hz	97 W	
GW S4 042GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Restricted 30°	4+4 LED 5700 K	66257130	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 043GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Medium 60°	4+4 LED 5700 K	66256637	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 044GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Diffused 100°	4+4 LED 5700 K	66256579	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 045GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Elliptical	4+4 LED 5700 K	66257148	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 046GS57K	SMART [4] 2.0 HB - Stand-Alone - 4+4L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Asymmetrical	4+4 LED 5700 K	66257171 66257189	Max. 950 mA		220-240 V - 50/60 Hz	97 W	
GW S4 051GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	700 x 254 x 75	Spotlight 10°	5+5 LED 5700 K	66257064	Max. 950 mA	GEWISS 160W cod. 66225566	220-240 V - 50/60 Hz	118 W	
GW S4 052GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	701 x 254 x 75	Restricted 30°	5+5 LED 5700 K	66257072	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 053GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	702 x 254 x 75	Medium 60°	5+5 LED 5700 K	66255290	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 054GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	703 x 254 x 75	Diffused 100°	5+5 LED 5700 K	66253220	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 055GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	704 x 254 x 75	Elliptical	5+5 LED 5700 K	66257080	Max. 950 mA		220-240 V - 50/60 Hz	118 W	
GW S4 056GS57K	SMART [4] 2.0 HB - Stand-Alone - 5+5L - IP66 - Class I - Grey RAL 7037	705 x 254 x 75	Asymmetrical	5+5 LED 5700 K	66257106 66257