

Mr. Carmine Cataldo
carmine.cataldo@gewiss.com
GEWISS S.p.A.
Via A. Volta, 1 - 24069 Cenate Sotto (BG) I

Your ref.....:
Our ref.....: **FP-03516/21-gm02 rev.2**
Date.....: **2021.10.05**
Product.....: **Power switchgear and controlgear assemblies**
Trademark.....: **GEWISS**

Test Report n.....: MI21-0065562-01

With reference to your application September 2019, covering the above mentioned product, we wish to inform you of the following:

Type tests have been carried out on a sample of the product with positive results.

Once the relevant administrative and procedural requirements will be fulfilled, IMQ will issue the Approval Certificate.

Series IB66 CBF							
	Switched socket-outlet	Rated current of the ASSEMBLY (I _{nA})	Poles	Voltage (V)	Earthing contact position	Frequency (Hz)	Colour
With bottom	GW66847	58 A	2P+E	100 – 130V	4h	50/60	Yellow
	GW66848	50 A	3P+E	100 – 130V	4h	50/60	Yellow
	GW66849	50 A	3P+N+E	100 – 130V	4h	50/60	Yellow
	GW66850	58 A	2P+E	200 – 250V	6h	50/60	Blue
	GW66851	50 A	3P+E	200 – 250V	9h	50/60	Blue
	GW66852	50 A	3P+N+E	200 – 250V	9h	50/60	Blue
	GW66853	58 A	2P+E	380 – 415V	9h	50/60	Red
	GW66854	50 A	3P+E	380 – 415V	6h	50/60	Red
	GW66855	50 A	3P+N+E	380 – 415V	6h	50/60	Red

IMQ S.p.A. A SOCIO UNICO
SOGGETTA AD ATTIVITÀ DI DIREZIONE
E COORDINAMENTO DI IMQ GROUP S.R.L.

tel. (+39) 02 5073 1
fax (+39) 02 5099 1550
direzione.imq@legalmail.it
info@imq.it - www.imq.it

Sede legale
Italia - 20138 Milano
via Quintiliano 43

Sedi secondarie
Macerata, Modena
Roma, Torino, Treviso, Udine

	GW66856	50 A	3P+E	480 – 500V	7h	50/60	Black
	GW66857	50 A	3P+N+E	480 – 500V	7h	50/60	Black

Vertical fixed interlocked socket outlet - with bottom - with fuse-holder base

Rated values : Ue 415 V 50/60 Hz IP66

Standard : IEC 61439-3:2012 for use in conjunction with IEC 61439-1:2011 / EN 61439-3:2012 for use in conjunction with EN 61439-1:2011

Series IB66 CBF							
	Switched socket-outlet	Rated current of the ASSEMBLY (I _{NA})	Poles	Voltage (V)	Earthing contact position	Frequency (Hz)	Colour
With bottom	GW66866	58 A	2P+E	100 – 130V	4h	50/60	Yellow
	GW66867	50 A	3P+E	100 – 130V	4h	50/60	Yellow
	GW66868	50 A	3P+N+E	100 – 130V	4h	50/60	Yellow
	GW66869	58 A	2P+E	200 – 250V	6h	50/60	Blue
	GW66870	50 A	3P+E	200 – 250V	9h	50/60	Blue
	GW66871	50 A	3P+N+E	200 – 250V	9h	50/60	Blue
	GW66872	58 A	2P+E	380 – 415V	9h	50/60	Red
	GW66873	50 A	3P+E	380 – 415V	6h	50/60	Red
	GW66874	50 A	3P+N+E	380 – 415V	6h	50/60	Red
	GW66875	50 A	3P+E	480 – 500V	7h	50/60	Black
	GW66876	50 A	3P+N+E	480 – 500V	7h	50/60	Black

Vertical fixed interlocked socket outlet - with bottom for mounting modular devices

Rated values : Ue 415 V 50/60 Hz IP66

Standard : IEC 61439-3:2012 for use in conjunction with IEC 61439-1:2011 / EN 61439-3:2012 for use in conjunction with EN 61439-1:2011

IMQ S.p.A.
B.U. PRODUCT CONFORMITY ASSESSMENT
(Operation Manager)

Gianluca Mastrodomenico