

## MOBILE PLUGS AND SOCKET-OUTLETS

### Technical characteristics

Reference standards: CEI 23-50; (IEC 60884-1)

### Technical data

- Shells in unbreakable material.
- Cavities protected by safety shields.
- Tug-proof cable clamp.

SOCKET-OUTLETS				PLUGS						
				S11	S17	SPA11	SPA17	S31	S31	
										
				GW 28 003 GW 28 004	GW 28 005 GW 28 006	GW 28 007 GW 28 008	GW 28 009 GW 28 010	GW 28 011 GW 28 013	GW 28 012	
				1 x 2.5mm <sup>2</sup>	1 x 2.5mm <sup>2</sup>	1 x 2.5mm <sup>2</sup>	1 x 2.5mm <sup>2</sup>	1 x 2.5mm <sup>2</sup>	1 x 2.5mm <sup>2</sup>	
SOCKET-OUTLETS	Type	Name of Standard	Terminal capacity							
	 GW 30 201	 GW 20 201 GW 21 201	P11	2x4mm <sup>2</sup>	•		•			
	 GW 30 203	 GW 20 203 GW 21 203	P17/11	2x4mm <sup>2</sup>	•	•	•	•		
	 GW 30 211	 GW 20 265 GW 21 265	German Standard	2x4mm <sup>2</sup>					•	•
	 GW 30 210	 GW 20 205 GW 21 205	P30	2x4mm <sup>2</sup>	•				•	•
	 GW 30 212	 GW 20 246 GW 21 246	German/Italian Standard	2x4mm <sup>2</sup>	•	•			•	•
 GW 30 227	 GW 20 212 GW 21 212	Euro-American Standard	2x4mm <sup>2</sup>	•		•				
MOBILE SOCKET-OUTLETS	 GW 28 203 GW 28 204		P11	1 x 2.5mm <sup>2</sup>	•		•			
	 GW 28 205 GW 28 206		P17/11	1 x 2.5mm <sup>2</sup>	•	•	•	•		

### Installation characteristics

- Allow the creation of mobile connections while maintaining an IP XXD degree of protection and a high level of safety.
- By using plugs with a 90° cable outlet (SPA17/11), it is possible to reduce the dimensions (e.g. behind furniture or in very confined spaces).

## MULTIPLE ADAPTERS AND MULTIPLE MOBILE SOCKET-OUTLETS

### Technical characteristics

Reference standards: CEI 23-50; IEC 60884-1; CEI 23-57

### Technical data

- Shells in unbreakable material.
- Cavities protected by safety shields.
- For multiple mobile socket-outlets, the S17 and S30 plugs are the type permanently connected to the cable.

	SYNOPTIC TABLE OF MULTIPLE ADAPTERS AND MULTIPLE MOBILE SOCKET-OUTLETS							
	PLUG 2P + E			No. OUTPUTS	SOCKET-OUTLET 2P + E			
	10A	16A	German Standard (with side earth contact)		10A	16A dual amp.	German/Italian Standard (with side and central earth contacts)	
	GW 28 409						•	
		GW 28 410					•	
			GW 28 415				•	
<b>Multiple adapters</b> 	GW 28 421			3	• • •			
		GW 28 423					• • •	
	GW 28 418					• • •		
		GW 28 419					• • •	
	GW 28 416					• •		•
		GW 28 417					• •	•
<b>Multiple mobile socket-outlets</b> 		GW 28 613		5			• • • • •	
		GW 28 601		6		• • • • • •		

• The number of points indicates the number of outlets of that particular type of socket-outlet.

### Installation characteristics

Possibility of making a high number of energy take-off points, especially with the multiple mobile socket-outlets, without the risk of creating mechanical (and consequently electrical) problems on the socket-outlet.

In compliance with Standard CEI 23-57, it is not possible to insert one adapter in another.

