



230 Vac
MCB Type C

<i>MCB current</i>	10 A	16 A	20 A
Max number of SMART			
SMART [4] 2L	62	102	125
SMART [4] 2+2L	30	48	62
SMART [4] 4L	30	48	62
SMART [4] 5L	30	48	62
SMART [4] 4+4L	15	24	31
SMART [4] 5+5L	15	24	31
SMART [4] 4x4L	7	12	15
SMART [4] 4x5L	7	12	15

LED CCT:

Optics:




≤ 5700 K

	100°	60°	30°	10°	Elliptical	Asymmetrical
	RG1:	RG1:	RG1:	RG1:	RG1:	RG1:
SMART [4] 2L	1,5 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 2+2L	2 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 4L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 5L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 4+4L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 5+5L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 4x4L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m
SMART [4] 4x5L	1 m	1,6 m	1,8 m	3,6 m	5,3 m	5,3 m

.....m






① = L
③ = N
④ =














SMART [4] LOWBAY 2L















SMART [4] LOWBAY 2+2L







SMART [4] LOWBAY 4L/5L











-  N°4 M6x40
-  N°4 D6
-  N°4 M6








GWL1926 for SMART 4L / 5L
GWL1930 for SMART 4+4L / 5+5L



SMART [4] HIGHBAY 4+4L/5+5L



SMART [4] Highbay 4x4L / 4x5L




SMART [4] 2L / 2+2L / 4L / 5L / 4+4L / 5+5L / 4x4L / 4x5L






SMART [4] 2L / 2+2L




SMART [4] 4L / 4+4L / 5L / 5+5L / 4x4L / 4x5L









SMART [4] 2L





GWL1921




SMART [4] 2+2L





GWL1922




SMART [4] 4L / 5L





GWL1923




SMART [4] 4+4L / 5+5L







GWL1924




SMART [4] 4x4L / 4x5L




GWL1925




SMART [4] 2L




SMART [4] 2+2L




SMART [4] 4L/5L



SMART [4] 4+4L - 5+5L



SMART [4] 4x4L - 4x5L



Punto di contatto indicato in adempimento ai fini delle direttive e regolamenti UE applicabili:

Contact details according to the relevant European Directives and Regulations:

GEWISS S.p.A. Via A.Volta, 1 IT-24069 Cenate Sotto (BG) Italy tel: +39 035 946 111 E-mail: qualitymarks@gewiss.com



+39 035 946 111

8.30 - 12.30 / 14.00 - 18.00
lunedì ÷ venerdì - monday ÷ friday



+39 035 946 260



sat@gewiss.com
www.gewiss.com