


IP66




	DIMMING				V
	1-10 V	5,7	0,038 m²	0,085 m²	220-240 V 50/60 Hz
	DALI	5,7	0,038 m²	0,085 m²	220-240 V 50/60 Hz






LED CCT		≤ 5700 K
Optics		RG1
	S1	10 m
	S2	10 m
	A1	10 m
	A2	10 m
	A3	12,5 m
	C4	11 m
	C3	11 m
	C2	11 m
	C1	11 m

T [°C]	Flux Factor 1-10V version	Flux Factor DALI version	I ± 5%	W ± 5%
25	1	1	0,7 A	165
30	1	1	0,7 A	165
35	1	1	0,7 A	165
40	1	1	0,7 A	165
45	-	0,9	0,63 A	148
50	-	0,8	0,56 A	132









Flux Factor = Flux (T) / Flux (T=25°C)





MCB Type B:	10A	16A	20A
	-	1	2
MCB Type C:	10A	16A	20A
	1	3	5
MCB Type D:	10A	16A	20A
	4	8	12




B






20 Nm



3 Nm



N°6



Punto di contatto indicato in adempimento ai fini delle direttive e regolamenti UE applicabili:

Contact details according to the relevant European Directives and Regulations:

GEWISS S.p.A. Via A.Volta, 1 IT-24069 Cenate Sotto (BG) Italy tel: +39 035 946 111 E-mail: qualitymarks@gewiss.com



+39 035 946 111

8.30 - 12.30 / 14.00 - 18.00
lunedì ÷ venerdì - monday ÷ friday



+39 035 946 260



sat@gewiss.com
www.gewiss.com