




FK-Xtreme

GEWISS

FK-Xtreme is a range of pliable conduit available in **4 diameters**, made using a **coextrusion process** which prevents liquid concrete ingress and maintains the product's integrity, even in **extreme conditions**. The range is designed to make **installation and wiring easier**.

Key benefits of the FK-Xtreme range




Double protection

With its double layer, there is no risk of micro-holes, making these conduits the right choice in applications using self-levelling liquid concrete.




Resistance to low temperatures

The external layer of the conduit holds its structure to -25° C and offers excellent protection against pressure and impact.



Smooth cabling

The inner layer of the conduits at diameter 20, 25 and 32 mm includes a special coating, making it easier to feed cable pulls and electric cables through, cutting installation time.



A complete range

Available in 4 diameters (from 20 to 40 mm) to cover any installation and in 6 colours for easy identification. The whole range is IMQ certified.



The right product for any application

FK15 - 33212

Available with and without cable puller, from 16 mm to 63 mm of diameter and in 6 colours, the FK15 pliable conduits are made of PVC and suitable for **brick wall and traditional screed installations**.

FK-Xtreme - 33412

Pliable conduits FK-Xtreme have been designed to protect against the ingress of **liquid concrete**. Available in 6 colours, the diameter range is between 20 mm and 40 mm.

ICTA - 34223

Made of polypropylene, the ICTA self recovering pliable conduits offer high impact resistance and a wide installation temperature range. Classified as **Low Smoke Zero Halogen** so can be installed in **public buildings**. Available in 6 colours, 16mm to 63mm diameter range and with or without cable puller.

**NEW
PACKAGING**



100%
Recyclable









Lower CO₂
emissions



Less waste on
construction
sites

Ask your sales
representative
for more
information.

Discover the full range of **FK-Xtreme** on www.gewiss.com

| Colours | Code | Ø Conduit (mm) | Coil (m) | Pallet (m) |
|--|-------------|----------------|----------|------------|
|  Black | DX 15 020 X | 20 | 100 | 5.200 |
| | DX 15 025 X | 25 | 75 | 3.300 |
| | DX 15 032 X | 32 | 50 | 1.800 |
| | DX 15 040 X | 40 | 25 | 500 |
|  Green | DX 15 220 X | 20 | 100 | 2.400 |
| | DX 15 225 X | 25 | 75 | 1.500 |
| | DX 15 232 X | 32 | 50 | 800 |
| | DX 15 240 X | 40 | 25 | 500 |
|  Light blue | DX 15 420 X | 20 | 100 | 2.400 |
| | DX 15 425 X | 25 | 75 | 1.500 |
| | DX 15 432 X | 32 | 50 | 800 |
| | DX 15 440 X | 40 | 25 | 500 |
|  Brown | DX 15 620 X | 20 | 100 | 2.400 |
| | DX 15 625 X | 25 | 75 | 1.500 |
| | DX 15 632 X | 32 | 50 | 800 |
| | DX 15 640 X | 40 | 25 | 500 |
|  Lilac | DX 15 820 X | 20 | 100 | 5.200 |
| | DX 15 825 X | 25 | 75 | 3.300 |
| | DX 15 832 X | 32 | 50 | 1.800 |
| | DX 15 840 X | 40 | 25 | 500 |
|  Natural white | DX 16 220 X | 20 | 100 | 2.400 |
| | DX 16 225 X | 25 | 75 | 1.500 |
| | DX 16 232 X | 32 | 50 | 800 |
| | DX 16 240 X | 40 | 25 | 500 |

The conduits of diameter 20, 25 and 32 mm have lubricated inner layer for an easier installation of the cables. Products are packed with a white UV-resistant and weatherproof extensible film.

Visit www.gewiss.com and follow us on:

