

IEC 309 HP (HIGH PERFORMANCE) is a complete range of mobile plugs and mobile or flush-mounting socket-outlets from 16A to 125A. Trusted by installers around the world for their high IP rating, strength and quality and great handling.

The exclusive advantages of the IEC 309 HP range



Complete protection

Over and above meeting the IP66/IP67 minimum regulation rating, IEC 309 HP trailing plugs and socket-outlets include two additional ingress protection ratings that are unique to the electrotechnical market: IP68 and IP69.



Green materials

All the products in this range are made using halogen-free materials (in accordance with standard EN50267-2-2). In addition, the technopolymers guarantee high resistance to UV rays and chemical agents.



Mechanical robustness

The use of high-performance technopolymers offers optimum impact resistance (IKO9), even at low temperatures (down to -25°C).



Practical. ergonomic shape

All the covers of the mobile socket-outlets are designed to be easily opened; in fact the cover can be held open with just one hand, and the plug is easy to insert into the socketoutlet.









Innovative features of the IEC 309 HP range

16A-32A versions





Special INVERTER versions

two phases can be quickly switched over using a screwdriver, to invert the running direction of three-phase motors.



Simplified connection

With the IEC 309 HP INVERTER versions, As well as traditional screw wiring SAFE-LOCK is a novel closure system half while increasing the reliability of security while keeping ease of access. the electrical connection between the cables and terminals.





Quick closure

versions, we also offer a fast (spring) that uses a simple quarter-turn coupling wiring option that cuts wiring times by and locking mechanism to ensure

63A-125A versions





Special rubber grip

With integrated rubber parts for an cable tightening heavy-duty applications.



Easy, accurate

hand



Safe connection

The cable connection uses screw plate easier grip, even if wearing gloves, and The cable clamp, with radial precision terminals with indirect tightening for maximising impact resistance even in tightening, ensures extremely easy cable optimum safety, guaranteeing the best tightening even if there are no tools to contact surfaces and pressure even with non-terminated cables.

Discover the complete IEC 309 HP range at www.gewiss.com

An advanced connection system







