


FK15



FK15 is a range of pliable protective conduits made from PVC and classified 33212. No matter the complexity of the electrical system. A **comprehensive range, ease of installation** and **constant quality** make FK15 the most suitable range for traditional screed, brick wall and ceiling installations.

Key benefits of the FK15 range




Flexibility

The profile of the FK15 conduits is characterised by a special geometry of the ribs to offer greater flexibility, higher load resistance and reduced thermal memory - characteristics that simplify and speed up the laying procedure inside the duct.



Line identification

The wide choice of colours in the FK15 range ensures a valid solution for modern electrical systems with their increasingly complex and subdivided structure, where the identification of the different lines is essential.



A complete range

Available in 7 diameters (from 16 to 63 mm) to cover any installation and in 6 colours for easy identification of the lines, FK15 are available with and without cable puller. The whole range is IMQ certified.



Protective packaging

The pallets are protected with white stretch film to prevent exposure of the coils to UV rays and ensure at the same time a greater resistance to weathering and improved preservation during external storage.



The right product for any application

FK15 - 33212

Available with and without cable puller, from 16 mm to 63 mm of diameter and in 6 colours, the FK15 pliable conduits are made of PVC and suitable for **brick wall and traditional screed installations**.

FK-Xtreme - 33412

Pliable conduits FK-Xtreme have been designed to protect against the ingress of **liquid concrete**. Available in 6 colours, the diameter range is between 20 mm and 40 mm.

ICTA - 34223 and FKHF - 23223

ICTA and FKHF are polypropylene conduits. Classified as **Low Smoke Zero Halogen** so can be installed in **public buildings and plasterboard walls**. ICTA is available in 6 colours, FKHF in grey RAL7035, both available up to 63 mm, with or without cable puller.

**NEW
PACKAGING**



100%
Recyclable



Lower CO₂
emissions



Less waste on
construction
sites

Ask your sales
representative
for more
information.

Discover the full FK range on www.gewiss.com

FK15 PLIABLE CONDUITS - CLASSIFICATION 33212

	Ø Conduit (mm)	Coil (m)						
			Black	Green	Light blue	Brown	Lilac	Natural white
Without cable puller	16	100	DX 15 016 R	DX 15 216 R	DX 15 416 R	DX 15 616 R	DX 15 816 R	DX 16 216 R
	20	100	DX 15 020 R	DX 15 220 R	DX 15 420 R	DX 15 620 R	DX 15 820 R	DX 16 220 R
	25	75	DX 15 025 R	DX 15 225 R	DX 15 425 R	DX 15 625 R	DX 15 825 R	DX 16 225 R
	32	50	DX 15 032 R	DX 15 232 R	DX 15 432 R	DX 15 632 R	DX 15 832 R	DX 16 232 R
	40	25	DX 15 040 R	DX 15 240 R	DX 15 440 R	DX 15 640 R	DX 15 840 R	DX 16 240 R
	50	25	DX 15 050 R	DX 15 250 R	DX 15 450 R	DX 15 650 R	DX 15 850 R	DX 16 250 R
	63	20	DX 15 063 R	-	-	-	-	-
With cable puller	16	100	DX 15 116 R	DX 15 316 R	DX 15 516 R	DX 15 716 R	DX 15 916 R	DX 16 316 R
	20	100	DX 15 120 R	DX 15 320 R	DX 15 520 R	DX 15 720 R	DX 15 920 R	DX 16 320 R
	25	75	DX 15 125 R	DX 15 325 R	DX 15 525 R	DX 15 725 R	DX 15 925 R	DX 16 325 R
	32	50	DX 15 132 R	DX 15 332 R	DX 15 532 R	DX 15 732 R	DX 15 932 R	DX 16 332 R
	40	25	DX 15 140 R	-	-	-	-	-
	50	25	DX 15 150 R	-	-	-	-	-
	63	20	DX 15 163 R	-	-	-	-	-