



RK9 - RK9 HF

Light rigid conduits



RK9 and **RK9 HF** are new **light rigid conduits** with a compression resistance of **320 N** and are recommended for wall mounting electrical plants with a low risk of damage. **RK9 is made of PVC**, making it suitable to be installed in uncrowded areas, while **RK9 HF is made of Halogen Free PP**, allowing the installation in offices, shopping centers, schools, etc. They represent the best solution for those who do not require an high impact resistance but at the same time **do not want to compromise on quality**.

Key benefits of RK9 and RK9 HF - Light rigid conduits



A complete range

RK9 range is available in 6 diameters to cover any installation, and is offered in the typical gray RAL 7035 or white RAL 9010. RK9 HF range is available in 4 diameters in white RAL 9010, matching with modern and bright spaces.



Halogen-Free versions

Conduits RK9 HF are Halogen Free according to the latest Standard EN 50642 which guarantees they are safe for people in event of fire and safe for the environment after disposal.



Maximum integration

The rigid conduit system can be perfectly integrated with flexible conduits, wall-mounting junction boxes and distribution boards through the specific interconnection couplings.



Accessories for all installation


GEWISS is able to supply not only a great variety of rigid conduits but also routing elements and installation supports to fulfill the habits of each installer.



Discover the full range of conduits on www.gewiss.com

RK9 Light rigid conduits (PVC)


Classification 22211 (Standard EN 61386-1, EN 61386-21)



| Conduit Ø (mm) | Lenght (m) | Colour | Product code | |
|----------------|------------|----------------|--------------|-------------|
| | | | Straight end | Sleeved end |
| 16 | 3 m | GREY RAL 7035 | DX25116 | DX24916 |
| 20 | | | DX25120 | DX24920 |
| 25 | | | DX25125 | DX24925 |
| 32 | | | DX25132 | DX24932 |
| 40 | | | DX25140 | DX24940 |
| 50 | | | DX25150 | DX24950 |
| 16 | 3 m | WHITE RAL 9010 | DX25116W | |
| 20 | | | DX25120W | |
| 25 | | | DX25125W | |
| 32 | | | DX25132W | |
| 40 | | | DX25140W | |
| 16 | 2 m | GREY RAL 7035 | | DX24816 |
| 20 | | | | DX24820 |
| 25 | | | | DX24825 |
| 32 | | | | DX24832 |
| 40 | | | | DX24840 |

RK9 HF Light rigid conduits Halogen Free (PP)

Classification 23431 (Standard EN 61386-1, EN 61386-21)



| Conduit Ø (mm) | Lenght (m) | Colour | Product code |
|----------------|------------|----------------|--------------|
| | | | Straight end |
| 16 | 3 m | WHITE RAL 9010 | DX26716W |
| 20 | | | DX26720W |
| 25 | | | DX26725W |
| 32 | | | DX26732W |

NOTE: Halogen Free according to EN 50642.