Trade Catalogue



2025-26

GEWISS





Gewiss headquarters - Italy

Our innovation journey

We have a great passion: innovation. A vocation that translates into a continuous passion for change, **a predisposition to excellence** that requires creativity, competence, enterprise, and enthusiasm: qualities that are part of our history and have allowed us to grow by demonstrating the ability to **"look beyond".**

Vision

To be a reference company in the sector by promoting **meaningful innovations for society**.

Mission

Create value for our customers and our team by offering innovative and scalable solutions for buildings, industries, and infrastructures that connect people and things and improve safety and quality of life, guided by the values of **integrity, culture of excellence,** and **sustainability**.



Sustainability

We operate to reduce waste and manage **human, natural, and financial resources** efficiently. We aim to create value for **our people, our clients, the communities, and future generations**.



Excellence

Our culture of excellence is driven by the constant push **to improve and achieve challenging goals**, creating something better every day than the day before, exploring innovative solutions, and **maximizing our potential**.



Integrity

Integrity is the foundation on which employees, clients, and all stakeholders build **relationships of trust**. Integrity means being responsible, reliable, and **guided by strong ethical principles**.

The World is Our Home

ITALY


WEA
West Europe & Americas
Iberian Peninsula, France, Franco Africa, UK, Benelux, Ireland, Latin, Central and North America

DACH
Germany, Switzerland, Austria

NEE
North & East Europe
Romania, Poland, Hungary, Czech Republic, Greece, Cyprus, Malta, Russia, Ukraine, Nordics, Baltics, Balkans and Armen

HGR
High Growth
Middle East, Turkey, Azerbaijan, Kazakhstan, Israel & Palestine, Africa (except Franco Africa), India, Far East, Oceania





Our Journey for Sustainable Development



GEWISS's approach to sustainability demonstrates strong coherence and synergy with the Company's Mission.

Our goal in daily activities is to create shared value for all stakeholders and throughout the entire value chain in all the territories where we operate, **pursuing sustainable development and promoting innovations** that concretely improve daily life. For this reason, we have chosen **to develop a responsible business** model that promotes respectful behavior towards people and the environment.

This philosophy took shape and was expressed in the **first unified Group Sustainability Report** with tangible results, some of which are expressed on the opposite page (data refer to 2023 compared to the previous year).

Environment

-14%	energy consumption
-31%	natural gas consumption
-16%	CO_2 emissions
-2.5%	waste produced
97%	production of non hazardous waste

Social

+43K	hours of training
2.235	employees
97%	permanent contracts

Governance

ISO 27001	Information Security Management System within information services
UNI PdR 125:2022	Gender Equality Management System in Organizations

Solutions that Generate Value

Innovation is not the end goal but the means through which GEWISS meets stakeholders' needs. GEWISS commits to **generating social and economic value** for the company and its stakeholders through services and **solutions that improve daily life, reduce costs, and respect the environment.**

Constant investments in research and development, staff training, and enhancing production facilities have enabled GEWISS to establish itself as a reference point in the market for producing solutions and services for home & building automation, energy protection and distribution, electric mobility, and smart lighting.

Installation



Energy



Building



Lighting



Mobility



Products overview

IEC 309 HP



p. 24

IEC 309 BTS



p. 59

IEC 309 MA



p. 66

IB



p. 78

68 Q-DIN



p. 112

40 CDE



p. 208

42 RV



p. 224

44 CE



p. 233

GW CONNECT



p. 245

42 TV



p. 249

FK



p. 344

DF



p. 356

PZ



p. 363

GW FIT



p. 378

90 RESTART



p. 422

97 MSS



p. 583

47 CVX 160 I



p. 593

47 CVX 160 E



p. 602

QDX 630 L



p. 619

QDX 630 H



p. 639

CHORUSMART ANTIBACTERIAL RANGE



p. 971

SYSTEM PLATES



p. 988

SYSTEM MODULAR DEVICES



p. 1004

27 COMBI



p. 1058

PLAYBUS PLATES



p. 1072

DATA CENTER



p. 1182

28 SPIC



p. 1189

DOMO CENTER



p. 1202

I-CON EVO



p. 1218

I-ON EVO



p. 1226

68 ACS



p. 128

70 RT HP



p. 147

74 PS



p. 160

46



p. 174

40 CD



p. 196

GREEN WALL



p. 260

40 CDi



p. 280

48



p. 301

24 SC



p. 316

RK



p. 330

90 MCB



p. 438

90 RCD



p. 467

90 AM



p. 501

90 PV



p. 539

MSX



p. 553

QDX 1600 H



p. 660

BUSBAR



p. 684

CHORUSMART PLATES

p. 697

CHORUSMART INSTALLATION ACCESSORIES



p. 769

CHORUSMART MODULAR DEVICES



p. 788

PLAYBUS MODULAR DEVICES



p. 1082

DAHLIA PLATES

p. 1097

DAHLIA MONOBLOC DEVICES



p. 1102

CONNECTED SMART HOME



p. 1126

HOME & BUILDING PRO



p. 1150

I-FAST



p. 1233

COMPONENTS



p. 1237

68 Q-MC 63X



p. 1246

68 Q-MC



p. 1254

Index

INSTALLATION

IEC 309 PLUGS AND SOCKET-OUTLETS	IEC 309 HP	Plugs and socket-outlets IEC 309 standard	**24**
	IEC 309 BTS	Extra-low voltage plugs and socket-outlets IEC 309 standard	**59**
	IEC 309 MA	Multiple sockets and adaptors for industrial and domestic use, protected and watertight	**66**
INTERLOCKED SOCKET-OUTLETS IEC 309 STANDARD	IB	Interlocked socket-outlets IEC 309 standard	**78**
IEC 309 COMBINED BOARDS	68 Q-DIN	Distribution boards	**112**
	68 ACS	ACS distribution board system for construction sites	**128**
CONTROL AND SIGNALLING	70 RT HP	Rotary isolators	**147**
	74 PS	Push-buttons, selectors and indicators Ø 22 mm	**160**
WALL-MOUNTING ENCLOSURES	46	Watertight surface-mounting distribution and automation boards	**174**
	40 CD	Surface-mounting distribution boards and enclosures	**196**
	40 CDE	Enclosures and distribution boards for specific standards	**208**
	42 RV	Surface and flush-mounting watertight emergency enclosures	**224**
	44 CE	Technopolymer surface-mounting watertight junction boxes	**233**
	GW Connect	Metal surface-mounting watertight junction boxes	**245**
	42 TV	Multifunctional supporting bases	**249**
FLUSH-MOUNTING ENCLOSURES	GREEN WALL	Flush-mounting system for plasterboard walls	**260**
	40 CDI	Flush-mounting distribution boards and enclosures	**280**
	48	Flush-mounting junction and modular boxes system	**301**
	24 SC	Flush-mounting, surface and underfloor boxes	**316**
CONDUITS AND ACCESSORIES FOR INSTALLATION	RK	Rigid protective conduit systems	**330**
	FK	Pliable protective conduit systems	**344**
	DF	Flexible protective conduit systems	**356**
	PZ	Access chambers systems	**363**
	GW FIT	Accessories for electrical installation	**378**

ENERGY

AUTOMATIC RECLOSING DEVICES	90 ReStart	Automatic reclosing devices	**422**
CIRCUIT BREAKERS FOR CIRCUIT PROTECTION	90 MCB	Modular circuit breakers for circuit protection	**438**
CIRCUIT BREAKERS FOR RESIDUAL CURRENT PROTECTION	90 RCD	Modular circuit breakers for residual current protection	**467**
MODULAR ACCESSORIES	90 AM	Modular accessories	**501**
	90 PV	Products for photovoltaic systems	**539**
MOULDED CASE CIRCUIT BRAKERS	MSX	Moulded case circuit breakers for power distribution	**553**
	97 MSS	Rotary switch disconnectors	**583**
ELECTRICAL DISTRIBUTION BOARDS	47 CVX 160 I	Flush-mounting distribution boards up to 160 A	**593**
	47 CVX 160 E	Wall-mounting distribution boards up to 160 A with extractable frame	**602**
	QDX 630 L	Modular distribution boards up to 630 A - IP43	**619**
	QDX 630 H	Monobloc and modular distribution boards up to 630 A - IP55	**639**
	QDX 1600 H	Modular enclosures up to 1600 A - IP55	**660**
	BUSBAR	Distribution systems for distribution boards	**684**

BUILDING

CHORUSMART	DOMESTIC RANGE	ONE International plates	**697**
		GEO International plates	**703**
		EGO International plates	**709**
		EGO SMART International plates	**715**
		LUX International plates	**722**
		ONE plates	**729**
		GEO plates	**735**
		EGO plates	**741**
		EGO SMART plates	**747**
		LUX plates	**754**
		ICE plates	**763**
		Installation accessories	**769**
		Glossy white modular devices	**788**
		Satin white modular devices	**822**
		Satin natural beige modular devices	**856**
		Satin black modular devices	**890**
		Glossy titanium modular devices	**924**
		Glossy ivory modular devices	**958**
		Antibacterial range	**971**
SYSTEM	DOMESTIC RANGE	Plates	**988**
		Modular devices	**1004**
27 COMBI	27 COMBI	Wall-mounting enclosures and modular components	**1058**
PLAYBUS	DOMESTIC RANGE	Plates	**1072**
		Modular devices	**1082**
DAHLIA	DOMESTIC RANGE	Plates	**1097**
		Monobloc devices	**1102**
SMART HOME & BUILDING	CONNECTED SMART HOME	Connected Smart Home range	**1126**
	HOME & BUILDING PRO	Home & Building Pro range	**1150**
DATA AND ENERGY DISTRIBUTION	DATA CENTER	Network cabling	**1182**
	28 SPIC	Plugs, sockets and adapters for domestic and similar uses	**1189**
FLUSH-MOUNTING ENCLOSURES	DOMO CENTER	Flush-mounting system columns for distribution, Home & Building automation and data	**1202**

MOBILITY

JOINON ELECTRIC VEHICLE CHARGING	I-CON EVO	AC charging wallboxes	**1218**
	I-ON EVO	AC charging stations	**1226**
	I-FAST	DC charging stations	**1233**
	COMPONENTS	Charging components	**1237**
ENERGY AND SERVICES DISTRIBUTION PEDESTALS	68 Q-MC 63X	Stainless steel distribution and service pedestals	**1246**
	68 Q-MC	Pedestals for energy distribution and service in insulating material	**1254**

ITEMS WHILE STOCKS LAST **1271**

Installation





IEC 309 plugs and socket-outlets

The IEC 309 system of sockets and plugs consists of the IEC 309 HP range (16 to 125A low-voltage sockets and plugs in mobile straight, 10° flush-mounted and wall-mounted versions), IEC 309 BTS (very low-voltage industrial sockets and plugs for requirements below 50V) and IEC 309 MA (a range of protected and watertight multipliers, adaptors and shunts for industrial and domestic uses).



Interlocked socket-outlets IEC 309 standard

The IEC 309 compliant interlocked socket system consists of the 67 IB (vertical interlocked sockets), 66 IB (heavy-duty vertical interlocked sockets), 44 IB (protected horizontal interlocked sockets) and COMBIBLOC (protected and watertight compact interlocked sockets) series.



IEC 309 combined boards

A system of empty or wired boards, compliant with the EN 61439 standard, able to satisfy any system necessity for wall, flush, mast and floor-mounting in service and industrial sectors, small and large construction sites and in ports.



Control and signalling

A complete system for the control and automation in industrial and robotic application, on-board machines and in electrical/electronic industry. The offer consists of wall-mounted or board rotary switch-disconnectors, push-buttons, selectors and indicators.



Wall-mounting enclosures

A range of containers for surface-mounting systems and applications in the industrial, commercial and residential contexts. The range consists of watertight boards (in technopolymer, polyester reinforced with fibreglass, metal and stainless steel), boxes (in technopolymer and metal) and multifunctional supporting bases.



Flush-mounting enclosures

Container system for commercial and residential applications. The system columns (for energy distribution, domotics and multimedia) are also part of the range, along with enclosures, distribution boards, boxes for domestic ranges and junction boxes with integrated DIN rail.



Conduits and accessories for installation

A range of protective conduits for surface-mounting and flush-mounting applications in the industrial, commercial and residential contexts. The range includes medium to heavy rigid conduits (including Halogen Free versions), medium folding protective conduits, coextruded folding protective conduits and self-recovering protective conduits (ICTA Halogen Free).

IEC 309 plugs and socket-outlets







IEC 309 HP

Plugs and socket-outlets IEC 309 standard

p. 24

IEC 309 BTS

Extra-low voltage plugs and socket-outlets IEC 309 standard

p. 59

IEC 309 MA

Multiple sockets and adaptors for industrial and domestic use, protected and watertight

p. 66

IEC 309 HP

16A and 32A Low voltage industrial plugs and socket-outlets IEC 309 standard - IEC 309 HP

Rated current (In)	Rated Voltage (Un)	Frequency	Poles	Reference h	Straight plugs IP44/IP54		Straight plugs IP66/IP67/IP68/IP69	
								
					Fast wiring	Screw wiring	Fast wiring	Screw wiring
16 A	100 ÷ 130 V	50/60 Hz	2P+E	4	GW 60 001 FH	GW 60 001 H	GW 60 023 FH	GW 60 023 H
			3P+E	4	GW 60 002 FH	GW 60 002 H	GW 60 024 FH	GW 60 024 H
			3P+N+E	4	GW 60 003 FH	GW 60 003 H	GW 60 025 FH	GW 60 025 H
	200 ÷ 250 V	50/60 Hz	2P+E	6	GW 60 004 FH	GW 60 004 H	GW 60 026 FH	GW 60 026 H
			3P+E	9	GW 60 005 FH	GW 60 005 H	GW 60 027 FH	GW 60 027 H
						GW 60 005 WH (*)		GW 60 027 WH (*)
			3P+N+E	9	GW 60 006 FH	GW 60 006 H	GW 60 028 FH	GW 60 028 H
						GW 60 006 WH (*)		GW 60 028 WH (*)
	380 ÷ 415 V	50/60 Hz	2P+E	9	GW 60 007 FH	GW 60 007 H	GW 60 029 FH	GW 60 029 H
			3P+E	6	GW 60 008 FH	GW 60 008 H	GW 60 030 FH	GW 60 030 H
						GW 60 008 WH (*)		GW 60 030 WH (*)
			3P+N+E	6	GW 60 009 FH	GW 60 009 H	GW 60 031 FH	GW 60 031 H
						GW 60 009 WH (*)		GW 60 031 WH (*)
	480 ÷ 500 V	50/60 Hz	2P+E	7		GW 60 701 H		GW 60 735 H
			3P+E	7		GW 60 010 H		GW 60 032 H
			3P+N+E	7		GW 60 011 H		GW 60 033 H
	600 ÷ 690 V	50/60 Hz	3P+E	5		GW 60 702 H		GW 60 736 H
			3P+N+E	5		GW 60 703 H		GW 60 737 H
	> 50 V	100 ÷ 300 Hz	2P+E	10		GW 60 704 H		GW 60 738 H
			3P+E	10		GW 60 705 H		GW 60 739 H
			3P+N+E	10		GW 60 706 H		GW 60 740 H
	> 50 V	> 300 ÷ 500 Hz	2P+E	2		GW 60 707 H		GW 60 741 H
			3P+E	2		GW 60 708 H		GW 60 742 H
			3P+N+E	2		GW 60 709 H		GW 60 743 H
	440 ÷ 460 V	60 Hz	3P+E	11		GW 60 710 H		GW 60 744 H
			3P+N+E	11		GW 60 711 H		GW 60 745 H
	380 V / 440 V	50 Hz / 60 Hz	3P+E	3		GW 60 712 H		GW 60 746 H
			3P+N+E	3		GW 60 713 H		GW 60 747 H
	transf.	50/60 Hz	2P+E	12		GW 60 714 H		GW 60 748 H
			3P+E	12		GW 60 715 H		GW 60 749 H
	> 50 ÷ 250V	dc	2P+E	3		GW 60 716 H		GW 60 750 H
	> 250V	dc	2P+E	8		GW 60 717 H		GW 60 751 H
32 A	100 ÷ 130 V	50/60 Hz	2P+E	4	GW 60 012 FH	GW 60 012 H	GW 60 034 FH	GW 60 034 H
			3P+E	4	GW 60 013 FH	GW 60 013 H	GW 60 035 FH	GW 60 035 H
			3P+N+E	4	GW 60 014 FH	GW 60 014 H	GW 60 036 FH	GW 60 036 H
	200 ÷ 250 V	50/60 Hz	2P+E	6	GW 60 015 FH	GW 60 015 H	GW 60 037 FH	GW 60 037 H
			3P+E	9	GW 60 016 FH	GW 60 016 H	GW 60 038 FH	GW 60 038 H
						GW 60 016 WH (*)		GW 60 038 WH (*)
			3P+N+E	9	GW 60 017 FH	GW 60 017 H	GW 60 039 FH	GW 60 039 H
						GW 60 017 WH (*)		GW 60 039 WH (*)
	380 ÷ 415 V	50/60 Hz	2P+E	9	GW 60 018 FH	GW 60 018 H	GW 60 040 FH	GW 60 040 H
			3P+E	6	GW 60 019 FH	GW 60 019 H	GW 60 041 FH	GW 60 041 H
						GW 60 019 WH (*)		GW 60 041 WH (*)
			3P+N+E	6	GW 60 020 FH	GW 60 020 H	GW 60 042 FH	GW 60 042 H
						GW 60 020 WH (*)		GW 60 042 WH (*)
	480 ÷ 500 V	50/60 Hz	2P+E	7		GW 60 718 H		GW 60 752 H
			3P+E	7		GW 60 021 H		GW 60 043 H
			3P+N+E	7		GW 60 022 H		GW 60 044 H
	600 ÷ 690 V	50/60 Hz	3P+E	5		GW 60 719 H		GW 60 753 H
			3P+N+E	5		GW 60 720 H		GW 60 754 H
	> 50 V	100 ÷ 300 Hz	2P+E	10		GW 60 721 H		GW 60 755 H
			3P+E	10		GW 60 722 H		GW 60 756 H
			3P+N+E	10		GW 60 723 H		GW 60 757 H
	> 50 V	> 300 ÷ 500 Hz	2P+E	2		GW 60 724 H		GW 60 758 H
			3P+E	2		GW 60 725 H		GW 60 759 H
			3P+N+E	2		GW 60 726 H		GW 60 760 H
	440 ÷ 460 V	60 Hz	3P+E	11		GW 60 727 H		GW 60 761 H
			3P+N+E	11		GW 60 728 H		GW 60 762 H
	380 V / 440 V	50 Hz / 60 Hz	3P+E	3		GW 60 729 H		GW 60 145 H
			3P+N+E	3		GW 60 730 H		GW 60 763 H
	transf.	50/60 Hz	2P+E	12		GW 60 731 H		GW 60 764 H
			3P+E	12		GW 60 732 H		GW 60 765 H
	> 50 ÷ 250V	dc	2P+E	3		GW 60 733 H		GW 60 766 H
	> 250V	dc	2P+E	8		GW 60 734 H		GW 60 767 H

(*) Straight plugs with phase inverter

Straight connectors IP44/IP54		Straight connectors IP66/IP67/IP68/IP69		10° flush-mounting socket-outlets IP44/IP45		10° flush-mounting socket-outlets IP66/IP67		APPLICATIONS
								
Fast wiring	Screw wiring	Fast wiring	Screw wiring	Fast wiring	Screw wiring	Fast wiring	Screw wiring	
GW 62 001 FH	GW 62 001 H	GW 62 023 FH	GW 62 023 H	GW 62 201 FH	GW 62 201 H	GW 62 224 FH	GW 62 224 H	Standard use
GW 62 002 FH	GW 62 002 H	GW 62 024 FH	GW 62 024 H	GW 62 202 FH	GW 62 202 H	GW 62 225 FH	GW 62 225 H	
GW 62 003 FH	GW 62 003 H	GW 62 025 FH	GW 62 025 H	GW 62 203 FH	GW 62 203 H	GW 62 226 FH	GW 62 226 H	
GW 62 004 FH	GW 62 004 H	GW 62 026 FH	GW 62 026 H	GW 62 205 FH	GW 62 205 H (**)	GW 62 227 FH	GW 62 227 H	
GW 62 005 FH	GW 62 005 H	GW 62 027 FH	GW 62 027 H	GW 62 206 FH	GW 62 206 H	GW 62 228 FH	GW 62 228 H	
GW 62 006 FH	GW 62 006 H	GW 62 028 FH	GW 62 028 H	GW 62 207 FH	GW 62 207 H	GW 62 229 FH	GW 62 229 H	
GW 62 007 FH	GW 62 007 H	GW 62 029 FH	GW 62 029 H	GW 62 208 FH	GW 62 208 H	GW 62 230 FH	GW 62 230 H	
GW 62 008 FH	GW 62 008 H	GW 62 030 FH	GW 62 030 H	GW 62 209 FH	GW 62 209 H	GW 62 231 FH	GW 62 231 H	
GW 62 009 FH	GW 62 009 H	GW 62 031 FH	GW 62 031 H	GW 62 210 FH	GW 62 210 H	GW 62 232 FH	GW 62 232 H	
	GW 62 701 H		GW 62 735 H		GW 62 801 H		GW 62 835 H	Use with particular voltage
	GW 62 010 H		GW 62 032 H		GW 62 211 H		GW 62 233 H	
	GW 62 011 H		GW 62 033 H		GW 62 212 H		GW 62 234 H	
	GW 62 702 H		GW 62 736 H		GW 62 802 H		GW 62 836 H	
	GW 62 703 H		GW 62 737 H		GW 62 803 H		GW 62 837 H	
	GW 62 704 H		GW 62 738 H		GW 62 804 H		GW 62 838 H	Use with high frequencies
	GW 62 705 H		GW 62 739 H		GW 62 805 H		GW 62 839 H	
	GW 62 706 H		GW 62 740 H		GW 62 806 H		GW 62 840 H	
	GW 62 707 H		GW 62 741 H		GW 62 807 H		GW 62 841 H	
	GW 62 708 H		GW 62 742 H		GW 62 808 H		GW 62 842 H	
	GW 62 709 H		GW 62 743 H		GW 62 809 H		GW 62 843 H	
	GW 62 710 H		GW 62 744 H		GW 62 810 H		GW 62 844 H	Marine, port and naval, installations
	GW 62 711 H		GW 62 745 H		GW 62 811 H		GW 62 845 H	
	GW 62 712 H		GW 62 746 H		GW 62 812 H		GW 62 846 H	Refrigeretion containers
	GW 62 713 H		GW 62 747 H		GW 62 813 H		GW 62 847 H	
	GW 62 714 H		GW 62 748 H		GW 62 814 H		GW 62 848 H	Isolation transformers
	GW 62 715 H		GW 62 749 H		GW 62 815 H		GW 62 849 H	
	GW 62 716 H		GW 62 750 H		GW 62 816 H		GW 62 850 H	Use in direct current
	GW 62 717 H		GW 62 751 H		GW 62 817 H		GW 62 851 H	
GW 62 012 FH	GW 62 012 H	GW 62 034 FH	GW 62 034 H	GW 62 213 FH	GW 62 213 H	GW 62 235 FH	GW 62 235 H	Standard use
GW 62 013 FH	GW 62 013 H	GW 62 035 FH	GW 62 035 H	GW 62 214 FH	GW 62 214 H	GW 62 236 FH	GW 62 236 H	
GW 62 014 FH	GW 62 014 H	GW 62 036 FH	GW 62 036 H	GW 62 215 FH	GW 62 215 H	GW 62 237 FH	GW 62 237 H	
GW 62 015 FH	GW 62 015 H	GW 62 037 FH	GW 62 037 H	GW 62 216 FH	GW 62 216 H	GW 62 238 FH	GW 62 238 H	
GW 62 016 FH	GW 62 016 H	GW 62 038 FH	GW 62 038 H	GW 62 217 FH	GW 62 217 H	GW 62 239 FH	GW 62 239 H	
GW 62 017 FH	GW 62 017 H	GW 62 039 FH	GW 62 039 H	GW 62 218 FH	GW 62 218 H	GW 62 240 FH	GW 62 240 H	
GW 62 018 FH	GW 62 018 H	GW 62 040 FH	GW 62 040 H	GW 62 219 FH	GW 62 219 H	GW 62 241 FH	GW 62 241 H	
GW 62 019 FH	GW 62 019 H	GW 62 041 FH	GW 62 041 H	GW 62 220 FH	GW 62 220 H	GW 62 242 FH	GW 62 242 H	
GW 62 020 FH	GW 62 020 H	GW 62 042 FH	GW 62 042 H	GW 62 221 FH	GW 62 221 H	GW 62 243 FH	GW 62 243 H	
	GW 62 718 H		GW 62 752 H		GW 62 818 H		GW 62 852 H	Use with particular voltage
	GW 62 021 H		GW 62 043 H		GW 62 222 H		GW 62 244 H	
	GW 62 022 H		GW 62 044 H		GW 62 223 H		GW 62 245 H	
	GW 62 719 H		GW 62 753 H		GW 62 819 H		GW 62 853 H	
	GW 62 720 H		GW 62 754 H		GW 62 820 H		GW 62 854 H	
	GW 62 721 H		GW 62 755 H		GW 62 821 H		GW 62 855 H	Use with high frequencies
	GW 62 722 H		GW 62 756 H		GW 62 822 H		GW 62 856 H	
	GW 62 723 H		GW 62 757 H		GW 62 823 H		GW 62 857 H	
	GW 62 724 H		GW 62 758 H		GW 62 824 H		GW 62 858 H	
	GW 62 725 H		GW 62 759 H		GW 62 825 H		GW 62 859 H	
	GW 62 726 H		GW 62 760 H		GW 62 826 H		GW 62 860 H	
	GW 62 727 H		GW 62 761 H		GW 62 827 H		GW 62 861 H	Marine, port and naval, installations
	GW 62 728 H		GW 62 762 H		GW 62 828 H		GW 62 862 H	
	GW 62 729 H		GW 62 128 H		GW 62 829 H		GW 62 283 H	Refrigeretion containers
	GW 62 730 H		GW 62 763 H		GW 62 830 H		GW 62 863 H	
	GW 62 731 H		GW 62 764 H		GW 62 831 H		GW 62 864 H	Isolation transformers
	GW 62 732 H		GW 62 765 H		GW 62 832 H		GW 62 865 H	
	GW 62 733 H		GW 62 766 H		GW 62 833 H		GW 62 866 H	Use in direct current
	GW 62 734 H		GW 62 767 H		GW 62 834 H		GW 62 867 H	

(**) APPLICATION: GW 62 204, cap of reduced dimensions (62 x 62mm) for use in restricted spaces.

IEC 309 HP

63A and 125A Low voltage industrial plugs and socket-outlets IEC 309 standard - IEC 309 HP

Rated current (In)	Rated voltage (Un)	Frequency	Poles	Reference h	Straight mobile plugs IP44/IP54  Mantle connection	Straight mobile plugs IP66/IP67/IP68/IP69  Mantle connection
63 A	100 ÷ 130 V	50/60 Hz	2P+E	4	GW 61 013 H	GW 61 045 H
			3P+E	4	GW 61 014 H	GW 61 046 H
			3P+N+E	4	GW 61 015 H	GW 61 047 H
	200 ÷ 250 V	50/60 Hz	2P+E	6	GW 61 016 H	GW 61 048 H
			3P+E	9	GW 61 017 H	GW 61 049 H
			3P+N+E	9	GW 61 018 H	GW 61 050 H
	380 ÷ 415 V	50/60 Hz	2P+E	9	GW 61 019 H	GW 61 051 H
			3P+E	6	GW 61 020 H	GW 61 052 H
			3P+N+E	6	GW 61 021 H	GW 61 053 H
	480 ÷ 500 V	50/60 Hz	2P+E	7		GW 61 056 H
			3P+E	7		GW 61 054 H
			3P+N+E	7		GW 61 055 H
	600 ÷ 690 V	50/60 Hz	3P+E	5		GW 61 057 H
			3P+N+E	5		GW 61 058 H
	> 50 V	100 ÷ 300 Hz	2P+E	10		GW 61 059 H
			3P+E	10		GW 61 060 H
			3P+N+E	10		GW 61 061 H
	> 50 V	> 300 ÷ 500 Hz	2P+E	2		GW 61 062 H
			3P+E	2		GW 61 063 H
			3P+N+E	2		GW 61 064 H
	440 ÷ 460 V	60 Hz	3P+E	11		GW 61 065 H
			3P+N+E	11		GW 61 066 H
	> 50 ÷ 250V	dc	2P+E	3		GW 61 067 H
	> 250V	dc	2P+E	8		GW 61 068 H
125 A	100 ÷ 130 V	50/60 Hz	2P+E	4		GW 60 664 H
			3P+E	4		GW 60 056 H
			3P+N+E	4		GW 60 057 H
	200 ÷ 250 V	50/60 Hz	2P+E	6		GW 60 665 H
			3P+E	9		GW 60 058 H
			3P+N+E	9		GW 60 059 H
	380 ÷ 415 V	50/60 Hz	2P+E	9		GW 60 666 H
			3P+E	6		GW 60 060 H
						GW 60 061 H
						GW 60 667 H
			3P+N+E	6		GW 60 062 H
						GW 60 063 H
						GW 60 668 H
	480 ÷ 500 V	50/60 Hz	2P+E	7		GW 60 669 H
			3P+E	7		GW 60 670 H
			3P+N+E	7		GW 60 671 H
	600 ÷ 690 V	50/60 Hz	3P+E	5		GW 60 672 H
			3P+N+E	5		GW 60 673 H
	> 50 V	100 ÷ 300 Hz	2P+E	10		GW 60 674 H
			3P+E	10		GW 60 675 H
			3P+N+E	10		GW 60 676 H
	> 50 V	> 300 ÷ 500 Hz	2P+E	2		GW 60 677 H
			3P+E	2		
			3P+N+E	2		
	440 ÷ 460 V	60 Hz	3P+E	11		
			3P+N+E	11		

NOTE: all plugs are equipped with pilot contact.
(*) connectors equipped with pilot contact (screw wiring);
(**) IP67 connectors equipped with potential-free contact.

Straight mobile connectors IP44/IP54	Straight connectors IP66/IP67/IP68/IP69	10° fixed flush-mounting socket-outlets IP44/IP54	10° fixed flush-mounting socket-outlets IP66/IP67	APPLICATIONS
				
Mantle connection	Mantle connection	Mantle connection	Mantle connection	
GW 63 013 H	GW 63 045 H	GW 63 213 H	GW 63 246 H	Standard use
GW 63 014 H	GW 63 046 H	GW 63 214 H	GW 63 247 H	
GW 63 015 H	GW 63 047 H	GW 63 215 H	GW 63 248 H	
GW 63 016 H	GW 63 048 H	GW 63 216 H	GW 63 249 H	
	GW 63 048 PH (*)		GW 63 249 PH (*)	
GW 63 017 H	GW 63 049 H	GW 63 217 H	GW 63 250 H	
GW 63 018 H	GW 63 050 H	GW 63 218 H	GW 63 251 H	
GW 63 019 H	GW 63 051 H	GW 63 219 H	GW 63 252 H	
GW 63 020 H	GW 63 052 H	GW 63 220 H	GW 63 253 H	
	GW 63 052 PH (*)		GW 63 253 PH (*)	
GW 63 021 H	GW 63 053 H	GW 63 221 H	GW 63 254 H	
	GW 63 053 PH (*)		GW 63 254 PH (*)	
	GW 63 056 H		GW 63 257 H	Use with particular voltage
	GW 63 054 H		GW 63 255 H	
	GW 63 054 PH (*)		GW 63 255 PH (*)	
	GW 63 055 H		GW 63 256 H	
	GW 63 057 H		GW 63 258 H	
	GW 63 058 H		GW 63 259 H	
	GW 63 058 PH (*)			
	GW 63 059 H		GW 63 260 H	Use with high frequencies
	GW 63 060 H		GW 63 261 H	
	GW 63 061 H		GW 63 262 H	
	GW 63 062 H		GW 63 263 H	
	GW 63 063 H		GW 63 264 H	
	GW 63 064 H		GW 63 265 H	
	GW 63 065 H		GW 63 266 H	Marine, port and naval, installations
	GW 63 066 H		GW 63 267 H	
	GW 63 067 H		GW 63 268 H	Use in direct current
	GW 63 068 H		GW 63 269 H	
	GW 62 664 H		GW 62 965 H	Standard use
	GW 62 056 H		GW 62 257 H	
			GW 62 257 PH (*)	
	GW 62 057 H		GW 62 258 H	
	GW 62 665 H		GW 62 966 H	
	GW 62 058 H		GW 62 259 H	
	GW 62 059 H		GW 62 260 H	
	GW 62 666 H		GW 62 967 H	
	GW 62 060 H		GW 62 261 H	
			GW 62 261 PH (*)	
	GW 62 060 PH (*)		GW 68 785 (**)	
	GW 62 061 H		GW 62 262 H	
			GW 62 262 PH (*)	
	GW 62 061 PH (*)		GW 68 786 (**)	
	GW 62 667 H		GW 62 968 H	Use with particular voltage
	GW 62 062 H		GW 62 263 H	
	GW 62 062 PH (*)		GW 62 263 PH (*)	
	GW 62 063 H		GW 62 264 H	
	GW 62 063 PH (*)		GW 62 264 PH (*)	
	GW 62 668 H		GW 62 969 H	
	GW 62 669 H		GW 62 970 H	
	GW 62 670 H		GW 62 971 H	Use with high frequencies
	GW 62 671 H		GW 62 972 H	
	GW 62 672 H		GW 62 973 H	
	GW 62 673 H		GW 62 974 H	
	GW 62 674 H		GW 62 975 H	
	GW 62 675 H		GW 62 976 H	
	GW 62 676 H		GW 62 977 H	Marine, port and naval, installations
	GW 62 677 H		GW 62 978 H	

IEC 309 HP

16-32-63-125A Low voltage industrial plugs and socket-outlets complying with IEC 309 standard

Rated current (In)	Rated voltage (Un)	Frequency	Poles	Reference h	90° plugs IP44	90° plugs IP67	Straight flush-mounting inlets IP44	Straight flush-mounting inlets IP67
								
					Screw wiring	Screw wiring	Screw wiring	Screw wiring
16 A	100 ÷ 130 V	50/60 Hz	2P+E	4	GW 60 082	GW 60 105	GW 60 201	GW 60 223
			3P+E	4	GW 60 083	GW 60 106	GW 60 202	GW 60 224
			3P+N+E	4	GW 60 084	GW 60 107	GW 60 203	GW 60 225
	200 ÷ 250 V	50/60 Hz	2P+E	6	GW 60 085	GW 60 108	GW 60 204	GW 60 226
			3P+E	9	GW 60 086	GW 60 109	GW 60 205	GW 60 227
			3P+N+E	9	GW 60 087	GW 60 110	GW 60 206	GW 60 228
	380 ÷ 415 V	50/60 Hz	2P+E	9	GW 60 088	GW 60 111	GW 60 207	GW 60 229
			3P+E	6	GW 60 089	GW 60 112	GW 60 208	GW 60 230
			3P+N+E	6	GW 60 090	GW 60 113	GW 60 209	GW 60 231
	480 ÷ 500 V	50/60 Hz	3P+E	7	GW 60 091	GW 60 114	GW 60 210	GW 60 232
			3P+N+E	7	GW 60 092	GW 60 115	GW 60 211	GW 60 233
32 A	100 ÷ 130 V	50/60 Hz	2P+E	4	GW 60 093	GW 60 116	GW 60 212	GW 60 234
			3P+E	4	GW 60 094	GW 60 117	GW 60 213	GW 60 235
			3P+N+E	4	GW 60 095	GW 60 118	GW 60 214	GW 60 236
	200 ÷ 250 V	50/60 Hz	2P+E	6	GW 60 096	GW 60 119	GW 60 215	GW 60 237
			3P+E	9	GW 60 097	GW 60 120	GW 60 216	GW 60 238
			3P+N+E	9	GW 60 098	GW 60 121	GW 60 217	GW 60 239
	380 ÷ 415 V	50/60 Hz	2P+E	9	GW 60 099	GW 60 122	GW 60 218	GW 60 240
			3P+E	6	GW 60 101	GW 60 123	GW 60 219	GW 60 241
			3P+N+E	6	GW 60 102	GW 60 124	GW 60 220	GW 60 242
	480 ÷ 500 V	50/60 Hz	3P+E	7	GW 60 103	GW 60 125	GW 60 221	GW 60 243
			3P+N+E	7	GW 60 104	GW 60 126	GW 60 222	GW 60 244
	380 V / 440 V	50 Hz / 60 Hz	3P+E	3		GW 60 146		GW 60 268
63 A	100 ÷ 130 V	50/60 Hz	2P+E	4				
			3P+E	4				
			3P+N+E	4				
	200 ÷ 250 V	50/60 Hz	2P+E	6				
			3P+E	9				
			3P+N+E	9				
	380 ÷ 415 V	50/60 Hz	2P+E	9				
			3P+E	6				
			3P+N+E	6				
	480 ÷ 500 V	50/60 Hz	3P+E	7				
			3P+N+E	7				
125 A	100 ÷ 130 V	50/60 Hz	3P+E	4				
			3P+N+E	4				
	200 ÷ 250 V	50/60 Hz	3P+E	9				
			3P+N+E	9				
	380 ÷ 415 V	50/60 Hz	3P+E	6				
			3P+N+E	6				
	480 ÷ 500 V	50/60 Hz	3P+E	7				
			3P+N+E	7				

Domestic socket-outlets - IP54



Description	Rated current (In)	Rated voltage (Un)	Poles	Dimensions (mm)	Code
Domestic socket-outlets, German standard - IP54	16 A	230V	2P+E	85x75	GW 62 392
Domestic socket-outlets, German standard - IP54	16 A	230V	2P+E	50x50	GW 62 393
Domestic socket-outlets, French standard - IP54	16 A	230V	2P+E	50x50	GW 62 394

90° surface-mounting inlets IP44	90° surface-mounting inlets IP67	10° surface-mounting socket-outlets IP44	10° surface-mounting socket-outlets IP67	90° surface-mounting socket-outlets IP44	90° surface-mounting socket-outlets IP67	APPLICATIONS
						
Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring	
GW 60 401	GW 60 423	GW 62 401	GW 62 423	GW 62 474	GW 62 496	Standard use
GW 60 402	GW 60 424	GW 62 402	GW 62 424	GW 62 475	GW 62 497	
GW 60 403	GW 60 425	GW 62 403	GW 62 425	GW 62 476	GW 62 498	
GW 60 404	GW 60 426	GW 62 404	GW 62 426	GW 62 477	GW 62 499	
GW 60 405	GW 60 427	GW 62 405	GW 62 427	GW 62 478	GW 62 501	
GW 60 406	GW 60 428	GW 62 406	GW 62 428	GW 62 479	GW 62 502	
GW 60 407	GW 60 429	GW 62 407	GW 62 429	GW 62 480	GW 62 503	
GW 60 408	GW 60 430	GW 62 408	GW 62 430	GW 62 481	GW 62 504	
GW 60 409	GW 60 431	GW 62 409	GW 62 431	GW 62 482	GW 62 505	
GW 60 410	GW 60 432	GW 62 410	GW 62 432	GW 62 483	GW 62 506	Use with particular voltage
GW 60 411	GW 60 433	GW 62 411	GW 62 433	GW 62 484	GW 62 507	
GW 60 412	GW 60 434	GW 62 412	GW 62 434	GW 62 485	GW 62 508	Standard use
GW 60 413	GW 60 435	GW 62 413	GW 62 435	GW 62 486	GW 62 509	
GW 60 414	GW 60 436	GW 62 414	GW 62 436	GW 62 487	GW 62 510	
GW 60 415	GW 60 437	GW 62 415	GW 62 437	GW 62 488	GW 62 511	
GW 60 416	GW 60 438	GW 62 416	GW 62 438	GW 62 489	GW 62 512	
GW 60 417	GW 60 439	GW 62 417	GW 62 439	GW 62 490	GW 62 513	
GW 60 418	GW 60 440	GW 62 418	GW 62 440	GW 62 491	GW 62 514	
GW 60 419	GW 60 441	GW 62 419	GW 62 441	GW 62 492	GW 62 515	
GW 60 420	GW 60 442	GW 62 420	GW 62 442	GW 62 493	GW 62 516	
GW 60 421	GW 60 443	GW 62 421	GW 62 443	GW 62 494	GW 62 517	Use with particular voltage
GW 60 422	GW 60 444	GW 62 422	GW 62 444	GW 62 495	GW 62 518	
	GW 60 482		GW 62 556		GW 62 557	Refrigeretion containers
	GW 61 445		GW 63 445		GW 63 519	Standard use
	GW 61 446		GW 63 446		GW 63 520	
	GW 61 447		GW 63 447		GW 63 521	
	GW 61 448		GW 63 448		GW 63 522	
	GW 61 449		GW 63 449		GW 63 523	
	GW 61 450		GW 63 450		GW 63 524	
	GW 61 451		GW 63 451		GW 63 525	
	GW 61 452		GW 63 452		GW 63 526	
	GW 61 453		GW 63 453		GW 63 527	
	GW 61 454		GW 63 454		GW 63 528	Use with particular voltage
	GW 61 455		GW 63 455		GW 63 529	
	GW 60 456				GW 62 530	Standard use
	GW 60 457				GW 62 531	
	GW 60 458				GW 62 532	
	GW 60 459				GW 62 533	
	GW 60 460				GW 62 534	
	GW 60 461				GW 62 535	
	GW 60 462				GW 62 536	Use with particular voltage
	GW 60 463				GW 62 537	

IEC 309 HP

Plugs and socket-outlets IEC 309 Standard



The IEC 309 HP system comprises plugs and socket-outlets from 16 to 125 A in two different versions – straight mobile and 10° flush-mounting – which have IP44/IP54 and IP66/IP67/IP68/IP69 degrees of protection (IP68/IP69 only available for straight versions). The introduction of all the hours references for the earthing contact completes the range for specific applications and installations. The 16-32 A versions are available with screw wiring or fast wiring with spring terminals, while the 63-125A versions propose indirect wiring with mantle terminals.

IEC 309 HP - LOW VOLTAGE FAST WIRING STRAIGHT PLUGS

IP44/IP54



GW 60 004 FH

Low voltage fast wiring straight plugs - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 001 FH	2P+E	100 - 130 V		50/60 Hz	4	25
GW 60 002 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 003 FH	3P+N+E	100 - 130 V		50/60 Hz	4	50
GW 60 004 FH	2P+E	200 - 250 V		50/60 Hz	6	50
GW 60 005 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 006 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 007 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 008 FH	3P+E	380 - 415 V		50/60 Hz	6	25
GW 60 009 FH	3P+N+E	380 - 415 V		50/60 Hz	6	50
Rated current (A): 32						
GW 60 012 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 60 013 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 014 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 015 FH	2P+E	200 - 250 V		50/60 Hz	6	15
GW 60 016 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 017 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 018 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 019 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 020 FH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
Halogen free according to EN 60754-2.
CHARACTERISTICS: connection technology with spring terminals. Nickel-plated pins.

IP66/IP67/IP68/IP69



GW 60 030 FH

Low voltage fast wiring straight plugs - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 023 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 60 024 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 025 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 026 FH	2P+E	200 - 250 V		50/60 Hz	6	50
GW 60 027 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 028 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 029 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 030 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 031 FH	3P+N+E	380 - 415 V		50/60 Hz	6	25
Rated current (A): 32						
GW 60 034 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 60 035 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 036 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 037 FH	2P+E	200 - 250 V		50/60 Hz	6	15
GW 60 038 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 039 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 040 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 041 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 042 FH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
IP68: 2 bar/6 h in accordance with EN 60529 after ageing according to standard EN 60309.
IP69: in accordance with EN 60529 after ageing according to standard EN 60309.
Halogen-free in compliance with EN 60754-2.
CHARACTERISTICS: connection technology with spring terminals. Nickel-plated plugs.

IEC 309 HP - LOW VOLTAGE SCREW WIRING STRAIGHT PLUGS

IP44/IP54



GW 60 004 H

Low voltage screw wiring straight plugs - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 001 H	2P+E	100 - 130 V		50/60 Hz	4	50
GW 60 002 H	3P+E	100 - 130 V		50/60 Hz	4	50
GW 60 003 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 004 H	2P+E	200 - 250 V		50/60 Hz	6	50
GW 60 005 H	3P+E	200 - 250 V		50/60 Hz	9	25
GW 60 006 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 007 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 008 H	3P+E	380 - 415 V		50/60 Hz	6	50
GW 60 009 H	3P+N+E	380 - 415 V		50/60 Hz	6	50
GW 60 701 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 60 010 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 60 011 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 60 702 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 60 703 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 60 704 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 60 705 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 60 706 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 60 707 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 60 708 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 60 709 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 60 710 H	3P+E	440 - 460 V		60 Hz	11	15
GW 60 711 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 60 712 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 60 713 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 60 714 H	2P+E	transf.		50/60 Hz	12	15
GW 60 715 H	3P+E	transf.		50/60 Hz	12	15
GW 60 716 H	2P+E	>50 - 250 V		d.c.	3	15
GW 60 717 H	2P+E	>250 V		d.c.	8	15
Rated current (A): 32						
GW 60 012 H	2P+E	100 - 130 V		50/60 Hz	4	15
GW 60 013 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 014 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 015 H	2P+E	200 - 250 V		50/60 Hz	6	25
GW 60 016 H	3P+E	200 - 250 V		50/60 Hz	9	50
GW 60 017 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 018 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 019 H	3P+E	380 - 415 V		50/60 Hz	6	50
GW 60 020 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 60 718 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 60 021 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 60 022 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 60 719 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 60 720 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 60 721 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 60 722 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 60 723 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 60 724 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 60 725 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 60 726 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 60 727 H	3P+E	440 - 460 V		60 Hz	11	15
GW 60 728 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 60 729 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 60 730 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 60 731 H	2P+E	transf.		50/60 Hz	12	15
GW 60 732 H	3P+E	transf.		50/60 Hz	12	15
GW 60 733 H	2P+E	>50 - 250 V		d.c.	3	15
GW 60 734 H	2P+E	>250 V		d.c.	8	15

NOTES: all products are packaged individually. Halogen free according to EN 60754-2.

CHARACTERISTICS: nickel-plated pins.

IP66/IP67/IP68/IP69

Low voltage screw wiring straight plugs - High Performance



GW 60 030 H

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 023 H	2P+E	100 - 130 V		50/60 Hz	4	25
GW 60 024 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 025 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 026 H	2P+E	200 - 250 V		50/60 Hz	6	50
GW 60 027 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 028 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 029 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 030 H	3P+E	380 - 415 V		50/60 Hz	6	25
GW 60 031 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 60 735 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 60 032 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 60 033 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 60 736 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 60 737 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 60 738 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 60 739 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 60 740 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 60 741 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 60 742 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 60 743 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 60 744 H	3P+E	440 - 460 V		60 Hz	11	15
GW 60 745 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 60 746 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 60 747 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 60 748 H	2P+E	transf.		50/60 Hz	12	15
GW 60 749 H	3P+E	transf.		50/60 Hz	12	15
GW 60 750 H	2P+E	>50 - 250 V		d.c.	3	15
GW 60 751 H	2P+E	>250 V		d.c.	8	15
Rated current (A): 32						
GW 60 034 H	2P+E	100 - 130 V		50/60 Hz	4	15
GW 60 035 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 60 036 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 60 037 H	2P+E	200 - 250 V		50/60 Hz	6	15
GW 60 038 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 039 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 040 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 60 041 H	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 042 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 60 752 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 60 043 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 60 044 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 60 753 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 60 754 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 60 755 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 60 756 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 60 757 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 60 758 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 60 759 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 60 760 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 60 761 H	3P+E	440 - 460 V		60 Hz	11	15
GW 60 762 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 60 145 H	3P+E	380 - 440 V		50/60 Hz	3	25
GW 60 763 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 60 764 H	2P+E	transf.		50/60 Hz	12	15
GW 60 765 H	3P+E	transf.		50/60 Hz	12	15
GW 60 766 H	2P+E	>50 - 250 V		d.c.	3	15
GW 60 767 H	2P+E	>250 V		d.c.	8	15

NOTES: all products are packaged individually. Halogen-free in compliance with EN 60754-2.
IP68: 2 bar/6 h according EN 60529 after ageing according to standard EN 60309.
IP69: in accordance with EN 60529 after ageing according to standard EN 60309.
CHARACTERISTICS: nickel-plated plugs.

IEC 309 HP

IEC 309 HP - LOW VOLTAGE SCREW WIRING STRAIGHT PLUGS WITH PHASE INVERTERS

IP44/IP54



GW 60 009 WH

Low voltage screw wiring straight plugs with phase inverter - High Performance inverter

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 005 WH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 006 WH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 008 WH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 009 WH	3P+N+E	380 - 415 V		50/60 Hz	6	15
Rated current (A): 32						
GW 60 016 WH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 017 WH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 019 WH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 020 WH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
Halogen free according to EN 60754-2.
CHARACTERISTICS: nickel-plated pins.
allow the fast exchange of two phases by using a screwdriver to reverse the direction of rotation of three-phase motors.

IP66/IP67/IP68/IP69



GW 60 030 WH

Low voltage screw wiring straight plugs with phase inverter - High Performance inverter

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 027 WH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 028 WH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 030 WH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 031 WH	3P+N+E	380 - 415 V		50/60 Hz	6	15
Rated current (A): 32						
GW 60 038 WH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 60 039 WH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 60 041 WH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 60 042 WH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
Halogen-free in compliance with EN 60754-2.
IP68: 2 bar/6 h according EN 60529 after ageing according to standard EN 60309.
IP69: in accordance with EN 60529 after ageing according to standard EN 60309.
CHARACTERISTICS: nickel-plated plugs.
Allow the fast exchange of two phases by using a screwdriver to reverse the direction of rotation of three-phase motors.

IEC 309 HP

IEC 309 HP - LOW VOLTAGE HIGH CURRENT STRAIGHT PLUGS WITH MANTLE CONNECTION

IP44/IP54



GW 61 016 H

Low voltage high current protected straight plugs with mantle terminal - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 61 013 H	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 014 H	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 015 H	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 016 H	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	1/4
GW 61 017 H	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 018 H	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 019 H	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	1/4
GW 61 020 H	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 61 021 H	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	1/4

NOTES: all products are packaged individually.
Halogen free in accordance with Standard EN 60754-2.
CHARACTERISTICS: connection technology with mantle terminals. Nickel-plated plugs.
Versions with pilot contact.

IP66/IP67/IP68/IP69



GW 61 053 H

Low voltage high current watertight straight plugs with mantle terminal - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 61 045 H	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 046 H	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 047 H	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 048 H	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	1/4
GW 61 049 H	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 050 H	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 051 H	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	1/4
GW 61 052 H	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 61 053 H	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 61 056 H	2P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
GW 61 054 H	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
GW 61 055 H	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
GW 61 057 H	3P+E	600 - 690 V		50/60 Hz	5	Pilot contact	1/4
GW 61 058 H	3P+N+E	600 - 690 V		50/60 Hz	5	Pilot contact	1/4
GW 61 059 H	2P+E	>50 V		100 - 300 Hz	10	Pilot contact	1/4
GW 61 060 H	3P+E	>50 V		100 - 300 Hz	10	Pilot contact	1/4
GW 61 061 H	3P+N+E	>50 V		100 - 300 Hz	10	Pilot contact	1/4
GW 61 062 H	2P+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/4
GW 61 063 H	3P+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/4
GW 61 064 H	3P+N+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/4
GW 61 065 H	3P+E	440 - 460 V		60 Hz	11	Pilot contact	1/4
GW 61 066 H	3P+N+E	440 - 460 V		60 Hz	11	Pilot contact	1/4
GW 61 067 H	2P+E	>50 - 250 V		d.c.	3	Pilot contact	1/4
GW 61 068 H	2P+E	>250 V		d.c.	8	Pilot contact	1/4
Rated current (A): 125							
GW 60 664 H	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 60 056 H	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 60 057 H	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 60 665 H	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	1/2
GW 60 058 H	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 60 059 H	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 60 666 H	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	1/2
GW 60 060 H	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 60 061 H	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 60 667 H	2P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 60 062 H	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 60 063 H	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 60 668 H	3P+E	600 - 690 V		50/60 Hz	5	Pilot contact	1/2
GW 60 669 H	3P+N+E	600 - 690 V		50/60 Hz	5	Pilot contact	1/2
GW 60 670 H	2P+E	>50 V		100 - 300 Hz	10	Pilot contact	1/2
GW 60 671 H	3P+E	>50 V		100 - 300 Hz	10	Pilot contact	1/2
GW 60 672 H	3P+N+E	>50 V		100 - 300 Hz	10	Pilot contact	1/2
GW 60 673 H	2P+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/2
GW 60 674 H	3P+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/2
GW 60 675 H	3P+N+E	>50 V		>300 - 500 Hz	2	Pilot contact	1/2
GW 60 676 H	3P+E	440 - 460 V		60 Hz	11	Pilot contact	1/2
GW 60 677 H	3P+N+E	440 - 460 V		60 Hz	11	Pilot contact	1/2

NOTES: all products are packaged individually.

Halogen-free according to EN 60754-2.

IP68:2 bar/ 6 h in accordance with EN 60529 after ageing according to Standard EN 60309.

IP69: in accordance with EN 60529 after ageing according to Standard EN 60309.

CHARACTERISTICS: connection technology with mantle terminals. Nickel-plated plugs.

Versions with pilot contact.

IEC 309 HP

60 - LOW VOLTAGE SCREW WIRING 90°PLUGS

IP44



GW 60 085

Low voltage screw wiring 90° plugs



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 082	2P+E	100 - 130 V		50/60 Hz	4	10/40
GW 60 083	3P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 084	3P+N+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 085	2P+E	200 - 250 V		50/60 Hz	6	10/40
GW 60 086	3P+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 087	3P+N+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 088	2P+E	380 - 415 V		50/60 Hz	9	10/20
GW 60 089	3P+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 090	3P+N+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 091	3P+E	480 - 500 V		50/60 Hz	7	10/20
GW 60 092	3P+N+E	480 - 500 V		50/60 Hz	7	10/20
Rated current (A): 32						
GW 60 093	2P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 094	3P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 095	3P+N+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 096	2P+E	200 - 250 V		50/60 Hz	6	8/16
GW 60 097	3P+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 098	3P+N+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 099	2P+E	380 - 415 V		50/60 Hz	9	8/16
GW 60 101	3P+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 102	3P+N+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 103	3P+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 104	3P+N+E	480 - 500 V		50/60 Hz	7	8/16

CHARACTERISTICS: PG16 cable gland for 16A versions; PG21 cable gland for 32A versions.

IP67



GW 60 112

Low voltage screw wiring 90° plugs



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 105	2P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 106	3P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 107	3P+N+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 108	2P+E	200 - 250 V		50/60 Hz	6	10/40
GW 60 109	3P+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 110	3P+N+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 111	2P+E	380 - 415 V		50/60 Hz	9	10/20
GW 60 112	3P+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 113	3P+N+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 114	3P+E	480 - 500 V		50/60 Hz	7	10/20
GW 60 115	3P+N+E	480 - 500 V		50/60 Hz	7	10/20
Rated current (A): 32						
GW 60 116	2P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 117	3P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 118	3P+N+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 119	2P+E	200 - 250 V		50/60 Hz	6	8/16
GW 60 120	3P+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 121	3P+N+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 122	2P+E	380 - 415 V		50/60 Hz	9	8/16
GW 60 123	3P+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 124	3P+N+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 125	3P+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 126	3P+N+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 146	3P+E	380 - 440 V		50/60 Hz	3	8/16

CHARACTERISTICS: PG16 cable gland for 16A versions; PG21 cable gland for 32A versions.

IEC 309 HP

60 - LOW VOLTAGE SCREW WIRING STRAIGHT FLUSH MOUNTING INLETS

IP44



GW 60 204

Low voltage screw wiring straight flush mounting inlets



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 60 201	2P+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 202	3P+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 203	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 204	2P+E	200 - 250 V		50/60 Hz	6	85x75	10/20
GW 60 205	3P+E	200 - 250 V		50/60 Hz	9	85x75	10/20
GW 60 206	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	10/20
GW 60 207	2P+E	380 - 415 V		50/60 Hz	9	85x75	10/20
GW 60 208	3P+E	380 - 415 V		50/60 Hz	6	85x75	10/20
GW 60 209	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	10/20
GW 60 210	3P+E	480 - 500 V		50/60 Hz	7	85x75	10/20
GW 60 211	3P+N+E	480 - 500 V		50/60 Hz	7	85x75	10/20
Rated current (A): 32							
GW 60 212	2P+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 213	3P+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 214	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 215	2P+E	200 - 250 V		50/60 Hz	6	95x80	8/16
GW 60 216	3P+E	200 - 250 V		50/60 Hz	9	95x80	8/16
GW 60 217	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	8/16
GW 60 218	2P+E	380 - 415 V		50/60 Hz	9	95x80	8/16
GW 60 219	3P+E	380 - 415 V		50/60 Hz	6	95x80	8/16
GW 60 220	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	8/16
GW 60 221	3P+E	480 - 500 V		50/60 Hz	7	95x80	8/16
GW 60 222	3P+N+E	480 - 500 V		50/60 Hz	7	95x80	8/16

IP67



GW 60 231

Low voltage screw wiring straight flush mounting inlets



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 60 223	2P+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 224	3P+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 225	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	10/20
GW 60 226	2P+E	200 - 250 V		50/60 Hz	6	85x75	10/20
GW 60 227	3P+E	200 - 250 V		50/60 Hz	9	85x75	10/20
GW 60 228	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	10/20
GW 60 229	2P+E	380 - 415 V		50/60 Hz	9	85x75	10/20
GW 60 230	3P+E	380 - 415 V		50/60 Hz	6	85x75	10/20
GW 60 231	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	10/20
GW 60 232	3P+E	480 - 500 V		50/60 Hz	7	85x75	10/20
GW 60 233	3P+N+E	480 - 500 V		50/60 Hz	7	85x75	10/20
Rated current (A): 32							
GW 60 234	2P+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 235	3P+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 236	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	8/16
GW 60 237	2P+E	200 - 250 V		50/60 Hz	6	95x80	8/16
GW 60 238	3P+E	200 - 250 V		50/60 Hz	9	95x80	8/16
GW 60 239	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	8/16
GW 60 240	2P+E	380 - 415 V		50/60 Hz	9	95x80	8/16
GW 60 241	3P+E	380 - 415 V		50/60 Hz	6	95x80	8/16
GW 60 242	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	8/16
GW 60 243	3P+E	480 - 500 V		50/60 Hz	7	95x80	8/16
GW 60 244	3P+N+E	480 - 500 V		50/60 Hz	7	95x80	8/16
GW 60 268	3P+E	380 - 440 V		50/60 Hz	3	95x80	8/16

IEC 309 HP

60 - LOW VOLTAGE SCREW WIRING 90° ANGLED SURFACE MOUNTING INLETS

IP44



GW 60 404


Low voltage screw wiring 90° angled surface mounting inlets



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 401	2P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 402	3P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 403	3P+N+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 404	2P+E	200 - 250 V		50/60 Hz	6	10/40
GW 60 405	3P+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 406	3P+N+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 407	2P+E	380 - 415 V		50/60 Hz	9	10/20
GW 60 408	3P+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 409	3P+N+E	380 - 415 V		50/60 Hz	6	10/20
GW 60 410	3P+E	480 - 500 V		50/60 Hz	7	10/20
GW 60 411	3P+N+E	480 - 500 V		50/60 Hz	7	10/20
Rated current (A): 32						
GW 60 412	2P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 413	3P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 414	3P+N+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 415	2P+E	200 - 250 V		50/60 Hz	6	8/16
GW 60 416	3P+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 417	3P+N+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 418	2P+E	380 - 415 V		50/60 Hz	9	8/16
GW 60 419	3P+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 420	3P+N+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 421	3P+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 422	3P+N+E	480 - 500 V		50/60 Hz	7	8/16

CHARACTERISTICS: PG21 cable gland for 16-32A versions.

IP67



GW 60 431

Low voltage screw wiring 90° angled surface mounting inlets



Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 423	2P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 424	3P+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 425	3P+N+E	100 - 130 V		50/60 Hz	4	10/20
GW 60 426	2P+E	200 - 250 V		50/60 Hz	6	10/40
GW 60 427	3P+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 428	3P+N+E	200 - 250 V		50/60 Hz	9	10/20
GW 60 429	2P+E	380 - 415 V		50/60 Hz	9	10/20
GW 60 430	3P+E	380 - 415 V		50/60 Hz	6	10/40
GW 60 431	3P+N+E	380 - 415 V		50/60 Hz	6	10/20
GW 60 432	3P+E	480 - 500 V		50/60 Hz	7	10/20
GW 60 433	3P+N+E	480 - 500 V		50/60 Hz	7	10/20
Rated current (A): 32						
GW 60 434	2P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 435	3P+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 436	3P+N+E	100 - 130 V		50/60 Hz	4	8/16
GW 60 437	2P+E	200 - 250 V		50/60 Hz	6	8/16
GW 60 438	3P+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 439	3P+N+E	200 - 250 V		50/60 Hz	9	8/16
GW 60 440	2P+E	380 - 415 V		50/60 Hz	9	8/16
GW 60 441	3P+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 442	3P+N+E	380 - 415 V		50/60 Hz	6	8/16
GW 60 443	3P+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 444	3P+N+E	480 - 500 V		50/60 Hz	7	8/16
GW 60 482	3P+E	380 - 440 V		50/60 Hz	3	8/16

CHARACTERISTICS: PG21 cable gland for 16-32A versions.

IEC 309 HP

60/61 - 90° SURFACE-MOUNTING FIXED PLUGS WITH LOW VOLTAGE HIGH CURRENT MANTLE CONNECTION

IP67



GW 61 453

Low voltage high current fixed watertight 90° surface-mounting plugs with mantle connection

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 61 445	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 446	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 447	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/4
GW 61 448	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	1/4
GW 61 449	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 450	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/4
GW 61 451	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	1/4
GW 61 452	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 61 453	3P+N+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 61 454	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
GW 61 455	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
Rated current (A): 125							
GW 60 456	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 60 457	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 60 458	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 60 459	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 60 460	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 60 461	3P+N+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 60 462	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 60 463	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2

CHARACTERISTICS: PG36 cable gland for 63A versions; PG48 cable gland for 125A versions. Equipped with pilot contact. Nickel-plated plugs.

ACCESSORIES FOR PLUGS

Watertight



GW 60 263

Watertight covers for plugs

Code	For inlets	Pack Carton
Rated current (A): 16		
GW 60 263	2P+E	10/120
GW 60 264	3P+E	10/120
GW 60 265	3P+N+E	10/80
Rated current (A): 32		
GW 60 266	2P+E and 3P+E	8/64
GW 60 267	3P+N+E	8/64
Rated current (A): 63		
GW 60 269	2P+E; 3P+E; 3P+N+E	5/40
Rated current (A): 125		
GW 60 270	2P+E; 3P+E; 3P+N+E	5/20

APPLICATIONS: used to mantain the original IP degree on IEC 309 HP mobile or fixed (up to IP66/IP67/IP68/IP69).

IEC 309 HP - LOW VOLTAGE FAST WIRING STRAIGHT CONNECTORS

IP44/IP54



GW 62 004 FH

Low voltage fast wiring straight connectors - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 001 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 002 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 003 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 004 FH	2P+E	200 - 250 V		50/60 Hz	6	50
GW 62 005 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 006 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 007 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 008 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 62 009 FH	3P+N+E	380 - 415 V		50/60 Hz	6	15
Rated current (A): 32						
GW 62 012 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 013 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 014 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 015 FH	2P+E	200 - 250 V		50/60 Hz	6	15
GW 62 016 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 017 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 018 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 019 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 62 020 FH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
Halogen free according to EN 60754-2.
CHARACTERISTICS: connection technology with spring terminals. Nickel-plated contacts.

IP66/IP67/IP68/IP69

Low voltage fast wiring straight connectors - High Performance



GW 62 030 FH

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 023 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 024 FH	3P+E	100 - 130 V		50/60 Hz	4	25
GW 62 025 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 026 FH	2P+E	200 - 250 V		50/60 Hz	6	50
GW 62 027 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 028 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 029 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 030 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 62 031 FH	3P+N+E	380 - 415 V		50/60 Hz	6	25
Rated current (A): 32						
GW 62 034 FH	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 035 FH	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 036 FH	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 037 FH	2P+E	200 - 250 V		50/60 Hz	6	15
GW 62 038 FH	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 039 FH	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 040 FH	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 041 FH	3P+E	380 - 415 V		50/60 Hz	6	15
GW 62 042 FH	3P+N+E	380 - 415 V		50/60 Hz	6	15

NOTES: all products are packaged individually.
IP68: 2 bar/6 h according EN 60529 after ageing according to standard EN 60309.
IP69: in accordance with EN 60529 after ageing according to standard EN 60309.
Halogen-free in compliance with EN 60754-2.
CHARACTERISTICS: connection technology with spring terminals. Nickel-plated contacts.

IEC 309 HP - LOW VOLTAGE SCREW WIRING STRAIGHT CONNECTORS

IP44/IP54



GW 62 004 H

Low voltage screw wiring straight connectors - HIGH PERFORMANCE

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 001 H	2P+E	100 - 130 V		50/60 Hz	4	50
GW 62 002 H	3P+E	100 - 130 V		50/60 Hz	4	50
GW 62 003 H	3P+N+E	100 - 130 V		50/60 Hz	4	25
GW 62 004 H	2P+E	200 - 250 V		50/60 Hz	6	50
GW 62 005 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 006 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 007 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 008 H	3P+E	380 - 415 V		50/60 Hz	6	50
GW 62 009 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 62 701 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 62 010 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 62 011 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 62 702 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 62 703 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 62 704 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 62 705 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 62 706 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 62 707 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 62 708 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 62 709 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 62 710 H	3P+E	440 - 460 V		60 Hz	11	15
GW 62 711 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 62 712 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 62 713 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 62 714 H	2P+E	transf.		50/60 Hz	12	15
GW 62 715 H	3P+E	transf.		50/60 Hz	12	15
GW 62 716 H	2P+E	>50 - 250 V		d.c.	3	15
GW 62 717 H	2P+E	>250 V		d.c.	8	15
Rated current (A): 32						
GW 62 012 H	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 013 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 014 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 015 H	2P+E	200 - 250 V		50/60 Hz	6	25
GW 62 016 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 017 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 018 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 019 H	3P+E	380 - 415 V		50/60 Hz	6	25
GW 62 020 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 62 718 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 62 021 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 62 022 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 62 719 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 62 720 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 62 721 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 62 722 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 62 723 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 62 724 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 62 725 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 62 726 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 62 727 H	3P+E	440 - 460 V		60 Hz	11	15
GW 62 728 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 62 729 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 62 730 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 62 731 H	2P+E	transf.		50/60 Hz	12	15
GW 62 732 H	3P+E	transf.		50/60 Hz	12	15
GW 62 733 H	2P+E	>50 - 250 V		d.c.	3	15
GW 62 734 H	2P+E	>250 V		d.c.	8	15

NOTES: all products are packaged individually. Halogen free according to EN 60754-2

CHARACTERISTICS: nickel-plated contacts.

Low voltage screw wiring straight connectors - HIGH PERFORMANCE



GW 62 030 H

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 023 H	2P+E	100 - 130 V		50/60 Hz	4	50
GW 62 024 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 025 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 026 H	2P+E	200 - 250 V		50/60 Hz	6	50
GW 62 027 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 028 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 029 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 030 H	3P+E	380 - 415 V		50/60 Hz	6	25
GW 62 031 H	3P+N+E	380 - 415 V		50/60 Hz	6	25
GW 62 735 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 62 032 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 62 033 H	3P+N+E	480 - 500 V		50/60 Hz	7	25
GW 62 736 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 62 737 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 62 738 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 62 739 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 62 740 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 62 741 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 62 742 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 62 743 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 62 744 H	3P+E	440 - 460 V		60 Hz	11	15
GW 62 745 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 62 746 H	3P+E	380 - 440 V		50/60 Hz	3	15
GW 62 747 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 62 748 H	2P+E	transf.		50/60 Hz	12	15
GW 62 749 H	3P+E	transf.		50/60 Hz	12	15
GW 62 750 H	2P+E	>50 - 250 V		d.c.	3	15
GW 62 751 H	2P+E	>250 V		d.c.	8	15
Rated current (A): 32						
GW 62 034 H	2P+E	100 - 130 V		50/60 Hz	4	15
GW 62 035 H	3P+E	100 - 130 V		50/60 Hz	4	15
GW 62 036 H	3P+N+E	100 - 130 V		50/60 Hz	4	15
GW 62 037 H	2P+E	200 - 250 V		50/60 Hz	6	15
GW 62 038 H	3P+E	200 - 250 V		50/60 Hz	9	15
GW 62 039 H	3P+N+E	200 - 250 V		50/60 Hz	9	15
GW 62 040 H	2P+E	380 - 415 V		50/60 Hz	9	15
GW 62 041 H	3P+E	380 - 415 V		50/60 Hz	6	15
GW 62 042 H	3P+N+E	380 - 415 V		50/60 Hz	6	15
GW 62 752 H	2P+E	480 - 500 V		50/60 Hz	7	15
GW 62 043 H	3P+E	480 - 500 V		50/60 Hz	7	15
GW 62 044 H	3P+N+E	480 - 500 V		50/60 Hz	7	15
GW 62 753 H	3P+E	600 - 690 V		50/60 Hz	5	15
GW 62 754 H	3P+N+E	600 - 690 V		50/60 Hz	5	15
GW 62 755 H	2P+E	>50 V		100 - 300 Hz	10	15
GW 62 756 H	3P+E	>50 V		100 - 300 Hz	10	15
GW 62 757 H	3P+N+E	>50 V		100 - 300 Hz	10	15
GW 62 758 H	2P+E	>50 V		>300 - 500 Hz	2	15
GW 62 759 H	3P+E	>50 V		>300 - 500 Hz	2	15
GW 62 760 H	3P+N+E	>50 V		>300 - 500 Hz	2	15
GW 62 761 H	3P+E	440 - 460 V		60 Hz	11	15
GW 62 762 H	3P+N+E	440 - 460 V		60 Hz	11	15
GW 62 128 H	3P+E	380 - 440 V		50/60 Hz	3	25
GW 62 763 H	3P+N+E	380 - 440 V		50/60 Hz	3	15
GW 62 764 H	2P+E	transf.		50/60 Hz	12	15
GW 62 765 H	3P+E	transf.		50/60 Hz	12	15
GW 62 766 H	2P+E	>50 - 250 V		d.c.	3	15
GW 62 767 H	2P+E	>250 V		d.c.	8	15

NOTES: all products are packaged individually. Halogen-free in compliance with EN 60754-2.
IP68: 2 bar/6 h according EN 60529 after ageing according to standard EN 60309.
IP69: in accordance with EN 60529 after ageing according to standard EN 60309.
CHARACTERISTICS: nickel-plated contacts.

IEC 309 HP

IEC 309 HP - LOW VOLTAGE HIGH CURRENT STRAIGHT CONNECTORS WITH MANTLE CONNECTION

IP44/IP54



GW 63 016 H

Low voltage high current straight connectors with mantle terminal - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 63						
GW 63 013 H	2P+E	100 - 130 V		50/60 Hz	4	1/4
GW 63 014 H	3P+E	100 - 130 V		50/60 Hz	4	1/4
GW 63 015 H	3P+N+E	100 - 130 V		50/60 Hz	4	1/4
GW 63 016 H	2P+E	200 - 250 V		50/60 Hz	6	1/4
GW 63 017 H	3P+E	200 - 250 V		50/60 Hz	9	1/4
GW 63 018 H	3P+N+E	200 - 250 V		50/60 Hz	9	1/4
GW 63 019 H	2P+E	380 - 415 V		50/60 Hz	9	1/4
GW 63 020 H	3P+E	380 - 415 V		50/60 Hz	6	1/4
GW 63 021 H	3P+N+E	346 - 415 V		50/60 Hz	6	1/4

NOTES: all products are packaged individually.
Halogen free in accordance with Standard EN 60754-2.
CHARACTERISTICS: connection technology with mantle terminals. nickel-plated contacts.
All the versions are available with a pilot contact upon request.

IP66/IP67/IP68/IP69

Low voltage high current watertight straight connectors with mantle terminal - High Performance



GW 63 053 H

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 63 045 H	2P+E	100 - 130 V		50/60 Hz	4	-	1/4
GW 63 046 H	3P+E	100 - 130 V		50/60 Hz	4	-	1/4
GW 63 047 H	3P+N+E	100 - 130 V		50/60 Hz	4	-	1/4
GW 63 048 H	2P+E	200 - 250 V		50/60 Hz	6	-	1/4
GW 63 048 PH	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	1/4
GW 63 049 H	3P+E	200 - 250 V		50/60 Hz	9	-	1/4
GW 63 050 H	3P+N+E	200 - 250 V		50/60 Hz	9	-	1/4
GW 63 051 H	2P+E	380 - 415 V		50/60 Hz	9	-	1/4
GW 63 052 H	3P+E	380 - 415 V		50/60 Hz	6	-	1/4
GW 63 052 PH	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 63 053 H	3P+N+E	346 - 415 V		50/60 Hz	6	-	1/4
GW 63 053 PH	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	1/4
GW 63 056 H	2P+E	480 - 500 V		50/60 Hz	7	-	1/4
GW 63 054 H	3P+E	480 - 500 V		50/60 Hz	7	-	1/4
GW 63 054 PH	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/4
GW 63 055 H	3P+N+E	480 - 500 V		50/60 Hz	7	-	1/4
GW 63 057 H	3P+E	600 - 690 V		50/60 Hz	5	-	1/4
GW 63 058 H	3P+N+E	600 - 690 V		50/60 Hz	5	-	1/4
GW 63 058 PH	3P+N+E	600 - 690 V		50/60 Hz	5	Pilot contact	1/4
GW 63 059 H	2P+E	>50 V		100 - 300 Hz	10	-	1/4
GW 63 060 H	3P+E	>50 V		100 - 300 Hz	10	-	1/4
GW 63 061 H	3P+N+E	>50 V		100 - 300 Hz	10	-	1/4
GW 63 062 H	2P+E	>50 V		>300 - 500 Hz	2	-	1/4
GW 63 063 H	3P+E	>50 V		>300 - 500 Hz	2	-	1/4
GW 63 064 H	3P+N+E	>50 V		>300 - 500 Hz	2	-	1/4
GW 63 065 H	3P+E	440 - 460 V		60 Hz	11	-	1/4
GW 63 066 H	3P+N+E	440 - 460 V		60 Hz	11	-	1/4
GW 63 067 H	2P+E	>50 - 250 V		d.c.	3	-	1/4
GW 63 068 H	2P+E	>250 V		d.c.	8	-	1/4
Rated current (A): 125							
GW 62 664 H	2P+E	100 - 130 V		50/60 Hz	4	-	1/2
GW 62 056 H	3P+E	100 - 130 V		50/60 Hz	4	-	1/2
GW 62 057 H	3P+N+E	100 - 130 V		50/60 Hz	4	-	1/2
GW 62 665 H	2P+E	200 - 250 V		50/60 Hz	6	-	1/2
GW 62 058 H	3P+E	200 - 250 V		50/60 Hz	9	-	1/2
GW 62 059 H	3P+N+E	200 - 250 V		50/60 Hz	9	-	1/2
GW 62 666 H	2P+E	380 - 415 V		50/60 Hz	9	-	1/2
GW 62 060 H	3P+E	380 - 415 V		50/60 Hz	6	-	1/2
GW 62 060 PH	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 62 061 H	3P+N+E	346 - 415 V		50/60 Hz	6	-	1/2
GW 62 061 PH	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 62 667 H	2P+E	480 - 500 V		50/60 Hz	7	-	1/2
GW 62 062 H	3P+E	480 - 500 V		50/60 Hz	7	-	1/2
GW 62 062 PH	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 62 063 H	3P+N+E	480 - 500 V		50/60 Hz	7	-	1/2
GW 62 063 PH	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 62 668 H	3P+E	600 - 690 V		50/60 Hz	5	-	1/2
GW 62 669 H	3P+N+E	600 - 690 V		50/60 Hz	5	-	1/2
GW 62 670 H	2P+E	>50 V		100 - 300 Hz	10	-	1/2
GW 62 671 H	3P+E	>50 V		100 - 300 Hz	10	-	1/2
GW 62 672 H	3P+N+E	>50 V		100 - 300 Hz	10	-	1/2
GW 62 673 H	2P+E	>50 V		>300 - 500 Hz	2	-	1/2
GW 62 674 H	3P+E	>50 V		>300 - 500 Hz	2	-	1/2
GW 62 675 H	3P+N+E	>50 V		>300 - 500 Hz	2	-	1/2
GW 62 676 H	3P+E	440 - 460 V		60 Hz	11	-	1/2
GW 62 677 H	3P+N+E	440 - 460 V		60 Hz	11	-	1/2

NOTES: all products are packaged individually. Halogen-free according to EN 60754-2.

IP68: 2 bar/ 6 h in accordance with EN60529 after ageing according to Standard EN60309.

IP69: in accordance with EN60529 after ageing according to Standard EN60309.

GW63048PH, GW63052PH, GW63053PH, GW63054PH, GW63058PH, GW62060PH, GW62061PH, GW62062PH, GW62063PH: connectors with pilot contact and direct screw wiring.

CHARACTERISTICS: connection technology with mantle terminals. nickel-plated contacts.

All the versions are available with a pilot contact upon request.

NEWS

IEC 309 HP

IEC 309 HP - LOW VOLTAGE FAST WIRING 10° ANGLED FLUSH-MOUNTING SOCKET-OUTLETS

IP44/IP54



GW 62 205 FH

Low voltage fast wiring 10° angled flush-mounting socket-outlets - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 201 FH	2P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 202 FH	3P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 203 FH	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 205 FH	2P+E	200 - 250 V		50/60 Hz	6	85x75	25
GW 62 206 FH	3P+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 207 FH	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 208 FH	2P+E	380 - 415 V		50/60 Hz	9	85x75	15
GW 62 209 FH	3P+E	380 - 415 V		50/60 Hz	6	85x75	15
GW 62 210 FH	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	15
Rated current (A): 32							
GW 62 213 FH	2P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 214 FH	3P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 215 FH	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 216 FH	2P+E	200 - 250 V		50/60 Hz	6	95x80	15
GW 62 217 FH	3P+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 218 FH	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 219 FH	2P+E	380 - 415 V		50/60 Hz	9	95x80	15
GW 62 220 FH	3P+E	380 - 415 V		50/60 Hz	6	95x80	15
GW 62 221 FH	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	15

NOTES: all products are packaged individually.
Halogen free according to EN 60754-2.
CHARACTERISTICS. connection technology with spring terminals. Nickel-plated contacts.

IP66/IP67



GW 62 231 FH

Low voltage fast wiring 10° angled flush-mounting socket-outlets - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 224 FH	2P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 225 FH	3P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 226 FH	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 227 FH	2P+E	200 - 250 V		50/60 Hz	6	85x75	25
GW 62 228 FH	3P+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 229 FH	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 230 FH	2P+E	380 - 415 V		50/60 Hz	9	85x75	15
GW 62 231 FH	3P+E	380 - 415 V		50/60 Hz	6	85x75	15
GW 62 232 FH	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	15
Rated current (A): 32							
GW 62 235 FH	2P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 236 FH	3P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 237 FH	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 238 FH	2P+E	200 - 250 V		50/60 Hz	6	95x80	15
GW 62 239 FH	3P+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 240 FH	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 241 FH	2P+E	380 - 415 V		50/60 Hz	9	95x80	15
GW 62 242 FH	3P+E	380 - 415 V		50/60 Hz	6	95x80	15
GW 62 243 FH	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	15

NOTES: all products are packaged individually.
Halogen free according to EN 60754-2.
CHARACTERISTICS: connection technology with spring terminals. Nickel-plated contacts.

IEC 309 HP

IEC 309 HP - LOW VOLTAGE SCREW WIRING 10° ANGLED FLUSH-MOUNTING SOCKET-OUTLETS

IP44/IP54



GW 62 205 H

Low voltage screw wiring 10° angled flush-mounting socket-outlets - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 201 H	2P+E	100 - 130 V		50/60 Hz	4	85x75	50
GW 62 202 H	3P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 203 H	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 205 H	2P+E	200 - 250 V		50/60 Hz	6	85x75	50
GW 62 206 H	3P+E	200 - 250 V		50/60 Hz	9	85x75	25
GW 62 207 H	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 208 H	2P+E	380 - 415 V		50/60 Hz	9	85x75	15
GW 62 209 H	3P+E	380 - 415 V		50/60 Hz	6	85x75	50
GW 62 210 H	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	50
GW 62 801 H	2P+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 211 H	3P+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 212 H	3P+N+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 802 H	3P+E	600 - 690 V		50/60 Hz	5	85x75	15
GW 62 803 H	3P+N+E	600 - 690 V		50/60 Hz	5	85x75	15
GW 62 804 H	2P+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 805 H	3P+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 806 H	3P+N+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 807 H	2P+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 808 H	3P+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 809 H	3P+N+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 810 H	3P+E	440 - 460 V		60 Hz	11	85x75	15
GW 62 811 H	3P+N+E	440 - 460 V		60 Hz	11	85x75	15
GW 62 812 H	3P+E	380 - 440 V		50/60 Hz	3	85x75	15
GW 62 813 H	3P+N+E	380 - 440 V		50/60 Hz	3	85x75	15
GW 62 814 H	2P+E	transf.		50/60 Hz	12	85x75	15
GW 62 815 H	3P+E	transf.		50/60 Hz	12	85x75	15
GW 62 816 H	2P+E	>50 - 250 V		d.c.	3	85x75	15
GW 62 817 H	2P+E	>250 V		d.c.	8	85x75	15
Rated current (A): 32							
GW 62 213 H	2P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 214 H	3P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 215 H	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 216 H	2P+E	200 - 250 V		50/60 Hz	6	95x80	25
GW 62 217 H	3P+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 218 H	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 219 H	2P+E	380 - 415 V		50/60 Hz	9	95x80	15
GW 62 220 H	3P+E	380 - 415 V		50/60 Hz	6	95x80	15
GW 62 221 H	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	25
GW 62 818 H	2P+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 222 H	3P+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 223 H	3P+N+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 819 H	3P+E	600 - 690 V		50/60 Hz	5	95x80	15
GW 62 820 H	3P+N+E	600 - 690 V		50/60 Hz	5	95x80	15
GW 62 821 H	2P+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 822 H	3P+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 823 H	3P+N+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 824 H	2P+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 825 H	3P+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 826 H	3P+N+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 827 H	3P+E	440 - 460 V		60 Hz	11	95x80	15
GW 62 828 H	3P+N+E	440 - 460 V		60 Hz	11	95x80	15
GW 62 829 H	3P+E	380 - 440 V		50/60 Hz	3	95x80	15
GW 62 830 H	3P+N+E	380 - 440 V		50/60 Hz	3	95x80	15
GW 62 831 H	2P+E	transf.		50/60 Hz	12	95x80	15
GW 62 832 H	3P+E	transf.		50/60 Hz	12	95x80	15
GW 62 833 H	2P+E	>50 - 250 V		d.c.	3	95x80	15
GW 62 834 H	2P+E	>250 V		d.c.	8	95x80	15

NOTES: all products are packaged individually. Halogen free according to EN 60754-2

CHARACTERISTICS: nickel-plated contacts.

IP66/IP67



GW 62 231 H

Low voltage screw wiring 10° angled flush-mounting socket-outlets - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 224 H	2P+E	100 - 130 V		50/60 Hz	4	85x75	25
GW 62 225 H	3P+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 226 H	3P+N+E	100 - 130 V		50/60 Hz	4	85x75	15
GW 62 227 H	2P+E	200 - 250 V		50/60 Hz	6	85x75	50
GW 62 228 H	3P+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 229 H	3P+N+E	200 - 250 V		50/60 Hz	9	85x75	15
GW 62 230 H	2P+E	380 - 415 V		50/60 Hz	9	85x75	15
GW 62 231 H	3P+E	380 - 415 V		50/60 Hz	6	85x75	25
GW 62 232 H	3P+N+E	380 - 415 V		50/60 Hz	6	85x75	25
GW 62 835 H	2P+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 233 H	3P+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 234 H	3P+N+E	480 - 500 V		50/60 Hz	7	85x75	15
GW 62 836 H	3P+E	600 - 690 V		50/60 Hz	5	85x75	15
GW 62 837 H	3P+N+E	600 - 690 V		50/60 Hz	5	85x75	15
GW 62 838 H	2P+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 839 H	3P+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 840 H	3P+N+E	>50 V		100 - 300 Hz	10	85x75	15
GW 62 841 H	2P+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 842 H	3P+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 843 H	3P+N+E	>50 V		>300 - 500 Hz	2	85x75	15
GW 62 844 H	3P+E	440 - 460 V		60 Hz	11	85x75	15
GW 62 845 H	3P+N+E	440 - 460 V		60 Hz	11	85x75	15
GW 62 846 H	3P+E	380 - 440 V		50/60 Hz	3	85x75	15
GW 62 847 H	3P+N+E	380 - 440 V		50/60 Hz	3	85x75	15
GW 62 848 H	2P+E	transf.		50/60 Hz	12	85x75	15
GW 62 849 H	3P+E	transf.		50/60 Hz	12	85x75	15
GW 62 850 H	2P+E	>50 - 250 V		d.c.	3	85x75	15
GW 62 851 H	2P+E	>250 V		d.c.	8	85x75	15
Rated current (A): 32							
GW 62 235 H	2P+E	100 - 130 V		50/60 Hz	4	95x80	25
GW 62 236 H	3P+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 237 H	3P+N+E	100 - 130 V		50/60 Hz	4	95x80	15
GW 62 238 H	2P+E	200 - 250 V		50/60 Hz	6	95x80	15
GW 62 239 H	3P+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 240 H	3P+N+E	200 - 250 V		50/60 Hz	9	95x80	15
GW 62 241 H	2P+E	380 - 415 V		50/60 Hz	9	95x80	15
GW 62 242 H	3P+E	380 - 415 V		50/60 Hz	6	95x80	15
GW 62 243 H	3P+N+E	380 - 415 V		50/60 Hz	6	95x80	15
GW 62 852 H	2P+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 244 H	3P+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 245 H	3P+N+E	480 - 500 V		50/60 Hz	7	95x80	15
GW 62 853 H	3P+E	600 - 690 V		50/60 Hz	5	95x80	15
GW 62 854 H	3P+N+E	600 - 690 V		50/60 Hz	5	95x80	15
GW 62 855 H	2P+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 856 H	3P+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 857 H	3P+N+E	>50 V		100 - 300 Hz	10	95x80	15
GW 62 858 H	2P+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 859 H	3P+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 860 H	3P+N+E	>50 V		>300 - 500 Hz	2	95x80	15
GW 62 861 H	3P+E	440 - 460 V		60 Hz	11	95x80	15
GW 62 862 H	3P+N+E	440 - 460 V		60 Hz	11	95x80	15
GW 62 283 H	3P+E	380 - 440 V		50/60 Hz	3	95x80	25
GW 62 863 H	3P+N+E	380 - 440 V		50/60 Hz	3	95x80	15
GW 62 864 H	2P+E	transf.		50/60 Hz	12	95x80	15
GW 62 865 H	3P+E	transf.		50/60 Hz	12	95x80	15
GW 62 866 H	2P+E	>50 - 250 V		d.c.	3	95x80	15
GW 62 867 H	2P+E	>250 V		d.c.	8	95x80	15

NOTES: all products are packaged individually. Halogen free according to EN 60754-2
CHARACTERISTICS: nickel-plated contacts

IEC 309 HP

IEC 309 HP - LOW VOLTAGE HIGH CURRENT 10° STRAIGHT FLUSH-MOUNTING FIXED SOCKET-OUTLETS WITH MANTLE CONNECTION

IP44/IP54



GW 63 216 H

Low voltage high current protected flush-mounting 10° socket-outlets with mantle terminal - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 63							
GW 63 213 H	2P+E	100 - 130 V		50/60 Hz	4	110x100	1/4
GW 63 214 H	3P+E	100 - 130 V		50/60 Hz	4	110x100	1/4
GW 63 215 H	3P+N+E	100 - 130 V		50/60 Hz	4	110x100	1/4
GW 63 216 H	2P+E	200 - 250 V		50/60 Hz	6	110x100	1/4
GW 63 217 H	3P+E	200 - 250 V		50/60 Hz	9	110x100	1/4
GW 63 218 H	3P+N+E	200 - 250 V		50/60 Hz	9	110x100	1/4
GW 63 219 H	2P+E	380 - 415 V		50/60 Hz	9	110x100	1/4
GW 63 220 H	3P+E	380 - 415 V		50/60 Hz	6	110x100	1/4
GW 63 221 H	3P+N+E	346 - 415 V		50/60 Hz	6	110x100	1/4

NOTES: all products are packaged individually.
Halogen free in accordance with Standard EN 60754-2.
CHARACTERISTICS: connection technology with mantle terminals. nickel-plated contacts.
All the versions are available with a pilot contact upon request.



GW 63 254 H

Low voltage high current watertight 10° fixed flush-mounting socket-outlets with mantle terminal - High Performance

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h		Flange dimensions (mm)	Pack Carton
Rated current (A): 63								
GW 63 246 H	2P+E	100 - 130 V		50/60 Hz	4	-	110x100	1/4
GW 63 247 H	3P+E	100 - 130 V		50/60 Hz	4	-	110x100	1/4
GW 63 248 H	3P+N+E	100 - 130 V		50/60 Hz	4	-	110x100	1/4
GW 63 249 H	2P+E	200 - 250 V		50/60 Hz	6	-	110x100	1/4
GW 63 249 PH	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	110x100	1/4
GW 63 250 H	3P+E	200 - 250 V		50/60 Hz	9	-	110x100	1/4
GW 63 251 H	3P+N+E	200 - 250 V		50/60 Hz	9	-	110x100	1/4
GW 63 252 H	2P+E	380 - 415 V		50/60 Hz	9	-	110x100	1/4
GW 63 253 H	3P+E	380 - 415 V		50/60 Hz	6	-	110x100	1/4
GW 63 253 PH	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	110x100	1/4
GW 63 254 H	3P+N+E	346 - 415 V		50/60 Hz	6	-	110x100	1/4
GW 63 254 PH	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	110x100	1/4
GW 63 257 H	2P+E	480 - 500 V		50/60 Hz	7	-	110x100	1/4
GW 63 255 H	3P+E	480 - 500 V		50/60 Hz	7	-	110x100	1/4
GW 63 255 PH	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	110x100	1/4
GW 63 256 H	3P+N+E	480 - 500 V		50/60 Hz	7	-	110x100	1/4
GW 63 258 H	3P+E	600 - 690 V		50/60 Hz	5	-	110x100	1/4
GW 63 259 H	3P+N+E	600 - 690 V		50/60 Hz	5	-	110x100	1/4
GW 63 260 H	2P+E	>50 V		100 - 300 Hz	10	-	110x100	1/4
GW 63 261 H	3P+E	>50 V		100 - 300 Hz	10	-	110x100	1/4
GW 63 262 H	3P+N+E	>50 V		100 - 300 Hz	10	-	110x100	1/4
GW 63 263 H	2P+E	>50 V		>300 - 500 Hz	2	-	110x100	1/4
GW 63 264 H	3P+E	>50 V		>300 - 500 Hz	2	-	110x100	1/4
GW 63 265 H	3P+N+E	>50 V		>300 - 500 Hz	2	-	110x100	1/4
GW 63 266 H	3P+E	440 - 460 V		60 Hz	11	-	110x100	1/4
GW 63 267 H	3P+N+E	440 - 460 V		60 Hz	11	-	110x100	1/4
GW 63 268 H	2P+E	>50 - 250 V		d.c.	3	-	110x100	1/4
GW 63 269 H	2P+E	>250 V		d.c.	8	-	110x100	1/4
Rated current (A): 125								
GW 62 965 H	2P+E	100 - 130 V		50/60 Hz	4	-	114x114	1/2
GW 62 257 H	3P+E	100 - 130 V		50/60 Hz	4	-	114x114	1/2
GW 62 257 PH	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	114x114	1/2
GW 62 258 H	3P+N+E	100 - 130 V		50/60 Hz	4	-	114x114	1/2
GW 62 966 H	2P+E	200 - 250 V		50/60 Hz	6	-	114x114	1/2
GW 62 259 H	3P+E	200 - 250 V		50/60 Hz	9	-	114x114	1/2
GW 62 260 H	3P+N+E	200 - 250 V		50/60 Hz	9	-	114x114	1/2
GW 62 967 H	2P+E	380 - 415 V		50/60 Hz	9	-	114x114	1/2
GW 62 261 H	3P+E	380 - 415 V		50/60 Hz	6	-	114x114	1/2
GW 62 261 PH	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	114x114	1/2
GW 62 262 H	3P+N+E	346 - 415 V		50/60 Hz	6	-	114x114	1/2
GW 62 262 PH	3P+N+E	346 - 415 V		50/60 Hz	6	Pilot contact	114x114	1/2
GW 62 968 H	2P+E	480 - 500 V		50/60 Hz	7	-	114x114	1/2
GW 62 263 H	3P+E	480 - 500 V		50/60 Hz	7	-	114x114	1/2
GW 62 263 PH	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	114x114	1/2
GW 62 264 H	3P+N+E	480 - 500 V		50/60 Hz	7	-	114x114	1/2
GW 62 264 PH	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	114x114	1/2
GW 62 969 H	3P+E	600 - 690 V		50/60 Hz	5	-	114x114	1/2
GW 62 970 H	3P+N+E	600 - 690 V		50/60 Hz	5	-	114x114	1/2
GW 62 971 H	2P+E	>50 V		100 - 300 Hz	10	-	114x114	1/2
GW 62 972 H	3P+E	>50 V		100 - 300 Hz	10	-	114x114	1/2
GW 62 973 H	3P+N+E	>50 V		100 - 300 Hz	10	-	114x114	1/2
GW 62 974 H	2P+E	>50 V		>300 - 500 Hz	2	-	114x114	1/2
GW 62 975 H	3P+E	>50 V		>300 - 500 Hz	2	-	114x114	1/2
GW 62 976 H	3P+N+E	>50 V		>300 - 500 Hz	2	-	114x114	1/2
GW 62 977 H	3P+E	440 - 460 V		60 Hz	11	-	114x114	1/2
GW 62 978 H	3P+N+E	440 - 460 V		60 Hz	11	-	114x114	1/2

NOTES: all products are packaged individually. Halogen-free according to EN 60754-2.

GW63249PH, GW63253PH, GW63254PH, GW63255PH, GW62257PH, GW62261PH, GW62262PH, GW62263PH, GW62264PH: socket-outlets with pilot contact and direct screw wiring.

CHARACTERISTICS: connection technology with mantle terminals. nickel-plated contacts. All the versions are available with a pilot contact upon request.

NEWS

IEC 309 HP

Flush-mounting socket-outlets with clean contact - 125 A - IP67



GW 68 785

Low voltage screw wiring 10° angled flush-mounting interlocked socket-outlets 125A

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
GW 68 785	3P+E	380 - 415 V		50/60 Hz	6	114x114	1
GW 68 786	3P+N+E	380 - 415 V		50/60 Hz	6	114x114	1

CHARACTERISTICS: the socket-outlets are equipped with a NO contact (mechanically activated by the plug pilot) to allow the creation of the electric interlock circuit. nickel-plated contacts.

62 - LOW VOLTAGE SCREW WIRING 10° ANGLED SURFACE-MOUNTING SOCKET-OUTLETS

IP44



GW 62 404

Low voltage screw wiring 10° angled surface-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 401	2P+E	100 - 130 V		50/60 Hz	4	40
GW 62 402	3P+E	100 - 130 V		50/60 Hz	4	20
GW 62 403	3P+N+E	100 - 130 V		50/60 Hz	4	20
GW 62 404	2P+E	200 - 250 V		50/60 Hz	6	40
GW 62 405	3P+E	200 - 250 V		50/60 Hz	9	20
GW 62 406	3P+N+E	200 - 250 V		50/60 Hz	9	20
GW 62 407	2P+E	380 - 415 V		50/60 Hz	9	20
GW 62 408	3P+E	380 - 415 V		50/60 Hz	6	40
GW 62 409	3P+N+E	380 - 415 V		50/60 Hz	6	40
GW 62 410	3P+E	480 - 500 V		50/60 Hz	7	20
GW 62 411	3P+N+E	480 - 500 V		50/60 Hz	7	20
Rated current (A): 32						
GW 62 412	2P+E	100 - 130 V		50/60 Hz	4	16
GW 62 413	3P+E	100 - 130 V		50/60 Hz	4	16
GW 62 414	3P+N+E	100 - 130 V		50/60 Hz	4	16
GW 62 415	2P+E	200 - 250 V		50/60 Hz	6	16
GW 62 416	3P+E	200 - 250 V		50/60 Hz	9	16
GW 62 417	3P+N+E	200 - 250 V		50/60 Hz	9	16
GW 62 418	2P+E	380 - 415 V		50/60 Hz	9	16
GW 62 419	3P+E	380 - 415 V		50/60 Hz	6	16
GW 62 420	3P+N+E	380 - 415 V		50/60 Hz	6	16
GW 62 421	3P+E	480 - 500 V		50/60 Hz	7	14
GW 62 422	3P+N+E	480 - 500 V		50/60 Hz	7	14

CHARACTERISTICS: nickel-plated contacts. Ø 29 mm cable gland.

NOTE: all products are packaged individually.

IP67

Low voltage screw wiring 10° angled surface-mounting socket-outlets



GW 62 430

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 423	2P+E	100 - 130 V		50/60 Hz	4	20
GW 62 424	3P+E	100 - 130 V		50/60 Hz	4	20
GW 62 425	3P+N+E	100 - 130 V		50/60 Hz	4	20
GW 62 426	2P+E	200 - 250 V		50/60 Hz	6	40
GW 62 427	3P+E	200 - 250 V		50/60 Hz	9	20
GW 62 428	3P+N+E	200 - 250 V		50/60 Hz	9	20
GW 62 429	2P+E	380 - 415 V		50/60 Hz	9	20
GW 62 430	3P+E	380 - 415 V		50/60 Hz	6	40
GW 62 431	3P+N+E	380 - 415 V		50/60 Hz	6	40
GW 62 432	3P+E	480 - 500 V		50/60 Hz	7	20
GW 62 433	3P+N+E	480 - 500 V		50/60 Hz	7	20
Rated current (A): 32						
GW 62 434	2P+E	100 - 130 V		50/60 Hz	4	16
GW 62 435	3P+E	100 - 130 V		50/60 Hz	4	16
GW 62 436	3P+N+E	100 - 130 V		50/60 Hz	4	16
GW 62 437	2P+E	200 - 250 V		50/60 Hz	6	16
GW 62 438	3P+E	200 - 250 V		50/60 Hz	9	16
GW 62 439	3P+N+E	200 - 250 V		50/60 Hz	9	16
GW 62 440	2P+E	380 - 415 V		50/60 Hz	9	16
GW 62 441	3P+E	380 - 415 V		50/60 Hz	6	16
GW 62 442	3P+N+E	380 - 415 V		50/60 Hz	6	16
GW 62 443	3P+E	480 - 500 V		50/60 Hz	7	14
GW 62 444	3P+N+E	480 - 500 V		50/60 Hz	7	14
GW 62 556	3P+E	380 - 440 V		50/60 Hz	3	16

CHARACTERISTICS: PG21 cable gland. Nickel-plated contacts.
NOTE: all products are packaged individually.

63 - LOW VOLTAGE SCREW WIRING 10° ANGLED SURFACE-MOUNTING SOCKET-OUTLETS

IP67

Low voltage screw wiring 10° angled surface-mounting socket-outlets for high currents



GW 63 453

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 63 445	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 446	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 447	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 448	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	2/4
GW 63 449	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	2/4
GW 63 450	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	2/4
GW 63 451	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	2/4
GW 63 452	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	2/4
GW 63 453	3P+N+E	380 - 415 V		50/60 Hz	6	Pilot contact	2/4
GW 63 454	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	2/4
GW 63 455	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	2/4

CHARACTERISTICS: cable gland PG36. Equipped with pilot contact. nickel-plated contacts.
NOTE: all products are packaged individually.

IEC 309 HP

62 - LOW VOLTAGE SCREW WIRING 90° ANGLED SURFACE-MOUNTING SOCKET-OUTLETS

IP44



GW 62 481

Low voltage screw wiring 90° angled surface-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 474	2P+E	100 - 130 V		50/60 Hz	4	20
GW 62 475	3P+E	100 - 130 V		50/60 Hz	4	20
GW 62 476	3P+N+E	100 - 130 V		50/60 Hz	4	20
GW 62 477	2P+E	200 - 250 V		50/60 Hz	6	20
GW 62 478	3P+E	200 - 250 V		50/60 Hz	9	20
GW 62 479	3P+N+E	200 - 250 V		50/60 Hz	9	20
GW 62 480	2P+E	380 - 415 V		50/60 Hz	9	20
GW 62 481	3P+E	380 - 415 V		50/60 Hz	6	20
GW 62 482	3P+N+E	380 - 415 V		50/60 Hz	6	20
GW 62 483	3P+E	480 - 500 V		50/60 Hz	7	20
GW 62 484	3P+N+E	480 - 500 V		50/60 Hz	7	20
Rated current (A): 32						
GW 62 485	2P+E	100 - 130 V		50/60 Hz	4	16
GW 62 486	3P+E	100 - 130 V		50/60 Hz	4	16
GW 62 487	3P+N+E	100 - 130 V		50/60 Hz	4	16
GW 62 488	2P+E	200 - 250 V		50/60 Hz	6	16
GW 62 489	3P+E	200 - 250 V		50/60 Hz	9	16
GW 62 490	3P+N+E	200 - 250 V		50/60 Hz	9	16
GW 62 491	2P+E	380 - 415 V		50/60 Hz	9	16
GW 62 492	3P+E	380 - 415 V		50/60 Hz	6	16
GW 62 493	3P+N+E	380 - 415 V		50/60 Hz	6	16
GW 62 494	3P+E	480 - 500 V		50/60 Hz	7	16
GW 62 495	3P+N+E	480 - 500 V		50/60 Hz	7	16

CHARACTERISTICS: Ø 20 mm cable gland for 16 A versions; Ø 23 mm cable gland for 32 A versions. nickel-plated contacts.
NOTE: all products are packaged individually.

IP67



GW 62 499

Low voltage screw wiring 90° angled surface-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 496	2P+E	100 - 130 V		50/60 Hz	4	20
GW 62 497	3P+E	100 - 130 V		50/60 Hz	4	20
GW 62 498	3P+N+E	100 - 130 V		50/60 Hz	4	20
GW 62 499	2P+E	200 - 250 V		50/60 Hz	6	20
GW 62 501	3P+E	200 - 250 V		50/60 Hz	9	20
GW 62 502	3P+N+E	200 - 250 V		50/60 Hz	9	20
GW 62 503	2P+E	380 - 415 V		50/60 Hz	9	20
GW 62 504	3P+E	380 - 415 V		50/60 Hz	6	20
GW 62 505	3P+N+E	380 - 415 V		50/60 Hz	6	20
GW 62 506	3P+E	480 - 500 V		50/60 Hz	7	20
GW 62 507	3P+N+E	480 - 500 V		50/60 Hz	7	20
Rated current (A): 32						
GW 62 508	2P+E	100 - 130 V		50/60 Hz	4	16
GW 62 509	3P+E	100 - 130 V		50/60 Hz	4	16
GW 62 510	3P+N+E	100 - 130 V		50/60 Hz	4	16
GW 62 511	2P+E	200 - 250 V		50/60 Hz	6	16
GW 62 512	3P+E	200 - 250 V		50/60 Hz	9	16
GW 62 513	3P+N+E	200 - 250 V		50/60 Hz	9	16
GW 62 514	2P+E	380 - 415 V		50/60 Hz	9	16
GW 62 515	3P+E	380 - 415 V		50/60 Hz	6	16
GW 62 516	3P+N+E	380 - 415 V		50/60 Hz	6	16
GW 62 517	3P+E	480 - 500 V		50/60 Hz	7	16
GW 62 518	3P+N+E	480 - 500 V		50/60 Hz	7	16
GW 62 557	3P+E	380 - 440 V		50/60 Hz	3	16

CHARACTERISTICS: PG21 cable gland.
NOTE: all products are packaged individually.

IEC 309 HP

62/63 - LOW VOLTAGE SCREW WIRING 90° ANGLED SURFACE-MOUNTING SOCKET-OUTLETS

IP67



GW 63 527

Low voltage screw wiring 90° angled surface-mounting socket-outlets for high currents

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Characteristics	Pack Carton
Rated current (A): 63							
GW 63 519	2P+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 520	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 521	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	2/4
GW 63 522	2P+E	200 - 250 V		50/60 Hz	6	Pilot contact	2/4
GW 63 523	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	2/4
GW 63 524	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	2/4
GW 63 525	2P+E	380 - 415 V		50/60 Hz	9	Pilot contact	2/4
GW 63 526	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	2/4
GW 63 527	3P+N+E	380 - 415 V		50/60 Hz	6	Pilot contact	2/4
GW 63 528	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	2/4
GW 63 529	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	2/4
Rated current (A): 125							
GW 62 530	3P+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 62 531	3P+N+E	100 - 130 V		50/60 Hz	4	Pilot contact	1/2
GW 62 532	3P+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 62 533	3P+N+E	200 - 250 V		50/60 Hz	9	Pilot contact	1/2
GW 62 534	3P+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 62 535	3P+N+E	380 - 415 V		50/60 Hz	6	Pilot contact	1/2
GW 62 536	3P+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2
GW 62 537	3P+N+E	480 - 500 V		50/60 Hz	7	Pilot contact	1/2

CHARACTERISTICS: PG36 cable gland for 63A versions; PG48 cable gland for 125A versions. Versions with pilot contact. nickel-plated contacts.
NOTE: all products are packaged individually.

FLUSH-MOUNTING SOCKETS FOR SPECIFIC USES

IP44/IP54



GW 62 204

Low voltage screw wiring 10° angled flush-mounting socket-outlets with reduced dimension flange

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 204	2P+E	200 - 250 V		50/60 Hz	6	62x62	10/100

CHARACTERISTICS: nickel-plated contacts. For use in restricted spaces.



GW 62 393

Domestic socket outlet - IP54

Code	No. of poles	Rated current (A)	Rated voltage	Colour	Frequency	Flange dimensions (mm)	Pack Carton
Standard: German							
GW 62 393	2P+E	16	230 V		50/60 Hz	50x50	1/20
GW 62 392	2P+E	16	200 - 250 V		50/60 Hz	85x75	1/12
Standard: French							
GW 62 394	2P+E	16	230 V		50/60 Hz	50x50	1/20

CHARACTERISTICS: domestic socket-outlets equipped with child protection (shutter) and with rear connection.
NOTES: domestic socket-outlets 50x50 mm can be installed also on flanges 85x75 mm using the adapter code GW68281.



IEC 309 HP



Scan the QR Code and find out all the technical informations.

4 IP DEGREES FOR TOTAL PROTECTION



The HP straight plugs and socket-outlets are the first and only on the electrotechnical field with IP68 and IP69 degrees of protection. Nickel-plated pins and slevees also offers the best protection against corrosion, oxidation and abrasion, even in critical environmental conditions.

EXCELLENT RESISTANCE TO STRESS



The use of high-performance technopolymers and the innest of rubberised surfaces to protect those most exposed to impact (in all 63-125A versions) offer excellent resistance to mechanical stress (IK09), also at low temperatures (down to -25 °C).

SAFE AND INTUITIVE ASSEMBLY



The 16-32A versions are distinguished by the patented SAFE-LOCK ¼ turn body-grip closure, while the 63-125A versions feature a closure system with captive screws attached to brass inserts made with an increased contrast-flange.

16A and 32A extra low voltage industrial plugs and socket-outlets to IEC 309 standard

Rated current (In)	Rated Voltage (Un)	Frequency	Poles	Reference h	Stright plugs IP44	90° plugs IP44	90° surface mounting inlets IP44	Straight connectors IP44	10° flush-mounting socket-outlets IP44	10° flush-mounting socket- outlets IP67	10° surface-mounting socket- outlets IP44	90° surface-mounting socket- outlets IP44
					Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring	Screw wiring
16 A	20 ÷ 25 V	50/60 Hz	2P	-	GW 60 064	GW 60 127	GW 60 464	GW 62 064	GW 62 265	GW 62 365	GW 62 456	GW 62 538
		50/60 Hz	3P	-	GW 60 065	GW 60 128	GW 60 465	GW 62 065	GW 62 266	GW 62 366	GW 62 457	GW 62 539
	40 ÷ 50 V	50/60 Hz	2P	12	GW 60 066	GW 60 129	GW 60 466	GW 62 066	GW 62 267		GW 62 458	GW 62 540
		50/60 Hz	3P	12	GW 60 067	GW 60 130	GW 60 467	GW 62 067	GW 62 268		GW 62 459	GW 62 541
	20 ÷ 25 V and 40 ÷ 50 V	100÷200 Hz	2P	4	GW 60 068	GW 60 131	GW 60 468	GW 62 068	GW 62 269		GW 62 460	GW 62 542
		100÷200 Hz	3P	4	GW 60 069	GW 60 132	GW 60 469	GW 62 069	GW 62 270		GW 62 461	GW 62 543
		> 400÷500 Hz	2P	11	GW 60 070	GW 60 133	GW 60 470	GW 62 070	GW 62 271		GW 62 462	GW 62 544
		> 400÷500 Hz	3P	11	GW 60 071	GW 60 134	GW 60 471	GW 62 071	GW 62 272		GW 62 463	GW 62 545
	20 ÷ 25 V and 40 ÷ 50 V	dc	2P	10	GW 60 072	GW 60 135	GW 60 472	GW 62 072	GW 62 273		GW 62 464	GW 62 546
32 A	20 ÷ 25 V	50/60 Hz	2P	-	GW 60 073	GW 60 136	GW 60 473	GW 62 073	GW 62 274		GW 62 465	GW 62 547
		50/60 Hz	3P	-	GW 60 074	GW 60 137	GW 60 474	GW 62 074	GW 62 275		GW 62 466	GW 62 548
	40 ÷ 50 V	50/60 Hz	2P	12	GW 60 075	GW 60 138	GW 60 475	GW 62 075	GW 62 276		GW 62 467	GW 62 549
		50/60 Hz	3P	12	GW 60 076	GW 60 139	GW 60 476	GW 62 076	GW 62 277		GW 62 468	GW 62 550
	20 ÷ 25 V and 40 ÷ 50 V	100÷200 Hz	2P	4	GW 60 077	GW 60 140	GW 60 477	GW 62 077	GW 62 278		GW 62 469	GW 62 551
		100÷200 Hz	3P	4	GW 60 078	GW 60 141	GW 60 478	GW 62 078	GW 62 279		GW 62 470	GW 62 552
		> 400÷500 Hz	2P	11	GW 60 079	GW 60 142	GW 60 479	GW 62 079	GW 62 280		GW 62 471	GW 62 553
		> 400÷500 Hz	3P	11	GW 60 080	GW 60 143	GW 60 480	GW 62 080	GW 62 281		GW 62 472	GW 62 554
	20 ÷ 25 V and 40 ÷ 50 V	dc	2P	10	GW 60 081	GW 60 144	GW 60 481	GW 62 081	GW 62 282		GW 62 473	GW 62 555

IEC 309 BTS

Extra-low voltage plugs and socket-outlets IEC 309 standard

The IEC 309 BTS range of extra-low voltage plugs and sockets for industrial applications enable machinery and devices that operate on voltages of less than 50 V to be connected. The range includes different versions – straight mobile, 90° connectors, surface-mounting and flush mounting, protected and watertight. Available for currents from 16 to 32 A.



60/62 - EXTRA LOW VOLTAGE SCREW WIRING INDUSTRIAL PLUGS AND SOCKET-OUTLETS

Straight plugs - IP44



GW 60 064

Extra-low voltage screw wiring straight plugs

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 064	2P	20-25 V		50 - 60 Hz	-	10/40
GW 60 065	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 066	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 067	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 068	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 069	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 070	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 071	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 072	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 60 073	2P	20-25 V		50 - 60 Hz	-	10/20
GW 60 074	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 075	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 076	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 077	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 078	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 079	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 080	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 081	2P	20-25V and 40-50 V		d.c.	10	10/20

CHARACTERISTICS: nickel-plated plugs. Ø 23mm cable gland.

90° plugs - IP44



GW 60 127

Extra-low voltage screw wiring 90° plugs

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 127	2P	20-25 V		50 - 60 Hz	-	10/40
GW 60 128	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 129	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 130	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 131	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 132	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 133	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 134	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 135	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 60 136	2P	20-25 V		50 - 60 Hz	-	10/20
GW 60 137	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 138	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 139	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 140	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 141	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 142	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 143	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 144	2P	20-25V and 40-50 V		d.c.	10	10/20

CHARACTERISTICS: nickel-plated plugs. PG21 cable gland.

IEC 309 BTS

90° surface-mounting inlets - IP44



GW 60 464

Extra-low voltage screw wiring 90° angled surface-mounting inlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 60 464	2P	20-25 V		50 - 60 Hz	-	10/40
GW 60 465	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 466	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 467	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 468	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 469	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 470	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 471	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 472	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 60 473	2P	20-25 V		50 - 60 Hz	-	10/20
GW 60 474	3P	20-25 V		50 - 60 Hz	-	10/20
GW 60 475	2P	40-50 V		50 - 60 Hz	12	10/20
GW 60 476	3P	40-50 V		50 - 60 Hz	12	10/20
GW 60 477	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 478	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 60 479	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 480	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 60 481	2P	20-25V and 40-50 V		d.c.	10	10/20

ACCESSORIES SUPPLIED: nickel-plated plugs. Ø 23mm cable gland.

Connectors - IP44



GW 62 064

Extra-low voltage screw wiring straight connectors

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 064	2P	20-25 V		50 - 60 Hz	-	10/40
GW 62 065	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 066	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 067	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 068	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 069	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 070	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 071	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 072	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 62 073	2P	20-25 V		50 - 60 Hz	-	10/20
GW 62 074	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 075	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 076	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 077	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 078	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 079	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 080	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 081	2P	20-25V and 40-50 V		d.c.	10	10/20

CHARACTERISTICS: nickel-plated contacts. Ø 23mm cable gland.

10° flush-mounting socket-outlets - IP44



GW 62 265

Extra-low voltage screw wiring 10° angled flush-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 265	2P	20-25 V		50 - 60 Hz	-	85x75	10/40
GW 62 266	3P	20-25 V		50 - 60 Hz	-	85x75	10/20
GW 62 267	2P	40-50 V		50 - 60 Hz	12	85x75	10/20
GW 62 268	3P	40-50 V		50 - 60 Hz	12	85x75	10/20
GW 62 269	2P	20-25V and 40-50 V		100 - 200 Hz	4	85x75	10/20
GW 62 270	3P	20-25V and 40-50 V		100 - 200 Hz	4	85x75	10/20
GW 62 271	2P	20-25V and 40-50 V		401 - 500 Hz	11	85x75	10/20
GW 62 272	3P	20-25V and 40-50 V		401 - 500 Hz	11	85x75	10/20
GW 62 273	2P	20-25V and 40-50 V		d.c.	10	85x75	10/20
Rated current (A): 32							
GW 62 274	2P	20-25 V		50 - 60 Hz	-	85x75	10/20
GW 62 275	3P	20-25 V		50 - 60 Hz	-	85x75	10/20
GW 62 276	2P	40-50 V		50 - 60 Hz	12	85x75	10/20
GW 62 277	3P	40-50 V		50 - 60 Hz	12	85x75	10/20
GW 62 278	2P	20-25V and 40-50 V		100 - 200 Hz	4	85x75	10/20
GW 62 279	3P	20-25V and 40-50 V		100 - 200 Hz	4	85x75	10/20
GW 62 280	2P	20-25V and 40-50 V		401 - 500 Hz	11	85x75	10/20
GW 62 281	3P	20-25V and 40-50 V		401 - 500 Hz	11	85x75	10/20
GW 62 282	2P	20-25V and 40-50 V		d.c.	10	85x75	10/20

CHARACTERISTICS: nickel-plated contacts.

10° flush-mounting socket-outlets - IP67



GW 62 366

Extra-low voltage screw wiring 10° angled flush-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
Rated current (A): 16							
GW 62 365	2P	20-25 V		50 - 60 Hz	-	85x75	10/40
GW 62 366	3P	20-25 V		50 - 60 Hz	-	85x75	10/20

CHARACTERISTICS: nickel-plated contacts.

IEC 309 BTS

10° surface-mounting socket-outlets - IP44



GW 62 456

Extra-low voltage screw wiring 10° angled surface-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 456	2P	20-25 V		50 - 60 Hz	-	10/40
GW 62 457	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 458	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 459	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 460	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 461	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 462	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 463	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 464	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 62 465	2P	20-25 V		50 - 60 Hz	-	10/20
GW 62 466	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 467	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 468	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 469	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 470	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 471	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 472	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 473	2P	20-25V and 40-50 V		d.c.	10	10/20

CHARACTERISTICS: nickel-plated contacts. Ø 29mm cable gland.

90° surface-mounting socket-outlets - IP44



GW 62 538

Extra-low voltage screw wiring 90° angled surface-mounting socket-outlets

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Pack Carton
Rated current (A): 16						
GW 62 538	2P	20-25 V		50 - 60 Hz	-	10/20
GW 62 539	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 540	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 541	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 542	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 543	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 544	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 545	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 546	2P	20-25V and 40-50 V		d.c.	10	10/20
Rated current (A): 32						
GW 62 547	2P	20-25 V		50 - 60 Hz	-	10/20
GW 62 548	3P	20-25 V		50 - 60 Hz	-	10/20
GW 62 549	2P	40-50 V		50 - 60 Hz	12	10/20
GW 62 550	3P	40-50 V		50 - 60 Hz	12	10/20
GW 62 551	2P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 552	3P	20-25V and 40-50 V		100 - 200 Hz	4	10/20
GW 62 553	2P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 554	3P	20-25V and 40-50 V		401 - 500 Hz	11	10/20
GW 62 555	2P	20-25V and 40-50 V		d.c.	10	10/20

CHARACTERISTICS: nickel-plated contacts. Ø 29mm cable gland.



IEC 309 BTS




Scan the QR Code and find out all the technical informations.

WIDE RANGE



The range consists of 16-32A straight and 90°, surface-mounting and flush-mounting plugs and socket-outlets, in protected versions (10° flush-mounting sockets versions also available in a waterproof version IP67).

FOR ULTRA-LOW VOLTAGE APPLICATIONS



The IEC 309 BTS range of plugs and sockets are ideal for connection and use with machinery and devices with voltages lower than 50V (e.g. bell transformers, toy transformers, halogen lamps, etc.)

SYNERGY WITH DISTRIBUTION BOARDS



The 10° flush-mounting socket-outlets of the extra-low voltage range have the same dimensions and the same fixing centre distance as the normal IEC 309 socket-outlets, therefore they can also be installed on the Q-DIN, Q-BOX and QMC boards.

IEC 309 MA

Multiple socket couplers

	INPUT					COUPLER OUTPUTS		
	Type	Rated current (In)	Rated Voltage (Un)	Poles	Reference h	No. 2 socket-outlets 16A	No. 3 socket-outlets 16A	No. 3 socket-outlets 32A
	Without cable	16 A	100 ÷ 130 V	2P+E	4	GW 64 008	GW 64 022	
				3P+E	4		GW 64 023	
			200 ÷ 250 V	2P+E	6	GW 64 010	GW 64 024	
				3P+E	9	GW 64 011	GW 64 025	
				3P+N+E	9	GW 64 012	GW 64 026	
			380 ÷ 415 V	3P+E	9	GW 64 013	GW 64 027	
				3P+N+E	6	GW 64 014	GW 64 028	
		32 A	380 ÷ 415 V	3P+E	6			GW 64 068
	With cable	16 A	100 ÷ 130 V	2P+E	4		GW 64 050	
			200 ÷ 250 V	2P+E	6		GW 64 052	
			380 ÷ 415 V	3P+E	6		GW 64 055	
				3P+N+E	6		GW 64 056	

Multiple socket adaptors

	INPUT				OUTLETS			
	Rated current (In)	Rated Voltage (Un)	Poles	Reference h	No. 3 socket-outlets			Code
					2P+E 230 V~	3P+E 400 V~	3P+N+E 400 V~	
	16 A	380 ÷ 415 V	3P+N+E	6	2x16A		1x16A	GW 64 059
					1x16A	1x16A	1x16A	GW 64 060
	32 A	200 ÷ 250 V	2P+E	6	3x16A			GW 64 062
		380 ÷ 415 V	3P+N+E	6	1x16A	1x16A	1x16A	GW 64 063
					2x16A		1x32A	GW 64 064
					1x32A	1x32A	1x32A	GW 64 061
	63 A	380 ÷ 415 V	3P+N+E	6	2x32A		1x63A	GW 64 065

Phase inverter

	INPUT				OUTLETS		
	Rated current (In)	Rated Voltage (Un)	Poles	Reference h	No. 1 socket outlets 3P+E 400 V~	No. 1 socket outlets 3P+N+E 400 V~	Code
	16 A	380 ÷ 415 V	3P+E	6	1x16A		GW 64 066
			3P+N+E	6		1x16A	GW 64 067

IMPORTANT NOTICE: the range of multiple socket adaptors, adaptors and shunts should be considered an integral part of the electrical system, since they are products suitable only for temporary,trailing installations and connections, and not for permanent applications. Furthermore, the range cannot be used in areas with a fire hazard.

System adaptors

	INPUT					DOMESTIC SOCKET-OUTLET					INDUSTRIAL SOCKET-OUTLET
	Type	Rated current (In)	Rated Voltage (Un)	Poles	Reference h	N. 2 outputs 2P+E 16A dual amp. (P17/P11)	No. 1 output 2P+E 16A dual amp. (P30/P17)	No. 1 output 2P+E 10/16A German Std.	No. 1 output 2P+E 16A French Std.	No. 1 output 2P+E 13A British Std.	2P+E 16A 230V 6h
	IEC 309 industrial plug	16 A	200 ÷ 250 V	2P+E	6	GW 64 211					
							GW 64 212				
								GW 64 210			
									GW 64 203		
										GW 64 204	
						GW 64 206 fitted for other combinations					
			380 ÷ 415 V	3P+N+E	6	GW 64 216					
							GW 64 217				
						GW 64 207 fitted for other combinations					
	Domestic sockets	2P+E 16A 250V S17									GW 64 208
		2P+E 16A 250V German/French Std.									GW 64 209

System branched adaptors

	INPUT					OUTPUT				Code
						INDUSTRIAL	DOMESTIC			
	Type	Rated current (In)	Rated Voltage (Un)	Poles	Reference h	IEC 309	No. 2 socket-outlets 2P+E 16A dual amp. (P17/P11)	No. 1 socket outlets 2P+E 16A dual amp. (P30/P17)	No. 2 socket-outlets 2P+E 16A dual amp. (P17/P11) No. 1 socket-outlet 2P+E 16A dual amp. (P30/P17)	
	IEC 309 industrial plug	16 A	200 ÷ 250 V	2P+E	6	•	•			GW 64 221
						•		•		GW 64 222
						•	Fitted for No. 2 SYSTEM modules			GW 64 223
						•			•	GW 64 231
						•	Fitted for No. 2+2 SYSTEM modules			GW 64 232
			380 ÷ 415 V	3P+N+E	6	•			•	GW 64 236
						•	Fitted for No. 2+2 SYSTEM modules			GW 64 237
	Cable with IEC309 plug			3P+N+E	6	•			•	GW 64 256
	Cable with domestic plug		200 ÷ 250 V	2P+E S17		2P+E 16A - 230V			•	GW 64 263
		Fitted for cable and plug				2P+E 16A - 230V	Fitted for No. 2+2 SYSTEM modules			GW 64 265

IMPORTANT NOTICE: the range of multiple socket adaptors, adaptors and shunts should be considered an integral part of the electrical system, since they are products suitable only for temporary,trailing installations and connections, and not for permanent applications. Furthermore, the range cannot be used in areas with a fire hazard.

IEC 309 MA

Multiple sockets and adaptors for industrial and domestic use, protected and watertight



The IEC 309 MA range is a range of multipliers, adapters and branched. They are available in currents of 16, 32 or 63 A and have a varying number of outlets and poles in numerous different combinations. These products should be considered supplementary to the system as they are only suitable for use in temporary installations and mobile connections, and they have not been designed for permanent applications.

64 - MULTIPLE SOCKET-COUPLERS

2-outputs



GW 64 013

Multiple socket-couplers 2 outputs with 16A plug - 50/60Hz - IP67



Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Plug IEC 309: 16A					
GW 64 008	2P+E	110 V		4	5/20
GW 64 010	2P+E	230 V		6	5/20
GW 64 011	3P+E	230 V		9	5/10
GW 64 012	3P+N+E	230 V		9	5/10
GW 64 013	3P+E	400 V		6	5/10
GW 64 014	3P+N+E	400 V		6	5/10

3-outputs



GW 64 027

Multiple socket-couplers 3 outputs with 16-32A plug - 50/60Hz - IP67



Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Plug IEC 309: 16A					
GW 64 022	2P+E	110 V		4	5/10
GW 64 023	3P+E	110 V		4	5/10
GW 64 024	2P+E	230 V		6	5/10
GW 64 025	3P+E	230 V		9	5/10
GW 64 026	3P+N+E	230 V		9	5/10
GW 64 027	3P+E	400 V		6	5/10
GW 64 028	3P+N+E	400 V		6	5/10
Plug IEC 309: 32A					
GW 64 068	3P+E	400 V		6	1/4

3-outputs with cable and plug



GW 64 052

Watertight multiple socket-couplers 3 outputs with 2m flexible cable and 16A plug - 50/60Hz - IP67



Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Plug IEC 309: 16A					
GW 64 050	2P+E	110 V		4	1/6
GW 64 052	2P+E	230 V		6	1/6
GW 64 055	3P+E	400 V		6	1/3
GW 64 056	3P+N+E	400 V		6	1/3

64 - MULTIPLE SOCKET-ADAPTORS

Configuration adaptors



GW 64 059

Watertight multiple socket-adaptors with 16A plug - 50/60 Hz - IP67

Code	Socket-outlet IEC 309	Socket-outlet IEC 309	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 3P+N+E - 16A - 400V ac				
GW 64 059	2P+E - 16A - 230V ac	2P+E - 16A - 230V ac	3P+N+E - 16A - 400V ac	5/10
GW 64 060	2P+E - 16A - 230V ac	3P+E - 16A - 400V ac	3P+N+E - 16A - 400V ac	5/10



GW 64 061

Watertight multiple socket-adaptors with 32A plug - 50/60Hz - IP67

Code	Socket-outlet IEC 309	Socket-outlet IEC 309	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 3P+N+E - 32A - 400V ac				
GW 64 061	2P+E - 32A - 230V ac	3P+E - 32A - 400V ac	3P+N+E - 32A - 400V ac	1/5

Current adaptors



GW 64 062

Watertight multiple-socket adaptor with 32 A plug - 50/60 Hz - IP67

Code	Socket-outlet IEC 309	Socket-outlet IEC 309	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 2P+E - 32A - 230V ac				
GW 64 062	2P+E - 16A - 230V ac	2P+E - 16A - 230V ac	2P+E - 16A - 230V ac	5/10
Plug IEC 309: 3P+N+E - 32A - 400V ac				
GW 64 063	2P+E - 16A - 230V ac	3P+E - 16A - 400V ac	3P+N+E - 16A - 400V ac	5/10
GW 64 064	2P+E - 16A - 230V ac	2P+E - 16A - 230V ac	3P+N+E - 32A - 400V ac	1/5



GW 64 065

Watertight multiple socket-adaptors plug 63A - 50/60 Hz - IP67

Code	Socket-outlet IEC 309	Socket-outlet IEC 309	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 3P+N+E - 63A - 400V ac				
GW 64 065	2P+E - 32A - 230V ac	2P+E - 32A - 230V ac	3P+N+E - 63A - 400V ac	1/2

IEC 309 MA

Phase inverter



GW 64 066

Protected phase inverter - 16 A - 50/60 Hz - IP44

Code	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 3P+E - 16A - 400V ac		
GW 64 066	3P+E - 16A - 400V ac	10/20
Plug IEC 309: 3P+N+E - 16A - 400V ac		
GW 64 067	3P+N+E - 16A - 400V ac	10/20

64 IC/CI - SYSTEM ADAPTORS

From industrial to domestic: wired



GW 64 203

System adaptors: IEC 309 IP44 plug / Socket-outlet for residential use - 50/60Hz

Code	Resid. socket-outlets 250V~	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac		
GW 64 203	N. 1 - 2P+E - 16A French	10/40
GW 64 204	N. 1 - 2P+E - 13A British	10/40
GW 64 210	N. 1 - 2P+E - 10/16A German	10/40
GW 64 211	N. 2 - 2P+E - 16A Dual amp (P17/11)	10/40
GW 64 212	N. 1 - 2P+E - 16A Dual amp (P30 - P17)	10/40
Plug IEC 309: 3P+N+E - 16A - 400V ac		
GW 64 216	N. 2 - 2P+E - 16A Dual amp (P17/11)	10/40
GW 64 217	N. 1 - 2P+E - 16A Dual amp (P30 - P17)	10/40

CHARACTERISTICS: GW64211 - GW64216, domestic socket-outlets with Ø 4 / 5 mm plug pins.
GW64212 - GW64217, domestic socket-outlets with Ø 4 / 4.8 / 5 mm plug pins, with side and central earth contact.
NOTES: only for temporary uses.

From industrial to domestic: fitted



GW 64 206

System adaptors: IEC 309 IP44 plug for Fitting for 2 module System range - 50/60Hz

Code	Housing for	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac		
GW 64 206	2	10/40
Plug IEC 309: 3P+N+E - 16A - 400V ac		
GW 64 207	2	10/40

ACCESSORIES SUPPLIED: wiring cables.
NOTES: only for temporary uses.

From domestic to industrial: wired



GW 64 209

System adaptors Domestic use plug / IEC 309 IP44 socket-outlet - 50/60Hz

Code	Socket-outlet IEC 309	Pack Carton
Domestic socket-outlet: 2P+E - 16A - 250V ac S17		
GW 64 208	2P+E - 16A - 230V ac	10/40
Domestic socket-outlet: 2P+E - 16A - 250V ac German/French		
GW 64 209	2P+E - 16A - 230V ac	10/40

CHARACTERISTICS: GW64209, with double earth contact (German standard side contact and French standard middle contact).
NOTES: only for temporary uses.

64 IC/CI - SYSTEM BRANCHED ADAPTORS

1 branched outlet: wired



GW 64 221

Conversion adaptors: Plug for domestic use / IEC 309 socket-coupler IP44 - 50/60Hz

Code	Resid. socket-outlets 250V~	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac			
GW 64 221	N. 2 - 2P+E - 16A Dual amp (P17/11)	2P+E - 16A - 230V ac	5/20
GW 64 222	N. 1 - 2P+E - 16A Dual amp (P30 - P17)	2P+E - 16A - 230V ac	5/20

CHARACTERISTICS: GW64221 domestic socket-outlets with plug pins Ø 4/5mm.
GW64222 domestic socket-outlets with plug pins Ø 4/4.8/5mm, with side and central earthing.
NOTES: only for temporary uses.

1 branched outlet: fitted



GW 64 223

Conversion adaptors: IEC 309 plug fitting for 2 SYSTEM modules/IEC 309 socket-coupler IP44 - 50/60Hz

Code	Housing for	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac			
GW 64 223	2	2P+E - 16A - 230V ac	5/20

ACCESSORIES SUPPLIED: wiring cables.
NOTES: only for temporary uses.

2 branched outlets: wired



GW 64 231

Conversion adaptors: Plug IEC 309 IP44. Socket-outlet for domestic use / IEC 309 socket-coupler IP44 - 50/60Hz

Code	Resid. socket-outlets 250V~	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac			
GW 64 231	N. 2 (P17/11) -N. 1 (P30-P17)	2P+E - 16A - 230V ac	5/20
Plug IEC 309: 3P+N+E - 16A - 400V ac			
GW 64 236	N. 2 (P17/11) -N. 1 (P30-P17)	3P+N+E - 16A - 400V ac	5/10

NOTES: only for temporary uses.

IEC 309 MA

2 branched outlets: fitted



GW 64 232

Conversion adaptors: IEC 309 plug. Fitting for 2+2 SYSTEM modules/IEC 309 socket-coupler IP44 - 50/60Hz

Code	Housing for	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 2P+E - 16A - 230V ac			
GW 64 232	2+2	2P+E - 16A - 230V ac	5/20
Plug IEC 309: 3P+N+E - 16A - 400V ac			
GW 64 237	2+2	3P+N+E - 16A - 400V ac	5/10

ACCESSORIES SUPPLIED: wiring cables.
NOTES: only for temporary uses.

2 branched outlets with cable and plug: wired



GW 64 256

Conversion adaptor shunt with 2 m of flexible cable: IEC 309 plug IP44 Domestic sockets / IEC 309 socket-coupler IP44 - 50/60Hz

Code	Resid. socket-outlets 250V~	Socket-outlet IEC 309	Pack Carton
Plug IEC 309: 3P+N+E - 16A - 400V ac			
GW 64 256	N. 2 (P17/11) -N. 1 (P30-P17)	3P+N+E - 16A - 400V ac	1/3

CHARACTERISTICS: 2 domestic socket-outlets with Ø 4 / 5 mm plug pins (P17/11) and 1 domestic socket-outlet with Ø 4 / 4.8 / 5 mm plug pins (P30 - P17) with side and central earth control.
NOTES: only for temporary uses.



GW 64 263

Conversion adaptor shunt with 2 m of flexible cable: plug for domesticuse / sockets-outlets for domestic use / IEC 309 socket-coupler IP44 - 50/60Hz

Code	Resid. socket-outlets 250V~	Socket-outlet IEC 309	Pack Carton
Domestic socket-outlet: 2P+E - 16A - 250V ac S17			
GW 64 263	N. 2 (P17/11) -N. 1 (P30-P17)	2P+E - 16A - 230V ac	1/6

CHARACTERISTICS: 2 domestic socket-outlets with Ø 4 / 5 mm plug pins (P17/11) and 1 domestic socket-outlet with Ø 4 / 4.8 / 5 mm plug pins (P30 - P17) with side and central earth control.
NOTES: only for temporary uses.

2 branched outlets fitted for cable and plug



GW 64 265

Conversion adaptor shunt: Fitting for 2+2 SYSTEM modules / IEC 309 socket-coupler IP44 - 50/60Hz

Code	Housing for	Socket-outlet IEC 309	Pack Carton
GW 64 265	2+2	2P+E - 16A - 230V ac	5/20

ACCESSORIES SUPPLIED: wiring cables.
NOTES: only for temporary uses.



IEC 309 MA



Scan the QR Code and find out all the technical informations.

MOBILE MULTIPLIERS



The IEC 309 MA range has a number of different watertight mobile multiplier models equipped with 2 or 3 outputs, with or without cable. Available with screw wiring and with currents up to 32A.

MULTIPLE-SOCKET ADAPTORS



3 versions that allow to meet even the most varied connection and power take-off requirements: configuration adaptors, current adaptors and phase inverters.

ADAPTORS AND BRANCHED-ADAPTORS



They can transform an industrial connection into a domestic connection and vice versa. Available with currents from 16A, pre-wired or just “prearranged” to allow the user to complete the configuration of the product depending on the specific needs.

Interlocked socket-outlets IEC 309 standard



67 IB

Vertical interlocked socket-outlets IEC 309 standard - IP66 / IP67

p. 78







66 IB

Vertical interlocked socket-outlets IEC 309 standard for heavy duty - IP66

p. 88

44 IB

Horizontal protected interlocked socket-outlets IEC 309 standard

p. 96

COMBIBLOC

Compact protected and watertight interlocke socket-outlets IEC 309 standard

p. 102

Vertical, horizontal and compact interlocked socket-outlets

				VERTICAL SOCKET-OUTLETS - 67 IB						VERTICAL SOCKET-OUTLETS FOR HEAVY DUTY USE - 66 IB		
												
Rated current In	**Rated voltage Un**	**No. poles**	**Reference h.**	Vertical socket-outlets with MCB, without bottom (AUTOMATIKA)	Vertical socket-outlets with MCB, with bottom (AUTOMATIKA)	Vertical socket-outlets with rotary switch, without bottom	Vertical socket-outlets with rotary switch, with bottom	Vertical socket-outlets with fuse-holder base, without bottom	Vertical socket-outlets with fuse-holder base, with bottom	Vertical socket-outlets with rotary switch, without bottom	Vertical socket-outlets with rotary switch, with bottom	Vertical socket-outlets with fuse-holder base, without bottom
				IP66 / IP67	**IP66 / IP67**	**IP66 / IP67**	**IP66 / IP67**	**IP66 / IP67**	**IP66 / IP67**	**IP66**	**IP66**	**IP66**
16 A	20 ÷ 25 V	2P	s.r.			GW 66 359 N	GW 66 259 N					GW 66 886
	100 ÷ 130 V	2P+E	4	GW 66 151 N	GW 66 051 N	GW 66 301 N	GW 66 201 N	GW 66 323 N	GW 66 223 N	GW 66 535	GW 66 501	GW 66 801
		3P+E	4	GW 66 152 N	GW 66 052 N	GW 66 302 N	GW 66 202 N	GW 66 324 N	GW 66 224 N	GW 66 536	GW 66 502	GW 66 802
		3P+N+E	4	GW 66 153 N	GW 66 053 N	GW 66 303 N	GW 66 203 N	GW 66 325 N	GW 66 225 N	GW 66 537	GW 66 503	GW 66 803
	200 ÷ 250 V	2P+E	6	GW 66 154 N	GW 66 054 N	GW 66 304 N	GW 66 204 N	GW 66 326 N	GW 66 226 N	GW 66 538	GW 66 504	GW 66 804
		3P+E	9	GW 66 155 N	GW 66 055 N	GW 66 305 N	GW 66 205 N	GW 66 327 N	GW 66 227 N	GW 66 539	GW 66 505	GW 66 805
		3P+N+E	9	GW 66 156 N	GW 66 056 N	GW 66 306 N	GW 66 206 N	GW 66 328 N	GW 66 228 N	GW 66 540	GW 66 506	GW 66 806
	380 ÷ 415 V	2P+E	9	GW 66 157 N	GW 66 057 N	GW 66 307 N	GW 66 207 N	GW 66 329 N	GW 66 229 N	GW 66 541	GW 66 507	GW 66 807
		3P+E	6	GW 66 158 N	GW 66 058 N	GW 66 308 N	GW 66 208 N	GW 66 330 N	GW 66 230 N	GW 66 542	GW 66 508	GW 66 808
		3P+N+E	6	GW 66 159 N	GW 66 059 N	GW 66 309 N	GW 66 209 N	GW 66 331 N	GW 66 231 N	GW 66 543	GW 66 509	GW 66 809
	480 ÷ 500 V	3P+E	7			GW 66 310 N	GW 66 210 N	GW 66 332 N	GW 66 232 N	GW 66 544	GW 66 510	GW 66 810
		3P+N+E	7			GW 66 311 N	GW 66 211 N	GW 66 333 N	GW 66 233 N	GW 66 545	GW 66 511	GW 66 811
32 A	100 ÷ 130 V	2P+E	4	GW 66 162 N	GW 66 062 N	GW 66 312 N	GW 66 212 N	GW 66 334 N	GW 66 234 N	GW 66 546	GW 66 512	GW 66 812
		3P+E	4	GW 66 163 N	GW 66 063 N	GW 66 313 N	GW 66 213 N	GW 66 335 N	GW 66 235 N	GW 66 547	GW 66 513	GW 66 813
		3P+N+E	4	GW 66 164 N	GW 66 064 N	GW 66 314 N	GW 66 214 N	GW 66 336 N	GW 66 236 N	GW 66 548	GW 66 514	GW 66 814
	200 ÷ 250 V	2P+E	6	GW 66 165 N	GW 66 065 N	GW 66 315 N	GW 66 215 N	GW 66 337 N	GW 66 237 N	GW 66 549	GW 66 515	GW 66 815
		3P+E	9	GW 66 166 N	GW 66 066 N	GW 66 316 N	GW 66 216 N	GW 66 338 N	GW 66 238 N	GW 66 550	GW 66 516	GW 66 816
		3P+N+E	9	GW 66 167 N	GW 66 067 N	GW 66 317 N	GW 66 217 N	GW 66 339 N	GW 66 239 N	GW 66 551	GW 66 517	GW 66 817
	380 ÷ 415 V	2P+E	9	GW 66 168 N	GW 66 068 N	GW 66 318 N	GW 66 218 N	GW 66 340 N	GW 66 240 N	GW 66 552	GW 66 518	GW 66 818
		3P+E	6	GW 66 169 N	GW 66 069 N	GW 66 319 N	GW 66 219 N	GW 66 341 N	GW 66 241 N	GW 66 553	GW 66 519	GW 66 819
		3P+N+E	6	GW 66 170 N	GW 66 070 N	GW 66 320 N	GW 66 220 N	GW 66 342 N	GW 66 242 N	GW 66 554	GW 66 520	GW 66 820
	480 ÷ 500 V	3P+E	7			GW 66 321 N	GW 66 221 N	GW 66 343 N	GW 66 243 N	GW 66 555	GW 66 521	GW 66 821
		3P+N+E	7			GW 66 322 N	GW 66 222 N	GW 66 344 N	GW 66 244 N	GW 66 556	GW 66 522	GW 66 822
	380/440 V	3P+E	3			GW 66 357 N	GW 66 257 N	GW 66 358 N	GW 66 258 N	GW 66 557	GW 66 523	GW 66 823
63 A	100 ÷ 130 V	2P+E	4			GW 67 356 N	GW 67 256 N	GW 66 345 N	GW 67 245 N		GW 66 524	
		3P+E	4			GW 67 357 N	GW 67 257 N	GW 66 346 N	GW 67 246 N		GW 66 525	
		3P+N+E	4			GW 67 358 N	GW 67 258 N	GW 66 347 N	GW 67 247 N		GW 66 526	
	200 ÷ 250 V	2P+E	6			GW 67 359 N	GW 67 259 N	GW 66 348 N	GW 67 248 N		GW 66 527	
		3P+E	9			GW 67 360 N	GW 67 260 N	GW 66 349 N	GW 67 249 N		GW 66 528	
		3P+N+E	9			GW 67 361 N	GW 67 261 N	GW 66 350 N	GW 67 250 N		GW 66 529	
	380 ÷ 415 V	2P+E	9			GW 67 362 N	GW 67 262 N	GW 66 351 N	GW 67 251 N		GW 66 530	
		3P+E	6			GW 67 363 N	GW 67 263 N	GW 66 352 N	GW 67 252 N		GW 66 531	
		3P+N+E	6			GW 67 364 N	GW 67 264 N	GW 66 353 N	GW 67 253 N		GW 66 532	
	480 ÷ 500 V	3P+E	7			GW 67 365 N	GW 67 265 N	GW 66 354 N	GW 67 254 N		GW 66 533	
		3P+N+E	7			GW 67 366 N	GW 67 266 N	GW 66 355 N	GW 67 255 N		GW 66 534	
											Vertical surface-mounting socket-outlets with electric interlock, with circuit breaker protection	
125 A	100 ÷ 130 V	3P+E	4								GW 66 581	
		3P+N+E	4								GW 66 582	
	200 ÷ 250 V	3P+E	9								GW 66 583	
		3P+N+E	9								GW 66 584	
	380 ÷ 415 V	3P+E	6								GW 66 585	
		3P+N+E	6								GW 66 586	

NOTE: interlocked sockets 63A equipped with pilot contact, interlocked sockets 125A equiped with 1NO clean contact.

VERTICAL SOCKET-OUTLETS FOR HEAVY DUTY USE - 66 IB			HORIZONTAL SOCKET-OUTLETS - 44 IB				COMPACT SOCKET-OUTLETS - COMBIBLOC			
										
Vertical socket-outlets with fuse-holder base, with bottom	Vertical socket-outlets for modular devices, without bottom	Vertical socket-outlets for modular devices, with bottom	Horizontal socket-outlets with rotary switch, without bottom	Horizontal socket-outlets with rotary switch, with bottom	Horizontal socket-outlets with fuse-holder base, without bottom	Horizontal socket-outlets with fuse-holder base, with bottom	Compact socket-outlets with rotary switch, without bottom	Compact socket-outlets with rotary switch, with bottom	Compact socket-outlets with rotary switch, without bottom	Compact socket-outlets with rotary switch, with bottom
IP66	**IP66**	**IP66**	**IP44**	**IP44**	**IP44**	**IP44**	**IP44**	**IP44**	**IP55**	**IP55**
GW 66 998										
GW 66 951	GW 66 824	GW 66 974	GW 66 101	GW 66 001	GW 66 123	GW 66 023	GW 66 423	GW 66 401	GW 66 467	GW 66 445
GW 66 952	GW 66 825	GW 66 975	GW 66 102	GW 66 002	GW 66 124	GW 66 024	GW 66 424	GW 66 402	GW 66 468	GW 66 446
GW 66 953	GW 66 826	GW 66 976	GW 66 103	GW 66 003	GW 66 125	GW 66 025	GW 66 425	GW 66 403	GW 66 469	GW 66 447
GW 66 954	GW 66 827	GW 66 977	GW 66 104	GW 66 004	GW 66 126	GW 66 026	GW 66 426	GW 66 404	GW 66 470	GW 66 448
GW 66 955	GW 66 828	GW 66 978	GW 66 105	GW 66 005	GW 66 127	GW 66 027	GW 66 427	GW 66 405	GW 66 471	GW 66 449
GW 66 956	GW 66 829	GW 66 979	GW 66 106	GW 66 006	GW 66 128	GW 66 028	GW 66 428	GW 66 406	GW 66 472	GW 66 450
GW 66 957	GW 66 830	GW 66 980	GW 66 107	GW 66 007	GW 66 129	GW 66 029	GW 66 429	GW 66 407	GW 66 473	GW 66 451
GW 66 958	GW 66 831	GW 66 981	GW 66 108	GW 66 008	GW 66 130	GW 66 030	GW 66 430	GW 66 408	GW 66 474	GW 66 452
GW 66 959	GW 66 832	GW 66 982	GW 66 109	GW 66 009	GW 66 131	GW 66 031	GW 66 431	GW 66 409	GW 66 475	GW 66 453
GW 66 960	GW 66 833	GW 66 983	GW 66 110	GW 66 010	GW 66 132	GW 66 032				
GW 66 961	GW 66 834	GW 66 984	GW 66 111	GW 66 011	GW 66 133	GW 66 033				
GW 66 962	GW 66 835	GW 66 985	GW 66 112	GW 66 012	GW 66 134	GW 66 034	GW 66 434	GW 66 412	GW 66 478	GW 66 456
GW 66 963	GW 66 836	GW 66 986	GW 66 113	GW 66 013	GW 66 135	GW 66 035	GW 66 435	GW 66 413	GW 66 479	GW 66 457
GW 66 964	GW 66 837	GW 66 987	GW 66 114	GW 66 014	GW 66 136	GW 66 036	GW 66 436	GW 66 414	GW 66 480	GW 66 458
GW 66 965	GW 66 838	GW 66 988	GW 66 115	GW 66 015	GW 66 137	GW 66 037	GW 66 437	GW 66 415	GW 66 481	GW 66 459
GW 66 966	GW 66 839	GW 66 989	GW 66 116	GW 66 016	GW 66 138	GW 66 038	GW 66 438	GW 66 416	GW 66 482	GW 66 460
GW 66 967	GW 66 840	GW 66 990	GW 66 117	GW 66 017	GW 66 139	GW 66 039	GW 66 439	GW 66 417	GW 66 483	GW 66 461
GW 66 968	GW 66 841	GW 66 991	GW 66 118	GW 66 018	GW 66 140	GW 66 040	GW 66 440	GW 66 418	GW 66 484	GW 66 462
GW 66 969	GW 66 842	GW 66 992	GW 66 119	GW 66 019	GW 66 141	GW 66 041	GW 66 441	GW 66 419	GW 66 485	GW 66 463
GW 66 970	GW 66 843	GW 66 993	GW 66 120	GW 66 020	GW 66 142	GW 66 042	GW 66 442	GW 66 420	GW 66 486	GW 66 464
GW 66 971	GW 66 844	GW 66 994	GW 66 121	GW 66 021	GW 66 143	GW 66 043				
GW 66 972	GW 66 845	GW 66 995	GW 66 122	GW 66 022	GW 66 144	GW 66 044				
GW 66 973	GW 66 846	GW 66 996								
GW 66 847		GW 66 866								
GW 66 848		GW 66 867								
GW 66 849		GW 66 868								
GW 66 850		GW 66 869								
GW 66 851		GW 66 870								
GW 66 852		GW 66 871								
GW 66 853		GW 66 872								
GW 66 854		GW 66 873								
GW 66 855		GW 66 874								
GW 66 856		GW 66 875								
GW 66 857		GW 66 876								
	Vertical surface-mounting socket-outlets with electric interlock with residual current circuit breaker protection									
	GW 66 591									
	GW 66 592									
	GW 66 593									
	GW 66 594									
	GW 66 595									
	GW 66 596									

Complementary items

			MODULAR BASES			DISTRIBUTION BOARDS				
										
			1 Socket-outlet	2 Socket-outlets	3 Socket-outlets	1 Socket-outlet	2 Socket-outlets	3 Socket-outlets		4 Socket-outlets
67 IB VERTICAL RANGE		IP67 vertical socket-outlets with rotary switch, with fuse-holder base and AUTOMATIKA 16/32A and 24V (SELV)	GW 66 690	GW 66 691	GW 66 694		GW 68 025 N (10 modules)	GW 68 010 N (14 modules)	GW 68 022 N (20 modules) 1 socket-outlet 63A 2 socket-outlets 16/32A	GW 68 015 N (20 modules)
		IP67 vertical socket-outlets with rotary switch (SBF) or with fuse-holder base 63A (CBF)	GW 66 693							
66 IB RANGE FOR HEAVY-DUTY USE		IP66 vertical socket-outlets for heavy duty use 16/32A	GW 66 696	GW 66 697	GW 66 698					
		IP66 vertical socket-outlets for heavy duty 63A	GW 66 700							
COMBIBLOC RANGE		IP44/55 compact protected watertight socket-outlets - 16/32A				GW 66 491	GW 66 492	GW 66 493		
44 IB HORIZONTAL RANGE		IP44 horizontal socket-outlets, without fuse-holder base (SBF) 16/32A					GW 68 006 N (14 modules)			GW 68 009 N (14 modules)
							GW 68 019 N (10 modules)			
		IP44 horizontal socket-outlets with fuse-holder base (CBF) 16/32A								GW 68 014 N (20 modules)

MODULAR BASES WITH WINDOW PANEL			LID/BOXES			
						
1 Socket-outlet	2 Socket-outlets	3 Socket-outlets	Flanged lid	Flush-mounting boxes (brick and plasterboard walls)	Surface-mounting bottom	
			GW 66 709 N	GW 66 683 N (*) (for brick wall)	GW 66 678 N	 GW 27 401
				GW 66 683 PM (*) (for plasterboard wall)		
					GW 66 686 (for SBF)	 GW 27 403
					GW 66 680 N (for CBF)	
GW 66 781 (6 modules)	GW 66 782 (12 modules)	GW 66 783 (18 modules)	GW 66 707		GW 66 685	 Serie IEC 309 HP
GW 66 784 (6 modules)						
				GW 66 498	GW 66 496	 Serie IEC 309 BTS
				GW 66 681 (for brick wall)	GW 66 676	 Serie 74 PS
				GW 66 681 PM (for plasterboard wall)		
				GW 66 682 (for brick wall)	GW 66 677	
				GW 66 682 PM (for plasterboard wall)		

(*) Cannot be used for SELV 24V

IB

Interlocked socket-outlets IEC 309 standard

System of industrial socket-outlets for power distribution in the industrial and commercial sector, equipped with locking device, enabling the most varied professional requirements of installers and panel builder to be met. The IB range is composed of 4 product lines: IP67 standard vertical socket-outlets, IP66 vertical socket-outlets for heavy duty applications, IP44 horizontal socket-outlets and IP44 and IP55 compact socket-outlets.



67 IB - VERTICAL INTERLOCKED SOCKET-OUTLETS - IP66 / IP67

AUTOMATIKA - with circuit breaker protection (MCB), without bottom - IP66 / IP67



GW 66 170 N

Automatika vertical interlocked socket-outlets
with miniature circuit breaker MT 6kA C characteristic - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 151 N	2P+E	100 - 130 V		4	1/12
GW 66 152 N	3P+E	100 - 130 V		4	1/12
GW 66 153 N	3P+N+E	100 - 130 V		4	1/12
GW 66 154 N	2P+E	200 - 250 V		6	1/12
GW 66 155 N	3P+E	200 - 250 V		9	1/12
GW 66 156 N	3P+N+E	200 - 250 V		9	1/12
GW 66 157 N	2P+E	380 - 415 V		9	1/12
GW 66 158 N	3P+E	380 - 415 V		6	1/12
GW 66 159 N	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 162 N	2P+E	100 - 130 V		4	1/12
GW 66 163 N	3P+E	100 - 130 V		4	1/12
GW 66 164 N	3P+N+E	100 - 130 V		4	1/12
GW 66 165 N	2P+E	200 - 250 V		6	1/12
GW 66 166 N	3P+E	200 - 250 V		9	1/12
GW 66 167 N	3P+N+E	200 - 250 V		9	1/12
GW 66 168 N	2P+E	380 - 415 V		9	1/12
GW 66 169 N	3P+E	380 - 415 V		6	1/12
GW 66 170 N	3P+N+E	380 - 415 V		6	1/12

CHARACTERISTICS: the socket-outlets use the miniature circuit breaker for control and protection.
ACCESSORIES SUPPLIED: the interlocked sockets are supplied with LED on the front that indicate the operating status of the switch and the presence of voltage.

AUTOMATIKA - with circuit breaker protection (MCB), with bottom - IP66 / IP67



GW 66 070 N

Automatika vertical interlocked socket-outlets
with miniature circuit breaker MT 6kA C characteristic - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 051 N	2P+E	100 - 130 V		4	1/12
GW 66 052 N	3P+E	100 - 130 V		4	1/12
GW 66 053 N	3P+N+E	100 - 130 V		4	1/12
GW 66 054 N	2P+E	200 - 250 V		6	1/12
GW 66 055 N	3P+E	200 - 250 V		9	1/12
GW 66 056 N	3P+N+E	200 - 250 V		9	1/12
GW 66 057 N	2P+E	380 - 415 V		9	1/12
GW 66 058 N	3P+E	380 - 415 V		6	1/12
GW 66 059 N	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 062 N	2P+E	100 - 130 V		4	1/12
GW 66 063 N	3P+E	100 - 130 V		4	1/12
GW 66 064 N	3P+N+E	100 - 130 V		4	1/12
GW 66 065 N	2P+E	200 - 250 V		6	1/12
GW 66 066 N	3P+E	200 - 250 V		9	1/12
GW 66 067 N	3P+N+E	200 - 250 V		9	1/12
GW 66 068 N	2P+E	380 - 415 V		9	1/12
GW 66 069 N	3P+E	380 - 415 V		6	1/12
GW 66 070 N	3P+N+E	380 - 415 V		6	1/12

CHARACTERISTICS: the socket-outlets use the miniature circuit breaker for command and protection.

ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 14/16mm. The interlocked sockets are supplied with LED on the front that indicate the operating status of the switch and the presence of voltage.

With rotary switch, without fuse-holder base (SBF), without bottom - IP66 / IP67



GW 66 357 N

Interlocked vertical socket-outlets with rotary switch
 without fuse-holder base without bottom - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 301 N	2P+E	100 - 130 V		4	1/12
GW 66 302 N	3P+E	100 - 130 V		4	1/12
GW 66 303 N	3P+N+E	100 - 130 V		4	1/12
GW 66 304 N	2P+E	200 - 250 V		6	1/12
GW 66 305 N	3P+E	200 - 250 V		9	1/12
GW 66 306 N	3P+N+E	200 - 250 V		9	1/12
GW 66 307 N	2P+E	380 - 415 V		9	1/12
GW 66 308 N	3P+E	380 - 415 V		6	1/12
GW 66 309 N	3P+N+E	380 - 415 V		6	1/12
GW 66 310 N	3P+E	480 - 500 V		7	1/12
GW 66 311 N	3P+N+E	480 - 500 V		7	1/12
Rated current (A): 32					
GW 66 312 N	2P+E	100 - 130 V		4	1/12
GW 66 313 N	3P+E	100 - 130 V		4	1/12
GW 66 314 N	3P+N+E	100 - 130 V		4	1/12
GW 66 315 N	2P+E	200 - 250 V		6	1/12
GW 66 316 N	3P+E	200 - 250 V		9	1/12
GW 66 317 N	3P+N+E	200 - 250 V		9	1/12
GW 66 318 N	2P+E	380 - 415 V		9	1/12
GW 66 319 N	3P+E	380 - 415 V		6	1/12
GW 66 320 N	3P+N+E	380 - 415 V		6	1/12
GW 66 321 N	3P+E	480 - 500 V		7	1/12
GW 66 322 N	3P+N+E	480 - 500 V		7	1/12
GW 66 357 N	3P+E	380 - 440 V		3	1/12



GW 67 364 N

Interlocked switched vertical socket-outlets without bottom - with rotary switch
 without fuse-holder base - 63A - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 63					
GW 67 356 N	2P+E	100 - 130 V		4	1/4
GW 67 357 N	3P+E	100 - 130 V		4	1/4
GW 67 358 N	3P+N+E	100 - 130 V		4	1/4
GW 67 359 N	2P+E	200 - 250 V		6	1/4
GW 67 360 N	3P+E	200 - 250 V		9	1/4
GW 67 361 N	3P+N+E	200 - 250 V		9	1/4
GW 67 362 N	2P+E	380 - 415 V		9	1/4
GW 67 363 N	3P+E	380 - 415 V		6	1/4
GW 67 364 N	3P+N+E	380 - 415 V		6	1/4
GW 67 365 N	3P+E	480 - 500 V		7	1/4
GW 67 366 N	3P+N+E	480 - 500 V		7	1/4

CHARACTERISTICS: 63A versions equipped with a pilot contact.



GW 66 359 N

Vertical socket-outlets without bottom
 with safety transformer (SELV) 230/24V 50/60Hz - IP66 / IP67

Code	No. of poles	Output voltage	Colour	Rated power	Pack Carton
Rated current (A): 16					
GW 66 359 N	2P	20-25 V		160 VA	1/4

CHARACTERISTICS: the socket-outlet is equipped with a thermal protection device. If the device trips, extract the plug from the socket-outlet and check the applied load.

With rotary switch, without fuse-holder base (SBF), with bottom - IP66 / IP67



GW 66 257 N

Interlocked vertical socket-outlets with bottom with rotary switch
without fuse-holder base - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 201 N	2P+E	100 - 130 V		4	1/12
GW 66 202 N	3P+E	100 - 130 V		4	1/12
GW 66 203 N	3P+N+E	100 - 130 V		4	1/12
GW 66 204 N	2P+E	200 - 250 V		6	1/12
GW 66 205 N	3P+E	200 - 250 V		9	1/12
GW 66 206 N	3P+N+E	200 - 250 V		9	1/12
GW 66 207 N	2P+E	380 - 415 V		9	1/12
GW 66 208 N	3P+E	380 - 415 V		6	1/12
GW 66 209 N	3P+N+E	380 - 415 V		6	1/12
GW 66 210 N	3P+E	480 - 500 V		7	1/12
GW 66 211 N	3P+N+E	480 - 500 V		7	1/12
Rated current (A): 32					
GW 66 212 N	2P+E	100 - 130 V		4	1/12
GW 66 213 N	3P+E	100 - 130 V		4	1/12
GW 66 214 N	3P+N+E	100 - 130 V		4	1/12
GW 66 215 N	2P+E	200 - 250 V		6	1/12
GW 66 216 N	3P+E	200 - 250 V		9	1/12
GW 66 217 N	3P+N+E	200 - 250 V		9	1/12
GW 66 218 N	2P+E	380 - 415 V		9	1/12
GW 66 219 N	3P+E	380 - 415 V		6	1/12
GW 66 220 N	3P+N+E	380 - 415 V		6	1/12
GW 66 221 N	3P+E	480 - 500 V		7	1/12
GW 66 222 N	3P+N+E	480 - 500 V		7	1/12
GW 66 257 N	3P+E	380 - 440 V		3	1/12

ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 14/16mm.



GW 67 264 N

Interlocked switched vertical socket-outlets with bottom and rotary switch
without fuse-holder base - 63A - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 63					
GW 67 256 N	2P+E	100 - 130 V		4	1/4
GW 67 257 N	3P+E	100 - 130 V		4	1/4
GW 67 258 N	3P+N+E	100 - 130 V		4	1/4
GW 67 259 N	2P+E	200 - 250 V		6	1/4
GW 67 260 N	3P+E	200 - 250 V		9	1/4
GW 67 261 N	3P+N+E	200 - 250 V		9	1/4
GW 67 262 N	2P+E	380 - 415 V		9	1/4
GW 67 263 N	3P+E	380 - 415 V		6	1/4
GW 67 264 N	3P+N+E	380 - 415 V		6	1/4
GW 67 265 N	3P+E	480 - 500 V		7	1/4
GW 67 266 N	3P+N+E	480 - 500 V		7	1/4

ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 25mm.
CHARACTERISTICS: 63A versions equipped with a pilot contact.



GW 66 259 N

Vertical socket-outlets with bottom
with safety transformer (SELV) 230/24V 50/60Hz - IP66 / IP67

Code	No. of poles	Output voltage	Colour	Rated power	Pack Carton
Rated current (A): 16					
GW 66 259 N	2P	20-25 V		160 VA	1/4

CHARACTERISTICS: the socket-outlet is equipped with a thermal protection device. If the device trips, extract the plug from the socket-outlet and check the applied load.
ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 14/16mm.

With rotary switch and fuse-holder base (CBF) without bottom - IP66 / IP67



GW 66 358 N

Interlocked vertical socket-outlets without bottom with rotary switch
 and fuse-holder base - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 16						
GW 66 323 N	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 324 N	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 325 N	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 326 N	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/12
GW 66 327 N	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 328 N	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 329 N	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/12
GW 66 330 N	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 331 N	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 332 N	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 333 N	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
Rated current (A): 32						
GW 66 334 N	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 335 N	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 336 N	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 337 N	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/12
GW 66 338 N	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 339 N	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 340 N	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/12
GW 66 341 N	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 342 N	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 343 N	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 344 N	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 358 N	3P+E	380 - 440 V		Ø 10.3x38 mm	3	1/12

NOTES:
fuses to be purchased separately. Measures for protection of person against electric shock by enclosures.



GW 66 353 N

Interlocked switched vertical socket-outlets without bottom - with rotary switch
 and fuse-holder base - 63A - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 63						
GW 66 345 N	2P+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 66 346 N	3P+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 66 347 N	3P+N+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 66 348 N	2P+E	200 - 250 V		Ø 22x58 mm	6	1/4
GW 66 349 N	3P+E	200 - 250 V		Ø 22x58 mm	9	1/4
GW 66 350 N	3P+N+E	200 - 250 V		Ø 22x58 mm	9	1/4
GW 66 351 N	2P+E	380 - 415 V		Ø 22x58 mm	9	1/4
GW 66 352 N	3P+E	380 - 415 V		Ø 22x58 mm	6	1/4
GW 66 353 N	3P+N+E	380 - 415 V		Ø 22x58 mm	6	1/4
GW 66 354 N	3P+E	480 - 500 V		Ø 22x58 mm	7	1/4
GW 66 355 N	3P+N+E	480 - 500 V		Ø 22x58 mm	7	1/4

NOTES: fuses to be purchased separately. Measures for protection of person against electric shock by enclosures.
CHARACTERISTICS: 63A versions equipped with a pilot contact.

With rotary switch and fuse-holder base (CBF) with bottom - IP66 / IP67



GW 66 258 N

Interlocked vertical socket-outlets with bottom with rotary switch
 and fuse-holder base - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 16						
GW 66 223 N	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 224 N	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 225 N	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 226 N	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/12
GW 66 227 N	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 228 N	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 229 N	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/12
GW 66 230 N	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 231 N	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 232 N	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 233 N	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
Rated current (A): 32						
GW 66 234 N	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 235 N	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 236 N	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/12
GW 66 237 N	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/12
GW 66 238 N	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 239 N	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/12
GW 66 240 N	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/12
GW 66 241 N	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 242 N	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/12
GW 66 243 N	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 244 N	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/12
GW 66 258 N	3P+E	380 - 440 V		Ø 10.3x38 mm	3	1/12

ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 14/16mm.
NOTES: Fuses to be purchased separately. Measures for protection of person against electric shock by enclosures.



GW 67 253 N

Interlocked switched vertical socket-outlets with bottom - with rotary switch
 and fuse-holder base - 63A - 50/60Hz - IP66 / IP67

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 63						
GW 67 245 N	2P+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 67 246 N	3P+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 67 247 N	3P+N+E	100 - 130 V		Ø 22x58 mm	4	1/4
GW 67 248 N	2P+E	200 - 250 V		Ø 22x58 mm	6	1/4
GW 67 249 N	3P+E	200 - 250 V		Ø 22x58 mm	9	1/4
GW 67 250 N	3P+N+E	200 - 250 V		Ø 22x58 mm	9	1/4
GW 67 251 N	2P+E	380 - 415 V		Ø 22x58 mm	9	1/4
GW 67 252 N	3P+E	380 - 415 V		Ø 22x58 mm	6	1/4
GW 67 253 N	3P+N+E	380 - 415 V		Ø 22x58 mm	6	1/4
GW 67 254 N	3P+E	480 - 500 V		Ø 22x58 mm	7	1/4
GW 67 255 N	3P+N+E	480 - 500 V		Ø 22x58 mm	7	1/4

ACCESSORIES SUPPLIED: 4 screwcaps in insulating material, diam. 25mm.
NOTES: fuses to be purchased separately. Measures for protection of person against electric shock by enclosures.
CHARACTERISTICS: 63A versions equipped with a pilot contact.

Components for vertical socket-outlets IP66 / IP67



GW 66 678 N

Surface-mounting boxes for vertical socket-outlets - 16/32A - IP66 / IP67

Code	Houseable interloc. socket	Houseable IB socket-outlets	Top entries	Bottom entries	Pack Carton
GW 66 678 N	1	16/32 A	2xØ 23	1xØ 29/37	1/12

NOTES: GW66678N for socket-outlets with rotary (SBF), with fuse-holder base (CBF) and Automatika 16-32A. Kit of screwcaps GW44622 and wall fixing brackets GW46621 (for double insulation) to be purchased separately.



GW 66 686

Surface-mounting boxes for vertical socket-outlets - 63A - SBF - IP66 / IP67

Code	Houseable interloc. socket	Houseable IB socket-outlets	Top entries	Bottom entries	Pack Carton
GW 66 686	1	63 A	2xØ 29/37	1xØ 37/47	1/10

NOTES: Kit of screwcaps GW44623 and wall fixing brackets GW46621 (for double insulation) to be purchased separately.



GW 66 680 N

Surface-mounting box for vertical socket-outlets - 63A - CBF - IP66 / IP67

Code	Houseable interloc. socket	Houseable IB socket-outlets	Top entries	Bottom entries	Pack Carton
GW 66 680 N	1	63A	2xØ 29/37	1xØ 37/47	1/10

NOTES: Kit of screwcaps GW44623 and wall fixing brackets GW46621 (for double insulation) to be purchased separately.



GW 44 622

Insulating screw caps

Code	Description	Characteristics	Pack Carton
GW 44 622	Screwcap Ø16mm	Halogen free	10/100
GW 44 623	Screwcap Ø25mm	Halogen free	10/100

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.

Wall fixing bracket, complete with self-tapping screws

Code	Characteristics	Pack Carton
GW 44 621	Halogen free	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.



GW 44 621

Surface-mounting box with flanged lid prearranged for 2 caps - IP66 / IP67

Code	Houseable IB socket-outlets	Top entries	Bottom entries	Pack Carton
GW 66 741 N	N. 1 IEC 309 16-32A IP44/67 + N.1 16A MAX 3P+E or GW27401/GW27403	2xØ 23	1xØ 29/37	1/10

APPLICATIONS: The flange of 85x75 mm dimension is suited for mounting IEC 309 16 A socket-outlets and COMBI-IN GW27401 and GW27403 watertight covers; The flange of 95x80 mm dimension is suited for IEC 309 16 -32 A socket-outlets.
ACCESSORIES SUPPLIED: 1 blank flange - blue - 16 A, 1 blank flange - blue 16 -32 A, 3 gaskets and fixing screws.



GW 66 741 N

Surface-mounting box with flanged cover fitted for 2 lids - IP55

Code	Flange dimensions (mm)	Top entries	Bottom entries	Pack Carton
GW 66 742	85x75 - 95x80	2xØ 23	1xØ 29/37	1/10

APPLICATIONS: 75x85 mm dimension is suited for mounting IEC309 16A devices or GW27401 COMBI-IN weatherproof cover.
80x95 mm dimension is suited for mounting IEC309 32A devices.
ACCESSORIES SUPPLIED: blank cap 32A, 2 gaskets and mounting screws.



GW 66 742

Modular bases for mounting combinations of fixed vertical socket-outlets - IP55

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	Pack Carton
GW 66 690	1	16/32 A	2xØ 23	2xØ 23	-	1/6
GW 66 691	2	16/32 A	4xØ 23	4xØ 23	1xØ 29	1/6
GW 66 694	3	16/32 A	2xØ 23	5xØ 23	-	1/6
GW 66 693	1	63 A	6xØ 23	2xØ 37/48	-	1/6

NOTES: the bases for 16-32A can house interlocked switched socket-outlets with rotary (SBF), fuse-holder base (CBF) or Automatika.
ACCESSORIES SUPPLIED: 1 coupling device for combined assembly and 4 screwcaps for restoring double insulation.
GW66694: 1 blank lid for closing the socket-outlet compartment.
GW66693: already supplied with adapter for new 67IB 63A socket-outlets SBF/CBF.



GW 66 690

Box with frame for the flush-mounting assembly of fixed vertical socket-outlets - IP55

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 683 N	1	16/32 A SBF / CBF / Automatika	For brick wall	1/10

NOTES: the box cannot house the version with a 24 V transformer.



GW 66 683 N



GW 66 683 PM

Box with frame for lightweight and plasterboard walls, for the flush-mounting assembly of vertical socket-outlets - IP55

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 683 PM	1	16/32 A SBF / CBF / Automatika	For plasterboard	1/10

NOTES: the box cannot house the version with a 24V transformer.
Halogen-free casing, in accordance with EN 60754-2.
Casing type H in accordance with EN 60670-1, and type Ha in accordance with IEC 60670-1.
GWT 850°C according to EN 60695-2-11.
CHARACTERISTICS: locators for tracing the wall along the edges of the box; box equipped with tabs for direct fixing on panels or a metal structure, for lightweight and plasterboard walls.
ACCESSORIES SUPPLIED: self-tapping screw kit ø 4x45mm.



GW 66 743 N

Boxes with frame for flush-mounting with flanged cover fitted for 2 lids - IP55

Code	Houseable IB socket-outlets	Pack Carton
GW 66 743 N	N. 1 IEC 309 16-32A IP44/67 + N.1 16A MAX 3P+E or GW27401/GW27403	1/10

APPLICATIONS: the flange of 85x75 mm dimension is suited for mounting IEC 309 16 A socket-outlets and COMBI-IN GW27401 and GW27403 flange; the flange of 95x80 mm dimension is suited for IEC 309 16 -32 A socket-outlets.
ACCESSORIES SUPPLIED: 1 blank flange - blue - 16 A; 1 blank flange - blue 16 -32 A; 3 gaskets and fixing screws.



GW 66 703 N

Blank lid for closing interlocked socket-outlet compartment 16- 32A - IP65

Code	Description	Pack Carton
GW 66 703 N	Lid for vertical interlocked socket-outlet 16-32A	1/10
GW 66 705 N	Lid for vertical interlocked socket-outlet 63A	1/10

APPLICATIONS: also compatible with flush-mounting boxes for brick walls (code GW66683N) and lightweight and plasterboard walls (code GW66683PM).



GW 66 709 N

Flanged lid prearranged for 2 caps - IP67

Code	Houseable IB socket-outlets	Pack Carton
GW 66 709 N	N. 1 IEC 309 16-32A IP44/67 + N.1 16A MAX 3P+E or GW27401/GW27403	1/10

APPLICATIONS: the flange of 85x75 mm dimension is suited for mounting IEC 309 16 A socket-outlets and COMBI-IN GW27401 and GW27403 flange; the flange of 95x80 mm dimension is suited for IEC 309 16 -32 A socket-outlets.
ACCESSORIES SUPPLIED: 1 blank flange - blue - 16 A; 1 blank flange - blue 16 -32 A; 3 gaskets and fixing screws.

Adapter flange IP65



GW 66 715 N

Code	Suitable for	Pack Carton
GW 66 715 N	IP67 16/32A vertical socket-outlets	1/10
GW 66 716 N	IP67 63A Vertical socket-outlets	1/10

APPLICATIONS: GW66715N to assemble all the vertical socket-outlets 16-32A IP67 of the 67 IB range on the Q-DIN boards, or on the modular bases of the previous versions for socket-outlets 16-32A CBF IP55. GW66716N to assemble the vertical socket-outlets 63A IP67 of the 67 IB range on the modular bases of the previous versions for socket-outlets 63A CBF IP55.

Distribution pillar for floor-mounting and work surfaces - IP55



GW 68 441

Code	Outer dim. LxHxD (mm)	Houseable IB socket-outlets	Installable Q-DIN boards	Characteristics	Pack Carton
GW 68 441	200x295x180	16/32 A	Q-DIN 5	Halogen free	1/6

CHARACTERISTICS: double-sided panels double-sided panels with smooth or honeycomb surface for fixing interlocked switched socket-outlets 16/32A of the IB range: Combibloc, horizontal IP44 with bottom and vertical IP67 with bottom.


Distribution boards for vertical socket-outlets - IP65




GW 68 025N



GW 68 010N



GW 68 015N



GW 68 022N

Q-DIN 10/14/20 watertight boards - unwired - RAL 7035 - IP65



GW 68 025 N

Code	No. IB socket-outlets houseable	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 10					
GW 68 025 N	2 IB Vert. 16-32A IP67	1 IB 16/32A	16	42	6
No. of modules EN 50022: 14					
GW 68 010 N	3 IB Vert. 16/32A IP67	1 IB 16/32A	24	64	3
No. of modules EN 50022: 20					
GW 68 015 N	4IB 16/32A IP67 + 4 IEC MAX 3P+E 16A	2 IB 16/32A + 4 IEC 16A	30	92	2
GW 68 022 N	1 IB Vert. 63A IP67 + 2 IB Vert. 16/32A IP67	1 IB 16/32A	30	92	2

ACCESSORIES SUPPLIED: cable clamp and 4/6 screwcaps.

NOTES: dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board.

GW68015N: the 4 flanges - measuring 85x75 - can be equipped with the COMBI-IN GW27401 and GW27403 watertight covers.

The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.

External dimensions GW68025N (LxHxD): 220x435x96.

External dimensions GW68010N (LxHxD): 320x360x120.

External dimensions GW68015N and GW68022N (LxHxD): 450x560x120.

66 IB - HEAVY DUTY, VERTICAL WATERTIGHT INTERLOCKED SOCKET-OUTLETS

Without bottom and without fuse-holder base - IP66



GW 66 542

Vertical interlocked socket-outlets - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 535	2P+E	100 - 130 V		4	1/6
GW 66 536	3P+E	100 - 130 V		4	1/6
GW 66 537	3P+N+E	100 - 130 V		4	1/6
GW 66 538	2P+E	200 - 250 V		6	1/6
GW 66 539	3P+E	200 - 250 V		9	1/6
GW 66 540	3P+N+E	200 - 250 V		9	1/6
GW 66 541	2P+E	380 - 415 V		9	1/6
GW 66 542	3P+E	380 - 415 V		6	1/6
GW 66 543	3P+N+E	380 - 415 V		6	1/6
GW 66 544	3P+E	480 - 500 V		7	1/6
GW 66 545	3P+N+E	480 - 500 V		7	1/6
Rated current (A): 32					
GW 66 546	2P+E	100 - 130 V		4	1/6
GW 66 547	3P+E	100 - 130 V		4	1/6
GW 66 548	3P+N+E	100 - 130 V		4	1/6
GW 66 549	2P+E	200 - 250 V		6	1/6
GW 66 550	3P+E	200 - 250 V		9	1/6
GW 66 551	3P+N+E	200 - 250 V		9	1/6
GW 66 552	2P+E	380 - 415 V		9	1/6
GW 66 553	3P+E	380 - 415 V		6	1/6
GW 66 554	3P+N+E	380 - 415 V		6	1/6
GW 66 555	3P+E	480 - 500 V		7	1/6
GW 66 556	3P+N+E	480 - 500 V		7	1/6
GW 66 557	3P+E	380 - 440 V		3	1/6

CHARACTERISTICS: IK10, in compliance with EN 62262.

With bottom and without fuse-holder base - IP66



GW 66 508

Vertical interlocked socket-outlets - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 501	2P+E	100 - 130 V		4	1/6
GW 66 502	3P+E	100 - 130 V		4	1/6
GW 66 503	3P+N+E	100 - 130 V		4	1/6
GW 66 504	2P+E	200 - 250 V		6	1/6
GW 66 505	3P+E	200 - 250 V		9	1/6
GW 66 506	3P+N+E	200 - 250 V		9	1/6
GW 66 507	2P+E	380 - 415 V		9	1/6
GW 66 508	3P+E	380 - 415 V		6	1/6
GW 66 509	3P+N+E	380 - 415 V		6	1/6
GW 66 510	3P+E	480 - 500 V		7	1/6
GW 66 511	3P+N+E	480 - 500 V		7	1/6
Rated current (A): 32					
GW 66 512	2P+E	100 - 130 V		4	1/6
GW 66 513	3P+E	100 - 130 V		4	1/6
GW 66 514	3P+N+E	100 - 130 V		4	1/6
GW 66 515	2P+E	200 - 250 V		6	1/6
GW 66 516	3P+E	200 - 250 V		9	1/6
GW 66 517	3P+N+E	200 - 250 V		9	1/6
GW 66 518	2P+E	380 - 415 V		9	1/6
GW 66 519	3P+E	380 - 415 V		6	1/6
GW 66 520	3P+N+E	380 - 415 V		6	1/6
GW 66 521	3P+E	480 - 500 V		7	1/6
GW 66 522	3P+N+E	480 - 500 V		7	1/6
GW 66 523	3P+E	380 - 440 V		3	1/6
Rated current (A): 63					
GW 66 524	2P+E	100 - 130 V		4	1/3
GW 66 525	3P+E	100 - 130 V		4	1/3
GW 66 526	3P+N+E	100 - 130 V		4	1/3
GW 66 527	2P+E	200 - 250 V		6	1/3
GW 66 528	3P+E	200 - 250 V		9	1/3
GW 66 529	3P+N+E	200 - 250 V		9	1/3
GW 66 530	2P+E	380 - 415 V		9	1/3
GW 66 531	3P+E	380 - 415 V		6	1/3
GW 66 532	3P+N+E	380 - 415 V		6	1/3
GW 66 533	3P+E	480 - 500 V		7	1/3
GW 66 534	3P+N+E	480 - 500 V		7	1/3

CHARACTERISTICS: IK10, in compliance with EN 62262. 63A versions equipped with a pilot contact.

Without bottom for mounting modular devices - IP66



GW 66 831

Vertical interlocked socket-outlets for mounting modular devices - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 824	2P+E	100 - 130 V		4	1/6
GW 66 825	3P+E	100 - 130 V		4	1/6
GW 66 826	3P+N+E	100 - 130 V		4	1/6
GW 66 827	2P+E	200 - 250 V		6	1/6
GW 66 828	3P+E	200 - 250 V		9	1/6
GW 66 829	3P+N+E	200 - 250 V		9	1/6
GW 66 830	2P+E	380 - 415 V		9	1/6
GW 66 831	3P+E	380 - 415 V		6	1/6
GW 66 832	3P+N+E	380 - 415 V		6	1/6
GW 66 833	3P+E	480 - 500 V		7	1/6
GW 66 834	3P+N+E	480 - 500 V		7	1/6
Rated current (A): 32					
GW 66 835	2P+E	100 - 130 V		4	1/6
GW 66 836	3P+E	100 - 130 V		4	1/6
GW 66 837	3P+N+E	100 - 130 V		4	1/6
GW 66 838	2P+E	200 - 250 V		6	1/6
GW 66 839	3P+E	200 - 250 V		9	1/6
GW 66 840	3P+N+E	200 - 250 V		9	1/6
GW 66 841	2P+E	380 - 415 V		9	1/6
GW 66 842	3P+E	380 - 415 V		6	1/6
GW 66 843	3P+N+E	380 - 415 V		6	1/6
GW 66 844	3P+E	480 - 500 V		7	1/6
GW 66 845	3P+N+E	480 - 500 V		7	1/6
GW 66 846	3P+E	380 - 440 V		3	1/6

CHARACTERISTICS: pre-arrangement for 6 DIN EN 50022 modules. IK10, in compliance with EN 62262.

With bottom for mounting modular devices - IP66



GW 66 981

Vertical interlocked socket-outlets for mounting modular devices - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 974	2P+E	100 - 130 V		4	1/6
GW 66 975	3P+E	100 - 130 V		4	1/6
GW 66 976	3P+N+E	100 - 130 V		4	1/6
GW 66 977	2P+E	200 - 250 V		6	1/6
GW 66 978	3P+E	200 - 250 V		9	1/6
GW 66 979	3P+N+E	200 - 250 V		9	1/6
GW 66 980	2P+E	380 - 415 V		9	1/6
GW 66 981	3P+E	380 - 415 V		6	1/6
GW 66 982	3P+N+E	380 - 415 V		6	1/6
GW 66 983	3P+E	480 - 500 V		7	1/6
GW 66 984	3P+N+E	480 - 500 V		7	1/6
Rated current (A): 32					
GW 66 985	2P+E	100 - 130 V		4	1/6
GW 66 986	3P+E	100 - 130 V		4	1/6
GW 66 987	3P+N+E	100 - 130 V		4	1/6
GW 66 988	2P+E	200 - 250 V		6	1/6
GW 66 989	3P+E	200 - 250 V		9	1/6
GW 66 990	3P+N+E	200 - 250 V		9	1/6
GW 66 991	2P+E	380 - 415 V		9	1/6
GW 66 992	3P+E	380 - 415 V		6	1/6
GW 66 993	3P+N+E	380 - 415 V		6	1/6
GW 66 994	3P+E	480 - 500 V		7	1/6
GW 66 995	3P+N+E	480 - 500 V		7	1/6
GW 66 996	3P+E	380 - 440 V		3	1/6
Rated current (A): 63					
GW 66 866	2P+E	100 - 130 V		4	1/3
GW 66 867	3P+E	100 - 130 V		4	1/3
GW 66 868	3P+N+E	100 - 130 V		4	1/3
GW 66 869	2P+E	200 - 250 V		6	1/3
GW 66 870	3P+E	200 - 250 V		9	1/3
GW 66 871	3P+N+E	200 - 250 V		9	1/3
GW 66 872	2P+E	380 - 415 V		9	1/3
GW 66 873	3P+E	380 - 415 V		6	1/3
GW 66 874	3P+N+E	380 - 415 V		6	1/3
GW 66 875	3P+E	480 - 500 V		7	1/3
GW 66 876	3P+N+E	480 - 500 V		7	1/3

CHARACTERISTICS: pre-arrangement for 6 DIN EN 50022 modules. IK10, in compliance with EN 62262. 63A versions equipped with a pilot contact.

Without bottom with fuse holder base - IP66



GW 66 808

Vertical interlocked socket-outlets and fuse holder base - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 16						
GW 66 801	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 802	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 803	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 804	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/6
GW 66 805	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 806	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 807	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/6
GW 66 808	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 809	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 810	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 811	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
Rated current (A): 32						
GW 66 812	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 813	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 814	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 815	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/6
GW 66 816	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 817	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 818	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/6
GW 66 819	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 820	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 821	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 822	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 823	3P+E	380 - 440 V		Ø 10.3x38 mm	3	1/6

CHARACTERISTICS: IK10, in compliance with EN 62262.



GW 66 886

Vertical socket-outlet with safety transformer (SELV) 230V / 24V - 50/60Hz - IP66

Code	No. of poles	Output voltage	Colour	Rated power	Type of fuse	Pack Carton
Rated current (A): 16						
GW 66 886	2P	20-25 V		160 VA	Ø 10.3x38 mm	1/4

CHARACTERISTICS: the socket-outlet is equipped with a thermal protection device. If the device trips, extract the plug from the socket-outlet and check the applied load. IK10, in compliance with EN 62262.
ACCESSORIES SUPPLIED: fuses (2A for primary and 6A for secondary).

With bottom with fuse holder base - IP66



GW 66 958

Vertical interlocked socket-outlets and fuse holder base - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Type of fuse	Reference h	Pack Carton
Rated current (A): 16						
GW 66 951	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 952	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 953	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 954	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/6
GW 66 955	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 956	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 957	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/6
GW 66 958	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 959	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 960	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 961	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
Rated current (A): 32						
GW 66 962	2P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 963	3P+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 964	3P+N+E	100 - 130 V		Ø 10.3x38 mm	4	1/6
GW 66 965	2P+E	200 - 250 V		Ø 10.3x38 mm	6	1/6
GW 66 966	3P+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 967	3P+N+E	200 - 250 V		Ø 10.3x38 mm	9	1/6
GW 66 968	2P+E	380 - 415 V		Ø 10.3x38 mm	9	1/6
GW 66 969	3P+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 970	3P+N+E	380 - 415 V		Ø 10.3x38 mm	6	1/6
GW 66 971	3P+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 972	3P+N+E	480 - 500 V		Ø 10.3x38 mm	7	1/6
GW 66 973	3P+E	380 - 440 V		Ø 10.3x38 mm	3	1/6
Rated current (A): 63						
GW 66 847	2P+E	100 - 130 V		Ø 22x58 mm	4	1/3
GW 66 848	3P+E	100 - 130 V		Ø 22x58 mm	4	1/3
GW 66 849	3P+N+E	100 - 130 V		Ø 22x58 mm	4	1/3
GW 66 850	2P+E	200 - 250 V		Ø 22x58 mm	6	1/3
GW 66 851	3P+E	200 - 250 V		Ø 22x58 mm	9	1/3
GW 66 852	3P+N+E	200 - 250 V		Ø 22x58 mm	9	1/3
GW 66 853	2P+E	380 - 415 V		Ø 22x58 mm	9	1/3
GW 66 854	3P+E	380 - 415 V		Ø 22x58 mm	6	1/3
GW 66 855	3P+N+E	380 - 415 V		Ø 22x58 mm	6	1/3
GW 66 856	3P+E	480 - 500 V		Ø 22x58 mm	7	1/3
GW 66 857	3P+N+E	480 - 500 V		Ø 22x58 mm	7	1/3

CHARACTERISTICS: IK10, in compliance with EN 62262. 63A versions equipped with a pilot contact.



GW 66 998

Vertical socket-outlet with safety transformer (SELV) - 230V / 24V - 50Hz - IP66

Code	No. of poles	Output voltage	Colour	Rated power	Type of fuse	Pack Carton
Rated current (A): 16						
GW 66 998	2P	20-25 V		160 VA	Ø 10.3x38 mm	1/4

CHARACTERISTICS: the socket-outlet is equipped with a thermal protection device. If the device trips, extract the plug from the socket-outlet and check the applied load. IK10, in compliance with EN 62262.
ACCESSORIES SUPPLIED: fuses (2A for primary and 6A for secondary).

Complementary items for interlocked socket-outlets - IP66



GW 66 685

Surface-mounting bottom for vertical fixed socket-outlets for heavy-duty use IP66

Code	Houseable interloc. socket	Houseable IB socket-outlets	Pack Carton
GW 66 685	1	16/32 A SELV	1/10

CHARACTERISTICS: Equipped with top and bottom centres to make the holes for mounting the cable glands PG 21 / 29.



GW 66 700

Modular bases for combination mounting of vertical socket-outlets for heavy-duty use - IP66

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	Pack Carton
GW 66 696	1	16/32 A SELV	2xØ 23	2xØ 23/29	-	1/6
GW 66 697	2	16/32 A SELV	4xØ 23	4xØ 23/29	1xØ 29/37	1/2
GW 66 698	3	16/32 A SELV	2xØ 23	5xØ 23/29	1xØ 29/37	1/2
GW 66 700	1	63 A	6xØ 23	2xØ 37/48	-	1/6

NOTES: Installation of the 63 A version is possible after removal of the socket-outlet base.
ACCESSORIES SUPPLIED: GW66698: 1 blank lid for closing the socket-outlet compartment.



GW 66 781

Modular bases with panel and with window with EN 50022 din rail - IP66

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	No. of modules EN 50022	Dispersible power (W)	Pack Carton
GW 66 781	1	16/32 A SELV	2xØ 23	2xØ 23/29	-	6	18	1/6
GW 66 782	2	16/32 A SELV	4xØ 23	4xØ 23/29	1xØ 29/37	12	27	1/2
GW 66 783	3	16/32 A SELV	2xØ 23	5xØ 23/29	1xØ 29/37	18	34	1/2
GW 66 784	1	63 A	6xØ 23	2xØ 37/48	-	6	18	1/6

CHARACTERISTICS: Possibility of installing security cylinder lock GW40422 (supplied with 2 keys).
Installation of the 63 A version is possible after removal of the socket-outlet base.
ACCESSORIES SUPPLIED: GW66783: 1 blank lid for closing the socket-outlet compartment.



GW 66 706

Blank lid vertical fixed socket-outlet compartment for heavy-duty use - IP66

Code	For Modular bases	For back boxes	Pack Carton
GW 66 706	GW66696 - GW66697 - GW66698 - GW66781 - GW66782 - GW66783	GW66685	1/10



GW 66 707

Flanged lid fitted for 2 covers - IP66

Code	Houseable IB socket-outlets	Pack Carton
GW 66 707	Nr 2 IEC 309 16-32A IP44/67	1/10

APPLICATIONS: possibility of assembly on modular bases GW66696 - GW66697 - GW66698 - GW66781 - GW66782 - GW66783 and back-mounting box GW66685.
The flange of 85x75 mm dimension is suited for mounting IEC 309 16 A socket-outlets and COMBI-IN GW27401 and GW27403 watertight covers.
The flange of 95x80 mm dimension is suited for mounting IEC 309 32 A socket-outlets.
ACCESSORIES SUPPLIED: 1 blank flange 16-32A, 1 gasket and fixing screws.

66 IB - VERTICAL SOCKET-OUTLETS ELECTRICAL INTERLOCKED FOR HEAVY-DUTY

With miniature circuit breaker - IP66



GW 66 585

Watertight vertical surface-mounting socket-outlets with electric interlock Circuit breaker protection - 125A - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (InA): 110					
GW 66 581	3P+E	100 - 130 V		4	1
GW 66 582	3P+N+E	100 - 130 V		4	1
GW 66 583	3P+E	200 - 250 V		9	1
GW 66 584	3P+N+E	200 - 250 V		9	1
GW 66 585	3P+E	380 - 415 V		6	1
GW 66 586	3P+N+E	380 - 415 V		6	1

CHARACTERISTICS: miniature circuit breaker: In= 125A, C curve, Icu (380/415V)= 25kA, electrical life= 8,000 cycles; mechanical life= 25,000 cycles; Insulating voltage Ui= 690V;
Terminal capacity: flexible cables: 2.5-50 mm², rigid cables: 2.5-70 mm².
125A versions equipped with 1 NO clean contact.

With residual current miniature circuit breaker - IP66



GW 66 595

Watertight vertical surface-mounting socket-outlets with electric interlock Residual current circuit breaker protection - 125A - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (InA): 110					
GW 66 591	3P+E	100 - 130 V		4	1
GW 66 592	3P+N+E	100 - 130 V		4	1
GW 66 593	3P+E	200 - 250 V		9	1
GW 66 594	3P+N+E	200 - 250 V		9	1
GW 66 595	3P+E	380 - 415 V		6	1
GW 66 596	3P+N+E	380 - 415 V		6	1

CHARACTERISTICS: residual current circuit breaker In= 125A, class A, Sensitivity= adjustable 30-3,000mA instantaneous and selective, Insulating voltage Ui= 690V.
Terminal capacity: flexible cables: 2.5-50 mm², rigid cables: 2.5-70 mm².
125A versions equipped with 1 NO clean contact.

44 IB - HORIZONTAL PROTECTED INTERLOCKED SOCKET-OUTLETS

Without bottom, without fuse-holder base - IP44



GW 66 108

Horizontal interlocked socket outlets - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 101	2P+E	100 - 130 V		4	1/12
GW 66 102	3P+E	100 - 130 V		4	1/12
GW 66 103	3P+N+E	100 - 130 V		4	1/12
GW 66 104	2P+E	200 - 250 V		6	1/12
GW 66 105	3P+E	200 - 250 V		9	1/12
GW 66 106	3P+N+E	200 - 250 V		9	1/12
GW 66 107	2P+E	380 - 415 V		9	1/12
GW 66 108	3P+E	380 - 415 V		6	1/12
GW 66 109	3P+N+E	380 - 415 V		6	1/12
GW 66 110	3P+E	480 - 500 V		7	1/12
GW 66 111	3P+N+E	480 - 500 V		7	1/12
Rated current (A): 32					
GW 66 112	2P+E	100 - 130 V		4	1/12
GW 66 113	3P+E	100 - 130 V		4	1/12
GW 66 114	3P+N+E	100 - 130 V		4	1/12
GW 66 115	2P+E	200 - 250 V		6	1/12
GW 66 116	3P+E	200 - 250 V		9	1/12
GW 66 117	3P+N+E	200 - 250 V		9	1/12
GW 66 118	2P+E	380 - 415 V		9	1/12
GW 66 119	3P+E	380 - 415 V		6	1/12
GW 66 120	3P+N+E	380 - 415 V		6	1/12
GW 66 121	3P+E	480 - 500 V		7	1/12
GW 66 122	3P+N+E	480 - 500 V		7	1/12

With bottom, without fuse-holder base - IP44



GW 66 004

Horizontal interlocked socket outlets - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 001	2P+E	100 - 130 V		4	1/12
GW 66 002	3P+E	100 - 130 V		4	1/12
GW 66 003	3P+N+E	100 - 130 V		4	1/12
GW 66 004	2P+E	200 - 250 V		6	1/12
GW 66 005	3P+E	200 - 250 V		9	1/12
GW 66 006	3P+N+E	200 - 250 V		9	1/12
GW 66 007	2P+E	380 - 415 V		9	1/12
GW 66 008	3P+E	380 - 415 V		6	1/12
GW 66 009	3P+N+E	380 - 415 V		6	1/12
GW 66 010	3P+E	480 - 500 V		7	1/12
GW 66 011	3P+N+E	480 - 500 V		7	1/12
Rated current (A): 32					
GW 66 012	2P+E	100 - 130 V		4	1/12
GW 66 013	3P+E	100 - 130 V		4	1/12
GW 66 014	3P+N+E	100 - 130 V		4	1/12
GW 66 015	2P+E	200 - 250 V		6	1/12
GW 66 016	3P+E	200 - 250 V		9	1/12
GW 66 017	3P+N+E	200 - 250 V		9	1/12
GW 66 018	2P+E	380 - 415 V		9	1/12
GW 66 019	3P+E	380 - 415 V		6	1/12
GW 66 020	3P+N+E	380 - 415 V		6	1/12
GW 66 021	3P+E	480 - 500 V		7	1/12
GW 66 022	3P+N+E	480 - 500 V		7	1/12

ACCESSORIES SUPPLIED: coupling for Ø 20 mm conduits and Ø 23 mm cable gland.

Without bottom, with fuse-holder base - IP44



GW 66 130

Horizontal interlocked socket outlets with fuse holder base - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Fuses holder	Reference h	Pack Carton
Rated current (A): 16						
GW 66 123	2P+E	100 - 130 V		E14	4	1/12
GW 66 124	3P+E	100 - 130 V		E14	4	1/12
GW 66 125	3P+N+E	100 - 130 V		E14	4	1/12
GW 66 126	2P+E	200 - 250 V		E14	6	1/12
GW 66 127	3P+E	200 - 250 V		E14	9	1/12
GW 66 128	3P+N+E	200 - 250 V		E14	9	1/12
GW 66 129	2P+E	380 - 415 V		E14	9	1/12
GW 66 130	3P+E	380 - 415 V		E14	6	1/12
GW 66 131	3P+N+E	380 - 415 V		E14	6	1/12
GW 66 132	3P+E	480 - 500 V		gG	7	1/12
GW 66 133	3P+N+E	480 - 500 V		gG	7	1/12
Rated current (A): 32						
GW 66 134	2P+E	100 - 130 V		E18	4	1/12
GW 66 135	3P+E	100 - 130 V		E18	4	1/12
GW 66 136	3P+N+E	100 - 130 V		E18	4	1/12
GW 66 137	2P+E	200 - 250 V		E18	6	1/12
GW 66 138	3P+E	200 - 250 V		E18	9	1/12
GW 66 139	3P+N+E	200 - 250 V		E18	9	1/12
GW 66 140	2P+E	380 - 415 V		E18	9	1/12
GW 66 141	3P+E	380 - 415 V		E18	6	1/12
GW 66 142	3P+N+E	380 - 415 V		E18	6	1/12
GW 66 143	3P+E	480 - 500 V		gG	7	1/12
GW 66 144	3P+N+E	480 - 500 V		gG	7	1/12

CHARACTERISTIC: compatible with ND fuses, except for versions 16A - 500V that have to accomodate GG cylindrical fuses ø 10,3x38 mm and version 32A - 500V that have to accommodate GG cylindrical fuses ø 14x51 mm.

With bottom, with fuse-holder base - IP44



GW 66 026

Horizontal interlocked socket outlets with fuse holder base - 50/60Hz

Code	No. of poles	Rated voltage	Colour	Fuses holder	Reference h	Pack Carton
Rated current (A): 16						
GW 66 023	2P+E	100 - 130 V		E14	4	1/12
GW 66 024	3P+E	100 - 130 V		E14	4	1/12
GW 66 025	3P+N+E	100 - 130 V		E14	4	1/12
GW 66 026	2P+E	200 - 250 V		E14	6	1/12
GW 66 027	3P+E	200 - 250 V		E14	9	1/12
GW 66 028	3P+N+E	200 - 250 V		E14	9	1/12
GW 66 029	2P+E	380 - 415 V		E14	9	1/12
GW 66 030	3P+E	380 - 415 V		E14	6	1/12
GW 66 031	3P+N+E	380 - 415 V		E14	6	1/12
GW 66 032	3P+E	480 - 500 V		gG	7	1/12
GW 66 033	3P+N+E	480 - 500 V		gG	7	1/12
Rated current (A): 32						
GW 66 034	2P+E	100 - 130 V		E18	4	1/12
GW 66 035	3P+E	100 - 130 V		E18	4	1/12
GW 66 036	3P+N+E	100 - 130 V		E18	4	1/12
GW 66 037	2P+E	200 - 250 V		E18	6	1/12
GW 66 038	3P+E	200 - 250 V		E18	9	1/12
GW 66 039	3P+N+E	200 - 250 V		E18	9	1/12
GW 66 040	2P+E	380 - 415 V		E18	9	1/12
GW 66 041	3P+E	380 - 415 V		E18	6	1/12
GW 66 042	3P+N+E	380 - 415 V		E18	6	1/12
GW 66 043	3P+E	480 - 500 V		gG	7	1/12
GW 66 044	3P+N+E	480 - 500 V		gG	7	1/12

ACCESSORIES SUPPLIED: coupling for Ø 20 mm and Ø 25 mm conduits and Ø 29 mm cable gland.
CHARACTERISTIC: compatible with ND fuses, except for versions 16A - 500V that have to accomodate GG cylindrical fuses ø 10,3x38 mm and version 32A - 500V that have to accommodate GG cylindrical fuses ø 14x51 mm.


Complementary items for socket-outlets without fuse-holder base - SBF - IP44



GW 66 676

Surface-mounting box for fixed horizontal socket-outlets - SBF - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	Pack Carton
GW 66 676	1	16/32 A	4xØ 23	3xØ 23	3xØ 23	1/10



GW 66 681

Box with frame for the flush-mounting assembly of fixed horizontal socket-outlets SBF - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 681	1	16/32 A	For brick wall	1/10



GW 66 681 PM

Box with frame for lightweight and plasterboard walls for the flush-mounting assembly of horizontal socket-outlets SBF - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 681 PM	1	16/32 A	For plasterboard	1/10

NOTES: Halogen-free casing, in accordance with EN 60754-2.
Casing type H in accordance with EN 60670-1, and type Ha in accordance with IEC 60670-1.
GWT 850°C according to EN 60695-2-11.
CHARACTERISTICS: locators for tracing the wall along the edges of the box; box equipped with tabs for direct fixing on panels or a metal structure, for lightweight and plasterboard walls.
ACCESSORIES SUPPLIED: self-tapping screw kit ø 4x45mm.



GW 66 701

Blank lid for the compartment containing fixed horizontal socket-outlets - SBF - IP44

Code	For distribution boards	For back boxes	For flush-mounting boxes	Pack Carton
GW 66 701	GW68006N/09N/19N	GW66676	GW66681 - GW66681PM	1/10



GW 68 441

Floor mounting and workbench tower - IP55

Code	Outer dim. LxHxD (mm)	Houseable IB socket-outlets	Installable Q-DIN boards	Characteristics	Pack Carton
GW 68 441	200x295x180	16/32 A	Q-DIN 5	Halogen free	1/6

CHARACTERISTICS: contrasting flanges with smooth and honeycomb surface, for fixing interlocked switched socket-outlets 16-32A of the IB range: Combibloc, horizontal socket-outlets IP44 with bottom and vertical socket-outlets IP67 with bottom.
APPLICATIONS: installed combined using the coupler GW26406.

Distribution boards for socket-outlets without fuse-holder base - SBF - IP65



GW 68 019N



GW 68 006N



GW 68 009N



GW 68 006 N

Q-DIN 10/14 watertight boards - unwired - RAL 7035 - IP65

Code	No. IB socket-outlets houseable	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 10					
GW 68 019 N	2 IB Horiz. 16/32A SBF IP44 overlapping	1 IB 16/32A	16	42	6
No. of modules EN 50022: 14					
GW 68 006 N	2 IB Horiz. 16/32A SBF IP44 side by side	1 IB 16/32A	24	64	4
GW 68 009 N	4 IB Horiz. 16/32A SBF IP44	2 IB 16/32A	24	64	3

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.
NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board.
The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.
External dimensions GW68019N (LxHxD): 220x435x96.
External dimensions GW68006N (LxHxD): 320x360x120.
External dimensions GW68009N (LxHxD): 320x510x120.


Complementary items for socket-outlets with fuse-holder base - CBF - IP44



GW 66 677

Surface-mounting bottom - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	Pack Carton
GW 66 677	1	16/32 A	4xØ 23	2xØ 23 - 1xØ 29	2xØ 23 - 1xØ 29	1/10



GW 66 682

Box with frame for flush-mounting fixed horizontal socket-outlets - CBF - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 682	1	16/32 A	For brick wall	1/10



GW 66 682 PM

Box with frame for lightweight and plasterboard walls for the flush-mounting assembly of horizontal socket-outlets CBF - IP44

Code	Houseable interloc. socket	Houseable IB socket-outlets	Characteristics	Pack Carton
GW 66 682 PM	1	16/32 A	For plasterboard	1/10

NOTES: Halogen-free casing, in accordance with EN 60754-2.
Casing type H in accordance with EN 60670-1, and type Ha in accordance with IEC 60670-1.
GWT 850°C in accordance with EN 60695-2-11.
CHARACTERISTICS: locators for tracing the wall along the edges of the box; box equipped with tabs for direct fixing on panels or a metal structure, for lightweight and plasterboard walls.
ACCESSORIES SUPPLIED: self-tapping screw kit ø 4x45mm.



GW 66 702

Blank lid for the compartment containing fixed horizontal socket-outlets - CBF - IP44

Code	For distribution boards	For back boxes	For flush-mounting boxes	Pack Carton
GW 66 702	GW68014N	GW66677	GW66682 - GW66682PM	1/10



GW 68 441


Floor mounting and workbench tower - IP55

Code	Outer dim. LxHxD (mm)	Houseable IB socket-outlets	Installable Q-DIN boards	Characteristics	Pack Carton
GW 68 441	200x295x180	16/32 A	Q-DIN 5	Halogen free	1/6

CHARACTERISTICS: contrasting flanges with smooth and honeycomb surface, for fixing interlocked switched socket-outlets 16-32A of the IB range: Combibloc, horizontal socket-outlets IP44 with bottom and vertical socket-outlets IP67 with bottom.

APPLICATIONS: installed combined using the coupler GW26406.

Distribution boards for socket-outlets with fuse-holder base - CBF - IP65



GW 68 014N



GW 68 014 N

Q-DIN 20 watertight board - unwired - RAL 7035 - IP65

Code	No. IB socket-outlets houseable	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 20					
GW 68 014 N	4 IB Horiz. 16/32A CBF IP44	2 IB 16/32A	30	92	2

ACCESSORIES SUPPLIED: cable clamp and 6 screw caps.

NOTES: dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board.

The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.

External dimensions (LxHxD): 450x560x120.

COMBIBLOC - COMPACT, PROTECTED AND WATERTIGHT INTERLOCKED SOCKET-OUTLETS

Without bottom and without fuse-holder base - IP44



GW 66 441

Compact interlocked socket-outlets - 50/60 Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 423	2P+E	100 - 130 V		4	1/12
GW 66 424	3P+E	100 - 130 V		4	1/12
GW 66 425	3P+N+E	100 - 130 V		4	1/12
GW 66 426	2P+E	200 - 250 V		6	1/12
GW 66 427	3P+E	200 - 250 V		9	1/12
GW 66 428	3P+N+E	200 - 250 V		9	1/12
GW 66 429	2P+E	380 - 415 V		9	1/12
GW 66 430	3P+E	380 - 415 V		6	1/12
GW 66 431	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 434	2P+E	100 - 130 V		4	1/12
GW 66 435	3P+E	100 - 130 V		4	1/12
GW 66 436	3P+N+E	100 - 130 V		4	1/12
GW 66 437	2P+E	200 - 250 V		6	1/12
GW 66 438	3P+E	200 - 250 V		9	1/12
GW 66 439	3P+N+E	200 - 250 V		9	1/12
GW 66 440	2P+E	380 - 415 V		9	1/12
GW 66 441	3P+E	380 - 415 V		6	1/12
GW 66 442	3P+N+E	380 - 415 V		6	1/12

CHARACTERISTICS: the interlock lever can be padlocked in the ON/OFF position using the security lock GW40422.

With bottom and without fuse-holder base - IP44



GW 66 404

Compact interlocked socket-outlets - 50/60 Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 401	2P+E	100 - 130 V		4	1/12
GW 66 402	3P+E	100 - 130 V		4	1/12
GW 66 403	3P+N+E	100 - 130 V		4	1/12
GW 66 404	2P+E	200 - 250 V		6	1/12
GW 66 405	3P+E	200 - 250 V		9	1/12
GW 66 406	3P+N+E	200 - 250 V		9	1/12
GW 66 407	2P+E	380 - 415 V		9	1/12
GW 66 408	3P+E	380 - 415 V		6	1/12
GW 66 409	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 412	2P+E	100 - 130 V		4	1/12
GW 66 413	3P+E	100 - 130 V		4	1/12
GW 66 414	3P+N+E	100 - 130 V		4	1/12
GW 66 415	2P+E	200 - 250 V		6	1/12
GW 66 416	3P+E	200 - 250 V		9	1/12
GW 66 417	3P+N+E	200 - 250 V		9	1/12
GW 66 418	2P+E	380 - 415 V		9	1/12
GW 66 419	3P+E	380 - 415 V		6	1/12
GW 66 420	3P+N+E	380 - 415 V		6	1/12

CHARACTERISTICS: the interlock lever can be padlocked in the ON/OFF position using the security lock GW40422.

Without bottom and without fuse-holder base - IP55



GW 66 471

Compact interlocked socket-outlets - 50/60 Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 467	2P+E	100 - 130 V		4	1/12
GW 66 468	3P+E	100 - 130 V		4	1/12
GW 66 469	3P+N+E	100 - 130 V		4	1/12
GW 66 470	2P+E	200 - 250 V		6	1/12
GW 66 471	3P+E	200 - 250 V		9	1/12
GW 66 472	3P+N+E	200 - 250 V		9	1/12
GW 66 473	2P+E	380 - 415 V		9	1/12
GW 66 474	3P+E	380 - 415 V		6	1/12
GW 66 475	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 478	2P+E	100 - 130 V		4	1/12
GW 66 479	3P+E	100 - 130 V		4	1/12
GW 66 480	3P+N+E	100 - 130 V		4	1/12
GW 66 481	2P+E	200 - 250 V		6	1/12
GW 66 482	3P+E	200 - 250 V		9	1/12
GW 66 483	3P+N+E	200 - 250 V		9	1/12
GW 66 484	2P+E	380 - 415 V		9	1/12
GW 66 485	3P+E	380 - 415 V		6	1/12
GW 66 486	3P+N+E	380 - 415 V		6	1/12

NOTES: the gasket is inserted in the complementary items, bottom box and distribution boards.

CHARACTERISTICS: the interlock lever can be padlocked in the ON/OFF position using the security lock GW40422.

With bottom and without fuse-holder base - IP55



GW 66 453

Compact interlocked socket-outlets - 50/60 Hz

Code	No. of poles	Rated voltage	Colour	Reference h	Pack Carton
Rated current (A): 16					
GW 66 445	2P+E	100 - 130 V		4	1/12
GW 66 446	3P+E	100 - 130 V		4	1/12
GW 66 447	3P+N+E	100 - 130 V		4	1/12
GW 66 448	2P+E	200 - 250 V		6	1/12
GW 66 449	3P+E	200 - 250 V		9	1/12
GW 66 450	3P+N+E	200 - 250 V		9	1/12
GW 66 451	2P+E	380 - 415 V		9	1/12
GW 66 452	3P+E	380 - 415 V		6	1/12
GW 66 453	3P+N+E	380 - 415 V		6	1/12
Rated current (A): 32					
GW 66 456	2P+E	100 - 130 V		4	1/12
GW 66 457	3P+E	100 - 130 V		4	1/12
GW 66 458	3P+N+E	100 - 130 V		4	1/12
GW 66 459	2P+E	200 - 250 V		6	1/12
GW 66 460	3P+E	200 - 250 V		9	1/12
GW 66 461	3P+N+E	200 - 250 V		9	1/12
GW 66 462	2P+E	380 - 415 V		9	1/12
GW 66 463	3P+E	380 - 415 V		6	1/12
GW 66 464	3P+N+E	380 - 415 V		6	1/12

CHARACTERISTICS: the interlock lever can be padlocked in the ON/OFF position using the security lock GW40422.

Complementary items



GW 66 496

Bottom for compact socket-outlets - IP55

Code	Houseable interloc. socket	Houseable IB socket-outlets	Side entries	Top entries	Bottom entries	Pack Carton
GW 66 496	1	Compact 16A/32A	2xØ 23	1xØ 23/29	1xØ 29/23	1/12

ACCESSORIES SUPPLIED: gasket for COMBIBLOC socket.



GW 66 498

Flush-mounting box with frame - IP55

Code	Houseable interloc. socket	Houseable IB socket-outlets	Pack Carton
GW 66 498	1	Compact 16A/32A	1/12

APPLICATIONS: possibility of mounting on rectangular flush-mounting box for modular ranges (GW24403) with 83.5mm distance between centres and on 48 PT range junction box (GW48002).
ACCESSORIES SUPPLIED: gasket for COMBIBLOC socket.



GW 68 295

Blank lid for IP55 combibloc cap

Code	Suitable for	Pack Carton
GW 68 295	Boards GW66491/2/3, flush-mounting boxes GW66498 e enclosures base boxes GW44696	1/10



GW 40 422

Cylindrical security lock

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: all the keys and relative locks with the same product code are identical.



GW 68 441

Floor mounting and workbench tower - IP55


Code	Outer dim. LxHxD (mm)	Houseable IB socket-outlets	Installable Q-DIN boards	Characteristics	Pack Carton
GW 68 441	200x295x180	16/32 A	Q-DIN 5	Halogen free	1/6

CHARACTERISTICS: double-sided panels with smooth or honeycomb surface, for fixing interlocked switched socket-outlets 16-32A of the IB range: Combibloc, horizontal IP44 with bottom and vertical IP67 with bottom.
APPLICATIONS: installed combined using the coupler GW26406.


Distribution boards for COMBIBLOC socket-outlet - IP55



GW 66 491



GW 66 492



GW 66 493

Empty boards for fixed compact socket-outlets



GW 66 493

Code	No. IB socket-outlets houseable	No. of modules EN 50022	No. of blank lids supplied	Dispersible power (W)	Pack Carton
GW 66 491	1 COMBIBLOC 16/32A	4	None	10	1/12
GW 66 492	2 COMBIBLOC 16/32A	8	1	13	1/6
GW 66 493	3 COMBIBLOC 16/32A	12	1	24	1/4

CHARACTERISTICS: the transparent door is pre-arranged for the GW40422 security lock.
ACCESSORIES SUPPLIED: sealing gaskets for COMBIBLOC socket-outlets.

Blank lid for interlocked switched socket-outlets COMBIBLOC IP55



GW 68 295

Code	Suitable for	Pack Carton
GW 68 295	Boards GW66491/2/3, flush-mounting boxes GW66498 e enclosures base boxes GW44696	1/10

Insulated screw terminal block bipolar and unipolar for enclosures and boards



GW 40 412 B

Code	Pole 1 (mm²)	Pole 2 (mm²)	Suitable for	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A					
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	GW66492 and GW66493	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	GW66493	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20					
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	GW66492 and GW66493	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	GW66493	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20					
GW 40 408 U	N/E (2x16) + (7x10)	-	GW66492 and GW66493	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	GW66493	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	GW66493	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: the installation of the GW40401, GW40408B and GW40408U terminal blocks on the GW66493 board is permitted by using the GW40413 adapter.

Adapters for screw terminal blocks



GW 40 413

Code	Suitable for	Fastener to supports	Pack Carton
GW 40 413	GW66493	With screws	20

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block.
INSTALLATION: it permits installation of the GW40401, GW40408B and GW40408U terminal blocks on the GW66493 board.

72 - FUSE FOR INTERLOCKED SOCKET-OUTLETS

Fuses



GW 72 003

ND fuses 380V~

Code	Rated current (A)	Rated voltage	Type	Breaking capacity	Pack Carton
Dimensions (mm): Ø 11 x 36					
GW 72 001	2	380 V	D01 E14	50 kA	10/100
GW 72 003	6	380 V	D01 E14	50 kA	10/100
GW 72 005	16	380 V	D01 E14	50 kA	10/100
Dimensions (mm): Ø 15 x 36					
GW 72 013	35	380 V	D02 E18	50 kA	10/100
GW 72 015	63	380 V	D02 E18	50 kA	10/100

NOTES: Compatible with interlocked socket-outlets horizontal type - 44IB Range.



GW 72 023

DD fuses 500V~

Code	Rated current (A)	Rated voltage	Type	Breaking capacity	Pack Carton
Dimensions (mm): Ø 13 x 50					
GW 72 021	2	500 V	DI E16 Delayed	50 kA	10/50
GW 72 023	6	500 V	DI E16 Delayed	50 kA	10/50
Dimensions (mm): Ø 22 x 50					
GW 72 065	16	500 V	DII E27 quick	50 kA	5/20
Dimensions (mm): Ø 28 x 50					
GW 72 092	35	500 V	DIII E33 Rapid	50 kA	5/20
GW 72 095	63	500 V	DIII E33 Rapid	50 kA	5/20



GW 72 122

gG cylindrical fuses - 500V~

Code	Rated current	Rated voltage	Type	Breaking capacity	Pack Carton
Dimensions (mm): Ø 10.3 x 38					
GW 72 104	2 A	500 V	gG	120 kA	10/100
GW 72 105	6 A	500 V	gG	120 kA	10/100
GW 72 101	16 A	500 V	gG	120 kA	10/100
GW 72 110	32 A	400 V	gG	120 kA	10/100
Dimensions (mm): Ø 14 x 51					
GW 72 122	32 A	500 V	gG	80 kA	10/100
Dimensions (mm): Ø 22 x 58					
GW 72 103	63 A	690 V	gG	80 kA	10/30

NOTES: Compatible with interlocked socket-outlets vertical type - 67IB and 66IB Range.



IB



67 IB



66 IB



44 IB



COMBIBLOC

Scan the QR Code and find out all the technical informations.

FULL RANGE FOR ALL APPLICATIONS




In addition to the 67 IB series, the offer is completed with 3 additional product lines. The 66 IB vertical socket-outlets are appreciated by operators for their robustness and electrical performance. The 44 IB horizontal socket-outlets are perfect for flush-mounted installations, even in drywall. The compact COMBIBLOC socket-outlets are the ideal solution for minimising space.

67 IB (AUTOMATIKA) WITH INTEGRATED MCB



The integration of the MCB switch in the socket-outlet individually protects the load reducing the spaces on boards. The LEDs integrated on the front indicate the operating status of the switch and the presence of voltage. Available with currents 16-32A.

67 IB (CBF) WITH FUSE BASE HOLDER



The knob has been designed to avoid the accumulations of dust and to ensure an ergonomic grip. The knob can also be padlocked to the ON/OFF position for added safety. Available with currents 16-32-63A.

IEC 309 combined boards





68 Q-DIN

Distribution boards

p. 112


68 ACS

ACS distribution board system for construction sites


p. 128

68 Q-DIN

Unwired versions

Type	No. EN 50022 modules	Code	Layout	Pre-arrangement
	5	GW 68 017 N		1 IEC 309 socket-outlet 16A IP44/67 or GW 27 401 or GW 27 403 watertight cap
		GW 68 018 N		2 IEC 309 socket-outlets 16A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 001 N		3 IEC 309 socket-outlets 16A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 031 N		3 IEC 309 socket-outlets 16A IP44/67 or GW 27 401 or GW 27 403 watertight caps and shockproof case
		GW 68 020 N		2 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 026 N		4 domestic socket std 50x50mm IP54
		GW 68 032 N		4 domestic socket std 50x50mm IP54 and shockproof case
	10	GW 68 002 N		Blank
		GW 68 003 N		2 IEC 309 socket-outlets 16A IP44/67 or GW 27 401 or GW 27 403 watertight caps 2 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 019 N		2 horizontal interlocked switched socket-outlets 16-32A IP44 with rotary switch
		GW 68 025 N		2 prese interbloccate verticali Serie 67 IB 16-32A IP67
		GW 68 027 N		3 domestic socket std 50x50mm IP54 2 IEC 309 socket-outlets 16-32A IP44/67
	14	GW 68 004 N		Blank
		GW 68 005 N		3 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 watertight caps
		GW 68 006 N		2 horizontal interlocked switched socket-outlets 16-32A IP44 with rotary switch
		GW 68 007 N		Blank
		GW 68 008 N		6 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 009 N		4 horizontal interlocked switched socket-outlets 16-32A IP44 with rotary switch
		GW 68 010 N		3 vertical interlocked switched socket-outlets 16-32A IP67
	20	GW 68 012 N		Blank
		GW 68 013 N		8 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 021 N		4 IEC 309 socket-outlets 16-32A IP44/67 or GW 27 401 or GW 27 403 watertight caps 2 IEC 309 socket-outlets 63A
		GW 68 014 N		4 horizontal interlocked switched socket-outlets 16-32A IP44 with fuse-holder base
		GW 68 015 N		4 vertical interlocked switched socket-outlets 16-32A IP67 4 IEC 309 socket-outlets 16A 2P+E or 16A 3P+E IP44/67 or GW 27 401 or GW 27 403 watertight caps
		GW 68 022 N		2 vertical interlocked switched socket-outlets 16-32A IP67 1 vertical interlocked switched socket-outlet 63A IP67
	14	GW 68 023 N		14 gang additional module
	20	GW 68 024 N		20 gang additional module

Wired versions

Type	No. EN 50022 modules	Code	Layout	Equipment	Code	Layout	Equipment
	5	GW 68 212 N		1 domestic socket-outlet 13A UK	GW 68 227 N		1 IEC 309 - socket-outlet 2P+E 16A IP44 230V
		GW 68 225 N		1 IEC 309 socket-outlet 2P+E 16A IP44 230V 1 Schuko domestic socket-outlet 10/16A	GW 68 226 N		1 IEC 309 socket-outlet 2P+E 16A IP44 230V 1 IEC 309 socket-outlet 3P+E 16A IP44 400V
		GW 68 224 N		1 IEC 309 socket-outlet 2P+E 16A IP44 230V 1 IEC 309 socket-outlet 3P+E 16A IP44 400V 1 Schuko domestic socket-outlet 10/16A			
	10	GW 68 202 N		2 GW IEC 309 2P+E 16A IP44 230V 1 IEC 309 socket outlet 3P+E 16A IP44 400V 1 domestic socket-outlet 10/16A Schuko	GW 68 228 N		1 IEC 309 socket-outlet 2P+E 16A IP44 230V 1 IEC 309 socket-outlet 3P+E 16A IP44 400V 1 IEC 309 socket-outlet 3P+N+E 16A IP44 400V 1 Schuko domestic socket-outlet 10/16A
		GW 68 232 N		2 vert.interl.socket-outlets 2P+E 16A IP67 230V with rotary switch	GW 68 233 N		1 vert.interl.socket-outlet 2P+E 16A IP67 230V 1 vert.interl.socket-outlet 3P+E 16A IP67 400V with rotary switch
	14	GW 68 205 N		2 IEC 309 socket-outlets 2P+E 16A IP67 230V 1 IEC 309 socket-outlet 3P+E 16A IP67 400V			
		GW 68 229 N		2 IEC 309 socket-outlets 2P+E 16A IP44 230V 1 IEC 309 socket-outlet 3P+E 16A IP44 400V 1 IEC 309 socket-outlet 3P+N+E 16A IP44 400V 1 IEC 309 socket-outlet 3P+E 32A IP44 400V 1 Schuko domestic socket-outlet 10/16A	GW 68 206 N		2 horiz. interlocked switched socket-outlets 2P+E 16A IP44 230V 1 horiz. interlocked switched socket-outlet 3P+E 16A IP44 400V 1 horiz. interlocked switched socket-outlet 3P+E 32A IP44 400V with rotary isolator
		GW 68 207 N		2 vert. interlocked switched socket-outlets 2P+E 16A IP67 230V 2 vert. interlocked switched socket-outlets 3P+E 16A IP67 400V with rotary switch	GW 68 230 N		2 AUTOMATIKA vert. interlocked switched socket-outlets 2P+E 16A IP67 230V 1 AUTOMATIKA vert. interlocked switched socket-outlet 3P+N+E 16A IP67 400V
		GW 68 231 N		1 AUTOMATIKA vert. interlocked switched socket-outlet 2P+E 16A IP67 230V 2 AUTOMATIKA vert. interlocked switched socket-outlets 3P+N+E 16A IP67 400V			
	20	GW 68 208 N		2 vert. interlocked switched socket-outlets 2P+E 16A IP67 230V 1 vert. interlocked switched socket-outlet 3P+E 16A IP67 400V 1 vert. interlocked switched socket-outlet 3P+E 32A IP67 400V with rotary switch			

68 Q-DIN

Distribution boards



A complete system of IP65 boards for distributing energy in tertiary, commercial sector and building applications, available both empty and pre-wired, in accordance with the international standard IEC 61439. The Q-DIN range comprises boards from 5 to 20 DIN modules, plus supplementary modules of 14 or 20 M to add even more DIN spaces. They can accommodate flush-mounting socket-outlets and interlocked socket-outlets of up to 63 A, and they can be combined with numerous accessories.

EMPTY BOARDS FOR MOBILE AND FIXED INSTALLATIONS


Q-DIN 5 - Surface-mounting - IP65



GW 68 017N



GW 68 018N



GW 68 001N
GW 68 031N



GW 68 020N



GW68026N
GW68032N




GW 68 001 N

Q-DIN 5 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 5					
GW 68 017 N	1 IEC 309 16A IP44/67	-	10	37	16
GW 68 018 N	2 IEC 309 16A IP44/67	-	10	37	12
GW 68 001 N	3 IEC 309 16A IP44/67	1 IEC 16A	10	37	8
GW 68 031 N	3 IEC 309 16A IP44/67	1 IEC 16A	10	37	4
GW 68 020 N	2 IEC 309 16/32A IP44/67	1 IEC 16/32A	10	37	8
GW 68 026 N	4 domestic socket std.50x50 mm	1 domestic socket std.50x50 mm	10	37	8

ACCESSORIES SUPPLIED: cable clamp and 2 screw caps. GW68031N complete with rubber shockproof case. Adapter flange for every IEC 309 socket-outlet housing seat - 16/32 A.
NOTES: key not installable. Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40 K overtemperature, between the temperature inside and outside the board. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.
External dimensions GW68017N (LxHxD): 105x258x96 mm.
External dimensions GW68018N (LxHxD): 105x337x96 mm.
External dimensions GW68001N and GW68020N (LxHxD): 105x430x96 mm.
External dimensions GW68031N (LxHxD): 140x560x105 mm.
Halogen-Free in accordance with Standard EN 60754-2.

Q-DIN 10 - Surface-mounting - IP65



GW 68 002N



GW 68 025N



GW 68 003N



GW 68 019N



GW68027N



GW 68 025 N

Q-DIN 10 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 10					
GW 68 002 N	Blank lid	-	16	42	6
GW 68 025 N	2 IB Vert. 16-32A IP67	1 IB 16/32A	16	42	6
GW 68 003 N	2 IEC 16A + 2 IEC 16/32A	1 IEC 309 16A+1 16/32A	16	42	6
GW 68 019 N	2 IB Horiz. 16/32A SBF IP44 overlapping	1 IB 16/32A	16	42	6
GW 68 027 N	3 dom.socket 50x50 mm + 2 IEC 16/32 A	1 domestic + 1 IEC 16 A	16	42	6

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps. Adapter flange for every IEC 309 socket-outlet housing seat - 16/32 A.
NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board.
GW68003N: pre-arranged for two 16-32 A socket-outlets in the lower flanges and two 16A socket-outlets in the upper flanges. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.
External dimensions (LxHxD): 220x435x96.
Halogen-Free in accordance with Standard EN 60754-2.

Q-DIN 14 - Surface-mounting - IP65



GW 68 004N



GW 68 005N



GW 68 006N



GW 68 005 N

Q-DIN 14 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 14					
GW 68 004 N	Blank lid	-	24	64	4
GW 68 005 N	3 IEC 309 16/32A IP44/67	1 IEC 16/32A	24	64	4
GW 68 006 N	2 IB Horiz. 16/32A SBF IP44 side by side	1 IB 16/32A	24	64	4

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps. Adapter flange for every IEC 309 socket-outlet housing seat - 16/32 A.

NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.

External dimensions (LxHxD): 320x360x120.

Halogen-Free in accordance with Standard EN 60754-2.

Q-DIN 14 - Surface-mounting - IP65



GW 68 007N



GW 68 008N



GW 68 009N



GW 68 010N



GW 68 008 N

Q-DIN 14 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 14					
GW 68 007 N	Blank lid	-	24	64	3
GW 68 008 N	6 IEC 309 16/32A IP44/67	2 IEC 16/32A	24	64	3
GW 68 009 N	4 IB Horiz. 16/32A SBF IP44	2 IB 16/32A	24	64	3
GW 68 010 N	3 IB Vert. 16/32A IP67	1 IB 16/32A	24	64	3

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps. Adapter flange for every IEC 309 socket-outlet housing seat - 16/32 A.

NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.

External dimensions (LxHxD): 320x510x120.

Halogen-Free in accordance with Standard EN 60754-2.


Q-DIN 20 - Surface-mounting - IP65



GW 68 012N



GW 68 013N



GW 68 014N



GW 68 021N



GW 68 014 N

Q-DIN 20 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 20					
GW 68 012 N	Blank lid	-	30	92	2
GW 68 013 N	8 IEC 309 16/32A IP44/67	2 IEC 16/32A	30	92	2
GW 68 014 N	4 IB Horiz. 16/32A CBF IP44	2 IB 16/32A	30	92	2
GW 68 021 N	2 IEC 309 63A - 4 IEC 309 16/32A	2 IEC 309 16/32A+1 63A	30	92	2


ACCESSORIES SUPPLIED: cable clamp and 6 screw caps. Adapter flange for every IEC 309 socket-outlet housing seat - 16/32 A.

NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.


External dimensions (LxHxD): 450x560x120.

Halogen-Free in accordance with Standard EN 60754-2.

Q-DIN 20 - Surface-mounting - IP65



GW 68 015N



GW 68 022N



GW 68 015 N

Q-DIN 20 watertight boards - unwired - RAL 7035 - IP65

Code	Houseable socket	No. of provided blank lids	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
No. of modules EN 50022: 20					
GW 68 015 N	4IB 16/32A IP67 + 4 IEC MAX 3P+E 16A	2 IB 16/32A + 4 IEC 16A	30	92	2
GW 68 022 N	1 IB Vert. 63A IP67 + 2 IB Vert. 16/32A IP67	1 IB 16/32A	30	92	2

ACCESSORIES SUPPLIED: cable clamp and 6 screw caps.

NOTES: Dispersible power (B) is calculated according to IEC 60890 standard. It refers to the 40K overtemperature, between the temperature inside and outside the board.

GW68015N: the 4 flanges - measuring 85x75 - can be equipped with the COMBI-IN GW27401 and GW27403 watertight covers. The IP65 degree of protection is obtained with blank flange lid installed correctly on all the seats of the unwired board.

External dimensions (LxHxD): 450x560x120.

Halogen-Free in accordance with Standard EN 60754-2.

Additional Q-DIN modules - IP65



GW 68 023N



GW 68 024N



GW 68 023 N

Additional Q-DIN modules - RAL 7035 - IP65

Code	No. of modules EN 50022	Dispersible power (W)	Pack Carton
GW 68 023 N	14	40	1/3
GW 68 024 N	20	52	1/3

NOTES: to be used with Q-DIN 14 and 20 M to double the DIN modules available. the dispersible power is calculated according to the document IEC 60890 (CEI 17-43) and refers to an overtemperature of 40K between the air temperature inside the board and in the room.

External dimensions GW68023N (LxHxD): 320x241x120.

External dimensions GW68024N (LxHxD): 450x241x120.

Halogen-Free in accordance with Standard EN 60754-2.

Complementary items



GW 68 431

Yellow-painted metal conduit support with support for cables of up to 20 m

Code	Outer dim. LxHxD (mm)	For distribution board type	Pack Carton
GW 68 431	350x715x435	Q-DIN 10	1
GW 68 433	350x770x520	Q-DIN 14/20	1

NOTES: the type of cable considered is H 07 RN - F 5 x 4 mm²; the length varies according to the type of cable.

GW68433: Q-DIN protection system against the front drops.

Metal carrier painted in yellow equipped with two wheels and rotating drum to wind up to 50 m of cable



GW 68 432

Code	Outer dim. LxHxD (mm)	For distribution board type	Pack Carton
GW 68 432	495x1000x605	Q-DIN 14/20	1

NOTES: the type of cable considered is H 07 RN - F 5 x 4 mm²; the length varies according to the type of cable. 1+1 flanges for socket-outlets IEC 309 16A and 32A.

Pole support kit for 68 Q-DIN boards



GW 46 552

Code	For Q-DIN	Max sustainable load (kg)	Pack Carton
GW 46 552	14	12	1
GW 46 553	20	125	1

CHARACTERISTICS: fixed on the back of the boards. The maximum sustainable load values refer to Q-DIN boards.
APPLICATIONS: for application of boards on poles from 60 to 80mm.
ACCESSORIES SUPPLIED: 2 pieces. For the correct use of the kit, see the instructions sheet.

Brackets for fixing boards to the wall



GW 46 446

Code	Material	For Q-DIN	Accessories supplied	Pack Carton
GW 44 621	Insulation	5	Self-tapping fixing screws	40/480
GW 46 446	Galvanised steel	10/14/20	Self-tapping fixing screws	20
GW 46 451	Stainless steel	10/14/20	Self-tapping fixing screws	20

NOTES: GW44621: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
GW46446 and GW46451: set composed of 4 brackets. Maximum sustainable load 8 kg for Q-DIN10, 12 kg for Q-DIN14 and 15 kg for Q-DIN20.

Domestic socket outlet - IP54



GW 62 393

Code	No. of poles	Rated current (A)	Rated voltage	Colour	Frequency	Flange dimensions (mm)	Pack Carton
Standard: German							
GW 62 393	2P+E	16	230 V		50/60 Hz	50x50	1/20
GW 62 392	2P+E	16	200 - 250 V		50/60 Hz	85x75	1/12
Standard: French							
GW 62 394	2P+E	16	230 V		50/60 Hz	50x50	1/20

CHARACTERISTICS: domestic socket-outlets equipped with child protection (shutter) and with rear connection.
NOTES: domestic socket-outlets 50x50 mm can be installed also on flanges 85x75 mm using the adapter code GW68281.

Round mushroom-head emergency push-button - Mushroom Ø 40mm



GW 74 361

Code	Functions	Characteristics	Pack Carton
GW 74 361	With holding	Not illuminated	10/60

APPLICATION: suitable for emergency use, in accordance with Standard IEC 60947-5-5.
SUPPLIED: 3-seat flange (2 of which are contact-holders).



Contacts - ITH=10A - 250V AC

Code	Type	Colour	Pack Carton
GW 74 501	1 NO	Green	1/30
GW 74 502	1 NC	Red	1/30
GW 74 503	2 NO	Green	1/30
GW 74 504	1 NO + 1 NC	White	1/30
GW 74 505	2 NC	Red	1/30

CHARACTERISTICS: GW74502 suitable for contact opening also in the event of slight sticking, in compliance with Standard EN 60947-5-1.
Clip assembly on the contact-holder flanges.
NOTES: the dual contacts type: GW74503, GW74504 and GW74505 are not compatible with the watertight emergency enclosures GW42204 and GW42207.

Cylindrical security lock

Code	Material	For distribution board type	Pack Carton
GW 40 422	Pressure die-cast metal	Q-DIN 10/14/20 and additional modules	1/10


ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.



GW 40 422

Q-DIN transportation handle

Code	Description	For distribution board type	Pack Carton
GW 68 436 N	Handle	Q-DIN 10/14/20 and additional modules	1/10



GW 68 436 N

Blank lids for closing compartment containing IEC and IB vertical socket-outlets

Code	Description	Dimensions LxH (mm)	Pack Carton
GW 68 292	Lid for IEC 309 16A	85x75	1/10
GW 68 293	Lid for IEC 309 32A	95x80	1/10
GW 68 294	Lid for IEC 309 63A	110x100	1/10
GW 66 703 N	Lid for vertical interlocked socket-outlet 16-32A	220x103	1/10
GW 66 705 N	Lid for vertical interlocked socket-outlet 63A	270x145	1/10
GW 68 296	Lid for domestic socket outlet 50x50 mm	50x50	1/10



GW 68 292

Blank lids for closing compartment containing IB horizontal socket-outlets

Code	For distribution boards	For back boxes	For flush-mounting boxes	Pack Carton
GW 66 701	GW68006N/09N/19N	GW66676	GW66681 - GW66681PM	1/10
GW 66 702	GW68014N	GW66677	GW66682 - GW66682PM	1/10



GW 66 702

Flanged lid prearranged for 2 caps - IP67

Code	Houseable IB socket-outlets	Pack Carton
GW 66 709 N	N. 1 IEC 309 16-32A IP44/67 + N.1 16A MAX 3P+E or GW27401/GW27403	1/10

APPLICATIONS: the flange of 85x75 mm dimension is suited for mounting IEC 309 16 A socket-outlets and COMBI-IN GW27401 and GW27403 flange; the flange of 95x80 mm dimension is suited for IEC 309 16 -32 A socket-outlets.
ACCESSORIES SUPPLIED: 1 blank flange - blue - 16 A; 1 blank flange - blue 16 -32 A; 3 gaskets and fixing screws.



GW 66 709 N

Adapter

Code	Suitable for	Pack Carton
GW 66 715 N	IP67 16/32A vertical socket-outlets	1/10
GW 66 716 N	IP67 63A Vertical socket-outlets	1/10
GW 68 281	Domestic socket outlet std.50x50 mm	1/10

APPLICATIONS: GW66715N to assemble all the vertical socket-outlets 16-32 A IP67 of the 67 IB range on the Q-DIN boards, or on the modular bases of the previous versions for socket-outlets 16-32 A CBF IP55. GW66716N to assemble the vertical socket-outlets 63A IP67 of the 67 IB range on the modular bases of the previous versions for socket-outlets 63A CBF IP55.



GW 66 715 N

COMBI-IN watertight covers for 2 System range modules

Code	Dimensions LxH (mm)	Door type	IP degree	Colour	Pack Carton
GW 27 401	75x85	With membrane	IP55	Grey RAL 7035	3/60
GW 27 403	75x85	Rigid IK09	IP65	Grey RAL 7035	3/60

NOTES: they are installed in the same seat of IEC 309 socket-outlets - 16 A IP44/67
ACCESSORIES SUPPLIED: gasket and mounting screws.



GW 27 403

Watertight lids

Code	Dimensions LxH (mm)	Suitable for	Colour	Pack Carton
GW 66 708	75x85	1 Button Ø22 mm Range 74 PS	Grey	1/20
GW 66 745	75x85	1 Button Ø22 mm Range 74 PS	Yellow	1/20

APPLICATIONS: GW66745 specific for emergency push-buttons.
ACCESSORIES SUPPLIED: gasket and mounting screws.



GW 66 745

Back-mounting plate in insulated material with self-tapping fixing screws

Code	For Q-DIN	Pack Carton
GW 44 626	10	20
GW 44 627	14	20
GW 44 628	20	4

NOTE: to be installed on the base of the Q-DIN, for inserting DIN rails/terminal blocks/components.



GW 44 626

68 Q-DIN



GW 40 412 B

Insulated screw terminal block bipolar and unipolar for enclosures and boards

Code	Pole 1 (mm²)	Pole 2 (mm²)	Suitable for	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A					
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	Q-DIN 10/14/20	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	Q-DIN 14/20	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20					
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	Q-DIN 10/14/20	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	Q-DIN 14/20	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20					
GW 40 408 U	N/E (2x16) + (7x10)	-	Q-DIN 10/14/20	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	Q-DIN 14/20	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	Q-DIN 14/20	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: the installation of the GW40401, GW40408B and GW40408U terminal blocks on Q-DIN 14/20 boards is permitted by using the GW40413 adapter.



GW 40 413

Adapters for screw terminal blocks

Code	Suitable for	Fastener to supports	Pack Carton
GW 40 413	Q-DIN 14/20	With screws	20

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block.
INSTALLATION: permits installation of the GW40401, GW40408B and GW40408U terminal blocks on Q-DIN 14/20 boards.



GW 66 673

Coupling for 68Q-DIN boards - IP65

Code	Description	Pack Carton
GW 66 673	Coupler PG29	10/120

Surface-mounting for COMBIBLOC compact socket-outlets IP44 - IP55



GW 66 493

Empty boards for fixed compact socket-outlets

Code	No. IB socket-outlets houseable	No. of modules EN 50022	No. of blank lids supplied	Dispersible power (W)	Pack Carton
GW 66 491	1 COMBIBLOC 16/32A	4	None	10	1/12
GW 66 492	2 COMBIBLOC 16/32A	8	1	13	1/6
GW 66 493	3 COMBIBLOC 16/32A	12	1	24	1/4

CHARACTERISTICS: the transparent door is pre-arranged for the GW40422 security lock.
ACCESSORIES SUPPLIED: sealing gaskets for COMBIBLOC socket-outlets.

Blank covers for COMBIBLOC interlocked switched socket-outlets



GW 68 295

Code	Dimensions LxH (mm)	Pack Carton
GW 68 295	132x71	1/10

ACCESSORIES SUPPLIED: sealing gasket and 4 fixing screws.

Insulated screw terminal block bipolar and unipolar for enclosures and boards



GW 40 412 B

Code	Pole 1 (mm²)	Pole 2 (mm²)	Suitable for	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A					
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	GW66492 and GW66493	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	GW66493	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20					
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	GW66492 and GW66493	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	GW66493	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20					
GW 40 408 U	N/E (2x16) + (7x10)	-	GW66492 and GW66493	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	GW66493	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	GW66493	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: the installation of the GW40401, GW40408B and GW40408U terminal blocks on the GW66493 board is permitted by using the GW40413 adapter.

Adapters for screw terminal blocks



GW 40 413

Code	Suitable for	Fastener to supports	Pack Carton
GW 40 413	GW66493	With screws	20

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block.
INSTALLATION: it permits installation of the GW40401, GW40408B and GW40408U terminal blocks on the GW66493 board.

WIRED BOARDS FOR FIXED APPLICATIONS

Surface-mounting



GW 68 226 N

Wired Q-DIN 5 DBU boards with IEC 309 socket-outlets - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Schuko socket-outlet 10/16A	UK socket-outlet 13A	Pack Carton
GW 68 212 N	-	-	-	1	1/8
GW 68 224 N	1	1	1	-	1/2
GW 68 225 N	1	-	1	-	1/6
GW 68 226 N	1	1	-	-	1/6
GW 68 227 N	1	-	-	-	1/8

PROTECTIONS:
GW68212N: Board In: 10A
1 RCCB - SD Range 2P 230 V 25 A 0,03 A - AC Type
GW68224N: Board In: 13A
1 RCBO - MDC Range 4P 400 V 16 A C 6 kA 0,03 A - AC Type
GW68225N: Board In: 13A
1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0,03 A - AC Type
GW68226N: Board In: 25A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
GW68227N: Board In: 13A
1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0,03 A - AC Type
ACCESSORIES SUPPLIED: cable clamp and 2 screw caps.



GW 68 202 N

Wired Q-DIN 10 DBU boards with IEC 309 socket-outlets - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-outlet 3P+N+E 16A - IEC 309	Schuko socket-outlet 10/16A	Pack Carton
GW 68 202 N	2	1	-	1	1/3
GW 68 228 N	1	1	1	1	1/3

PROTECTIONS:
GW68202N: Board In: 25A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
GW68228N: Board In: 25A
2 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 4P 400 V 16 A C 6 kA
ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.



GW 68 233 N

Watertight Q-DIN 10 DBO boards wired with vertical interlocked switched socket-outlets - IP65

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Pack Carton
GW 68 232 N	2	-	1/2
GW 68 233 N	1	1	1/2

PROTECTIONS:
GW68232N: Board In: 25 A.
2 MCB - MT Range 2P 230 V 16 A C 6 kA.
GW68233N: Board In: 25 A.
1 MCB - MT Range 2P 230 V 16 A C 6 kA.
1 MCB - MT Range 3P 400 V 16 A C characteristic 6 kA.
ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.



GW 68 205 N

Wired Q-DIN 14 DBO distribution board with non-interlocked socket-outlets - IP65

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Pack Carton
GW 68 205 N	2	1	1/3

Board In: 25A
PROTECTIONS:
2 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.

Wired Q-DIN 14 DBU board with IEC 309 socket-outlets - IP44



GW 68 229 N

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-outlet 3P+N+E 16A - IEC 309	Socket-out 3P+E 32A - IEC309	Schuko socket-outlet 16A	Pack Carton
GW 68 229 N	2	1	1	1	1	1

Board In: 50A

PROTECTIONS: 1 MCB - MTC Range 2P 230 V 16 A C 6 kA for the 2P+E 16 A 230 V and the 10/16 A IT/DE 230 V domestic socket-outlets
1 MCB - MTC Range 4P 400 V 16 A C 6 kA for the 3P+E 16 A 400 V and 3P+N+E 16 A 400 V socket-outlets
1 MCB - MTC Range 3P 400 V 32 A C 6 kA for the 3P+E 32 A 400 V socket-outlet

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.

Wired, Q-DIN 14 DBU board with horizontal interlocked socket-outlets - IP44



GW 68 206 N

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-out 3P+E 32A - IB	Pack Carton
GW 68 206 N	2	1	1	1

Board In: 50A

PROTECTIONS: Board with horizontal interlocked switched socket-outlets 44 IB
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 32 A C 6 kA

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.

Wired Q-DIN 14 DBO boards with vertical interlocked socket-outlets - IP65



GW 68 207 N

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-outlet 3P+N+E 16A - IB	Pack Carton
GW 68 207 N	2	1	-	1
GW 68 230 N	2	-	1	1
GW 68 231 N	1	-	2	1

PROTECTIONS:

GW68207N: Board In: 25A
2 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA

GW68230N: Board In: 25A
1 RCCB - SD Range 4P 400 V 40 A 0,03 A - AC Type
2 MCB - MT Range 2P 230 V 16 A C 6 kA
1 MCB - MT Range 4P 400 V 16 A C 6 kA

GW68231N: Board In: 32A
1 RCCB - SD Range 4P 400 V 40 A 0,03 A - AC Type
1 MCB - MT Range 2P 230 V 16 A C 6 kA
2 MCB - MT Range 4P 400 V 16 A C 6 kA

CHARACTERISTICS: GW68230N and GW68231N board equipped with AUTOMATIKA sockets.

ACCESSORIES SUPPLIED: cable clamp and 4 screw caps.

Wired Q-DIN 20 DBU board with vertical interlocked socket-outlets and 4 flanges for non-interlocked socket-outlets 16A - IP65



GW 68 208 N

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-out 3P+E 32A - IB	Pack Carton
GW 68 208 N	2	1	1	1

Board In: 50A

PROTECTIONS: 2 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 32 A C 6 kA

ACCESSORIES SUPPLIED: cable clamp and 6 screw caps.

Surface-mounting with COMBIBLOC compact socket-outlets



GW 66 391

Wired COMBIBLOC board with compact interlocked socket-outlets - IP44

Code	Socket-outlet 2P+E 16A - IB	IP degree	Pack Carton
GW 66 391	1	IP44	1/2

Board In: 14A

PROTECTIONS: 1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0,03 A - AC Type



GW 66 392

Wired COMBIBLOC boards with compact interlocked socket-outlets - IP44 / IP55

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-outlet 3P+N+E 16A - IB	IP degree	Pack Carton
GW 66 392	1	1	-	IP44	1/2
GW 66 393	1	-	1	IP55	1/2

PROTECTIONS:

GW66392: Board In: 25A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA

GW66393: Board In: 25A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 4P 400 V 16 A C 6 kA.



GW 66 394

Wired COMBIBLOC boards with compact interlocked socket-outlets - IP44 / IP55

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-outlet 3P+N+E 16A - IB	Socket-out 3P+E 32A - IB	IP degree	Pack Carton
GW 66 394	1	1	1	-	IP44	1
GW 66 395	2	1	-	-	IP55	1
GW 66 396	1	1	-	1	IP44	1
GW 66 397	1	1	1	-	IP55	1

PROTECTIONS:

GW66394: Board In: 20A
1 RCCB - SD Range 4P 400 V 25 A 0,03 A - AC Type
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 4P 400 V 16 A C 6 kA

GW66395: Board In: 20A
1 RCCB - SD Range 4P 400 V 25 A 0,03 A - AC Type
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA

GW66396: Board In: 50A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 32 A C 6 kA

GW66397: Board In: 38A
1 MCB - MTC Range 2P 230 V 16 A C 6 kA
1 MCB - MTC Range 3P 400 V 16 A C 6 kA
1 MCB - MTC Range 4P 400 V 16 A C 6 kA.



68 Q-DIN



Scan the QR Code and find out all the technical informations.

WIDE AND CONFIGURABLE RANGE



The power distribution board range is made up of 23 empty casings with IP65 degree of protection, for flush-mounting and interlocked socket-outlets up to 63A, and with numerous complementary items that increase the fields of application.

INNOVATIVE TECHNICAL SOLUTIONS



The boards have many innovative technical features, such as the ergonomic handle, which simplifies the opening of the door, and the screws to “hinge” the front facilitating wiring. Additional enclosures 14 and 20M modules are also available, ideal for increasing the modular space.

TOP-LEVEL ACCESSORY OPTIONS



The boards can be equipped with a key lock with a metal cylinder and mushroom emergency button. They can be fixed to a pole, surface-mounting, flush-mounted or on accident prevention mobile supports.

68 ACS

68 QP ACS - Wired main boards for construction sites

TYPE	DOOR	MAIN SWITCH			EMERGENCY KIT	POWER MAX (kW)	CODE
		N° OF POLES	In (A)	PROTECTION DEVICE			
QP 	Blind	4	125	MCB 125A 4P C 10kA + RCD adjustable - A Type	YES	65	GW 68 521
		4	160	MSXD 160A - 3P+N 25kA + integrated adjustable RCD	YES	85	GW 68 526
		4	250	MSXD 250A - 3P+N 36kA + integrated adjustable RCD	YES	130	GW 68 531

68 Q-BOX ACS - Wired distribution boards for construction sites

TYPE	TOTAL N. SOCKET OUTLETS	SOCKET-OUTLETS CONFIGURATION									MAIN RCBO		EMERGENCY KIT	POWER MAX (kW)
		16A Std. DE	16A 2P+E 230 V	16A 3P+E 400 V	16A 3P+N+E 400 V	32A 2P+E 230 V	32A 3P+E 400 V	32A 3P+N+E 400 V	63A 3P+E 400 V	63A 3P+N+E 400 V	N° OF POLES	In (A)		
Q-BOX	4		4								2	32	YES	6
			3	1							4	32	YES	17
			2	2							4	32	YES	17
			2	1	1						4	32	YES	17
			3			1					2	63	YES	12
			3				1				4	32	YES	17
			3					1			4	32	YES	17
			2	1			1				4	32	YES	17
			2		1			1			4	32	YES	17
			2	1				1			4	32	YES	17
			1	2			1				4	32	YES	17
	5		2	3							4	63	YES	33
			3	1			1				4	63	YES	33
			3	1				1			4	63	YES	33
			2	2			1				4	63	YES	33
			2	2				1			4	63	YES	33
			2	1	1			1			4	63	YES	33
			2	1			1		1		4	63	YES	33
			2	1			1		1		4	80	YES	42
			2		1			1		1	4	80	YES	42
	6		6								2	32	YES	6
			4	2							4	32	YES	17
			3	3							4	32	YES	17
			3	2	1						4	32	YES	17
			3	2			1				4	63	YES	33
			3	2				1			4	63	YES	33
			3		2			1			4	63	YES	33
			3	1	1		1				4	63	YES	33
			3	1	1			1			4	63	YES	33
			2	3			1				4	63	YES	33
			2	2			1	1			4	63	YES	33
			2	1	1		1	1			4	63	YES	33
			2	2			2				4	63	YES	33
			2		2			2			4	63	YES	33
			2	1				3			4	63	YES	33
			3					2		1	4	100	YES	53
			2					2		2	4	100	YES	53
	8		4	3				1			4	63	YES	33
	9	4	2	2				1			4	63	YES	33
	11	4	3	2				1		1	4	100	YES	53
	12		6	3	1			2			4	63	YES	33
			12								2	63	YES	12
			6	6							4	63	YES	33

(*) Versions where n.2 sockets-outlets 16A 2P+E are type IEC 309 (not interlocked)

68 CDK ACS - Wired main boards for construction sites

TYPE	DOOR	MAIN SWITCH			EMERGENCY KIT	POWER MAX (kW)	CODE
		N° OF POLES	In (A)	PROTECTION DEVICE			
CDK 	Transparent	4	32	MDC 32A - 4P - 6kA - 30 mA - AC Type	YES	17	GW 68 536
		4	63	MT 63A - 4P - 6kA + DIFF. 30 mA - AC Type	YES	33	GW 68 537
		4	100	MTHP 100A - 4P - 10kA + DIFF. 30 mA - AC Type	YES	53	GW 68 538
		4	125	MTHP 125A - 4P - 10kA + DIFF. 30 mA - AC Type	YES	65	GW 68 539

SOCKETS TYPE					COMPLEMENTARY ITEMS
INTERLOCKED WITHOUT FUSE HOLDER (SBF)		INTERLOCKED WITH FUSE HOLDER (CBF)		FIXED IEC 309	
SUPPLY TERMINAL BLOCK	SUPPLY FIXED PLUG	SUPPLY TERMINAL BLOCK	SUPPLY FIXED PLUG	SUPPLY TERMINAL BLOCK	
GW 68 561	GW 68 584	GW 68 561 F	GW 68 584 F		 Secutity lock GW 46 445
GW 68 562	GW 68 481	GW 68 562 F	GW 68 481 F		
GW 68 563	GW 68 482	GW 68 563 F	GW 68 482 F		
GW 68 564	GW 68 585	GW 68 564 F			
GW 68 511		GW 68 511 F			
GW 68 565		GW 68 565 F			
GW 68 566		GW 68 566 F			
GW 68 567	GW 68 586	GW 68 567 F	GW 68 586 F		
GW 68 568		GW 68 568 F			
GW 68 569	GW 68 587	GW 68 569 F	GW 68 587 F		
GW 68 570	GW 68 588	GW 68 570 F	GW 68 588 F		 Floor mounting support GW 68 463
GW 68 512 (*)		GW 68 512 F			
GW 68 571 (*)	GW 68 589 (*)	GW 68 571 F	GW 68 589 F		
GW 68 572	GW 68 590 (*)	GW 68 572 F	GW 68 590 F		
GW 68 513 (*)	GW 68 483 (*)	GW 68 513 F	GW 68 483 F		
GW 68 573	GW 68 592 (*)	GW 68 573 F	GW 68 592 F		
GW 68 514 (*)	GW 68 484 (*)	GW 68 514 F	GW 68 484 F		
GW 68 574 (*)	GW 68 593 (*)				
		GW 68 574 F			
		GW 68 498 F			
GW 68 575	GW 68 594	GW 68 575 F	GW 68 594 F		 Pole support kit (only for Q-BOX4) GW 46 554
GW 68 576	GW 68 595	GW 68 576 F	GW 68 595 F		
GW 68 577	GW 68 473	GW 68 577 F	GW 68 473 F		
GW 68 578	GW 68 596	GW 68 578 F	GW 68 596 F		
GW 68 493	GW 68 471	GW 68 493 F	GW 68 471 F		
GW 68 579	GW 68 597	GW 68 579 F	GW 68 597 F		
	GW 68 598		GW 68 598 F		
GW 68 580		GW 68 580 F			
GW 68 581					
GW 68 582	GW 68 472	GW 68 582 F	GW 68 472 F		 Plug-socket outlets block GW 68 505
GW 68 583	GW 68 599	GW 68 583 F	GW 68 599 F		
GW 68 492					
GW 68 494	GW 68 600	GW 68 494 F	GW 68 600 F		
GW 68 491	GW 68 474	GW 68 491 F			
GW 68 495					
GW 68 496					 Document holder wallet GW 46 447
GW 68 497					
GW 68 542					
GW 68 541					
GW 68 543					
GW 68 544					
				GW 68 468	
				GW 68 469	

68 Q-DIN ACS - Wired mobile boards for construction sites

TYPE	TOTAL N. SOCKET OUTLETS	IP DEGREE	SOCKET-OUTLETS CONFIGURATION						
			16A std. DE	16A 2P 24 V	16A 2P+E 230 V	16A 3P+E 400 V	16A 3P+N+E 400 V	32A 3P+E 400 V	32A 3P+N+E 400 V
Q-DIN 	2	IP65		2					
	3	IP44	1		2				
		IP65			3				
		IP65			3				
		IP65			2	1			
		IP65			1	2			
		IP65				3			
	4	IP44	2		2				
		IP44	1		2	1			
		IP65			4				
		IP65			3	1			
		IP65			3		1		
		IP65			2	2			
		IP65				4			
		IP65			2	1		1	
		IP65		2	2				
	6	IP65			6				
		IP65			4	2			
		IP65			3	3			
		IP65			3	2		1	
		IP44	2		2	2			
	8	IP44	2		2	2		2	
COMBIBLOC 	3	IP55			2		1		
		IP55			1		1		1
QMC 	6	IP56			2	1	2		1
	7	IP56			7				
		IP56			4	1	1		1

(*) Version GW68223N with yellow shockproof case versions GW68401N, GW66388 ad GW68389 with metal conduit support versions GW68411N, GW68421N and GW68424N equipped with metal conduit carriage with two wheels

MAIN RCBO		EMERGENCY KIT	POWER MAX (kW)	SOCKETS TYPE		COMPLEMENTARY ITEMS
N° OF POLES	In (A)			INTERLOCKED WITHOUT FUSE HOLDER (SBF)	FIXED IEC 309	
2	16		3	GW 68 235 N		
2	16		3		GW 68 241N	 Security lock GW 40 422 (Q-DIN 10/14/20)
2	16		3		GW 68 217 N	
2	16		3		GW 68 223 N (*)	
4	16		8		GW 68 242 N	
4	16		8		GW 68 243 N	
4	16		8		GW 68 244 N	
2	16		3		GW 68 203 N	 Floor mounting support GW 68 431 (Q-DIN 10) GW 68 433 (Q-DIN 14/20)
4	16		8		GW 68 401 N (*)	
2	16		3		GW 68 216 N	
4	16		8		GW 68 245 N	
4	16		8		GW 68 246 N	
4	16		8		GW 68 204 N	
4	16		8		GW 68 247 N	 Metal carrier with two wheels GW 68 432 (Q-DIN 14/20)
4	63		33	GW 68 424 N (*)		
2	16		3	GW 68 236 N		
4	16		8		GW 68 248 N	
4	32		17		GW 68 249 N	
4	32		17		GW 68 250 N	
4	32		17		GW 68 251 N	 Metallic transportation handle GW 68 436 N (Q-DIN 10/14/20)
4	32		17		GW 68 411 N (*)	
4	32		17		GW 68 421 N (*)	
4	40		21	GW 66 388 (*)		
4	40		21	GW 66 389 (*)		
4	50	YES	26		GW 68 884 A	
4	40	YES	21		GW 68 881 A	
4	50	YES	26		GW 68 883 A	

68 ACS

ACS distribution board system for construction sites



The 68 ACS range is composed of an extensive selection of wired boards which are certified in accordance with the Standard EN 61439-4, and are capable of meeting all electrification requirements, from the smallest to the biggest construction sites. The boards are available in numerous configurations that differ in terms of number and type of socket-outlet, protected by MCB or fuse holder base. A selection of ready to use pre-wired or empty versions is available, and these can be personalised to suit all site needs and certified using ENERGY PRO software. The range is completed by a range of portable floodlights and luminous indicator devices.

WIRED MAIN BOARDS FOR CONSTRUCTION SITES

68 CDK ACS - waterthight termhoplastic boards



GW 68 537

Wired boards in thermoplastic with transparent door equipped with lock - Grey RAL 7035

Code	Outer dim. LxHxD (mm)	In/out power supply	MCB'S MT main RCCB	Power suppliable (kW)	Pack Carton
No. of poles: 4					
GW 68 536	298x260x140	PG29x2	RCBO 32 A	17	1
GW 68 537	298x260x140	PG36x2	RCBO 63 A	33	1
GW 68 538	410x285x140	PG36x2	RCBO 100 A	53	1
GW 68 539	410x285x140	PG42x2	RCBO 125 A	65	1

APPLICATIONS: Typical application: main boars for construction sites. It is installed downstream of the energy meter and protects the lenght of the cable from the main energy board to the secondary distribution boards.
ACCESSORIES SUPPLIED: Emergency push-botton; PG-type cable glands for cable inlet and outlet: kit of 4 wall fixing brackets.

68 QP ACS - Watertight polyester boards



GW 68 526

Wired polyester boards with blank door equipped with lock - Grey RAL 7035

Code	Outer dim. LxHxD (mm)	In/out power supply	Mains switch	RCCB protection	Power suppliable (kW)	Pack Carton
No. of poles: 4						
GW 68 521	405x500x200	2xPG42	MTHP 125	Side-by-side -adjustable	60	1
GW 68 526	405x500x200	2xPG42	MSXD 160	Integrated adjustable	75	1
GW 68 531	515x650x250	8xPG29	MSXD 250	Integrated adjustable	140	1

CHARACTERISTICS: The last modular row of the board should be reserved for the cable input / output terminals. the cable glands for cable input / output are positioned on the back of the boards.
APPLICATIONS: Typical application: main boars for construction sites. It is installed downstream of the energy meter and protects the lenght of the cable from the main energy board to the secondary distribution boards.
ACCESSORIES SUPPLIED: Transportation handle; mushroom-head emergency push-button connected to the minimum voltage release of the mains switch; PG-type cable glands for cable inlet and outlet; set of 4 surface-mounting fixing brackets in stainless steel; key-operated security locks with handle.

WIRED DISTRIBUTION BOARDS FOR CONSTRUCTION SITES

Q-BOX board with sockets IEC 309



GW 68 469

Q-BOX 4 - wired boards with sockets IEC 309 equipped with terminal block - IP55

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Power suppliable (kW)	Pack Carton
No. socket outlets: 12				
GW 68 468	12	-	12	1
GW 68 469	6	6	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-BOX board with interlocked socket-outlets (SBF type)



GW 68 511

Q-BOX 4 - wired boards with interlocked sockets equipped with terminal block - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	2P+E 32 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4								
GW 68 561	4	-	-	-	-	-	6	1
GW 68 562	3	1	-	-	-	-	17	1
GW 68 563	2	2	-	-	-	-	17	1
GW 68 564	2	1	1	-	-	-	17	1
GW 68 511	3	-	-	1	-	-	12	1
GW 68 565	3	-	-	-	1	-	17	1
GW 68 566	3	-	-	-	-	1	17	1
GW 68 567	2	1	-	-	1	-	17	1
GW 68 568	2	-	1	-	-	1	17	1
GW 68 569	2	1	-	-	-	1	17	1
GW 68 570	1	2	-	-	1	-	17	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 513

Q-BOX 4 - wired boards with interlocked sockets and not interlocked sockets (IEC 309) equipped with terminal block - IP55

Code	2P+ E 16 A - IEC 309	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	3P+E 63 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 5									
GW 68 512	2	-	3	-	-	-	-	33	1
GW 68 571	2	1	1	-	1	-	-	33	1
GW 68 572	2	1	1	-	-	1	-	33	1
GW 68 513	2	-	2	-	1	-	-	33	1
GW 68 573	2	-	2	-	-	1	-	33	1
GW 68 514	2	-	1	1	-	1	-	33	1
GW 68 574	2	-	1	-	1	-	1	33	1
No. socket outlets: 8									
GW 68 542	-	4	3	-	-	1	-	53	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
GW68542 equipped with interlocked sockets type COMBIBLOC IP55.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 541

Q-BOX 4 - wired boards with interlocked sockets and domestic sockets equipped with terminal block - IP55

Code	German Std socket-outlet 16 A	2P+E 16 A	3P+E 16 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 9						
GW 68 541	4	2	2	1	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 491

Q-BOX 6 - wired boards with interlocked sockets equipped with terminal block - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	3P+N+E 63 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 6								
GW 68 575	6	-	-	-	-	-	6	1
GW 68 576	4	2	-	-	-	-	17	1
GW 68 577	3	3	-	-	-	-	17	1
GW 68 578	3	2	1	-	-	-	17	1
GW 68 493	3	2	-	1	-	-	33	1
GW 68 579	3	2	-	-	1	-	33	1
GW 68 580	3	1	1	1	-	-	33	1
GW 68 581	3	1	1	-	1	-	33	1
GW 68 582	2	3	-	1	-	-	33	1
GW 68 583	2	2	-	1	1	-	33	1
GW 68 492	2	1	1	1	1	-	33	1
GW 68 494	2	2	-	2	-	-	33	1
GW 68 491	2	-	2	-	2	-	33	1
GW 68 495	2	1	-	-	3	-	33	1
GW 68 496	3	-	-	-	2	1	53	1
GW 68 497	2	-	-	-	2	2	53	1
No. socket outlets: 12								
GW 68 544	6	3	1	-	2	-	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
GW68544 equipped with interlocked sockets type COMBIBLOC IP55.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 914x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 543

Q-BOX 6 - wired boards with interlocked sockets and domestic sockets equipped with terminal block - IP55

Code	German Std socket-outlet 16 A	2P+E 16 A	3P+E 16 A	3P+N+E 32 A	3P+N+E 63 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 11							
GW 68 543	4	3	2	1	1	53	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 914x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 481

Q-BOX 4 - wired boards with interlocked sockets equipped with fixed plug - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4							
GW 68 584	4	-	-	-	-	6	1
GW 68 481	3	1	-	-	-	17	1
GW 68 482	2	2	-	-	-	17	1
GW 68 585	2	1	1	-	-	17	1
GW 68 586	2	1	-	1	-	17	1
GW 68 587	2	1	-	-	1	17	1
GW 68 588	1	2	-	1	-	17	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, fixed plug, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 483

Q-BOX 4 - wired boards with interlocked sockets and sockets IEC 309 equipped with fixed plug - IP55

Code	2P+ E 16 A - IEC 309	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	3P+E 63 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 5									
GW 68 589	2	1	1	-	1	-	-	33	1
GW 68 590	2	1	1	-	-	1	-	33	1
GW 68 483	2	-	2	-	1	-	-	33	1
GW 68 592	2	-	2	-	-	1	-	33	1
GW 68 484	2	-	1	1	-	1	-	33	1
GW 68 593	2	-	1	-	1	-	1	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, fixed plug, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 473

Q-BOX 6 - wired boards with interlocked sockets equipped with fixed plug - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 6							
GW 68 594	6	-	-	-	-	6	1
GW 68 595	4	2	-	-	-	17	1
GW 68 473	3	3	-	-	-	17	1
GW 68 596	3	2	1	-	-	17	1
GW 68 471	3	2	-	1	-	33	1
GW 68 597	3	2	-	-	1	33	1
GW 68 598	3	-	2	-	1	33	1
GW 68 472	2	3	-	1	-	33	1
GW 68 599	2	2	-	1	1	33	1
GW 68 600	2	2	-	2	-	33	1
GW 68 474	2	-	2	-	2	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses.
ACCESSORIES SUPPLIED: Emergency push-botton, fixed plug, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 914x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-BOX board with interlocked socket-outlets with fuse-holder (CBF type)



GW 68 562 F

Q-BOX 4 - wired boards with interlocked sockets and fuse-holder equipped with terminal bloc - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	2P+E 32 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4								
GW 68 561 F	4	-	-	-	-	-	6	1
GW 68 562 F	3	1	-	-	-	-	17	1
GW 68 563 F	2	2	-	-	-	-	17	1
GW 68 564 F	2	1	1	-	-	-	17	1
GW 68 511 F	3	-	-	1	-	-	12	1
GW 68 565 F	3	-	-	-	1	-	17	1
GW 68 566 F	3	-	-	-	-	1	17	1
GW 68 567 F	2	1	-	-	1	-	17	1
GW 68 568 F	2	-	1	-	-	1	17	1
GW 68 569 F	2	1	-	-	-	1	17	1
GW 68 570 F	1	2	-	-	1	-	17	1
No. socket outlets: 5								
GW 68 512 F	2	3	-	-	-	-	33	1
GW 68 571 F	3	1	-	-	1	-	33	1
GW 68 572 F	3	1	-	-	-	1	33	1
GW 68 513 F	2	2	-	-	1	-	33	1
GW 68 573 F	2	2	-	-	-	1	33	1
GW 68 514 F	2	1	1	-	-	1	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses. Each sockets is protected by fuses (supplied as accessory in the boards).
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 577 F

Q-BOX 6 - wired boards with interlocked sockets and fuse-holder equipped with terminal block - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	3P+E 63 A	3P+N+E 63 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 5									
GW 68 574 F	2	1	-	1	-	1	-	42	1
GW 68 498 F	2	-	1	-	1	-	1	42	1
No. socket outlets: 6									
GW 68 575 F	6	-	-	-	-	-	-	6	1
GW 68 576 F	4	2	-	-	-	-	-	17	1
GW 68 577 F	3	3	-	-	-	-	-	17	1
GW 68 578 F	3	2	1	-	-	-	-	17	1
GW 68 493 F	3	2	-	1	-	-	-	33	1
GW 68 579 F	3	2	-	-	1	-	-	33	1
GW 68 580 F	3	1	1	1	-	-	-	33	1
GW 68 582 F	2	3	-	1	-	-	-	33	1
GW 68 583 F	2	2	-	1	1	-	-	33	1
GW 68 494 F	2	2	-	2	-	-	-	33	1
GW 68 491 F	2	-	2	-	2	-	-	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses. Each sockets is protected by fuses (supplied as accessory in the boards).
ACCESSORIES SUPPLIED: Emergency push-botton, terminal block, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 914x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 481 F

Q-BOX 4 - wired boards with interlocked sockets and fuse-holder equipped with fixed plug - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4							
GW 68 584 F	4	-	-	-	-	6	1
GW 68 481 F	3	1	-	-	-	17	1
GW 68 482 F	2	2	-	-	-	17	1
GW 68 586 F	2	1	-	1	-	17	1
GW 68 587 F	2	1	-	-	1	17	1
GW 68 588 F	1	2	-	1	-	17	1
No. socket outlets: 5							
GW 68 589 F	3	1	-	1	-	33	1
GW 68 590 F	3	1	-	-	1	33	1
GW 68 483 F	2	2	-	1	-	33	1
GW 68 592 F	2	2	-	-	1	33	1
GW 68 484 F	2	1	1	-	1	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses. Each sockets is protected by fuses (supplied as accessory in the boards).
ACCESSORIES SUPPLIED: Emergency push-botton, fixed plug, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 636x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 473 F

Q-BOX 6 - wired boards with interlocked sockets and fuse-holder equipped with fixed plug - IP55

Code	2P+E 16 A	3P+E 16 A	3P+N+E 16 A	3P+E 32 A	3P+N+E 32 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 6							
GW 68 594 F	6	-	-	-	-	6	1
GW 68 595 F	4	2	-	-	-	17	1
GW 68 473 F	3	3	-	-	-	17	1
GW 68 596 F	3	2	1	-	-	17	1
GW 68 471 F	3	2	-	1	-	33	1
GW 68 597 F	3	2	-	-	1	33	1
GW 68 598 F	3	-	2	-	1	33	1
GW 68 472 F	2	3	-	1	-	33	1
GW 68 599 F	2	2	-	1	1	33	1
GW 68 600 F	2	2	-	2	-	33	1

CHARACTERISTICS: Thermoplastic boards with high resistance impact (IK10). Typical application: main or secondary distribution boards for construction sites, exibition areas, and temporary uses. Each sockets is protected by fuses (supplied as accessory in the boards).
ACCESSORIES SUPPLIED: Emergency push-botton, fixed plug, stainless steel tear-proof cablefastening hooks, N. 2 triangolar lock, set of steel brackets for surface-mounting.
NOTES: external dimensions (BxHxP) 914x821x400 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

WIRED MOBILE BOARDS FOR CONSTRUCTION SITES

Q-DIN 5 - mobile, portable boards with sockets IEC 309



GW 68 241 N

Protected board equipped with cable and mobile plug - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	German Std socket-outlet 16 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 3				
GW 68 241 N	2	1	3	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 105x430x96 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 217 N

Watertight board equipped with cable and mobile plug - IP65

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Power suppliable (kW)	Pack Carton
No. socket outlets: 3				
GW 68 217 N	3	-	3	1
GW 68 242 N	2	1	8	1
GW 68 243 N	1	2	8	1
GW 68 244 N	-	3	8	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 105x430x96 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 223 N

Watertight board in yellow schockproof equipped with cable and mobile plug - IP65

Code	Socket-outlet 2P+E 16A - IEC 309	Power suppliable (kW)	Pack Carton
No. socket outlets: 3			
GW 68 223 N	3	3	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 140x560x105 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-DIN 10 - mobile, portable boards with sockets IEC 309



GW 68 203 N

Protected board equipped with cable and mobile plug - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	German Std socket-outlet 16 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4				
GW 68 203 N	2	2	3	1

NOTES: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 140x560x105 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 216 N

Watertight board equipped with cable and mobile plug - IP65

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-outlet 3P+N+E 16A - IEC 309	Power suppliable (kW)	Pack Carton
No. socket outlets: 4					
GW 68 216 N	4	-	-	3	1
GW 68 245 N	3	1	-	8	1
GW 68 246 N	3	-	1	8	1
GW 68 204 N	2	2	-	8	1
GW 68 247 N	-	4	-	8	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 220x435x96 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 401 N

Protected board equipped with cable and mobile plug, with yellow painted accident prevention metal conduit support - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	German Std socket-outlet 16 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 4					
GW 68 401 N	2	1	1	8	1

ACCESSORIES SUPPLIED: 15 m of cable H 07 RN - F and mobile plug, yellow metal support.
NOTES: external dimensions (BxHxP) 220x435x96 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-DIN 14 - mobile, portable boards with sockets IEC 309



GW 68 250 N

Watertight board equipped with cable and mobile plug - IP65

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-outlet 3P+E 32A - IEC 309	Power suppliable (kW)	Pack Carton
No. socket outlets: 6					
GW 68 248 N	6	-	-	8	1
GW 68 249 N	4	2	-	17	1
GW 68 250 N	3	3	-	17	1
GW 68 251 N	3	2	1	17	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) 320x510x120 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.



GW 68 411 N

Protected board equipped with cable and mobile plug, with yellow painted accident prevention metal conduit carriage with two wheels and rotary drum for rewinding and storing the cable - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	German Std socket-outlet 16 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 6					
GW 68 411 N	2	2	2	17	1

ACCESSORIES SUPPLIED: 25 m of cable H 07 RN - F and mobile plug, yellow metal carriage.
NOTES: external dimensions (BxHxP) 320x510x120 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-DIN 20 - mobile, portable boards with sockets IEC 309 and interlocked socket-outlets



GW 68 421 N

Protected board equipped with cable and mobile plug, with yellow painted accident prevention metal conduit carriage with two wheels and rotary drum for rewinding and storing the cable - IP44

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-out 3P+E 32A - IEC309	German Std socket-outlet 16 A	Power suppliable (kW)	Pack Carton
No. socket outlets: 8						
GW 68 421 N	2	2	2	2	17	1

ACCESSORIES SUPPLIED: 35 m of cable H 07 RN - F and mobile plug, yellow metal carriage.
NOTES: external dimensions (BxHxP) 450x560x120 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

68 ACS



GW 68 424 N

Watertight board equipped with cable and mobile plug, with yellow painted accident prevention metal conduit carriage with two wheels and rotary drum for rewinding and storing the cable - IP65

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+E 16A - IB	Socket-out 3P+E 32A - IB	Power suppliable (kW)	Pack Carton
No. socket outlets: 4					
GW 68 424 N	2	1	1	33	1

ACCESSORIES SUPPLIED: 35 m of cable H 07 RN - F and mobile plug, yellow metal carriage.
NOTES: external dimensions (BxHxP) 450x560x120 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

Q-DIN - mobile, portable boards with safety transformer



GW 68 235 N

Watertight board with equipped safety transformer with cable and mobile plug - IP65

Code	with transformer 2P - 16A - 24V	Socket-outlet 2P+E 16A - IB	Power suppliable (kW)	Pack Carton
No. socket outlets: 2				
GW 68 235 N	2	-	3	1/2
No. socket outlets: 4				
GW 68 236 N	2	2	3	1

ACCESSORIES SUPPLIED: 4 m of cable H 07 RN - F and mobile plug, insulating screw caps to mantain double insulation and original IP degree of boards.
NOTES: external dimensions (BxHxP) GW68235N 220x435x96 mm; GW68236N 450x560x120 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

66 COMBIBLOC - WIRED BOARDS FOR CONSTRUCTION SITES

COMBIBLOC - Portable distribution boards



GW 66 388

Combibloc ACS boards equipped with cable and plug IEC309 Metal conduit support yellow-painted support - IP55

Code	Socket-outlet 2P+E 16A - IB	Socket-outlet 3P+N+E 16A - IB	Socket-outlet 3P+N+E 32A - IB	Pack Carton
GW 66 388	2	1	-	1
GW 66 389	1	1	1	1

ACCESSORIES SUPPLIED: 5 m of cable H 07 RN - F and mobile plug, metal conduit support.
NOTES: external dimensions (BxHxP) 320x360x95 mm.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

68 QMC - WIRED PEDESTAL FOR CONSTRUCTION SITES

Q-MC 16T - Transportable pedestal



GW 68 881 A

QMC 16 T ACS transportable wired terminal with double-face take-off equipped with non-interlocked switched socket-outlets - IP56

Code	Socket-outlet 2P+E 16A - IEC 309	Socket-outlet 3P+E 16A - IEC 309	Socket-outlet 3P+N+E 16A - IEC 309	Socket-outlet 3P+N+E 32A - IEC 309	Pack Carton
GW 68 881 A	7	-	-	-	1
GW 68 883 A	4	1	1	1	1
GW 68 884 A	2	1	2	1	1

CHARACTERISTICS: Stainless steel cable fastener devices, enclosure with hinged opening that can be fitted with security lock for access to modular devices.
ACCESSORIES SUPPLIED: 5 m of cable H 07 RN - F and mobile plug, metal conduit support.
Please refer to Gewiss web site to download the wiring diagrams of the boards.

ACS PREDETERMINED CONSTRUCTION SYSTEM COMPONENTS

46 QP - Watertight polyester boards - IP66



GW 46 004 F

Watertight boards in polyester with blank door fitted with lock - Grey RAL 7035

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Pack Carton
GW 46 003 F	405x500x200	54 (18x3)	2	1
GW 46 004 F	405x650x200	72 (18x4)	2	1
GW 46 005 F	515x650x250	96 (24x4)	2	1
GW 46 006 F	585x800x300	140 (28x5)	2	1

NOTES: it is necessary use ENERGY PRO software to realize certification in accordance with ACS standard and the GEWISS construction standard.
Refer to section in the catalogue " 46 QP Range - Watertight Surface mounting distribution and automation borads" for any further information related to the boards and their acceries.



GW 46 203 F

Polyester watertight boards with transparent door and lock - Grey RAL 7035

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Pack Carton
GW 46 203 F	405x500x200	54 (18x3)	2	1
GW 46 204 F	405x650x200	72 (18x4)	2	1
GW 46 205 F	515x650x250	96 (24x4)	2	1
GW 46 206 F	585x800x300	140 (28x5)	2	1

NOTES: It is necessary use ENERGY PRO software to realize certification in accordance with ACS standard and the GEWISS construction standard.
Refer to section in the catalogue " 46 QP Range - Watertight Surface mounting distribution and automation borads" or any further information related to the boards and their acceries.

40 CDK - unwired enclosures fir ingoing and measurement assemblies



GW 40 103

Enclosures prearranged for housing terminal blocks Transparent smoked door - smooth walls - IP65

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pack Carton
GW 40 103	12	298x260x140	6
GW 40 106	18	410x285x140	3
GW 40 104	24	298x420x140	3

NOTES: It is necessary use ENERGY PRO software to realize certification in accordance with ACS standard and the GEWISS construction standard.
Refer to section in the catalogue " 40 CDK Range - Surface mounting distribution borads and enclosures" for any further information related to the boards and their acceries.

68 Q-BOX - Unwired final distribution board



GW 68 465

Q-BOX 4 unwired distribution board - IP55

Code	Supplied Earth Terminal block	No. of modules EN 50022	Pack Carton
GW 68 465	(7x10 mm²)	12	1

ACCESSORIES SUPPLIED: modular enclosure 12+1M and blank enclosure for terminal block. Set of brackets for surface-mounting.
NOTES: It is necessary use ENERGY PRO software to realize certification in accordance with ACS standard and the GEWISS construction standard




GW 68 466

Q-BOX 6 unwired distribution boards - IP55

Code	Supplied Earth Terminal block	No. of modules EN 50022	Pack Carton
GW 68 466	(2x25mm²)+(10x10mm²)	24 (12+12)	1

ACCESSORIES SUPPLIED: 2 modular enclosures 12+1M each, and blank enclosure for terminal block. Set of brackets for surface-mounting.
NOTES: It is necessary use ENERGY PRO software to realize certification in accordance with ACS standard and the GEWISS construction standard.

Complementary items for 68 Q-BOX



GW 46 554

Pole support kit

Code	For distribution boards	Pack Carton
GW 46 554	Q-BOX 4	1

APPLICATIONS: for applying boards 68 Q-BOX 4 on poles from 60mm to 80mm.
CHARACTERISTICS: fixed on the back of the boards.
ACCESSORIES SUPPLIED: 2 pieces. For the correct use of the kit, see the instructions sheet.



GW 68 552

Panels for Q-BOX 4/6 - IP55

Code	Description	Dimensions (mm)	Pack Carton
GW 68 551	Panel - blank	270x368	1
GW 68 552	12 modules board	270x368	1
GW 68 554	4 COMBIBLOC 16-32A IP44/55	270x368	1
GW 68 556	2 IB Vert. 16-32A IP67 + 2 IEC 309 16A IP44/67 or GW27401	270x368	1
GW 68 559	5 IB Vert. 16-32A IP67 + 4 IEC 309 16A IP44/67 or GW27401	540x368	1

ACCESSORIES SUPPLIED: panels with base, fixing screws and closure.
CHARACTERISTICS:
Internal space of Q-BOX 4: 540x415mm
Internal space of Q-BOX 6: 810x415mm.



GW 68 591

Fixing kit for 160A one-way switches for GW68552 panel

Code	Description	Pack Carton
GW 68 591	For inserting from 160A	1/20



GW 68 504

Emergency push button kit

Code	Description	Pack Carton
GW 68 504	Kit equipped with red emergency push button and green light to show the integrity of the circuit	1/4



GW 68 503

12-module watertight enclosure front for Q-BOX - IP55

Code	No. of modules EN 50022	Pack Carton
GW 68 503	12+1	1/8



GW 68 505

Watertight plug - socket-outlet block

Code	Description	Pack Carton
GW 68 505	Plug/socket-outlet block	1/10

NOTE: the block is suitable for 32A (only 3P+E and 3P+N+E) and 63 A socket-outlet - plug connections.



GW 68 463

Yellow metal support for Q-BOX 4/6

Code	Outer dim. LxHxD (mm)	Pack Carton
GW 68 463	1100x1650x630	1

CHARACTERISTICS: 2 side handles for manual handling; 2 slots on the top for lifting with a crane.



GW 46 445

Security lock with handle

Code	Description	Pack Carton
GW 46 445	Security lock key and handle	10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: all the keys and relative locks with the same product code are identical.



GW 46 447

Document holder pocket in self-adhesive insulating material with kit of blank labels

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10

CHARACTERISTICS: the document wallet can be inserted in all Gewiss distribution boards starting with the 405x500x200 mm dimension.

LUMINOUS INDICATOR DEVICES

RETTA - Rectangular luminaires



GW 80 401

Versions for incandescent lamps - IP44 - Class II

Code	Max lamp power	Lamp	Lamp holder	Diffuser colour	Weight (kg)	Pack Carton
GW 80 401	75 W	IA/IB	E27	Transparent	0.3	12
GW 80 403	75 W	IA/IB	E27	Red	0.3	12
GW 80 404	75 W	IA/IB	E27	Green	0.3	12

TARTA - Oval luminaires



GW 80 411

Versions for incandescent lamps - IP44 - Class II

Code	Max lamp power	Lamp	Lamp holder	Diffuser colour	Weight (kg)	Pack Carton
GW 80 409	60 W	IA/IB	E27	Transparent	0.2	36
GW 80 411	60 W	IA/IB	E27	Red	0.2	36
GW 80 412	60 W	IA/IB	E27	Green	0.2	36

CHARACTERISTICS: suitable for installation directly on to walls via screws or on to pipes using cable ties.



68 ACS



Scan the QR Code and find out all the technical informations.

OUT-OF-THE-BOX WIRED SOLUTIONS



Pre-wired versions are available, equipped with interlocked sockets (with or without fuse holder base) up to 63A or IEC type fixed sockets. They are also equipped with an emergency push button, key locked doors, SST strain-resistant cable hooks and carrying handles located at the top of the enclosure.

CUSTOMISABLE CONFIGURATIONS

ENERGY PRO SELECTION

Empty versions are available that can be customised for all site needs. With ENERGY PRO software, you can quickly and easily create and certify your ASC configuration.

CONFIGURATION PANELS



Specific additional panels permit to create different distribution board configurations, according to the specific needs of each construction site. Thanks to switchboard panels, for example, it is possible to obtain panels of switches only (up to 60 modules), while with the socket-outlets panels it is possible to have boards with 12 interlocked socket-outlets.

Control and signalling





70 RT HP

Rotary isolators

p. 147

74 PS

Push-buttons,
selectors and
indicators Ø 22 mm

p. 160

70 RT HP

Rotary isolators

In	POLES	VERSIONS IN INSULATING ENCLOSURE				VERSIONS IN ALUMINIUM ENCLOSURE	
		CONTROL	CONTROL	EMERGENCY	EMERGENCY	CONTROL	CONTROL
							
		Dim: 125 x 150 x 75,5 mm	Dim: 153,6 x 200,6 x 117 mm	Dim: 125 x 150 x 75,5 mm	Dim: 153,6 x 200,6 x 117 mm	Dim: 140 x 165 x 64 mm	Dim: 200 x 230 x 110 mm
16A	2P	GW 70 401 P		GW 70 431 P		GW 70 401 M	
	3P	GW 70 402 P		GW 70 432 P		GW 70 402 M	
	3P+N	GW 70 402 NP		GW 70 432 NP		GW 70 402 NM	
	4P	GW 70 403 P		GW 70 433 P		GW 70 403 M	
	6P		GW 70 601 P		GW 70 641P		GW 70 701 M
	8P		GW 70 621 P		GW 70 661P		GW 70 721 M
25A	2P	GW 70 416 P		GW 70 486 P		GW 70 416 M	
	3P	GW 70 417 P		GW 70 487 P		GW 70 417 M	
	3P+N	GW 70 417 NP		GW 70 487 NP		GW 70 417 NM	
	4P	GW 70 418 P		GW 70 488 P		GW 70 418 M	
	6P		GW 70 602 P		GW 70 642 P		GW 70 702 M
	8P		GW 70 622 P		GW 70 662 P		GW 70 722 M
32A	2P	GW 70 404 P		GW 70 434 P		GW 70 404 M	
	3P	GW 70 405 P		GW 70 435 P		GW 70 405 M	
	3P+N	GW 70 405 NP		GW 70 435 NP		GW 70 405 NM	
	4P	GW 70 406 P		GW 70 436 P		GW 70 406 M	
	6P		GW 70 603 P		GW 70 643 P		GW 70 703 M
	8P		GW 70 623 P		GW 70 663 P		GW 70 723 M
40A	2P	GW 70 413 P		GW 70 441 P		GW 70 413 M	
	3P	GW 70 414 P		GW 70 442 P		GW 70 414 M	
	3P+N	GW 70 414 NP		GW 70 442 NP		GW 70 414 NM	
	4P	GW 70 415 P		GW 70 443 P		GW 70 415 M	
	6P		GW 70 604 P		GW 70 644 P		GW 70 704 M
	8P		GW 70 624 P		GW 70 664 P		GW 70 724 M
							
		Dim: 156 x 200 x 95 mm	236,5 x 315,5 x 178 mm	Dim: 156 x 200 x 95 mm	Dim: 236,5 x 315,5 x 178 mm	Dim: 215 x 252 x 91 mm	Dim: 257 x 307 x 121 mm
63A	3P	GW 70 407 P		GW 70 437 P		GW 70 407 M	
	3P+N	GW 70 407 NP		GW 70 437 NP		GW 70 407 NM	
	4P	GW 70 408 P		GW 70 438 P		GW 70 408 M	
	6P		GW 70 605 P		GW 70 645 P		GW 70 705 M
	8P		GW 70 625 P		GW 70 665 P		GW 70 725 M
80A	3P	GW 70 419 P		GW 70 489 P		GW 70 419 M	
	3P+N	GW 70 419 NP		GW 70 489 NP		GW 70 419 NM	
	4P	GW 70 420 P		GW 70 490 P		GW 70 420 M	
							
		Dim: 236,5 x 316 x 178 mm	Dim: 236,5 x 316 x 178 mm	Dim: 236,5 x 316 x 178 mm	Dim: 236,5 x 316 x 178 mm	Dim: 257 x 307 x 121 mm	Dim: 257 x 307 x 121 mm
100A	3P	GW 70 421 P		GW 70 491 P		GW 70 421 M	
	3P+N	GW 70 421 NP		GW 70 491 NP		GW 70 421 NM	
	4P	GW 70 422 P		GW 70 492 P		GW 70 422 M	
	6P		GW 70 607 P		GW 70 647 P		GW 70 707 M
	8P		GW 70 627 P		GW 70 667 P		GW 70 727 M
125A	3P	GW 70 423 P		GW 70 493 P		GW 70 423 M	
	3P+N	GW 70 423 NP		GW 70 493 NP		GW 70 423 NM	
	4P	GW 70 424 P		GW 70 494 P		GW 70 424 M	
160A	3P	GW 70 425 P		GW 70 495 P		GW 70 425 M	
	3P+N	GW 70 425 NP		GW 70 495 NP		GW 70 425 NM	
	4P	GW 70 426 P		GW 70 496 P		GW 70 426 M	

NOTE: the dimensions shown above refer to the external dimensions of the boxes without considering the knob.

VERSIONS IN ALUMINIUM ENCLOSURE		AUXILIARY CONTACTS			DC VERSIONS FOR PHOTOVOLTAIC APPLICATIONS IN INSULATING ENCLOSURE	ATEX VERSIONS IN ALUMINIUM ENCLOSURE	
EMERGENCY	EMERGENCY					CONTROL	EMERGENCY
							
Dim: 140 x 165 x 64 mm	**Dim: 200 x 230 x 110 mm**	**1NO + 1NC**	**2NO**	**2NC**	**Dim: 153,6 x 200,6 x 117 mm**	**Dim: 140 x 165 x 63 mm**	**Dim: 140 x 165 x 63 mm**
GW 70 431 M		GW 70 026	GW 70 027	GW 70 028	GW 70 231	GW 70 451	GW 70 471
GW 70 432 M						GW 70 452	GW 70 472
GW 70 432 NM							
GW 70 433 M						GW 70 453	GW 70 473
	GW 70 741 M	GW 70 029					
	GW 70 761 M						
GW 70 486 M		GW 70 026	GW 70 027	GW 70 028			
GW 70 487 M					GW 70 235		
GW 70 487 NM							
GW 70 488 M							
	GW 70 742 M	GW 70 029					
	GW 70 762 M						
GW 70 434 M		GW 70 026	GW 70 027	GW 70 028		GW 70 454	GW 70 474
GW 70 435 M					GW 70 238	GW 70 455	GW 70 475
GW 70 435 NM							
GW 70 436 M					GW 70 239	GW 70 456	GW 70 476
	GW 70 743 M	GW 70 029					
	GW 70 763 M						
GW 70 441 M		GW 70 026	GW 70 027	GW 70 028			
GW 70 442 M							
GW 70 442 NM							
GW 70 443 M					GW 70 242		
	GW 70 744 M	GW 70 029					
	GW 70 764 M						
							
Dim: 215 x 252 x 91 mm	**257 x 307 x 121 mm**	**1NO + 1NC**	**2NO**	**2NC**		**Dim: 215 x 252 x 91 mm**	**Dim: 215 x 252 x 91 mm**
GW 70 437 M		GW 70 026	GW 70 027	GW 70 028		GW 70 457	GW 70 477
GW 70 437 NM							
GW 70 438 M						GW 70 458	GW 70 478
	GW 70 745 M	GW 70 029					
	GW 70 765 M						
GW 70 489 M		GW 70 026	GW 70 027	GW 70 028			
GW 70 489 NM							
GW 70 490 M							
							
Dim: 257 x 307 x 121 mm	**Dim: 257 x 307 x 121 mm**	**1NO + 1NC**	**2NO**	**2NC**		**Dim: 307 x 257 x 120 mm**	**Dim: 307 x 257 x 120 mm**
GW 70 491 M		GW 70 029				GW 70 459	GW 70 479
GW 70 491 NM							
GW 70 492 M						GW 70 460	GW 70 480
	GW 70 747 M						
	GW 70 767 M						
GW 70 493 M							
GW 70 493 NM							
GW 70 494 M							
GW 70 495 M							
GW 70 495 NM							
GW 70 496 M							

Rotary isolators

In	POLES	VERSIONS FOR BOARD				
		PANEL/DOOR MOUNTING (*)	DIN RAIL MOUNTING	AUXILIARY CONTACTS		
				1NO + 1NC	2NO	2NC
16A	2P	GW 70 001	GW 70 201	GW 70 026	GW 70 027	GW 70 028
	3P	GW 70 002	GW 70 202			
	4P	GW 70 003	GW 70 203			
25A	3P	GW 70 052				
	4P	GW 70 053				
32A	2P	GW 70 004	GW 70 204			
	3P	GW 70 005	GW 70 205			
	4P	GW 70 006	GW 70 206			
40A	3P	GW 70 055				
	4P	GW 70 056				
63A	3P	GW 70 007	GW 70 207			
	4P	GW 70 008	GW 70 208			
80A	3P	GW 70 058				
	4P	GW 70 059				
100A	3P	GW 70 061		GW 70 029		
	4P	GW 70 062				
125A	3P	GW 70 064				
	4P	GW 70 065				
160A	3P	GW 70 067				
	4P	GW 70 068				

(*) Versions for panel/door mounting can be accessorized with galvanized steel extending brackets GW 70 009.

In	POLES	VERSIONS FOR BOARD					
		PANEL/DOOR MOUNTING	AUXILIARY CONTACTS		PHASE BARRIERS	TERMINAL COVERS	SHAFTS
			1NC	1EB			
200A	3P	GW 70 070	GW 70 035	GW 70 036	GW 70 171	GW 70 181	GW 70 040
	4P	GW 70 071			GW 70 172	GW 70 182	
250A	3P	GW 70 073			GW 70 171	GW 70 181	
	4P	GW 70 074			GW 70 172	GW 70 182	
315A	3P	GW 70 076			GW 70 173	GW 70 183	
	4P	GW 70 077			GW 70 174	GW 70 184	
400A	3P	GW 70 079			GW 70 173	GW 70 183	
	4P	GW 70 080			GW 70 174	GW 70 184	
630A	3P	GW 70 085			GW 70 175	GW 70 185	GW 70 041
	4P	GW 70 086			GW 70 176	GW 70 186	
800A	3P	GW 70 088			GW 70 175	GW 70 185	
	4P	GW 70 089			GW 70 176	GW 70 186	
1000A	3P	GW 70 091			GW 70 175	GW 70 185	
	4P	GW 70 092			GW 70 176	GW 70 186	

70 RT HP

Rotary isolators



70 RT HP is a complete offer of rotary isolator switches from 16A to 160A, available in boxes both in insulating material and aluminium, in control or emergency versions, compatible with the main applications for residential, tertiary and industrial contexts. DC versions for photovoltaic applications are also available from 16A to 40A in insulating box. The series is completed with versions for board from 16A to 1000A and for DIN rail fixing from 16A to 63A, which can be equipped with auxiliary contacts. The devices have been designed to reduce wiring time, facilitate installation and guarantee the maximum safety and robustness even in the most demanding conditions.

70 RT HP - SURFACE MOUNTING ROTARY ISOLATOR IN INSULATING ENCLOSURE - IP66/IP67/69

Control versions



GW 70 406 P

Surface-mounting isolator - control version with lockable black knob - IP66/IP67/IP69

Code	No. of poles	Outer dim. LxHxD (mm)	Holes entry	Lid screws (no. and type)	Pack Carton
Rated current (A): 16					
GW 70 401 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 402 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 402 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 403 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 601 P	6P	153,6x200,6x117	4xM20	4 insulation	1/4
GW 70 621 P	8P	153,6x200,6x117	4xM20	4 insulation	1/4
Rated current (A): 25					
GW 70 416 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 417 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 417 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 418 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 602 P	6P	153,6x200,6x117	4xM25	4 insulation	1/4
GW 70 622 P	8P	153,6x200,6x117	4xM25	4 insulation	1/4
Rated current (A): 32					
GW 70 404 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 405 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 405 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 406 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 603 P	6P	153,6x200,6x117	4xM25	4 insulation	1/4
GW 70 623 P	8P	153,6x200,6x117	4xM25	4 insulation	1/4
Rated current (A): 40					
GW 70 413 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 414 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 414 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 415 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 604 P	6P	153,6x200,6x117	4xM32	4 insulation	1/4
GW 70 624 P	8P	153,6x200,6x117	4xM32	4 insulation	1/4
Rated current (A): 63					
GW 70 407 P	3P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 407 NP	3P+N	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 408 P	4P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 605 P	6P	236,5x315,5x178	-	4 insulation	1
GW 70 625 P	8P	315,5x236,5x178	-	4 insulation	1
Rated current (A): 80					
GW 70 419 P	3P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 419 NP	3P+N	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 420 P	4P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
Rated current (A): 100					
GW 70 421 P	3P	236,5x316x178	-	4 insulation	1
GW 70 421 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 422 P	4P	236,5x316x178	-	4 insulation	1
GW 70 607 P	6P	236,5x315,5x178	-	4 insulation	1
GW 70 627 P	8P	315,5x236,5x178	-	4 insulation	1
Rated current (A): 125					
GW 70 423 P	3P	236,5x316x178	-	4 insulation	1
GW 70 423 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 424 P	4P	236,5x316x178	-	4 insulation	1
Rated current (A): 160					
GW 70 425 P	3P	236,5x316x178	-	4 insulation	1
GW 70 425 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 426 P	4P	236,5x316x178	-	4 insulation	1

NOTE: can be padlocked in ON and OFF position with max. 3 locks with diameter max. 8 mm. The 63-100A 6P-8P versions can be padlocked only in the OFF position with IP66/IP69 protection degree. Versions 100-160A up to 4P and 63-100A 6P and 8P allow to install max. 2 x M63 cable glands. All Lid screws are sealable.

Emergency versions



GW 70 436 P

Surface-mounting isolator - emergency version with lockable red knob - IP66/IP67/IP69

Code	No. of poles	Outer dim. LxHxD (mm)	Holes entry	Lid screws (no. and type)	Pack Carton
Rated current (A): 16					
GW 70 431 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 432 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 432 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 433 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 641 P	6P	153,6x200,6x117	4xM20	4 insulation	1/4
GW 70 661 P	8P	153,6x200,6x117	4xM20	4 insulation	1/4
Rated current (A): 25					
GW 70 486 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 487 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 487 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 488 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 642 P	6P	153,6x200,6x117	4xM25	4 insulation	1/4
GW 70 662 P	8P	153,6x200,6x117	4xM25	4 insulation	1/4
Rated current (A): 32					
GW 70 434 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 435 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 435 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 436 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 643 P	6P	153,6x200,6x117	4xM25	4 insulation	1/4
GW 70 663 P	8P	153,6x200,6x117	4xM25	4 insulation	1/4
Rated current (A): 40					
GW 70 441 P	2P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 442 P	3P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 442 NP	3P+N	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 443 P	4P	125x150x75,5	2 x M20/25 + 2 x M20/25	4 insul. 1/4 turn	1/16
GW 70 644 P	6P	153,6x200,6x117	4xM32	4 insulation	1/4
GW 70 664 P	8P	153,6x200,6x117	4xM32	4 insulation	1/4
Rated current (A): 63					
GW 70 437 P	3P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 437 NP	3P+N	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 438 P	4P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 645 P	6P	236,5x315,5x178	-	4 insulation	1
GW 70 665 P	8P	315,5x236,5x178	-	4 insulation	1
Rated current (A): 80					
GW 70 489 P	3P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 489 NP	3P+N	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
GW 70 490 P	4P	156x200x95	2 x M25/32 + 2 x M25/32	4 insul. 1/4 turn	1/6
Rated current (A): 100					
GW 70 491 P	3P	236,5x316x178	-	4 insulation	1
GW 70 491 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 492 P	4P	236,5x316x178	-	4 insulation	1
GW 70 647 P	6P	236,5x315,5x178	-	4 insulation	1
GW 70 667 P	8P	315,5x236,5x178	-	4 insulation	1
Rated current (A): 125					
GW 70 493 P	3P	236,5x316x178	-	4 insulation	1
GW 70 493 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 494 P	4P	236,5x316x178	-	4 insulation	1
Rated current (A): 160					
GW 70 495 P	3P	236,5x316x178	-	4 insulation	1
GW 70 495 NP	3P+N	236,5x316x178	-	4 insulation	1
GW 70 496 P	4P	236,5x316x178	-	4 insulation	1

NOTE: can be padlocked in OFF position with max. 3 locks with diameter max. 8 mm. The 63-100A 6P-8P versions can be padlocked only in the OFF position with IP66/IP69 protection degree. Versions 100-160A up to 4P and 63-100A 6P and 8P allow to install max. 2 x M63 cable glands. All Lid screws are sealable.

70 RT HP - SURFACE-MOUNTING ROTARY ISOLATOR IN ALUMINIUM ENCLOSURE - IP66

Control versions



GW 70 406 M

Surface-mounting isolator - control version with lockable black/grey knob - IP66

Code	No. of poles	Outer dim. LxHxD (mm)	Holes entry	Pack Carton
Rated current (A): 16				
GW 70 401 M	2P	140x165x64	4xM20	1
GW 70 402 M	3P	140x165x64	4xM20	1
GW 70 402 NM	3P+N	140x165x64	4xM20	1
GW 70 403 M	4P	140x165x64	4xM20	1
GW 70 701 M	6P	200x230x110	4xM20	1
GW 70 721 M	8P	200x230x110	4xM20	1
Rated current (A): 25				
GW 70 416 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 417 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 417 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 418 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 702 M	6P	200x230x110	4xM20	1
GW 70 722 M	8P	200x230x110	4xM20	1
Rated current (A): 32				
GW 70 404 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 405 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 405 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 406 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 703 M	6P	200x230x110	4xM20	1
GW 70 723 M	8P	200x230x110	4xM20	1
Rated current (A): 40				
GW 70 413 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 414 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 414 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 415 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 704 M	6P	200x230x110	4xM25	1
GW 70 724 M	8P	200x230x110	4xM25	1
Rated current (A): 63				
GW 70 407 M	3P	215x252x91	4xM32	1
GW 70 407 NM	3P+N	215x252x91	4xM32	1
GW 70 408 M	4P	215x252x91	4xM32	1
GW 70 705 M	6P	257x307x121	-	1
GW 70 725 M	8P	257x307x121	-	1
Rated current (A): 80				
GW 70 419 M	3P	215x252x91	4xM32	1
GW 70 419 NM	3P+N	215x252x91	4xM32	1
GW 70 420 M	4P	215x252x91	4xM32	1
Rated current (A): 100				
GW 70 421 M	3P	257x307x121	-	1
GW 70 421 NM	3P+N	257x307x121	-	1
GW 70 422 M	4P	257x307x121	-	1
GW 70 707 M	6P	257x307x121	-	1
GW 70 727 M	8P	257x307x121	-	1
Rated current (A): 125				
GW 70 423 M	3P	257x307x121	-	1
GW 70 423 NM	3P+N	257x307x121	-	1
GW 70 424 M	4P	257x307x121	-	1
Rated current (A): 160				
GW 70 425 M	3P	257x307x121	-	1
GW 70 425 NM	3P+N	257x307x121	-	1
GW 70 426 M	4P	257x307x121	-	1

NOTE: can be padlocked in ON and OFF position with max. 3 locks with diameter max. 8 mm.

Versions 100-160A up to 4P and 63-100A 6P and 8P allow to install max. 2 x M63 cable glands.

70 RT HP

Emergency versions



GW 70 436 M

Surface-mounting isolator - emergency version with lockable red/yellow - IP66

Code	No. of poles	Outer dim. LxHxD (mm)	Holes entry	Pack Carton
Rated current (A): 16				
GW 70 431 M	2P	140x165x64	4xM20	1
GW 70 432 M	3P	140x165x64	4xM20	1
GW 70 432 NM	3P+N	140x165x64	4xM20	1
GW 70 433 M	4P	140x165x64	4xM20	1
GW 70 741 M	6P	200x230x110	4xM20	1
GW 70 761 M	8P	200x230x110	4xM20	1
Rated current (A): 25				
GW 70 486 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 487 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 487 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 488 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 742 M	6P	200x230x110	4xM20	1
GW 70 762 M	8P	200x230x110	4xM20	1
Rated current (A): 32				
GW 70 434 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 435 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 435 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 436 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 743 M	6P	200x230x110	4xM20	1
GW 70 763 M	8P	200x230x110	4xM20	1
Rated current (A): 40				
GW 70 441 M	2P	140x165x64	2 x M20 + 2 x M25	1
GW 70 442 M	3P	140x165x64	2 x M20 + 2 x M25	1
GW 70 442 NM	3P+N	140x165x64	2 x M20 + 2 x M25	1
GW 70 443 M	4P	140x165x64	2 x M20 + 2 x M25	1
GW 70 744 M	6P	200x230x110	4xM25	1
GW 70 764 M	8P	200x230x110	4xM25	1
Rated current (A): 63				
GW 70 437 M	3P	215x252x91	4xM32	1
GW 70 437 NM	3P+N	215x252x91	4xM32	1
GW 70 438 M	4P	215x252x91	4xM32	1
GW 70 745 M	6P	257x307x121	-	1
GW 70 765 M	8P	257x307x121	-	1
Rated current (A): 80				
GW 70 489 M	3P	215x252x91	4xM32	1
GW 70 489 NM	3P+N	215x252x91	4xM32	1
GW 70 490 M	4P	215x252x91	4xM32	1
Rated current (A): 100				
GW 70 491 M	3P	257x307x121	-	1
GW 70 491 NM	3P+N	257x307x121	-	1
GW 70 492 M	4P	257x307x121	-	1
GW 70 747 M	6P	257x307x121	-	1
GW 70 767 M	8P	257x307x121	-	1
Rated current (A): 125				
GW 70 493 M	3P	257x307x121	-	1
GW 70 493 NM	3P+N	257x307x121	-	1
GW 70 494 M	4P	257x307x121	-	1
Rated current (A): 160				
GW 70 495 M	3P	257x307x121	-	1
GW 70 495 NM	3P+N	257x307x121	-	1
GW 70 496 M	4P	257x307x121	-	1

NOTE: can be padlocked in OFF position with max. 3 locks with diameter max. 8 mm.
Versions 100-160A up to 4P and 63-100A 6P and 8P allow to install max. 2 x M63 cable glands.

70 RT HP - SURFACE MOUNTING ROTARY ISOLATOR IN INSULATING ENCLOSURE IN DIRECT CURRENT - IP66/IP67/IP69

Versions for photovoltaic application



GW 70 231

Surface-mounting isolator - control version with lockable black knob - IP66/IP67/IP69

Code	No. of poles	Outer dim. LxHxD (mm)	Holes entry	Lid screws (no. and type)	Pack Carton
Rated current (A): 16					
GW 70 231	2P	153,6x200,6x117	4xM20	4 insulation	1/4
Rated current (A): 25					
GW 70 235	3P	153,6x200,6x117	4xM20	4 insulation	1/4
Rated current (A): 32					
GW 70 238	3P	153,6x200,6x117	4xM20	4 insulation	1/4
GW 70 239	4P	153,6x200,6x117	4xM25	4 insulation	1/4
Rated current (A): 40					
GW 70 242	4P	153,6x200,6x117	4xM25	4 insulation	1/4

70 RT HP

ROTARY ISOLATORS FOR AUTOMATION AND DISTRIBUTION BOARDS

Versions for boards 16 ÷ 160 A




GW 70 001

Isolator switches for distribution board with padlockable red/yellow knob and control transmission shaft

Code	No. of poles	No. of modules EN 50022	Regulation field	Pack Carton
Rated current (A): 16				
GW 70 001	2P	4	87 - 145 mm	1/10
GW 70 002	3P	4	87 - 145 mm	1/10
GW 70 003	4P	4	87 - 145 mm	1/10
Rated current (A): 25				
GW 70 052	3P	4	87 - 145 mm	1/10
GW 70 053	4P	4	87 - 145 mm	1/10
Rated current (A): 32				
GW 70 004	2P	4	87 - 145 mm	1/10
GW 70 005	3P	4	87 - 145 mm	1/10
GW 70 006	4P	4	87 - 145 mm	1/10
Rated current (A): 40				
GW 70 055	3P	4	87 - 145 mm	1/10
GW 70 056	4P	4	87 - 145 mm	1/10
Rated current (A): 63				
GW 70 007	3P	5	114 - 177 mm	1/5
GW 70 008	4P	5	114 - 177 mm	1/5
Rated current (A): 80				
GW 70 058	3P	5	114 - 177 mm	1/5
GW 70 059	4P	5	114 - 177 mm	1/5
Rated current (A): 100				
GW 70 061	3P	4	Max 194 mm	1/6
GW 70 062	4P	6	Max 194 mm	1/6
Rated current (A): 125				
GW 70 064	3P	4	Max 194 mm	1/6
GW 70 065	4P	6	Max 194 mm	1/6
Rated current (A): 160				
GW 70 067	3P	4	Max 194 mm	1/6
GW 70 068	4P	6	Max 194 mm	1/6

CHARACTERISTICS: the regulation field can be obtained by cutting the shaft supplied. Versions for panel/door mounting 16A ÷ 80A can be accessorized with galvanized steel extending brackets GW 70 009.



GW 70 009

Galvanized steel extending brackets for rear fixing

Code	For isolator	Regulation field	Pack Carton
Rated current (A): 16			
GW 70 009	16 A - 25 A - 32 A - 40 A - 63 A - 80 A	117-305mm (16-40A) - 144-337mm (63-80A)	1/10

CHARACTERISTICS: the regulation field can be obtained by cutting both the shaft supplied and the extension brackets at the references shown.
ACCESSORIES SUPPLIED: self-tapping screw kit.

Versions for boards 200 ÷ 1000 A



GW 70 070

Isolator switches for distribution board with padlockable black knob and control transmission shaft

Code	No. of poles	No. of modules EN 50022	Regulation field	Pack Carton
Rated current (A): 200				
GW 70 070	3P	9	152 - 246 mm	1
GW 70 071	4P	11	152 - 246 mm	1
Rated current (A): 250				
GW 70 073	3P	9	152 - 246 mm	1
GW 70 074	4P	11	152 - 246 mm	1
Rated current (A): 315				
GW 70 076	3P	12	161 - 256 mm	1
GW 70 077	4P	14	161 - 256 mm	1
Rated current (A): 400				
GW 70 079	3P	12	161 - 256 mm	1
GW 70 080	4P	14	161 - 256 mm	1
Rated current (A): 630				
GW 70 085	3P	16	212 - 282 mm	1
GW 70 086	4P	20	212 - 282 mm	1
Rated current (A): 800				
GW 70 088	3P	16	212 - 282 mm	1
GW 70 089	4P	20	212 - 282 mm	1
Rated current (A): 1000				
GW 70 091	3P	16	212 - 282 mm	1
GW 70 092	4P	20	212 - 282 mm	1

Versions for fixing on DIN rail



GW 70 203

Isolator switches for DIN rail with black knob

Code	No. of poles	No. of modules EN 50022	Pack Carton
Rated current (A): 16			
GW 70 201	2P	4	1/24
GW 70 202	3P	4	1/24
GW 70 203	4P	4	1/24
Rated current (A): 32			
GW 70 204	2P	4	1/24
GW 70 205	3P	4	1/24
GW 70 206	4P	4	1/24
Rated current (A): 63			
GW 70 207	3P	5	1/12
GW 70 208	4P	5	1/12

Complementary items



GW 70 026

Auxiliary contacts

Code	Type of contact	For isolator	Pack Carton
GW 70 026	1 NO + 1 NC	16 A - 25 A - 32 A - 40 A - 63 A - 80 A	1/12
GW 70 027	2 NO	16 A - 25 A - 32 A - 40 A - 63 A - 80 A	1/12
GW 70 028	2 NC	16 A - 25 A - 32 A - 40 A - 63 A - 80 A	1/12
GW 70 029	1 NO + 1 NC	100 A - 125 A - 160 A e 16-100A 6P and 8P	1/12
GW 70 035	1 NC	200 ÷ 1000 A	1/12
GW 70 036	1 EB	200 ÷ 1000 A	1/12



GW 70 040

Shafts for board versions

Code	Length	For isolator	Pack Carton
GW 70 040	300 mm	200 ÷ 400 A	1/20
GW 70 041	300 mm	630 ÷ 1000 A	1/20



GW 70 171

Phase barriers

Code	Kit	For isolator	Pack Carton
GW 70 171	6 pieces	200 ÷ 250 A 3P	1/20
GW 70 172	8 pieces	200 ÷ 250 A 4P	1/20
GW 70 173	6 pieces	315 ÷ 400 A 3P	1/20
GW 70 174	8 pieces	315 ÷ 400 A 4P	1/20
GW 70 175	6 pieces	630 A ÷ 1000 A 3P	1/20
GW 70 176	8 pieces	630 A ÷ 1000 A 4P	1/15



GW 70 181

Terminal covers

Code	Kit	For isolator	Pack Carton
GW 70 181	3 pieces	200 ÷ 250 A 3P	1/20
GW 70 182	4 pieces	200 ÷ 250 A 4P	1/15
GW 70 183	3 pieces	315 ÷ 400 A 3P	1/10
GW 70 184	4 pieces	315 ÷ 400 A 4P	1/10
GW 70 185	3 pieces	630 A ÷ 1000 A 3P	1/8
GW 70 186	4 pieces	630 A ÷ 1000 A 4P	1/6



GW 44 622

Insulating screw caps

Code	Description	Modules	Pack Carton
GW 44 622	Screwcap Ø16mm	-	10/100
GW 44 623	Screwcap Ø25mm	-	10/100

NOTE: required to maintain the double insulation and the IP protection degree when drilling the internal fixing points to install the versions in insulating box.

70 ATEX - DISCONNECTING SWITCHES IN PAINTED ALUMINIUM ENCLOSURE - ZONE 22 (D)

Control versions in aluminium alloy box



GW 70 451

ATEX rotary wall-mounting switches for control, with black knob - IP65

Code	No. of poles	Power AC3 400V (kW)	Outer dim. LxHxD (mm)	Pack Carton
Rated current (A): 16				
GW 70 451	2P	6 (230V)	140x165x135	1
GW 70 452	3P	10	140x165x135	1
GW 70 453	4P	10	140x165x135	1
Rated current (A): 32				
GW 70 454	2P	9 (230V)	140x165x135	1
GW 70 455	3P	15	140x165x135	1
GW 70 456	4P	15	140x165x135	1
Rated current (A): 63				
GW 70 457	3P	18.5	140x165x135	1
GW 70 458	4P	18.5	140x165x135	1
Rated current (A): 100				
GW 70 459	3P	30	215x252x94	1
GW 70 460	4P	30	215x252x94	1

ACCESSORIES SUPPLIED: cable gland M25 for 16A versions, M32 for 32-63A versions, and M40 for 100A.
CHARACTERISTICS: box in aluminium alloy painted in Grey RAL 7037.
ATEX Classification: Equipment-group II Category 3D.
Dust protection mode: tc.
Room temperature: -20°C <= Ta <= +40 °C.
NOTES: Can be padlocked with 3 locks in the OFF position and one in the ON position.

Emergency versions in aluminium alloy box



GW 70 471

ATEX rotary wall-mounting switches for emergency, with red knob - IP65

Code	No. of poles	Power AC3 400V (kW)	Outer dim. LxHxD (mm)	Pack Carton
Rated current (A): 16				
GW 70 471	2P	6 (230V)	140x165x135	1
GW 70 472	3P	10	140x165x135	1
GW 70 473	4P	10	140x165x135	1
Rated current (A): 32				
GW 70 474	2P	9 (230V)	140x165x135	1
GW 70 475	3P	15	140x165x135	1
GW 70 476	4P	15	140x165x135	1
Rated current (A): 63				
GW 70 477	3P	18.5	140x165x135	1
GW 70 478	4P	18.5	140x165x135	1
Rated current (A): 100				
GW 70 479	3P	30	215x252x94	1
GW 70 480	4P	30	215x252x94	1

ACCESSORIES SUPPLIED: cable gland M25 for 16A versions, M32 for 32-63A versions, and M40 for 100A.
CHARACTERISTICS: box in aluminium alloy painted in Grey RAL 7037.
ATEX Classification: Equipment-group II Category 3D.
Dust protection mode: tc.
Room temperature: -20°C <= Ta <= +40 °C.
NOTES: Can be padlocked with 3 locks in the OFF position.



70 RT HP



Scan the QR Code and find out all the technical informations.

TOTAL PROTECTION



The versions in plastic box have a degree of protection up to IP66/IP67/IP69, which guarantee a total protection against the entry of dust and liquids. Thanks to their high impact resistance, this range is suitable for all the most demanding application contexts.

QUICK MOUNTING



The frontal part of the versions in plastic box is fixed with only 4 captive and sealable screws with ¼ turn: a simple and innovative system, which allows to fix or remove the cover in less time than any other system currently available on the market.

VERSATILE AND INNOVATIVE



Double metric inputs, external points for wall fixing, large internal space for cable routing and accessorisability with different auxiliary contacts, are just some of the features that make this range suitable for various applications.

74 PS

Momentary round push-buttons

Colour	With guard		Without guard		With backlit guard	
Green	GW 74 301		GW 74 313		GW 74 341 (*)	
Black	GW 74 302		GW 74 312		-	
White	GW 74 303		GW 74 314		GW 74 342 (*)	
Red	GW 74 304		GW 74 311		GW 74 343 (*)	
Blue	GW 74 305		GW 74 315		GW 74 344 (*)	
Yellow	GW 74 306		GW 74 316		GW 74 345 (*)	

Round mushroom-head push-buttons - ø 40 mm

Colour	With holding		Without holding	
Red	GW 74 364		GW 74 363	
	GW 74 367 (*)		GW 74 366 (*)	

Round mushroom-head emergency push-buttons - ø 40 mm

Colour	With holding		With holding and key	
Red	GW 74 361		GW 74 362	
	GW 74 365 (*)			

Round selectors

Positions	Lever type with fixed positions		Extractable key with fixed position		Lever type with return	
0 - 1	GW 74 401		GW 74 411		GW 74 421	
1 - 0 - 2	GW 74 402		GW 74 412		GW 74 422	

Luminous indicators

Colour	Direct power supply	
Green	GW 74 451	
Red	GW 74 452	
Yellow	GW 74 453	
Light blue	GW 74 454	
White	GW 74 455	

Complementary items

Type		Contact	
Single contact	1 NO	GW 74 501	
	1 NC	GW 74 502	
Dual contact	2 NO	GW 74 503	
	2 NC	GW 74 505	
	1 NO + 1 NC	GW 74 504	
Lamp-holder - BA9S coupling		GW 74 511	

(*) Backlit

Complete containers

Indicator lights Ø 22	With guard		No. gangs	Contacts	Dimensions (LxHxD) mm
Generic (black)	GW 27 201		1	1 NO	66x82x65
Emergency (red)	GW 27 202		1	1 NO 1 NC	66x82x65
Start (green)	GW 27 203		2	1 NO 1 NC	132x82x65
Stop (red)					
Start (green)	GW 27 204		3	1 NO 1 NC	66x171x65
Stop (red)					
Signalling (white)					

Empty containers

No. gangs	Code		Side entries	Top / Bottom entries	Dimensions (LxHxD) mm
1	GW 27 101		2 x Ø 23	2 x Ø 23	66x82x65
1	GW 27 111 (*)		2 x Ø 23	2 x Ø 23	66x82x65
2	GW 27 102		6 x Ø 23	2 x Ø 23	132x82x65
3	GW 27 103		4 x Ø 23	2 x Ø 23	66x171x65
6	GW 27 104		4 x Ø 23	6 x Ø 23	132x171x65
12	GW 27 105		4 x Ø 23	6 x Ø 23	264x171x65

(*) GW 27 111: yellow lid and grey back-mounting box - Specific for emergency push-buttons.
For all illuminated versions, the LED lamp must be purchased separately: GW 74 515 (12V); GW 74 516 (24V); GW 74 517 (110V); GW 74 518 (230V).

74 PS

Push-buttons, selectors and indicators Ø 22 mm



The 74 PS range is a system of push-buttons, selectors and indicators (diameter 22 mm) with a degree of protection of IP66 for creating a real interface between man and machine, whilst at the same time controlling the operating status of the drives and equipment to ensure the highest safety standards. The range includes six types of empty enclosure with between 1 and 12 gangs, and enclosures that come fitted with push-buttons and contacts.

OPERATORS Ø 22 MM - IP66





Momentary push-buttons



GW 74 301

Momentary push-buttons with round guard

Code	Colour	Pack Carton
GW 74 301	Green	10/60
GW 74 302	Black	10/60
GW 74 303	White	10/60
GW 74 304	Red	10/60
GW 74 305	Blue	10/60
GW 74 306	Yellow	10/60

APPLICATION: suitable for avoiding accidental activation, e.g.: gates, tool machines, etc.
SUPPLIED: 3-seat flange (2 of which are contact-holders).
CHARACTERISTICS: Also compatible with the watertight emergency enclosure GW42204 and GW42207.



GW 74 311

Momentary push-buttons without round guard

Code	Colour	Pack Carton
GW 74 311	Red	10/60
GW 74 312	Black	10/60
GW 74 313	Green	10/60
GW 74 314	White	10/60
GW 74 315	Blue	10/60
GW 74 316	Yellow	10/60

SUPPLIED: 3-seat flange (2 of which are contact-holders).
CHARACTERISTICS: Also compatible with the watertight emergency enclosure GW42204 and GW42207.



GW 74 345

Momentary push-buttons with backlit round guard

Code	Colour	Pack Carton
GW 74 341	Green	10/60
GW 74 342	White	10/60
GW 74 343	Red	10/60
GW 74 344	Blue	10/60
GW 74 345	Yellow	10/60

APPLICATION: ideal for viewing the user operating status without the need for additional indicator lamps.
SUPPLIED: 3-seat flange (2 of which are contact-holders).
CHARACTERISTICS: can be combined with the lamp-holder GW74511 + LED lamp.
Also compatible with the watertight emergency enclosure GW42204 and GW42207.

Mushroom-head push-buttons



GW 74 367

Round mushroom-head push-buttons - Mushroom Ø 40mm

Code	Functions	Characteristics	Pack Carton
GW 74 363	Without holding	Not illuminated	10/60
GW 74 364	With holding	Not illuminated	10/60
GW 74 366	Without holding	Backlit	10/60
GW 74 367	With holding	Backlit	10/60

SUPPLIED: 3-seat flange (2 of which are contact-holders).
NOTE: compatible with the emergency enclosure GW42204.
CHARACTERISTICS: GW74366 and GW74367 can be combined with the lamp-holder GW74511 + LED lamp.
Also compatible with the watertight emergency enclosure GW42204 and GW42207.

Emergency push-buttons



GW 74 361

Round mushroom-head emergency buttons - Mushroom Ø 40mm

Code	Functions	Characteristics	Pack Carton
GW 74 361	With holding	Not illuminated	10/60
GW 74 362	With holding and key	Not illuminated	10/60
GW 74 365	With holding	Backlit	10/60

APPLICATION: suitable for emergency use, in accordance with Standard IEC 60947-5-5.
SUPPLIED: 3-seat flange (2 of which are contact-holders).
NOTE: all the keys are supplied with a standardised code.
CHARACTERISTICS: GW74365 can be combined with the lamp-holder GW74511 + LED lamp.

Selectors



GW 74 401

Round lever selectors with fixed position

Code	No. gangs	Type	Pack Carton
GW 74 401	2	0 - 1	10/60
GW 74 402	3	1 - 0 - 2	10/60

CHARACTERISTICS: operator in thermoplastic material.
Also compatible with the watertight emergency enclosure GW42204 and GW42207.
SUPPLIED: 3-seat flange (2 of which are contact-holders).



GW 74 411

Round key selectors with fixed position and removable key

Code	No. gangs	Type	Pack Carton
GW 74 411	2	0 - 1	10/60
GW 74 412	3	1 - 0 - 2	10/60

CHARACTERISTIC: operator in thermoplastic material.
SUPPLIED: 3-seat flange (2 of which are contact-holders).
NOTE: all the keys are supplied with a standardised code.



GW 74 421

Round lever selectors with - O - return position

Code	No. gangs	Type	Pack Carton
GW 74 421	2	0 - 1	10/60
GW 74 422	3	1 - 0 - 2	10/60

CHARACTERISTIC: operator in thermoplastic material. Also compatible with the watertight emergency enclosure GW42204 und GW42207.
SUPPLIED: 3-seat flange (2 of which are contact-holders).

INDICATORS - IP66



IP
66

Indicators



GW 74 452

Round backlit indicators with direct supply nominal voltage 230 V - BA9S lamp fixing

Code	Colour	Pack Carton
GW 74 451	Green	10/60
GW 74 452	Red	10/60
GW 74 453	Yellow	10/60
GW 74 454	Blue	10/60
GW 74 455	White	10/60

CHARACTERISTICS: lamp not included. Max lamp power 1 W.
Also compatible with the watertight emergency enclosure GW42204 and GW42207.
NOTE: the colour of the diffuser should be chosen in accordance with the colour code recommended by Standard CEI 16-3. If using 110 V LEDs code GW74517 and 230 V LEDs code GW74518, it is recommended to remove the opal cover on the indicator to improve the light flow.

COMPLEMENTARY ITEMS

Accessories



Contacts - ITH=10A - 250V AC

Code	Type	Colour	Pack Carton
GW 74 501	1 NO	Green	1/30
GW 74 502	1 NC	Red	1/30
GW 74 503	2 NO	Green	1/30
GW 74 504	1 NO + 1 NC	White	1/30
GW 74 505	2 NC	Red	1/30

CHARACTERISTICS: GW74502 suitable for contact opening also in the event of slight sticking, in compliance with Standard EN 60947-5-1.
Clip assembly on the contact-holder flanges.
NOTES: the dual contacts type: GW74503, GW74504 and GW74505 are not compatible with the watertight emergency enclosures GW42204 and GW42207.



GW 74 511

Lamp-holder - Lamp coupling BA9S

Code	Power supply	Lamp power	Pack Carton
GW 74 511	Direct	1 W	1/30

CHARACTERISTICS: Clip assembly on the contact-holder flanges. To be positioned in the central seat of the flange.
APPLICATIONS: to be used with the backlit momentary push-buttons with guard and backlit mushroom-head push-buttons, to produce operating signals.

Bulbs - BA9S lamp fixing



GW 74 515

Code	Type	Rated voltage	Pack Carton
GW 74 515	LED	12 V	10/100
GW 74 516	LED	24 V	10/100
GW 74 517	LED	110 V	10/100
GW 74 518	LED	230 V	10/100

APPLICATIONS: To be used with the backlit indicators or the lamp-holder GW74511.
NOTE: If using 110 V LEDs code GW74517 and 230 V LEDs code GW74518, it is recommended to remove the opal cover on the indicator to improve the light flow.

Black screwcap for unwired enclosures for push-buttons with a round shape - Ø 22 mm



GW 74 521

Code	Colour	Pack Carton
GW 74 521	Black	10/100

CHARACTERISTIC: thermoplastic screw cap.

Plates



GW 74 523

Code	Suitable for	Shape	Colour	Text	Pack Carton
GW 74 522	Push-buttons, indicators and selectors Ø 22mm	Rectangular	Black	-	5/100
GW 74 523	Mushroom-head emergency button	Round	Yellow	Emergency-Stop	10/100

CHARACTERISTIC: the plates allow you to assign the push-button, selector and indicator functions.
NOTE: GW74523 to be used when the emergency push-buttons are installed on the panel.

Tools



GW 74 525

Code	Description	Material	Pack Carton
GW 74 524	Tool for mounting ring nuts	Metal	10/100
GW 74 525	extraction tool Lamp	Thermoplastic	10/100

COMBI 22 - INSULATING ENCLOSURES FOR OPERATORS AND INDICATORS - IP66





Enclosures



GW 27 101

Unwired enclosures for push-buttons, controls and indicators Ø 22 mm - Grey RAL 7035

Code	No. gangs	Side entries	Top entries	Bottom entries	Outer dim. LxHxD (mm)	Pack Carton
Colour: Grey RAL 7035						
GW 27 101	1	2xØ 23	1xØ 23	1xØ 23	66x82x65	5/60
GW 27 102	2	6xØ 23	1xØ 23	1xØ 23	132x82x65	2/30
GW 27 103	3	4xØ 23	1xØ 23	1xØ 23	66x171x65	1/20
GW 27 104	6	4xØ 23	3xØ 23	3xØ 23	132x171x65	1/10
GW 27 105	12	4xØ 23	3xØ 23	3xØ 23	264x171x65	1/10
Colour: Yellow cover						
GW 27 111	1	2xØ 23	1xØ 23	1xØ 23	66x82x65	5/60

CHARACTERISTICS: degree of protection guaranteed with IP66 operators correctly installed.
The hole seat has knockouts for installing operators with any reference.
GW27111 with specific yellow lid for assembling emergency push-buttons GW74361, GW74362 and GW74365.
NOTES: the empty containers can be supplied with push-buttons, commands and indicators Ø 22 mm and single contacts, type GW74501 and GW74502.

Complete enclosures



GW 27 202

Complete enclosures - Grey RAL 7035

Code	No. gangs	Contacts	Operators Ø 22	Outer dim. LxHxD (mm)	Pack Carton
GW 27 201	1	1 NO	General (black)	66x82x65	1/30
GW 27 202	1	1 NO - 1 NC	Emergency (red)	66x82x65	1/30
GW 27 203	2	1 NO - 1 NC	Start (green) Stop (red)	132x82x65	1/10
GW 27 204	3	1 NO - 1 NC	Start, stop, indicator	66x171x65	1/10

CHARACTERISTICS: 3-seat flange. Maximum protrusion of the operator from the container: GW27201, GW20203, GW27204 - 20mm; GW27202 - 25mm.
GW27202: yellow lid, mushroom-head push-button with retainer.
GW27204: direct supply, BA9S coupling included, max 380V-2 W, lamp not included, operators Ø 22 for run (green), stop (red), signalling (white).
Complete insulation, in accordance with Standard IEC 536.



GW 66 745

Watertight lids

Code	Dimensions LxH (mm)	Suitable for	Colour	Pack Carton
GW 66 708	75x85	1 Button Ø22 mm Range 74 PS	Grey	1/20
GW 66 745	75x85	1 Button Ø22 mm Range 74 PS	Yellow	1/20

APPLICATIONS: GW66745 specific for emergency push-buttons.
ACCESSORIES SUPPLIED: gasket and mounting screws.

Complementary items



GW 27 402

Junction box for combined assembly of modular containers Grey RAL 7035 - IP55

Code	No. knockout holes Ø23	Lid screws	Outer dim. LxHxD (mm)	Pack Carton
GW 27 402	8 on sides / 1 on the bottom	Stainless steel	132x82x55	2/60

CHARACTERISTICS: knockout holes removable with tool. Enclosures are fit for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.



GW 26 406

Watertight coupling device for containers, devices and boxes - IP55

Code	Mounting hole Ø (mm)	Type of pitch	Pack Carton
GW 26 406	23	PG16	25/250

APPLICATIONS: for the combined assembly of enclosures, junction boxes, etc.



GW 44 622

Insulating screw cap

Code	Description	Pack Carton
GW 44 622	Screwcap Ø16mm	10/100


APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.



Contacts - ITH=10A - 250V AC

Code	Type	Colour	Pack Carton
GW 74 501	1 NO	Green	1/30
GW 74 502	1 NC	Red	1/30

CHARACTERISTICS: GW74502 suitable for contact opening also in the event of slight sticking, in compliance with Standard EN 60947-5-1.
Clip assembly on the contact-holder flanges. Compatible with the emergency enclosure GW42204.



74 PS



Scan the QR Code and find out all the technical informations.

QUICK, RELIABLE AND SAFE INSTALLATION



Thanks to the practical clip coupling mechanism of the contacts, panel assembly times are drastically reduced. The dual contact versions increase installation flexibility and extend the maxiumum number of contacts for each device.

SYNERGY WITH GEWISS RANGES



The high degree of protection - IP66 - means the 74 PS operators can be housed inside or outside GEWISS containers such as the 46 range boards, the 42 RV emergency enclosures, the 27 COMBI boxes or the 42 TV support bases.

THE BENEFITS OF LED TECHNOLOGY



The products of the 74 PS range can be illuminated and combined with LED lamps with a BA9S coupling for optimum performance, full reliability, a longer lifespan and less maintenance.

Wall-mounting enclosures







46

Watertight surface-mounting distribution and automation boards

p. 174

40 CD

Surface-mounting distribution boards and enclosures

p. 196

40 CDE

Enclosures and distribution boards for specific standards

p. 208



42 RV

Surface and flush-mounting watertight emergency enclosures

p. 224



44 CE

Technopolymer surface-mounting watertight junction boxes


p. 233



GW Connect

Metal surface-mounting watertight junction boxes

p. 245



42 TV

Multifunctional supporting bases

p. 249

Watertight surface-mounting distribution and automation boards

	BOARD					COMPLEMENTARY ITEMS		
						FRONT CONFIGURATION		
						SINGLE PANELS	PANELS	
								
	DIMENSIONS (LxHxD) mm	Material	Code Blank door	Code Transparent door	No. modules EN 50022	with window and DIN rail	with window and DIN rail	Blank
44 CEP GWPLAST 120 IP55 	200x254x135	GWPLAST 120	GW 44 808	GW 44 818	-	-	-	
	236x316x135	GWPLAST 120	GW 44 809	GW 44 819	8	GW 44 852 8 modules	-	
	316x396x160	GWPLAST 120	GW 44 810	GW 44 820	24 (12x2)	GW 44 853 14 modules GW 44 854 24 modules (12x2)	-	
	396x474x160	GWPLAST 120	GW 44 811	GW 44 821	32 (16x2)	GW 44 855 32 modules (16x2)	-	
46 QP POLYESTER BOARD IP66 	250x300x160	Polyester	GW 46 001 F	GW 46 201 F	-	-	-	
		Metal	GW 46 031	-				
	310x425x160	Polyester	GW 46 002 F	GW 46 202 F	36 (12x3)	-	3 single panels width 12 modules	
		Metal	GW 46 032	GW 46 232			GW 46 420 F	GW 46 425 F
		Stainless steel	GW 46 052	-				
46 QM METAL BOARD IP55 	405x500x200	Polyester	GW 46 003 F	GW 46 203 F	54 (18x3)	-	3 single panels width 18 modules	
		Metal	GW 46 033	GW 46 233			GW 46 421 F	GW 46 426 F
	405x650x200	Polyester	GW 46 004 F	GW 46 204 F	72 (18x4)	-	4 single panels width 18 modules	
		Metal	GW 46 034	GW 46 234			GW 46 421 F	GW 46 426 F
		Stainless steel	GW 46 054	-				
46 QX STAINLESS STEEL BOARD IP55 	515x650x250	Polyester	GW 46 005 F	GW 46 205 F	96 (24x4)	-	4 single panels width 24 modules	
		Metal	GW 46 035	GW 46 235			GW 46 422 F	GW 46 427 F
	585x800x300	Polyester	GW 46 006 F	GW 46 206 F	140 (28x5)	-	5 single panels width 28 modules	
		Metal	GW 46 036	GW 46 236			GW 46 423 F	GW 46 428 F
		Stainless steel	GW 46 056	-				
	800x1060x350	Polyester	GW 46 007 F	GW 46 207 F	180 (36x5)	-	5 single panels width 28 modules	
		Metal	GW 46 037	GW 46 237			GW 46 424 F	GW 46 429 F

COMPLEMENTARY ITEMS

FRONT CONFIGURATION				INTERNAL CONFIGURATION			SERVICE ACCESSORIES	
DOUBLE PANELS	INNER DOORS	UPRIGHTS	DIN RAILS	BACK-MOUNTING PLATES	PLATES		POLE SUPPORT	MISCELLANEOUS
 Blank	 Material: insulating/ metal	 Pair	 simple/ double	 Material: metal/ steel (perforated)/ insulating	 H 1 module: full	H 2 modules: full		
-	-	-	-	GW 44 636 GW 44 646	-	-	-	 Resin bracket GW 44 621
-	-	-	-	GW 44 637 GW 44 647	-	-	-	 Safety lock with handle GW 46 445
-	-	-	-	GW 44 638 GW 44 648	-	-	-	 4 stainless steel brackets GW 46 451
-	-	-	-	GW 44 639 GW 44 649	-	-	-	 Set 4 galvanised brackets GW 46 446
-	-	-	-	GW 46 401 GW 46 461 GW 46 408	-	-	GW 46 551 -	 Clip nut GW 46 450
								 4 stainless steel brackets GW 46 451
1 double panel GW 46 475 F	GW 46 414 GW 46 564	GW 46 435 F	GW 46 430 F GW 46 530 F	GW 46 402 GW 46 462 GW 46 409	3 single plates GW 46 540	1 double plate GW 46 580	GW 46 552 - -	 Set 4 galvanised brackets GW 46 446
								 Gasket for board coupling GW 46 449
1 double panel GW 46 476 F	GW 46 415 GW 46 565	GW 46 436 F	GW 46 431 F GW 46 531 F	GW 46 403 GW 46 463 GW 46 410	3 single plates GW 46 541	1 double plate GW 46 581	GW 46 553 -	 Set of 4 reversible squares for back-mounting plate fixing or uprights for modular equipment fixing For back plate fixing GW 46 521 F
								 Safety lock with handle GW 46 445
2 double panels GW 46 476 F	GW 46 416 GW 46 566	GW 46 437 F	GW 46 431 F GW 46 531 F	GW 46 404 GW 46 464 GW 46 411	4 single plates GW 46 541	2 double plates GW 46 581	GW 46 553 - -	
2 double panels GW 46 477 F	GW 46 417 GW 46 567	GW 46 437 F	GW 46 432 F GW 46 532 F	GW 46 405 GW 46 465 GW 46 412	4 single plates GW 46 542	2 double plates GW 46 582	GW 46 554 -	 Document holder wallet GW 46 447
								 Ventilation kit IP 44 GW 46 448 and GW 46 471
2 double panels GW 46 478 F	GW 46 418 GW 46 568	GW 46 438 F	GW 46 433 F GW 46 533 F	GW 46 406 GW 46 466 GW 46 413	5 single plates GW 46 543	2 double plates GW 46 583	GW 46 555 - -	 KIT for wiring trunking GW 46 557 F
								 Double insulation KIT GW 46 526
2 double panels GW 46 479 F	GW 46 419 GW 46 569	GW 46 439 F	GW 46 434 F GW 46 534 F	GW 46 407 GW 46 467	5 single plates GW 46 544	2 double plates GW 46 584	-	 Pair of handles for transport GW 46 591
								 Kit inserts GW 46 592 F

Compatibility between 46 range boards and kit for MCCBs MSX range and kit switch disconnectors MSS range

	BOARD				
	DIMENSIONS (LxHxD) mm	Material	Code		No. modules EN 50022
			Blank door	Transparent door	
44 CEP GWPLAST 120 IP55 	200x254x135	GWPLAST 120	GW 44 808	GW 44 818	-
	236x316x135	GWPLAST 120	GW 44 809	GW 44 819	8
	316x396x160	GWPLAST 120	GW 44 810	GW 44 820	24 (12x2)
	396x474x160	GWPLAST 120	GW 44 811	GW 44 821	32 (16x2)
46 QP POLYESTER BOARD IP66 	250x300x160	Polyester	GW 46 001 F	GW 46 201 F	-
		Metal	GW 46 031	-	
	310x425x160	Polyester	GW 46 002 F	GW 46 202 F	36 (12x3)
		Metal	GW 46 032	GW 46 232	
		Stainless steel	GW 46 052	-	
46 QM METAL BOARD IP55 	405x500x200	Polyester	GW 46 003 F	GW 46 203 F	54 (18x3)
		Metal	GW 46 033	GW 46 233	
	405x650x200	Polyester	GW 46 004 F	GW 46 204 F	72 (18x4)
		Metal	GW 46 034	GW 46 234	
		Stainless steel	GW 46 054	-	
	515x650x250	Polyester	GW 46 005 F	GW 46 205 F	96 (24x4)
		Metal	GW 46 035	GW 46 235	
46 QX STAINLESS STEEL BOARD IP55 	585x800x300	Polyester	GW 46 006 F	GW 46 206 F	140 (28x5)
		Metal	GW 46 036	GW 46 236	
		Stainless steel	GW 46 056	-	
	800x1060x350	Polyester	GW 46 007 F	GW 46 207 F	180 (36x5)
		Metal	GW 46 037	GW 46 237	

NOTES: The configurations reported in the table are ONLY valid if the peak current of the indicated switch (in correspondence of the assumed short-circuit current in the installation point) is NOT higher than 17kA, or if the assumed short-circuit current in the delivery point, in line with the main board switch, is NOT greater than 10kA.
Check the thermal power according to the method indicated in the pages of the technical catalogue.
The kits are fixed by means of uprights. The kit panels are 2-modules high.
MSX/M 160c (both 3P and 4P) must be fixed to the DIN rail through the specific brackets contained in the kit GWD8875.
MSX/M 250c, MSX/D 125, MSX/D 160 e MSX/D 250 (both 3P and 4P) require the kit GWD8876.
In the case of cable entry from below, it is recommended to insert a blank panel above the moulded-case/switch disconnector kit, so the wires can be pulled more easily.
MSX moulded case circuit breakers can be mounted on the same DIN rail close to modular devices and MSS switch disconnectors using GWD3317 depth adapter in order to compensate difference in depth.

MCCBs	SWITCH DISCONNECTOR	
MSX/M 160c - MSX/M 250c - MSX/D 125 - MSX/D 160 - MSX/D 250	MSS 160	MSS 250
		
-	-	-
-	-	-
GW 44 853 (for MSX/M 160c and MSX/D 160 only)	-	-
GW 44 855 (for MSX/M 160c and MSX/D 160 only)	-	-
-	-	-
-	-	-
GW 46 570 F	GW 46 570 F	-
GW 46 570 F	GW 46 570 F	-
GW 46 571 F	GW 46 571 F	GW 46 577 F
GW 46 572 F	GW 46 572 F	GW 46 578 F
GW 46 573 F	GW 46 573 F	GW 46 579 F

46

Watertight surface-mounting distribution and automation boards



The offer includes: 46 QP boards - monobloc, Halogen Free glass fiber loaded polyester, degree of protection IP66; 46 QM boards - IP55 in metal; 46 QX boards - IP55 in stainless steel; 44 CEP boards - monobloc, Halogen Free technopolymer. The 46 QP, QM and 44 CEP boards are available in transparent and blank door versions. In addition, 46 QP, QM and QX boards features Fast & Easy accessories with metal snap fastening.

46 QP - POLYESTER WATERTIGHT BOARDS - IP66











Distribution boards



GW 46 004 F

Polyester watertight boards with blank door fitted with lock - Grey RAL 7035

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 46 001 F	250x300x160	-	1	34	-	1
GW 46 002 F	310x425x160	36 (12x3)	2	48	39	1
GW 46 003 F	405x500x200	54 (18x3)	2	95	53	1
GW 46 004 F	405x650x200	72 (18x4)	2	118	81	1
GW 46 005 F	515x650x250	96 (24x4)	2	126	106	1
GW 46 006 F	585x800x300	140 (28x5)	2	205	146	1
GW 46 007 F	800x1060x350	180 (36x5)	2	324	226	1

CHARACTERISTICS: boxes equipped with inserts pre-assembled in the slots, to speed up the configuration of the board. Doors equipped with functional grid of reference for fixing the devices. From board GW46002F to board GW46006F it is possible to fix the panels with windows or blank (1 or 2 modules) directly in the seats housed in the vertical walls of the boards; for the board GW46007F use uprights GW46439F. Impact resistance: IK10 according to EN 62262.

ACCESSORIES SUPPLIED: 4 reversible brackets with relative screws for fixing back-mounting plates or uprights for modular devices.

NOTES: Dispersible power calculated according to CEI 23-49.

Dispersible power A (W): board configuration with back-mounting plate (as far back as possible).

Dispersible power B (W): board configuration with DIN rails + panels with windows.

The nominal dimensions in the table above refer to the external size of the boards; for the real outer dimensions refer to the technical data sheet downloadable from professionals website GEWISS or to the technical section of this catalogue.

For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.



GW 46 203 F

Polyester watertight boards with transparent door and lock - Grey RAL 7035

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 46 201 F	250x300x160	-	1	34	-	1
GW 46 202 F	310x425x160	36 (12x3)	2	48	39	1
GW 46 203 F	405x500x200	54 (18x3)	2	95	53	1
GW 46 204 F	405x650x200	72 (18x4)	2	118	81	1
GW 46 205 F	515x650x250	96 (24x4)	2	126	106	1
GW 46 206 F	585x800x300	140 (28x5)	2	205	146	1
GW 46 207 F	800x1060x350	180 (36x5)	2	324	226	1

ACCESSORIES SUPPLIED: boxes equipped with inserts pre-assembled in the slots, to speed up the configuration of the board. For the transparent door version: GWT 650°C. From board GW46202F to board GW46206F it is possible to fix the panels with windows or blank (1 or 2 modules) directly in the seats housed in the vertical walls of the boards; for the board GW46207F use uprights GW46439F. Impact resistance of the bottom: IK10 according to EN 62262.

ACCESSORIES SUPPLIED: 4 reversible brackets with relative screws for fixing back-mounting plates or uprights for modular devices.

NOTES: Dispersible power calculated according to CEI 23-49.

Dispersible power A (W): board configuration with back-mounting plate (as far back as possible).

Dispersible power B (W): board configuration with DIN rails + panels with windows.

The nominal dimensions in the table above refer to the external size of the boards; for the real outer dimensions refer to the technical data sheet downloadable from professionals website GEWISS or to the technical section of this catalogue.

For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.

Spare parts



GW 46 504 F

Blank door with lock

Code	For boards LxH (mm)	No. locks	Pack Carton
GW 46 501 F	250x300	1	1/6
GW 46 502 F	310x425	2	1/6
GW 46 503 F	405x500	2	1/8
GW 46 504 F	405x650	2	1/8
GW 46 505 F	515x650	2	1
GW 46 506 F	585x800	2	1
GW 46 507 F	800x1060	2	1

NOTE: spare blank doors as compatible with the respective back plates of the previous boards of the 46QP range.



GW 46 513 F

Transparent door and lock

Code	For boards LxH (mm)	No. locks	Pack Carton
GW 46 511 F	250x300	1	1/6
GW 46 512 F	310x425	2	1/6
GW 46 513 F	405x500	2	1/8
GW 46 514 F	405x650	2	1/8
GW 46 515 F	515x650	2	1
GW 46 516 F	585x800	2	1
GW 46 517 F	800x1060	2	1

NOTE: spare transparent doors as compatible with the respective back plates of the previous boards of the 46QP range.

46 QM - WATERTIGHT METAL BOARDS - IP55



IP
55

Distribution boards



GW 46 034

Watertight boards in metal with blank door fitted with lock Grey RAL 7035

FAST & EASY

IK
10

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 46 031	250x300x160	-	1	49	-	1
GW 46 032	310x425x160	36 (12x3)	2	70	58	1
GW 46 033	405x500x200	54 (18x3)	2	106	80	1
GW 46 034	405x650x200	72 (18x4)	2	135	97	1
GW 46 035	515x650x250	96 (24x4)	2	180	115	1
GW 46 036	585x800x300	140 (28x5)	2	240	159	1
GW 46 037	800x1060x350	180 (36x5)	2	400	284	1

ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular devices.
GW46034, GW46035, GW46036, GW46037 with perforated bottom equipped with flange for cables to pass through.
NOTES: Dispersible power calculated according to CEI 23-49.
For the front configuration (via panels and DIN rails), it is necessary to use the uprights.
Dispersible power A (W): board configuration with back-mounting plate (as far back as possible).
Dispersible power B (W): board configuration with DIN rails + panels with windows.
The technical and functional characteristics, and the nominal values, refer to vertical installation only.
APPLICATIONS: for indoor use (e.g. in industrial systems, on machines, etc.).
The nominal dimensions in the table above refer to the external size of the boards; for the real outer dimensions refer to the technical data sheet downloadable via the QR code at the end of the section.



GW 46 232

Watertight boards in metal with blank door fitted with tempered glass window and lock Grey RAL 7035

FAST & EASY

IK
08

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 46 232	310x425x160	36 (12x3)	2	70	58	1
GW 46 233	405x500x200	54 (18x3)	2	106	80	1
GW 46 234	405x650x200	72 (18x4)	2	135	97	1
GW 46 235	515x650x250	96 (24x4)	2	180	115	1
GW 46 236	585x800x300	140 (28x5)	2	240	159	1
GW 46 237	800x1060x350	180 (36x5)	2	400	284	1

ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular devices.
GW46234, GW46235, GW46236, GW46237 with perforated bottom equipped with flange for cables to pass through.
NOTES: Dispersible power calculated according to CEI 23-49.
For the front configuration (via panels and DIN rails), it is necessary to use the uprights.
Dispersible power A (W): board configuration with back-mounting plate (as far back as possible).
Dispersible power B (W): board configuration with DIN rails + panels with windows.
The technical and functional characteristics, and the nominal values, refer to vertical installation only.
APPLICATIONS: for indoor use (e.g. in industrial systems, on machines, etc.).
The nominal dimensions in the table above refer to the external size of the boards; for the real outer dimensions refer to the technical data sheet downloadable via the QR code at the end of the section.

46 QX - WATERTIGHT BOARDS IN STAINLESS STEEL - IP55



IK 10

IP 55

Distribution boards



GW 46 054

Watertight boards in satin stainless steel with blank door fitted with lock

FAST & EASY

Code	Nominal dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 46 052	310x425x160	36 (12x3)	2	70	58	1
GW 46 054	405x650x200	72 (18x4)	2	135	97	1
GW 46 056	585x800x300	140 (28x5)	2	240	159	1

ACCESSORIES SUPPLIED: screwcaps, threaded pins or reversible squares with the relative bolts and screws for fixing the back-mounting plates or uprights for modular equipment.

GW46054, GW46056 with perforated bottom equipped with flange for cables to pass through.

NOTES: Dispersible power calculated according to CEI 23-49.

For the front configuration (via panels and DIN rails), it is necessary to use the uprights.

Dispersible power A (W): board configuration with back-mounting plate (as far back as possible).

Dispersible power B (W): board configuration with DIN rails + panels with windows.

The technical and functional characteristics, and the nominal values, refer to vertical installation only.

The nominal dimensions in the table above refer to the external size of the boards; for the real outer dimensions refer to the technical data sheet downloadable via the QR code at the end of the section.

APPLICATIONS: for indoor use, in areas that are frequently cleaned with water jets for reasons of hygiene (e.g. industrial kitchens, butchers' shops, etc.).

COMPLEMENTARY ITEMS FOR 46 QP, QM AND QX BOARDS

Front configuration



GW 46 414

Hinged enclosure doors in polyester for assembly of command, signalling and measuring devices - Grey RAL 7035

Code	For boards LxH (mm)	Pack Carton
GW 46 414	310x425	1/5
GW 46 415	405x500	1/4
GW 46 416	405x650	1/5
GW 46 417	515x650	1/2
GW 46 418	585x800	1/2
GW 46 419	800x1060	1

NOTES: for further information about the distances between board door, inner door and back-mounting plate, refer to the dimensional data in the technical catalogue.
CHARACTERISTICS: these are reversible (for the technical details refer to the dedicated section in the technical catalogue).



GW 46 566

Hinged enclosure doors in metal for assembly of command, signalling and measuring devices - Grey RAL 7035

Code	For boards LxH (mm)	Pack Carton
GW 46 564	310x425	1/5
GW 46 565	405x500	1/4
GW 46 566	405x650	1/5
GW 46 567	515x650	1/2
GW 46 568	585x800	1/2
GW 46 569	800x1060	1

NOTES: for further information about the distances between board door, inner door and back-mounting plate, refer to the dimensional data in the technical catalogue. The use of the metal inner door in the boards of the 46QP range requires the earth pin to be connected to the relative PE protection conductor only if non-class 2 devices are assembled on it.
CHARACTERISTICS: these are reversible (for the technical details refer to the dedicated section in the technical catalogue).



GW 46 421 F

Covering panels with window, height 1 module, Fast and Easy quick assembly - Grey RAL 7035

Code	No. of modules EN 50022	For standard boards (mm)	Pack Carton
Height: 1 Module			
GW 46 420 F	12	310	1/10
GW 46 421 F	18	405	1/10
GW 46 422 F	24	515	1/10
GW 46 423 F	28	585	1/5
GW 46 424 F	36	800	1/5

CHARACTERISTICS: captive panel 1/4 turn sealing screws.
GW46420F, GW46421F, GW46422F, GW464223F, possibility to fix directly on the inner walls of the polyester boards.
ACCESSORIES SUPPLIED: fixing accessories. Complete with DIN rail.
NOTES: in all boards, the panel GW46424F can be fixed only with uprights GW46439F.

Fast and Easy quick assembly blank covering panels - Grey RAL 7035



GW 46 425 F

Code	For standard boards (mm)	Pack Carton
Height: 1 Module		
GW 46 425 F	310	1/10
GW 46 426 F	405	1/10
GW 46 427 F	515	1/13
GW 46 428 F	585	1/5
GW 46 429 F	800	1/5
Height: 2 Modules		
GW 46 475 F	310	1/5
GW 46 476 F	405	1/5
GW 46 477 F	515	1/5
GW 46 478 F	585	1/5
GW 46 479 F	800	1

CHARACTERISTICS:

GW46425F, GW46426F, GW46427F, GW46428F, GW46475F, GW46476F, GW46477F, GW46478F possibility to fix directly on the inner walls of the polyester boards. captive panel 1/4 turn sealing screws. in all boards, the panel GW46429F and GW46479F can be fixed only with uprights GW46439F.

ACCESSORIES SUPPLIED: fixing accessories.

Pair of uprights for installation of Fast and Easy quick assembly technical components, for modular devices, moulded-case devices, switch- disconnectors and blank/perforated plates H = 1 and 2 modules



GW 46 437 F

Code	For boards LxH (mm)	Pack Carton
GW 46 435 F	310x425	1/10
GW 46 436 F	405x500	1/10
GW 46 437 F	405x650/515x650	1/10
GW 46 438 F	585x800	1/10
GW 46 439 F	800x1060	1/10

ACCESSORIES SUPPLIED: the uprights are provided with a kit with 4 inserts to be inserted in the seats located on the lower and upper horizontal surfaces. The position of the seats where the inserts have to be housed is shown on the instruction sheet inside the 46QP boards. The insert is fixed in the seat through the expansion of the plate located inside the insert, using a pin with diameter 4 mm. The uprights are installed using the 4 brackets provided with the 46QP boards.

APPLICATIONS: the uprights make it possible to implement extractable frames by using: panels without and with windows, perforated or non-perforated plate with height of 1 or 2 modules, MCCB or switch disconnector kits.

Fast and Easy quick assembly DIN rails



GW 46 431 F

Code	No. of modules EN 50022	For standard boards (mm)	Pack Carton
GW 46 430 F	12	310	1/10
GW 46 431 F	18	405	1/10
GW 46 432 F	24	515	1/10
GW 46 433 F	28	585	1/10
GW 46 434 F	36	800	1/10

ACCESSORIES SUPPLIED: accessories for fixing to panel brackets.

NOTES: To use the DIN rails without the relative blank panel, use the GW46524F kit.

To restore the minimum degree of protection of the open door board, use the relative inner door.

Fast and Easy quick assembly double DIN rails



GW 46 531 F

Code	No. of modules EN 50022	For standard boards (mm)	Pack Carton
GW 46 530 F	12	310	1/10
GW 46 531 F	18	405	1/10
GW 46 532 F	24	515	1/10
GW 46 533 F	28	585	1/10
GW 46 534 F	36	800	1/10

APPLICATIONS: suitable for use with the GWFIX 100 system.

ACCESSORIES SUPPLIED: accessories for fixing to panel brackets.

NOTES: the use of the double DIN rails GW46531F, GW46532F, GW46533F, GW46534F prevents the positioning of the vertical trunking.

To use the DIN rails without the relative blank panel, use the GW46524F kit.

To restore the minimum degree of protection of the open door board, use the relative inner door.



GW 46 570 F

Kit of moulded-case devices and switch-disconnectors - fixing by means of uprights - 2-module panel height - Grey RAL 7035

Code	MSX Type	Disconnector Type	For standard boards (mm)	Pack Carton
Equipment fixing: Plate, DIN rail EN 50022				
GW 46 570 F	MSX/M 160c - MSX/M 250c - MSX/D 125 - MSX/D 160 - MSX/D 250	MSS 160	405	1
GW 46 571 F	MSX/M 160c - MSX/M 250c - MSX/D 125 - MSX/D 160 - MSX/D 250	MSS 160	515	1
GW 46 572 F	MSX/M 160c - MSX/M 250c - MSX/D 125 - MSX/D 160 - MSX/D 250	MSS 160	585	1
GW 46 573 F	MSX/M 160c - MSX/M 250c - MSX/D 125 - MSX/D 160 - MSX/D 250	MSS 160	800	1
Equipment fixing: on plate				
GW 46 577 F	-	MSS 250	515	1
GW 46 578 F	-	MSS 250	585	1
GW 46 579 F	-	MSS 250	800	1

CHARACTERISTICS: panels with windows H=45mm; captive and sealing 1/4 turn screws; Fixed with uprights.
Pre-arrangement for vertically positioned devices. Halogen-free plastic material in accordance with EN 60754-2 (CEI EN 50267-2-2).
ACCESSORIES SUPPLIED: fixing accessories.
NOTES: the MSX/M 160c (both 3P and 4P) must be fixed to the DIN rail through the brackets of the kit GWD8875.
The MSX/M 250c, MSX/D 125, MSX/D 160 and MSX/D 250 (both 3P and 4P) require the kit GWD8876.
You are advised to always insert a blank panel above the moulded-case/switch-disconnector kit, to facilitate the cord positioning in the case of cord entry from the bottom. The MSX can be installed together with MSS on the same DIN rail through the depth adapter GWD3317 to compensate the different heights
The peak current of the one-way switch indicated (in line with the presumed short-circuit current in the installation point) must NOT be greater than 17kA.
The presumed short-circuit current in the power supply line of the main switch of the board must NOT be greater than 10kA.

Internal configuration




GW 46 401

Steel back-mounting plates with anti-corrosion treatment for the assembly of non-modular equipment

Code	For boards LxH (mm)	Pack Carton
GW 46 401	250x300	1/5
GW 46 402	310x425	1/5
GW 46 403	405x500	1/5
GW 46 404	405x650	1/4
GW 46 405	515x650	1/2
GW 46 406	585x800	1/2
GW 46 407	800x1060	1

NOTES: for further information relating to the maximum applicable loads, see the table on the corresponding pages of the technical catalogue.




GW 46 464

Perforated back-mounting plates in galvanised steel for the assembly of non-modular equipment

Code	For boards LxH (mm)	Pack Carton
GW 46 461	250x300	1/5
GW 46 462	310x425	1/5
GW 46 463	405x500	1/5
GW 46 464	405x650	1/5
GW 46 465	515x650	1/4
GW 46 466	585x800	1/3
GW 46 467	800x1060	1/2

NOTES: to install devices, use nut and clips GW46450.
for further information relating to the maximum applicable loads, see the table on the corresponding pages of the technical catalogue.




GW 46 408

Back-mounting plates in insulating material for the assembly of non-modular equipment

Code	For boards LxH (mm)	Pack Carton
GW 46 408	250x300	1/5
GW 46 409	310x425	1/5
GW 46 410	405x500	1/5
GW 46 411	405x650	1/4
GW 46 412	515x650	1/3
GW 46 413	585x800	1/2

NOTES: for further information relating to the maximum applicable loads, see the table on the corresponding pages of the technical catalogue.

Blank plates in steel - Fixing by means of uprights



GW 46 540

Code	For boards LxH (mm)	No. of modules EN 50022	Pack Carton
Height: 1 Module			
GW 46 540	310x425	12	1/5
GW 46 541	405x500/405x650	18	1/5
GW 46 542	515x650	24	1/5
GW 46 543	585x800	28	1/5
GW 46 544	800x1060	36	1/4
Height: 2 Modules			
GW 46 580	310x425	12	1/5
GW 46 581	405x500/405x650	18	1/5
GW 46 582	515x650	24	1/5
GW 46 583	585x800	28	1/5
GW 46 584	800x1060	36	1/2

NOTES: to install non-standard devices and/or moulded-case devices.

Nut and clips in galvanised steel for the fixing of devices on to perforated back-mounting plates



GW 46 450

Code	Description	Pack Carton
GW 46 450	Clip nut for screw M5	10/100

Service complementary items

Double insulation and drainage kit



GW 46 526

Code	Description	Pack Carton
GW 46 526	4 caps for resetting double insulation and 1 cap for closing the drain hole	1/20

CHARACTERISTICS: isolating technopolymer.
APPLICATIONS: correctly installed, makes it possible to restore original IP degree and double insulation of 46QP range boards in case of direct fixing of the board to the wall by drilling the back plate and without using the set of 4 steel brackets.


Set of 4 steel brackets for fixing surface-mounting boards



GW 46 451

Code	Material	Accessories supplied	Pack Carton
GW 46 446	Galvanised steel	Self-tapping fixing screws	20
GW 46 451	Stainless steel	Self-tapping fixing screws	20

CHARACTERISTICS: To restore the double insulation and original IP degree of the boards in case of indirect fixing to the wall. Suitable also for 46QP photovoltaic application.



GW 46 551

Pole support kit for boards 46 QP

Code	For boards LxH (mm)	Max sustainable load (kg)	Pack Carton
GW 46 551	250x300	125	1
GW 46 552	310x425	125	1
GW 46 553	405x500/405x650	125	1
GW 46 554	515x650	125	1
GW 46 555	585x800	125	1

CHARACTERISTICS: fixed on the back of the boards.
APPLICATIONS: for applications of the 46QP boards on poles from 60 to 80mm and, by means of a banding (not included with the accessories supplied), from 80 to 200mm. To restore the double insulation and original IP degree of the boards in case of indirect fixing to the wall. Suitable also for 46QP photovoltaic application.
ACCESSORIES SUPPLIED: 2 pieces. For the correct use of the kit, see the instructions sheet.




GW 46 557 F

Kit for wiring trunking assembly

Code	Trunking use	Pack Carton
GW 46 557 F	Horizontal and/or vertical	1/10

CHARACTERISTICS: fixing on the board uprights. In the boards of size 3, 4, 5 and 6, vertical trunking support up to (LxH) 60x60 mm and horizontal trunking up to (LxH) 60x40 mm, while for boards of size 7, vertical and horizontal trunking support up to (LxH) 40x60 mm.
APPLICATIONS: for boards of at least 405x500 mm.
NOTES: the kit for wiring trunking assembly is used to create flat horizontal and vertical routes.
ACCESSORIES SUPPLIED: 2 trunking fixing brackets, 2 DIN rail assembly brackets and 6 - 4x6 mm screws. For the use of the kit, see the instructions sheet.



GW 46 524 F

Fast and Easy quick assembly brackets kit with support slide, adjustable for DIN rails

Code	Used for DIN rails	Pack Carton
GW 46 524 F	Simple and double	1/4

NOTES: use the GW46524F kit to assembly the 18, 24, 28 and 36M DIN rails without the specific blanck panel.
To restore the minimum degree of protection of the open door board, use the relative inner door.



GW 46 591

Handles for transportation

Code	Description	Pack Carton
GW 46 591	Pair of handles	1/10

APPLICATIONS: allows the 46QP boards to be transported.
NOTES: the handle kit can be used simultaneously with the pole support kit or the set of brackets, for wall mounting.

Blanking module profile in plastic material - Grey RAL 7035




GW 47 291

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 423	4.5	Grey RAL 7035	50
GW 47 291	24	Grey RAL 7035	10

CHARACTERISTICS: clip fixing on DIN perforated front panels.

Depth adapter



GW D3 317

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).

Seal for coupling boards equipped with drilling template - IP55



GW 46 449

Code	Dimensions (mm)	Pack Carton
GW 46 449	300x171	1/10

APPLICATIONS: can be used on enclosures starting with the 515x650x250 mm dimension.

Set of 4 reversible squares for fixing back-mounting plates or uprights for modular equipment



GW 46 521 F


Code	Description	Pack Carton
GW 46 521 F	Reversible squares	1/20

APPLICATIONS: allows the combined installation of the back-mounting plate and the frame.
ACCESSORIES SUPPLIED: fixing screws; 4 inserts.

Inserts kit

Code	Description	Pack Carton
GW 46 592 F	M6 inserts kit	1/100

APPLICATIONS: allows you to extend the possibility of adding functional accessories to all the slots of the 46QP boards.
NOTES: the inserts are inserted in the free slots of the 46QP boards and are expanded in the housing using a small dowel with a diameter of 4mm. One insert kit package contains 10 inserts.



GW 46 592 F

Triangular key

Code	Description	Pack Carton
GW 46 522	Triangular key	10

APPLICATIONS: for boards 46QP, QX, QM e CEP.



GW 46 522

Triangular lock

Code	Description	Pack Carton
GW 46 523	Triangular lock	10

APPLICATIONS: for boards 46QP, QX, QM e CEP.



GW 46 523

Security lock with handle

Code	Description	Pack Carton
GW 46 445	Security lock key and handle	10

APPLICATIONS: for boards 46QP, QX, QM e CEP.
ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.



GW 46 445

Ventilation kit



GW 46 448

Code	IP degree	Rated voltage	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 448	IP44	230 V - 50 / 60 Hz	125x117	123x115	1/2

CHARACTERISTICS: the fan takes in air from the outside and introduces it into the distribution board, creating a slight overpressure that prevents foreign particles from entering. Max fan capacity 60 m³/h. Absorbed power equal to 20 W.
APPLICATIONS: forced ventilation in critical thermal conditions.
ACCESSORIES SUPPLIED: drilling template.

Aeration kit



GW 46 471

Code	IP degree	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 471	IP44	125x117	123x115	1/10

ACCESSORIES SUPPLIED: drilling template.

Document holder pocket in self-adhesive insulating material with kit of blank labels



GW 46 447

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10

CHARACTERISTICS: can be inserted in all GEWISS enclosures from dimension 405x500x200 mm upwards.

Two-pole distribution terminal blocks with transparent protection cover - fixing on plate or DIN rail EN 50022 - 750V - T 85°C




GW 44 693

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 691	68x47x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/40
Rated current (A): 125						
GW 44 693	134x47x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/12

CHARACTERISTICS: the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".
NOTES: products bearing the IMQ quality mark.

Four-pole distribution terminal blocks with transparent protection cover. Fixing on plate or DIN rail EN 50022 - 750V - T 85°C




GW 44 696

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 696	72x98x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/20
Rated current (A): 125						
GW 44 698	138x98x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/10
Rated current (A): 160						
GW 44 699	186x136x70	11	1x(16-50) mm²	[2x(10-35) + 2x(6-25) + 8x(4-16)] mm²	10 kA	1/12

CHARACTERISTICS: terminal tightening torque: input cables 4 Nm, output cables 1.5 Nm.
the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".
NOTES: products bearing the IMQ quality mark.

Horizontal four-pole divider 250 A with pre-drilled threaded M6 bars - 20x5 mm



GW 44 700

Code	Dimensions (mm)	No. of modules EN 50022	Installation	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
GW 44 700	285x190x70	16	On profile EN 50022	1xM12	10xM6	17 kA	1/2

ACCESSORIES SUPPLIED: installation clip on DIN rail.

44 CEP - WATERTIGHT BOARDS IN GWPLAST 120 - GWT 650 °C - IP55



IK 08

IP 55

GWT 650°C





Distribution boards



GW 44 810

Watertight boards with blank door fitted with lock - Grey RAL 7035

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 44 808	200x254x135	-	1	16	17	4
GW 44 809	236x316x135	8	1	26	31	4
GW 44 810	316x396x160	24 (12X2)	2	42	34	2
GW 44 811	396x474x160	32 (16X2)	2	52	46	2

CHARACTERISTICS: Doors equipped with functional grid of reference for fixing the devices. Impact resistance: 5 J.
ACCESSORIES SUPPLIED: frame for semi-flush-mounting installations, screwcap for double insulation, triangle key.
NOTES: The technical and functional characteristics, and the nominal values, refer to vertical installation only.
Dispersible power calculated according to CEI 23-49:
Dispersible power A (W): configuration of the board with relative back-mounting plate.
Dispersible power B (W): configuration of the board with relative panel with windows.



GW 44 820

Watertight boards with transparent door fitted with lock - Grey RAL 7035

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	No. locks	Dispersible power A (W)	Dispersible power B (W)	Pack Carton
GW 44 818	200x254x135	-	1	16	17	4
GW 44 819	236x316x135	8	1	26	31	4
GW 44 820	316x396x160	24 (12X2)	2	42	34	2
GW 44 821	396x474x160	32 (16X2)	2	52	46	2

CHARACTERISTICS: Doors equipped with functional grid of reference for fixing the devices. Impact resistance: 5 J.
ACCESSORIES SUPPLIED: frame for semi-flush-mounting installations, screwcap for double insulation, triangle key.
NOTES: The technical and functional characteristics, and the nominal values, refer to vertical installation only.
Dispersible power calculated according to CEI 23-49:
Dispersible power A (W): configuration of the board with relative back-mounting plate.
Dispersible power B (W): configuration of the board with relative panel with windows.


Internal configuration



GW 44 639

Back-mounting plate in galvanised steel with self-tapping fixing screws

Code	For boards LxH (mm)	Pack Carton
GW 44 636	200x254	20
GW 44 637	236x316	20
GW 44 638	316x396	5
GW 44 639	396x474	5



GW 44 649

Back-mounting plate in insulated material with self-tapping fixing screws

Code	For boards LxH (mm)	Pack Carton
GW 44 646	200x254	20
GW 44 647	236x316	20
GW 44 648	316x396	4
GW 44 649	396x474	5

CHARACTERISTICS: equipped with functional grid for fixing devices.



GW 44 854

Panels with window for modular devices and moulded-case circuit breakers in fixed position execution, up to 160 A coupling - Grey RAL 7035

HF HALOGEN FREE

Code	No. of modules EN 50022	For boards LxH (mm)	Suitable for	Pack Carton
GW 44 852	8	236x316	Moulded case max 125 A	8
GW 44 853	14	316x396	Moulded case max 160 A	8
GW 44 854	24 (12X2)	316x396	Moulded case max 125 A	8
GW 44 855	32 (16X2)	396x474	Moulded case max 160 A	8

ACCESSORIES SUPPLIED: fixing uprights and DIN rails, module masks, user labels.

Service complementary items

Set of 4 steel brackets for fixing surface-mounting boards



GW 46 451

Code	Material	Accessories supplied	Pack Carton
GW 46 446	Galvanised steel	Self-tapping fixing screws	20
GW 46 451	Stainless steel	Self-tapping fixing screws	20

Wall fixing bracket




GW 44 621

Code	Material	Accessories supplied	For enclosures For dist. boards	Pack Carton
GW 44 621	Insulation	Self-tapping fixing screws	All wall types	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.

Plastic module cover profile



GW 40 423

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 423	4.5	Grey RAL 7035	50

CHARACTERISTICS: clip fixing on DIN perforated front panels.

Triangular key



GW 46 522

Code	Description	Pack Carton
GW 46 522	Triangular key	10

APPLICATIONS: for boards 46QP, QX, QM e CEP.

Triangular lock

Code	Description	Pack Carton
GW 46 523	Triangular lock	10

APPLICATIONS: for boards 46QP, QX, QM e CEP.



GW 46 523

Security lock with handle

Code	Description	Pack Carton
GW 46 445	Security lock key and handle	10

ACCESSORIES SUPPLIED: 2 keys.

NOTES: All the keys and relative locks with the same product code are identical.



GW 46 445



46



Scan the QR Code and find out all the technical informations.

46 QP - NEW STYLE AND PERFORMANCE



The 46 QP polyester boards feature an IP66 protection rating, and the modern-design transparent door versions offer more than 20% extra internal visibility than previous versions.

46 QP - SOLUTIONS FOR EVERY APPLICATION



GEWISS has subjected the 46 QP boards to rigorous testing in order to obtain valid certifications for their use in various applications. 46 QP boards are, for example, ASC approved and certified for site applications and are ideal for photovoltaic installations.

FAST & EASY - ROBUSTNESS, SPEED AND MULTIPLE ACCESSORY OPTIONS



The FAST & EASY system, common to the 46 QP/QM/QX boards, reduces assembly time by up to 40% compared to traditional systems. Robustness and reliability are achieved through the use of metal components and via a rapid and intuitive usage.

40 CD

Surface-mounting enclosures

			40 CDK SURFACE-MOUNTING MODULAR WATERTIGHT ENCLOSURES AND BOARDS IP65			40 CD SURFACE-MOUNTING WATERTIGHT ENCLOSURES IP55
			Colour: RAL 7035 Grey Walls: smooth 			Colour: RAL 7035 Grey Walls: with perforations centres 
			Door: smoked transparent			Door: smoked transparent
			Without terminal block	With 80A - IP20 bipolar terminal block		
				1st level	2nd level	
Modules		2	-	-	-	-
		4	GW 40 101	-	-	GW 40 001
		6	-	-	-	-
		8	GW 40 102	GW 40 102 BS	-	GW 40 003
		12	GW 40 103	GW 40 103 BS	-	GW 40 005
		18	GW 40 106	GW 40 106 BS	-	-
		24 (12x2)	GW 40 104	GW 40 104 BS	GW 40 104 BD	GW 40 007
		36 (12x3)	GW 40 105	GW 40 105 BD	GW 40 105 UD	-
		36 (18x2)	GW 40 107	GW 40 107 BS	GW 40 107 BD	GW 40 009
		54 (18x3)	GW 40 108	GW 40 108 BD	GW 40 108 BT	-
		72 (18x4)	GW 40 109	GW 40 109 BD	GW 40 109 BQ	-
COMPLEMENTARY ITEMS	INSTALLATION	Surface-mounting fixing brackets for enclosures and boards 	4 x GW 44 621			4 x GW 44 621
		Stylish coupling covers for conduit and trunking entry 	**Modules**	**Code**		-
			12-24-36(12x3)	GW 40 473		
			18-36(18x2)-54-72	GW 40 474		
	WIRING	Internal horizontal dividers 	**Modules**	**Code**		-
			24-36(12x3)	GW 40 487		
			36(18x2)-54-72	GW 40 488		
		Blind cover panels 1 module height	**Modules**	**Code**		-
			24-36(12x3)	GW 40 492		
			36(18x2)-54-72	GW 40 493		
	MISCELLANEOUS	Cylindrical safety lock 	**Modules**	**Code**		-
			4-8-12-18-24-36(18x2)	1 x GW 40 422		
			36(12x3)-54-72	2 x GW 40 422		
		Triangular key 	-			1 x GW 40 421

40 CD PROTECTED SURFACE-MOUNTING DECORATIVE ENCLOSURES IP40						40 CD PROTECTED SURFACE-MOUNTING ENCLOSURES IP40
Colour: RAL 9016 White Walls: smooth						Colour: RAL 7035 Grey Walls: awith perforation centres 
Door: smoked transparent			Door: blank			Door: no
Without terminal block	With 80A - IP20 bipolar terminal block		Without terminal block	With 80A - IP20 bipolar terminal block		Without terminal block
	1st level	2nd level		1st level	2nd level	
-	-	-	-	-	-	GW 40 022
-	-	-	-	-	-	GW 40 023
-	-	-	-	-	-	GW 40 024
GW 40 043	GW 40 043 BS	-	GW 40 063	GW 40 063 BS	-	GW 40 026
GW 40 045	GW 40 045 BS	-	GW 40 065	GW 40 065 BS	-	GW 40 028
-	-	-	-	-	-	-
GW 40 047	GW 40 047 BS	GW 40 047 BD	GW 40 067	GW 40 067 BS	GW 40 067 BD	GW 40 030
-	-	-	-	-	-	GW 40 032
GW 40 049	GW 40 049 BS	GW 40 049 BD	GW 40 069	GW 40 069 BS	GW 40 069 BD	-
GW 40 051	GW 40 051 BD	-	GW 40 071	GW 40 071 BD	-	-
GW 40 053	GW 40 053 BD	GW 40 053 BQ	GW 40 073	GW 40 073 BD	GW 40 073 BQ	-
4 x GW 44 621						4 x GW 44 621
-						-
-						-
-						-
Modules			**Code**			-
8-12-18-24-36-54			1 x GW 40 422			
72			2 x GW 40 422			
-						-

Compatibility of surface mounting enclosures with bipolar and unipolar terminal blocks

Surface-mounting encloure range	Modules	Door	Code	Terminal blocks position	Screw terminal blocks Terminal block size 1 Bipolar 125 A 2 x [(1x35)+(7x10)] GW 40 401	Bipolar 80 A 2 x [(2x16)+(7x10)] GW 40 408 B	Unipolar 80 A 1 x [(2x16)+(7x10)] GW 40 408 U
40 CDK SURFACE-MOUNTING MODULAR WATERTIGHT ENCLOSURES AND BOARDS IP65 	**8**	Door: smoked transparent	GW 40 102		N° 1	N° 1	N° 1
	12	Door: smoked transparent	GW 40 103		N° 1 (*)	N° 1 (*)	N° 1 (*)
	18	Door: smoked transparent	GW 40 106		N° 1 (*)	N° 1 (*)	N° 1 (*)
	24 (12x2)	Door: smoked transparent	GW 40 104		N° 2 (*)	N° 2 (*)	N° 2 (*)
	36 (12x3)	Door: smoked transparent	GW 40 105		N° 2 (*)	N° 2 (*)	N° 2 (*)
	36 (18x2)	Door: smoked transparent	GW 40 107		N° 2 (*)	N° 2 (*)	N° 2 (*)
	54 (18x3)	Door: smoked transparent	GW 40 108		N° 3 (*)	N° 3 (*)	N° 3 (*)
	72 (18x4)	Door: smoked transparent	GW 40 109		N° 4 (*)	N° 4 (*)	N° 4 (*)
40 CD SURFACE-MOUNTING WATERTIGHT ENCLOSURES IP55 	**8**	Door: smoked transparent	GW 40 003		N° 1	N° 1	N° 1
	12	Door: smoked transparent	GW 40 005		N° 1 (*)	N° 1 (*)	N° 1 (*)
	24 (12x2)	Door: smoked transparent	GW 40 007		N° 2	N° 2	N° 2
	36 (18x2)	Door: smoked transparent	GW 40 009		N° 2 (*)	N° 2 (*)	N° 2 (*)
40 CD PROTECTED SURFACE-MOUNTING DECORATIVE ENCLOSURES IP40  	**8**	Door: smoked transparent	GW 40 043		N° 1	N° 1	N° 1
		Door: blank	GW 40 063				
	12	Door: smoked transparent	GW 40 045		N° 1 (*)	N° 1 (*)	N° 1 (*)
		Door: blank	GW 40 065				
	24 (12x2)	Door: smoked transparent	GW 40 047		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Door: blank	GW 40 067				
	36 (18x2)	Door: smoked transparent	GW 40 049		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Door: blank	GW 40 069				
	54 (18x3)	Door: smoked transparent	GW 40 051		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Door: blank	GW 40 071				
	72 (18x4)	Door: smoked transparent	GW 40 053		N° 4 (*)	N° 4 (*)	N° 4 (*)
		Door: blank	GW 40 073				
40 CD PROTECTED SURFACE-MOUNTING ENCLOSURES IP40 	**8**	Door: no	GW 40 026		N° 1	N° 1	N° 1
	12	Door: no	GW 40 028		N° 1 (*)	N° 1 (*)	N° 1 (*)
	24 (12x2)	Door: no	GW 40 030		N° 2	N° 2	N° 2
	36 (12x3)	Door: no	GW 40 032		N° 2 (*)	N° 2 (*)	N° 2 (*)

(*) The installation is allowed using No.1 adapter GW40413 for each terminal block installed.

Screw terminal blocks



Terminal block size 2				Terminal block size 3		
Bipolar 125 A 2 x [(3x35)+(10x10)]	Bipolar 80 A 2 x [(3x16)+(11x10)]	Unipolar 80 A 1 x [(3x16)+(11x10)]	Unipolar 80 A 1 x [(3x16)+(29x10)]	Bipolar 125 A 2 x [(5x35)+(14x10)]	Bipolar 80 A 2 x [(3x16)+(17x10)]	Unipolar 80 A 1 x [(3x16)+(17x10)]
GW 40 402	GW 40 412 B	GW 40 412 U	GW 40 422 U	GW 40 404	GW 40 418 B	GW 40 418 U
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 1 (*)	N° 1 (*)	N° 1 (*)	N° 1 (*)	N° 1	N° 1	N° 1
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3	N° 3	N° 3
N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4	N° 4	N° 4
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
-	-	-	-	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4	N° 4	N° 4
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
-	-	-	-	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-

40 CD

Surface-mounting distribution boards and enclosures



The 40CD Series of control units, available in transparent or blind door versions and in sizes from 8 to 72 modules, guarantees aesthetic integration with all types of furniture. The offer includes: 40CDK - IP65 watertight panels with removable frame (from 24M) and lead-in panels; accessories with wiring ducts, locks, aesthetic covers and blind panels, 40CD - IP55 watertight control units with drilling doilies on the walls, door with lock for each modular row; 40CD control units protected by furniture - IP40 up to 72M in the smoke and blind door versions; 40CD control units without door - IP40. All materials are Halogen Free.

40 CDK - MODULAR WATERTIGHT ENCLOSURES AND DISTRIBUTION BOARDS - IP65













Smoked transparent door - Smooth walls



GW 40 101

Enclosures - predisposed for terminal block - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 101	4	143x210x100	13	19
GW 40 102	8	215x210x100	16	12
GW 40 103	12	298x260x140	26	6
GW 40 106	18	410x285x140	38	3

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels. GW40102, GW40103 and GW40106, self-adhesive label to be filled out for certification according to standard CEI 23-51.
NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).
For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.



GW 40 102 BS

Enclosures - equipped with 80 A IP20 bipolar screw terminal block - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 102 BS	8	215x210x100	16	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	12
GW 40 103 BS	12	298x260x140	26	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	6
GW 40 106 BS	18	410x285x140	38	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	3

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter. To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621). For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.
CHARACTERISTICS: thermo-pressure with ball equal to 70°C.



GW 40 105

Distribution boards with panels with window and extractable frame predisposed for terminal block - Grey RAL 7035

EN 62208 EN 62208

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 104	24 (12X2)	298x420x140	32	3
GW 40 105	36 (12x3)	298x570x140	42	2
GW 40 107	36 (18x2)	410x463x140	43	2
GW 40 108	54 (18x3)	410x655x140	66	1
GW 40 109	72 (18x4)	410x878x160	89	1

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).
For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.
CHARACTERISTICS: removable and plumbable panels with windows. Thermo-pressure with ball equal to 70°C.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.



GW 40 105 BD

Distribution boards with windowed removable panels, extractable frame equipped with 80 A IP20 bipolar screw terminal blocks - Grey RAL 7035

EN 62208 EN 62208

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 104 BS	24 (12X2)	298x420x140	32	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	3
GW 40 104 BD	24 (12X2)	298x420x140	32	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	3
GW 40 105 BD	36 (12x3)	298x570x140	42	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	2
GW 40 105 UD	36 (12x3)	298x570x140	42	N/E (3x16) + (29x10)	N/E (3x16) + (29x10)	2
GW 40 107 BS	36 (18x2)	410x463x140	43	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	2
GW 40 107 BD	36 (18x2)	410x463x140	43	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 108 BD	54 (18x3)	410x655x140	66	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 108 BT	54 (18x3)	410x655x140	66	N/E 3x[(3x16) + (17x10)]	N/E 3x[(3x16) + (17x10)]	1
GW 40 109 BD	72 (18x4)	410x878x160	89	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 109 BQ	72 (18x4)	410x878x160	89	N/E 4x[(3x16) + (17x10)]	N/E 4x[(3x16) + (17x10)]	1

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter. To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621). For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.
CHARACTERISTICS: thermo-pressure with ball equal to 70°C.

40 CD - WATERTIGHT ENCLOSURES - IP55



IK 09

IP 55

GWT 650°C





Smoked transparent door - Walls with perforation centres



GW 40 001

Enclosures predisposed for terminal block - Grey RAL 7035

EN 62208 EN 62208

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 001	4	105x170x98	12	24
GW 40 003	8	180x180x98	13	24
GW 40 005	12	250x250x135	25	8
GW 40 007	24 (12X2)	250x375x135	27	6
GW 40 009	36 (18x2)	376x400x135	41	4

ACCESSORIES SUPPLIED: screwcaps and module masks, circuit labels, spare screws in insulating material.
Self-adhesive label to be filled out for certification according to standard CEI 23-51.
GW40005, GW40007, GW40009: doors equipped with lock, with 2 triangular keys.
NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).
For applications in the photovoltaic environment, use the surface-mounting brackets - code GW44621.
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.

40 CD - PROTECTED DECORATIVE ENCLOSURES - IP40



IK 08

IP 40

GWT 650°C





Smoked transparent door - Smooth walls

Enclosures predisposed for terminal block - White RAL 9016



GW 40 043

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 043	8	200x180x100	15	14
GW 40 045	12	280x225x100	22	9
GW 40 047	24 (12X2)	280x350x100	25	6
GW 40 049	36 (18x2)	400x400x130	45	2
GW 40 051	54 (18x3)	400x550x130	63	2
GW 40 053	72 (18x4)	400x850x150	75	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
GW40049, GW40051, GW40053, fitted with removable frame, to carry out the wiring operations outside the enclosure.
NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps or brackets for surface-mounting).
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.

Enclosures equipped with 80 A IP20 bipolar screw terminal blocks - White RAL 9016



GW 40 043 BS

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 043 BS	8	200x180x100	15	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	14
GW 40 045 BS	12	280x225x100	22	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	9
GW 40 047 BS	24 (12X2)	280x350x100	25	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	6
GW 40 047 BD	24 (12X2)	280x350x100	25	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	6
GW 40 049 BS	36 (18x2)	400x400x130	45	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	2
GW 40 049 BD	36 (18x2)	400x400x130	45	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 051 BD	54 (18x3)	400x550x130	63	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 053 BD	72 (18x4)	400x850x150	75	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 053 BQ	72 (18x4)	400x850x150	75	N/E 4x[(3x16) + (17x10)]	N/E 4x[(3x16) + (17x10)]	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. GW40049BS,GW40049BD GW40051BD,GW40053BD GW40053BQ, fitted with removable frame, to carry out the wiring operations outside the enclosure. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter. To restore the double insulation, use the relative accessories supplied (module masks and screwcaps or brackets for surface-mounting).
CHARACTERISTICS: thermo-pressure with ball equal to 70°C.

Blank door - Smooth walls



GW 40 067

Enclosures predisposed for terminal block - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 063	8	200x180x100	15	14
GW 40 065	12	280x225x100	22	9
GW 40 067	24 (12X2)	280x350x100	25	6
GW 40 069	36 (18x2)	400x400x130	45	2
GW 40 071	54 (18x3)	400x550x130	63	2
GW 40 073	72 (18x4)	400x850x150	75	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. GW40069, GW40071, GW40073, fitted with removable frame, to carry out the wiring operations outside the enclosure.

NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter. To restore the double insulation, use the relative accessories supplied (module masks and screwcaps or brackets for surface-mounting).

CHARACTERISTICS: thermo-pressure with ball equal to 70°C.

INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.



GW 40 067 BD

Enclosures equipped with 80A IP20 bipolar screw terminal blocks - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm^2)	Pole 2 (mm^2)	Pack Carton
GW 40 063 BS	8	200x180x100	15	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	14
GW 40 065 BS	12	280x225x100	22	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	9
GW 40 067 BS	24 (12X2)	280x350x100	25	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	6
GW 40 067 BD	24 (12X2)	280x350x100	25	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	6
GW 40 069 BS	36 (18x2)	400x400x130	45	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	2
GW 40 069 BD	36 (18x2)	400x400x130	45	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 071 BD	54 (18x3)	400x550x130	63	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 073 BD	72 (18x4)	400x850x150	75	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 073 BQ	72 (18x4)	400x850x150	75	N/E 4x[(3x16) + (17x10)]	N/E 4x[(3x16) + (17x10)]	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. GW40069BS, GW40069BD, GW40071BD, GW40073BD, GW40073BQ fitted with removable frame, to carry out the wiring operations outside the enclosure. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame) before wiring.

NOTES: dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter. To restore the double insulation, use the relative accessories supplied (module masks and screwcaps or brackets for surface-mounting).

CHARACTERISTICS: thermo-pressure with ball equal to 70°C.


40 CD - PROTECTED ENCLOSURES - IP40



IK 08

IP 40

GWT 650°C





Without door - Walls with perforation centres

Enclosures pre-arranged for terminal block - Grey RAL 7035



GW 40 022


Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 022	2	45x130x85	7	84
GW 40 023	4	90x130x85	9	36
GW 40 024	6	140x155x85	14	34
GW 40 026	8	180x180x95	18	24
GW 40 028	12+1	250x215x95	27	12
GW 40 030	24+2 (12x2)	250x340x95	40	12
GW 40 032	36+3 (12x3)	250x465x95	54	9

CHARACTERISTICS: Thermo-pressure with ball equal to 70°C. GW40022 plumbable front.
ACCESSORIES SUPPLIED: module masks, circuit labels.
GW40026, GW40028, GW40030, GW40032 supplied with self-adhesive label to be filled out for certification according to standard CEI 23-51.
NOTES: Dispersible power calculated according to CEI 23-49. For the perforations, use the GW52401 milling cutter.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps or brackets for surface-mounting). To maintain the IP degree declared, install devices with a degree of protection of at least IP40 and use the relative accessories (module masks, screwcaps or wall mounting brackets).
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.

COMPLEMENTARY ITEMS

Installation and coupling

Wall fixing bracket



GW 44 621

Code	Material	Accessories supplied	For enclosures For dist. boards	Pack Carton
GW 44 621	Insulation	Self-tapping fixing screws	All wall types	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.

Aesthetic coupling covers for conduit and trunking entry for CDK distribution boards and enclosures



GW 40 474

Code	For encl. /boards with rail	Fixing	Pack Carton
GW 40 473	12 Modules	Clip	20
GW 40 474	18 Modules	Clip	20

CHARACTERISTICS: covers with internal knockouts for trunking from 60x30mm to 200x60mm.

Wiring



GW 40 412 B

Insulated screw terminal block bipolar and unipolar for enclosures and boards

Code	Pole 1 (mm²)	Pole 2 (mm²)	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A				
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	With screws and/or clip	10
GW 40 404	N (5x35) + (14x10)	E (5x35) + (14x10)	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20				
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	With screws and/or clip	1/10
GW 40 418 B	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20				
GW 40 408 U	N/E (2x16) + (7x10)	-	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	With screws and/or clip	1/10
GW 40 418 U	N/E (3x16) + (17x10)	-	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
USES: Ideal also for earth connection of SPD.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.

Adapters for screw terminal blocks

Code	For enclosures	Fastener to supports	Pack Carton
GW 40 413	12 M (and multiples) and 18 M (and multiples)	With screws	20



GW 40 413

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block and pre-cut to allow installation also in enclosures with a 12 M modular step.
INSTALLATION: used to expand the number of possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF SURFACE-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CD range.

Internal horizontal dividers for CDK distribution boards



GW 40 488

Code	For boards EN 50022 rail	Fixing	Pack Carton
GW 40 487	12 Modules	Clip	10/100
GW 40 488	18 Modules	Clip	10/100

NOTES: they permit making internal separation between the circuits having different voltages located on more than one row inside the same shell.

Blank cover panels 1 module high for CDK distribution boards



GW 40 493

Code	Suitable for	For boards EN 50022 rail	Colour	Pack Carton
GW 40 492	CDK enclosures and boards decorative (Surface-mounting)	12 Modules	Grey RAL 7035	20
GW 40 493	CDK enclosures and boards decorative (Surface-mounting)	18 Modules	Grey RAL 7035	20

CHARACTERISTICS: sealing.

Miscellaneous



GW 40 421

Security triangular key

Code	For enclosures	Material	Pack Carton
GW 40 421	40 CD Watertight IP55	Insulation	10/100



GW 40 422

Cylindrical security lock - for 40 CDK and 40 CD decorative enclosures

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

GW 40 467

Plastic module cover profile

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50
GW 40 423	4.5	Grey RAL 7035	50

CHARACTERISTICS: clip fixing.




GW 44 623

Insulating screw caps

Code	Description	Pack Carton
GW 44 623	Screwcap Ø25mm	10/100

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.



40 CD



Scan the QR Code and find out all the technical informations.

40 CDK - WATERTIGHT ENCLOSURES AND DISTRIBUTION BOARDS



IP65 40 CDK 4 to 72M watertight enclosure range in smoked transparent door version. The main technical features are: reversible bottoms and fronts, removable windowed frames and panels, and doors that open up to 180°, are removable and can be fitted with a lock.

40 CD - DECORATIVE PROTECTED ENCLOSURES



The IP40-rated 40 CD protected decorative enclosures are available in sizes from 8 to 72M and ensure seamless aesthetic integration with any interior design scheme. Available with smoked transparent or white blank doors, feature the “PUSH” opening and closing system.

ONE-POLE AND TWO-POLE TERMINAL BLOCKS - 80 A - IP20



Available with screw wiring, the two-pole and single-pole terminal blocks enable quick wiring as the cable screws are supplied unscrewed. The terminal blocks can be fixed directly on the back plate of the enclosures or with specific adapter.

Surface-mounting enclosures and distribution boards

					40 CDe FRENCH STANDARD ENCLOSURES - IP30
				Colour: White RAL 9016	
					Door: no
					With terminal blocks
MODULES		13			GW 40 501
		26 (13x2)			GW 40 502
		39 (13x3)			GW 40 503
		52 (13x4)			GW 40 504
COMPLEMENTARY ITEMS	INSTALLATION	Kit of modular spacers		13 modules	GW 40 516
				26 modules	GW 40 517
				39 modules	GW 40 518
				52 modules	GW 40 519
		Blank door with frame - White RAL 9016 - IP40		13 modules	GW 40 531
				26 modules	GW 40 532
				39 modules	GW 40 533
				52 modules	GW 40 534
		Transparent smoked door with frame - White RAL 9016 - IP40		13 modules	GW 40 536
				26 modules	GW 40 537
				39 modules	GW 40 538
				52 modules	GW 40 539
		Black-mounting plate		13 modules	GW 40 526
				26 modules	GW 40 527
				39 modules	GW 40 528
				52 modules	GW 40 529
		Support base		13 modules (P=40mm)	GW 40 511
				13 modules (P=55mm)	GW 40 512
		White RAL 9016 door with frame - IP40		13 modules	GW 40 541
		Transparent smoked door with frame - IP40		13 modules	GW 40 542
		2 pipe fitting for vertical and horizontal coupling of enclosures		Clip	GW 40 546
		Home VDI enclosure - Grade 1 - White RAL 9016		4xRJ45 connectors + 4xTV/SAT output	GW 40 506
	WIRING	Isolated unipolar terminal blocks		3x25 + 12x4 - Green	GW 40 591
				4x25 + 24x4 - Green	GW 40 592
				1x35 + 5x25 - Black	GW 40 593
				1x35 + 5x25 - Blue	GW 40 594
	ACCESSORIES	Cylindrical security lock		-	GW 40 422

					40 CDe GERMAN STANDARD ENCLOSURES		
					Colour: Gray RAL 7035 	Colour: Gray RAL 7035 	Colour: White RAL 9016 
					IP65		IP30
					Door: smoked transparent		Door: no
					With terminal blocks	With terminal blocks and two interchangeable flanges	With terminal blocks
MODULES		4			GW 40 101 (ready for terminal blocks)	-	-
		8			GW 40 112	-	-
		12			-	GW 40 113 * GW 40 123 **	GW 43 021 S
		18			GW 40 116	-	-
		24 (12x2)			-	GW 40 114 * GW 40 124 **	GW 43 022 S
		36 (12x3)			-	GW 40 115 * GW 40 125 **	GW 43 023 S
		36 (18x2)			GW 40 117	-	-
		48 (12x4)			-	-	GW 43 024 S
		54 (18x3)			GW 40 118	-	-
		72 (18x4)			GW 40 119	-	-
COMPLEMENTARY ITEMS	INSTALLATION	Wall fixing brackets		-	4 x GW 44 621		-
		Design coupling cover for conduit entry		12-24-36(12x3) mod.	GW 40 473		-
				18-36(18x2)-54-72 mod.	GW 40 474		-
	WIRING	Internal horizontal divider		24-36(12x3) mod.	GW 40 487		-
				36(18x2)-54-72 mod.	GW 40 488		-
		Blank lid panels - 1 module height		24-36(12x3) mod.	GW 40 492		-
				36(18x2)-54-72 mod.	GW 40 493		-
	ACCESSORIES	Cylindrical security lock		4-8-12-18-24-36(18x2) mod.	1 x GW 40 422		-
				36(12x3)-54-72 mod.	2 x GW 40 422		-
		Interchangeable flange with quick-entry cable glands		-	GW 40 428		-
	INSTALLATION	Blank doors - White RAL 9016		12 mod.	-		GW 43 071 S
				24 (12x2) mod.	-		GW 43 072 S
				36 (12x3) mod.	-		GW 43 073 S
				48 (12x4) mod.	-		GW 43 074 S
		Plastic frontal - White RAL 9016		12 mod.	-		GW 43 111 S
				24 (12x2) mod.			GW 43 112 S
				36 (12x3) mod.	-		GW 43 113 S
				48 (12x4) mod.	-		GW 43 114 S
	WIRING	Bipolar terminal blocks		12 modules	-		GW 40 451
				24 modules	-		GW 40 452
				36-48 modules	-		GW 40 453
	ACCESSORIES	Security lock		-	-		GW 40 463

* 2 flanges with knockout holes
** 1 flange with knockout holes + 1 flange with quick-entry cable glands

40 CDE

Enclosures and distribution boards for country-specific standards



The range of enclosures and distribution boards for specific country standards: 40 CD French standard enclosures (IP30), also including VDI multimedia enclosures (Grade 1, Grade 2 and Grade 3); 40 CDKE German standard enclosures - IP65 watertight with flanges for quick cable insertion, and 40CDE German standard enclosures - IP40 for home use, either surface-mounted or flush-mounted in masonry or plasterboard. The range is completed by the 40 CDE Spanish standard enclosures - IP40 with smoked transparent doors.

40 CDE - SPANISH STANDARD SURFACE-MOUNTING AND FLUSH-MOUNTING ENCLOSURES

Flush-mounting enclosures with door - IP40



GW 40 336

Distribution boards to house ICP power limiting circuit breaker sealable - In=40A - Smoked transparent door

Code	No. EN 50022 mod. ICP sect.	N. EN 50022 mod. CB section	Outer dim. LxHxD (mm)	R.U. 1407-D Classifications	Pack Carton
GW 40 336	4	8	329x225x75	CCE-ICP32	10
GW 40 337	4	12	400x225x75	CCE-ICP32	6

ACCESSORIES SUPPLIED: service labels.

40 CDKE - GERMAN STANDARD SURFACE-MOUNTING ENCLOSURES AND DISTRIBUTION BOARDS

Enclosures with smoked transparent door - IP65



GW 40 112

Enclosures and distribution boards fitted with bipolar 125 A terminal blocks

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 112	8	215x210x100	N (1x25) + (7x10)	E (1x25) + (7x10)	1/12
GW 40 116	18	410x285x140	N (5x25) + (14x10)	E (5x25) + (14x10)	1/3



GW 40 119

Enclosures and distribution boards fitted with bipolar 125 A terminal blocks

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 117	36 (18x2)	410x463x140	N (10x25)+(28x10)	E (10x25)+(28x10)	1/2
GW 40 118	54 (18x3)	410x655x140	N (10x25)+(28x10)	E (10x25)+(28x10)	1
GW 40 119	72 (18x4)	410x878x160	N (10x25)+(28x10)	E (10x25)+(28x10)	1



GW 40 113

Distribution boards and enclosures equipped with bipolar 125 A terminal blocks and two interchangeable flanges (2 flanges with knockouts hole) - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 113	12	298x260x140	N (3x35) + (10x10)	E (3x35) + (10x10)	6
GW 40 114	24 (12X2)	298x420x140	N (3x35) + (10x10)	E (3x35) + (10x10)	3
GW 40 115	36 (12x3)	298x570x140	N (6x35)+(20x10)	E (6x35)+(20x10)	2

CHARACTERISTICS: the flanges with knockout holes have the following inputs: 4xM16; 4xM20; 3xM25; 1xM32; Glow Wire Test: 750°C
ACCESSORIES SUPPLIED: terminal block, screwcaps and module masks for double insulation, circuit labels.
To restore the double insulation, use the relative accessories (module masks, screwcaps or wall mounting brackets).



GW 40 124

Distribution boards and enclosures equipped with bipolar 125 A terminal blocks and two interchangeable flanges (1 flange with knockouts hole + 1 flange with quick entry cable glands) - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 123	12	298x260x140	N (3x35) + (10x10)	E (3x35) + (10x10)	6
GW 40 124	24 (12X2)	298x420x140	N (3x35) + (10x10)	E (3x35) + (10x10)	3
GW 40 125	36 (12x3)	298x570x140	N (6x35)+(20x10)	E (6x35)+(20x10)	2

CHARACTERISTICS: the flanges with knockout holes have the following inputs: 4xM16; 4xM20; 3xM25; 1xM32; Glow Wire Test: 750°C
ACCESSORIES SUPPLIED: terminal block, screwcaps and module masks for double insulation, circuit labels.
To restore the double insulation, use the relative accessories (module masks, screwcaps or wall mounting brackets).

Complementary items

Wall fixing bracket




GW 44 621

Code	Material	Accessories supplied	For enclosures For dist. boards	Pack Carton
GW 44 621	Insulation	Self-tapping fixing screws	All wall types	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.

4.5 Modules cover



GW 40 423

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50
GW 40 423	4.5	Grey RAL 7035	50

CHARACTERISTICS: clip fixing.

Insulating screw caps



GW 44 623

Code	Description	Pack Carton
GW 44 623	Screwcap Ø25mm	10/100

APPLICATIONS: used to restore the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.

Design coupling cover for conduit and trunking entry for CDK enclosures and boards



GW 40 473

Code	For encl. /boards with rail	Fixing	Pack Carton
GW 40 473	12 Modules	Clip	20
GW 40 474	18 Modules	Clip	20

CHARACTERISTICS: covers with internal knockouts for trunking from 60x30mm to 200x60mm.

Insulated screw terminal block bipolar and unipolar for enclosures and boards



GW 40 412 B

Code	Pole 1 (mm²)	Pole 2 (mm²)	Suitable for	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A					
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	40 CDKe std. Germany	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	40 CDKe std. Germany	With screws and/or clip	10
GW 40 404	N (5x35) + (14x10)	E (5x35) + (14x10)	-	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20					
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	40 CDKe std. Germany	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	40 CDKe std. Germany	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20					
GW 40 408 U	N/E (2x16) + (7x10)	-	40 CDKe std. Germany	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	40 CDKe std. Germany	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	40 CDKe std. Germany	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: The GW40401, GW40408B and GW40408U terminal blocks can be installed on the Germany standard 40CDKe enclosures using the GW40413 adapter.

Adapter for screw terminal blocks

Code	Suitable for	Fastener to supports	Pack Carton
GW 40 413	40 CDKe std. Germany	With screws	20



GW 40 413

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block and pre-cut to allow installation also on enclosures with a 12 M modular step.
INSTALLATION: permits the installation of GW40401, GW40408B and GW40408U terminal blocks on Germany standard 40CDKe enclosures.

Internal horizontal divider for CDK boards

Code	For boards EN 50022 rail	Fixing	Pack Carton
GW 40 487	12 Modules	Clip	10/100
GW 40 488	18 Modules	Clip	10/100



GW 40 487

CHARACTERISTICS: sealing.

Blank lid panels - 1 module height for CDKe boards

Code	Suitable for	For boards EN 50022 rail	Colour	Pack Carton
GW 40 492	CDK enclosures and boards decorative (Surface-mounting)	12 Modules	Grey RAL 7035	20
GW 40 493	CDK enclosures and boards decorative (Surface-mounting)	18 Modules	Grey RAL 7035	20



GW 40 492

NOTES: for creating internal separation between circuits of differing voltages on several rows within a single casing.

Cylindrical security lock - for 40 CDKe enclosures

Code	Material	Pack Carton
GW 40 421	Insulation	10/100
GW 40 422	Pressure die-cast metal	1/10



GW 40 422

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

Interchangeable flange with quick-entry cable glands

Code	Entries for flanged	Pack Carton
GW 40 428	1 for cables Ø 16-29 mm 4 for cables Ø 11-20 m 8 f	1/20



GW 40 428

40 CDE - GERMAN STANDARD SURFACE-MOUNTING ENCLOSURES AND DISTRIBUTION BOARDS

40 CDe IP30 with terminal block



GW 43 022 S

Surface-mounting small distribution boards - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Pack Carton
GW 43 021 S	12	300x245x95	1
GW 43 022 S	24 (12X2)	300x370x95	1
GW 43 023 S	36 (12x3)	300x515x95	1
GW 43 024 S	48 (12x4)	300x640x95	1

Complementary items



GW 43 071 S

Blank doors for surface-mounting small distribution boards - White RAL 9016


Code	No. of modules EN 50022	Colour	Pack Carton
GW 43 071 S	12	White RAL 9016	1/4
GW 43 072 S	24 (12X2)	White RAL 9016	1/6
GW 43 073 S	36 (12x3)	White RAL 9016	1/2
GW 43 074 S	48 (12x4)	White RAL 9016	1/2



GW 43 112 S

Plastic frontal for surface-mounting small distribution boards

Code	No. of modules EN 50022	Pack Carton
GW 43 111 S	12	1
GW 43 112 S	24 (12X2)	1
GW 43 113 S	36 (12x3)	1
GW 43 114 S	48 (12x4)	1



GW 40 451

Bipolar terminal blocks with support for german standard surface-mounting small distribution boards

Code	Pole 1 (mm²)	Pole 2 (mm²)	For enclosures	Pack Carton
GW 40 451	N (1x25)+(3x16)+(14x10)	E (1x25)+(3x16)+(14x10)	12 modules	20
GW 40 452	N (2x25)+(6x16)+(16x10)	E (1x25)+(3x16)+(14x10)	24 modules	20
GW 40 453	N (2x25)+(6x16)+(22x10)	E (1x25)+(5x16)+(22x10)	36-48 modules	20

CHARACTERISTICS: clip fixing.



GW 43 042 S

Sealable closure

Code	Suitable for	Pack Carton
GW 43 042 S	Wall mounting	2/20



GW 40 463

Security lock

Code	For enclosures	Pack Carton
GW 40 463	40 CDE German standard surface-mounting	1/10

ACCESSORIES SUPPLIED: 2 keys.

NOTES: All the keys and relative locks with the same product code are identical.

4.5 Modules cover - Colour white

GW 40 467

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50

CHARACTERISTICS: clip fixing.

Circuit lettering strips



GW 43 122 S

Code	Dimensions (mm)	Pack Carton
GW 43 122 S	265x120	1/10

Circuit lettering strips



GW 43 044 S

Code	Dimensions (mm)	Pack Carton
GW 43 044 S	350x165	10/100

Enclosure door lock closing shutter



GW 43 052 S

Code	Description	Pack Carton
GW 43 052 S	Lock seat shutter	1/10

Screw for enclosure front



GW 43 040 S

Code	Description	Pack Carton
GW 43 040 S	Screws for enclosure front	100

40 CDE - GERMAN STANDARD FLUSH-MOUNTING DISTRIBUTION BOARDS

Metal door distribution boards - IP40



GW 40 153 N

Distribution boards for brick walls equipped with bipolar terminal blocks - RAL 9016

Code	No. of modules EN 50022	Pole 1 (mm²)	Pole 2 (mm²)	Dispersible power (W)	Pack Carton
GW 40 151 N	12+2	N (2x16)+(8x10)	PE (2x16)+(8x10)	60	1
GW 40 152 N	24+4 (12x2)	N (2x16)+(14x10)	PE (2x16)+(14x10)	80	1
GW 40 153 N	36+6 (12x3)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	90	1
GW 40 154 N	48+8 (12x4)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	100	1
GW 40 155 N	60+10 (12x5)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	120	1

Accessories supplied: positioning brackets, mortar guard, certification label, modules cover, terminal blocks.
Notes: extractable frame already installed.



GW 40 161 N

Distribution boards for plasterboard (GWT 850 °C) walls equipped with bipolar terminal blocks - RAL 9016

Code	No. of modules EN 50022	Pole 1 (mm²)	Pole 2 (mm²)	Dispersible power (W)	Pack Carton
GW 40 161 N	12+2	N (2x16)+(8x10)	PE (2x16)+(8x10)	60	1
GW 40 162 N	24+4 (12x2)	N (2x16)+(14x10)	PE (2x16)+(14x10)	80	1
GW 40 163 N	36+6 (12x3)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	90	1
GW 40 164 N	48+8 (12x4)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	100	1
GW 40 165 N	60+10 (12x5)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	120	1

Accessories supplied: installation brackets, plaster guard, certification label, modules cover, terminal blocks.
Notes: extractable frame already installed.

Metal door multimedia enclosure - IP40



GW 40 173 N

Multimedia enclosures for brick walls - RAL 9016

Code	No. line	Pack Carton
GW 40 173 N	3	1
GW 40 174 N	4	1

Accessories supplied: positioning brackets, mortar guard, 1x multimedia device bracket, 2x Schuko socket, 2x supports, 1x Dahlia plate
Notes: perforated mounting plates and patch panel already installed.



GW 40 178 N

Multimedia enclosures for plasterboard (GWT 850 °C) walls - RAL 9016

Code	No. line	Pack Carton
GW 40 178 N	3	1
GW 40 179 N	4	1

Accessories supplied: installation brackets, plaster guard, 1x multimedia device bracket, 2x Schuko socket, 2x supports, 1x Dahlia plate
Notes: perforated mounting plates and patch panel already installed.

Complementary items

Terminal blocks



GW 40 454 N

Code	Description	Pack Carton
GW 40 454 N	N+PE terminal block (2x16 mm² + 14x10 mm²)	1
GW 40 455 N	Terminal block N (7x16mm²)	1

Accessories

GW 40 467

Code	Description	Pack Carton
GW 40 461 N	Pair of brackets for horizontal coupling	1
GW 40 463 N	Safety lock for German standard flush-mounting enclosures	1
GW 40 467	Plastic module cover profile	50

40 CDE - FRENCH STANDARD MODULAR SURFACE-MOUNTING ENCLOSURES

Enclosures without door - IP30



GW 40 501

Enclosures equipped with multipolar terminal blocks - walls with knockout elements - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Phase terminal block (mm²)	Neutral terminal block (mm²)	Earth terminal block (mm²)	Pack Carton
GW 40 501	13	250x225x93.5	-	-	E(3x25)+(12x4)	8
GW 40 502	26 (13x2)	250x350x93.5	L(1x35)+(5x25)	N(1x35)+(5x25)	E(4x25)+(24x4)	4
GW 40 503	39 (13x3)	250x475x93.5	L(1x35)+(5x25)	N(1x35)+(5x25)	E(7x25)+(36x4)	4
GW 40 504	52 (13x4)	250x600x93.5	L(1x35)+(5x25)	N(1x35)+(5x25)	E(8x25)+(48x4)	2

ACCESSORIES SUPPLIED: terminal blocks, module masks, circuit labels with self-adhesive pictograms, instruction sheet.
NOTES: earth terminal blocks with Push-Wire technology.
To restore the double insulation, use the relative accessories (module masks and screwcaps)

Support bases for TARIF BLEU connecting switch



GW 40 512

Support bases without door for EDF connection switch - plumbable White RAL 9016

Code	Depth	Outer dim. LxHxD (mm)	Pack Carton
GW 40 511	40 mm	250x225x43.5	4
GW 40 512	55 mm	250x225x58.5	3

ACCESSORIES SUPPLIED: fixing screws for the circuit breaker, screwcaps for sealing.

Home VDI enclosure - Grade 1



GW 40 506

Home VDI enclosure grade 1 with 4 connectors RJ 45 and 4 TV-SAT outputs - White RAL 9016

Code	Outer dim. LxHxD (mm)	Pack Carton
GW 40 506	250x225x112	4

APPLICATIONS: allows to distribute Voice (telephone), Data (Internet) and Image (television) signals in every room of the house.
Complete and pre-equipped enclosure fitted with:
1 DTI RJ45 connection box with RC module integrated.
1 xDSL filter 4 outputs for phone et 1 output for modem.
1 TV-SAT splitter 5-2500 MHz 4 outputs.
1 Patch panel with 8 seats RJ45 "Keystone".
4 Connectors RJ45 Cat.5e UTP wiring without tool.
1 Kit of cords RJ45 for connection.
1 Earth terminal block.
1 Free space 100mm on DIN rail for the optical fiber DTI.
NOTES: complies with the minimum equipment required by the French standard NF C 15-100 and guide UTE C 90-483.



Accessories for expansion and wiring

Code	Description	Pack Carton
GW 40 596	Expansion kit with 2 RJ45 connectors cat. 5e	1/10
GW 40 597	Quadruple RJ45 cord	1/10

GW40596 is composed with:
2 Connectors RJ45 Cat.5e UTP wiring without tool:
1 Patch cord RJ45 - L = 30 cm.
NOTES: GW40597 cord RJ45 1 input/ 4 outputs RJ45 for delivering the phone on 4 connectors from only one input.

Complementary items




GW 40 516

Kit of modular spacers for subscriber enclosures, bases, containers and boards 50mm thick - Clip assembly - White RAL 9016

Code	Outer dim. LxHxD (mm)	Pack Carton
GW 40 516	250x225x50	8
GW 40 517	250x350x50	4
GW 40 518	250x475x50	4
GW 40 519	250x600x50	2

NOTE: code GW40516 is also suitable for the support bases and containers for services via cable (T.R.I.)



GW 40 546

2 pipe fittings for vertical and horizontal coupling of enclosures, bases and spacers

Code	Fixing type	Pack Carton
GW 40 546	Clip	20

APPLICATIONS: for creating combined compositions and subscriber boards.




GW 40 526

Back-mounting plates in insulating material for surface-mounting enclosures and spacer kit - Slide fixing on rail

Code	Outer dim. LxHxD (mm)	For enclosures	Pack Carton
GW 40 526	156x216x2	13 mod.- 1 row	8
GW 40 527	156x341x2	26 mod.- 2 rows	4
GW 40 528	156x466x2	39 mod.- 3 rows	4
GW 40 529	156x591x2	52 mod.- 4 rows	2

Isolated unipolar terminal blocks IP20 for French standard modular enclosures



GW 40 591

Code	Type	Cap colour	Connections no. x section (mm²)	Type of connection	For enclosures	Pack Carton
GW 40 591	Earth	Green	(3x25)+(12x4)	Push-Wire	13M-39M	20
GW 40 592	Earth	Green	(4x25)+(24x4)	Push-Wire	26M-39M-52M	20
GW 40 593	Phase	Black	(1x35)+(5x25)	With screw	26M-39M-52M	20
GW 40 594	Neutral	Blue	(1x35)+(5x25)	With screw	26M-39M-52M	20

CHARACTERISTICS: Terminal blocks for phase and neutral with In=100 A and Vn=450V.

Blank door with frame for finishing French Standard modular enclosures without door - White RAL 9016 - IP40



GW 40 531

Code	For enclosures	Pack Carton
GW 40 531	13 mod.- 1 row	8
GW 40 532	26 mod.- 2 rows	4
GW 40 533	39 mod.- 3 rows	4
GW 40 534	52 mod.- 4 rows	2

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks

Transparent smoked door with frame for finishing French Standard modular enclosures without door - White RAL 9016 - IP40



GW 40 536

Code	For enclosures	Pack Carton
GW 40 536	13 mod.- 1 row	8
GW 40 537	26 mod.- 2 rows	4
GW 40 538	39 mod.- 3 rows	4
GW 40 539	52 mod.- 4 rows	2

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks

Door with frame for finishing support bases - Clip fixing - White RAL 9016 - IP40



GW 40 542

Code	Outer dim. LxHxD (mm)	Door colour	Pack Carton
GW 40 541	250x225	White RAL 9016	4
GW 40 542	250x225	Smoked Transparent	4

CHARACTERISTICS: pre-arranged for housing the GW40422 cylinder security locks.

Cylindrical security lock - for 40 CDe (French standard) enclosures



GW 40 422

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

Screwcaps in insulating material



GW 44 622

Code	Description	For enclosures	Pack Carton
GW 44 622	Screwcap Ø16mm	GW42201	10/100

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.

Plastic module cover profile

GW 40 467

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50

CHARACTERISTICS: clip fixing.



40 CDE



Scan the QR Code and find out all the technical informations.

FRENCH STANDARD ENCLOSURES



Surface-mounting enclosures equipped with phase, neutral and earth terminal blocks, with an IP20 rating in accordance with French regulations. Earth terminal blocks with Push-Wire clamping. VDI enclosures complete the offer for the distribution of TV, internet and telephony signals.

GERMAN STANDARD ENCLOSURES



IP65-rated surface-mounting enclosures with top or bottom cable-entry flanges. IP30 surface- and IP40 flush-mounting versions with metal frame and door for masonry and plasterboard. Also available flush-mounting multimedia enclosures.

SPANISH STANDARD ENCLOSURES



Flush-mounted versions with smoked door and IP40 rating. The enclosures are designed to accommodate the ICP power limiter.

42 RV

Surface and flush-mounting watertight emergency enclosures

		EQUIPPED WITH ILLUMINABLE PUSH-BUTTON					
							
	Code	**GW 42 201**					
	Colour	**Red RAL 3000**					
 Hammer		GW 42 216					
 Replacement glass		GW 42 211					
 Watertight cylinder security lock		-					
 Contacts	NO	GW 74 201					
	NC	GW 74 202					
 Signalling unit	Code	GW 10 893	GW 30 943	GW 30 947	GW 30 958	GW 30 959	GW 30 960
	Voltage (V ac/dc)	12-24	230	110-230	12-24	110-230	48
	Power (W)	0.4	0.4	1			
	Light emission	White	Red	White	Green	Green	Green

PRE-ARRANGED WITH Ø 22 mm HOLE	WITH DIN RAIL				WITH BACKMOUNTING PLATE	FLUSH-MOUNTING ENCLOSURE WITH DIN RAIL	
							
GW 42 204	**GW 42 206** (4 modules)	**GW 42 202** (8 modules)	**GW 42 207** (4 modules)	**GW 42 208** (8 modules)	**GW 42 203**	**GW 42 231** (4 modules)	**GW 42 232** (4 modules)
Red RAL 3000	**Red RAL 3000**	**Red RAL 3000**	**Grey RAL 7035**	**Grey RAL 7035**	**Red RAL 3000**	**Red RAL 3000**	**Grey RAL 7035**
GW 42 216	GW 42 216	GW 42 216	GW 42 216	GW 42 216	GW 42 216	GW 42 216	GW 42 216
GW 42 213	GW 42 213	GW 42 212	GW 42 213	GW 42 212	GW 42 212	GW 42 214	GW 42 214
GW 48 644	GW 48 644	GW 48 644	GW 48 644	GW 48 644	GW 48 644	GW 48 644	GW 48 644
-	-				-	-	-
-	-				-	-	-

42 RV

Surface and flush-mounting watertight emergency enclosures

IP55 watertight enclosures, Red RAL 3000, available in 5 versions: with backlit push button; can be equipped with 22 mm dia. stop button or with rail coupling, the latter being available in Grey RAL 7035. The best seller is the GW42201, equipped with 1 NO contact and 1 NC contact and expandable up to 4 contacts, supplied with 1 long automatically operated push-button when glass is broken or short button for manual operation.



42 RV - WATERTIGHT ENCLOSURES FOR EMERGENCY MANOEUVRES - IP55



IP 55

GWT 650°C



CLASS II

EN 61140

Equipment with illuminable push-button



GW 42 201

Watertight enclosure for emergency systems, equipped with illuminated push-button and 2 contacts 1NO+1NC that can be expanded up to 4 contacts - Pre-arrangement for use of green LED to indicate the good condition of the emergency circuit

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Colour	No. of contacts that can be installed	Pack Carton
GW 42 201	120x120x50	Red RAL 3000	4	1/10

CHARACTERISTICS: can be mounted on flush-mounting box GW24403. Contact-holder flange with 4 seats.
ACCESSORIES SUPPLIED: substitute button key for the possible configuration of manual or automatic activation when the glass is broken, self-adhesive pictograms "Break the glass" and "Press the button key", screwcaps for double insulation, screws and accessories for plumbing the front, 1 NO contact and 1 NC contact.
Sicur Push breakable glass.
NOTES: substitute NO contacts: GW74201, NC: GW74202: lamps for push-button backlighting: GW10893 12-24 V~/-, GW30943 230 V~/-; green LEDs for signalling the integrity of the emergency circuit: GW30958 for 12 to 24 V~/-, GW30959 for 110 to 230 V~/-, GW30960 for 48 V~/-;
To restore the double insulation use the relative screwcaps supplied.
Pre-arranged for installation of 4 contacts type NO or NC.

Fitted with hole Ø 22 mm



GW 42 204

Watertight enclosure for emergency systems fitted with hole Ø 22mm

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Colour	Pack Carton
GW 42 204	108x180x100	Red RAL 3000	1/10

ACCESSORIES SUPPLIED: Door fitted with lock with 2 keys, self adhesive pictogram "Break glass" and screwcaps for double insulation.
Sicur Push breakable glass.
To restore the double insulation, use the relative accessories supplied (module masks and screwcaps) or the brackets for surface-mounting (GW44621).
NOTES: compatible with momentary push-buttons, selectors and indicators Ø 22 mm of the 74 PS series.

With DIN rail



GW 42 202

Watertight enclosures for emergency use and special applications with rail DIN

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
Colour: Red RAL 3000				
GW 42 206	4	108x180x100	12	1/10
GW 42 202	8	180x180x100	18	1/10
Colour: Grey RAL 7035				
GW 42 207	4	108x180x100	12	1/10
GW 42 208	8	180x180x100	18	1/10

ACCESSORIES SUPPLIED: door fitted with lock with 2 keys, self adhesive pictogram "Break glass", circuit label and screwcaps for double insulation. Sicur Push breakable glass.
GW44207 pre-arranged also for the installation of momentary push-buttons, mushroom-head push-buttons, selectors and indicators ø 22 mm of the 74PS series.
NOTES: Dispersible power calculated according to CEI 23-49.
To restore the double insulation use the relative accessories supplied (module mask and screwcaps) or brackets for surface mounting GW44621.

With back-mounting plate



GW 42 203

Watertight enclosure for emergency use and special applications with galvanised metal back mounting plate

Code	Outer dim. LxHxD (mm)	Colour	Pack Carton
GW 42 203	180x180x100	Red RAL 3000	1/10

ACCESSORIES SUPPLIED: Door fitted with lock with 2 keys, self adhesive pictogram "Break glass" and screwcaps for double insulation.
"Sicur Push" breakable glass.
To restore the double insulation use the relative accessories supplied (module mask and screwcaps) or brackets for surface mounting GW44621

Flush-mounting enclosure with DIN rail



GW 42 232

Watertight flush-mounting enclosures for emergencies and special applications with rail DIN

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Colour	Pack Carton
GW 42 231	4	145x200x70	12	Red RAL 3000	1/10
GW 42 232	4	145x200x70	12	Grey RAL 7035	1/10

ACCESSORIES SUPPLIED: door equipped with security lock with 1 key, self-adhesive pictogram "Break the glass", user label.
"Sicur Push" breakable glass.
NOTES: if the flush-mounting box is not embedded in line with the wall, use the screw kit plus the spacers GW48645.
dispersible power calculated according to IEC 60670-24.
To restore the double insulation use the relative accessories supplied (module masks and screwcaps)

PLATES FOR LIFTS / EMERGENCY

Wired plates for lift and emergency



GW 32 450

Self-supporting wired plates for lift/emergency with illuminable button switch triangle key and breakable glass - IP40

Code	Output contacts	Colour	Suitable for	Pack Carton
GW 32 450	1 NO + 1 NC 10A (AC1) / 6A (AC15) 380 V ac	White	Lift	1/10
GW 32 451	1 NO + 1 NC	Red	Emergency	1/10

The articles are supplied with an 11mm button key already assembled, without a lamp. They use the GW30943 230V-/~ signalling units.
CHARACTERISTICS: the plates are suitable for the GW40422 security lock, available as an accessory.
For flush-mounting box GW24403; for surface-mounting box GW32431, GW32432;
ACCESSORIES SUPPLIED: accessory button key, 17mm high, to operate the contacts when glass is broken.

COMPLEMENTARY ITEMS

Glass breaker



GW 42 216

Glass breaker with universal fixing support

Code	Colour	Support dimension (mm)	Pack Carton
GW 42 216	Toner black	70x60	1/10

CHARACTERISTICS: the hammer is joined to the base with a fine chain, so it can not be lost.


Spare glass



GW 42 212

Spare Sicur Push glass for watertight enclosures for emergencies

Code	For enclosures	Pack Carton
GW 42 211	GW42201	1/10
GW 42 213	GW42204, GW42206, GW42207	1/10
GW 42 212	GW42202, GW42203, GW42208	1/10
GW 42 214	GW42231, GW42232	1/10



GW 32 457

Spare breakable glass for plates for lifts/emergencies

Code	Suitable for	Pack Carton
GW 32 457	GW32450, GW32451, GW32452, GW32453	1/10

Accessories and spare parts



Miniature lamps with wired lead

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 30 943	230 V ac	0.4 W	Fluorescent	Red	50
GW 10 893	12-24V ac/dc	0.4 W	LED	White	50
GW 30 947	110 / 230V ac	0.6 W	LED	White	50

Signalling unit for integrity of emergency circuit - With LEDs

Code	Lamp voltage	Lamp	Light emitted	Pack Carton
GW 30 958	12-24V ac/dc	LED	Green	10
GW 30 959	110-230V ac/dc	LED	Green	10
GW 30 960	48V ac/dc	LED	Green	10



GW 30 958

Contacts - Ith 10A - 240V ac

Code	Type	Category of use 240V ac15	Category of use 240V dc13	Colour	For enclosure	Pack Carton
GW 74 201	1 NO	3 A	0.27 A	Green	GW42201	10/60
GW 74 202	1 NC	3 A	0.27 A	Red	GW42201	10/60

CHARACTERISTICS: GW74202, suitable for opening the contact also in the event of it slightly sticking, in conformity with the EN 60947-5-1 standard.
Clip assembly on the contact-holder flanges. Contacts compatible with emergency control unit GW42201.



Cylindrical security lock - suitable for plates used in lifts/emergencies

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.



GW 40 422

Watertight cylindrical security lock

Code	For enclosures	Material	Pack Carton
GW 48 644	48 PTC and 42 RV range	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.



GW 48 644




GW 48 645

Kit containing 4 long self-threading screws with spacers for fixing lids and fronts

Code	Screw dimension (mm)	Spacer thickness (mm)	Pack Carton
GW 48 645	Ø 4x45	Max 10 mm reducible	1/100

CHARACTERISTICS: the kit can also be used for the following flush-mounting ranges: CD/CDK (starting from 6 modules), 48 CM and 42 RV.



GW 44 621

Wall fixing bracket, complete with self-tapping screws

Code	Suitable for	Pack Carton
GW 44 621	Enclosures 42 RV wall range	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.




GW 44 622

Screwcaps in insulating material

Code	Description	For enclosures	Pack Carton
GW 44 622	Screwcap Ø16mm	GW42201	10/100
GW 44 623	Screwcap Ø25mm	from GW42202 to GW42208	10/100


APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.



GW 40 423

4.5 Modules cover - Colour white

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 423	4.5	Grey RAL 7035	50



42 RV



Scan the QR Code and find out all the technical informations.

ENCLOSURES FOR EMERGENCY SYSTEMS



The GW42201 emergency-system enclosure is the ideal product for handling emergency systems. It can be fitted with up to four NO and NC contacts, and it also offers the possibility of signalling emergency circuit integrity, thanks to the green LED.

FUNCTIONALITY AND FLEXIBILITY IN A SINGLE ITEM



The GW42201 enclosure can be fitted with a short or long push button for voluntary movement or intrinsically safe operation, and has a back panel flange that expands the number of contacts installable up to four, thus increasing the configurable solutions.



MAXIMUM SECURITY



All the enclosures have a high IP55 protection rating and thanks to the emergency hammer (available as accessory), breakable panel and halogen-free materials, they are suitable for use even in areas open to the public.

44 CE

Technopolymer surface-mounting watertight junction boxes

Material		**Technopolymer GW PLAST 75**							
Heat resistance		**Thermo-pressure with ball: 85°C**							
Fire resistance		**Glow Wire Test: 650°C - UL94: HB**							
Applications		**For ordinary junctions**							
Degree of protection		**IP44**	**IP55**			**IP56**			
Walls		**with quick entry cable glands**	**with quick entry cable glands**		**smooth**	**smooth**			
Depth of back-mounting box		**standard**	**standard**		**standard**	**standard**		**high capacity**	
Cover		**blank plain**	**1/4 turn screws blank plain**	**blank plain**	**1/4 turn screws blank plain**	**blank plain**	**deep blank**	**blank plain**	**transparent plain**
INTERNAL DIMENSIONS OF BOX BASE LxH (mm)	**Dimensioni (mm)**								
	Ø 65	**GW 44 001**	-	-	-	-	-	-	-
	Ø 80	**GW 44 002**	-	-	-	-	-	-	-
	80x80	**GW 44 003**	-	-	-	-	-	-	-
	100x100	-	**GW 44 024**	**GW 44 004**	**GW 44 234**	**GW 44 204**	**GW 44 214**	**GW 44 114**	-
	120x80	-	-	**GW 44 005**	-	**GW 44 205**	**GW 44 215**	-	-
	150x110	-	**GW 44 026**	**GW 44 006**	**GW 44 236**	**GW 44 206**	**GW 44 216**	-	-
	190x140	-	-	**GW 44 007**	-	**GW 44 207**	**GW 44 217**	**GW 44 117**	**GW 44 137**
	240x190	-	-	**GW 44 008**	-	**GW 44 208**	**GW 44 218**	**GW 44 118**	**GW 44 138**
	300x220	-	-	**GW 44 009**	-	**GW 44 209**	**GW 44 219**	**GW 44 119**	**GW 44 139**
	380x300	-	-	**GW 44 010**	-	**GW 44 210**	**GW 44 220**	**GW 44 120**	**GW 44 140**
	460x380	-	-	**GW 44 011**	-	**GW 44 211**	**GW 44 221**	-	-

(*) Versions with red back-mounting box and grey cover
(**) Versions CSA approved (in accordance to the UL50 Standard)
(***) UL94: V0 only back-mounting box and cover
In green: insulation voltage Ui=1000V according to EN 60670-1 and EN 60670-22. For photovoltaic applications use the wall fixing brackets , code GW 44 621.
In bold: Halogen-Free material versions.

Technopolymer GW PLAST 75					Technopolymer GW PLAST 120			
Thermo-pressure with ball: 85°C					Thermo-pressure with ball: 110°C			
Glow Wire Test: 960 °C - UL94: V0 (***)					Glow Wire Test: 650°C - UL94: HB			
For special uses (e.g. raised floors, suspended ceilings...)					For industrial uses			
IP44	IP55		IP56		IP56			
with quick entry cable glands	with quick entry cable glands		smooth		smooth			
standard	standard		standard		standard			
blank plain	1/4 turn screws blank plain	blank plain	blank plain	deep blank	blank plain	deep blank	transparent plain	transparent deep
								
GW 44 051 GW 44 051 R (*)	-	-	-	-	-	-	-	-
GW 44 052	-	-	-	-	-	-	-	-
GW 44 053 GW 44 053 R (*)	-	-	-	-	-	-	-	-
-	GW 44 054 GW 44 054 R (*)	-	GW 44 274	GW 44 254	**GW 44 404**	**GW 44 414**	-	-
-	-	GW 44 055	GW 44 275	GW 44 255	**GW 44 405**	**GW 44 415**	-	-
-	GW 44 056 GW 44 056 R (*)		GW 44 276 GW 44 276 C (**)	GW 44 256	**GW 44 406**	**GW 44 416**	**GW 44 426**	**GW 44 436**
-	-	GW 44 057	GW 44 277 GW 44 277 C (**)	GW 44 257	**GW 44 407**	**GW 44 417**	**GW 44 427**	**GW 44 437**
-	-	GW 44 058	GW 44 278	GW 44 258	**GW 44 408**	**GW 44 418**	**GW 44 428**	**GW 44 438**
-	-	GW 44 059	GW 44 279	GW 44 259	**GW 44 409**	**GW 44 419**	**GW 44 429**	**GW 44 439**
-	-	GW 44 060	GW 44 280	GW 44 260	**GW 44 410**	**GW 44 420**	**GW 44 430**	**GW 44 440**
-	-	GW 44 061	GW 44 281	GW 44 261	**GW 44 411**	**GW 44 421**	**GW 44 431**	**GW 44 441**

Accessories

ACCESSORIES FOR COUPLING AND JUNCTION SURFACE-MOUNTING BOXES

			Code	INTERNAL DIMENSIONS OF BOX BASE (mm)										
				Ø 65	Ø 80	80x80	100x100	120x80	150x110	190x140	240x190	300x220	380x300	460x380
	EQUIPOTENTIAL SINGLE-POLE TERMINAL BLOCKS		GW 44 704	●	●	●	●	●	●	●	●	●	●	●
			GW 44 706	●	●	●	●	●	●	●	●	●	●	●
			GW 44 708		●	●	●	●	●	●	●	●	●	●
			GW 44 671	●	●	●	●	●	●	●	●	●	●	●
			GW 44 672		●	●	●	●	●	●	●	●	●	●
			GW 44 673				●		●	●	●	●	●	●
			GW 44 674											
			GW 44 675						●	●	●	●	●	●
			GW 44 676						●	●	●	●	●	●
	MULTIPLE TERMINAL BLOCKS		GW 44 606	●	●	●	●	●						
			GW 44 607	●	●	●	●	●						
			GW 44 608	●	●	●	●	●						
	MULTIPLE FEEDTHROUGH TERMINAL BLOCKS		GW 44 609		●	●	●	●	●	●	●	●	●	●
			GW 44 610											
			GW 44 611											
			GW 44 610 C (*)				●	●	●	●	●	●	●	●
			GW 44 612											
			GW 44 613 GW 44 614							●	●	●	●	●
	BACK-MOUNTING PLATES	Galvanised sheet metal 	GW 44 615							●	● (1)			
			GW 44 616								●	● (2)		
			GW 44 617									●	● (3)	
			GW 44 618										●	
			GW 44 619											●
		Insulating material 	GW 44 625							●	● (1)			
			GW 44 626								●	● (2)		
			GW 44 627									●	● (3)	
			GW 44 628										●	
			GW 44 629											●
	COUPL.		GW 44 620				●			●	●	●	●	●
	SCREW CAPS		GW 44 622	2	2	2	4	4	4	4	4	4		
			GW 44 623										6	supplied
	BRACKET		GW 44 621							6	8	12	16	8
	CABLE GLANDS		GW 50 428											
			GW 50 429	4	4	6								
			GW 50 430				6	6	10					
			GW 50 431							10	12			
			GW 50 432									12	12	14

(*) CSA certified version (in according with UL50 standards).
(1) Only for GW 44 118 and GW 44 138.
(2) Only for GW 44 119 and GW 44 139.
(3) Only for GW 44 120 and GW 44 140.
NOTE: quick entry cable glands with exception of GW 50 428

44 CE

Technopolymer surface-mounting watertight junction boxes

The 44 CE junction boxes range consists of 3 families made of different technopolymers (two of which are Halogen Free) and available in 11 sizes with an ordinary or high-capacity base, high or low lids, blank or transparent lids, smooth walls or with quick-entry cable glands.



SURFACE-MOUNTING BOXES IN GWPLAST 75 - GWT 650°C - FOR ORDINARY JUNCTIONS



IK 08

GWT 650°C





Walls with quick entry cable glands - IP44 and IP55

Junction boxes with plain press-on lid - IP44 - Grey RAL 7035



GW 44 001

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 44 001	Ø 65x35	4 / 23	5/280
GW 44 002	Ø 80x40	4 / 23	5/135
GW 44 003	80x80x40	6 / 23	5/90

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.
CHARACTERISTICS: IP 44 boxes with IK07 impact resistance.
The external part of the junction box bottom is provided of central threaded seat. Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 mm. pressure closing lid.

Junction boxes with plain quick fixing lid - IP55 - Grey RAL 7035



GW 44 024

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Pack Carton
GW 44 024	100x100x50	6 / 29	4 insul. a 1/4 turn, sealable	66
GW 44 026	150x110x70	10 / 29	4 insul. a 1/4 turn, sealable	40

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.
CHARACTERISTICS: Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 and 25 mm. the box bottom has 2 windows of dimensions 6 x 4 mm that allows the box mounting of the box, using the cables ties, to mesh wire cables trays, perforated cables trays, pole supports, etc.

Junction boxes with plain screwed lid - IP55 - Grey RAL 7035



GW 44 007

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Pack Carton
GW 44 004	100x100x50	6 / 29	4 - Stainless steel	66
GW 44 005	120x80x50	6 / 29	4 - Stainless steel	66
GW 44 006	150x110x70	10 / 29	4 - Stainless steel	40
GW 44 007	190x140x70	10 / 37	4 insul. sealable hinged	24
GW 44 008	240x190x90	12 / 37	4 insul. sealable hinged	12
GW 44 009	300x220x120	12 / 48	4 insul. sealable hinged	6
GW 44 010	380x300x120	12 / 48	4 insul. sealable hinged	4
GW 44 011	460x380x120	14 / 48	6 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44011 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.
CHARACTERISTICS:
quick entry cable glands, suitable for cables with Ø from 4 to 14mm.
For GW44007 and GW44008 quick entry cable glands suitable for conduits ø 16, 20, 25 and 32mm.
For GW44007, GW4408 quick entry cable glands suitable for conduits ø 16, 20, 25 and 32 mm.
For GW44009, GW44010, GW44011 quick entry cable glands suitable for conduits ø 16, 20, 25, 32 and 40mm.

Smooth walls - IP55 and IP56

Junction boxes with plain quick fixing lid - IP55 - Grey RAL 7035



GW 44 234

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 234	100x100x50	29 mm	4 insul. a 1/4 turn, sealable	105
GW 44 236	150x110x70	29 mm	4 insul. a 1/4 turn, sealable	50

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.

Junction boxes with plain screwed lid - IP56 - Grey RAL 7035



GW 44 207

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 204	100x100x50	29 mm	4 - Stainless steel	105
GW 44 205	120x80x50	29 mm	4 - Stainless steel	91
GW 44 206	150x110x70	29 mm	4 - Stainless steel	50
GW 44 207	190x140x70	37 mm	4 insul. sealable hinged	30
GW 44 208	240x190x90	37 mm	4 insul. sealable hinged	14
GW 44 209	300x220x120	48 mm	4 insul. sealable hinged	6
GW 44 210	380x300x120	48 mm	4 insul. sealable hinged	4
GW 44 211	460x380x120	48 mm	6 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44211 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.

Junction boxes with deep screwed lid - IP56 - Grey RAL 7035



GW 44 217

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 214	100x100x120	29 mm	4 - Stainless steel	45
GW 44 215	120x80x120	29 mm	4 - Stainless steel	55
GW 44 216	150x110x140	29 mm	4 - Stainless steel	24
GW 44 217	190x140x140	37 mm	4 insul. sealable hinged	12
GW 44 218	240x190x160	37 mm	4 insul. sealable hinged	12
GW 44 219	300x220x180	48 mm	4 insul. sealable hinged	7
GW 44 220	380x300x180	48 mm	4 insul. sealable hinged	3
GW 44 221	460x380x180	48 mm	6 insul. sealable hinged	2

ACCESSORIES SUPPLIED: GW44221 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.

High capacity bottom with smooth walls - IP56

Junction boxes with high capacity bottom and plain screwed lid - Grey RAL 7035



GW 44 117

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Effective height of bottom	Lid screws (no. and type)	Pack Carton
GW 44 114	100x100x80	48 mm	63 mm	4 - Stainless steel	1/45
GW 44 117	190x140x110	54 mm	83 mm	4 insul. sealable hinged	1/16
GW 44 118	240x190x130	54 mm	100 mm	4 insul. sealable hinged	1/12
GW 44 119	300x220x170	54 mm	119 mm	4 insul. sealable hinged	1/7
GW 44 120	380x300x170	54 mm	119 mm	4 insul. sealable hinged	1/3

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm. For all box/back-mounting plate combinations, refer to the summary.
APPLICATIONS: used to connect conduits up to Ø 40mm (for the 100x100x80mm version) and up to Ø 50mm (for the other sizes).
CHARACTERISTICS: for applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.

Junction boxes with high capacity bottom and transparent plain screwed lid - Grey RAL 7035



GW 44 137

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Effective height of bottom	Lid screws (no. and type)	Pack Carton
GW 44 137	190x140x110	54 mm	83 mm	4 insul. sealable hinged	1/16
GW 44 138	240x190x130	54 mm	100 mm	4 insul. sealable hinged	1/12
GW 44 139	300x220x170	54 mm	119 mm	4 insul. sealable hinged	1/7
GW 44 140	380x300x170	54 mm	119 mm	4 insul. sealable hinged	1/3

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm. For all box/back-mounting plate combinations, refer to the summary.
APPLICATIONS: used to connect conduits up to Ø 50mm.
CHARACTERISTICS: for applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.

SURFACE-MOUNTING BOXES IN GWPLAST 75 - GWT 960°C - FOR SPECIAL USES



IK 08

GWT 960°C



CLASS II

EN 61140

Walls with quick entry cable glands - IP44 and IP55

Junction boxes with plain press-on lid - IP44 - Grey RAL 7035



GW 44 051

GWT 960°C

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 44 051	Ø 65x35	4 / 23	5/280
GW 44 052	Ø 80x40	4 / 23	5/135
GW 44 053	80x80x40	6 / 23	5/90

CHARACTERISTICS: casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
IK07 impact resistance.
The external part of the junction box bottom is provided of central threaded seat.
Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 mm.
pressure closing lid.
APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.
Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 mm.

Junction boxes with plain quick fixing lid - IP55 - Grey RAL 7035



GW 44 054

GWT 960°C

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Pack Carton
GW 44 054	100x100x50	6 / 29	4 insul. a 1/4 turn, sealable	66
GW 44 056	150x110x70	10 / 29	4 insul. a 1/4 turn, sealable	40

CHARACTERISTICS: casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1. Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 and 25 mm. the box bottom has 2 windows of dimensions 6 x 4 mm that allows the box mounting of the box, using the cables ties, to mesh wire cables trays, perforated cables trays, pole supports, etc.
APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.

Junction boxes with plain press-on lid - IP44 - Box base Red RAL 3000, lid and cable gland Grey RAL 7035



GW 44 051 R

GWT
960°C

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 44 051 R	Ø 65x35	4 / 23	5/280
GW 44 053 R	80x80x40	6 / 23	5/90

CHARACTERISTICS: Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1. thermo-pressure with ball = 75° C.
The external part of the junction box bottom is provided of central threaded seat.
Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 mm.
pressure closing lid.
APPLICATION: Ideal for safety circuits (door release, illumination, signal) and for ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.
Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 mm.

Junction boxes with plain quick fixing lid - IP55 - Box base Red RAL 3000, lid and cable gland Grey RAL 7035



GW 44 054 R

GWT
960°C

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Pack Carton
GW 44 054 R	100x100x50	6 / 29	4 insul. a 1/4 turn, sealable	66
GW 44 056 R	150x110x70	10 / 29	4 insul. a 1/4 turn, sealable	40

CHARACTERISTICS: Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1. thermo-pressure with ball = 75° C. Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 and 25 mm. the box bottom has 2 windows of dimensions 6 x 4 mm that allows the box mounting of the box, using the cables ties, to mesh wire cables trays, perforated cables trays, pole supports, etc.
APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps.
Quick entry cable glands for cables with Ø from 4 to 14 mm and tubes with Ø 16, 20 and 25 mm.

44 CE

Junction boxes with plain screwed lid - IP55 - Grey RAL 7035



GW 44 057

GWT
960°C

Code	Internal dim. LxHxD (mm)	Entries No. holes / Ø	Lid screws (no. and type)	Pack Carton
GW 44 055	120x80x50	6 / 29	4 - Stainless steel	66
GW 44 057	190x140x70	10 / 37	4 insul. sealable hinged	24
GW 44 058	240x190x90	12 / 37	4 insul. sealable hinged	12
GW 44 059	300x220x120	12 / 48	4 insul. sealable hinged	6
GW 44 060	380x300x120	12 / 48	4 insul. sealable hinged	4
GW 44 061	460x380x120	14 / 48	4 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44061 screwcaps for double insulation.

CHARACTERISTICS: Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.

APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.

For GW44055 quick entry cable glands, suitable for cables with Ø from 4 to 14mm and conduits Ø 16, 20 and 25mm.

For GW44057 and GW44058 quick entry cable glands, suitable for cables with Ø from 4 to 14mm and conduits Ø 16, 20, 25 and 32mm.

For GW44059, GW44060 and GW44061 quick entry cable glands, suitable for cables with Ø from 4 to 14mm and conduits Ø 16, 20, 25, 32 and 40mm.

Smooth walls - IP56

Junction boxes with plain screwed lid - IP56 - Grey RAL 7035



GW 44 277

GWT
960°C

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 274	100x100x50	29 mm	4 - Stainless steel	105
GW 44 275	120x80x50	29 mm	4 - Stainless steel	91
GW 44 276	150x110x70	29 mm	4 - Stainless steel	50
GW 44 276 C	150x110x70	29 mm	4 - Stainless steel	50
GW 44 277	190x140x70	37 mm	4 insul. sealable hinged	30
GW 44 277 C	190x140x70	37 mm	4 insul. sealable hinged	30
GW 44 278	240x190x90	37 mm	4 insul. sealable hinged	14
GW 44 279	300x220x120	48 mm	4 insul. sealable hinged	6
GW 44 280	380x300x120	48 mm	4 insul. sealable hinged	4
GW 44 281	460x380x120	48 mm	6 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44281 screwcaps for double insulation.

CHARACTERISTICS: for applications in a photovoltaic environment, use the surface-mounting brackets - code GW44621. Type H casing in accordance with EN60670-1, and type Ha in accordance with IEC60670-1. For junction boxes GW44276C and GW44277C, thermo-pressure with ball TP = 75°C according to EN 60670-1 and IEC 60670-1. Maximum installation temperature +50°C.

APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190 x 140mm. Junction boxes GW44276C and GW44277C certified CSA (in accordance with UL50). To be used with multipolar terminal blocks 5 x 6mm² GW44610C.

Junction boxes with deep screwed lid - IP56 - Grey RAL 7035



GW 44 260

GWT
960°C

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 254	100x100x120	29 mm	4 - Stainless steel	45
GW 44 255	120x80x120	29 mm	4 - Stainless steel	55
GW 44 256	150x110x140	29 mm	4 - Stainless steel	24
GW 44 257	190x140x140	37 mm	4 insul. sealable hinged	16
GW 44 258	240x190x160	37 mm	4 insul. sealable hinged	12
GW 44 259	300x220x180	48 mm	4 insul. sealable hinged	7
GW 44 260	380x300x180	48 mm	4 insul. sealable hinged	3
GW 44 261	460x380x180	48 mm	6 insul. sealable hinged	2

ACCESSORIES SUPPLIED: GW44261 screwcaps for double insulation.

CHARACTERISTICS: for applications in the photovoltaic environment, use the wall fixing brackets - code GW44621. Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.

APPLICATIONS: ideal for applications requiring a minimum GWT of 850°C in compliance with standards EN 60670 and IEC 60670, such as floating floors and suspended ceilings.

NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.

SURFACE-MOUNTING BOXES IN GWPLAST 120 - GWT 650°C - FOR INDUSTRIAL USES



IK 08

GWT 650°C





Blank lid - IP56

Boxes with smooth walls for junctions and for electric and electronic equipment - Plain screwed lid - Grey RAL 7035



GW 44 407

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 404	100x100x50	29 mm	4 - Stainless steel	108
GW 44 405	120x80x50	29 mm	4 - Stainless steel	108
GW 44 406	150x110x70	29 mm	4 - Stainless steel	50
GW 44 407	190x140x70	37 mm	4 insul. sealable hinged	32
GW 44 408	240x190x90	37 mm	4 insul. sealable hinged	14
GW 44 409	300x220x120	48 mm	4 insul. sealable hinged	6
GW 44 410	380x300x120	48 mm	4 insul. sealable hinged	4
GW 44 411	460x380x120	48 mm	6 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44411 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.
CHARACTERISTICS: Ui=1000V in accordance with EN 60670-1 and EN 60670-22.
For applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.

Boxes with smooth walls for junctions and for electric and electronic equipment - Deep screwed lid - Grey RAL 7035



GW 44 417

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 414	100x100x120	29 mm	4 - Stainless steel	45
GW 44 415	120x80x120	29 mm	4 - Stainless steel	55
GW 44 416	150x110x140	29 mm	4 - Stainless steel	24
GW 44 417	190x140x140	37 mm	4 insul. sealable hinged	16
GW 44 418	240x190x160	37 mm	4 insul. sealable hinged	12
GW 44 419	300x220x180	48 mm	4 insul. sealable hinged	7
GW 44 420	380x300x180	48 mm	4 insul. sealable hinged	3
GW 44 421	460x380x180	48 mm	6 insul. sealable hinged	2

ACCESSORIES SUPPLIED: GW44421 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.
CHARACTERISTICS: Ui=1000V in accordance with EN 60670-1 and EN 60670-22.
For applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.

Transparent lid - IP56



GW 44 427

Boxes with smooth walls for junctions and for electric and electronic equipment - Plain screwed lid - Grey RAL 7035

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 426	150x110x70	29 mm	4 - Stainless steel	50
GW 44 427	190x140x70	37 mm	4 insul. sealable hinged	32
GW 44 428	240x190x90	37 mm	4 insul. sealable hinged	14
GW 44 429	300x220x120	48 mm	4 insul. sealable hinged	6
GW 44 430	380x300x120	48 mm	4 insul. sealable hinged	4
GW 44 431	460x380x120	48 mm	6 insul. sealable hinged	3

ACCESSORIES SUPPLIED: GW44431 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.
CHARACTERISTICS: Ui=1000V in accordance with EN 60670-1 and EN 60670-22.
For applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.



GW 44 437

Boxes with smooth walls for junctions and for electric and electronic equipment - Deep screwed lid - Grey RAL 7035

Code	Internal dim. LxHxD (mm)	Max Ø holes possible	Lid screws (no. and type)	Pack Carton
GW 44 436	150x110x140	29 mm	4 - Stainless steel	24
GW 44 437	190x140x140	37 mm	4 insul. sealable hinged	16
GW 44 438	240x190x160	37 mm	4 insul. sealable hinged	12
GW 44 439	300x220x180	48 mm	4 insul. sealable hinged	7
GW 44 440	380x300x180	48 mm	4 insul. sealable hinged	3
GW 44 441	460x380x180	48 mm	6 insul. sealable hinged	2

ACCESSORIES SUPPLIED: GW44441 screwcaps for double insulation.
NOTES: to restore the double insulation and original IP degree of protection of the boxes, use the isolating screwcaps or the surface-mounting fixing brackets for boxes measuring at least 190x140mm.
CHARACTERISTICS: Ui=1000V in accordance with EN 60670-1 and EN 60670-22.
For applications in the photovoltaic environment, use the wall fixing brackets - code GW44621.

COMPLEMENTARY ITEMS

Back-mounting plates



GW 44 615

Back-mounting plate in galvanised steel with self-tapping fixing screws

Code	For boxes centre distance BxH (mm)	Pack Carton
GW 44 615	190x140	20
GW 44 616	240x190	20
GW 44 617	300x220	20
GW 44 618	380x300	5
GW 44 619	460x380	5

NOTES: GW44615 also fitted for high capacity boxes GW44118 and GW44138.
GW44616 also fitted for high capacity boxes GW44119 and GW44139.
GW44617 also fitted for high capacity boxes GW44120 and GW44140.



GW 44 625

Back-mounting plate in insulated material with self-tapping fixing screws

Code	For boxes centre distance BxH (mm)	Pack Carton
GW 44 625	190x140	20
GW 44 626	240x190	20
GW 44 627	300x220	20
GW 44 628	380x300	4
GW 44 629	460x380	5

NOTES: GW44625 also fitted for high capacity boxes GW44118 and GW44138.
GW44626 also fitted for high capacity boxes GW44119 and GW44139.
GW44627 also fitted for high capacity boxes GW44120 and GW44140.

Installation and coupling elements

Insulating screw caps




GW 44 622

Code	Description	Pack Carton
GW 44 622	Screwcap Ø16mm	10/100
GW 44 623	Screwcap Ø25mm	10/100

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.

Wall fixing bracket, complete with self-tapping screws



GW 44 621

Code	For boxes centre distance BxH (mm)	Pack Carton
GW 44 621	300x220 380x300 460x380 190x140 240x190	40/480

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.
ACCESSORIES SUPPLIED: 2 fixing screws.

Watertight coupler - IP56



GW 44 620

Code	For boxes centre distance BxH (mm)	For holes Ø (mm)	Ø ring nut (mm)	Internal Ø (mm)	Length (mm)	Pack Carton
GW 44 620	300x220 380x300 460x380	48	58.5	39	37.5	10/160

Cable glands in flexible polymer - Grey RAL 7035 - IP55



GW 50 430

Code	For ext. conduits max (mm)	Mounting hole Ø (mm)	Glow Wire Test	Pack Carton
GW 50 428	16	19	960 °C	100/1000
GW 50 429	20	23	960 °C	100/1000
GW 50 430	25	29	960 °C	100/1000
GW 50 431	32	37	960 °C	50/500
GW 50 432	40	48	960 °C	35/350

NOTES: quick entry cable glands, except GW50428.
CHARACTERISTICS: quick entry cable glands, suitable for cables with Ø from 4 to 14mm.
Cable gland GW50429, suitable for conduits ø 16, 20mm.
Cable gland GW50430, suitable for conduits ø 16, 20, 25mm.
Cable gland GW50431, suitable for conduits ø 16, 20, 25, 32mm.
Cable gland GW50432, suitable for conduits ø 16, 20, 25, 32, 40mm.

Multi-diameter drill milling cutter in HSS steel to drill boxes, boards and trunking in insulating material



GW 52 401

Code	Description	Ø of perforation	Pack Carton
GW 52 401	Drill milling cutter	From 3.5 to 40	1/4



44 CE



Scan the QR Code and find out all the technical informations.

VERSIONS WITH QUICK-ENTRY CABLE GLANDS



The boxes with cable glands enable quick insertion of rigid and flexible cables. The innovative geometric shape guarantees high-levels of mechanical performance and ensures that IP rating of the box is maintained even with cables or conduits inserted, thanks to the special suction effect.

LARGE CAPACITY BOXES



The boxes with high-capacity bottoms have been studied in every detail for practicality and robustness, even for the connection of larger diameter conduits (up to 50 mm). This attention to detail has produced a range of boxes that are ideal in systems with a high-density of connections.

HINGED LID VERSIONS



All GEWISS junction boxes 190x140 mm and larger in size have plastic screws with a spherical head allowing the lid to open like a small distribution board (GEWISS patent). This innovative system also allows the covers to be sealed.

Metal surface-mounting watertight junction boxes

DIE-CAST ALUMINIUM JUNCTION BOXES - IP66				
DIMENSIONS LxHxD (mm)	VARNISHED	NOT VARNISHED	ATEX	BOTTOM PLATES
				
91x91x54	GW 76 261	GW 76 281	GW 76 291	-
128x103x57	GW 76 262	GW 76 282	GW 76 292	GW 76 272
155x130x58	GW 76 263	GW 76 283	GW 76 293	GW 76 273
178x156x75	GW 76 264	GW 76 284	GW 76 294	GW 76 274
239x202x85	GW 76 265	GW 76 285	GW 76 295	GW 76 275
294x244x114	GW 76 266	GW 76 286	GW 76 296	GW 76 276
392x298x149	GW 76 267	GW 76 287	GW 76 297	GW 76 277

GW Connect

Metal surface-mounting watertight junction boxes



Made of die-cast aluminium. In addition to junction and connection, they are also used in automation applications. The offer includes painted and unpainted versions and ATEX versions for Zone 2 (G) and Zone 22 (D). The cover is equipped with stainless steel captive screws. The back plate of the box has a ground insert and is ready for the assembly of the DIN rail. Accessories include back-mounting plates in galvanised steel (available from the second dimension).

WALL-MOUNTING BOXES IN DIE-CAST ALUMINIUM - IP66



IP 66

IK 08

Painted boxes



GW 76 261

Metallised grey boxes

Code	Internal dim. LxHxD (mm)	IP degree	Pack Carton
GW 76 261	91x91x54	IP66	1/40
GW 76 262	128x103x57	IP66	1/32
GW 76 263	155x130x58	IP66	1/24
GW 76 264	178x156x75	IP66	1/16
GW 76 265	239x202x85	IP66	1/8
GW 76 266	294x244x114	IP66	1/4
GW 76 267	392x298x149	IP66	1

CHARACTERISTICS: Temperature range: -60° C to +100° C.

Unpainted boxes



GW 76 281

Boxes

Code	Internal dim. LxHxD (mm)	IP degree	Pack Carton
GW 76 281	91x91x54	IP66	1/40
GW 76 282	128x103x57	IP66	1/32
GW 76 283	155x130x58	IP66	1/24
GW 76 284	178x156x75	IP66	1/16
GW 76 285	239x202x85	IP66	1/8
GW 76 286	294x244x114	IP66	1/4
GW 76 287	392x298x149	IP66	1

CHARACTERISTICS: Temperature range: -60° C to +100° C.

76 ATEX - painted boxes - zone 2 (G) zone 22 (D)



GW 76 291

Grey RAL 7037 boxes

Code	Internal dim. LxHxD (mm)	IP degree	Pack Carton
GW 76 291	91x91x54	IP66	1/40
GW 76 292	128x103x57	IP66	1/32
GW 76 293	155x130x58	IP66	1/24
GW 76 294	178x156x75	IP66	1/16
GW 76 295	239x202x85	IP66	1/8
GW 76 296	294x244x114	IP66	1/4
GW 76 297	392x298x149	IP66	1

ACCESSORIES SUPPLIED: kit for external earthing.
ATEX Classification: Equipment-group II Category 3GD.
Type of protection for use in explosive gas atmospheres: nA.
Type of protection for use in explosive dust atmospheres: tc.
Ambient temperature range: -20°C <= Ta <= +85°C.

Complementary items



GW 76 272

Back-mounting plate in galvanised steel

Code	For boxes LxH (mm)	Pack Carton
GW 76 272	128x103	1/10
GW 76 273	155x130	1/10
GW 76 274	178x156	1/10
GW 76 275	239x202	1/5
GW 76 276	294x244	1/5
GW 76 277	392x298	1/5



GW Connect



Scan the QR Code and find out all the technical informations.

CONVENIENCE AND ROBUSTNESS



The 7 sizes are designed for surface mounting, with both internal and external fixing. The cover has stainless steel captive screws, with thicknesses optimised for maximum mechanical strength and resistance to climate and environmental stresses.

PROFESSIONAL RANGE



The IP66 rated boxes can be used as junction boxes, with options to mount bottom plates or DIN rails. The cover is equipped with stainless steel captive fixing screws and the bottom contains a earthing insert.

ATEX VERSIONS

The GW Connect Series boxes are available in coated and uncoated versions and also in an ATEX version, to integrate perfectly with other GEWISS solutions for potentially explosive environments, classified as 2(G) and 22(D) areas.

Multifunctional supporting bases

SURFACE-MOUNTING BOARDS

Code		External dimensions LxHxD (mm)	Input number	Input diameter (mm)
	GW 42 001	200x150x40	16	Ø 20,5
	GW 42 002	200x150x60	12	
	GW 42 003	200x150x80	12	
	GW 42 004	300x200x40	16	
	GW 42 005	300x200x60	16	Ø 23/29
	GW 42 006	300x200x80	16	
	GW 42 007	300x200x120	16	
	GW 42 008	400x300x60	22	
	GW 42 009	400x300x80	22	
	GW 42 010	400x300x120	22	

BACK-MOUNTING PLATES

METAL	INSULATING	Dimensions LxH (mm)
		
GW 44 615	GW 44 625	190x140
GW 44 615	GW 44 625	
GW 44 615	GW 44 625	
GW 44 616	GW 44 626	240x190
GW 44 616	GW 44 626	
GW 44 616	GW 44 626	
GW 44 616	GW 44 626	
GW 44 617	GW 44 627	300x220
GW 44 617	GW 44 627	
GW 44 617	GW 44 627	

FLOOR-MOUNTING DISTRIBUTION BOARD

Code		External dimensions LxHxD (mm)	Input number	Input diameter (mm)
	GW 68 441	200x295x180	-	-

SOCKET-OUTLETS IB 16/32 A


Vertical 67 IB with back-mounting box IP67	Combibloc IP44/55		Horizontal 44 IB with back-mounting box IP44	
- SBF - CBF - AUTOMATIKA (MT)	Without back-mounting box	With back-mounting box	Without fuse-holder base	With fuse-holder base
				
	They can only be installed in the high part of the support base			

Q-DIN 5		27 COMBI IP55
	GW 68 227 N	
	GW 68 212 N	
	GW 68 017 N	Up to 12-module version

42 TV

Multifunctional supporting bases

A range of boards for universal applications, as for example the support of electronic devices, power supply units or for the creation of small control boards with indicators and push-buttons. The cover with honeycomb finish offers the possibility of direct screw mounting of exposed equipment. Completing the offer is the watertight floor version outlet box ideal for example for the fixing of surface or recessed sockets-outlets.



DISTRIBUTION TOWER AND BOARDS



IK 08


GWT 650°C



CLASS II

EN 61140

Surface-mounting distribution boards - IP41



GW 42 001

Boards with reversible door - smooth and honeycomb surface - Grey RAL 7035

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	No. input	Pack Carton
GW 42 001	200x150x40	Ø 20.5 = 16	32
GW 42 002	200x150x60	Ø 20.5 = 12 Ø 20.5/23 = 4	44
GW 42 003	200x150x80	Ø 20.5 = 12 Ø 20.5/23 = 4	32
GW 42 004	300x200x40	Ø 20.5 = 16	16
GW 42 005	300x200x60	Ø 23/29 = 16	21
GW 42 006	300x200x80	Ø 23/29 = 16	16
GW 42 007	300x200x120	Ø 23/29 = 16	10
GW 42 008	400x300x60	Ø 23/29 = 22	10
GW 42 009	400x300x80	Ø 23/29 = 22	8
GW 42 010	400x300x120	Ø 23/29 = 22	5

CHARACTERISTICS: TV board (BxH) 200x150 mm with impact resistance IK07.
NOTES: to restore the double insulation, use the screwcaps provided.

Floor mounting and workbench tower - IP55



GW 68 441

Pillar with reversible door with smooth and honeycombed surface - Grey RAL 7035

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Houseable IB socket-outlets	Installable Q-DIN boards	Pack Carton
GW 68 441	200x295x180	16/32 A	Q-DIN 5	1/6

CHARACTERISTICS: double-sided panels with smooth or honeycomb surface, for fixing interlocked switched socket-outlets 16/32A of the IB range: Combibloc, horizontal IP44 with bottom and vertical IP67 with bottom.

Complementary items

Waterproof coupler

Code	Mounting hole Ø (mm)	Type of pitch	Pack Carton
GW 26 406	23	PG16	25/250

APPLICATIONS: for the combined assembly of enclosures, junction boxes, etc.



GW 26 406

Back-mounting plate with self-tapping fixing screws

Code	For boxes dimensions	For distribution boards	Pack Carton
Material: Galvanized metal			
GW 44 615	190x140	GW42001 - GW42002 - GW42003	20
GW 44 616	240x190	GW42004 - GW42005 - GW42006 - GW42007	20
GW 44 617	300x220	GW42008 - GW42009 - GW42010	20
Material: Insulation			
GW 44 625	190x140	GW42001 - GW42002 - GW42003	20
GW 44 626	240x190	GW42004 - GW42005 - GW42006 - GW42007	20
GW 44 627	300x220	GW42008 - GW42009 - GW42010	20



GW 44 615

Cup drill milling cutter to drill panels

Code	Description	Pack Carton
GW 52 402	Cup drill milling Ø56	10


APPLICATIONS: suitable for low voltage flush-mounting socket-outlets IEC 309 2P+E 16A and for all the extra-low voltage flush-mounting socket-outlets IEC 309.



GW 52 402



42 TV



Scan the QR Code and find out all the technical informations.

A COMPLETE OFFER



The range consists of three sizes with different depths, and the practical floor-mounted tower. The accessories line includes back-mounting plates in sheet metal or insulating material, screwcaps to restore the IP protection rating and double insulation.

APPLICATION MULTIFUNCTIONALITY



The front panel of the support bases is reversible: one face is smooth, to facilitate the fitting of recessed components and the other has a hollow structure to facilitate visible fitting of the products. Ideal for control and signalling boards.

FLOOR-STANDING TOWER VERSION



The practical and functional floor-standing tower, with an IP55 rating, enables configurations with IB interlocked sockets, Q-DIN distribution boards and enclosures of the 27 COMBI range.

Flush-mounting enclosures





Domo Center

Flush-mounting system columns for distribution, Home & Building automation and data

p. 1202

Green Wall

Flush-mounting system for plasterboard walls

p. 260







40 CDI

Flush-mounting distribution boards and enclosures

p. 280

48

Flush-mounting junction and modular boxes system

p. 301

24 SC

Flush-mounting, surface and underfloor boxes

p. 316

Green Wall

40 CDKi Range Green Wall - Modular and protected enclosure and distribution boards - IP40



Color: RAL 9016 white
Door: smoked transparent

Modules	Code
12	GW 40 605 PM
24 (12x2)	GW 40 606 PM
36 (18x2)	GW 40 609 PM
54 (18x3)	GW 40 610 PM
72 (18x4)	GW 40 611 PM

COMPLEMENTARY ITEMS

1-module cover profile	kit long self -threading screws	Element for combined coupling	Internal horizontal dividers	Blank covering panels	Cylindrical security lock
					
Code	Code	Code	Code	Code	Code
GW 40 467	GW 48 645	2 x GW 40 425	-	-	1 x GW 40 422
			GW 40 487	GW 40 495	
			GW 40 488	GW 40 496	2 x GW 40 422

48 PT DIN Green Wall - Boxes for junction and domotics - IP40




(equipped with DIN rail on the bottom)

Code	Dimensions	Lid colour
GW 48 006 PM	196x152x75	RAL 9016 white
GW 48 126 PM	196x152x75	Transparent
GW 48 007 PM	294x152x75	RAL 9016 white
GW 48 008 PM	392x152x75	RAL 9016 white
GW 48 009 PM	480x160x75	RAL 9016 white

COMPLEMENTARY ITEMS

Protective shield	No. of internal divider	Joining element	Spare lid plain IP40	Spare lid deep IP40
				
Code	Code	Code	Code	Code
GW 48 006 P	1 x GW 48 012	2 x GW 48 051	GW 48 017	GW 48 086
GW 48 007 P	2 x GW 48 012		GW 48 018	GW 48 087
GW 48 008 P	3 x GW 48 012		GW 48 019	GW 48 088
GW 48 009 P	2 x GW 48 012		GW 48 020	-

48 CM Green Wall - Large capacity connection and junction boxes - IP40



			COMPLEMENTARY ITEMS			
			No. of internal divider	Joining element	Spare lid plain IP44	Spare lid deep IP44
Code	Dimensions	Lid colour	Code	Code	Code	Code
GW 48 207 PM	260x260x121	RAL 9016 white	1 supplied	2 supplied	GW 48 247	GW 48 267
GW 48 211 PM	520x260x121	RAL 9016 white	4 supplied	2 supplied	GW 48 251	GW 48 271

40 CDKI Green Wall - Protected enclosures and distribution boards - IP40 with antibacterial front

Modules	Antibacterial Front	Green Wall Back box
12	GW 41 885 AB	GW 40 685 PM
24 (12x2)	GW 41 886 AB	GW 40 687 PM
36 (18x2)	GW 41 889 AB	GW 40 688 PM
54 (18x3)	GW 41 890 AB	GW 40 689 PM
72 (18x4)	GW 41 891 AB	GW 40 690 PM

48 PT DIN Green Wall - Boxes for junction and domotics - IP40 with antibacterial lid IK10







Dimensions	Lid colour	Antibacterial Lid	Green Wall Back box
196x152x75	RAL 9016 white	GW 48 017 AB	GW 48 116 PM
294x152x75	RAL 9016 white	GW 48 018 AB	GW 48 117 PM
392x152x75	RAL 9016 white	GW 48 019 AB	GW 48 118 PM
480x160x75	RAL 9016 white	GW 48 020 AB	GW 48 119 PM

Green Wall

Green Wall boxes for interlocked sockets

Flush-mounting boxes for 67 IB sockets	 
Code	**Houseable sockets**
GW 66 683 PM	16/32A version SBF-CBF-AUTOMATIKA
Flush-mounting boxes for 44 IB horizontal sockets	 
Code	**Houseable sockets**
GW 66 681 PM	16/32A version SBF
GW 66 682 PM	16/32A version CBF

24 SC Green Wall - flush-mounting boxes for modular range

24 SC RANGE GREEN WALL		No. place	CHORUSMART RANGE		SYSTEM RANGE		COMPLEMENTARY ITEMS	
Boxes	Code		Support	Plates	Support	Support	Internal divider	Lid
RECTANGULAR 	GW 24 403 PM	1	 GW 16 802	 ONE - GEO - EGO	 GW 24 201	 TOP SYSTEM - VIRNA	GW 24 321	-
		2	 GW 16 802	 ONE - GEO - EGO - LUX - ICE	 GW 24 262	 TOP SYSTEM - VIRNA		
		3	 GW 16 803 - GW 16 803 N*	 ONE - GEO - EGO - LUX - ICE - ICE TOUCH - ICE TOUCH KNX	 GW 24 201	 TOP SYSTEM - VIRNA		
	GW 24 404 PM	4	 GW 16 804 - GW 16 804 N* GW 16 824	 ONE - GEO - EGO - LUX - ICE	 GW 24 202	 TOP SYSTEM - VIRNA		
	GW 24 406 PM	6	 GW 16 806	 ONE - GEO - LUX - ICE	 GW 24 230	 TOP SYSTEM - VIRNA		
		7	 GW 16 807 N	 EGO	-	-		
	GW 24 237 PM	(4+4)	 GW 16 808	 ONE	 GW 24 240	 TOP SYSTEM - VIRNA	-	-
ROUND 	GW 24 234 PM	1	 GW 16 802	 ONE - GEO - EGO	-	-	-	GW 24 218
		2	 GW 16 802	 ONE - GEO - EGO - ICE	-			
			 GW 16 822 - GW 16 822 N*	 ONE - GEO - EGO - LUX (International)	-			

* For EGO SMART

Green Wall

Compatibility of flush-mounting enclosures with bipolar and unipolar terminal blocks

Enclosures	Code	Terminal block position	SCREW TERMINAL TYPE		
					
			TERMINAL BLOCK SIZE 1		
			Bipolar 125 A 2 x [(1x35)+(7x10)]	Bipolar 80 A 2 x [(2x16)+(7x10)]	Unipolar 80 A 1 x [(2x16)+(7x10)]
			GW 40 401	GW 40 408 B	GW 40 408 U
40 CDK GREEN WALL ENCLOSURES AND DISTRIBUTION BOARDS FOR PLASTERBOARD WALLS IP40 	GW 40 605 PM		N° 1 (*)	N° 1 (*)	N° 1 (*)
	GW 40 606 PM		N° 2 (*)	N° 2 (*)	N° 2 (*)
	GW 40 609 PM		N° 2 (*)	N° 2 (*)	N° 2 (*)
	GW 40 610 PM		N° 3 (*)	N° 3 (*)	N° 3 (*)
	GW 40 611 PM		N° 4 (*)	N° 4 (*)	N° 4 (*)

(*) The installation is allowed using No.1 adapter GW40413 for each terminal block installed.

Compatibility between GEWISS domotic device and 48 PT DIN green wal

GEWISS DOMOTIC DEVICES		48 PT DIN GREEN WALL BOXES				
		Code	GW 48 006 PM GW 48 126 PM	GW 48 007 PM	GW 48 008 PM	GW 48 009 PM
		Compartments	2	3	4	3
		No. of EN 50022 modules per compartment	4,5	5	5	8
		No. mod. EN 50022 / MAX pde (W)*	11	13	17	25
KNX DEVICES FROM DIN RAIL	KNX line/field couplers	2	●	●	●	●
	KNX power supplies	4	●	●	●	●
	KNX motor control actuators	4	●	●	●	●
		8				
	KNX dimmer	4	●	●	●	●
	KNX general actuators	4	●	●	●	●
		8				●
	DALI/KNX, Gateway	4	●	●	●	●
	KNX input modules	4	●	●	●	●
	KNX BUS interfaces	1	●	●	●	●
DOMOTIC DEVICES FOR DOMESTIC RANGES	KNX domestic range actuators	3	●	●	●	●
	Relay	1,5 and 3	●	●	●	●

* Dispersible power calculated according to IEC 60674-24.

SCREW TERMINAL TYPE



TERMINAL BLOCK SIZE 2				TERMINAL BLOCK SIZE 3		
Bipolar 125 A 2 x [(3x35)+(10x10)]	**Bipolar 80 A 2 x [(3x16)+(11x10)]**	**Unipolar 80 A 1 x [(3x16)+(11x10)]**	**Unipolar 80 A 1 x [(3x16)+(29x10)]**	**Bipolar 125 A 2 x [(5x35)+(14x10)]**	**Bipolar 80 A 2 x [(3x16)+(17x10)]**	**Unipolar 80 A 1 x [(3x16)+(17x10)]**
GW 40 402	GW 40 412 B	GW 40 412 U	GW 40 422 U	GW 40 404	GW 40 418 B	GW 40 418 U
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3	N° 3	N° 3
N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4	N° 4	N° 4

Compatibility between 48 Green Wall boxes and and terminal blocks 44 Range

		MULTI-POLE			SINGLE-POLE EQUIPOTENTIAL							
		GW 44 609 GW 44 610 GW 44 610 C	GW 44 611 GW 44 612	GW 44 613 GW 44 614	GW 44 704	GW 44 706	GW 44 708	GW 44 671	GW 44 672	GW 44 673 GW 44 674	GW 44 675	GW 44 676
Serie	**Code**											
48 PT DIN GREEN WALL	GW 48 006 PM	●	●	●	●	●	●	●	●	●	-	-
	GW 48 126 PM	●	●	●	●	●	●	●	●	●	-	-
	GW 48 007 PM	●	●	●	●	●	●	●	●	●	-	-
	GW 48 008 PM	●	●	●	●	●	●	●	●	●	-	-
	GW 48 009 PM	●	●	●	●	●	●	●	●	●	-	-
48 CM GREEN WALL	GW 48 207 PM	●	●	-	●	●	●	●	●	●	-	-
	GW 48 211 PM	●	●	-	●	●	●	●	●	●	-	-

Green Wall

Flush-mounting system for plasterboard walls



The most complete system of containers for lightweight and plasterboard walls; GEWISS patented solutions. Made with halogen-free technopolymer and GWT 850°C. The range include: enclosures and distribution boards up to 72 M; 48 PT DIN GREENWALL range junction boxes with integrated DIN rail on the back plate, compliant with CEI 23-49, ideal for the pre-arrangement and installation of domotic devices; boxes for wiring devices and boxes for interlocked switched socket-outlets.

40 CDKI GREEN WALL - ENCLOSURES AND DISTRIBUTION BOARDS FOR LIGHTWEIGHT AND PLASTERBOARD WALLS - IP40



IK 08

IP 40

GWT 850°C

CLASS II

EN 61140

Smoked transparent door



GW 40 606 PM

Modular enclosures and distribution boards with windowed panel and extractable frame predisposed for housing terminal blocks - White RAL 9016 - smoked door

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 605 PM	12	330x270x85	36	8
GW 40 606 PM	24 (12X2)	330x420x85	37	6
GW 40 609 PM	36 (18x2)	465x505x85	52	3
GW 40 610 PM	54 (18x3)	465x680x95	62	3
GW 40 611 PM	72 (18x4)	465x880x95	95	1

CHARACTERISTICS: Lead sealable and removable panels with windows, except for code GW40605PM. Back plates equipped with tabs for fixing on a metal structure for lightweight and plasterboard walls. Locators to mark the wall along the edges of the back plate. Horizontal modularity using the joining element GW40425 for enclosure GW40605PM. Vertical modularity using the joining element GW40425 for boards GW40606PM-GW40609PM-GW40610PM-GW40611PM.

NOTES: Dissipated power calculated according to CEI 23-49. Casing type H according to EN 60670-1, and type Ha according to IEC 60670-1.

GWT 850°C, according to EN 60695-2-11, related to the green flush-mounting box.

Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.

ACCESSORIES SUPPLIED: Self-tapping screws kit ø 4x45 mm with spacers for fixing frontal panels.

INSTALLATION: For the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Antibacterial front kit



GW 41 890 AB

Distribution front kit windowed panels and extractable frame predisposed for housing the terminal blocks - White RAL 9016 - Antibacterial

Anti bacterial

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 41 885 AB	12	330x270x16	36	12
GW 41 886 AB	24 (12X2)	330x420x16	37	5
GW 41 889 AB	36 (18x2)	465x505x16	52	3
GW 41 890 AB	54 (18x3)	465x680x25	62	2
GW 41 891 AB	72 (18x4)	465x880x25	95	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.

NOTES: dissipated power calculated according to CEI 23-49. The antibacterial front kit is composed of frame, door, lock covers, opening handles. The kit includes also functional frame and DIN rails.

CHARACTERISTICS: lead sealable and removable panels with windows. Thermo-pressure with ball equal to 70 °C. Flush-mounting boxes can be assembled side-by-side through the coupling tool code GW40425.

INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING GREEN WALL ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" at the beginning of the section.



GW 40 689 PM

Flush-mounting Green Wall back box for Antibacterial front kit - For plasterboard wall

Code	No. of modules EN 50022	Suitable for ANTIBACTERIAL front kit	Pack Carton
GW 40 685 PM	12	GW41885AB	1/12
GW 40 687 PM	24 (12X2)	GW41886AB	1/5
GW 40 688 PM	36 (18x2)	GW41889AB	1/5
GW 40 689 PM	54 (18x3)	GW41890AB	1/3
GW 40 690 PM	72 (18x4)	GW41891AB	1/2

CHARATTERISTICS: equipped with tabs for fixing on a metal structure for lightweight and plasterboard walls. Locators to mark the wall along the edges of the back box. Back boxes can be coupled with the accessory GW40425.
NOTE: GWT 850°C, according to EN 60695-2-11.
INSTALLATION: the matching antibacterial front kit must be ordered separately.

Complementary items for enclosures and boards 40 CDKi GREEN WALL

Cylinder security lock for 40 CDKi enclosures



GW 40 422

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

Plastic module cover profile

GW 40 467

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50

CHARACTERISTICS: clip fixing.

Element for combined coupling of CDKi and CDi flush-mounting decorative enclosures and distribution boards




GW 40 425

Code	Fixing	Pack Carton
GW 40 425	Clip	10

APPLICATIONS: for CDKi enclosures and boards from 12 modules upwards. Also suitable for 40 CDi decorative enclosures with 8 and 12 modules and for the QDSA enclosures. For CDKi GREEN WALL enclosures and boards, the GW40425 element permits horizontal paths for the 12M enclosure and vertical paths for 24M to 72M boards.
NOTES: GWT 850 °C according to EN 60695-2-11.

Internal horizontal dividers for CDKi distribution boards



GW 40 487

Code	For boards EN 50022 rail	Fixing	Pack Carton
GW 40 487	12 Modules	Clip	10/100
GW 40 488	18 Modules	Clip	10/100

NOTES: they permit making internal separation between the circuits having different voltages located on more than one row inside the same shell.

Blank covering panels - 1-module height - for CDKi boards



GW 40 495

Code	Suitable for	For boards EN 50022 rail	Colour	Pack Carton
GW 40 495	Flush mounting distr. boards	12 Modules	White RAL 9016	20
GW 40 496	Flush mounting distr. boards	18 Modules	White RAL 9016	20

CHARACTERISTICS: sealing.

Insulated screw terminal block bipolar and unipolar for enclosures and boards

Code	Pole 1 (mm²)	Pole 2 (mm²)	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A				
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	With screws and/or clip	10
GW 40 404	N (5x35) + (14x10)	E (5x35) + (14x10)	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20				
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	With screws and/or clip	1/10
GW 40 418 B	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20				
GW 40 408 U	N/E (2x16) + (7x10)	-	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	With screws and/or clip	1/10
GW 40 418 U	N/E (3x16) + (17x10)	-	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	With screws and/or clip	1/10



GW 40 412 B

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.
CHARACTERISTICS: GWT 960°C according to EN60695-2-11.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "EQUIPPABILITY OF GREEN WALL FLUSH-MOUNTING ENCLOSURES WITH TWO-POLE OR ONE-POLE TERMINAL" within the selection guides for the GREEN WALL range.

Adapter for screw terminal blocks

Code	For enclosures	Fastener to supports	Pack Carton
GW 40 413	12 M (and multiples) and 18 M (and multiples)	With screws	20



GW 40 413

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block and pre-cut to allow installation also in enclosures with a 12 M modular step.
INSTALLATION: used to expand the numer of possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of GREEN WALL range.

Kit of 4 long self-tapping screws with spacers for fixing lids and fronts

Code	Screw dimension (mm)	Spacer thickness (mm)	Pack Carton
GW 48 645	Ø 4x45	Max 10 mm reducible	1/100

CHARACTERISTICS: the kit can be used for the following flush-mounting ranges: CD Chorus, CDi/CDKi (from 6 modules upwards), 48 CM and 42 RV.



GW 48 645

40 CDKI GREEN WALL - MULTI-SERVICE SYSTEM ENCLOSURES



IK 08

IP 40

GWT 850°C

CLASS II

EN 61140

Multimedia enclosures



GW 40 390 C

Multimedia enclosure compact version 36 DIN modules - White RAL 9016 - Blank door

HF HALOGEN FREE

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 40 390 C	Front cover, inner frame and accessories 36 DIN modules	465x505x85	1
GW 40 688 PM	Empty Green Wall back box 36 DIN modules	-	1/5

APPLICATIONS: the compact multimedia enclosure is the central element of multi-service wiring within the home, allowing the distribution of signals to the various rooms. The compact version is ideal for settings where the available space is limited and a small number of services need to be managed.
CHARACTERISTICS: the product is compliant with the CEI 306-2 Guide. The back of the box has plastic tabs for an easier installation on metal frames and drywall panels. The product can be joined vertically with other enclosures of the CDKi range (minimum size 36 DIN modules) using GW40425 coupling elements.
ACCESSORIES SUPPLIED: the GW40390C is composed of 1 pc front cover with blank door, 1 pc detachable frame with 2 pcs perforated mounting plates (1 pc with 18 Keystone Jack slots), 2 m velcro roll w=16 mm, 4 pcs brackets with screws, 4 pcs self-adhesive cable clips with cable ties, 5 pcs RJ45 Cat.6 keystone jacks.
INSTALLATION: the product can be installed on both lightweight and plasterboard partition walls.



GW 40 390 F

Multimedia enclosure compact version 54 DIN modules - White RAL 9016 - Blank door

HF HALOGEN FREE

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 40 390 F	Front cover, inner frame and accessories 54 DIN modules	465x680x95	1
GW 40 689 PM	Empty Green Wall back box 54 DIN modules	-	1/3

APPLICATIONS: the complete multimedia enclosure is the central element of multi-service wiring within the home, allowing the distribution of signals to the various rooms. The full version is ideal for residential settings where a large number of services and reception/transmission devices need to be managed.
CHARACTERISTICS: the product is compliant with the CEI 306-2 Guide. The back box has plastic tabs for easier installation on metal frames and drywall panels. The product can be joined vertically with other enclosures of the CDKi range (minimum size 36 DIN modules) using GW40425 coupling elements.
ACCESSORIES SUPPLIED: the GW40390F includes of 1 pc front cover with blank door, 1 pc detachable frame with 3 pcs perforated mounting plates (1 pc with 18 Keystone Jack slots), 3 m velcro roll w=16 mm, 6 pcs brackets with screws, 6 pcs self-adhesive cable clips with cable ties, 6 pcs RJ45 Cat.6 data sockets, 6 pcs RJ45-RJ45 Cat.6 Ethernet cable 0.6 m, 1 pc telephone splitter with 5 pcs RJ11 socket and 5 pcs RJ11-RJ45 telephone cables, 1 pc multiple socket.
INSTALLATION: the product can be installed on both lightweight and plasterboard partition walls.

Technical accessories for home networking enclosures



GW 40 422

Cylindrical security lock

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: all the keys and relative locks with the same product code are identical.

Green Wall



GW 40 425

Element for combined coupling of CDKi and CDi flush-mounting decorative enclosures and distribution boards

Code	Fixing	Pack Carton
GW 40 425	Clip	10

APPLICATIONS: for CDKi enclosures and boards from 12 modules upwards. Also suitable for 40 CDi decorative enclosures with 8 and 12 modules and for the QDSA enclosures. For CDKi GREEN WALL enclosures and boards, the GW40425 element permits horizontal paths for the 12M enclosure and vertical paths for 24M to 72M boards.
NOTES: GWT 850 °C according to EN 60695-2-11.



GW 38 098

Telephone jack expansion kit

Code	Description	Pack Carton
GW 38 098	RJ11 telephone socket and telephone cable	1

ACCESSORIES SUPPLIED: 1 multiple telephone socket-outlet with 5 RJ11 socket-outlets.

48 PT DIN GREEN WALL - JUNCTION BOXES FOR LIGHTWEIGHT AND PLASTERBOARD WALLS - IP40



IK 07

IP 40

GWT 850°C



For lightweight and plasterboard walls



GW 48 006 PM

Junction and connection boxes for side-by-side assembly with DIN rail integrated - on the back-mounting box - Colour: White lid RAL 9016

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	No. EN 50022 mod. per comp.	Domotic equipment coupling	Dispersible max power (W)	No. supports GW44720	Pack Carton
GW 48 006 PM	196x152x75	2	4.5	DIN rail	11	2	1/30
GW 48 007 PM	294x152x75	3	5	DIN rail	13	3	1/21
GW 48 008 PM	392x152x75	4	5	DIN rail	17	4	1/14
GW 48 009 PM	480x160x75	3	8	DIN rail	25	5	1/12

APPLICATIONS: boxes with a built-in DIN rail on the back-mounting box, in accordance with regulations that require to fix by DIN rail the devices that disperse a certain amount of power inside the junction boxes (calculated in compilance with CEI 23-49). ideal for relocation of domotic equipment as actuators, power supplies, etc.
CHARACTERISTICS: surface embossing of the covers to facilitate painting. Pre-arrangement combined horizontal coupling using joining element, code GW48051. Lid protected with heat-shrinking film that also contains the bag of fixing screws. Locators to aid tracing the wall along the edges of the box. Boxes equipped with tabs for direct fixing on panels or a metal structure for lightweight and plasterboard walls. Possibility of fixing directly on the back-mounting box of the box.
ACCESSORIES SUPPLIED: ø3x38 mm screw kit for lid fixing.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors. Dispersible power calculated according to CEI 23-49. Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting back-mounting box. Also for KNX devices from DIN rail, domotic devices for domestic ranges, and devices for video entryphones.



GW 48 126 PM

Junction and connection box for side-by-side assembly with DIN rail integrated - on the back-mounting box - Transparent lid

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	No. EN 50022 mod. per comp.	Domotic equipment coupling	Dispersible max power (W)	No. supports GW44720	Pack Carton
GW 48 126 PM	196x152x75	2	4.5	DIN rail	11	2	1/30

APPLICATION: boxes with a built-in DIN rail on the back-mounting box, in accordance with regulations that require to fix by DIN rail the devices that disperse a certain amount of power inside the junction boxes (calculated in compilance with CEI 23-49).
CHARACTERISTICS: Pre-arrangement combined horizontal coupling using joining element, code GW48051. Lid protected with heat-shrinking film that also contains the bag of fixing screws. Locators to aid tracing the wall along the edges of the box. Boxes equipped with tabs for direct fixing on panels or a metal structure for lightweight and plasterboard walls. Possibility of fixing directly on the back-mounting box of the box.
ACCESSORIES SUPPLIED: ø3x38 mm screw kit for lid fixing.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors. Dispersible power calculated according to CEI 23-49. Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting back-mounting box. Ideal for medical room applications where the earthing point must be inspectable.

Antibacterial shockproof lids



GW 48 017 AB

Antibacterial shockproof lids for PT / PT DIN and PT DIN Green Wall boxes white RAL 9016 - IP40

Code	Suitable for	Mechanical resistance	Pack Carton
GW 48 017 AB	GW48116 and GW48116PM	IK10	1/50
GW 48 018 AB	GW48117 and GW48117PM	IK10	80/40
GW 48 019 AB	GW48118 and GW48118PM	IK10	1/20
GW 48 020 AB	GW48119 and GW48119PM	IK10	1/20

CHARACTERISTICS: the packaging includes screws for installation in brick walls or plasterboard walls. GWT 850 °C according to EN 60695-2-11.



GW 48 116 PM

Flush-mounting Green Wall back boxes for Antibacterial shockproof lids - For brick wall

Code	Suitable for	Pack Carton
GW 48 116 PM	GW48017AB	30
GW 48 117 PM	GW48018AB	20
GW 48 118 PM	GW48019AB	10
GW 48 119 PM	GW48020AB	10

NOTE: the Antibacterial shockproof lid must be ordered separately.

Complementary items for boxes for lightweight and plasterboard walls



GW 48 006 P

Protective shield for junction, connection and domotics boxes PT DIN and PT DIN GREEN WALL

Code	For boxes PT DIN	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 006 P	GW48006	GW48006PM and GW48126PM	70
GW 48 007 P	GW48007	GW48007PM	60
GW 48 008 P	GW48008	GW48008PM	50
GW 48 009 P	GW48009	GW48009PM	40

CHARACTERISTICS: in technopolymer. applying the protective shield beneath the lid, the dispersible power of the box is reduced by 2W for GW48006PM, GW48007PM, GW48008PM boxes and by 3W for GW48009.
NOTES: clip fixing to speed up assembly and removal operations. Reusable.



GW 48 051

Joining element for PT / PT DIN and PT DIN GREEN WALL boxes

Code	For PT / PT DIN boxes	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 051	GW48003 - GW48011	GW48006PM - GW48009PM	10

NOTES: the use of the joining element makes it possible to create horizontal and/or vertical sets of boxes PT/PT DIN. For PT DIN GREEN WALL boxes, GW40425 element permits horizontal paths. GW48051 also for the box with transparent lid GW48126PM. GWT 850 °C according to EN 60695-2-11.

Internal divider for PT DIN and PT DIN GREEN WALL boxes



GW 48 012

Code	For boxes PT DIN	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 012	GW48006 - GW48011	GW48006PM - GW48009PM	50/300

High-resistance shockproof plain covers for PT DIN and PT DIN GREEN WALL boxes White RAL 9016 - IP40



GW 48 018

Code	Suitable for	Mechanical resistance	Pack Carton
GW 48 017	GW48006 and GW48006PM	IK10	10/100
GW 48 018	GW48007 and GW48007PM	IK10	10/80
GW 48 019	GW48008 and GW48008PM	IK10	10/40
GW 48 020	GW48009 and GW48009PM	IK10	10/40

CHARACTERISTICS: surface embossing of the covers to facilitate painting.

Deep lids for PT DIN and PT DIN GREEN WALL boxes



GW 48 086

Code	Suitable for	Pack Carton
GW 48 086	GW48006 and GW48006PM	1/10
GW 48 087	GW48007 and GW48007PM	1/5
GW 48 088	GW48008 and GW48008PM	1/5

CHARACTERISTICS: the deep lids are ideal for passing from an exposed system to a chased one. They have a removable front plate and a frame for connecting with trunking.
Max lid H = 49mm for boxes up to 196x152; max lid H = 66mm for boxes up to 392x152 and conduits with max Ø = 32mm.

Long self-tapping screws for securing cover



GW 48 023

Code	Dimensions (mm)	Suitable for	Pack Carton
GW 48 023	Ø3x38	Junction boxes range 48 PT / PT DIN and PT DIN GREEN WALL	300/4200

44 ME - UNIPOLAR EQUIPOTENTIAL TERMINAL BLOCKS

GWT 850°C

TP 125°C

Terminal blocks for side-by-side assembly



GW 44 706

Terminal blocks with indirect plate tightening - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 704	4 ways x 6 mm²	10/100
GW 44 706	6 ways x 6 mm²	10/100
GW 44 708	8 ways x 6 mm²	10/100

APPLICATIONS: embedded fixing on the GW44720 support, for coupling with the DIN rail.
NOTES: for the connection capacity, refer to the technical catalogue

Accessories for terminal blocks for side-by-side assembly



GW 44 720

Support for fixing side-by-side terminal blocks on DIN rail

Code	For equipotential terminal blocks	Terminal block fixing	Fixing on DIN rail	Pack Carton
GW 44 720	GW44704, GW44706, GW44708	Clip	Lock-joint	1/50

NOTES: ideal for applications on boxes of the 48 PT DIN range.
CHARACTERISTICS: supports a combination of terminal blocks with maximum 12-way capacity.
Possible combinations: 3xGW44704; 2xGW44706; 1xGW44704 + 1xGW44706; 1xGW44704 + 1xGW44708; Modular overall dimensions (width): 4.5 modules EN 50022.

Modular terminal blocks



GW 44 671


Terminal blocks with indirect screw tightening - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 671	3 ways x 6 mm²	10/100
GW 44 672	5 ways x 6 mm²	10/100
GW 44 673	4 ways x 16 mm²	10/50
GW 44 674	2 ways x 16mm² + 3 ways x 6 mm²	10/50
GW 44 675	2 ways x 16mm² + 9 ways x 6 mm²	5/25
GW 44 676	2 ways x 35 mm² + 4 ways x 16 mm²	1/10

APPLICATIONS: especially suitable for creating equipotential nodes.
ACCESSORIES SUPPLIED: self-adhesive label for identification of electrical lines.
NOTES: GW44676 equipped with feedthrough terminals. These allow the creation of cut-outs from the main cables which, unsheathed in the part concerned, are not interrupted.

Accessories for modular terminal blocks

Support for fixing modular terminal blocks on DIN rail



GW 44 681

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 681	From GW44671 to GW44676	Clip	100

Adapter for fixing modular terminal blocks




GW 44 682

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 682	From GW44671 to GW44676	Lock-joint	200

APPLICATIONS: for fixing the equipotential terminal blocks on the plates or directly on the base inside the junction boxes and watertight boxes.
ACCESSORIES SUPPLIED: screws for fixing the adapter.

48 CM GREEN WALL - HIGH-CAPACITY BOXES FOR LIGHTWEIGHT AND PLASTERBOARD WALLS - IP40



IK 07

IP 40

GWT 850°C



Plain lid



GW 48 207 PM

Junction and connection boxes for side-by-side assembly, for uprights for lightweight and plasterboard walls plain plumbable lid - White RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Dispersible max power (W)	Pack Carton
GW 48 207 PM	260x260x121	2	13	8
GW 48 211 PM	520x260x121	5	30	6

ACCESSORIES SUPPLIED: internal dividers, joint elements for combined assembly, self-adhesive symbol labels for circuit identification, and plumbable screws.
NOTES: dispersible power calculated according to IEC 60670-24. Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting back-mounting box.
CHARACTERISTICS: Locators to aid tracing the wall along the edges of the box. Boxes equipped with tabs for direct fixing on panels or a metal structure for lightweight and plasterboard walls. Possibility of fixing directly on the back-mounting box of the box. Horizontal modularity.

Complementary items



GW 48 251

Shockproof plumbable plain lids for boxes for uprights - White RAL 9016- IP44

Code	Front dim. LxH (mm)	Mechanical resistance	Pack Carton
GW 48 247	260x260	IK10	1/15
GW 48 251	520x260	IK10	1/10

ACCESSORIES SUPPLIED: self-adhesive symbol labels for circuit identification, and plumbable screws.



GW 48 271

Shockproof sealable deep lids for boxes for uprights - Grey RAL 7035 - IP44

Code	For boxes dimensions	Mechanical resistance	Pack Carton
GW 48 267	260x260	IK10	1/10
GW 48 271	520x260	IK10	1/5

CHARACTERISTICS: the lid has a removable front plate and a frame for connection with trunking (max h = 65mm) and conduits (max Ø = 40mm).
The frame is fitted for fixing the DIN rails (not supplied).
Pre-arrangement EN 50022: GW48267 horizontal 24 modules (2x12), vertical 24 modules (2x12); GW48271 horizontal 78 modules (26x3), vertical 36 modules (12x3)
ACCESSORIES SUPPLIED: self-adhesive symbol labels for circuit identification, and plumbable screws.

24 SC GREEN WALL - BOXES FOR MODULAR RANGES AND KNX DEVICES







Rectangular boxes for lightweight and plasterboard walls



GW 24 403 PM

High capacity rectangular boxes for modular domestic ranges

HF HALOGEN FREE

Code	Description	Fixing supports axles distance	Compartment pre-arrangement	Outer dim. LxHxD (mm)	Pack Carton
GW 24 403 PM	3 modules	83.5 mm	2	110x73x50	9/180
GW 24 404 PM	4 modules	108.5 mm	2	133x73x50	2/120
GW 24 406 PM	6-7 modules	100 mm	3	182x73x50	2/60
GW 24 237 PM	8 modules (4+4)	108.5 mm	2	131x129x53	2/24

CHARACTERISTICS: high resistance to mechanical stress and crushing. Removal of the knockouts without the use of tools. GW24403PM, GW24404PM, GW24406PM with unlosable metal grips and inserts with adjustable depth for fixing. GW24237PM with tabs for direct fixing on panels or a metal structure.
It is recommended to use a Ø 68 mm hollow mill for the correct installation of the rectangular boxes.
NOTES: Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting box.

Round boxes for lightweight and plasterboard walls



GW 24 234 PM

Flush-mounting round boxes ø65 with adjustable depth inserts

HF HALOGEN FREE

Code	Description	Fixing supports axles distance	Dimensions (mm)	Pack Carton
GW 24 234 PM	Round	60 mm	Ø 65x45	5/200
GW 24 282 PM	Double	-	125x72x45	2/108

CHARACTERISTICS: high resistance to mechanical stress and crushing. GW24282PM vertical assembly to be used in combination with 2 pcs vertically coupled GW16821 or GW16822 or GW16823 supports, (removing the knockouts located on their contact side) and the ChoruSmart International plates, 2 vertical gangs, 57 mm centre distance; Supplied with 4 pcs fixing screws. GW24234PM to be used in combination with GW16821 or GW16822 or GW16823 supports and the ChoruSmart International plates. Supplied with 4 pcs fixing screws. Removal of the knockouts without the use of tools. It is recommended to use a Ø 65 mm router bit for the correct installation of the round boxes.
NOTES: Casing type H in accordance with EN60670-1, and type Ha in accordance with IEC60670-1.
GWT 850°C, according to EN 60695-2-11 relative to the green flush-mounting box. for the inputs, remove the knockouts after cutting the relative tangs using scissors.

Complementary items for boxes for lightweight and plasterboard walls - 24 SC Green Wall



GW 24 321

Functional divider for rectangular boxes

Code	For BIG BOX boxes	For GREEN WALL boxes	Pack Carton
GW 24 321	GW24403, GW24404, GW24406	GW24403PM, GW24404PM, GW24406PM	200

APPLICATIONS: to separate circuits of different voltages in accordance with Systems Standard IEC 60364 (international) and HD 384 (european).



GW 24 218

Lid for round flush-mounting boxes - White

Code	Description	Fixing	Pack Carton
GW 24 218	Ø 65mm	With fixing clutches	50/400

GREEN WALL BOXES FOR INTERLOCKED SOCKET-OUTLETS 67IB AND 44IB



Flush-mounting box for vertical interlocked switched socket-outlets 67IB for lightweight and plasterboard walls



GW 66 683 PM


Box with frame for flush-mounting of vertical interlocked socket-outlets - IP55

HF HALOGEN FREE

Code	Houseable interloc. socket	For 67IB socket-outlets	Pack Carton
GW 66 683 PM	1	-	1/10

NOTES: the box cannot house the version with a 24V transformer. Halogen-free casing, in accordance with EN 60754-2. Casing type H in accordance with EN 60670-1, and type Ha in accordance with IEC 60670-1
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting back-mounting box.
CHARACTERISTICS: locators for tracing the wall along the edges of the box; box equipped with tabs for direct fixing on panels or a metal structure, for lightweight and plasterboard walls.
ACCESSORIES SUPPLIED: self-tapping screw kit ø 4x45mm.

Flush-mounting boxes for horizontal interlocked switched socket-outlets 44IB for lightweight and plasterboard walls



GW 66 681 PM

Boxes with frame for flush-mounting of fixed horizontal socket-outlets SBF and CBF - IP44

HF HALOGEN FREE

Code	Houseable interloc. socket	For 44 IB socket-outlets	Houseable IB socket-outlets	Pack Carton
GW 66 681 PM	1	16/32 A SBF	16/32 A	1/10
GW 66 682 PM	1	16/32 A CBF	16/32 A	1/10

NOTES: Halogen-free casings, in accordance with EN 60754-2.
Casing type H in accordance with EN 60670-1, and type Ha in accordance with IEC 60670-1.
GWT 850°C, according to EN 60695-2-11, relative to the green flush-mounting back-mounting box.
CHARACTERISTICS: locators for tracing the wall along the edges of the boxes; Boxes equipped with tabs for direct fixing on panels or a metal structure for lightweight and plasterboard walls.
ACCESSORIES SUPPLIED: self-tapping screw kit ø 4x45mm.

PLIABLE CONDUITS FOR THE GREEN WALL SYSTEM



ICTA - Halogen Free and Low Smoke medium pliable conduit




DX 22 016 R

Medium pliable conduit, green , self-extinguishing and self- recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 22 016 R	16	100/2800
DX 22 020 R	20	100/2400
DX 22 025 R	25	75/1500
DX 22 032 R	32	50/800
DX 22 040 R	40	25/500
DX 22 050 R	50	25/400
Type: with cable puller		
DX 22 116 R	16	100/2800
DX 22 120 R	20	100/2400
DX 22 125 R	25	75/1500
DX 22 132 R	32	50/800
DX 22 140 R	40	25/500
DX 22 150 R	50	25/400

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



Green Wall



Scan the QR Code and find out all the technical informations.

VERSATILE AND SAFE FIXING




The fixing tabs on the enclosures allow fixing on plasterboard metal struts or panels. The clamps on the wiring devices boxes allow installation on plasterboard panels. The fixing holes allow surface mounting in the case of renovation.

SIMPLE AND INNOVATIVE



The 24 SC Green Wall range has been completely renewed: the special geometry of the knock-out holes enables convenient insertion of the conduit, which is held firmly in place. The “L” profile allows the conduit to be rotated vertically within its fitting.

HIGH QUALITY MATERIALS



Constant research in the field of plastic materials has enabled the use of materials with high mechanical strength, that are halogen-free, and that pass the GWT 850°C Glow Wire Test, in accordance with the specific product standard and the CEI [Comitato Elettrotecnico Italiano] 64/8 system standard.

Flush-mounting enclosures

			40 CDi RANGE PROTECTED DECORATIVE ENCLOSURES IP40					40 CDKI RANGE - MODULAR PROTECTED ENCLOSURES AND DISTRIBUTION BOARDS - IP40		40 CDKI RANGE - MODULAR PROTECTED ENCLOSURES AND DISTRIBUTION BOARDS - ANTIBACTERIAL - IP40		
												
			White		Black	Varnished titanium	Varnished slate	White RAL 9016		White RAL 9016 Antibacterial	Back box for brickwall	Back box for plasterboard
		Door / Enclosure	Smoked transparent	Blank	Smoked transparent	Smoked transparent	Smoked transparent	Smoked transparent	Blank	Blank		
MODULES	2	with back-mounting box	-	-	-	-	-	GW 40 601 (*)	-	-	-	-
	4	with back-mounting box	GW 40 237 TB	GW 40 287 TB	GW 40 237 TN	GW 40 237 VT	GW 40 237 VA	GW 40 602	GW 40 882	-	-	-
		front cover	GW 41 237 TB	-	GW 41 237 TN	GW 41 237 VT	GW 41 237 VA	-	-	-	-	-
	6	with back-mounting box	-	-	-	-	-	GW 40 603	GW 40 883	-	-	-
	8	with back-mounting box	GW 40 225 TB	GW 40 285 TB	GW 40 225 TN	GW 40 225 VT	GW 40 225 VA	GW 40 604	GW 40 884	-	-	-
		including back-mounting box and terminal block	-	-	-	-	-	-	-	-	-	-
		front cover	GW 41 225 TB	-	GW 41 225 TN	GW 41 225 VT	GW 41 225 VA	-	-	-	-	-
	12	with back-mounting box	GW 40 229 TB	GW 40 289 TB	GW 40 229 TN	GW 40 229 VT	GW 40 229 VA	GW 40 605	GW 40 885	GW 41 885 AB	GW 40 685	GW 40 685 PM
		including back-mounting box and terminal block	-	-	-	-	-	-	-			
		front cover	GW 41 229 TB	-	GW 41 229 TN	GW 41 229 VT	GW 41 229 VA	-	-			
	18	with back-mounting box	-	-	-	-	-	GW 40 608	GW 40 888	-	-	-
		including back-mounting box and terminal block	-	-	-	-	-	-	-	-	-	-
	24 (12x2)	with back-mounting box	GW 40 233 TB	GW 40 293 TB	GW 40 233 TN	GW 40 233 VT	GW 40 233 VA	GW 40 606	GW 40 886	GW 41 886 AB	GW 40 687	GW 40 687 PM
		including back-mounting box and terminal block	-	-	-	-	-	-	-			
		front cover	GW 41 233 TB	-	GW 41 233 TN	GW 41 233 VT	GW 41 233 VA	-	-			
	36 (12x3)	with back-mounting box	GW 40 239 TB	GW 40 299 TB	GW 40 239 TN	GW 40 239 VT	GW 40 239 VA	-	-	-	-	-
		including back-mounting box and terminal block	-	-	-	-	-	-	-	-	-	-
		front cover	GW 41 239 TB	-	GW 41 239 TN	GW 41 239 VT	GW 41 239 VA	-	-	-	-	-
	36 (18x2)	with back-mounting box	-	-	-	-	-	GW 40 609	GW 40 889	GW 41 889 AB	GW 40 688	GW 40 688 PM
		including back-mounting box and terminal block	-	-	-	-	-	-	-			
	48 (12x4)	including back-mounting box and terminal block	-	-	-	-	-	-	-	-	-	-
	54 (18x3)	with back-mounting box	-	-	-	-	-	GW 40 610	GW 40 890	GW 41 890 AB	GW 40 689	GW 40 689 PM
		including back-mounting box and terminal block	-	-	-	-	-	-	-			
	60 (12x5)	including back-mounting box and terminal block	-	-	-	-	-	-	-	-	-	-
	72 (18x4)	with back-mounting box	-	-	-	-	-	GW 40 611	GW 40 891	GW 41 891 AB	GW 40 690	GW 40 690 PM
		including back-mounting box and terminal block	-	-	-	-	-	-	-			

COMPLEMENTARY ITEMS	Anti-deformation brackets for walling back-mounting boxes	-					GW 40 479 dal 36M						
	Combined coupling component	2 x GW 40 425 for 8M and 12M					2 x GW 40 425 dal 12M						
	Kit of 4 long screws with spacers	GW 48 645 from 8M					GW 48 645 dal 6M						
	Internal dividers (horizontal and vertical)	-					horizontal	Modules	Code				
								24 (12x2)	GW 40 487				
								36-54-72	GW 40 488				
	1-module high blank cover panels	-					Modules	Code					
							24	GW 40 495					
							36-54-72	GW 40 496					
	Security lock	Modules			Code		Modules	Code					
		24			1 x GW 40 422		4-6-8-12-18-24-36	1 x GW 40 422					
		36			2 x GW 40 422		54-72	2 x GW 40 422					
	Back-mounting boxes	Modules	Code				-						
		4	GW 40 671										
		8	GW 40 673										
		12	GW 40 674										
		24	GW 40 677										
		36	GW 40 679										
	Blanking module profile	6,5M					4,5M						
		GW 40 467 TB (White)	GW 40 467 TB (White)	GW 40 467 TN (Black)	GW 40 467 VT (Titanium)	GW 40 467 VA (Slate)	White RAL 9016 GW 40 467						
	Expansion kit for home network enclosure	-					-						

(*) Without door.

40 CDi RANGE PROTECTED ENCLOSURES IP40	48 PTC RANGE MODULAR WATERTIGHT ENCLOSURES AND BOARDS IP55	40 CDKI RANGE GREEN WALL MODULAR AND PROTECTED ENCLOSURE AND DISTRIBUTION BOARDS FOR PLASTERBOARD - IP40		40 CDE RANGE PROTECTED DISTRIBUTION BOARDS METAL DOOR - IP40		HOME NETWORKING KIT
						
White RAL 9016	Grey RAL 7035	White RAL 9016		White RAL 9016		White RAL 9016
Blank	Smoked transparent	Smoked transparent		Brickwall	Plasterboard	Blank
-	-	-		-	-	-
-	GW 48 686 (prepared to housing N°2 IEC309 socket-outlets)	-		-	-	-
-	-	-		-	-	-
-	GW 48 681	-		-	-	-
GW 40 655	-	-		-	-	-
-	-	-		-	-	-
-	-	-		-	-	-
GW 40 657	GW 48 682	GW 40 605 PM		-	-	-
-	-	-		GW 40 151 N	GW 40 161 N	-
-	-	-		-	-	-
-	-	-		-	-	-
-	-	-		-	-	-
GW 40 659	-	GW 40 606 PM		-	-	-
-	-	-		GW 40 152 N	GW 40 162 N	-
-	-	-		-	-	-
-	-	-		-	-	-
-	-	-		GW 40 153 N GW 40 173 N (*)	GW 40 163 N GW 40 178 N (*)	-
-	-	-		-	-	-
GW 40 661	-	GW 40 609 PM		-	-	Front kit 36M GW 40 390 C Plasterboard box GW 40 688 PM Brickwall box GW 40 688
-	-	-		-	-	
-	-	-		GW 40 154 N GW 40 174 N (*)	GW 40 164 N GW 40 179 N (*)	-
-	-	GW 40 610 PM		-	-	Front kit 54M GW 40 390 F Plasterboard box GW 40 689 PM Brickwall box GW 40 689
-	-	-		-	-	
-	-	-		GW 40 155 N	GW 40 165 N	-
-	-	GW 40 611 PM		-	-	-
-	-	-		-	-	-
-	-	-		-		-
-	GW 48 026 (also more than one)	2 x GW 40 425 PM for 12 M		1 x GW 40 461 N		2 x GW 40 425
GW 48 645	GW 48 645	GW 48 645 for 12 M		-		-
-	-	**Modules**	**Code**	-		-
		24	GW 40 487 (horizontal)			
		36-54-72	GW 40 488 (horizontal)			
-	-	**Modules**	**Code**	-		-
		24	GW 40 495			
		36-54-72	GW 40 496			
1 x GW 40 421 (triangular) from 12M	1 x GW 48 644 (watertight metal cylinder)	**Modules**	**Code**	1 x GW 40 463 (metal cylinder)		1x GW 40 422 (36M) 2x GW 40 422 (54M)
		12-24-36	1 x GW 40 422			
		54-72	2 x GW 40 422			
-	-	-		-		GW 40 688 PM (36M) GW 40 689 PM (54M)
4,5M	4,5M	4,5M		4,5M		-
White RAL 9016 - GW 40 467	Grey RAL 7035 - GW 40 423	White RAL 9016 - GW 40 467		White RAL 9016 - GW 40 467		-
-	-	-		-		GW 38 098

(*) Multimedia enclosure - IP30

Compatibility of flush-mounting enclosures with bipolar and unipolar terminal blocks

Flush-mounting enclosure range	MODULES	Door	Code	Terminal blocks position	SCREW TERMINAL BLOCKS TYPE  TERMINAL BLOCK SIZE 1 Bipolar 125 A 2 x [(1x35)+(7x10)] GW 40 401	Bipolar 80 A 2 x [(2x16)+(7x10)] GW 40 408 B	Unipolar 80 A 1 x [(2x16)+(7x10)] GW 40 408 U
40CDI DECORATIVE ENCLOSURES IP40	8	Smoked transparent	GW 40 225 TB		N° 1	N° 1	N° 1
		Smoked transparent	GW 40 225 TN				
		Smoked transparent	GW 40 225 VT				
		Smoked transparent	GW 40 225 VA				
		Blank	GW 40 285 TB				
	12	Smoked transparent	GW 40 229 TB		N° 1 (*)	N° 1 (*)	N° 1 (*)
		Smoked transparent	GW 40 229 TN				
		Smoked transparent	GW 40 229 VT				
		Smoked transparent	GW 40 229 VA				
		Blank	GW 40 289 TB				
	24 (12x2)	Smoked transparent	GW 40 233 TB		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Smoked transparent	GW 40 233 TN				
		Smoked transparent	GW 40 233 VT				
		Smoked transparent	GW 40 233 VA				
		Blank	GW 40 293 TB				
	36 (12x3)	Smoked transparent	GW 40 239 TB		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Smoked transparent	GW 40 239 TN				
		Smoked transparent	GW 40 239 VT				
		Smoked transparent	GW 40 239 VA				
		Blank	GW 40 299 TB				
40 CDKi PROTECTED MODULAR ENCLOSURES AND DISTRIBUTION BOARDS IP40	8	Smoked transparent	GW 40 604		N° 1	N° 1	N° 1
		Blank	GW 40 884				
	12	Smoked transparent	GW 40 605		N° 1 (*)	N° 1 (*)	N° 1 (*)
		Blank	GW 40 885				
	18	Smoked transparent	GW 40 608		N° 1 (*)	N° 1 (*)	N° 1 (*)
		Blank	GW 40 888				
	24 (12x2)	Smoked transparent	GW 40 606		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Blank	GW 40 886				
	36 (18x2)	Smoked transparent	GW 40 609		N° 2 (*)	N° 2 (*)	N° 2 (*)
		Blank	GW 40 889				
	54 (18x3)	Smoked transparent	GW 40 610		N° 3 (*)	N° 3 (*)	N° 3 (*)
		Blank	GW 40 890				
	72 (18x4)	Smoked transparent	GW 40 611		N° 4 (*)	N° 4 (*)	N° 4 (*)
		Blank	GW 40 891				
40 CDi PROTECTED ENCLOSURES IP40	8	Blank	GW 40 655		N° 1	N° 1	N° 1
	12	Blank	GW 40 657		N° 1 (*)	N° 1 (*)	N° 1 (*)
	24 (12x2)	Blank	GW 40 659		N° 2	N° 2	N° 2
	36 (18x2)	Blank	GW 40 661		N° 2 (*)	N° 2 (*)	N° 2 (*)
40 CDK GREEN WALL ENCLOSURES AND DISTRIBUTION BOARDS FOR PLASTERBOARD WALLS - IP40	12	Smoked transparent	GW 40 605 PM		N° 1 (*)	N° 1 (*)	N° 1 (*)
	24 (12x2)	Smoked transparent	GW 40 606 PM		N° 2 (*)	N° 2 (*)	N° 2 (*)
	36 (18x2)	Smoked transparent	GW 40 609 PM		N° 2 (*)	N° 2 (*)	N° 2 (*)
	54 (18x3)	Smoked transparent	GW 40 610 PM		N° 3 (*)	N° 3 (*)	N° 3 (*)
	72 (18x4)	Smoked transparent	GW 40 611 PM		N° 4 (*)	N° 4 (*)	N° 4 (*)

(*) The installation is allowed using No.1 adapter GW40413 for each terminal block installed.

SCREW TERMINAL BLOCKS TYPE



TERMINAL BLOCK SIZE 2				TERMINAL BLOCK SIZE 3		
Bipolar 125 A 2 x [(3x35)+(10x10)]	**Bipolar 80 A 2 x [(3x16)+(11x10)]**	**Unipolar 80 A 1 x [(3x16)+(11x10)]**	**Unipolar 80 A 1 x [(3x16)+(29x10)]**	**Bipolar 125 A 2 x [(5x35)+(14x10)]**	**Bipolar 80 A 2 x [(3x16)+(17x10)]**	**Unipolar 80 A 1 x [(3x16)+(17x10)]**
GW 40 402	GW 40 412 B	GW 40 412 U	GW 40 422 U	GW 40 404	GW 40 418 B	GW 40 418 U
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 1 (*)	N° 1 (*)	N° 1 (*)	N° 1 (*)	N° 1	N° 1	N° 1
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3	N° 3	N° 3
N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4	N° 4	N° 4
-	-	-	-	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
-	-	-	-	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 1	N° 1	N° 1	N° 1	-	-	-
N° 2	N° 2	N° 2	N° 2	-	-	-
N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2 (*)	N° 2	N° 2	N° 2
N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3 (*)	N° 3	N° 3	N° 3
N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4 (*)	N° 4	N° 4	N° 4

40 CDi

Flush-mounting distribution boards and enclosures



The widest offer of flush-mounting distribution boards and enclosures currently available on the market. Seven families designed to offer advanced solutions in the residential and commercial sector, also available in halogen-free material. Versions from 2 to 72 modules, degree of protection from IP40 to IP55 and special versions for plasterboard. The range includes also two Multimedia Enclosures: Full Version (54 modules) and Compact Version (36 modules).

40 CDI - DECORATIVE ENCLOSURES - IP40



IK 08


IP 40

GWT 650°C





Smoked transparent door



GW 40 229 TB

Decorative enclosures pre-arranged for housing terminal blocks

HF HALOGEN FREE

Code	Colour	Front dim. LxHxD (mm)	Spare base	Dispersible power (W)	Pack Carton
No. of modules EN 50022: 4+1/2					
GW 40 237 TB	White	148x165x23	GW40671	13	12
GW 40 237 TN	Toner black	148x165x23	GW40671	13	12
GW 40 237 VT	Varnished titanium	148x165x23	GW40671	13	12
GW 40 237 VA	Varnished slate	148x165x23	GW40671	13	12
No. of modules EN 50022: 8+1/2					
GW 40 225 TB	White	250x195x26	GW40673	19	16
GW 40 225 TN	Toner black	250x195x26	GW40673	19	16
GW 40 225 VT	Varnished titanium	250x195x26	GW40673	19	16
GW 40 225 VA	Varnished slate	250x195x26	GW40673	19	16
No. of modules EN 50022: 12+1					
GW 40 229 TB	White	330x218x25	GW40674	24	12
GW 40 229 TN	Toner black	330x218x25	GW40674	24	12
GW 40 229 VT	Varnished titanium	330x218x25	GW40674	24	12
GW 40 229 VA	Varnished slate	330x218x25	GW40674	24	12
No. of modules EN 50022: 24+2 (12x2)					
GW 40 233 TB	White	330x338x28	GW40677	25	5
GW 40 233 TN	Toner black	330x338x28	GW40677	25	5
GW 40 233 VT	Varnished titanium	330x338x28	GW40677	25	5
GW 40 233 VA	Varnished slate	330x338x28	GW40677	25	5
No. of modules EN 50022: 36+3 (12x3)					
GW 40 239 TB	White	330x493x28	GW40679	42	5
GW 40 239 TN	Toner black	330x493x28	GW40679	42	5
GW 40 239 VT	Varnished titanium	330x493x28	GW40679	42	5
GW 40 239 VA	Varnished slate	330x493x28	GW40679	42	5

ACCESSORIES SUPPLIED: 6.5 M module-covering profiles co-ordinated with the colour of the enclosure front (for 4, 8 and 12-module enclosures - 1 profile; for 24-module enclosures - 2 profiles; for 36-module enclosures- 3 profiles), circuit labels, mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.

NOTES: Dispersible power calculated according to CEI 23-49.

CHARACTERISTICS: Module-covering profiles can be divided into 1/2 module elements, using scissors.

Mortar guard element assembled by pressing on the base opening. Thermo-pressure with ball equal to 70°C.

IP40 guaranteed even with open door, in the case of wall-embedded installation using devices of at least IP40 and the module-covering profiles supplied.

Bottoms of 8 and 12 module enclosures can be assembled side-by-side using combined coupling element GW40425.

Enclosures composed by front cover;Front of the enclosure and DIN rail frame fully compatible with the bottom of the previous decorative flush mounting enclosures 40CDi Range DIN frame, terminal blocks and back plastic bottom.

INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Blank door



GW 40 293 TB

Decorative enclosures predisposed for housing terminal blocks -White

Code	No. of modules EN 50022	Colour	Outer dim. LxHxD (mm)	Dispersible power (W)	Spare base	Pack Carton
GW 40 287 TB	4	White	146x165x108	13	GW40671	12
GW 40 285 TB	8	White	248x195x107	19	GW40673	16
GW 40 289 TB	12	White	328x218x106	24	GW40674	12
GW 40 293 TB	24 (12X2)	White	328x338x108	25	GW40677	5
GW 40 299 TB	36 (12x3)	White	328x493x118	42	GW40679	5

ACCESSORIES SUPPLIED: 6.5 M module-covering profiles co-ordinated with the colour of the enclosure front (for 4, 8 and 12-module enclosures - 1 profile; for 24-module enclosures - 2 profiles; for 36-module enclosures- 3 profiles), circuit labels, mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: Dispersible power calculated according to CEI 23-49.
CHARACTERISTICS: Module-covering profiles can be divided into 1/2 module elements, using scissors.
Mortar guard element assembled by pressing on the base opening. Thermo-pressure with ball equal to 70°C.
IP40 guaranteed even with open door, in the case of wall-embedded installation using devices of at least IP40 and the module-covering profiles supplied.
Bottoms of 8 and 12 module enclosures can be assembled side-by-side using combined coupling element GW40425.
Enclosures composed by front cover;Front of the enclosure and DIN rail frame fully compatible with the bottom of the previous decorative flush mounting enclosures 40CDi Range DIN frame, terminal blocks and back plastic bottom.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Complementary items for decorative enclosures



GW 41 229 VT

Front covers and relative functional frames with DIN rail for decorative enclosures

Code	Colour	Front dim. LxHxD (mm)	Corresponding back plate	Dispersible power (W)	Pack Carton
No. of modules EN 50022: 4+1/2					
GW 41 237 TB	White	148x165x23	GW40671	13	12
GW 41 237 TN	Black	148x165x23	GW40671	13	12
GW 41 237 VT	Varnished titanium	148x165x23	GW40671	13	12
GW 41 237 VA	Varnished slate	148x165x23	GW40671	13	12
No. of modules EN 50022: 8+1/2					
GW 41 225 TB	White	250x195x26	GW40673	19	16
GW 41 225 TN	Black	250x195x26	GW40673	19	16
GW 41 225 VT	Varnished titanium	250x195x26	GW40673	19	16
GW 41 225 VA	Varnished slate	250x195x26	GW40673	19	16
No. of modules EN 50022: 12+1					
GW 41 229 TB	White	330x218x25	GW40674	24	12
GW 41 229 TN	Black	330x218x25	GW40674	24	12
GW 41 229 VT	Varnished titanium	330x218x25	GW40674	24	12
GW 41 229 VA	Varnished slate	330x218x25	GW40674	24	12
No. of modules EN 50022: 24+2 (12x2)					
GW 41 233 TB	White	330x338x28	GW40677	25	5
GW 41 233 TN	Black	330x338x28	GW40677	25	5
GW 41 233 VT	Varnished titanium	330x338x28	GW40677	25	5
GW 41 233 VA	Varnished slate	330x338x28	GW40677	25	5
No. of modules EN 50022: 36+3 (12x3)					
GW 41 239 TB	White	330x493x28	GW40679	42	5
GW 41 239 TN	Black	330x493x28	GW40679	42	5
GW 41 239 VT	Varnished titanium	330x493x28	GW40679	42	5
GW 41 239 VA	Varnished slate	330x493x28	GW40679	42	5

ACCESSORIES SUPPLIED: 6.5M module-covering profiles co-ordinated with the colour of the enclosure front (for 4, 8 and 12-module enclosures - 1 profile; for 24-module enclosures - 2 profiles; for 36-module enclosures- 3 profiles), service labels.
NOTES: dispersible power calculated according to IEC 60670-24.
CHARACTERISTICS: Module-covering profiles can be divided into 1/2 module elements, using scissors. Thermo-pressure with ball equal to 70°C.
IP40 guaranteed even with open door, in the case of wall-embedded installation using devices of at least IP40 and the module-covering profiles supplied.
Front of the enclosure and DIN rail frame fully compatible with the bottom of the previous decorative flush mounting enclosures 40CDi Range.

40 CDI

Back-mounting boxes for decorative enclosures designed to house a terminal block



GW 40 674

Code	No. of modules EN 50022	Back plate dim. LxHxD (mm)	Pack Carton
GW 40 671	4	115x142x85	12
GW 40 673	8	209x174x81	16
GW 40 674	12	293x189x81	12
GW 40 677	24	294x310x80	5
GW 40 679	36	294x461x90	5

ACCESSORIES SUPPLIED: Mortar guard element in cardboard with clip-fixing on the opening of the back-mounting box - supplied as standard and packed with paper banding.
CHARACTERISTICS: there is an identification code on the back-mounting box, along with the word "up" to aid installation.

40 CDKI - PROTECTED MODULAR ENCLOSURES AND DISTRIBUTION BOARDS - IP40













Smoked transparent door



GW 40 602

Enclosures predisposed for terminal block housing with extractable frame - White RAL 9016

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 601	2	83x160x74	12	60
GW 40 602	4	120x160x85	18	36
GW 40 603	6	200x170x85	19	21
GW 40 604	8	240x195x85	20	12
GW 40 605	12	330x270x85	36	8
GW 40 608	18	465x310x85	50	4

CHARACTERISTICS: GW40601, provided without the door and with the DIN rail fixed directly on the back plate.
Thermo-pressure with ball equal to 70 °C.
Flush-mounting boxes in 12 and 18 modules can be assembled side-by-side through the coupling tool code GW40425.
ACCESSORIES SUPPLIED: Module masks, circuit labels.
For GW40604, GW40605 and GW40608, self-adhesive labels to be filled out for certification according to standard CEI 23-51.
NOTES: Dissipated power calculated according to CEI 23-49.
Upon request, starting from the 8 modules version, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.
INSTALLATION: For the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.



GW 40 604 BS

Enclosures equipped with 80 A IP20 bipolar screw terminal block and extractable frame - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 604 BS	8	240x195x85	20	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	12
GW 40 605 BS	12	330x270x85	36	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	8
GW 40 608 BS	18	465x310x85	50	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	4

CHARACTERISTICS: Thermo-pressure with ball equal to 70°C. Bottoms of 12 and 18 module enclosures can be assembled side-by-side using combined coupling element GW40425.
ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive labels to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.



GW 40 606

Distribution boards with windowed panel and extractable frame predisposed for terminal block housing - White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 606	24 (12X2)	330x420x85	37	6
GW 40 609	36 (18x2)	465x505x85	52	3
GW 40 610	54 (18x3)	465x680x95	62	2
GW 40 611	72 (18x4)	465x880x95	95	1

ACCESSORIES SUPPLIED: Module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.

NOTES: Dissipated power calculated according to CEI 23-49.

Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.

CHARACTERISTICS: Lead sealable and removable panels with windows. Thermo-pressure with ball equal to 70 °C.

Flush-mounting boxes can be assembled side-by-side through the coupling tool code GW40425.

INSTALLATION: For the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.



GW 40 606 BD

Distribution boards with windowed and 80 A IP20 bipolar screw terminal block and extractable frame White RAL 9016

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 606 BS	24 (12X2)	330x420x85	37	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	6
GW 40 606 BD	24 (12X2)	330x420x85	37	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	6
GW 40 609 BS	36 (18x2)	465x505x85	52	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	3
GW 40 609 BD	36 (18x2)	465x505x85	52	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	3
GW 40 610 BD	54 (18x3)	465x680x95	62	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 610 BT	54 (18x3)	465x680x95	62	N/E 3x[(3x16) + (17x10)]	N/E 3x[(3x16) + (17x10)]	2
GW 40 611 BD	72 (18x4)	465x855x95	95	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 611 BQ	72 (18x4)	465x880x95	95	N/E 4x[(3x16) + (17x10)]	N/E 4x[(3x16) + (17x10)]	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.

NOTES: dispersible power calculated according to CEI 23-49. Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.

CHARACTERISTICS: removable and plumbable panels with windows. Thermo-pressure with ball equal to 70°C. Bottoms of enclosures can be assembled side-by-side using combined coupling element GW40425.

Blank door

Enclosures predisposed for terminal block housing and extractable frame - White RAL 9016



GW 40 885

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 882	4	120x160x85	18	36
GW 40 883	6	200x170x85	19	21
GW 40 884	8	240x195x85	20	12
GW 40 885	12	330x270x85	36	8
GW 40 888	18	465x310x85	50	4

ACCESSORIES SUPPLIED: Module masks, circuit labels.
For GW40884, GW40885 and GW40888, self-adhesive labels to be filled out for certification according to standard CEI 23-51.
NOTES: Dissipated power calculated according to CEI 23-49. Upon request, starting from the 8 modules version, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.
CHARACTERISTICS: Thermo-pressure with ball equal to 70 °C.
Flush-mounting boxes in 12 and 18 modules can be assembled side-by-side through the coupling tool code GW40425.
INSTALLATION: For the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Enclosures equipped with 80 A IP20 bipolar screw terminal block and extractable frame - White RAL 9016



GW 40 885 BS

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 884 BS	8	240x195x85	20	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	12
GW 40 885 BS	12	330x270x85	36	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	8
GW 40 888 BS	18	465x310x85	50	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	4

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive labels to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.
CHARACTERISTICS: thermo-pressure with ball equal to 70°C. Bottoms of 12 and 18 module enclosures can be assembled side-by-side using combined coupling element GW40425.

Distribution boards windowed panels and extractable frame predisposed for housing the terminal blocks- White RAL 9016



GW 40 890

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 886	24 (12X2)	330x420x85	37	6
GW 40 889	36 (18x2)	465x505x85	52	3
GW 40 890	54 (18x3)	465x680x95	62	2
GW 40 891	72 (18x4)	465x880x95	95	1

ACCESSORIES SUPPLIED: Module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
NOTES: Dissipated power calculated according to CEI 23-49.
Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.
CHARACTERISTICS: Lead sealable and removable panels with windows. Thermo-pressure with ball equal to 70 °C.
Flush-mounting boxes can be assembled side-by-side through the coupling tool code GW40425.
INSTALLATION: For the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Distribution boards with windowed panels and 80 A IP20 bipolar screw terminal block and extractable frame White RAL 9016



GW 40 890 BT

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pole 1 (mm²)	Pole 2 (mm²)	Pack Carton
GW 40 886 BS	24 (12X2)	330x420x85	37	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	6
GW 40 886 BD	24 (12X2)	330x420x85	37	N/E 2x[(3x16) + (11x10)]	N/E 2x[(3x16) + (11x10)]	6
GW 40 889 BS	36 (18x2)	465x505x85	52	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	3
GW 40 889 BD	36 (18x2)	465x505x85	52	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	3
GW 40 890 BD	54 (18x3)	465x680x95	62	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	2
GW 40 890 BT	54 (18x3)	465x680x95	62	N/E 3x[(3x16) + (17x10)]	N/E 3x[(3x16) + (17x10)]	2
GW 40 891 BD	72 (18x4)	465x855x95	95	N/E 2x[(3x16) + (17x10)]	N/E 2x[(3x16) + (17x10)]	1
GW 40 891 BQ	72 (18x4)	465x880x95	95	N/E 4x[(3x16) + (17x10)]	N/E 4x[(3x16) + (17x10)]	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51. Insulated bipolar screw 80A - IP20 terminal blocks to be installed on the frame before wiring.
NOTES: dispersible power calculated according to CEI 23-49. Upon request, flush-mounting boxes and cabinets (including frame and DIN rails) can be supplied separately.
CHARACTERISTICS: removable and plumbable panels with windows. Thermo-pressure with ball equal to 70°C. Bottoms of enclosures can be assembled side-by-side using combined coupling element GW40425.

Antibacterial front kit



GW 41 890 AB

Distribution front kit windowed panels and extractable frame predisposed for housing the terminal blocks - White RAL 9016 - Antibacterial

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 41 885 AB	12	330x270x16	36	12
GW 41 886 AB	24 (12X2)	330x420x16	37	5
GW 41 889 AB	36 (18x2)	465x505x16	52	3
GW 41 890 AB	54 (18x3)	465x680x25	62	2
GW 41 891 AB	72 (18x4)	465x880x25	95	1

ACCESSORIES SUPPLIED: module masks, circuit labels. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
NOTES: dissipated power calculated according to CEI 23-49. The antibacterial front kit is composed of frame, door, lock covers, opening handles. The kit includes also functional frame and DIN rails.
CHARACTERISTICS: lead sealable and removable panels with windows. Thermo-pressure with ball equal to 70 °C. Flush-mounting boxes can be assembled side-by-side through the coupling tool code GW40425.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING GREEN WALL ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" at the beginning of the section.



GW 40 689

Flush-mounting back box for Antibacterial front kit - For brick wall

Code	No. of modules EN 50022	Suitable for ANTIBACTERIAL front kit	Pack Carton
GW 40 685	12	GW41885AB	1/12
GW 40 687	24 (12X2)	GW41886AB	1/5
GW 40 688	36 (18x2)	GW41889AB	1/5
GW 40 689	54 (18x3)	GW41890AB	1/3
GW 40 690	72 (18x4)	GW41891AB	1/2

CHARACTERISTICS: back boxes can be coupled with the accessory GW40425.
INSTALLATION: the matching antibacterial front kit must be ordered separately.

40 CDKI GREEN WALL - MULTI-SERVICE SYSTEM ENCLOSURES

Multimedia enclosures



IK 08

IP 40

GWT 650°C

CLASS II

EN 61140

Multimedia enclosure compact version 36 DIN modules - White RAL 9016 - Blank door



GW 40 390 C

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 40 390 C	Front cover, inner frame and accessories 36 DIN modules	465x505x85	1
GW 40 688	Empty masonry bottom for compact multimedia enclosure	-	1/5

APPLICATIONS: the compact multimedia enclosure is the central element of multi-service wiring within the home, allowing the distribution of signals to the various rooms. The compact version is ideal for settings where the available space is limited and a small number of services need to be managed.

CHARACTERISTICS: the product is compliant with the CEI 306-2 Guide. The back of the box has plastic tabs for an easier installation on metal frames and drywall panels. The product can be joined vertically with other enclosures of the CDKi range (minimum size 36 DIN modules) using GW40425 coupling elements.

ACCESSORIES SUPPLIED: the GW40390C is composed of 1 pc front cover with blank door, 1 pc detachable frame with 2 pcs perforated mounting plates (1 pc with 18 Keystone Jack slots), 2 m velcro roll w=16 mm, 4 pcs brackets with screws, 4 pcs self-adhesive cable clips with cable ties, 5 pcs RJ45 Cat.6 keystone jacks.

INSTALLATION: suitable for recessed installation on masonry walls.

Multimedia enclosure compact version 54 DIN modules - White RAL 9016 - Blank door



GW 40 390 F

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 40 390 F	Front cover, inner frame and accessories 54 DIN modules	465x680x95	1
GW 40 689	Empty masonry bottom for full multimedia enclosure	-	1/3

APPLICATIONS: the complete multimedia enclosure is the central element of multi-service wiring within the home, allowing the distribution of signals to the various rooms. The full version is ideal for residential settings where a large number of services and reception/transmission devices need to be managed.

CHARACTERISTICS: the product is compliant with the CEI 306-2 Guide. The back box has plastic tabs for easier installation on metal frames and drywall panels. The product can be joined vertically with other enclosures of the CDKi range (minimum size 36 DIN modules) using GW40425 coupling elements.

ACCESSORIES SUPPLIED: the GW40390F includes of 1 pc front cover with blank door, 1 pc detachable frame with 3 pcs perforated mounting plates (1 pc with 18 Keystone Jack slots), 3 m velcro roll w=16 mm, 6 pcs brackets with screws, 6 pcs self-adhesive cable clips with cable ties, 6 pcs RJ45 Cat.6 data sockets, 6 pcs RJ45-RJ45 Cat.6 Ethernet cable 0.6 m, 1 pc telephone splitter with 5 pcs RJ11 socket and 5 pcs RJ11-RJ45 telephone cables, 1 pc multiple socket.

INSTALLATION: suitable for recessed installation on masonry walls.

40 CDE - GERMAN STANDARD FLUSH-MOUNTING DISTRIBUTION BOARDS

Metal door distribution boards - IP40



GW 40 153 N

Distribution boards for brick walls equipped with bipolar terminal blocks - RAL 9016

Code	No. of modules EN 50022	Pole 1 (mm²)	Pole 2 (mm²)	Dispersible power (W)	Pack Carton
GW 40 151 N	12+2	N (2x16)+(8x10)	PE (2x16)+(8x10)	60	1
GW 40 152 N	24+4 (12x2)	N (2x16)+(14x10)	PE (2x16)+(14x10)	80	1
GW 40 153 N	36+6 (12x3)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	90	1
GW 40 154 N	48+8 (12x4)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	100	1
GW 40 155 N	60+10 (12x5)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	120	1

Accessories supplied: positioning brackets, mortar guard, certification label, modules cover, terminal blocks.
Notes: extractable frame already installed.



GW 40 161 N

Distribution boards for plasterboard (GWT 850 °C) walls equipped with bipolar terminal blocks - RAL 9016

Code	No. of modules EN 50022	Pole 1 (mm²)	Pole 2 (mm²)	Dispersible power (W)	Pack Carton
GW 40 161 N	12+2	N (2x16)+(8x10)	PE (2x16)+(8x10)	60	1
GW 40 162 N	24+4 (12x2)	N (2x16)+(14x10)	PE (2x16)+(14x10)	80	1
GW 40 163 N	36+6 (12x3)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	90	1
GW 40 164 N	48+8 (12x4)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	100	1
GW 40 165 N	60+10 (12x5)	N 2x[(2x16)+(14x10)]	PE 2x[(2x16)+(14x10)]	120	1

Accessories supplied: installation brackets, plaster guard, certification label, modules cover, terminal blocks.
Notes: extractable frame already installed.

Metal door multimedia enclosure - IP40



GW 40 173 N

Multimedia enclosures for brick walls - RAL 9016

Code	No. line	Pack Carton
GW 40 173 N	3	1
GW 40 174 N	4	1

Accessories supplied: positioning brackets, mortar guard, 1x multimedia device bracket, 2x Schuko socket, 2x supports, 1x Dahlia plate
Notes: perforated mounting plates and patch panel already installed.



GW 40 178 N

Multimedia enclosures for plasterboard (GWT 850 °C) walls - RAL 9016

Code	No. line	Pack Carton
GW 40 178 N	3	1
GW 40 179 N	4	1

Accessories supplied: installation brackets, plaster guard, 1x multimedia device bracket, 2x Schuko socket, 2x supports, 1x Dahlia plate
Notes: perforated mounting plates and patch panel already installed.

Complementary items

Terminal blocks



GW 40 454 N

Code	Description	Pack Carton
GW 40 454 N	N+PE terminal block (2x16 mm² + 14x10 mm²)	1
GW 40 455 N	Terminal block N (7x16mm²)	1

Accessories

GW 40 467

Code	Description	Pack Carton
GW 40 461 N	Pair of brackets for horizontal coupling	1
GW 40 463 N	Safety lock for German standard flush-mounting enclosures	1
GW 40 467	Plastic module cover profile	50

40 CDI - PROTECTED ENCLOSURES - IP40



IK 08

IP 40

GWT 650°C





Blank door



GW 40 655

Enclosures predisposed for terminal block - White RAL 9016

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Dispersible power (W)	Pack Carton
GW 40 655	8	236x195x89	19	18
GW 40 657	12+1	326x217x89	26	8
GW 40 659	24+2 (12x2)	326x346x89	36	6
GW 40 661	36+2 (18x2)	453x396x95	47	3

ACCESSORIES SUPPLIED: module masks, circuit labels, spare hinges. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
GW40657, GW40659, GW40661 door equipped with lock, with 2 triangular keys.
NOTES: Dispersible power calculated according to CEI 23-49.
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

48 PTC - COMBINATION WATERTIGHT ENCLOSURES AND BOARDS - IP55



IK 08

IP 55

GWT 650°C





Modular enclosures with smoked transparent door



GW 48 681


Watertight flush-mounting modular enclosures with shockproof fronts - Grey RAL 7035

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Front dim. LxH (mm)	Dispersible power (W)	Pack Carton
GW 48 681	6	138x169x70	175x210	15	1/6
GW 48 682	12	308x169x70	345x210	25	1/4

ACCESSORIES SUPPLIED: module masks, user labels, kit of self-tapping stainless steel screws Ø 4x32mm.
mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: dispersible power calculated according to IEC 60670-24.
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026.
Mortar guard element assembled by pressing on the base opening.

Combination board with smoked transparent door



GW 48 686

Watertight flush-mounting combined board fitted for modular devices and for 2 flanges 85x75 mm for mounting IEC 309 standard socket-outlets - shockproof front - Grey RAL 7035

HF HALOGEN FREE

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Front dim. LxH (mm)	Dispersible power (W)	Pack Carton
GW 48 686	4	308x169x70	345x210	19	1/4

ACCESSORIES SUPPLIED: user labels, kit of self-tapping screws of Ø 4 x 32mm in stainless steel. mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: dispersible power calculated according to IEC 60670-24. Compatible with IEC 309 16A 10° angled receptacle.
CHARACTERISTICS: Thermo-pressure with ball equal to 70°C.
pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026. Mortar guard element assembled by pressing on the base opening.

COMPLEMENTARY ITEMS

Installation and coupling



GW 40 467 VT

Module cover profile in plastic - Colours co-ordinated with 40CDi flush-mounting decorative enclosures

Code	Colour	No. of modules EN 50022	Pack Carton
GW 40 467 TB	White	6.5	50
GW 40 467 TN	Black	6.5	50
GW 40 467 VT	Titanium	6.5	50
GW 40 467 VA	Slate	6.5	50

CHARACTERISTICS: clip fixing on the windows of the front. Can be divided into 1/2 module elements, using scissors.



GW 48 645

Kit containing 4 long self-threading screws with spacers for fixing lids and fronts

Code	Screw dimension (mm)	Spacer thickness (mm)	Pack Carton
GW 48 645	Ø 4x45	Max 10 mm reducible	1/100

CHARACTERISTICS: the kit can be used for the following flush-mounting ranges: CD Chorus, CDi/CDKi (from 6 modules upwards), 48 CM and 42 RV.



GW 40 425

Element for combined coupling of CDKi and CDi flush-mounting decorative enclosures and distribution boards

Code	Fixing	Pack Carton
GW 40 425	Clip	10

APPLICATIONS: for CDKi enclosures and boards from 12 modules upwards. Also suitable for 40 CDi decorative enclosures with 8 and 12 modules and for the Home Networking enclosure.
NOTE: GWT 850° C according to EN 60695-2-11.



GW 40 479

Anti-deformation bracket for walling base boxes of CDKi boards

Code	For boards EN 50022 rail	Pack Carton
GW 40 479	18 Modules	5

APPLICATIONS: avoid back-mounting box deformations during masonry work.




GW 48 026

PTC box coupling adaptor

Code	Description	Pack Carton
GW 48 026	Base box coupling	5/25

APPLICATIONS: allows the creation of vertical/horizontal combined compositions and easier cable passage.



GW 70 009

Galvanized steel extending brackets for rear fixing complete with self-tapping screws - Set of 4 brackets - 70 RT range

Code	Adjustament range	Pack Carton
GW 70 009	90 - 160 mm	1/10

APPLICATIONS: when creating upright columns, it allows the creation of an air gap for the passage of conduits between the PTC box and the wall.

Wiring



GW 40 412 B

Insulated screw terminal block bipolar and unipolar for enclosures and boards

Code	Pole 1 (mm²)	Pole 2 (mm²)	Fastener to supports	Pack Carton
Type: Bipolar - Rated current 125 A				
GW 40 401	N (1x35) + (7x10)	E (1x35) + (7x10)	With screws	10
GW 40 402	N (3x35) + (10x10)	E (3x35) + (10x10)	With screws and/or clip	10
GW 40 404	N (5x35) + (14x10)	E (5x35) + (14x10)	With screws and/or clip	10
Type: Bipolar - Rated current 80 A - IP20				
GW 40 408 B	N/E (2x16) + (7x10)	N/E (2x16) + (7x10)	With screws	1/10
GW 40 412 B	N/E (3x16) + (11x10)	N/E (3x16) + (11x10)	With screws and/or clip	1/10
GW 40 418 B	N/E (3x16) + (17x10)	N/E (3x16) + (17x10)	With screws and/or clip	1/10
Type: Unipolar - Rated current 80 A - IP20				
GW 40 408 U	N/E (2x16) + (7x10)	-	With screws	1/10
GW 40 412 U	N/E (3x16) + (11x10)	-	With screws and/or clip	1/10
GW 40 418 U	N/E (3x16) + (17x10)	-	With screws and/or clip	1/10
GW 40 422 U	N/E (3x16) + (29x10)	-	With screws and/or clip	1/10

ACCESSORIES SUPPLIED: fixing screws. The 80 A terminal blocks are equipped with N and E labels to be placed on the respective spaces to identify the poles.

CHARACTERISTICS: GWT 960°C according to EN60695-2-11.

INSTALLATION: for the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Adapters for screw terminal blocks

Code	Material	For enclosures	Fastener to supports	Pack Carton
GW 40 413	Metal	12 M (and multiples) and 18 M (and multiples)	With screws	20




GW 40 413

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: the adapter is pre-drilled for the correct assembly of the terminal block and pre-cut to allow installation also in enclosures with a 12 M modular step.
INSTALLATION: used to expand the number of the possible enclosure-terminal block combinations, refer to the summary "COMPATIBILITY OF FLUSH-MOUNTING ENCLOSURES WITH BIPOLAR AND UNIPOLAR TERMINAL BLOCKS" in the selection guides of 40CDi range.

Internal horizontal dividers for CDKi distribution boards

Code	For boards EN 50022 rail	Fixing	Pack Carton
GW 40 487	12 Modules	Clip	10/100
GW 40 488	18 Modules	Clip	10/100



GW 40 488

NOTES: they permit making internal separation between the circuits having different voltages located on more than one row inside the same shell.

Blank covering panels - 1-module height - for CDKi boards

Code	Suitable for	For boards EN 50022 rail	Colour	Pack Carton
GW 40 495	Flush mounting distr. boards	12 Modules	White RAL 9016	20
GW 40 496	Flush mounting distr. boards	18 Modules	White RAL 9016	20



GW 40 495

CHARACTERISTICS: sealing.

Watertight lids for combined enclosure 48 PTC range, of the GW48686 type

Code	Dimensions LxH (mm)	Suitable for	Colour	Pack Carton
GW 66 708	75x85	1 Button Ø22 mm Range 74 PS	Grey	1/20
GW 66 745	75x85	1 Button Ø22 mm Range 74 PS	Yellow	1/20
GW 27 403	75x85	2 SYSTEM modules	Grey RAL 7035	3/60
GW 27 401	75x85	2 SYSTEM modules	Grey RAL 7035	3/60



GW 66 745

APPLICATIONS: GW66745 specific for emergency push-buttons. Possibility of assembly on Q-DIN boards, PTC junction boxes, flanged lids and panels.
ACCESSORIES SUPPLIED: gasket and mounting screws.

Others

Triangular security key - for 40CDi enclosures protected with a blank door



GW 40 421

Code	Material	Pack Carton
GW 40 421	Insulation	10/100

Cylinder security lock - for 40 CDKi and 40 CDi decorative enclosures



GW 40 422

Code	Material	Pack Carton
GW 40 422	Pressure die-cast metal	1/10

APPLICATIONS: for all the 40 CDKi with door, for the decorative 40 CDi with 24 and 36 modules and for QDSA.
ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

Watertight cylindrical security lock



GW 48 644

Code	For enclosures	Material	Pack Carton
GW 48 644	48 PTC and 42 RV range	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.
NOTES: All the keys and relative locks with the same product code are identical.

Plastic module cover profile

GW 40 467

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 467	4.5	White RAL 9016	50
GW 40 423	4.5	Grey RAL 7035	50
GW 40 468	4.5	Toner black	50

CHARACTERISTICS: clip fixing.

Technical accessories for home networking enclosures



GW 38 098

Telephone jack expansion kit

Code	Description	Pack Carton
GW 38 098	RJ11 telephone socket and telephone cable	1

ACCESSORIES SUPPLIED: 1 multiple telephone socket-outlet with 5 RJ11 socket-outlets.



40 CDI



Scan the QR Code and find out all the technical informations.

40 CDI - DECORATIVE ENCLOSURES



The enclosures feature a modern, elegant and linear design that matches the shapes and colours of the ChoruSmart wiring devices. Available in four colours, the white version is available with smoked transparent or blank doors.

40 CDKI - PROTECTED ENCLOSURES AND DISTRIBUTION BOARDS



The 40 CDKi enclosures and distribution boards come in 10 sizes (from 2 to 72 modules) and various models, available in smoked transparent door versions (particularly suitable for the tertiary and industrial sectors) and with blank doors ideal for home automation applications.

MULTIMEDIA ENCLOSURES FOR MULTISERVICE SYSTEMS



The offer is completed by the multimedia enclosures, which contain and sort the services and optical signals intended for the apartment, hosting the passive components (apartment termination box, mixers, filters) and active devices (modems, switches, signal amplifiers) of the home system.

Accessories

48 PT / PT DIN and 48 PTC:
cardboard mortar guard element supplied

48 CM:
protective technopolymer shield supplied

RANGE	Code		Dimensions (mm)	Protective shield	No. of internal dividers	Coupling element	Boxes	Spare lids		
								Antibacterial	Plain	Deep
										
48 PT / PT DIN	GW 48 001		92x92x45	-	-	-	-	-	IP40 GW 48 013	-
	GW 48 002		118x96x50	-	-	-	-	-	IP40 GW 48 014	-
	GW 48 003		118x96x70	-	-	2 x GW 48 051	-	-	IP40 GW 48 014	-
	GW 48 004		152x98x70	-	-	2 x GW 48 051	-	-	IP40 GW 48 015	IP40 GW 48 084
	GW 48 005		160x130x70	-	-	2 x GW 48 051	-	-	IP40 GW 48 016	IP40 GW 48 085
	GW 48 006		196x152x70	1 x GW 48 006 P	1 x GW 48 012	2 x GW 48 051	Brickwall GW 48 116 Plasterboard GW 48 116 PM	IP40 - IK10 GW 48 017 AB	IP40 - IK10 GW 48 017	IP40 GW 48 086
	GW 48 007		294x152x70	1 x GW 48 007 P	2 x GW 48 012	2 x GW 48 051	Brickwall GW 48 117 Plasterboard GW 48 117 PM	IP40 - IK10 GW 48 018 AB	IP40 - IK10 GW 48 018	IP40 GW 48 087
	GW 48 008		392x152x70	1 x GW 48 008 P	3 x GW 48 012	2 x GW 48 051	Brickwall GW 48 118 Plasterboard GW 48 118 PM	IP40 - IK10 GW 48 019 AB	IP40 - IK10 GW 48 019	IP40 GW 48 088
	GW 48 009		480x160x70	1 x GW 48 009 P	2 x GW 48 012	2 x GW 48 051	Brickwall GW 48 119 Plasterboard GW 48 119 PM	IP40 - IK10 GW 48 020 AB	IP40 - IK10 GW 48 020	-
	GW 48 010		516x202x80	1 x GW 48 010 P	2 x GW 48 012	2 x GW 48 051	-	-	IP40 - IK10 GW 48 021	-
	GW 48 011		516x294x80	1 x GW 48 011 P	5 supplied	2 x GW 48 051	-	-	IP40 - IK10 GW 48 022	-
48 CM	GW 48 207		260x260x121	-	1 supplied	2 supplied	-	-	IP44 GW 48 247	IP44 GW 48 267
	GW 48 211		520x260x121	-	4 supplied	2 supplied	-	-	IP44 GW 48 251	IP44 GW 48 271
	GW 48 227		260x260x121	-	2 supplied	2 supplied	-	-	IP44 GW 48 247	IP44 GW 48 267
	GW 48 231		520x260x121	-	5 supplied	2 supplied	-	-	IP44 GW 48 251	IP44 GW 48 271
48 PTC - IP 40	GW 48 661		138x169x70	-	-	In-line coupling connector GW 48 026	-	-	GW 48 611	-
	GW 48 662		308x169x70	-	1 x GW 48 024				GW 48 612	-
	GW 48 663		398x169x70	-	2 x GW 48 024				GW 48 613	-
48 PTC - IP 55	GW 48 671		138x169x70	-	-				GW 48 621	-
	GW 48 691								GW 48 651	
	GW 48 672		308x169x70	-	1 x GW 48 024				GW 48 622	-
	GW 48 673		398x169x70	-	2 x GW 48 024				GW 48 623	-

Terminal blocks

Multi-pole feedthrough			Single-pole equipotential							
GW 44 609 GW 44 610	GW 44 611	GW 44 613	GW 44 704	GW 44 706	GW 44 708	GW 44 671	GW 44 672	GW 44 673	GW 44 675	GW 44 676
GW 44 610 C	GW 44 612	GW 44 614						GW 44 674		
										
●	-	-	●	●	●	●	●	-	-	-
●	●	-	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	●	-
●	●	-	●	●	●	●	●	●	-	-
●	●	-	●	●	●	●	●	●	-	-
●	●	-	●	●	●	●	●	●	-	-
●	●	-	●	●	●	●	●	●	-	-
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	●	●
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	●	-
●	●	●	●	●	●	●	●	●	●	-

Compatibility between GEWISS domotic devices and 48 PT DIN range boxes

The PT DIN boxes for domotics establish a new market standard in the world of domotic Home & Building Automation systems, as they allow you to distribute the domotic devices in the key points of the building; this widens the advantages of domotics, producing innovative solutions while optimising resources and reducing wiring.
The following table shows all the possible combinations - in terms of dimensions and dispersible power - of individual Gewiss domotic devices and individual PT DIN compartment.

GEWISS DOMOTIC DEVICES		48 PT DIN BOXES						
		Code	GW 48 006	GW 48 007	GW 48 008	GW 48 009	GW 48 010	GW 48 011
		Compartments	2	3	4	3	3	6
		No. of EN 50022 modules per compartment	4,5	5	5	8	9	4
		No. mod. EN 50022 / MAX pde (W)	11	13	17	25	29	30
KNX DEVICES FROM DIN RAIL	KNX line/field couplers	2	●	●	●	●	●	●
	KNX power supplies	4	●	●	●	●	●	●
	KNX motor control actuators	4	●	●	●	●	●	●
		8					●	
	KNX dimmer	4	●	●	●	●	●	●
	KNX general actuators	4	●	●	●	●	●	●
		8				●	●	
	DALI/KNX Gateway	4	●	●	●	●	●	●
	KNX input modules	4	●	●	●	●	●	●
	Combined devices	4	●	●	●	●	●	●
	KNX BUS interfaces	1	●	●	●	●	●	●
DOMOTIC DEVICES FOR DOMESTIC RANGES	KNX domestic range actuators	3	●	●	●	●	●	●
	Relay	1,5 and 3	●	●	●	●	●	●

48

Flush-mounting junction and modular boxes range



The system is composed of three ranges:
48 PT / 48 PT DIN Range with moulded DIN rail, compliant to CEI 23-48, suitable to install also H&B devices; 48 CM Range composed of high-capacity junction boxes, suitable to create distribution columns; 48 PTC Range composed of modular junction, control and distribution boxes. All boxes are made with Halogen Free technopolymer.

48 PT / PT DIN - JUNCTION, CONNECTION AND DOMOTIC BOXES - IP40



IK 07

IP 40

GWT 650°C



For brick walls



GW 48 004

48 PT - Junction and connection boxes for side-by-side assembly - White lid RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Pack Carton
GW 48 001	92x92x45	1	162
GW 48 002	118x96x50	1	114
GW 48 003	118x96x70	1	84
GW 48 004	152x98x70	1	64
GW 48 005	160x130x70	1	49

CHARACTERISTICS: surface embossing of the lids to facilitate painting.
External knurling of the base to improve mortar adherence.
Pre-arrangement for combined coupling (both horizontal and vertical) via the joining element GW48051.
Lid protected with heat-shrinking film that also contains the bag of fixing screws.
Mortar guard element assembled by pressing on the base opening.
ACCESSORIES SUPPLIED: ø3x25 mm screw kit for lid fixing. mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors.



GW 48 006

48 PT DIN - Junction and connection boxes for side-by-side assembly with DIN rail integrated on the back-mounting box Colour: White lid RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	No. EN 50022 mod. per comp.	Domotic equipment coupling	Dispersible max power (W)	No. supports GW44720	Pack Carton
GW 48 006	196x152x75	2	4.5	DIN rail	11	2	34
GW 48 007	294x152x75	3	5	DIN rail	13	3	22
GW 48 008	392x152x75	4	5	DIN rail	17	4	17
GW 48 009	480x160x75	3	8	DIN rail	25	5	17
GW 48 010	516x202x90	3	9	DIN rail	29	5	9
GW 48 011	516x294x90	6	4	DIN rail	30	5	5

APPLICATIONS: boxes with a built-in DIN rail on the back-mounting box, in accordance with regulations that require to fix by DIN rail the devices that disperse a certain amount of power inside the junction boxes (calculated in compilance with CEI 23-49). Ideal for installation of home and building automation equipment as actuators, power supplies, etc.
CHARACTERISTICS: surface embossing of the covers to facilitate painting. External knurling of the base to improve mortar adherence. Pre-arrangement for combined coupling (both horizontal and vertical) via the joining element GW48051. Lid protected with heat-shrinking film that also contains the bag of fixing screws. Mortar guard element assembled by pressing on the base opening.
ACCESSORIES SUPPLIED: Junction box GW48011 supplied with 5 internal separators. ø 3x25mm screw kit for lid fixing. Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors.

Antibacterial shockproof lids



GW 48 017 AB

Antibacterial shockproof lids for PT / PT DIN and PT DIN Green Wall boxes white RAL 9016 - IP40

Code	Suitable for	Mechanical resistance	Pack Carton
GW 48 017 AB	GW48116 and GW48116PM	IK10	1/50
GW 48 018 AB	GW48117 and GW48117PM	IK10	80/40
GW 48 019 AB	GW48118 and GW48118PM	IK10	1/20
GW 48 020 AB	GW48119 and GW48119PM	IK10	1/20

CHARACTERISTICS: the packaging includes screws for installation in brick walls or plasterboard walls. GWT 850 °C according to EN 60695-2-11.



GW 48 116

Flush-mounting back boxes for Antibacterial shockproof lids - For brick wall

Code	Suitable for	Pack Carton
GW 48 116	GW48017AB	30
GW 48 117	GW48018AB	20
GW 48 118	GW48019AB	10
GW 48 119	GW48020AB	10

NOTE: the Antibacterial shockproof lid must be ordered separately.

COMPLEMENTARY ITEMS FOR 48 PT / PT DIN E 48 PT DIN GREEN WALL

Complementary items



GW 48 007 P

Protective shield for junction, connection and domotics boxes

Code	For boxes PT DIN	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 006 P	GW48006	GW48006PM and GW48126PM	70
GW 48 007 P	GW48007	GW48007PM	60
GW 48 008 P	GW48008	GW48008PM	50
GW 48 009 P	GW48009	GW48009PM	40
GW 48 010 P	GW48010	-	30
GW 48 011 P	GW48011	-	25

CHARACTERISTICS: in technopolymer. Total protection during brick wall work, painting and finishing operations. Applying the protective shield beneath the lid, the dispersible power of the box is reduced by 2 W for GW48006, GW48007, GW48008, GW48010, GW48011, GW48006PM, GW48007PM, GW48008PM boxes and by 3W GW48009 and GW48009PM boxes.
NOTES: clip fixing to speed up assembly and removal operations. Reusable.



GW 48 051

Joining element for PT / PT DIN and PT DIN GREEN WALL boxes

Code	For PT / PT DIN boxes	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 051	GW48003 - GW48011	GW48006PM - GW48009PM	10

NOTES: the use of the joining element makes it possible to create horizontal and/or vertical sets of boxes PT/PT DIN. For PT DIN GREEN WALL boxes, GW40425 element permits horizontal paths. GW48051 also for the box with transparent lid GW48126PM. GWT 850 °C according to EN 60695-2-11.

Internal separator for PT DIN and PT DIN GREEN WALL boxes



GW 48 012

Code	For boxes PT DIN	For PT DIN GREEN WALL boxes	Pack Carton
GW 48 012	GW48006 - GW48011	GW48006PM - GW48009PM	50/300

High resistance shockproof plain lids for PT / PT DIN and PT DIN GREEN WALL boxes - White RAL 9016 - IP40



GW 48 018

Code	Suitable for	Mechanical resistance	Pack Carton
GW 48 013	GW48001	IK10	10/120
GW 48 014	GW48002 - GW48003	IK10	10/100
GW 48 015	GW48004	IK10	10/100
GW 48 016	GW48005	IK10	10/100
GW 48 017	GW48006 and GW48006PM	IK10	10/100
GW 48 018	GW48007 and GW48007PM	IK10	10/80
GW 48 019	GW48008 and GW48008PM	IK10	10/40
GW 48 020	GW48009 and GW48009PM	IK10	10/40
GW 48 021	GW48010	IK10	10/30
GW 48 022	GW48011	IK10	10/20

CHARACTERISTICS: surface embossing of the covers to facilitate painting. GWT 850 °C according to EN 60695-2-11.

Deep lids for PT / PT DIN and PT DIN GREEN WALL boxes - White RAL 9016 - IP40



GW 48 084

Code	Suitable for	Pack Carton
GW 48 084	GW48004	1/10
GW 48 085	GW48005	1/8
GW 48 086	GW48006 and GW48006PM	1/10
GW 48 087	GW48007 and GW48007PM	1/5
GW 48 088	GW48008 and GW48008PM	1/5

CHARACTERISTICS: the deep lids are ideal for passing from an exposed system to a chased one. They have a removable front plate and a frame for connecting with trunking.
GWT 850 °C secondo EN 60695-2-11; max lid H = 66mm for boxes up to 392x152 and conduits with max Ø = 32mm.

Long self-tapping screws for securing cover



GW 48 023

Code	Dimensions (mm)	Suitable for	Pack Carton
GW 48 023	Ø3x38	Junction boxes range 48 PT / PT DIN and PT DIN GREEN WALL	300/4200

44 ME - UNIPOLAR EQUIPOTENTIAL TERMINAL BLOCKS

GWT 850°C

TP 125°C

Terminal blocks for side-by-side assembly



GW 44 706

Terminal blocks with indirect plate tightening - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 704	4 ways x 6 mm²	10/100
GW 44 706	6 ways x 6 mm²	10/100
GW 44 708	8 ways x 6 mm²	10/100

APPLICATIONS: embedded fixing on the GW44720 support, for coupling with the DIN rail.
NOTES: for the connection capacity, refer to the technical catalogue

Accessories for terminal blocks for side-by-side assembly



GW 44 720

Support for fixing side-by-side terminal blocks on DIN rail

Code	For equipotential terminal blocks	Terminal block fixing	Fixing on DIN rail	Pack Carton
GW 44 720	GW44704, GW44706, GW44708	Clip	Lock-joint	1/50

NOTES: ideal for applications on boxes of the 48 PT DIN range.
CHARACTERISTICS: supports a combination of terminal blocks with maximum 12-way capacity.
Possible combinations: 3xGW44704; 2xGW44706; 1xGW44704 + 1xGW44706; 1xGW44704 + 1xGW44708; Modular overall dimensions (width): 4.5 modules EN 50022.

Modular terminal blocks



GW 44 671


Terminal blocks with indirect screw tightening - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 671	3 ways x 6 mm²	10/100
GW 44 672	5 ways x 6 mm²	10/100
GW 44 673	4 ways x 16 mm²	10/50
GW 44 674	2 ways x 16mm² + 3 ways x 6 mm²	10/50
GW 44 675	2 ways x 16mm² + 9 ways x 6 mm²	5/25
GW 44 676	2 ways x 35 mm² + 4 ways x 16 mm²	1/10

APPLICATIONS: especially suitable for creating equipotential nodes.
ACCESSORIES SUPPLIED: self-adhesive label for identification of electrical lines.
NOTES: GW44676 equipped with feedthrough terminals. These allow the creation of cut-outs from the main cables which, unsheathed in the part concerned, are not interrupted.

Accessories for modular terminal blocks

Support for fixing modular terminal blocks on DIN rail



GW 44 681

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 681	From GW44671 to GW44676	Clip	100

Adapter for fixing modular terminal blocks



GW 44 682

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 682	From GW44671 to GW44676	Lock-joint	200

APPLICATIONS: for fixing the equipotential terminal blocks on the plates or directly on the base inside the junction boxes and watertight boxes.
ACCESSORIES SUPPLIED: screws for fixing the adapter.

48 CM - LARGE CAPACITY CONNECTION AND JUNCTION BOXES - IP40




IK 07

IP 40

GWT 650°C



Plain lid




GW 48 207

Junction and connection boxes for side-by-side assembly, for uprights - plain plumbable lid - White RAL 9016

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Dispersible max power (W)	Pack Carton
GW 48 207	260x260x121	2	13	8
GW 48 211	520x260x121	5	30	6

ACCESSORIES SUPPLIED: internal dividers, joint elements for combined assembly, self-adhesive symbol labels for circuit identification, and sealing screws.
Mortar-proof paint protection shield in technopolymer with additional electro-acoustic insulation function, with central handles making it easier to pull it out.
NOTES: applying the protective shield beneath the lid, the dispersible power of the box is reduced by 2W for GW48207 and by 3W for the GW48211 box.
dispersible power calculated according to IEC 60670-24.

Deep lid



GW 48 227

Junction and connection boxes for side-by-side assembly, for uprights - deep plumbable lid - Grey RAL 7035

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Dispersible max power (W)	Pack Carton
GW 48 227	260x260x121	2	13	4
GW 48 231	520x260x121	5	30	4

CHARACTERISTICS: the lid has a removable front plate and a frame for the connection with the trunking (max height = 66mm) and conduits (max Ø = 40mm).
The frame is fitted for fixing the DIN rails (not supplied).
Pre-arrangement EN 50022: GW48227 horizontal - 24 modules (2x12), vertical - 24 modules (2x12); GW48231: horizontal - 78 modules (26x3), vertical - 36 modules (12x3).
ACCESSORIES SUPPLIED: internal dividers, joint elements for combined assembly, self-adhesive symbol labels for circuit identification, and sealing screws.
Mortar-proof paint protection shield in technopolymer with additional electro-acoustic insulation function, with central handles making it easier to pull it out.
NOTES: applying the protective shield beneath the lid, the dispersible power of the box is reduced by 2W for GW48227 and by 3W for the GW48231 box.
dispersible power calculated according to IEC 60670-24.

COMPLEMENTARY ITEMS FOR 48 CM AND 48 CM GREEN WALL

Complementary items



GW 48 251

Shockproof sealable plain lids for boxes for uprights - White RAL 9016 - IP44

Code	Front dim. LxH (mm)	Mechanical resistance	Pack Carton
GW 48 247	260x260	IK10	1/15
GW 48 251	520x260	IK10	1/10

ACCESSORIES SUPPLIED: self-adhesive symbol labels for circuit identification, and plumbable screws.



GW 48 271

Shockproof sealable deep lids for boxes for uprights - Grey RAL 7035 - IP44

Code	For boxes dimensions	Mechanical resistance	Pack Carton
GW 48 267	260x260	IK10	1/10
GW 48 271	520x260	IK10	1/5

CHARACTERISTICS: the lid has a removable front plate and a frame for connection with trunking (max h = 65mm) and conduits (max Ø = 40mm).
The frame is fitted for fixing the DIN rails (not supplied).
Pre-arrangement EN 50022: GW48267 horizontal 24 modules (2x12), vertical 24 modules (2x12); GW48271 horizontal 78 modules (26x3), vertical 36 modules (12x3)
ACCESSORIES SUPPLIED: self-adhesive symbol labels for circuit identification, and plumbable screws.

48 PTC - MODULAR JUNCTIONS, CONTROL AND DISTRIBUTION BOXES



IK 07

GWT 650°C



Boxes with lid - IP55



GW 48 671

Modular, watertight, flush-mounting junction and connection boxes - shockproof lid - Grey RAL 7035

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Pack Carton
GW 48 671	138x169x70	1	1/28
GW 48 672	308x169x70	2	1/14
GW 48 673	398x169x70	3	1/9

ACCESSORIES SUPPLIED: self-adhesive symbol discs for the identification of circuits, kit of Ø 4x32mm stainless steel self-tapping screws, hinge for constrained lid opening.
GW48672 pre-arranged to house a DIN rail. Space available: 14 modules.
Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
CHARACTERISTICS: pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026.
Mortar guard element assembled by pressing on the base opening.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors.
The IP55 degree of protection is guaranteed with the lid closed and with installations on waterproof walls made of tiles or similar materials, without joints.

Boxes with transparent shockproof lid - IP55



GW 48 691

Modular, watertight, flush-mounting junction and connection box - transparent shockproof lid

HF HALOGEN FREE

Code	Outer dim. LxHxD (mm)	Compartment pre-arrangement	Pack Carton
GW 48 691	138x169x70	1	1/28

ACCESSORIES SUPPLIED: self-adhesive symbol discs for the identification of circuits, kit of Ø 4x32mm stainless steel self-tapping screws, hinge for constrained lid opening.
Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
CHARACTERISTICS: pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026.
Mortar guard element assembled by pressing on the base opening.
NOTES: for the inputs, remove the knockouts after cutting the relative tangs with scissors.
The IP55 degree of protection is guaranteed with the lid closed and with installations on waterproof walls made of tiles or similar materials, without joints.
APPLICATIONS: ideal for medical room applications where the earthing point must be inspectable.

Modular enclosures with smoked transparent door - IP55




GW 48 681

Watertight flush-mounting modular enclosures with shockproof fronts - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Front dim. LxH (mm)	Dispersible power (W)	Pack Carton
GW 48 681	6	138x169x70	175x210	15	1/6
GW 48 682	12	308x169x70	345x210	25	1/4

ACCESSORIES SUPPLIED: module masks, user labels, kit of self-tapping stainless steel screws Ø 4x32mm.
Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding. Enclosures with back plastic bottom.
CHARACTERISTICS: pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026.
Mortar guard element assembled by pressing on the base opening.
NOTES: dispersible power calculated according to IEC 60670-24.



GW 48 686

Watertight flush-mounting combined board fitted for modular devices and for 2 flanges 85x75 mm for mounting IEC 309 standard socket-outlets - shockproof front - Grey RAL 7035

Code	No. of modules EN 50022	Outer dim. LxHxD (mm)	Front dim. LxH (mm)	Dispersible power (W)	Pack Carton
GW 48 686	4	308x169x70	345x210	19	1/4

ACCESSORIES SUPPLIED: user labels, kit of self-tapping screws of Ø 4 x 32mm in stainless steel.
Mortar guard element in cardboard supplied as standard in the packs and packed with paper banding.
Enclosures with back plastic bottom.
CHARACTERISTICS: pre-arrangement for combined coupling (both horizontal and vertical) via the feedthrough coupling device GW48026.
Mortar guard element assembled by pressing on the base opening.
NOTES: dispersible power calculated according to IEC 60670-24. Compatible with IEC 309 16A 10° angled receptacle.

Complementary items



GW 48 024

Internal divider for PTC boxes

Code	For boxes dimensions	Pack Carton
GW 48 024	398x169x70 and 308x169x70 mm	10/200

APPLICATIONS: guarantees that circuits of a different nature are separated according to Standard CEI 64-8.




GW 48 026

PTC box coupling adaptor

Code	Description	Pack Carton
GW 48 026	Base box coupling	5/25

APPLICATIONS: allows the creation of vertical/horizontal combined compositions and easier cable passage.



GW 70 009

Galvanized steel extending brackets for rear fixing, complete with self-tapping screws - Set of 4 brackets - 70 RT range

Code	Adjustament range	Pack Carton
GW 70 009	90 - 160 mm	1/10

APPLICATIONS: when creating upright columns, it allows the creation of an air gap for the passage of conduits between the PTC box and the wall.



GW 44 683

Rail for fixing equipotential terminal blocks in the PTC modular flush- mounting boxes

Code	Installable terminal blocks	Pack Carton
GW 44 683	4xGW44671; 3xGW44672; 2xGW44673; 2xGW44674; 1xGW44675	1/50

CHARACTERISTICS: width: 1 compartment. For applications with PTC boxes with 2 and 3 compartments, the rail is fixed on the dividers GW48024.



GW 48 643

Kit for sealing lids / fronts of PTC boxes 2 screws with head with through hole

Code	Description	Screw dimension (mm)	Pack Carton
GW 48 643	Screws nichel-plated brass	Ø 4x32	1/100

APPLICATIONS: in areas that can be accessed by unauthorised personnel, it prevents anyone tampering with the system.



GW 48 645

Kit containing 4 long self-threading screws with spacers for fixing lids and fronts

Code	Screw dimension (mm)	Spacer thickness (mm)	Pack Carton
GW 48 645	Ø 4x45	Max 10 mm reducible	1/100

CHARACTERISTICS: the kit can be used for the following flush-mounting ranges: CD/CDK (from 6 modules upwards), 48 CM and 42 RV.



GW 48 644

Watertight cylindrical security lock

Code	For enclosures	Material	Pack Carton
GW 48 644	48 PTC and 42 RV range	Pressure die-cast metal	1/10

ACCESSORIES SUPPLIED: 2 keys.

NOTES: All the keys and relative locks with the same product code are identical.



GW 66 745

Watertight lids for combined enclosure 48 PTC range, of the GW48686 type

Code	Dimensions LxH (mm)	Suitable for	Colour	Pack Carton
GW 66 708	75x85	1 Button Ø22 mm Range 74 PS	Grey	1/20
GW 66 745	75x85	1 Button Ø22 mm Range 74 PS	Yellow	1/20
GW 27 401	75x85	2 SYSTEM modules	Grey RAL 7035	3/60
GW 27 403	75x85	2 SYSTEM modules	Grey RAL 7035	3/60

APPLICATIONS: GW66745 specific for emergency push-buttons. Possibility of assembly on Q-DIN boards, PTC junction boxes, flanged lids and panels.

ACCESSORIES SUPPLIED: gasket and mounting screws.

Spare parts



GW 48 621

Watertight shockproof lids for PTC junction boxes - RAL 7035 - IP55

Code	For boxes dimensions	Pack Carton
GW 48 621	138x169x70	1/30
GW 48 622	308x169x70	1/20
GW 48 623	398x169x70	1/15

ACCESSORIES SUPPLIED: stainless steel self-tapping screw kit 4x32 mm.




GW 48 651

Protected watertight transparent shockproof lids for PTC junction boxes - I55

Code	For boxes dimensions	Pack Carton
GW 48 651	138x169x70	1/30

ACCESSORIES SUPPLIED: stainless steel self-tapping screw kit 4x32 mm.




GW 40 423

Plastic module cover profile

Code	No. of modules EN 50022	Colour	Pack Carton
GW 40 423	4.5	Grey RAL 7035	50



48



Scan the QR Code and find out all the technical informations.

48 PT / PT DIN BOXES



The range comes in 11 sizes, complete with mortar guard elements, which enable the creation of junctions for all needs. The sizes of boxes from 6 to 11 have a built-in DIN rail on the bottom, a feature that makes the range unique. Dispersible max power can be used to match the value with domotic and video entryphone devices, a feature that makes the range unique in the market.

48 CM BOXES



Thanks to the great depth of the box, all the models in the range are able to accommodate a greater number of conduits, even of large diameter, vertically and horizontally along the walls. The range has ideal features for junctions along the system uprights.


48 PTC BOXES









A system of boxes, enclosures and modular distribution boards for junctions, control and distribution. The IP55 version is the ideal solution in technical rooms, kitchens or spaces where the devices can be accidentally subjected to water jets.

24 SC

Underfloor boxes

UNDERFLOOR OUTLET BOXES				ACCESSORIES		
						
With hollow lid		With stainless steel lid		Metal casing		Kit for installation of devices on DIN rail
10 mod.	20 mod.	10 mod.	20 mod.	10 mod.	20 mod.	
GW 24 601	GW 24 602	GW 24 611	GW 24 612	GW 24 621	GW 24 622	GW 24 633

Flush-mounting boxes for modular range

24 SC RANGE		No. place	CHORUSMART RANGE		SYSTEM RANGE		COMPLEMENTARY ITEMS	
Boxes	Code		Support	Plates	Support	Plates	Internal divider	Lid
RECTANGULAR	GW 24 403	1	 GW 16 802	 ONE - GEO - EGO	 GW 24 201	 TOP SYSTEM - VIRNA	GW 24 321	-
		2	 GW 16 802	 ONE - GEO - EGO - LUX - ICE	 GW 24 262	 TOP SYSTEM - VIRNA		
		3	 GW 16 803 - GW 16 803 N*	 ONE - GEO - EGO - LUX - ICE - ICE TOUCH - ICE TOUCH KNX	 GW 24 201	 TOP SYSTEM - VIRNA		
	GW 24 404	4	 GW 16 804 - GW 16 804 N* GW 16 824	 ONE - GEO - EGO - LUX - ICE	 GW 24 202	 TOP SYSTEM - VIRNA		
	GW 24 406	6	 GW 16 806	 ONE - GEO - LUX - ICE	 GW 24 230	 TOP SYSTEM - VIRNA		
		7	 GW 16 807 N	 EGO	-	-		
	GW 24 237	(4+4)	 GW 16 808	 ONE	 GW 24 240	 TOP SYSTEM - VIRNA	-	-
	GW 24 238	(6+6)	 GW 16 812	 ONE	-	-	-	-
ROUND/SQUARE 	GW 24 231 GW 24 232	1	 GW 16 802	 ONE - GEO - EGO	-	-	-	GW 24 218 **
		2	 GW 16 802	 ONE - GEO - EGO - ICE	-			
			 GW 16 822 - GW 16 822 N*	 ONE - GEO - EGO - LUX (International)	-			

* For EGO SMART
** For round box


24 SC

Flush-mounting, surface and underfloor boxes

Wide range of surface-mounting and flush-mounting boxes for domestic ranges with high mechanical robustness and accessories supplied: dividers, junction elements, mortarguard shield, etc. Completing the range, the distribution outlet boxes for floor-mounting installations can be personalised in terms of capacity, external design finish, and internal fittings (they take both System range components and DIN rail devices).




UNDERFLOOR OUTLET BOXES



GWT 850°C

Underfloor outlet boxes - With supports positioned vertically

Underfloor outlet boxes with hollow lid - Glow wire test 850° C




GW 24 601

Code	Internal modularity	No. of supports	Outer dim. LxHxD (mm)	Pack Carton
GW 24 601	10 SYSTEM modules	2 supports with 5 System mod.	212x98x320	1
GW 24 602	20 SYSTEM modules	4 supports with 5 System mod.	364x98x320	1

CHARACTERISTICS: the supports are suitable for the insertion of plastic mobile dividers (energy/data) included.
The lid can be removed with the aid of a tool, and can be assembled on either side of the box.
The lid can be completed by inserting the same finish as used for the floor of the installation area.

Underfloor outlet boxes with stainless steel lid - Glow wire test 850° C



GW 24 612

Code	Internal modularity	No. of supports	Outer dim. LxHxD (mm)	Pack Carton
GW 24 611	10 SYSTEM modules	2 supports with 5 System mod.	212x98x320	1
GW 24 612	20 SYSTEM modules	4 supports with 5 System mod.	364x98x320	1

CHARACTERISTICS: the supports are suitable for the insertion of plastic mobile dividers (energy/data) included.
The lid can be removed with the aid of a tool, and can be assembled on either side of the box.
The lid has a stainless steel design surface finish.

Underfloor outlet boxes - With supports positioned horizontally

Underfloor outlet boxes with hollow lid - Glow wire test 850° C



GW 24 606

Code	Internal modularity	No. of bases	No. of supports	Outer dim. LxHxD (mm)	Pack Carton
GW 24 606	16 SYSTEM modules	1 base	8 supports with 2 System mod.	212x98x320	1
GW 24 607	32 SYSTEM modules	2 bases	16 supports with 2 System mod.	364x98x320	1

CHARACTERISTICS: each base includes 8 snap-fit System supports.
The base is fixed with screws to the underfloor outlet box.
Plastic dividers (energy/data) are already included in the base.
The lid can be removed with the aid of a tool, and can be assembled on either side of the box.
The lid can be completed by inserting the same finish as used for the floor of the installation area.

Underfloor outlet boxes with stainless steel lid - Glow wire test 850° C



GW 24 616

Code	Internal modularity	No. of bases	No. of supports	Outer dim. LxHxD (mm)	Pack Carton
GW 24 616	16 SYSTEM modules	1 base	8 supports with 2 System mod.	212x98x320	1
GW 24 617	32 SYSTEM modules	2 bases	16 supports with 2 System mod.	364x98x320	1

CHARACTERISTICS: each base includes 8 snap-fit System supports.
The base is fixed with screws to the underfloor outlet box.
Plastic dividers (energy/data) are already included in the base.
The lid can be removed with the aid of a tool, and can be assembled on either side of the box.
The lid has a stainless steel design surface finish.

Accessories

Metal casing



GW 24 622

Code	Suitable for outlet boxes	Pack Carton
GW 24 621	GW24601, GW24611, GW24606, GW24616	1
GW 24 622	GW24602, GW24612, GW24607, GW24617	1

NOTES: suitable for the laying of the underfloor outlet boxes in cast flooring. Supplied with coupling flanges for conduits and channels. With lid.

Kit for installation of devices on DIN rail




GW 24 633

Code	Suitable for outlet boxes	Pack Carton
GW 24 633	GW24601, GW24611, GW24602, GW24612	1/30

CHARACTERISTICS: suitable for the installation of DIN rail devices - max. 2 modules, only for underfloor outlet boxes with supports positioned vertically.
NOTES: the kit includes a DIN rail to be fixed on the back-mounting box of the underfloor outlet box, along with a plastic covering support.

FLUSH-MOUNTING BOXES FOR MASONRY WALLS







Rectangular boxes - BIG BOX

BIG BOX high capacity rectangular boxes for domestic, modular and domotics ranges




GW 24 403

Code	Description	Fixing supports axles distance	Compartment pre-arrangement	Outer dim. LxHxD (mm)	Pack Carton
GW 24 403	3 modules	83.5 mm	3	119x80x50	15/345
GW 24 404	4 modules	108.5 mm	4	144x85x50	5/135
GW 24 406	6-7 modules	100 mm	6	194x90x50	3/36
GW 24 206	6 modules (3+3)	83.5 mm	1	108x124x50	5/150
GW 24 237	8 modules (4+4)	108.5 mm	2	131x129x53	2/24
GW 24 238	12 modules (6+6)	163.5 mm	2	186x132x53	2/24
GW 24 239	18 modules (6+6+6)	163.5 mm	3	186x190x65	2/16

CHARACTERISTICS: GW24403, GW24404 and GW24406 can be combined with a reusable, mortar-proof, protective shield; functional dividers and joint elements.
GW24206: suitable for assembly of GW24005 self-supporting "Compact" plates and GW24215 - GW24216 blank "Compact" plates.
ACCESSORIES SUPPLIED: GW24237, GW24238 and GW24239 include functional dividers.
APPLICATIONS: ideal for use in the Home and Building Automation.
NOTES: GW24239 for PLAYBUS range only.

Mortar-proof protective shields for BIG BOX rectangular boxes



GW 24 403 P

Code	For BIG BOX boxes	Pack Carton
GW 24 403 P	GW24403	200
GW 24 404 P	GW24404	50
GW 24 406 P	GW24406	50

CHARACTERISTICS: in technopolymer. Total protection during brick wall work, painting and finishing operations.
Equipped with soft technopolymer antennas for identification purposes, and a central handle making it easier to pull it out.
NOTES: clip fixing to speed up assembly and removal operations.

Functional divider for rectangular boxes



GW 24 321

Code	For BIG BOX boxes	For GREEN WALL boxes	Pack Carton
GW 24 321	GW24403, GW24404, GW24406	GW24403PM, GW24404PM, GW24406PM	200

APPLICATIONS: to separate circuits of different voltages in accordance with Systems Standard IEC 60364 (international) and HD 384 (european).

Connection element for the combined assembly of BIG BOX rectangular boxes



GW 24 330

Code	For BIG BOX boxes	Pack Carton
GW 24 330	GW24403, GW24404, GW24406	150

APPLICATIONS: for horizontal/vertical composition of BIG BOX boxes from 3/4/6 gang.
NOTES: GW24330 allows for the mounting of System, Playbus and ChoruSmart series plates.

Square box

Modular square box



GW 24 231

Code	Description	Fixing supports axles distance	Outer dim. LxHxD (mm)	Pack Carton
GW 24 231	2 modules sectional	60 mm	70x70x50	5/200

CHARACTERISTICS: fitted for multiple horizontal/vertical configurations, with centre distance 71 mm between the boxes. Supplied with 2 fixing screws.

Round boxes



GW 24 232

Round modular boxes Ø 60mm with columns for the fixing screws

Code	Description	Fixing supports axles distance	Dimensions (mm)	Pack Carton
GW 24 232	Modular round	60 mm	Ø 60 x 42	5/200
GW 24 233	Base/unit spacer for coupling at 91 mm	-	-	20/200

CHARACTERISTICS: GW24232, fitted for single or double installation, with centre distance composition of 71mm (or 91mm with the special spacer available as an accessory).
Supplied with 2 fixing screws.




GW 24 208

Round boxes

Code	Description	Dimensions (mm)	Pack Carton
GW 24 208	Conical	Ø 60 x 46	270
GW 24 209	Cylindrical	Ø 65x38	312
GW 24 210	Cylindrical	Ø 85x42	152

Telephone systems box




GW 24 221

Telephone systems box - Ivory colour lid

Code	Type of installation	Outer dim. LxHxD (mm)	Pack Carton
GW 24 221	Conventional	68x68x30	280

CHARACTERISTICS: entries for conduits Ø 20 mm.

WALL-MOUNTING BOXES







Boxes for CHORUSMART range



GW 16 743

Wall-mounting boxes for mini-trunking and trunking used as skirting for ONE plates

HF HALOGEN FREE

Code	Description	Support	Outer dim. LxHxD (mm)	Pack Carton
Colour: Satin White				
GW 16 743	3 modules	GW16803	118x90x46	3/60
GW 16 744	4 modules	GW16804	140x90x46	1/30
Colour: Satin black				
GW 16 773	3 modules	GW16803	118x90x46	3/30
GW 16 774	4 modules	GW16804	140x90x46	1/30

CHARACTERISTICS: support and plate not included. Use ONE plates (interchangeability with the entire colour range of plates). Pre-arranged for mini-trunking with dimensions BxH (mm): 15x8, 15x10, 22x10, 30x15.
NOTES: fitted for fixing the earth terminal GW26407.



GW 16 752

Wall-mounting boxes for mini-trunking and trunking used as skirting for ONE International plates

HF HALOGEN FREE

Code	Description	Type	Support	Outer dim. LxHxD (mm)	Pack Carton
Colour: Satin White					
GW 16 752	2 modules	-	GW16822	90x90x46	1/30
GW 16 753	2+2 modules	Horizontal	GW16822	161x90x46	1/15
GW 16 754	2+2 modules	Vertical	GW16822	90x161x46	1/15
Colour: Satin black					
GW 16 782	2 modules	-	GW16822	90x90x46	1/30
GW 16 783	2+2 modules	Horizontal	GW16822	161x90x46	1/15
GW 16 784	2+2 modules	Vertical	GW16822	90x161x46	1/15

CHARACTERISTICS: support and plate not included. Use ONE International plates (interchangeability with the entire colour range of the plates).
Pre-arranged for mini-trunking with dimensions BxH (mm): 15x15, 20x20, 22x10, 30x10, 30x15, 35x15, 45x15.
GW16754 and GW16784 to be used together with plates with a centre distance of 71mm.
GW16752 - GW16782 supplied with 2 fixing screws. GW16753 - GW16754 - GW16783 - GW16784 supplied with 6 fixing screws.
NOTES: fitted for fixing the earth terminal GW26407.

Boxes for SYSTEM range



GW 22 471

Wall-mounting boxes for TOP SYSTEM plates

HF HALOGEN FREE

Code	Suitable for	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Pack Carton
GW 22 471	1/2/3 modules TOP SYSTEM	Cloud white	14x8.5 30x13 20x10	16 - 20	3/60
GW 22 472	4 modules TOP SYSTEM	Cloud white	14x8.5 30x13 20x10	16 - 20	3/30

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

24 SC

Wall-mounting boxes for COMPACT self-supporting plates



GW 24 006

Code	Suitable for	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Pack Carton
GW 24 006	1/2/3 modules COMPACT	Cloud white	14x8.5 30x13 20x10	16 - 20 - 25	3/60
GW 24 007	3+3 modules COMPACT	Cloud white	14x8.5 30x13 20x10	16 - 20 - 25	3/30

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

Wall-mounting boxes for VIRNA plates



GW 32 431

Code	Suitable for plates	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Pack Carton
GW 32 431	1/2/3 modules	Cloud white	15x17 / 22x10 / 25x17	16 - 20	3/60
GW 32 432	1/2/3 modules	Toner black	15x17 / 22x10 / 25x17	16 - 20	3/60

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.

Boxes for PLAYBUS range

Wall-mounting boxes



GW 32 431

Code	Suitable for	Colour	Pack Carton
GW 32 431	1/2/3 modules PLAYBUS	Cloud white	3/60
GW 32 432	1/2/3 modules PLAYBUS	Toner black	3/60

CHARACTERISTICS: fitted for fixing the earth terminal GW26407. Suitable for conduit Ø 16 - 20 mm.

Complementary items

Functional dividers in metal for modular, flush-mounting containers



GW 24 322

Code	Suitable for	Pack Carton
GW 24 322	GW24237	10/100
GW 24 323	GW24238	10/100
GW 24 324	GW24239	10/100

APPLICATIONS: energy separation - signal / separation special circuits.

Deep lids for 3-gang flush-mounting rectangular boxes to interface between wall and flush installations - IP40



GW 24 227

Code	Description	Colour	Pack Carton
GW 24 227	Blank lid	Cloud white	5/50
GW 24 228	Device frame	Cloud white	5/50

APPLICATIONS: the deep lids allow the system to be extended, deriving additional points for drawing and controlling power from a 3 gang flush-mounting rectangular box.
The version with a window, GW24228, permits installing frames and plates with up to 3 gang.
CHARACTERISTICS: for trunking, 15x17 - 22x10 - 25x17mm.

Blank plates for rectangular flush-mounting boxes



GW 24 211

Code	Description	Configuration	Fixing	Colour	Pack Carton
GW 24 211	3 modules	-	With screw	Cloud white	1/120
GW 24 212	3 modules	-	With screw	Toner black	1/120
GW 24 213	4 modules	-	With screw	Cloud white	1/60
GW 24 214	4 modules	-	With screw	Toner black	1/60
GW 24 215	3+3 modules	Overlapping	With screw	Cloud white	1/60
GW 24 216	3+3 modules	Overlapping	With screw	Toner black	1/60

24 SC



GW 24 218

Lids for round flush-mounting boxes

Code	Description	Colour	Fixing	Pack Carton
GW 24 218	Ø 65mm	White RAL 9016	With fixing clutches	50/400
GW 24 220	Ø 85mm	White	With fixing clutches	50/600



GW 24 224

Special self-tapping screws for fixing the supports and COMPACT self- supporting plates

Code	Dimensions (mm)	Suitable for	Pack Carton
GW 24 224	TC 3.5x17	Wood, plastic, aluminium	500/7000
GW 24 225	TC 3.5x30	Deep-mounted boxes	300/4200
GW 24 229	TC 3.5x50	Deep-mounted boxes	300/4200




24 SC



Scan the QR Code and find out all the technical informations.

BOXES FOR BRICK WALLS



The BIG BOX robust, high-capacity boxes are ideal for traditional and smart home applications. They differ to conventional products due to their greater internal space and the large number of accessories available (mortar guards, separators, joining elements, etc.).

BOXES FOR UNDERFLOOR APPLICATIONS



The range of underfloor boxes meets the demands for safety, connectivity and energy usage. 10-20 or 16-32 System module versions, with walkable cover (empty or stainless finish). Also available metal casing for installation in poured cement floors.

BOXES FOR SURFACE-MOUNTING DOMESTIC RANGE PLATES



Developed with an aesthetic line that adapts to the GEWISS domestic series plate design, the wall boxes for the ChoruSmart, System and Playbus ranges make quality installations possible even in environments where concealed installation is not possible.

Conduits and accessories for installation





RK

Rigid protective conduit systems


p. 330

FK

Pliable protective conduit systems

p. 344







DF

Flexible protective conduit systems

p. 356

PZ

Access chambers systems

p. 363

GW FIT

Accessories for electrical installation

p. 378

Rigid protective conduit systems

Ø Conduit (mm)	RIGID CONDUITS											
	RK9 range				RK9 HF range	IRL/B range		RK 15 range		RKB range	RKHF range	
	 2M	 3M	 3M	 3M	 3M	 2M	 3M	 2M	 3M	 3M	 2M	 3M
16	DX 24 816	DX 24 916	DX 25 116	DX 25 116 W	**DX 26 716 W**	DX 27 616	DX 27 716	DX 25 216	DX 25 316	DX 25 716	**DX 26 216**	**DX 26 316**
20	DX 24 820	DX 24 920	DX 25 120	DX 25 120 W	**DX 26 720 W**	DX 27 620	DX 27 720	DX 25 220	DX 25 320	DX 25 720	**DX 26 220**	**DX 26 320**
25	DX 24 825	DX 24 925	DX 25 125	DX 25 125 W	**DX 26 725 W**	DX 27 625	DX 27 725	DX 25 225	DX 25 325	DX 25 725	**DX 26 225**	**DX 26 325**
32	DX 24 832	DX 24 932	DX 25 132	DX 25 132 W	**DX 26 732 W**	DX 27 632	DX 27 732	DX 25 232	DX 25 332	DX 25 732	**DX 26 232**	**DX 26 332**
40	DX 24 840	DX 24 940	DX 25 140	DX 25 140 W	-	DX 27 640	DX 27 740	-	DX 25 340	DX 25 740	**DX 26 240**	-
50	-	DX 24 950	DX 25 150	-	-	DX 27 650	DX 27 750	-	DX 25 350	DX 25 750	**DX 26 250**	-
63	-	-	-	-	-	DX 27 663	DX 27 763	-	DX 25 363	DX 25 763	**DX 26 263**	-

Description	BOXES	COUPLING DEVICES FOR TRIX AND QUADRIX BOXES - IP54		
		Cap	Box-box coupling device	Coupling device for smooth conduits
				 Conduit Ø 16 mm
TRIX BOX 3-inlet	DX 45 003	DX 47 000	DX 47 001	DX 47 616
QUADRIX BOX 4-inlet	DX 45 004	DX 47 000	DX 47 001	DX 47 616
QUADRIX BOX 7-inlet	DX 45 007	DX 47 000	DX 47 001	DX 47 616
QUADRIX BOX 10-inlet	DX 45 010	DX 47 000	DX 47 001	DX 47 616

Ø Conduit (mm)	IP 44 - IP 66 ROUTING COMPONENTS		ACCESSORIES		
	Flexible couplings SPEEDY-FLEX range		Conduit-bending springs RK 15	Conduit-bending springs RKB	Conduit cutting shears
	 IP66	 IP44			
16	GW 50 201	GW 50 207	DX 51 416	DX 51 316	DX 51 600
20	GW 50 202	GW 50 208	DX 51 420	DX 51 320	
25	GW 50 203	GW 50 209	DX 51 425	DX 51 325	
32	GW 50 204	GW 50 210	DX 51 432	-	
40	GW 50 205	GW 50 211	DX 51 440	-	-
50	GW 50 206	GW 50 212	DX 51 450	-	

In bold: Halogen Free material versions

RK RANGE - IP40 COUPLINGS				MORBIDX RANGE - WATERTIGHT COUPLINGS								
Coupling IP40	Narrow radius curves IP40	Inspectionable T-joint IP40	Inspectionable bend IP40	Coupling IP67	Narrow radius curves IP67	Conduit-box coupling IP67		Conduit-sheath coupling device IP65		Conduit-sheath coupling device equal diameter - IP65		La Svolta conduit-conduit IP65
						Metric pitch		Sheath Ø		Sheath Ø		
DX 40 016	**DX 40 116**	DX 40 216	DX 40 316	**DX 43 016**	**DX 43 116**	M16x1,5	**DX 43 216**	12	**DX 43 316**	16	**DX 43 416**	DX 43 516
DX 40 020	**DX 40 120**	DX 40 220	DX 40 320	**DX 43 020**	**DX 43 120**	M20x1,5	**DX 43 220**	16	**DX 43 320**	20	**DX 43 420**	DX 43 520
DX 40 025	**DX 40 125**	DX 40 225	DX 40 325	**DX 43 025**	**DX 43 125**	M25x1,5	**DX 43 225**	20	**DX 43 325**	25	**DX 43 425**	DX 43 525
DX 40 032	**DX 40 132**	DX 40 232	DX 40 332	**DX 43 032**	**DX 43 132**	M32x1,5	**DX 43 232**	25	**DX 43 332**	28	**DX 43 432**	DX 43 532
DX 40 040	**DX 40 140**	-	-	**DX 43 040**	**DX 43 140**	M40x1,5	**DX 43 240**	32	**DX 43 340**	40	**DX 43 440**	DX 43 540
DX 40 050	**DX 40 150**	-	-	**DX 43 050**	**DX 43 150**	M50x1,5	**DX 43 250**	40	**DX 43 350**	-	-	DX 43 550
DX 40 063	DX 40 163	-	-	-	-	-	-	-	-	-	-	-

COUPLING DEVICES FOR TRIX AND QUADRIX BOXES - IP54

Coupling device for smooth conduits		Coupling device for spiral sheaths			Cable gland coupling device		
							
Conduit Ø 20 mm	Conduit Ø 25 mm	Sheath Ø 12 mm	Sheath Ø 16 mm	Sheath Ø 20 mm	Cables Ø 3-6 mm	Cables Ø 6-9 mm	Cables Ø 9-12 mm
DX 47 620	DX 47 625	DX 47 212	DX 47 216	DX 47 220	DX 47 503	DX 47 506	DX 47 509
DX 47 620	DX 47 625	DX 47 212	DX 47 216	DX 47 220	DX 47 503	DX 47 506	DX 47 509
DX 47 620	DX 47 625	DX 47 212	DX 47 216	DX 47 220	DX 47 503	DX 47 506	DX 47 509
DX 47 620	DX 47 625	DX 47 212	DX 47 216	DX 47 220	DX 47 503	DX 47 506	DX 47 509

RK

Rigid protective conduit systems



The system of rigid protective conduits, made of extremely high quality material, guarantees excellent quality such as to offer greater performance. Available with diameters from 16 to 63 mm, in versions RK9 (light), RK15 (medium) and RKB (heavy), made of PVC. Also available Halogne Free versions RK9 HF (light) and RKHF (heavy), made of PP. They may be fully integrated into flexible conduit systems and junction boxes. Completing the offer, a wide range of couplings and routing components with IP40 and IP67 protection ratings.

RIGID CONDUITS

RK9 light rigid conduit - Grey RAL 7035





DX 25 116

Light rigid conduit - Straight end - Lenght: 3 meters - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 25 116	16	111/3330
DX 25 120	20	57/2223
DX 25 125	25	57/1311
DX 25 132	32	30/780
DX 25 140	40	30/540
DX 25 150	50	15/360



DX 24 816

Light rigid conduit - Sleeved - Lenght: 2 meters - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 24 816	16	74/2220
DX 24 820	20	48/1344
DX 24 825	25	48/864
DX 24 832	32	38/532
DX 24 840	40	14/350



DX 24 916

Light rigid conduit - Sleeved - Lenght: 3 meters - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 24 916	16	75/3150
DX 24 920	20	51/2142
DX 24 925	25	51/1224
DX 24 932	32	30/780
DX 24 940	40	21/525
DX 24 950	50	15/360

RK9 light rigid conduit - White RAL 9010



DX 25 116 W

Light rigid conduit - Straight end - Lenght: 3 meters - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 25 116 W	16	111/3330
DX 25 120 W	20	57/2223
DX 25 125 W	25	57/1311
DX 25 132 W	32	30/780
DX 25 140 W	40	30/540

RK9 HF light rigid conduit Halogen Free (EN 50642) - White RAL 9010





DX 26 716 W

Light rigid conduit - Straight end - Lenght: 3 meters - PP HF

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
DX 26 716 W	16	87/1827
DX 26 720 W	20	69/1449
DX 26 725 W	25	60/840
DX 26 732 W	32	36/504

IRL/B medium rigid conduit - Grey RAL 7035



Medium rigid conduit - Sleeved - length: 2 metres - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 27 616	16	74/2220
DX 27 620	20	48/1344
DX 27 625	25	48/864
DX 27 632	32	38/532
DX 27 640	40	14/350
DX 27 650	50	10/240
DX 27 663	63	6/120



DX 27 616

Medium rigid conduit - Sleeved - length: 3 metres - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 27 716	16	75/3150
DX 27 720	20	51/2142
DX 27 725	25	51/1224
DX 27 732	32	30/780
DX 27 740	40	21/525
DX 27 750	50	15/360
DX 27 763	63	9/180



DX 27 716

RK 15 medium rigid conduit - Grey RAL 7035



Medium rigid conduit - Straight end - Lenght: 2 meters - PVC



DX 25 216

Code	Conduits Ø (mm)	Pack Carton
DX 25 216	16	74/2220
DX 25 220	20	48/1344
DX 25 225	25	48/864
DX 25 232	32	38/532

Medium rigid conduit - Straight end - Lenght: 3 meters - PVC



DX 25 316

Code	Conduits Ø (mm)	Pack Carton
DX 25 316	16	111/3330
DX 25 320	20	57/2223
DX 25 325	25	57/1311
DX 25 332	32	30/780
DX 25 340	40	30/540
DX 25 350	50	15/360
DX 25 363	63	9/180

RKB heavy rigid conduit - Grey RAL 7035





DX 25 716

Heavy rigid conduit - Straight end - Length: 3 metres - PVC

Code	Conduits Ø (mm)	Pack Carton
DX 25 716	16	57/3192
DX 25 720	20	57/2223
DX 25 725	25	57/1311
DX 25 732	32	30/780
DX 25 740	40	30/540
DX 25 750	50	15/360
DX 25 763	63	9/180

RKHF heavy rigid conduit Halogen Free (EN 50642) - Grey RAL 7035





DX 26 216

Heavy rigid conduit - Straight end - Length: 2 meters - PP HF

HF HALOGEN FREE LS LOW SMOKE

Code	External Ø conduits (mm)	Internal Ø conduits (mm)	Pack Carton
DX 26 216	16	10.8	60/4620
DX 26 220	20	14.5	46/3542
DX 26 225	25	19.3	48/2640
DX 26 232	32	25.8	36/1980
DX 26 240	40	32.8	30/1080
DX 26 250	50	42.4	18/648
DX 26 263	63	54.6	12/420

NOTE: to fix the RKHF conduit, you are advised to use collar clip with a distance between clip to clip equal 50 ÷ 60cm.



DX 26 316

Heavy rigid conduit - Straight end - Length: 3 meters - PP HF

HF HALOGEN FREE LS LOW SMOKE

Code	External Ø conduits (mm)	Internal Ø conduits (mm)	Pack Carton
DX 26 316	16	10.8	87/1827
DX 26 320	20	14.5	69/1449
DX 26 325	25	19.3	60/840
DX 26 332	32	25.8	36/504

NOTE: to fix the RKHF conduit, you are advised to use collar clip with a distance between clip to clip equal 50 ÷ 60cm.

RK connections - Grey RAL 7035



DX 40 016

Coupling - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 016	16	30/300
DX 40 020	20	30/450
DX 40 025	25	20/240
DX 40 032	32	10/100
DX 40 040	40	5/25
DX 40 050	50	15
DX 40 063	63	8



DX 40 116

Tight radius bend - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 116	16	30/300
DX 40 120	20	30/300
DX 40 125	25	20/100
DX 40 132	32	10/50
DX 40 140	40	5/25
DX 40 150	50	10
DX 40 163	63	1

NOTE: DX40163 not Halogen Free.



DX 40 216

Inspectable T - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 216	16	30/120
DX 40 220	20	30/120
DX 40 225	25	20/60
DX 40 232	32	10/30



DX 40 316

Inspectable bend - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 316	16	30/180
DX 40 320	20	30/120
DX 40 325	25	20/60
DX 40 332	32	10/40

MORBIDX connections - Grey RAL 7035



DX 43 016

Release coupling - IP67

Code	Conduits Ø (mm)	Pack Carton
DX 43 016	16	10/300
DX 43 020	20	10/240
DX 43 025	25	5/150
DX 43 032	32	5/120
DX 43 040	40	5/90
DX 43 050	50	3/54



DX 43 116

Release tight bend - IP67

Code	Conduits Ø (mm)	Pack Carton
DX 43 116	16	10/100
DX 43 120	20	10/80
DX 43 125	25	5/50
DX 43 132	32	5/30
DX 43 140	40	5/15
DX 43 150	50	8



DX 43 216

Release conduit-box coupling - IP67

Code	Conduits Ø (mm)	ISO pitch	For holes Ø (mm)	Pack Carton
DX 43 216	16	M 16x1.5	16	10/360
DX 43 220	20	M 20x1.5	20	10/300
DX 43 225	25	M 25x1.5	25	5/180
DX 43 232	32	M 32x1.5	32	5/150
DX 43 240	40	M 40x1.5	40	5/30
DX 43 250	50	M 50x1.5	50	5/15



DX 43 316

Release conduit-sheath coupling - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 316	16	12	10/450
DX 43 320	20	16	10/300
DX 43 325	25	20	5/210
DX 43 332	32	25	5/120
DX 43 340	40	32	5/25
DX 43 350	50	40	5/20



DX 43 416

Release conduit-sheath coupling equal diameter - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 416	16	16	10/360
DX 43 420	20	20	10/240
DX 43 425	25	25	5/150
DX 43 432	32	28	5/40
DX 43 440	40	40	5/20

USE: coupling of a rigid protective conduit with a spiral sheath of the DIFLEX range these connections allow rigid conduits and sheaths to have the same internal diameter, making the wiring easy.



DX 43 516

LA SVOLTA conduit-conduit coupling - IP65

Code	Conduits Ø (mm)	Working length (mm)	Pack Carton
DX 43 516	16	110	60
DX 43 520	20	132	40
DX 43 525	25	209	20
DX 43 532	32	301	20
DX 43 540	40	302	12
DX 43 550	50	311	9

SPEEDY-FLEX couplings - Grey RAL 7035



GW 50 201

Watertight flexible couplings - IP66

Code	For external conduits (mm)	External Ø (mm)	Internal Ø (mm)	Length (mm)	Pack Carton
GW 50 201	16	27	13	140	20/60
GW 50 202	20	31.5	17	160	20/120
GW 50 203	25	41	21.5	205	10/40
GW 50 204	32	55	28	290	10/60
GW 50 205	40	65	35.5	400	6/30
GW 50 206	50	72	44.5	515	6/36

CHARACTERISTICS: multifunctional couplings allowing the realisation of 0-90° variable angle curves and misaligned conduit-conduit couplings.



GW 50 210

Protected flexible couplings - IP44

Code	For external conduits (mm)	External Ø (mm)	Internal Ø (mm)	Length (mm)	Pack Carton
GW 50 207	16	24	13	135	20/60
GW 50 208	20	30	17	160	20/120
GW 50 209	25	35	21.5	205	20/120
GW 50 210	32	45	28	280	10/20
GW 50 211	40	55	35.5	400	6/30
GW 50 212	50	65	44.5	515	6/36

CHARACTERISTICS: multifunctional couplings allowing the realisation of 0-90° variable angle curves and misaligned conduit-conduit couplings.

Accessories



DX 51 416

Conduit-bending spring for RK15

Code	Conduits Ø (mm)	Pack Carton
DX 51 416	16	1/10
DX 51 420	20	1/10
DX 51 425	25	1/5
DX 51 432	32	1/5
DX 51 440	40	1
DX 51 450	50	1

USE: for cold bending rigid conduits.
MATERIAL: special galvanised steel square wire mesh.



DX 51 316

Conduit-bending spring for RKB

Code	Conduits Ø (mm)	Pack Carton
DX 51 316	16	1/10
DX 51 320	20	1/10
DX 51 325	25	1/5

USE: for cold bending rigid conduits.
MATERIAL: special galvanised steel square wire mesh.



DX 51 600

Conduit cutter

Code	Description	Pack Carton
DX 51 600	Conduit cutter	1/5

JUNCTION BOXES

TRIX - Grey RAL 7035



DX 45 003

TRIX box - IP54

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
DX 45 003	TX3-3 inputs	87x64x53	3/15

NOTES: Without coupling devices and without caps.

QUADRIX - Grey RAL 7035



DX 45 004

QUADRIX box - IP54

Code	Description	Accessories supplied	Outer dim. LxHxD (mm)	Pack Carton
DX 45 004	QX4-4 inputs	1 cap	100x106x53	5/60
DX 45 007	QX7-7 inputs	3 caps	106x106x53	5/60
DX 45 010	QX10-10 inputs	4 caps	140x140x53	1/16

NOTE: Without coupling devices.

Couplings and accessories - Grey RAL 7035



DX 47 616

TRIX/QUADRIX-Conduit MORBIDX coupling

Code	Conduits Ø (mm)	Pack Carton
DX 47 616	16	10/390
DX 47 620	20	10/360
DX 47 625	25	10/300



DX 47 212

Sheath -TRIX/QUADRIX coupling

Code	Sheath Ø (mm)	Pack Carton
DX 47 212	12	10/450
DX 47 216	16	10/450
DX 47 220	20	10/390



DX 47 503

Cable - TRIX/QUADRIX cable gland coupling

Code	For cables Ø (mm)	Pack Carton
DX 47 503	6	10/300
DX 47 506	9	10/300
DX 47 509	12	10/300



DX 47 000

Closure cap


Code	Description	Pack Carton
DX 47 000	Closing Cap	50/450



DX 47 001

Box-box coupling

Code	Description	Pack Carton
DX 47 001	Box-box pipe-fitting	20/60




RK




Scan the QR Code and find out all the technical informations.

FOR EVERY INSTALLATION NEED



The GEWISS rigid conduit range includes the RK9 (classification 22211), RK9 HF (classification 23431), RK15 (classification 3321), RKB (classification 4321) and RKHF (classification 4422), available in 7 sizes from 16 to 63 mm, and specific routing components for the creation of watertight or protected surface-mounted systems.

SIMPLE AND RELIABLE SYSTEM



The MORBIDX quick connect system allows the creation of surface mounted systems with IP65 and IP67 ratings, and a significant reduction in installation time. The perfect fit of the O-ring seal material ensures a firm conduit seal even in vertical position or if the conduit is not cut perfectly to size.

HALOGEN-FREE RANGE



RK9 HF, RKHF and a wide range of HF routing components enable the installation of Halogen Free surface-mounting systems, ideal for installations in public environments with high concentrations of people, thanks to lower toxic emissions and less smoke opacity in the event of fire.

FK

Medium pliable conduits FK15

Ø CONDUITS (mm)	Natural white		Black		Green	
		 with probe		 with probe		 with probe
16	DX 16 216 R	DX 16 316 R	DX 15 016 R	DX 15 116 R	DX 15 216 R	DX 15 316 R
20	DX 16 220 R	DX 16 320 R	DX 15 020 R	DX 15 120 R	DX 15 220 R	DX 15 320 R
25	DX 16 225 R	DX 16 325 R	DX 15 025 R	DX 15 125 R	DX 15 225 R	DX 15 325 R
32	DX 16 232 R	DX 16 332 R	DX 15 032 R	DX 15 132 R	DX 15 232 R	DX 15 332 R
40	DX 16 240 R	-	DX 15 040 R	DX 15 140 R	DX 15 240 R	-
50	DX 16 250 R	-	DX 15 050 R	DX 15 150 R	DX 15 250 R	-
63	-	-	DX 15 063 R	DX 15 163 R	-	-

Medium co-extruded pliable conduits FK-Xtreme

Ø CONDUITS (mm)	Natural white	Black	Green
			
20	DX 16 220 X	DX 15 020 X	DX 15 220 X
25	DX 16 225 X	DX 15 025 X	DX 15 225 X
32	DX 16 232 X	DX 15 032 X	DX 15 232 X
40	DX 16 240 X	DX 15 040 X	DX 15 240 X

Medium Halogen Free pliable self-recovering conduits ICTA

Ø CONDUITS (mm)	Grey		Dark grey		Green	
		 with probe		 with probe		 with probe
16	**DX 20 016 R**	**DX 20 116 R**	**DX 20 416 R**	**DX 20 516 R**	**DX 22 016 R**	**DX 22 116 R**
20	**DX 20 020 R**	**DX 20 120 R**	**DX 20 420 R**	**DX 20 520 R**	**DX 22 020 R**	**DX 22 120 R**
25	**DX 20 025 R**	**DX 20 125 R**	**DX 20 425 R**	**DX 20 525 R**	**DX 22 025 R**	**DX 22 125 R**
32	**DX 20 032 R**	**DX 20 132 R**	**DX 20 432 R**	**DX 20 532 R**	**DX 22 032 R**	**DX 22 132 R**
40	**DX 20 040 R**	**DX 20 140 R**	**DX 20 440 R**	**DX 20 540 R**	**DX 22 040 R**	**DX 22 140 R**
50	**DX 20 050 R**	**DX 20 150 R**	**DX 20 450 R**	**DX 20 550 R**	**DX 22 050 R**	**DX 22 150 R**
63	**DX 20 063 R**	**DX 20 163 R**	**DX 20 463 R**	**DX 20 563 R**	**-**	**-**

Cable puller probes



	Probe Ø 3 mm	Probe Ø 4 mm		
Length (m)			Flexible head	Tail ring
5	DX 52 205	DX 52 305	DX 52 299	DX 52 399
10	DX 52 210	DX 52 310	DX 52 299	DX 52 399
15	DX 52 215	DX 52 315	DX 52 299	DX 52 399
20	DX 52 220	DX 52 320	DX 52 299	DX 52 399
25	DX 52 225	DX 52 325	DX 52 299	DX 52 399


In bold: halogen-free material versions

Components





Coupling	Cap	Conduit-box coupling device
DX 52 016	DX 52 116	GW 50 415
DX 52 020	DX 52 120	GW 50 416
DX 52 025	DX 52 125	GW 50 417
DX 52 032	DX 52 132	GW 50 418
DX 52 040	DX 52 140	GW 50 419
DX 52 050	DX 52 150	GW 50 420
DX 52 063	DX 52 163	-

Light blue		Brown		Lilac	
					
	with probe		with probe		with probe
DX 15 416 R	DX 15 516 R	DX 15 616 R	DX 15 716 R	DX 15 816 R	DX 15 916 R
DX 15 420 R	DX 15 520 R	DX 15 620 R	DX 15 720 R	DX 15 820 R	DX 15 920 R
DX 15 425 R	DX 15 525 R	DX 15 625 R	DX 15 725 R	DX 15 825 R	DX 15 925 R
DX 15 432 R	DX 15 532 R	DX 15 632 R	DX 15 732 R	DX 15 832 R	DX 15 932 R
DX 15 440 R	-	DX 15 640 R	-	DX 15 840 R	-
DX 15 450 R	-	DX 15 650 R	-	DX 15 850 R	-
-	-	-	-	-	-

Light blue	Brown	Lilac
		
DX 15 420 X	DX 15 620 X	DX 15 820 X
DX 15 425 X	DX 15 625 X	DX 15 825 X
DX 15 432 X	DX 15 632 X	DX 15 832 X
DX 15 440 X	DX 15 640 X	DX 15 840 X

Light Halogen Free pliable conduits FKHF

Blue		Ø CONDUITS (mm)	Grey	
				
	with probe			with probe
DX 23 016 R	**DX 23 116 R**	16	**DX 23 216 R**	**DX 23 316 R**
DX 23 020 R	**DX 23 120 R**	20	**DX 23 220 R**	**DX 23 320 R**
DX 23 025 R	**DX 23 125 R**	25	**DX 23 225 R**	**DX 23 325 R**
DX 23 032 R	**DX 23 132 R**	32	**DX 23 232 R**	**DX 23 332 R**
DX 23 040 R	**DX 23 140 R**	40	**DX 23 240 R**	**DX 23 340 R**
DX 23 050 R	**DX 23 150 R**	50	**DX 23 250 R**	**DX 23 350 R**
-	-	63	-	-

Medium pliable conduits FKMF - SUPERSPEED

Ø CONDUITS (mm)	Grey
	
16	DX 24 216 R
20	DX 24 220 R
25	DX 24 225 R
32	DX 24 232 R
40	DX 24 240 R
50	DX 24 250 R
63	DX 24 263 R

Light pliable conduits FK9

Ø CONDUITS (mm)	Light grey	
		
		with probe
16	DX 10 016 R	DX 10 116 R
20	DX 10 020 R	DX 10 120 R
25	DX 10 025 R	DX 10 125 R
32	DX 10 032 R	DX 10 132 R
40	DX 10 040 R	DX 10 140 R
50	DX 10 050 R	DX 10 150 R

NOTES: diameter 20, 25 and 32 mm with SUPERSPEED layer.

FK

Pliable protective conduit systems

System of protective corrugated conduits for concealed installation, available in two materials: PVC and Polypropylene (PP) and in different colours for easy identification of the lines according to normative recommendations. The pallets are protected with white stretch film to prevent exposure of the coils to UV rays and ensure at the same time a greater resistance to weathering and improved preservation during external storage.



SELF-EXTINGUISHING PLIABLE CONDUITS



FK9 light pliable conduit



DX 10 016 R

Light grey RAL 7035 pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 10 016 R	16	100/6400
DX 10 020 R	20	100/5200
DX 10 025 R	25	75/3300
DX 10 032 R	32	50/1800
DX 10 040 R	40	25/1100
DX 10 050 R	50	25/400
Type: with cable puller		
DX 10 116 R	16	100/6400
DX 10 120 R	20	100/5200
DX 10 125 R	25	75/3300
DX 10 132 R	32	50/1800
DX 10 140 R	40	25/500
DX 10 150 R	50	25/400

APPLICATION: recommended for chased wall and ceiling installation. Cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods. Do not remove the protective white film during the storage.

ARCOBALENO SELF-EXTINGUISHING PLIABLE CONDUITS



FK15 medium pliable conduit



DX 16 216 R

Medium natural white pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 16 216 R	16	100/2800
DX 16 220 R	20	100/2400
DX 16 225 R	25	75/1500
DX 16 232 R	32	50/800
DX 16 240 R	40	25/500
DX 16 250 R	50	25/400
Type: with cable puller		
DX 16 316 R	16	100/2800
DX 16 320 R	20	100/2400
DX 16 325 R	25	75/1500
DX 16 332 R	32	50/800

USE: natural white is recommended for the identification of the co-axial computer cables.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.




DX 15 116 R

Medium black pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 016 R	16	100/6400
DX 15 020 R	20	100/5200
DX 15 025 R	25	75/3300
DX 15 032 R	32	50/1800
DX 15 040 R	40	25/1100
DX 15 050 R	50	25/400
DX 15 063 R	63	20/240
Type: with cable puller		
DX 15 116 R	16	100/6400
DX 15 120 R	20	100/5200
DX 15 125 R	25	75/3300
DX 15 132 R	32	50/1800
DX 15 140 R	40	25/500
DX 15 150 R	50	25/400
DX 15 163 R	63	20/240

USE: black is recommended for the identification of the distribution and force lines.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 15 216 R

Medium green pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 216 R	16	100/2800
DX 15 220 R	20	100/5200
DX 15 225 R	25	75/3300
DX 15 232 R	32	50/800
DX 15 240 R	40	25/500
DX 15 250 R	50	25/400
Type: with cable puller		
DX 15 316 R	16	100/2800
DX 15 320 R	20	100/2400
DX 15 325 R	25	75/1500
DX 15 332 R	32	50/800

USE: the green colour is recommended for identifying the telephone lines, BUS lines and domestic automation lines.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.




DX 15 516 R

Medium light blue pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 416 R	16	100/2800
DX 15 420 R	20	100/5200
DX 15 425 R	25	75/3300
DX 15 432 R	32	50/800
DX 15 440 R	40	25/500
DX 15 450 R	50	25/400
Type: with cable puller		
DX 15 516 R	16	100/2800
DX 15 520 R	20	100/2400
DX 15 525 R	25	75/1500
DX 15 532 R	32	50/800

USE: light blue is recommended for the identification of the entryphone lines.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 15 616 R

Medium brown pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 616 R	16	100/2800
DX 15 620 R	20	100/2400
DX 15 625 R	25	75/1500
DX 15 632 R	32	50/800
DX 15 640 R	40	25/500
DX 15 650 R	50	25/400
Type: with cable puller		
DX 15 716 R	16	100/2800
DX 15 720 R	20	100/2400
DX 15 725 R	25	75/1500
DX 15 732 R	32	50/800

USE: brown is recommended for the identification of the emergency light and alarm lines.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 15 916 R

Medium lilac pliable conduit - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 816 R	16	100/2800
DX 15 820 R	20	100/2400
DX 15 825 R	25	75/1500
DX 15 832 R	32	50/800
DX 15 840 R	40	25/500
DX 15 850 R	50	25/400
Type: with cable puller		
DX 15 916 R	16	100/2800
DX 15 920 R	20	100/2400
DX 15 925 R	25	75/1500
DX 15 932 R	32	50/800

USE: lilac is recommended for the identification of the cable radio and hi-fi lines.
The cable puller-feeder allows the wires to be pulled easily.
Conformity to standards refers to the protective conduit and not to the cable puller-feeder. Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.

SELF-EXTINGUISHING PLIABLE CONDUITS FOR LIQUID CONCRETE



FK-Xtreme medium pliable conduit coextruded

Medium natural white pliable conduit, coextruded - PVC



DX 16 220 X

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 16 220 X	20	100/2400
DX 16 225 X	25	75/1500
DX 16 232 X	32	50/800
DX 16 240 X	40	25/500

NOTE: conduits with diameter 20, 25 and 32 mm feature internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Natural white colour is recommended for identifying the computer coaxial cables.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.

Medium black pliable conduit, coextruded - PVC




DX 15 020 X

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 020 X	20	100/5200
DX 15 025 X	25	75/3300
DX 15 032 X	32	50/1800
DX 15 040 X	40	25/500

NOTE: conduits with diameter 20, 25 and 32 mm with internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Black colour is recommended for identifying the force distribution lines.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.

Medium green pliable conduit, coextruded - PVC



DX 15 220 X

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 220 X	20	100/2400
DX 15 225 X	25	75/1500
DX 15 232 X	32	50/800
DX 15 240 X	40	25/500

NOTE: conduits with diameter 20; 25 and 32 mm with internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Green colour is recommended for identifying the telephone lines, BUS lines and domestic automation lines.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.


Medium light blue pliable conduit, coextruded - PVC



DX 15 420 X

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 420 X	20	100/2400
DX 15 425 X	25	75/1500
DX 15 432 X	32	50/800
DX 15 440 X	40	25/500

NOTE: conduits with diameter 20; 25 and 32 mm with internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Light blue is recommended for the identification of the entryphone lines.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 15 620 X

Medium brown pliable conduit, coextruded - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 620 X	20	100/2400
DX 15 625 X	25	75/1500
DX 15 632 X	32	50/800
DX 15 640 X	40	25/500

NOTE: conduits with diameter 20; 25 and 32 mm with internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Brown is recommended for the identification of the emergency light and alarm lines.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 15 820 X

Medium lilac pliable conduit, coextruded - PVC

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 15 820 X	20	100/5200
DX 15 825 X	25	75/3300
DX 15 832 X	32	50/1800
DX 15 840 X	40	25/500

NOTE: conduits with diameter 20; 25 and 32 mm with internal lubrication.
APPLICATIONS: ideal for use in self-levelling liquid cement. Lilac blue is recommended for the identification of the cable radio and hi-fi lines.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.

SELF-EXTINGUISHING PLIABLE CONDUITS FKMF - SUPERSPEED



FKMF - SUPERSPEED - Medium pliable conduit



DX 24 220 R

Medium pliable conduit, grey

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 24 216 R	16	100/5600
DX 24 220 R	20	100/4400
DX 24 225 R	25	75/2700
DX 24 232 R	32	50/1600
DX 24 240 R	40	25/500
DX 24 250 R	50	25/400
DX 24 263 R	63	20/240

NOTE: SUPERSPEED versions, with specific internal layer for high speed cables sliding, related to 20,25,32 mm diameters.

PLIABLE SELF-RECOVERING CONDUITS ICTA HALOGEN FREE



ICTA - Medium pliable self-recovering conduit - Halogen Free - Low Smoke



DX 20 016 R

Medium pliable conduit, grey RAL 7035, self-extinguishing and self-recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 20 016 R	16	100/6400
DX 20 020 R	20	100/5200
DX 20 025 R	25	75/3300
DX 20 032 R	32	50/1800
DX 20 040 R	40	25/500
DX 20 050 R	50	25/400
DX 20 063 R	63	20/240
Type: with cable puller		
DX 20 116 R	16	100/6400
DX 20 120 R	20	100/5200
DX 20 125 R	25	75/3300
DX 20 132 R	32	50/1800
DX 20 140 R	40	25/500
DX 20 150 R	50	25/400
DX 20 163 R	63	20/240

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 20 516 R

Medium pliable conduit, dark grey, self-extinguishing and self-recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 20 416 R	16	100/6400
DX 20 420 R	20	100/5200
DX 20 425 R	25	75/3300
DX 20 432 R	32	50/1800
DX 20 440 R	40	25/500
DX 20 450 R	50	25/400
DX 20 463 R	63	20/240
Type: with cable puller		
DX 20 516 R	16	100/6400
DX 20 520 R	20	100/5200
DX 20 525 R	25	75/3300
DX 20 532 R	32	50/1800
DX 20 540 R	40	25/500
DX 20 550 R	50	25/400
DX 20 563 R	63	20/240

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 22 016 R

Medium pliable conduit, green , self-extinguishing and self- recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 22 016 R	16	100/2800
DX 22 020 R	20	100/2400
DX 22 025 R	25	75/1500
DX 22 032 R	32	50/800
DX 22 040 R	40	25/500
DX 22 050 R	50	25/400
Type: with cable puller		
DX 22 116 R	16	100/2800
DX 22 120 R	20	100/2400
DX 22 125 R	25	75/1500
DX 22 132 R	32	50/800
DX 22 140 R	40	25/500
DX 22 150 R	50	25/400

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.



DX 23 116 R

Medium pliable conduit, Light blue , self-extinguishing and self- recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 23 016 R	16	100/2800
DX 23 020 R	20	100/2400
DX 23 025 R	25	75/1500
DX 23 032 R	32	50/800
DX 23 040 R	40	25/500
DX 23 050 R	50	25/400
Type: with cable puller		
DX 23 116 R	16	100/2800
DX 23 120 R	20	100/2400
DX 23 125 R	25	75/1500
DX 23 132 R	32	50/800
DX 23 140 R	40	25/500
DX 23 150 R	50	25/400

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.
Do not expose the conduits to direct solar irradiation for long periods.
Do not remove the protective white film during the storage.

PLIABLE CONDUIT FKHF HALOGEN-FREE



FKHF - Light pliable conduit - Halogen Free - Low Smoke



DX 23 216 R

Light pliable conduit, grey, halogen-free, self-extinguishing and self-recovering - PP

HF HALOGEN FREE LS LOW SMOKE

Code	Conduits Ø (mm)	Pack Carton
Type: without cable puller		
DX 23 216 R	16	100/2800
DX 23 220 R	20	100/5200
DX 23 225 R	25	75/3300
DX 23 232 R	32	50/800
DX 23 240 R	40	25/500
DX 23 250 R	50	25/400
Type: with cable puller		
DX 23 316 R	16	100/2800
DX 23 320 R	20	100/5200
DX 23 325 R	25	75/3300
DX 23 332 R	32	50/800
DX 23 340 R	40	25/500
DX 23 350 R	50	25/400

USE: the cable puller-feeder allows the wires to be pulled easily. Conformity to standards refers to the protective conduit and not to the cable puller-feeder.

COMPONENTS FOR PLIABLE CONDUITS

Coupling




DX 52 016

GF coupling for pliable conduit

Code	Conduits Ø (mm)	Pack Carton
DX 52 016	16	50/200
DX 52 020	20	50/300
DX 52 025	25	50/200
DX 52 032	32	25/150
DX 52 040	40	10/40
DX 52 050	50	10/40
DX 52 063	63	25

USE: for the jointing of corrugated conduits of the same diameter. the corrugation creates a vacuum effect between the crest and its underside, making the connection highly effective.
This accessory allows you to recover and use pieces of corrugated conduit, thereby minimising waste.
MATERIAL: Soft transparent PVC.

Caps



DX 52 116

Pliable conduit cap

Code	Conduits Ø (mm)	Pack Carton
DX 52 116	16	100/500
DX 52 120	20	100/400
DX 52 125	25	50/250
DX 52 132	32	25/125
DX 52 140	40	25/100
DX 52 150	50	25/75
DX 52 163	63	50

USE: protects tubing from undesired entry of liquids or solid bodies during the installation phase or when left empty. Ready for the subsequent passage of the cables. Accidental obstructions are avoided, and the caps can be removed/re-used when the work is finished.
MATERIAL: PP - Grey RAL 7035.

Couplings and cable-glands



GWT 750°C



GW 50 415

Shockproof polymer conduit/box couplings Grey RAL 7035

Code	For external conduits (mm)	Mounting hole Ø (mm)	IP with rigid conduit	IP with corrugated conduit	Pack Carton
GW 50 415	16	20	IP66	IP54	25/200
GW 50 416	20	23	IP66	IP54	25/200
GW 50 417	25	29	IP66	IP54	25/150
GW 50 418	32	37	IP66	IP54	10/100
GW 50 419	40	48	IP66	IP44	6/60
GW 50 420	50	54	IP66	IP44	5/50

CHARACTERISTICS: the box conduit coupling device allows corrugated conduits to be connected to the junction boxes, guaranteeing the minimum IP4X degree of protection in areas at greater risk in the event of a fire whenever required.

ACCESSORIES SUPPLIED: fixing nut.

Cable puller-feeder



DX 52 205

Ø 3 mm nylon cable puller-feeder

Code	Length (m)	Pack Carton
DX 52 205	5	1/10
DX 52 210	10	1/10
DX 52 215	15	1/10
DX 52 220	20	1/10
DX 52 225	25	1/10

USE: for the insertion of electrical cables into protective conduits. It consists of a solid nylon rod 3 mm in diameter giving the probe extreme lightnessand flexibility, ideal for systems with short and simple sections. It is also equipped at one end with a probe with extreme resistance to wear and therefore very durable.



DX 52 305

Ø 4 mm nylon cable puller-feeder and accessories

Code	Description	Length (m)	Pack Carton
DX 52 305	-	5	1/40
DX 52 310	-	10	1/25
DX 52 315	-	15	1/15
DX 52 320	-	20	1/15
DX 52 325	-	25	1/15
DX 52 299	Flexible head	-	10/200
DX 52 399	Tail ring	-	10/200

USE: this probe is powerful and flexible, allowing it to cope with even sharp bends in conduit, thanks to a 4mm nylon rod and soft flexible head. The interchangeability of the head with the tail ring also helps to reduce the times for inserting the cables in short sections.




FK



Scan the QR Code and find out all the technical informations.

FK-XTREME COEXTRUDED MEDIUM CONDUIT



The FK-Xtreme conduits, thanks to their special double-walled design, ensure total protection from the penetration of liquid cement components. The outer coating offers additional resistance during construction work against trampling, crushing and impact, even at low temperatures (down to -25°C).

FK15 ARCOBALENO MEDIUM CONDUIT



Available in versions with or without cable puller feeder and in six different colourways for all ordinary construction installations. A ringed profile gives the conduits better flexibility, higher load resistance and reduced thermal memory.

ICTA SELF-RECOVERING MEDIUM CONDUIT



Those with classification 34223 have high resistance to impact and a wide range of operating temperatures. Made of “Halogen Free” and “Low Smoke” material, they are ideal in public environments (e.g. theatres, schools, etc.). Also available in version with cable pullers.

Flexible protective conduit systems

SHEATH Ø (mm)	SPIRALLED SHEATHS		
	DIFLEX range		LIGHT range
	Grey 	Black 	Grey 
8	DX 30 008	DX 30 108	-
10	DX 30 010	DX 30 110	-
12	DX 30 012	DX 30 112	DX 30 812
14	DX 30 014	DX 30 114	-
16	DX 30 016	DX 30 116	DX 30 816
20	DX 30 020	DX 30 120	DX 30 820
22	DX 30 022	DX 30 122	-
25	DX 30 025	DX 30 125	DX 30 825
28	DX 30 028	DX 30 128	-
32	DX 30 032	DX 30 132	-
35	DX 30 035	DX 30 135	-
40	DX 30 040	DX 30 140	-
50	DX 30 050	DX 30 150	-
60	DX 30 060	DX 30 160	-

SHEATH Ø (mm)	FIXED STRAIGHT PIPE FITTINGS - RUN IP54 RANGE						PIPE FITTINGS IP65			
	Metric pitch	Grey 	GAS pitch	Grey 	PG pitch	Grey 	Conduit-sheath pipe fitting Ø Conduit		Conduit-sheath pipe fitting (equal diameter) Ø Conduit	
8	M12x1	DX 56 008	1/4”	DX 56 208	7	DX 56 408	-	-	-	-
10	M16x1,5	DX 56 010	1/4”	DX 56 210	7	DX 56 410	-	-	-	-
12	M16x1,5	DX 56 012	3/8”	DX 56 212	9	DX 56 411	16	DX 43 316	-	-
					11	DX 56 412				
					13,5	DX 56 413				
14	M16x1,5	DX 56 014	1/2”	DX 56 214	13,5	DX 56 414	-	-	-	-
16	M20x1,5	DX 56 016	1/2”	DX 56 216	11	DX 56 415	20	DX 43 320	16	DX 43 416
					13,5	DX 56 416				
					16	DX 56 417				
20	M25x1,5	DX 56 022	3/4”	DX 56 222	16	DX 56 422	25	DX 43 325	20	DX 43 420
					21	DX 56 423				
22	M25x1,5	DX 56 022	3/4”	DX 56 222	16	DX 56 422	-	-	-	-
					21	DX 56 423				
25	M25x1,5	DX 56 025	3/4”	DX 56 225	21	DX 56 425	32	DX 43 332	25	DX 43 425
28	M32x1,5	DX 56 028	1”	DX 56 228	29	DX 56 428	-	-	32	DX 43 432
32			11/4”	DX 56 232	36	DX 56 432	40	DX 43 340	-	-
35			11/4”	DX 56 235	36	DX 56 435	-	-	-	-
40	M40x1,5	DX 56 040	11/4”	DX 56 240	42	DX 56 440	50	DX 43 350	40	DX 43 440
50	M50x1,5	DX 56 050	2”	DX 56 250	48	DX 56 450	-	-	-	-

ROTATING STRAIGHT PIPE FITTINGS - IP54 RANGE

Metric pitch	Grey 	Black 	GAS pitch	Grey 	Black 	PG pitch	Grey 	Black 
M12x1,5	DX 54 008	DX 54 108	1/4”	DX 54 208	DX 54 308	7	DX 54 408	DX 54 508
M16x1,5	DX 54 010	DX 54 110	1/4”	DX 54 210	DX 54 310	7	DX 54 410	DX 54 510
						9	DX 54 411	DX 54 511
M16x1,5	DX 54 012	DX 54 112	3/8”	DX 54 212	DX 54 312	11	DX 54 412	DX 54 512
						13,5	DX 54 413	DX 54 513
-	-	-	1/2”	DX 54 214	DX 54 314	13,5	DX 54 414	DX 54 514
M20x1,5	DX 54 016	DX 54 116	1/2”	DX 54 216	DX 54 316	13,5	DX 54 416	DX 54 516
						16	DX 54 417	DX 54 517
M25x1,5	DX 54 020	DX 54 120	3/4”	DX 54 220	DX 54 320	21	DX 54 420	DX 54 520
M25x1,5	DX 54 022	DX 54 122	3/4”	DX 54 222	DX 54 322	21	DX 54 422	DX 54 522
M32x1,5	DX 54 025	DX 54 125	1”	DX 54 225	DX 54 325	29	DX 54 425	DX 54 525
M32x1,5	DX 54 028	DX 54 128	1”	DX 54 228	DX 54 328	29	DX 54 428	DX 54 528
M40x1,5	DX 54 032	DX 54 132	1 1/4”	DX 54 232	DX 54 332	36	DX 54 432	DX 54 532
			1 1/4”	DX 54 235	DX 54 335	36	DX 54 435	DX 54 535
M50x1,5	DX 54 040	DX 54 140	1 1/2”	DX 54 240	DX 54 340	-	-	-
M63x1,5	DX 54 050	DX 54 150	2”	DX 54 250	DX 54 350	-	-	-
-	-	-	-	-	-	-	-	-

DF

Flexible protective conduit systems

The DF range of flexible protective conduits and accessories provide protection for the wiring of moving mechanical parts, as well as the interface between rigid conduits, junction boxes and distribution boards for the completion of exposed systems in tertiary and industrial sectors. Available in two mechanical strength levels, two colours and 14 diameters from 8 to 60 mm.



SELF-EXTINGUISHING INSULATING SHEATHS



DIFLEX spiralled sheath



DX 30 008

DIFLEX spiralled sheath - Grey RAL 7035 - PVC

Code	Sheath Ø (mm)	Pack Carton
DX 30 008	8	30/2070
DX 30 010	10	30/1800
DX 30 012	12	30/1800
DX 30 014	14	30/1440
DX 30 016	16	30/1080
DX 30 020	20	30/1080
DX 30 022	22	30/720
DX 30 025	25	30/600
DX 30 028	28	30/480
DX 30 032	32	30/480
DX 30 035	35	30/480
DX 30 040	40	30/360
DX 30 050	50	30/180
DX 30 060	60	30/120

NOTE: the specified measurements must be considered internal diameters. Do not expose the sheaths to direct sunlight.



DX 30 108

DIFLEX spiralled sheath - Black RAL 9005 - PVC

Code	Sheath Ø (mm)	Pack Carton
DX 30 108	8	30/2070
DX 30 110	10	30/1800
DX 30 112	12	30/1800
DX 30 114	14	30/1440
DX 30 116	16	30/1080
DX 30 120	20	30/1080
DX 30 122	22	30/720
DX 30 125	25	30/600
DX 30 128	28	30/480
DX 30 132	32	30/480
DX 30 135	35	30/480
DX 30 140	40	30/360
DX 30 150	50	30/180
DX 30 160	60	30/120

NOTE: the specified measurements must be considered internal diameters. Do not expose the conduits to direct sunlight.

COUPLINGS

Rotating unions



DX 54 020

Straight, revolving coupling device - Metric pitch - IP54

Code	Sheath Ø (mm)	ISO pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 008	8	M 12x1.5	20/180
DX 54 010	10	M 16x1.5	20/160
DX 54 012	12	M 16x1.5	10/100
DX 54 016	16	M 20x1.5	10/150
DX 54 020	20	M 25x1.5	10/100
DX 54 022	22	M 25x1.5	10/100
DX 54 025	25	M 32x1.5	5/60
DX 54 028	28	M 32x1.5	5/40
DX 54 032	32	M 40x1.5	5/30
DX 54 040	40	M 50x1.5	25
DX 54 050	50	M 63x1.5	15
Colour: Black RAL 9005			
DX 54 108	8	M 12x1.5	20/180
DX 54 110	10	M 16x1.5	20/160
DX 54 112	12	M 16x1.5	10/100
DX 54 116	16	M 20x1.5	10/150
DX 54 120	20	M 25x1.5	10/100
DX 54 122	22	M 25x1.5	10/100
DX 54 125	25	M 32x1.5	5/60
DX 54 128	28	M 32x1.5	5/40
DX 54 132	32	M 40x1.5	5/30
DX 54 140	40	M 50x1.5	25
DX 54 150	50	M 63x1.5	15

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with metric pitch or in non-threaded holes via the nut and gasket supplied.



DX 54 220

Straight, revolving coupling device - GAS pitch - IP54

Code	Sheath Ø (mm)	GAS pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 208	8	1/4"	20/180
DX 54 210	10	1/4"	20/160
DX 54 212	12	3/8"	10/100
DX 54 214	14	1/2"	10/150
DX 54 216	16	1/2"	10/150
DX 54 220	20	3/4"	10/100
DX 54 222	22	3/4"	10/100
DX 54 225	25	1"	5/60
DX 54 228	28	1"	5/40
DX 54 232	32	1 1/4"	5/30
DX 54 235	35	1 1/4"	5/30
DX 54 240	40	1 1/2"	25
DX 54 250	50	2"	15
Colour: Black RAL 9005			
DX 54 308	8	1/4"	20/180
DX 54 310	10	1/4"	20/160
DX 54 312	12	3/8"	10/100
DX 54 314	14	1/2"	10/150
DX 54 316	16	1/2"	10/150
DX 54 320	20	3/4"	10/100
DX 54 322	22	3/4"	10/100
DX 54 325	25	1"	5/60
DX 54 328	28	1"	5/40
DX 54 332	32	1 1/4"	5/30
DX 54 335	35	1 1/4"	5/30
DX 54 340	40	1 1/2"	25
DX 54 350	50	2"	15

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with GAS pitches or in non-threaded holes via the nut and gasket supplied.



DX 54 420

Straight, revolving coupling device - PG pitch - IP54

Code	Sheath Ø (mm)	PG pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 408	8	7	20/180
DX 54 410	10	7	20/160
DX 54 411	10	9	20/160
DX 54 412	12	11	10/100
DX 54 413	12	13.5	10/100
DX 54 414	14	13.5	10/150
DX 54 416	16	13.5	10/150
DX 54 417	16	16	10/150
DX 54 420	20	21	10/100
DX 54 422	22	21	10/100
DX 54 425	25	29	5/60
DX 54 428	28	29	5/40
DX 54 432	32	36	5/30
DX 54 435	35	36	5/30
Colour: Black RAL 9005			
DX 54 508	8	7	20/180
DX 54 510	10	7	20/160
DX 54 511	10	9	20/160
DX 54 512	12	11	10/100
DX 54 513	12	13.5	10/100
DX 54 514	14	13.5	10/150
DX 54 516	16	13.5	10/150
DX 54 517	16	16	10/150
DX 54 520	20	21	10/100
DX 54 522	22	21	10/100
DX 54 525	25	29	5/60
DX 54 528	28	29	5/40
DX 54 532	32	36	5/30
DX 54 535	35	36	5/30

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with Pg pitches or in non-threaded holes via the nut and gasket supplied.

Fixed unions



DX 56 008

Straight, fixed coupling device - Metric pitch - IP54

Code	Sheath Ø (mm)	ISO pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 008	8	M12x1,5	20/160
DX 56 010	10	M16x1.5	10/170
DX 56 012	12	M16x1.5	10/150
DX 56 014	14	M16x1.5	10/130
DX 56 016	16	M20x1.5	10/110
DX 56 022	22	M25x1.5	10/50
DX 56 025	25	M25x1.5	10/50
DX 56 028	28	M32x1.5	10/40
DX 56 040	40	M40x1.5	15
DX 56 050	50	M50x1.5	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with metric pitch or in non-threaded holes via the nut and gasket supplied.



DX 56 208

Straight, fixed coupling device - GAS pitch - IP54

Code	Sheath Ø (mm)	GAS pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 208	8	1/4”	20/160
DX 56 210	10	1/4”	10/170
DX 56 212	12	3/8”	10/150
DX 56 214	14	1/2”	10/130
DX 56 216	16	1/2”	10/110
DX 56 222	22	3/4”	10/50
DX 56 225	25	3/4”	10/50
DX 56 228	28	1”	10/40
DX 56 232	32	1 1/4”	3/18
DX 56 235	35	1 1/4”	3/18
DX 56 240	40	1 1/2”	15
DX 56 250	50	2”	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with GAS pitches or in non-threaded holes via the nut and gasket supplied.



DX 56 408

Straight, fixed coupling device - PG pitch - IP54

Code	Sheath Ø (mm)	PG pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 408	8	7	20/160
DX 56 410	10	7	10/170
DX 56 411	12	9	10/150
DX 56 412	12	11	10/150
DX 56 413	12	13.5	10/150
DX 56 414	14	13.5	10/130
DX 56 415	16	11	10/110
DX 56 416	16	13.5	10/110
DX 56 417	16	16	10/110
DX 56 422	22	16	10/50
DX 56 423	22	21	10/50
DX 56 425	25	21	10/50
DX 56 428	28	29	10/40
DX 56 432	32	36	3/18
DX 56 435	35	36	3/18
DX 56 440	40	42	15
DX 56 450	50	48	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with Pg pitches or in non-threaded holes via the nut and gasket supplied.

Conduit-sheath unions



DX 43 316

MORBIDX release conduit-sheath union - IP65

HF HALOGEN FREE

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 316	16	12	10/450
DX 43 320	20	16	10/300
DX 43 325	25	20	5/210
DX 43 332	32	25	5/120
DX 43 340	40	32	5/25
DX 43 350	50	40	5/20



DX 43 416

Release conduit-sheath union equal diameter - IP65

HF HALOGEN FREE

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 416	16	16	10/360
DX 43 420	20	20	10/240
DX 43 425	25	25	5/150
DX 43 432	32	28	5/40
DX 43 440	40	40	5/20

USE: coupling of a solid protective conduit with a spiral sheath of the DIFLEX range;
allows the maintenance of the same internal diameter in line with the joint; the internal section for cable passage remains constant, increasing the space available for the system wires.

SHEATH FOR NON-HEAVY DUTY USES









LIGHT Spiralled sheath



DX 30 812

LIGHT spiralled sheath - Grey RAL 7035 - PVC

Code	Sheath Ø (mm)	Pack Carton
DX 30 812	12	30/1800
DX 30 816	16	30/1080
DX 30 820	20	30/1080
DX 30 825	25	30/600

NOTE: all measurements are internal diameters. Do not expose the sheaths to direct solar irradiation.



DF



Scan the QR Code and find out all the technical informations.

PROFESSIONAL SPIRALLED SHEATHS



The range of spiralled sheaths with classification 2311 is available in 14 different diameters in grey and black. They are also available in the Light version, with classification 1311 (in 12, 16, 20 and 25 mm diameters), ideal for use in air conditioning equipment.

FLEXIBILITY AND DURABILITY



The particular shape of the sheath, which has a rigid PVC inner coil and plasticised PVC outer coating, provides high resistance to crushing and ensures the flexibility necessary for every type of application and routing.

COUPLING DEVICES FOR EASY INSTALLATION



Once in place, the sheath can rotate freely, while maintaining IP54 rated protection, thanks to the straight swivel couplings. This facilitates the movement of sheaths already connected to boxes and distribution boards.

Access chambers systems


THERMOPLASTIC ACCESS CHAMBERS

Type	Dimensions (mm)	Complete access chambers	Access chambers without covers	Covers						Separator Plate	Sealing gaskets	Kit of 4 screws	Central bolt for lifting kit
				Closed			Gridded						
				Grey	Green	Blue	Grey	Green	Blue				
													
Square base access chambers	200x200x200	DX 59 401	DX 59 402	DX 59 410	DX 59 430		DX 59 411	DX 59 431		DX 59 440	DX 59 451	DX 59 450	-
	300x300x300	DX 59 701	DX 59 702	DX 59 710	DX 59 730		DX 59 711	DX 59 731		DX 59 740	DX 59 751	DX 59 450	-
	400x400x400	DX 59 801	DX 59 802	DX 59 810	DX 59 830		DX 59 811	DX 59 831		DX 59 840	DX 59 851	DX 59 452	DX 59 453
	550x550x520	DX 59 901	DX 59 902	DX 59 910	DX 59 930		DX 59 911	DX 59 931		DX 59 940	DX 59 951	DX 59 452	DX 59 453
Rectangular base access chambers 	360x260x326	DX 59 501	DX 59 502	DX 59 511	DX 59 230	DX 59 220	DX 59 520	DX 59 231	DX 59 221	Transversal DX 59 240 Longitudinal DX 59 241 Diagonal DX 59 242	DX 59 551	DX 59 650	-

PZ

Access chambers systems

The range of PZ access chambers, available in 5 sizes, is ideal for junctions and manholes in electrical and telecommunication systems. These are provided with knockouts for cable ducts and knockouts base for stacking installation. Thanks to the thermoplastic material, knockouts for cable ducts and knockouts base for stacking installation, the PZ range is an efficient alternative to the access chambers made of concrete.



THERMOPLASTIC ACCESS CHAMBERS

Square access chambers



DX 59 401

Square access chamber 200x200x200

Code	Characteristics	Colour	Pack Carton
DX 59 401	Flat knockout base and high resistance lid	Grey	1/60
DX 59 402	Flat semi-pierced base for boosting	Grey	1/60



Covers and components


Code	Description	Characteristics	Colour	Pack Carton
DX 59 410	Closed cover	High resistance	Grey	1/5
DX 59 430	Closed cover	High resistance	Green	1/5
DX 59 411	Gridded cover	High resistance	Grey	1/5
DX 59 431	Gridded cover	High resistance	Green	1/5
DX 59 440	Separator plate	-	-	1/10
DX 59 451	Seal	-	-	1/10
DX 59 450	4 screws kit	Self-threading steel screws	-	1/50



DX 59 701

Square access chamber 300x300x300

Code	Characteristics	Colour	Pack Carton
DX 59 701	Flat knockout base and high resistance lid	Grey	1/36
DX 59 702	Flat semi-pierced base for boosting	Grey	1/36



Covers and components


Code	Description	Characteristics	Colour	Pack Carton
DX 59 710	Closed cover	High resistance	Grey	1/5
DX 59 730	Closed cover	High resistance	Green	1/5
DX 59 711	Gridded cover	High resistance	Grey	1/5
DX 59 731	Gridded cover	High resistance	Green	1/5
DX 59 740	Separator plate	-	-	1/10
DX 59 751	Seal	-	-	1/10
DX 59 450	4 screws kit	Self-threading steel screws	-	1/50



DX 59 801


Square access chambers 400x400x400

Code	Characteristics	Colour	Pack Carton
DX 59 801	Flat knockout base and high resistance lid	Grey	1/18
DX 59 802	Flat semi-pierced base for boosting	Grey	1/24



Covers and components


Code	Description	Characteristics	Colour	Pack Carton
DX 59 810	Closed cover	High resistance	Grey	1/5
DX 59 830	Closed cover	High resistance	Green	1/5
DX 59 811	Gridded cover	High resistance	Grey	1/5
DX 59 831	Gridded cover	High resistance	Green	1/5
DX 59 840	Separator plate	-	-	1/10
DX 59 851	Seal	-	-	1/10
DX 59 452	4 screws kit	Self-threading steel screws	-	1/50
DX 59 453	Kit - central bolt for lifting	-	-	1/20



DX 59 901

Square access chambers 550x550x520

Code	Characteristics	Colour	Pack Carton
DX 59 901	Flat knockout base and high resistance lid	Grey	1/8
DX 59 902	Flat semi-pierced base for boosting	Grey	1/8



Covers and components

Code	Description	Characteristics	Colour	Pack Carton
DX 59 910	Closed cover	High resistance	Grey	1/5
DX 59 930	Closed cover	High resistance	Green	1/5
DX 59 911	Gridded cover	High resistance	Grey	1/5
DX 59 931	Gridded cover	High resistance	Green	1/5
DX 59 940	Separator plate	-	-	1/10
DX 59 951	Seal	-	-	1/10
DX 59 452	4 screws kit	Self-threading steel screws	-	1/50
DX 59 453	Kit - central bolt for lifting	-	-	1/20

Rectangular access chamber




DX 59 501

Rectangular access chamber 360x260x320

Code	Characteristics	Accessories supplied	Colour	Pack Carton
DX 59 501	Flat semi-pierced base	Cover high resistance and 4 S/Steel screws	Grey	1
DX 59 502	Flat semi-pierced base for boosting	4 stainless steel screws	Grey	1

NOTE: the lids supplied are without the gasket, available as an accessory DX59551.




Covers and components

Code	Description	Characteristics	Colour	Pack Carton
DX 59 511	Closed cover	High resistance	Grey	1/6
DX 59 520	Gridded cover	-	Grey	1/6
DX 59 230	Closed cover	-	Green	1/6
DX 59 231	Gridded cover	-	Green	1/6
DX 59 240	Separator plate	Cross	-	1/6
DX 59 241	Separator plate	Longitudinal	-	1/4
DX 59 242	Separator plate	Diagonal	-	1/4
DX 59 551	Seal	-	-	1/10
DX 59 650	4 screws kit	Self-threading steel screws	-	1/50



PZ




Scan the QR Code and find out all the technical informations.

WIDE AND FUNCTIONAL RANGE



A broad offering that includes square and rectangular access chambers and related technical components. The rectangular access chamber offers the option of a double junction on the long side, and of installing separators longitudinally, transversely or diagonally.

KNOCKOUTS AND STAKING OPTIONS



The sides of the access chamber have knock-outs of different dimeters for cable ducts entry. The removable base allows the PZ access chambers be layered, creating a modular system to increase access chamber depth and capacity.

HIGH-STRENGTH LIDS



The high-resistance PZ access chamber covers can be secured with 4 stainless steel self-threading screws for added safety and stability during installation. Only one tool is required to open the access chamber.

GW FIT

Accessories for electrical installation

	PLASTIC CABLE GLANDS									METAL CABLE GLANDS			
	IP68		IP66		IP66 with housing			IP54		IP68		IP 65	
													
Thread	Code	For cables Ø (mm)	Code	For cables Ø (mm)	Code	For conduits Ø (mm)	For cables Ø (mm)	Code	For cables Ø (mm)	Code	For cables Ø (mm)	Code	For cables Ø (mm)
PG7	GW 52 071	3 ÷ 6,5	GW 52 001	3 ÷ 6	-	-	-	GW 52 081	4 ÷ 6	-	-	-	-
PG9	GW 52 072	4 ÷ 8	GW 52 002	5 ÷ 8	-	-	-	GW 52 082	4,5 ÷ 7	-	-	-	-
PG11	GW 52 073	5 ÷ 10	GW 52 003	7 ÷ 10,5	-	-	-	GW 52 083	6 ÷ 9	GW 76 825	4 ÷ 9	GW 76 841	7,5/10/12,5
PG13,5	GW 52 074	6 ÷ 12	GW 52 004	9 ÷ 12,5	GW 52 024	16	9 ÷ 12,5	GW 52 084	9 ÷ 12	GW 76 826	7 ÷ 11	GW 76 842	7,5/10/12,5
PG16	GW 52 075	10 ÷ 14	GW 52 005	13 ÷ 16	GW 52 025	20	13 ÷ 16	GW 52 085	11 ÷ 14	GW 76 827	10 ÷ 13	GW 76 843	7,5/10/12,5
PG21	GW 52 076	13 ÷ 18	GW 52 006	9 ÷ 10 17 ÷ 20	GW 52 026	25	9 ÷ 10 17 ÷ 20	GW 52 086	14 ÷ 18	GW 76 828	12 ÷ 17	GW 76 844	10/13/16/19
PG29	GW 52 077	18 ÷ 25	GW 52 007	13,5 ÷ 15 21 ÷ 26	GW 52 027	32	13,5 ÷ 15 21 ÷ 26	GW 52 087	18 ÷ 25	GW 76 829	17 ÷ 24	GW 76 845	18/21/24/27
PG36	GW 52 078	22 ÷ 32	GW 52 008	17 ÷ 20 30 ÷ 34	GW 52 028	40	17 ÷ 20 30 ÷ 34	GW 52 088	26 ÷ 32	GW 76 830	20 ÷ 26 27 ÷ 24	GW 76 846	24/27/30/33
PG42	GW 52 079	30 ÷ 38	GW 52 009	36 ÷ 39 40 ÷ 43	GW 52 029	50	36 ÷ 39 40 ÷ 43	-	-	GW 76 897	32 ÷ 36	GW 76 847	30/33/36/39
PG48	GW 52 080	34 ÷ 44	GW 52 010	38 ÷ 40 46 ÷ 50	-	-	-	-	-	-	-	-	-
M12	GW 52 042	3 ÷ 6,5	-	-	-	-	-	-	-	GW 76 894	3 ÷ 6,5	-	-
M16	GW 52 043	5 ÷ 10	-	-	-	-	-	-	-	GW 76 896	4 ÷ 9	-	-
M20	GW 52 044	10 ÷ 14	-	-	-	-	-	-	-	GW 76 831	10 ÷ 13	GW 76 848	4/7/10/13
M25	GW 52 045	13 ÷ 18	-	-	-	-	-	-	-	GW 76 832	12 ÷ 17	GW 76 849	8,5/11,5/14,5/17,5
M32	GW 52 046	18 ÷ 25	-	-	-	-	-	-	-	GW 76 833	14 ÷ 21	GW 76 850	16/19/22/25
M40	GW 52 047	22 ÷ 32	-	-	-	-	-	-	-	GW 76 834	19 ÷ 27	GW 76 851	23/26/29/32
M50	GW 52 048	30 ÷ 38	-	-	-	-	-	-	-	GW 76 835	25 ÷ 34	GW 76 852	30/33/36/39
M63	GW 52 049	35 ÷ 44	-	-	-	-	-	-	-	GW 76 895	34 ÷ 48	-	-

	PLASTIC ACCESSORIES			METAL ACCESSORIES						GASKETS
	Caps	Nuts		Caps	Nuts		Extensions			O-ring for caps
										
Thread	Code	Code	Spanner (mm)	Code	Code	Spanner (mm)	Code	Male thread	Female thread	Code
PG7	GW 52 361	GW 52 341	19	-	-	-	-	-	-	GW 52 441
PG9	GW 52 362	GW 52 342	22	-	-	-	-	-	-	GW 52 442
PG11	GW 52 363	GW 52 343	24	GW 76 980	GW 76 957	21	GW 76 865	PG11	PG13,5	GW 52 443
PG13,5	GW 52 364	GW 52 344	27	GW 76 981	GW 76 958	23	GW 76 866	PG13,5	PG16	GW 52 444
PG16	GW 52 365	GW 52 345	30	GW 76 982	GW 76 959	26	GW 76 867	PG16	PG21	GW 52 445
PG21	GW 52 366	GW 52 346	36	GW 76 983	GW 76 960	32	GW 76 868	PG21	PG29	GW 52 446
PG29	GW 52 367	GW 52 347	46	GW 76 984	GW 76 961	41	GW 76 869	PG29	PG36	GW 52 447
PG36	GW 52 368	GW 52 348	60	GW 76 985	GW 76 962	51	-	-	-	GW 52 448
PG42	GW 52 369	GW 52 349	65	GW 76 986	GW 76 963	60	-	-	-	GW 52 449
PG48	GW 52 370	GW 52 350	70	-	-	-	-	-	-	GW 52 450
M12	GW 52 372	GW 52 352	18	GW 76 972	GW 76 966	15	-	-	-	GW 52 452
M16	GW 52 373	GW 52 353	22	GW 76 973	GW 76 951	19	-	-	-	GW 52 453
M20	GW 52 374	GW 52 354	26	GW 76 975	GW 76 952	23	GW 76 870	M20	M25	GW 52 454
M25	GW 52 375	GW 52 355	32	GW 76 976	GW 76 953	29	GW 76 871	M25	M32	GW 52 455
M32	GW 52 376	GW 52 356	41	GW 76 977	GW 76 954	36	GW 76 872	M32	M40	GW 52 456
M40	GW 52 377	GW 52 357	50	GW 76 978	GW 76 955	45	GW 76 873	M40	M50	GW 52 457
M50	GW 52 378	GW 52 358	60	GW 76 979	GW 76 956	55	-	-	-	GW 52 458
M63	GW 52 379	GW 52 359	75	GW 76 974	GW 76 967	70	-	-	-	GW 52 459

METAL CABLE GLANDS WITH FIXING NUTS - IP68 - ATEX VERSION

Cable glands				Fixing nuts			
Thread		Thread		Thread		Thread	
PG7	GW 76 901	M12	GW 76 921	PG7	GW 76 941	M12	GW 76 949
PG9	GW 76 902	M16	GW 76 922	PG9	GW 76 942	M16	GW 76 951
PG11	GW 76 903	M20	GW 76 923	PG11	GW 76 957	M20	GW 76 952
PG13,5	GW 76 904	M25	GW 76 924	PG13,5	GW 76 958	M25	GW 76 953
PG16	GW 76 905	M32	GW 76 925	PG16	GW 76 959	M32	GW 76 954
PG21	GW 76 906	M40	GW 76 926	PG21	GW 76 960	M40	GW 76 955
PG29	GW 76 907	M50	GW 76 927	PG29	GW 76 961	M50	GW 76 956
PG36	GW 76 908	M63	GW 76 928	PG36	GW 76 962	M63	GW 76 950
PG42	GW 76 909	-	-	PG42	GW 76 963	-	-
PG48	GW 76 910	-	-	PG48	GW 76 943	-	-

NOTE: the ATEX products are only available in the following countries: Austria, France, Germany, Italy, Liechtenstein, Luxemburg, the Principality of Monaco, the United Kingdom and Spain. For all other countries, contact GEWISS Technical service assistance.

COUPLINGS FOR CONDUITS AND CABLES

For conduits/ cables (mm)	Conduit-box couplings				Conduit-box couplings in flexible polymer IP44		Cable glands in flexible polymer IP55	
								
	Code	Assembly hole (mm)	IP with rigid conduits	IP with corrugated conduits	Code	Assembly hole (mm)	Code	Assembly hole (mm)
16	GW 50 415	20	IP66	IP54	GW 50 421	23	GW 50 428	19
20	GW 50 416	23	IP66	IP54	GW 50 422	23	GW 50 429	23
					GW 50 423	29		
25	GW 50 417	29	IP66	IP54	GW 50 424	29	GW 50 430	29
32	GW 50 418	37	IP66	IP54	GW 50 425	37	GW 50 431	37
40	GW 50 419	48	IP66	IP44	GW 50 426	37	GW 50 432	48
50	GW 50 420	54	IP66	IP44	GW 50 427	42	-	-

Accessories for electrical installation

PLASTIC FIXING DEVICES

Ø conduits (mm)	Clip-on supports	Collar supports	Rail for clip-on and collar supports	Supports with multi-diameter clamp
				
16	**GW 50 601**	**GW 50 605**	GW 50 609	GW 50 651
20	**GW 50 602**	**GW 50 606**	GW 50 609	GW 50 651
25	**GW 50 603**	**GW 50 607**	GW 50 609	GW 50 652
32	**GW 50 604**	**GW 50 608**	GW 50 609	GW 50 652
40	GW 50 628	**GW 50 630**	GW 50 609	GW 50 653
50	GW 50 629	**GW 50 631**	GW 50 609	GW 50 653

In bold: halogen-free material versions

PLASTIC FIXING DEVICES

Ø conduits (mm)	Re-openable fixing collars	Non re-openable fixing collars		Wall plugs	
					
				Wall plug Ø 6mm	**Wall plug Ø 8mm**
16	**DX 51 120**	**DX 51 232**	-	DX 51 306	DX 51 308
20	**DX 51 120**	**DX 51 232**	-	DX 51 306	DX 51 308
25	-	**DX 51 232**	**DX 51 263**	DX 51 306	DX 51 308
32	-	**DX 51 232**	**DX 51 263**	DX 51 306	DX 51 308
40	-	-	**DX 51 263**	DX 51 306	DX 51 308
50	-	-	**DX 51 263**	DX 51 306	DX 51 308
63	-	-	**DX 51 263**	DX 51 306	DX 51 308

In bold: halogen-free material versions

FIXING SUPPORTS AND ACCESSORIES FOR CABLES

Ø cables (mm)	Staples with nail	Width of flat cables (mm)	Staples with nail for flat cables
			
3-4	GW 50 610	-	-
5-6	GW 50 611	**5-6**	GW 50 623
	GW 50 621*		
7-8	GW 50 612	**7-8**	GW 50 624
	GW 50 622*		
9-10	GW 50 613	**10-11**	GW 50 625
11-12	GW 50 614	-	-
13-14	GW 50 615	-	-
15-16	GW 50 616	-	-
19-20	GW 50 617	-	-
21-22	GW 50 618	-	-
25-26	GW 50 619	-	-
31-32	GW 50 620	-	-

* Colour: White

METAL FIXING DEVICES

Ø cables/conduits (mm)	Galvanized steel collars with 2 screws	Galvanized steel staples with a single hole	Galvanized steel staples with a double hole
			
10-11	GW 50 801	GW 50 811	GW 50 821
12-13	GW 50 802	GW 50 812	GW 50 822
14-15	GW 50 803	GW 50 813	GW 50 823
16-17	GW 50 804	GW 50 814	GW 50 824
19-20	GW 50 805	GW 50 815	GW 50 825
21-22	GW 50 806	GW 50 816	GW 50 826
25-26	GW 50 807	GW 50 817	GW 50 827
31-32	GW 50 808	GW 50 818	GW 50 828
38-40	GW 50 809	GW 50 819	GW 50 829
48-50	GW 50 810	GW 50 820	GW 50 830

FIXING STRAPS

Galvanized steel fixing strap - 10m	Fabric fixing strap - 10m	Firing pin for manual nailing	Steel nail, 18mm long
			
GW 50 791	GW 50 792	GW 50 798	GW 50 799

Accessories for electrical installation

RK RANGE - IP40 COUPLINGS

CONDUITS Ø (mm)	Coupling IP40	Tight radius elbow IP40	Controllable "T" joint IP40	Controllable elbow IP40
				
16	**DX 40 016**	**DX 40 116**	DX 40 216	DX 40 316
20	**DX 40 020**	**DX 40 120**	DX 40 220	DX 40 320
25	**DX 40 025**	**DX 40 125**	DX 40 225	DX 40 325
32	**DX 40 032**	**DX 40 132**	DX 40 232	DX 40 332
40	**DX 40 040**	**DX 40 140**	-	-
50	**DX 40 050**	**DX 40 150**	-	-
63	**DX 40 063**	DX 40 163	-	-

MORBIDX RANGE - WATERTIGHT COUPLINGS

CONDUITS Ø (mm)	Coupling IP67	Tight radius elbow IP67	Conduit-box coupling IP67		Conduit-sheath coupling IP65		Conduit-sheath coupling (equal diameter) IP65	
								
	Code	**Code**	**Metric pitch**	**Code**	**Sheath Ø**	**Code**	**Sheath Ø**	**Code**
16	**DX 43 016**	**DX 43 116**	M16x1,5	**DX 43 216**	12	**DX 43 316**	16	**DX 43 416**
20	**DX 43 020**	**DX 43 120**	M20x1,5	**DX 43 220**	16	**DX 43 320**	20	**DX 43 420**
25	**DX 43 025**	**DX 43 125**	M25x1,5	**DX 43 225**	20	**DX 43 325**	25	**DX 43 425**
32	**DX 43 032**	**DX 43 132**	M32x1,5	**DX 43 232**	25	**DX 43 332**	28	**DX 43 432**
40	**DX 43 040**	**DX 43 140**	M40x1,5	**DX 43 240**	32	**DX 43 340**	40	**DX 43 440**
50	**DX 43 050**	**DX 43 150**	M50x1,5	**DX 43 250**	40	**DX 43 350**		

FLEXIBLE COUPLINGS

CONDUITS Ø (mm)	Flexible couplings SPEEDY-FLEX range		La Svolta conduit-conduit
			
	IP66	**IP44**	**IP 65**
16	GW 50 201	GW 50 207	DX 43 516
20	GW 50 202	GW 50 208	DX 43 520
25	GW 50 203	GW 50 209	DX 43 525
32	GW 50 204	GW 50 210	DX 43 532
40	GW 50 205	GW 50 211	DX 43 540
50	GW 50 206	GW 50 212	DX 43 550

In bold: versions with halogen-free material.

STRAIGHT ROTATING COUPLING DEVICES - IP54 RANGE

Ø sheaths (mm)	M pitch	Grey	Black	GAS pitch	Grey	Black	PG pitch	Grey	Black
									
8	M12	DX 54 008	DX 54 108	1/4”	DX 54 208	DX 54 308	7	DX 54 408	DX 54 508
10	M16	DX 54 010	DX 54 110	1/4”	DX 54 210	DX 54 310	7	DX 54 410	DX 54 510
							9	DX 54 411	DX 54 511
12	M16	DX 54 012	DX 54 112	3/8”	DX 54 212	DX 54 312	11	DX 54 412	DX 54 512
							13,5	DX 54 413	DX 54 513
14	-	-	-	1/2”	DX 54 214	DX 54 314	13,5	DX 54 414	DX 54 514
16	M20	DX 54 016	DX 54 116	1/2”	DX 54 216	DX 54 316	13,5	DX 54 416	DX 54 516
							16	DX 54 417	DX 54 517
20	M25	DX 54 020	DX 54 120	3/4”	DX 54 220	DX 54 320	21	DX 54 420	DX 54 520
22	M25	DX 54 022	DX 54 122	3/4”	DX 54 222	DX 54 322	21	DX 54 422	DX 54 522
25	M32	DX 54 025	DX 54 125	1”	DX 54 225	DX 54 325	29	DX 54 425	DX 54 525
28	M32	DX 54 028	DX 54 128	1”	DX 54 228	DX 54 328	29	DX 54 428	DX 54 528
32	M40	DX 54 032	DX 54 132	1 1/4”	DX 54 232	DX 54 332	36	DX 54 432	DX 54 532
35	-	-	-	1 1/4”	DX 54 235	DX 54 335	36	DX 54 435	DX 54 535
40	M50	DX 54 040	DX 54 140	1 1/2”	DX 54 240	DX 54 340	-	-	-
50	M63	DX 54 050	DX 54 150	2”	DX 54 250	DX 54 350	-	-	-

STRAIGHT FIXED COUPLING DEVICES - IP54 RANGE

COUPLING DEVICES IP65

Ø sheaths (mm)	M pitch	Grey	GAS pitch	Grey	PG pitch	Grey	Conduit-sheath pipe coupling		Conduit-sheath coupling (equal diameter)	
							Ø conduits (mm)		Ø conduits (mm)	
8	M12	DX 56 008	1/4”	DX 56 208	7	DX 56 408	-	-	-	-
10	M16	DX 56 010	1/4”	DX 56 210	7	DX 56 410	-	-	-	-
12	M16	DX 56 012	3/8”	DX 56 212	9	DX 56 411	16	DX 43 316	-	-
					11	DX 56 412				
					13,5	DX 56 413				
14	M16	DX 56 014	1/2”	DX 56 214	13,5	DX 56 414	-	-	-	-
16	M20	DX 56 016	1/2”	DX 56 216	11	DX 56 415	20	DX 43 320	16	DX 43 416
					13,5	DX 56 416				
					16	DX 56 417				
20	M25	DX 56 022	3/4”	DX 56 222	16	DX 56 422	25	DX 43 325	20	DX 43 420
					21	DX 56 423				
22	M25	DX 56 022	3/4”	DX 56 222	16	DX 56 422	-	-	-	-
					21	DX 56 423				
25	M25	DX 56 025	3/4”	DX 56 225	21	DX 56 425	32	DX 43 332	25	DX 43 425
28	M32	DX 56 028	1”	DX 56 228	29	DX 56 428	-	-	32	DX 43 432
32	-	-	11/4”	DX 56 232	36	DX 56 432	40	DX 43 340	-	-
35	-	-	11/4”	DX 56 235	36	DX 56 435	-	-	-	-
40	M40	DX 56 040	11/4”	DX 56 240	42	DX 56 440	50	DX 43 350	40	DX 43 440
50	M50	DX 56 050	2”	DX 56 250	48	DX 56 450				

GW FIT

Accessories for electrical installation

CABLE TIES

Dimensions LxH (mm)	Tightening capacity Ø (mm)	STANDARD TYPE	FOR HEAVY DUTY	RE-OPENABLE	WITH EYELET	WITH PLATE
						
2,4x75	1.5 - 18	GW 52 231	GW 52 251	-	-	-
2,5x96	1.5 - 23	GW 52 232	GW 52 252	-	-	-
2,5x100	1.5 - 25	-	-	-	GW 52 281	-
2,5x100	5 - 25	-	-	-	-	GW 52 291
2,5x110	1.5 - 25	-	-	-	-	GW 52 292
2,5x140	1.5 - 35	GW 52 233	GW 52 253	-	-	-
2,5x200	10 - 50	-	-	-	-	GW 52 293
2,5x203	1.5 - 55	GW 52 234	GW 52 254	-	-	-
3,6x150	2.5 - 39	GW 52 235	GW 52 255	-	-	-
3,6x203	2.5 - 55	GW 52 236	GW 52 256	-	-	-
3,6x292	2.5 - 85	GW 52 237	GW 52 257	-	-	-
4,2x205	2.5 - 60	-	-	-	GW 52 282	-
4,6x200	10 - 50	-	-	-	-	GW 52 294
4,8x190	3 - 52	GW 52 238	GW 52 258	-	-	-
4,8x280	3 - 81	GW 52 239	GW 52 259	-	-	-
4,8x368	3 - 182	GW 52 240	GW 52 260	-	-	-
7,6x150	4 - 35	-	-	GW 52 271	-	-
7,6x200	4 - 50	-	-	GW 52 272	-	-
7,6x300	4 - 80	-	-	GW 52 273	-	-
7,6x380	4 - 110	GW 52 241	GW 52 261	-	-	-
9,0x610	5 - 185	GW 52 242	GW 52 262	-	-	-
9,0x914	5 - 270	GW 52 243	GW 52 263	-	-	-

TECHNICAL COMPONENTS AND ACCESSORIES FOR CABLE TIES

Self-adhesive fixing clips for ties		GW 52 226	For tie widths up to 4.5mm
		GW 52 227	For tie widths up to 5mm
Fixing supports for ties		GW 52 228	For tie widths up to 5mm
		GW 52 229	For tie widths up to 9mm
Tie-puller clamp		GW 52 410	Tie-puller clamp for standard ties


OUTDOOR TIES

Dimensions LxH (mm)	Tightening capacity Ø (mm)	LTR TIES
		
6x115	5 - 25	GW 52 201
6x180	9 -45	GW 52 202
6x290	20 - 78	GW 52 203
9x180	10 - 40	GW 52 204
9x265	26 - 60	GW 52 205
9x360	26 - 93	GW 52 206
9x510	70 - 140	GW 52 207
9x760	70 - 220	GW 52 208

TECHNICAL COMPONENTS AND ACCESSORIES FOR OUTDOOR TIES

Supports for outdoor ties		GW 52 209	Screw support
Fixing supports for ties		GW 52 210	Wall plug support
Tie-puller clamp		GW 52 411	Tie-puller clamp for outdoor ties

44 MS - MOBILE AND MODULAR TERMINAL BLOCKS

CONNECTION CAPACITY	MODULAR BARS TRAILING TERMINAL BLOCKS TRANSPARENT - IP20		12-POLE MODULAR TERMINAL BLOCKS WITH BRASS TERMINALS - BLACK	
		SCREW TYPE: SLOTTED		-
2,5 mm²		GW 44 661		GW 44 601
4 mm²		GW 44 665		GW 44 602
6 mm²		GW 44 662		-
10 mm²		GW 44 663		GW 44 603
16 mm²		GW 44 664		GW 44 604
		SCREW TYPE: HEXAGONAL		-
25 mm²		GW 44 666		GW 44 605
35 mm²		GW 44 667		-

44 MM - MULTI-POLE TERMINAL BLOCKS

CONNECTION CAPACITY	PRESS-ON FIXING MULTI-POLE TERMINAL BLOCKS - GREY RAL 7035		SCREW-ON FIXING MULTI-POLE FEEDTHROUGH TERMINAL BLOCKS - GREY RAL 7035	
3 poles x 4 mm²		GW 44 606		-
3 poles x 6 mm²		-		GW 44 609
3 poles x 16 mm²		-		GW 44 611
3 poles x 35 mm²		-		GW 44 613
4 poles x 4 mm²		GW 44 607		-
5 poles x 4 mm²		GW 44 608		-
5 poles x 6 mm²		-		GW 44 610
5 poles x 16 mm²		-		GW 44 612
5 poles x 35 mm²		-		GW 44 614

44 ME - SINGLE-POLE EQUIPOTENTIAL TERMINAL BLOCKS


CONNECTION CAPACITY	SINGLE-POLE EQUIPOTENTIAL TERMINAL BLOCKS WITH INDIRECT PLATE-TIGHTENING - TRANSPARENT	
4 ways x 6 mm²		GW 44 704
6 ways x 6 mm²		GW 44 706
8 ways x 6 mm²		GW 44 708
Support for fixing on DIN rail		GW 44 720
SINGLE-POLE EQUIPOTENTIAL TERMINAL BLOCKS WITH INDIRECT SCREW-TIGHTENING - TRANSPARENT		
3 ways x 6 mm²		GW 44 671
5 ways x 6 mm²		GW 44 672
4 ways x 16 mm²		GW 44 673
2 ways x 16 mm² + 3 ways x 6 mm²		GW 44 674
2 ways x 16 mm² + 9 ways x 6 mm²		GW 44 675
2 ways x 35 mm² + 4 ways x 16 mm²		GW 44 676
Support for fixing on DIN rail		GW 44 681
Adapter		GW 44 682
Rail for fixing in PTC boxes		GW 44 683

44 MP - MODULAR DISTRIBUTION TERMINAL BLOCKS

RATED CURRENT		Code	MAX. INPUT CONNECTION	MAX. OUTPUT CONNECTION	Icw (1s)
TWO-POLE MODULAR DIVIDER TERMINAL BLOCKS WITH TRANSPARENT PROTECTION COVER					
In: 100 A		GW 44 691	1x(6-35) mm²	[1x(4-25) + 5x(1,5-10)] mm²	6 kA
In: 125 A		GW 44 693	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1,5-10)] mm²	6 kA
FOUR-POLE MODULAR DIVIDER TERMINAL BLOCKS WITH TRANSPARENT PROTECTION COVER					
In: 100 A		GW 44 696	1x(6-35) mm²	[1x(4-25) + 5x(1,5-10)] mm²	6 kA
In: 125 A		GW 44 698	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1,5-10)] mm²	6 kA
In: 160 A		GW 44 699	1x(16-50) mm²	[2x(10-35) + 2x(6-25) + 8x(4-16)] mm²	10 kA

GW FIT

Accessories for electrical installation

			COMPATIBILITY BETWEEN TERMINAL BLOCKS AND JUNCTION BOXES					
			44 MM RANGE - MULTI-POLE TERMINAL BLOCKS					
			PRESS-ON FIXING			SCREW-ON FIXING WITH FEEDTHROUGH TERMINALS		
								
Type	**Range**	**Dimensions (mm)**	**GW 44 606** 3x4 mm²	**GW 44 607** 4x4 mm²	**GW 44 608** 5x4 mm²	**GW 44 609** 3x6 mm² **GW 44 610** 5x6 mm²	**GW 44 611** 3x16 mm² **GW 44 612** 5x16 mm²	**GW 44 613** 3x35 mm² **GW 44 614** 5x35 mm²
44 CE RANGE: SURFACE-MOUNTING JUNCTION BOXES	IP 44 	Ø 65	●	●	●			
		Ø 80	●	●	●	●		
		80x80	●	●	●	●		
	IP 55 - IP 56 	100x100	●	●	●	●	●	
		120x80	●	●	●	●	●	
		150x110				●	●	●
		190x140				●	●	●
		240x190				●	●	●
		300x220				●	●	●
		380x300				●	●	●
		460x380				●	●	●
48 RANGE: FLUSH-MOUNTING JUNCTION BOXES	48 PT/PT DIN 	92x92				●	●	
		118x96				●	●	
		152x98				●	●	
		160x130				●	●	●
		196x152				●	●	●
		294x152				●	●	●
		392x152				●	●	●
		480x160				●	●	●
		516x202				●	●	●
		516x294				●	●	●
	48 CM 	260x260				●	●	
		520x260				●	●	
	48 PTC 	138x169	●	●	●	●	●	●
		308x169				●	●	●
		398x169				●	●	●

• = Suitable

COMPATIBILITY BETWEEN TERMINAL BLOCKS AND JUNCTION BOXES

44 ME RANGE - SINGLE-POLE EQUIPOTENTIAL TERMINAL BLOCKS

			With indirect plate-tightening			With indirect screw-tightening				
										
Type	**Range**	**Dimensions (mm)**	**GW 44 704** 4 ways x 6 mm²	**GW 44 706** 6 ways x 6 mm²	**GW 44 708** 8 ways x 6 mm²	**GW 44 671** 3 ways x 6 mm²	**GW 44 672** 5 ways x 6 mm²	**GW 44 673** 4 ways x 16 mm² **GW 44 674** (2x16)+(3x6) mm²	**GW 44 675** (2x16)+(9x6) mm²	**GW 44 676** (2x35)+(4x16) mm²
44 CE RANGE: SURFACE-MOUNTING JUNCTION BOXES	**IP 44** 	Ø 65	●	●		●				
		Ø 80	●	●	●	●	●			
		80x80	●	●	●	●	●			
		100x100	●	●	●	●	●	●		
		120x80	●	●	●	●	●	●		
		150x110	●	●	●	●	●	●	●	●
		190x140	●	●	●	●	●	●	●	●
	IP 55 - IP 56	240x190	●	●	●	●	●	●	●	●
		300x220	●	●	●	●	●	●	●	●
		380x300	●	●	●	●	●	●	●	●
		460x380	●	●	●	●	●	●	●	●
48 RANGE: FLUSH-MOUNTING JUNCTION BOXES		92x92	●	●	●	●	●			
		118x96	●	●	●	●	●	●		
		152x98	●	●	●	●	●	●		
	48 PT/PT DIN	160x130	●	●	●	●	●	●	●	
		196x152	●	●	●	●	●	●		
		294x152	●	●	●	●	●	●		
		392x152	●	●	●	●	●	●		
		480x160	●	●	●	●	●	●		
	(with GW 44 682 adapter)	516x202	●	●	●	●	●	●	●	
		516x294	●	●	●	●	●	●	●	
	48 CM 	260x260	●	●	●	●	●	●		
	(with GW 44 682 adapter)	520x260	●	●	●	●	●	●		
	48 PTC 	138x169	●	●	●	●	●	●	●	●
		308x169	●	●	●	●	●	●		
	(with adapter)	398x169	●	●	●	●	●	●		
	48 PTC 	138x169	●	●	●	●	●	●	●	
		308x169	●	●	●	●	●	●	●	
	(with GW 44 683 rail)	398x169	●	●	●	●	●	●	●	

● = Suitable

NOTE: The 44 ME range terminal blocks with indirect screw-tightening are mounted on plates, or on the bottom of the boxes, using the suitable GW 44 682 adapter.
For 48 PTC range boxes on the other hand, use code GW 44 683.
The 44 ME range terminal blocks with indirect plate-tightening are mounted on the DIN rail of the 48 PT DIN boxes, using the suitable GW 44 720 support.

GW FIT

Accessories for electrical installation

Complete system comprising cable glands, plastic and metal fixings, couplings for rigid conduits and sheaths, cable ties for external and junction and connection terminal blocks. The depth of the range and breadth of the offers of each family makes GEWISS the specialist and ideal partner when implementing any type of system, from residential to commercial and industrial sector.



PLASTIC CABLE GLANDS AND ACCESSORIES

Cable glands



GWT
650°C



GW 52 001

Nylon cable glands - PG pitch - grey RAL 7035 - IP66

Code	PG pitch	Mounting hole Ø (mm)	For cables Ø (mm)	Pack Carton
GW 52 001	7	12.5	from 3 to 6	50/900
GW 52 002	9	16	from 6 to 8	50/600
GW 52 003	11	19	from 8 to 10.5	25/500
GW 52 004	13.5	20	from 9 to 12.5	25/500
GW 52 005	16	23	from 13 to 16	25/375
GW 52 006	21	29	from 9 to 10/from 17 to 20	25/400
GW 52 007	29	37	from 13.5 to 15/from 21 to 26	25/250
GW 52 008	36	48	from 17 to 20/from 30 to 34	10/130
GW 52 009	42	54	from 36 to 39/from 40 to 43	6/120
GW 52 010	48	60	from 38 to 40/from 46 to 50	5/100

ACCESSORIES SUPPLIED: fixing nut.
APPLICATIONS: for making watertight installations with direct grip on cable.



GW 52 075

Nylon cable glands - PG pitch - grey RAL 7035 - IP68

Code	PG pitch	Mounting hole Ø (mm)	For cables Ø (mm)	Pack Carton
GW 52 071	7	12.5	from 3.5 to 6.5	50/600
GW 52 072	9	16	from 4 to 8	50/400
GW 52 073	11	19	from 5 to 10	50/600
GW 52 074	13.5	20	from 6 to 12	25/300
GW 52 075	16	23	from 10 to 14	25/300
GW 52 076	21	29	from 13 to 18	25/200
GW 52 077	29	37	from 18 to 25	25/150
GW 52 078	36	48	from 22 to 32	10/120
GW 52 079	42	54	from 30 to 38	6/84
GW 52 080	48	60	from 34 to 44	5/60

ACCESSORIES SUPPLIED: fixing nut.



GW 52 042

Nylon cable glands - METRIC pitch - grey RAL 7035 - IP68

Code	ISO pitch	Mounting hole Ø (mm)	For cables Ø (mm)	Pack Carton
GW 52 042	12x1.25	12	from 3 to 6.5	50/600
GW 52 043	16x1.5	16	from 5 to 10	50/400
GW 52 044	20x1.5	20	from 10 to 14	25/300
GW 52 045	25x1.5	25	from 13 to 18	25/200
GW 52 046	32x1.5	32	from 18 to 25	25/150
GW 52 047	40x1.5	40	from 22 to 32	10/120
GW 52 048	50x1.5	50	from 30 to 38	6/84
GW 52 049	63x1.5	63	from 35 to 44	5/60

ACCESSORIES SUPPLIED: fixing nut.
APPLICATIONS: direct installation on fixing enclosures or components in feedthrough holes.
Coupling in installations where a high protection rating is required in the presence of chemical substances, shocks and vibrations.



GW 52 025

Nylon cable glands - PG pitch with housing for rigid conduit - grey RAL 7035 - IP66

Code	PG pitch	Mounting hole Ø (mm)	For external conduits (mm)	For cables Ø (mm)	Pack Carton
GW 52 024	13.5	20	16	from 9 to 12.5	15/300
GW 52 025	16	23	20	from 13 to 16	15/240
GW 52 026	21	29	25	from 9 to 10/from 17 to 20	15/240
GW 52 027	29	37	32	from 13.5 to 15/from 21 to 26	15/135
GW 52 028	36	48	40	from 17 to 20/from 30 to 34	6/54
GW 52 029	42	54	50	from 36 to 39/from 40 to 43	4/80

ACCESSORIES SUPPLIED: fixing nut.

APPLICATIONS: for making watertight installations with direct clamping on the cable and attractive conduit-box coupling.

Closure caps



GW 52 366

Nylon closure caps - grey RAL 7035 - IP65

Code	Pitch	Pack Carton
GW 52 361	PG7	100/500
GW 52 362	PG9	100/500
GW 52 363	PG11	100/400
GW 52 364	PG13.5	100/400
GW 52 365	PG16	100/300
GW 52 366	PG21	100/300
GW 52 367	PG29	50/250
GW 52 368	PG36	25/150
GW 52 369	PG42	25/125
GW 52 370	PG48	10/100
GW 52 372	M12	100/500
GW 52 373	M16	100/500
GW 52 374	M20	100/400
GW 52 375	M25	100/400
GW 52 376	M32	50/250
GW 52 377	M40	50/200
GW 52 378	M50	25/150
GW 52 379	M63	10/100

NOTE: IP65 - only obtained with the aid of an O-ring.



GW 52 452

O-ring for closure caps

Code	For caps with pitch	Pack Carton
GW 52 441	PG7	500/2500
GW 52 442	PG9	500/2500
GW 52 443	PG11	500/2000
GW 52 444	PG13.5	500/2000
GW 52 445	PG16	500/2000
GW 52 446	PG21	500/1500
GW 52 447	PG29	250/1250
GW 52 448	PG36	100/1000
GW 52 449	PG42	50/500
GW 52 450	PG48	50/400
GW 52 452	M12	500/2500
GW 52 453	M16	500/2500
GW 52 454	M20	500/2000
GW 52 455	M25	500/2000
GW 52 456	M32	250/1250
GW 52 457	M40	50/1250
GW 52 458	M50	500/1000
GW 52 459	M63	50/500

Fixing nuts



GW 52 341

Nylon fixing nuts - Grey RAL 7035

Code	Pitch	Pack Carton
GW 52 341	PG7	100/1000
GW 52 342	PG9	100/1000
GW 52 343	PG11	100/800
GW 52 344	PG13.5	100/800
GW 52 345	PG16	100/600
GW 52 346	PG21	100/500
GW 52 347	PG29	50/250
GW 52 348	PG36	25/200
GW 52 349	PG42	25/150
GW 52 350	PG48	25/100
GW 52 352	M12	100/1000
GW 52 353	M16	100/1000
GW 52 354	M20	100/800
GW 52 355	M25	100/800
GW 52 356	M32	100/600
GW 52 357	M40	100/500
GW 52 358	M50	50/250
GW 52 359	M63	25/125

Couplings and cable-glands



Shockproof polymer conduit/box couplings Grey RAL 7035

GWT
650°C



GW 50 415

Code	For external conduits (mm)	Mounting hole Ø (mm)	IP with rigid conduit	IP with corrugated conduit	Pack Carton
GW 50 415	16	20	IP66	IP54	25/200
GW 50 416	20	23	IP66	IP54	25/200
GW 50 417	25	29	IP66	IP54	25/150
GW 50 418	32	37	IP66	IP54	10/100
GW 50 419	40	48	IP66	IP44	6/60
GW 50 420	50	54	IP66	IP44	5/50

CHARACTERISTICS: the box conduit coupling device allows corrugated conduits to be connected to the junction boxes, guaranteeing the minimum IP4X degree of protection in areas at greater risk in the event of a fire whenever required.
ACCESSORIES SUPPLIED: fixing nut.

Flexible polymer conduit/box couplings Grey RAL 7035 - IP44

GWT
650°C



GW 50 421

Code	For external conduits (mm)	Mounting hole Ø (mm)	Pack Carton
GW 50 421	16	23	50/700
GW 50 422	20	23	50/700
GW 50 423	20	29	25/350
GW 50 424	25	29	25/350
GW 50 425	32	37	15/210
GW 50 426	40	37	10/160
GW 50 427	50	48	10/90

Flexible polymer cable gland - Grey RAL 7035 - IP55

GWT
960°C



GW 50 430

Code	For ext. conduits max (mm)	Mounting hole Ø (mm)	Pack Carton
GW 50 428	16	19	100/1000
GW 50 429	20	23	100/1000
GW 50 430	25	29	100/1000
GW 50 431	32	37	50/500
GW 50 432	40	48	35/350

NOTE: quick entry cable glands, except GW50428.
CHARACTERISTICS: quick entry cable glands, suitable for cables with Ø from 4 to 14mm.
Cable gland GW50429, suitable for conduits ø 16, 20mm.
Cable gland GW50430, suitable for conduits ø 16, 20, 25mm.
Cable gland GW50431, suitable for conduits ø 16, 20, 25, 32mm.
Cable gland GW50432, suitable for conduits ø 16, 20, 25, 32, 40mm.

METAL CABLE GLANDS AND ACCESSORIES



Cable glands

Insulated cable gland - IP65



GW 76 837

Code	Type of pitch	Seals Ø (mm)	Pack Carton
GW 76 837	PG11	7.5 / 10 / 12.5	1/50
GW 76 839	M20	4 / 7 / 10 / 13	1/50

Nickel-plated brass cable glands - IP65



GW 76 845

Code	Type of pitch	Seals Ø (mm)	Pack Carton
GW 76 841	PG11	7.5 / 10 / 12.5	1/50
GW 76 842	PG13.5	7.5 / 10 / 12.5	1/50
GW 76 843	PG16	7.5 / 10 / 12.5	1/50
GW 76 844	PG21	10 / 13 / 16 / 19	1/50
GW 76 845	PG29	18 / 21 / 24 / 27	1/10
GW 76 846	PG36	24 / 27 / 30 / 33	1/10
GW 76 847	PG42	30 / 33 / 36 / 39	1/10
GW 76 848	M20	4 / 7 / 10 / 13	1/50
GW 76 849	M25	8.5 / 11.5 / 14.5 / 17.5	1/50
GW 76 850	M32	16 / 19 / 22 / 25	1/10
GW 76 851	M40	23 / 26 / 29 / 32	1/10
GW 76 852	M50	30 / 33 / 36 / 39	1/10

CHARACTERISTICS: nickel-plated brass cable gland with complete sealing gaskets for a wide range of cable diameters.



GW 76 829

Nickel-plated brass cable glands - IP68

Code	Type of pitch	For cables Ø (mm)	Pack Carton
GW 76 825	PG11	from 4 to 9	10/100
GW 76 826	PG13.5	from 7 to 11	10/100
GW 76 827	PG16	from 10 to 13	10/100
GW 76 828	PG21	from 12 to 17	5/50
GW 76 829	PG29	from 17 to 24	5/50
GW 76 830	PG36	from 20 to 26 / from 27 to 34	5/50
GW 76 897	PG42	from 32 to 36	2/10
GW 76 894	M12	from 3 to 6.5	50/250
GW 76 896	M16	from 4 to 9	10/100
GW 76 831	M20	from 10 to 13	10/100
GW 76 832	M25	from 12 to 17	10/100
GW 76 833	M32	from 14 to 21	5/50
GW 76 834	M40	from 19 to 27	5/50
GW 76 835	M50	from 25 to 34	2/10
GW 76 895	M63	from 34 to 48	5/40

CHARACTERISTICS: nickel-plated brass cable gland with mechanic cable-snap device.
NOTE: fixing nuts not supplied.

Extensions



GW 76 867

Nickel-plated brass extensions - IP65

Code	Male thread	Female thread	Pack Carton
GW 76 865	PG11	PG13.5	10/100
GW 76 866	PG13.5	PG16	10/100
GW 76 867	PG16	PG21	10/100
GW 76 868	PG21	PG29	5/50
GW 76 869	PG29	PG36	5/50
GW 76 870	M20	M25	10/100
GW 76 871	M25	M32	10/100
GW 76 872	M32	M40	5/50
GW 76 873	M40	M50	5/50

NOTE: IP degree of protection: depends on the other components with which they are coupled.

Closure caps



GW 76 979

Nickel-plated brass closure caps - IP65

Code	Type of pitch	Pack Carton
GW 76 980	PG11	10/100
GW 76 981	PG13.5	10/100
GW 76 982	PG16	10/100
GW 76 983	PG21	10/100
GW 76 984	PG29	5/50
GW 76 985	PG36	5/50
GW 76 986	PG42	5/50
GW 76 972	M12	100/400
GW 76 973	M16	100/300
GW 76 975	M20	10/100
GW 76 976	M25	10/100
GW 76 977	M32	10/100
GW 76 978	M40	5/50
GW 76 979	M50	5/50
GW 76 974	M63	10/100

ACCESSORIES SUPPLIED: sealing gasket.

Fixing nuts




GW 76 959

Nickel-plated brass fixing nuts

Code	Type of pitch	Pack Carton
GW 76 957	PG11	25/100
GW 76 958	PG13.5	25/100
GW 76 959	PG16	25/100
GW 76 960	PG21	25/100
GW 76 961	PG29	25/100
GW 76 962	PG36	10/50
GW 76 963	PG42	10/50
GW 76 966	M12	100/500
GW 76 951	M16	25/100
GW 76 952	M20	25/100
GW 76 953	M25	25/100
GW 76 954	M32	25/100
GW 76 955	M40	10/50
GW 76 956	M50	10/50
GW 76 967	M63	25/125

METAL CABLE GLANDS AND ACCESSORIES FOR ATEX ENVIRONMENTS - ZONE 1(G) - ZONE 20(D)



Metal cable glands



GW 76 901

ATEX cable glands in nickel-plated brass with PG-pitch and long thread - IP68

Code	Type of pitch	Mounting hole Ø (mm)	For cables Ø (mm)	Pack Carton
GW 76 901	PG7	12.5	from 3 to 6.5	10/100
GW 76 902	PG9	16	from 4 to 8	10/100
GW 76 903	PG11	19	from 5 to 10	10/100
GW 76 904	PG13.5	20	from 6.5 to 12	10/100
GW 76 905	PG16	23	from 7 to 12	10/100
GW 76 906	PG21	29	from 13 to 18	5/50
GW 76 907	PG29	37	from 18 to 25	5/50
GW 76 908	PG36	48	from 22 to 32	5/50
GW 76 909	PG42	54	from 32 to 38	2/10
GW 76 910	PG48	60	from 37 to 44	2/10

NOTE: fixing nuts not supplied.
ATEX Classification. Equipment-group II Category 2G 1D.
Type of protection for use in explosive gas atmospheres: e.
Type of protection for use in explosive dust atmospheres: ta.
Ambient temperature range: -60°C <= Ta <= +95°C.



GW 76 921

ATEX cable glands in nickel-plated brass with metric pitch and long thread - IP68

Code	Type of pitch	Mounting hole Ø (mm)	For cables Ø (mm)	Pack Carton
GW 76 921	M12	12	from 3 to 6.5	10/100
GW 76 922	M16	16	from 6 to 10	10/100
GW 76 923	M20	20	from 10 to 14	10/100
GW 76 924	M25	25	from 14 to 18	10/100
GW 76 925	M32	32	from 20 to 25	5/50
GW 76 926	M40	40	from 22 to 32	5/50
GW 76 927	M50	50	from 32 to 38	2/10
GW 76 928	M63	63	from 37 to 44	2/10

NOTE: fixing nuts not supplied.
ATEX Classification. Equipment-group II Category 2G 1D.
Type of protection for use in explosive gas atmospheres: e.
Type of protection for use in explosive dust atmospheres: ta.
Ambient temperature range: -60°C <= Ta <= +95°C.

Fixing nuts




GW 76 941

Nickel-plated brass fixing nuts

Code	Type of pitch	Pack Carton
GW 76 941	PG7	25/100
GW 76 942	PG9	25/100
GW 76 957	PG11	25/100
GW 76 958	PG13.5	25/100
GW 76 959	PG16	25/100
GW 76 960	PG21	25/100
GW 76 961	PG29	25/100
GW 76 962	PG36	10/50
GW 76 963	PG42	10/50
GW 76 943	PG48	10/50
GW 76 949	M12	25/100
GW 76 951	M16	25/100
GW 76 952	M20	25/100
GW 76 953	M25	25/100
GW 76 954	M32	25/100
GW 76 955	M40	10/50
GW 76 956	M50	10/50
GW 76 950	M63	10/50

PLASTIC FIXINGS FOR CONDUITS AND CABLES

Fixings for conduits





GW 50 603

Shockproof polymer saddle snap clip - Grey RAL 7035

HF HALOGEN FREE

Code	For external conduits (mm)	Wall-conduit axis distance (mm)	Pack Carton
GW 50 601	16	20	100/1800
GW 50 602	20	22	100/1600
GW 50 603	25	24.5	100/900
GW 50 604	32	28	100/900
GW 50 628	40	32	50/450
GW 50 629	50	37	50/450

NOTES: suitable for riveting machines.GW50628 and GW50629 are not Halogen Free.
APPLICATIONS: recommended for surface mounting



GW 50 605

Shockproof polymer saddle collar clip - Grey RAL 7035


HF HALOGEN FREE

Code	For external conduits (mm)	Wall-conduit axis distance (mm)	Pack Carton
GW 50 605	16	20	100/900
GW 50 606	20	22	100/900
GW 50 607	25	24.5	100/600
GW 50 608	32	28	50/450
GW 50 630	40	32	35/350
GW 50 631	50	37	25/200

APPLICATIONS: Recommended for ceiling applications.

Modular lock-joint rail to fix shockproof polymer supports - Grey RAL 7035

Code	Length (mm)	Pack Carton
GW 50 609	200	50/350



GW 50 609

Multi-diameter clamp supports - Grey RAL 7035

Code	For external conduits (mm)	Wall-conduit axis distance (mm)	Pack Carton
GW 50 651	16-20	14-16	75/900
GW 50 652	25-32	21.5-25	25/250
GW 50 653	40-50	30-35	15/150



GW 50 651



DX 51 120

Fixing collar - Grey RAL 7035

Code	For external conduits (mm)	Description	Pack Carton
DX 51 120	16-20	Reopened collar	100/1500
DX 51 232	16-32	Collar cannot be reopened	100/800
DX 51 263	25-63	Collar cannot be reopened	100/400

USE: rigid conduits can be fixed to the wall with the aid of the wall plugs. Assembly hole Ø7mm.
MATERIAL: self-extinguishing polyamide.
NOTE: for an optimal collar closing use the tie tool.



DX 51 306

Fixing dowels for collar - Grey RAL 7035

Code	For mounting holes Ø (mm)	Characteristics	Pack Carton
DX 51 306	6	1 Impact insert included	200/600
DX 51 308	8	1 Impact insert included	200/600

USE: allow fixing of rigid conduits fixing collars to walls.

Fixings for cables



GW 50 610

Shockproof polymer clips with hardened steel pin - Grey RAL 7035

Code	For external conduits (mm)	Pack Carton
Colour: Grey RAL 7035		
GW 50 610	3-4	100/8000
GW 50 611	5-6	100/8000
GW 50 612	7-8	100/8000
GW 50 613	9-10	100/6000
GW 50 614	11-12	100/6000
GW 50 615	13-14	100/6000
GW 50 616	15-16	100/3000
GW 50 617	19-20	100/1800
GW 50 618	21-22	100/2000
GW 50 619	25-26	50/900
GW 50 620	31-32	50/1000
Colour: White		
GW 50 621	5-6	100/8000
GW 50 622	7-8	100/8000



GW 50 623

Flat shockproof polymer clips with pin of hardened steel - White

Code	Colour	For flat cables width	Pack Carton
GW 50 623	White	5 - 6 mm	100/4000
GW 50 624	White	7 - 8 mm	100/15000
GW 50 625	White	10 - 11 mm	100/4800



GW 50 626

Hardened steel pins

Code	Description	Pack Carton
GW 50 626	Totally insulated	100/1000
GW 50 627	With insulating collar	100/1000

NOTE: Each package contains 100 small nails.

METAL COLLARS FOR CONDUITS AND CABLES

Collars in galvanized steel



GW 50 801

Galvanised steel collars M6 thread with 2 screws

Code	For external conduits (mm)	Pack Carton
GW 50 801	10-11	100/1600
GW 50 802	12-13	100/800
GW 50 803	14-15	100/800
GW 50 804	16-17	100/800
GW 50 805	19-20	100/800
GW 50 806	21-22	100/600
GW 50 807	25-26	100/600
GW 50 808	31-32	100/600
GW 50 809	38-40	100/300
GW 50 810	48-50	50/300

Clips in galvanized steel



GW 50 811

Galvanised steel clips hole 12x6 mm

Code	For external conduits (mm)	Pack Carton
GW 50 811	10-11	100/2400
GW 50 812	12-13	100/2000
GW 50 813	14-15	100/2000
GW 50 814	16-17	100/1600
GW 50 815	19-20	100/1000
GW 50 816	21-22	50/1000
GW 50 817	25-26	50/1000
GW 50 818	31-32	50/600
GW 50 819	38-40	50/600
GW 50 820	48-50	50/300



GW 50 821

Galvanised steel U-bolts with two holes

Code	For external conduits (mm)	Pack Carton
Hole dimension (mm): 7x4		
GW 50 821	10-11	100/2400
GW 50 822	12-13	100/3500
GW 50 823	14-15	100/2000
GW 50 824	16-17	100/1600
GW 50 825	19-20	100/2000
GW 50 826	21-22	50/1000
GW 50 827	25-26	50/800
Hole dimension (mm): 10x6		
GW 50 828	31-32	50/600
GW 50 829	38-40	50/600
GW 50 830	48-50	50/300

GW FIT

STRAPS FOR CORRUGATED CONDUITS

Fixing straps



GW 50 791

Straps for positioning the conduits on the floor

Code	Description	Roll length (m)	Ribbon height (mm)	Pack Carton
GW 50 791	Strap in perforated, galvanized steel	10	12	1/10
GW 50 792	Strap in fabric	10	15	10/100



GW 50 798

Kit for manual riveting

Code	Description	Pack Carton
GW 50 798	Firing pin	1/10
GW 50 799	Steel pin - 18mm	200/4000

DISPENSER FOR ACCESSORIES

Dispenser case for electrical installation accessories



GW 52 420

Multi-compartment dispenser case with snap-on security closure

Code	Accessories supplied	Dimensions LxHxD (mm)	Pack Carton
GW 52 420	Upper compartment and 4 extractable compartments	420x400x320 mm	1

TOOLS FOR PERFORATING ENCLOSURES

Drill milling cutter

Multi-diameter drill milling cutter in HSS steel to drill boxes, boards and trunking in insulating material



GW 52 401

Code	Description	Ø of perforation	Pack Carton
GW 52 401	Drill milling cutter	From 3.5 to 40	1/4

Cup drill milling cutter to drill panels



GW 52 402

Code	Description	Pack Carton
GW 52 402	Cup drill milling Ø56	10

APPLICATIONS: suitable for low voltage flush-mounting socket-outlets IEC 309 2P+E 16A and for all the extra-low voltage flush-mounting socket-outlets IEC 309.

Cup drill milling cutter to drill hollow cavity wall



GW 52 403

Code	Description	Pack Carton
GW 52 403	Cup drill milling Ø62	10

Tapered drill milling cutter in HSS steel to finish and countersink holes for metal boards and trunking



GW 52 412

Code	Description	For holes Ø (mm)	Pack Carton
GW 52 412	Tapered drill milling cutter	40	1/4

COUPLING DEVICES FOR RIGID CONDUITS

RK connections - Grey RAL 7035



DX 40 016

Coupling - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 016	16	30/300
DX 40 020	20	30/450
DX 40 025	25	20/240
DX 40 032	32	10/100
DX 40 040	40	5/25
DX 40 050	50	15
DX 40 063	63	8



DX 40 116

Tight radius bend - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 116	16	30/300
DX 40 120	20	30/300
DX 40 125	25	20/100
DX 40 132	32	10/50
DX 40 140	40	5/25
DX 40 150	50	10
DX 40 163	63	1

NOTE: DX40163 not Halogen Free.

Inspectable T - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 216	16	30/120
DX 40 220	20	30/120
DX 40 225	25	20/60
DX 40 232	32	10/30



DX 40 216

Inspectable bend - IP40

Code	Conduits Ø (mm)	Pack Carton
DX 40 316	16	30/180
DX 40 320	20	30/120
DX 40 325	25	20/60
DX 40 332	32	10/40



DX 40 316

MORBIDX connections - Grey RAL 7035



DX 43 016

Release coupling - IP67

Code	Conduits Ø (mm)	Pack Carton
DX 43 016	16	10/300
DX 43 020	20	10/240
DX 43 025	25	5/150
DX 43 032	32	5/120
DX 43 040	40	5/90
DX 43 050	50	3/54



DX 43 116

Release tight bend - IP67

Code	Conduits Ø (mm)	Pack Carton
DX 43 116	16	10/100
DX 43 120	20	10/80
DX 43 125	25	5/50
DX 43 132	32	5/30
DX 43 140	40	5/15
DX 43 150	50	8



DX 43 216

Release conduit-box coupling - IP67

Code	Conduits Ø (mm)	ISO pitch	For holes Ø (mm)	Pack Carton
DX 43 216	16	M 16x1.5	16	10/360
DX 43 220	20	M 20x1.5	20	10/300
DX 43 225	25	M 25x1.5	25	5/180
DX 43 232	32	M 32x1.5	32	5/150
DX 43 240	40	M 40x1.5	40	5/30
DX 43 250	50	M 50x1.5	50	5/15



DX 43 316

Release conduit-sheath coupling - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 316	16	12	10/450
DX 43 320	20	16	10/300
DX 43 325	25	20	5/210
DX 43 332	32	25	5/120
DX 43 340	40	32	5/25
DX 43 350	50	40	5/20

GW FIT



DX 43 416

Release conduit-sheath coupling equal diameter - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 416	16	16	10/360
DX 43 420	20	20	10/240
DX 43 425	25	25	5/150
DX 43 432	32	28	5/40
DX 43 440	40	40	5/20

USE: coupling of a rigid protective conduit with a spiral sheath of the DIFLEX range these connections allow rigid conduits and sheaths to have the same internal diameter, making the wiring easy.



DX 43 516

LA SVOLTA conduit-conduit coupling - IP65

Code	Conduits Ø (mm)	Working length (mm)	Pack Carton
DX 43 516	16	110	60
DX 43 520	20	132	40
DX 43 525	25	209	20
DX 43 532	32	301	20
DX 43 540	40	302	12
DX 43 550	50	311	9

SPEEDY-FLEX couplings - Grey RAL 7035



GW 50 201

Watertight flexible couplings - IP66

Code	For external conduits (mm)	External Ø (mm)	Internal Ø (mm)	Length (mm)	Pack Carton
GW 50 201	16	27	13	140	20/60
GW 50 202	20	31.5	17	160	20/120
GW 50 203	25	41	21.5	205	10/40
GW 50 204	32	55	28	290	10/60
GW 50 205	40	65	35.5	400	6/30
GW 50 206	50	72	44.5	515	6/36

CHARACTERISTICS: multifunctional couplings allowing the realisation of 0-90° variable angle curves and misaligned conduit-conduit couplings.



GW 50 210

Protected flexible couplings - IP44

Code	For external conduits (mm)	External Ø (mm)	Internal Ø (mm)	Length (mm)	Pack Carton
GW 50 207	16	24	13	135	20/60
GW 50 208	20	30	17	160	20/120
GW 50 209	25	35	21.5	205	20/120
GW 50 210	32	45	28	280	10/20
GW 50 211	40	55	35.5	400	6/30
GW 50 212	50	65	44.5	515	6/36

CHARACTERISTICS: multifunctional couplings allowing the realisation of 0-90° variable angle curves and misaligned conduit-conduit couplings.

Accessories



DX 51 416

Conduit-bending spring for RK15

Code	Conduits Ø (mm)	Pack Carton
DX 51 416	16	1/10
DX 51 420	20	1/10
DX 51 425	25	1/5
DX 51 432	32	1/5
DX 51 440	40	1
DX 51 450	50	1

USE: for cold bending rigid conduits.
MATERIAL: special galvanised steel square wire mesh.



DX 51 316

Conduit-bending spring for RKB

Code	Conduits Ø (mm)	Pack Carton
DX 51 316	16	1/10
DX 51 320	20	1/10
DX 51 325	25	1/5

USE: for cold bending rigid conduits.
MATERIAL: special galvanised steel square wire mesh.



DX 51 600

Conduit cutter

Code	Description	Pack Carton
DX 51 600	Conduit cutter	1/5

COUPLING DEVICES FOR SPIRAL SHEATH

Rotating unions



DX 54 020

Straight, revolving coupling device - Metric pitch - IP54

Code	Sheath Ø (mm)	ISO pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 008	8	M 12x1.5	20/180
DX 54 010	10	M 16x1.5	20/160
DX 54 012	12	M 16x1.5	10/100
DX 54 016	16	M 20x1.5	10/150
DX 54 020	20	M 25x1.5	10/100
DX 54 022	22	M 25x1.5	10/100
DX 54 025	25	M 32x1.5	5/60
DX 54 028	28	M 32x1.5	5/40
DX 54 032	32	M 40x1.5	5/30
DX 54 040	40	M 50x1.5	25
DX 54 050	50	M 63x1.5	15
Colour: Black RAL 9005			
DX 54 108	8	M 12x1.5	20/180
DX 54 110	10	M 16x1.5	20/160
DX 54 112	12	M 16x1.5	10/100
DX 54 116	16	M 20x1.5	10/150
DX 54 120	20	M 25x1.5	10/100
DX 54 122	22	M 25x1.5	10/100
DX 54 125	25	M 32x1.5	5/60
DX 54 128	28	M 32x1.5	5/40
DX 54 132	32	M 40x1.5	5/30
DX 54 140	40	M 50x1.5	25
DX 54 150	50	M 63x1.5	15

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with metric pitch or in non-threaded holes via the nut and gasket supplied.



DX 54 220

Straight, revolving coupling device - GAS pitch - IP54

Code	Sheath Ø (mm)	GAS pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 208	8	1/4”	20/180
DX 54 210	10	1/4”	20/160
DX 54 212	12	3/8”	10/100
DX 54 214	14	1/2”	10/150
DX 54 216	16	1/2”	10/150
DX 54 220	20	3/4”	10/100
DX 54 222	22	3/4”	10/100
DX 54 225	25	1”	5/60
DX 54 228	28	1”	5/40
DX 54 232	32	1 1/4”	5/30
DX 54 235	35	1 1/4”	5/30
DX 54 240	40	1 1/2”	25
DX 54 250	50	2”	15
Colour: Black RAL 9005			
DX 54 308	8	1/4”	20/180
DX 54 310	10	1/4”	20/160
DX 54 312	12	3/8”	10/100
DX 54 314	14	1/2”	10/150
DX 54 316	16	1/2”	10/150
DX 54 320	20	3/4”	10/100
DX 54 322	22	3/4”	10/100
DX 54 325	25	1”	5/60
DX 54 328	28	1”	5/40
DX 54 332	32	1 1/4”	5/30
DX 54 335	35	1 1/4”	5/30
DX 54 340	40	1 1/2”	25
DX 54 350	50	2”	15

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with GAS pitches or in non-threaded holes via the nut and gasket supplied.



DX 54 420

Straight, revolving coupling device - PG pitch - IP54

Code	Sheath Ø (mm)	PG pitch	Pack Carton
Colour: Grey RAL 7035			
DX 54 408	8	7	20/180
DX 54 410	10	7	20/160
DX 54 411	10	9	20/160
DX 54 412	12	11	10/100
DX 54 413	12	13.5	10/100
DX 54 414	14	13.5	10/150
DX 54 416	16	13.5	10/150
DX 54 417	16	16	10/150
DX 54 420	20	21	10/100
DX 54 422	22	21	10/100
DX 54 425	25	29	5/60
DX 54 428	28	29	5/40
DX 54 432	32	36	5/30
DX 54 435	35	36	5/30
Colour: Black RAL 9005			
DX 54 508	8	7	20/180
DX 54 510	10	7	20/160
DX 54 511	10	9	20/160
DX 54 512	12	11	10/100
DX 54 513	12	13.5	10/100
DX 54 514	14	13.5	10/150
DX 54 516	16	13.5	10/150
DX 54 517	16	16	10/150
DX 54 520	20	21	10/100
DX 54 522	22	21	10/100
DX 54 525	25	29	5/60
DX 54 528	28	29	5/40
DX 54 532	32	36	5/30
DX 54 535	35	36	5/30

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with Pg pitches or in non-threaded holes via the nut and gasket supplied.

Fixed unions



DX 56 008

Straight, fixed coupling device - Metric pitch - IP54

Code	Sheath Ø (mm)	ISO pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 008	8	M12x1,5	20/160
DX 56 010	10	M16x1.5	10/170
DX 56 012	12	M16x1.5	10/150
DX 56 014	14	M16x1.5	10/130
DX 56 016	16	M20x1.5	10/110
DX 56 022	22	M25x1.5	10/50
DX 56 025	25	M25x1.5	10/50
DX 56 028	28	M32x1.5	10/40
DX 56 040	40	M40x1.5	15
DX 56 050	50	M50x1.5	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with metric pitch or in non-threaded holes via the nut and gasket supplied.



DX 56 208

Straight, fixed coupling device - GAS pitch - IP54

Code	Sheath Ø (mm)	GAS pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 208	8	1/4”	20/160
DX 56 210	10	1/4”	10/170
DX 56 212	12	3/8”	10/150
DX 56 214	14	1/2”	10/130
DX 56 216	16	1/2”	10/110
DX 56 222	22	3/4”	10/50
DX 56 225	25	3/4”	10/50
DX 56 228	28	1”	10/40
DX 56 232	32	1 1/4”	3/18
DX 56 235	35	1 1/4”	3/18
DX 56 240	40	1 1/2”	15
DX 56 250	50	2”	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with GAS pitches or in non-threaded holes via the nut and gasket supplied.



DX 56 408

Straight, fixed coupling device - PG pitch - IP54

Code	Sheath Ø (mm)	PG pitch	Pack Carton
Colour: Grey RAL 7035			
DX 56 408	8	7	20/160
DX 56 410	10	7	10/170
DX 56 411	12	9	10/150
DX 56 412	12	11	10/150
DX 56 413	12	13.5	10/150
DX 56 414	14	13.5	10/130
DX 56 415	16	11	10/110
DX 56 416	16	13.5	10/110
DX 56 417	16	16	10/110
DX 56 422	22	16	10/50
DX 56 423	22	21	10/50
DX 56 425	25	21	10/50
DX 56 428	28	29	10/40
DX 56 432	32	36	3/18
DX 56 435	35	36	3/18
DX 56 440	40	42	15
DX 56 450	50	48	12

USE: for the coupling of spiral sheaths to junction boxes in threaded holes with Pg pitches or in non-threaded holes via the nut and gasket supplied.

Conduit-sheath unions



DX 43 316

MORBIDX release conduit-sheath union - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 316	16	12	10/450
DX 43 320	20	16	10/300
DX 43 325	25	20	5/210
DX 43 332	32	25	5/120
DX 43 340	40	32	5/25
DX 43 350	50	40	5/20



DX 43 416

Release conduit-sheath union equal diameter - IP65

Code	Conduits Ø (mm)	Sheath Ø (mm)	Pack Carton
DX 43 416	16	16	10/360
DX 43 420	20	20	10/240
DX 43 425	25	25	5/150
DX 43 432	32	28	5/40
DX 43 440	40	40	5/20

USE: coupling of a solid protective conduit with a spiral sheath of the DIFLEX range;
allows the maintenance of the same internal diameter in line with the joint; the internal section for cable passage remains constant, increasing the space available for the system wires.

52 FS - CABLE TIES



GWT
650°C

Standard type



GW 52 231

Standard cable ties in colourless polymer

Code	Dimensions LxH (mm)	Tensile stress (daN)	Terminal grip capacity Ø	Pack Carton
GW 52 231	2.4x75	8	2 - 13 mm	1000/20000
GW 52 232	2.5x96	8	2 - 19 mm	1000/20000
GW 52 233	2.5x142	8	3 - 32 mm	100/10000
GW 52 234	2.5x203	8	4 - 50 mm	100/10000
GW 52 235	3.6x150	18	3 - 33 mm	100/10000
GW 52 236	3.6x203	18	5 - 47 mm	100/10000
GW 52 237	3.6x292	18	7 - 75 mm	100/5000
GW 52 238	4.8x190	18	4 - 45 mm	100/5000
GW 52 239	4.8x280	22	7 - 70 mm	100/5000
GW 52 240	4.8x368	22	7 - 96 mm	100/5000
GW 52 241	7.6x380	55	8 - 96 mm	100/1000
GW 52 242	9.0x610	80	11 - 162 mm	50/500
GW 52 243	9.0x914	80	12 - 253 mm	50/500

daN = Decanewton (approx. 1kg).

CHARACTERISTICS: sloping tail and rounded edges. Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

Heavy-duty



GW 52 251

Heavy duty wiring ties - black polymer

Code	Dimensions LxH (mm)	Tensile stress (daN)	Terminal grip capacity Ø	Pack Carton
GW 52 251	2.4x75	8	2 - 13 mm	1000/20000
GW 52 252	2.5x96	8	2 - 19 mm	1000/20000
GW 52 253	2.5x142	8	3 - 32 mm	100/10000
GW 52 254	2.5x203	8	4 - 50 mm	100/10000
GW 52 255	3.6x150	18	3 - 33 mm	100/10000
GW 52 256	3.6x203	18	5 - 47 mm	100/10000
GW 52 257	3.6x292	18	7 - 75 mm	100/5000
GW 52 258	4.8x190	18	4 - 45 mm	100/5000
GW 52 259	4.8x280	22	7 - 70 mm	100/5000
GW 52 260	4.8x368	22	7 - 96 mm	100/5000
GW 52 261	7.6x380	55	8 - 96 mm	100/1000
GW 52 262	9.0x610	80	11 - 162 mm	50/500
GW 52 263	9.0x914	80	12 - 253 mm	50/500

daN = Decanewton (approx. 1kg).

CHARACTERISTICS: sloping tail and rounded edges. Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

GW FIT

Re-openable



GW 52 271

Re-openable cable ties in black polymer

Code	Dimensions LxH (mm)	Tensile stress (daN)	Terminal grip capacity Ø	Pack Carton
GW 52 271	7.6x150	22	6 - 32 mm	100/1000
GW 52 272	7.6x203	22	6 - 46 mm	100/1000
GW 52 273	7.6x300	22	6 - 73 mm	100/1000

daN = Decanewton (approx. 1kg).

CHARACTERISTICS: Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

With eyelet



GW 52 281

Cable ties with eyelet in colourless polymer

Code	Dimensions LxH (mm)	Hole dimensions (mm)	Tensile stress (daN)	Terminal grip capacity Ø	Pack Carton
GW 52 281	2.5x110	4.8	8	3 - 23 mm	100/5000
GW 52 282	4.2x219	4.8	22	4 - 47 mm	100/2000

daN = Decanewton (approx. 1kg).

CHARACTERISTICS: sloping tail and rounded edges. Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

With plate



GW 52 291


Cable ties with identification tag in colourless polymer

Code	Dimensions LxH (mm)	Tensile stress (daN)	Terminal grip capacity Ø	Label	Pack Carton
GW 52 291	2.5x100	8	6 - 21 mm	25 x 8 crossways	100/5000
GW 52 292	2.5x110	8	4 - 18 mm	25 x 8 double-sided	100/5000
GW 52 293	2.5x200	8	6 - 46 mm	30 x 15 crossways	100/2000
GW 52 294	4.6x200	22	12 - 46 mm	28 x 13 lenghtways	100/2000

daN = Decanewton (approx. 1kg).

CHARACTERISTICS: sloping tail and rounded edges. Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

Complementary items



GW 52 227

Two-way self-adhesive bases in colourless polymer to secure cable ties

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 52 226	For ties up to 4.5mm	19x3.9x19	100/3000
GW 52 227	For ties up to 5mm	28x4.0x28	100/3000

USE: use the self-adhesive clips for non heavy-duty applications only, In all other cases where it is necessary to guarantee the hold, use the special supports.

NOTES: to install the product correctly, fix the clip on a smooth, clean, dry surface, with a maximum distance of 10cm between the clips, and place on a horizontal surface with the self-adhesive part facing downwards.

Colourless polymer saddles to secure cable ties



GW 52 229

Code	Description	Outer dim. LxHxD (mm)	Pack Carton
GW 52 228	For ties up to 5mm	15x7x10	100/3000
GW 52 229	For ties up to 9mm	23x9x16	100/3000

CHARACTERISTICS: screw fixing.

Tie tool



GW 52 410

Code	Suitable for	Pack Carton
GW 52 410	Cable ties	1/10

52 FS - OUTDOOR TIES



GWT
650°C

L.T.R. ties



GW 52 201

Outdoor black ties in L.T.R. polyamide 12

Code	Dimensions LxH (mm)	Number of heads	Tensile stress (daN)	Terminal grip capacity Ø	Pack Carton
GW 52 201	6x115	1	24.5	5 - 25 mm	100/4000
GW 52 202	6x180	1	24.5	9 - 45 mm	100/3000
GW 52 203	6x290	1	24.5	20 - 78 mm	100/1000
GW 52 204	9x180	1	36	10 - 40 mm	100/3000
GW 52 205	9x265	2	50	26 - 60 mm	100/1200
GW 52 206	9x360	2	50	26 - 93 mm	100/1000
GW 52 207	9x510	2	53	70 - 140 mm	100/500
GW 52 208	9x760	2	53	70 - 220 mm	100/500

daN = Decanewton (approx. 1kg).

L.T.R. (Low Temperature Resistance): high resistance to tensile stress at low temperatures.

CHARACTERISTICS: Values for resistance to tensile stress refer to T=20°C, in compliance with Standard EN 62275.

Complementary items



Shockproof polymer saddles to secure outdoor cable ties

Code	Description	Pack Carton
GW 52 209	Screw support	100/3000
GW 52 210	Wall plug base	100/3000

CHARACTERISTICS: GW52209 can be installed with Ø 4.8 mm self-tapping screws.

GW52210 can be installed with Ø 8 mm holes in hard materials (e.g. concrete) and Ø 7 mm in soft materials (e.g. hollow brick).



GW 52 411

Tie tool

Code	Suitable for	Pack Carton
GW 52 411	Outdoor ties	1/10

44 MS - TRAILING AND MODULAR TERMINAL BLOCKS

GWT 850°C

TP 125°C

Trailing terminals blocks



GW 44 665

Mobile terminal blocks with modular busbars - 450V - T 85°C - Transparent - IP20

Code	Max. section flex. cables	Min. section flex. cables	No. poles per bar	Pack Carton
Type of screw: Slotted				
GW 44 661	2.5 mm²	1 mm²	10	10/450
GW 44 665	4 mm²	1.5 mm²	10	10/450
GW 44 662	6 mm²	2.5 mm²	10	10/450
GW 44 663	10 mm²	4 mm²	10	10/300
GW 44 664	16 mm²	6 mm²	5	10/240
Type of screw: Socket head 5mm				
GW 44 666	25 mm²	10 mm²	1	5/150
GW 44 667	35 mm²	16 mm²	1	5/150

CHARACTERISTICS: GW44666 and GW44667 supplied in single terminals.

Modular terminal blocks



GW 44 601

Polymer 12 pole modular terminal blocks with brass terminals - 450V - T 85°C - Black


Code	Max. section flex. cables	Min. section flex. cables	hole Ø	Max load	Outer dim. LxHxD (mm)	Fixing	Pack Carton
GW 44 601	2.5 mm²	0.75 mm²	2.9 mm	24 A	95x15x16	With screw	10/480
GW 44 602	4 mm²	1.5 mm²	3.4 mm	32 A	117x17x20	With screw	10/240
GW 44 603	10 mm²	4 mm²	4.4 mm	57 A	141x20x23	With screw	10/160
GW 44 604	16 mm²	6 mm²	5.8 mm	76 A	172x25x32	With screw	10/120
GW 44 605	25 mm²	10 mm²	7.4 mm	101 A	210x34x38	With screw	3/36

44 MM - MULTI-POLE TERMINAL BLOCKS

GWT 850°C

TP 125°C

Press-on fixing



GW 44 608

Press-on multi-pole terminal blocks - 450 V - Grey RAL 7035

Code	Connecting capacity	Pack Carton
GW 44 606	3 holes x 4 mm²	10/100
GW 44 607	4 holes x 4 mm²	10/100
GW 44 608	5 holes x 4 mm²	10/100

NOTES: press-on fixing on 44 CE range boxes. (see "Selection Guide" synoptic table).

Screw-on fixing



GW 44 610

Screw-on feedthrough multi-pole terminal blocks - 750V- T 85°C - Grey RAL 7035

Code	Connecting capacity	Pack Carton
GW 44 609	3 holes x 6 mm²	10/100
GW 44 610	5 holes x 6 mm²	10/100
GW 44 610 C	5 holes x 6 mm²	10/100
GW 44 611	3 holes x 16 mm²	10/100
GW 44 612	5 holes x 16 mm²	10/100
GW 44 613	3 holes x 35 mm²	1/10
GW 44 614	5 holes x 35 mm²	1/10

APPLICATIONS: These allow the creation of cut-outs from the main cables which, unsheathed in the part concerned, are not interrupted.
ACCESSORIES SUPPLIED: fixing screws.
NOTE: Multi-pole terminal block GW44610C is certified CSA (according to UL1059). For use also with junction boxes GW44276C and GW44277C.

44 ME - UNIPOLAR EQUIPOTENTIAL TERMINAL BLOCKS



Terminal blocks for side-by-side assembly



GW 44 706

Terminal blocks with indirect plate tightening - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 704	4 ways x 6 mm²	10/100
GW 44 706	6 ways x 6 mm²	10/100
GW 44 708	8 ways x 6 mm²	10/100

APPLICATIONS: embedded fixing on the GW44720 support, for coupling with the DIN rail.
NOTES: for the connection capacity, refer to the technical catalogue

Accessories for terminal blocks for side-by-side assembly



GW 44 720

Support for fixing side-by-side terminal blocks on DIN rail

Code	For equipotential terminal blocks	Terminal block fixing	Fixing on DIN rail	Pack Carton
GW 44 720	GW44704, GW44706, GW44708	Clip	Lock-joint	1/50

NOTES: ideal for applications on boxes of the 48 PT DIN range.
CHARACTERISTICS: supports a combination of terminal blocks with maximum 12-way capacity.
Possible combinations: 3xGW44704; 2xGW44706; 1xGW44704 + 1xGW44706; 1xGW44704 + 1xGW44708. Modular overall dimensions (width): 4.5 modules EN 50022.

Modular terminal blocks




GW 44 671

Single-pole equipotential terminal blocks with blanket grip - 450V - T 85°C - Transparent

Code	Connecting capacity	Pack Carton
GW 44 671	3 ways x 6 mm²	10/100
GW 44 672	5 ways x 6 mm²	10/100
GW 44 673	4 ways x 16 mm²	10/50
GW 44 674	2 ways x 16mm² + 3 ways x 6 mm²	10/50
GW 44 675	2 ways x 16mm² + 9 ways x 6 mm²	5/25
GW 44 676	2 ways x 35 mm² + 4 ways x 16 mm²	1/10

APPLICATIONS: especially suitable for creating equipotential nodes.
ACCESSORIES SUPPLIED: self-adhesive label for identification of electrical lines.
NOTES: GW44676 equipped with feedthrough terminals. These allow the creation of cut-outs from the main cables which, unsheathed in the part concerned, are not interrupted.

Accessories for modular terminal blocks



GW 44 681

Support for fixing equipotential terminal blocks on rail DIN

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 681	From GW44671 to GW44676	Clip	100

NOTE: not compatible with PT DIN and PT DIN GREEN WALL.



GW 44 682

Adaptor for fixing equipotential terminal blocks

Code	For equipotential terminal blocks	Terminal block fixing	Pack Carton
GW 44 682	From GW44671 to GW44676	Lock-joint	200

APPLICATIONS: for fixing the equipotential terminal blocks on the plates or directly on the base inside the junction boxes and watertight boxes.
ACCESSORIES SUPPLIED: screws for fixing the adapter.



GW 44 683

Rail for fixing equipotential terminal blocks in PTC flush-mounting modular boxes

Code	Installable terminal blocks	Pack Carton
GW 44 683	4xGW44671; 3xGW44672; 2xGW44673; 2xGW44674; 1xGW44675	1/50

CHARACTERISTICS: width: 1 compartment. For applications with PTC boxes with 2 and 3 compartments, the rail is fixed on the dividers GW48024.

44 MP - MODULAR DISTRIBUTING FRAME TERMINAL BLOCKS

GWT 850°C

TP 125°C

Two-pole



GW 44 691


Two-pole distribution terminal blocks with transparent protection cover - fixing on plate or DIN rail EN 50022 - 750V - T 85°C

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 691	68x47x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/40
Rated current (A): 125						
GW 44 693	134x47x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/12

CHARACTERISTICS: the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".

NOTES: products bearing the IMQ quality mark.

Four-pole




GW 44 696

Four-pole distribution terminal blocks with transparent protection cover - fixing on plate or DIN rail EN 50022 - 750V - T 85°C

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 696	72x98x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/20
Rated current (A): 125						
GW 44 698	138x98x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/10
Rated current (A): 160						
GW 44 699	186x136x70	11	1x(16-50) mm²	[2x(10-35) + 2x(6-25) + 8x(4-16)] mm²	10 kA	1/12

CHARACTERISTICS: terminal tightening torque: input cables 4 Nm, output cables 1.5 Nm.
the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".

NOTES: products bearing the IMQ quality mark.



GW FIT



Scan the QR Code and find out all the technical informations.

HIGH PERFORMANCE CABLE GLANDS



The GEWISS cable gland range includes plastic and metal versions with IP54, IP66 and IP68 protection ratings, developed to adapt to all installation requirements, including industrial and machine applications. Metal glands for ATEX environments complete the offer.

AN EXTENSIVE CONDUIT AND CABLE FIXING SYSTEM



Available in plastic and metal and designed to meet every need: the range consists of snap-fit or collar conduit fixings accessories, also in multidiameter version and with a built-in wall plug version for faster installation.

CABLE TIES AND TERMINAL BLOCKS FOR EFFECTIVE WIRING



The cable-tie range includes 6 different product lines, from versions for wiring in PA66 to external “Low Temperature Resistance” versions in PA12. The range of terminal blocks covers various types: single-screw, multi-pole, modular distribution and single-pole equipotential terminal blocks for DIN rails.

Energy





Automatic reclosing devices

In the event that the automatic circuit breaker trips, the ReStart devices restore the power supply after checking the system status, thereby ensuring continuity of service in complete safety. Available both for residual current circuit breakers and miniature circuit breakers, the Restart range also includes Autotest and PRO versions.



Circuit breakers for circuit protection

The 90 MCB range meets any requirement for protection against overcurrent and short-circuit, for all domestic, commercial and industrial applications. The range consists of MTC (compact miniature circuit breakers), MT (traditional miniature circuit breakers) and MTHP (high performance miniature circuit breakers).



Circuit breakers for residual current protection

The RCD 90 range is ideal for ground fault protection. The range consists of MDC compact miniature circuit breakers, BD and BDHP add-on residual current devices for MT and MTHP circuit breakers and IDP residual current circuit breaker.



Modular accessories

The 90 AM range, in addition to auxiliaries common for the all circuit breakers, comprises many modular accessories for the protection, command, programming, measurement and signalling in electrical systems.



Moulded case circuit breakers

The GEWISS range of moulded-case protection circuit breakers and control switch disconnectors ensures maximum reliability and safety in every environment. The range includes a wide range of accessories, releases and connection terminals.



Electrical distribution boards

The GEWISS metal distribution boards are the best solution for the installation of all modular and moulded-case products. With a design that seamlessly integrates into any environment, these floor and surface-mounting boards provide increased robustness with reduced overall dimensions.

Automatic reclosing devices







90 ReStart

Automatic reclosing devices

p. 422

ReStart Autotest PRO - Automatic reclosing devices with preventive check of the insulation and automatic test of the residual current circuit breaker

	COUPLED VERSIONS WITH RCCB							
	ATR2 - 2 poles			ATR4 - 4 poles				
	5 mod.		7 mod.	7 mod.				
								
	A[IR] type		B type	A[IR] type		B type		A[S] type
In (A)	IΔn = 30 mA	IΔn = 300 mA	IΔn = 30 mA	IΔn = 30 mA	IΔn = 300 mA	IΔn = 30 mA	IΔn = 300 mA	IΔn = 300 mA
25	GW 90 901 N	GW 90 917	GW 90 911 B	GW 90 921	GW 90 927	GW 90 921 B	GW 90 927 B	-
40	GW 90 902 N	GW 90 918	GW 90 912 B	GW 90 922	GW 90 928	GW 90 922 B	GW 90 928 B	-
63	GW 90 913	GW 90 919	GW 90 913 B	GW 90 923	GW 90 929	GW 90 923 B	GW 90 929 B	GW 90 930

NOTE: ARD must be supplied with 230 V ac phase-neutral for working.

RESTART SELECTION

ReStart Configurator

Selection of ReStart automatic reclosing devices

RESTART is an online software that can be used by any device connected to Internet (smartphones, tablets or PCs), with which it is possible to find ReStart automatic reclosing devices.

Scan the QR code to find out more about the ReStart range and choose the device most suited to your needs.

ReStart RD - Automatic reclosing devices with preventive check of the insulation

	COUPLED VERSIONS WITH RCCB IDP	
	RD2 - 2 poles	RD2 - 2 poles, PRO version
	3 mod.	
		
	IΔn = 30 mA	
In (A)	A type	
25	GW D4 817 R	GW D4 817 P
40	GW D4 827 R	GW D4 827 P

		VERSIONS TO BE COUPLED WITH RCCB IDP							
		RD2 - 2 poles	RD2 - 2 poles, PRO version			RD4 - 4 poles, PRO version			
									
		GW D0 971	GW D0 976	GW D0 978		GW 90 967	GW 90 969		
		1 mod.	1 mod.			3 mod.			
		+	+	+		+	+		
		RCCB IDP 2P				RCCB IDP 4P			
		2 mod.				4 mod.			
									
In (A)	Type	IΔn = 30 mA	IΔn = 100 mA	IΔn = 300 mA	IΔn = 500 mA	IΔn = 30 mA	IΔn = 100 mA	IΔn = 300 mA	IΔn = 500 mA
25	AC	GW D4 002 GW D4 617*	GW D4 003	GW D4 004	-	GW D4 102	GW D4 103	GW D4 104	-
	A	GW D4 012 GW D4 817*	GW D4 013	GW D4 014	-	GW D4 112	GW D4 113	GW D4 114	-
	A[IR]	GW D4 202	-	GW D4 203	-	GW D4 217	-	GW D4 218	-
	F	GW D4 261	-	-	-	GW D4 281	-	-	-
	B	-	-	-	-	GW D4 502 **	-	GW D4 504 **	-
		-	-	-	-	GW D4 527	-	GW D4 529	-
40	AC	GW D4 022 GW D4 627*	GW D4 023	GW D4 024	GW D4 025	GW D4 122	GW D4 123	GW D4 124	GW D4 125
	A	GW D4 032 GW D4 827*	GW D4 033	GW D4 034	GW D4 035	GW D4 132	GW D4 133	GW D4 134	GW D4 135
	A[IR]	GW D4 205	-	GW D4 206	-	GW D4 220	-	GW D4 221	-
	A[S]	-	-	GW D4 234	GW D4 235	-	-	GW D4 249	GW D4 250
	F	GW D4 265	-	-	-	GW D4 285	-	-	-
	B	-	-	-	-	GW D4 507 **	-	GW D4 509 **	-
		-	-	-	-	GW D4 532	-	GW D4 534	-
63	AC	GW D4 042	GW D4 043	GW D4 044	GW D4 045	GW D4 142	GW D4 143	GW D4 144	GW D4 145
	A	GW D4 052	GW D4 053	GW D4 054	GW D4 055	GW D4 152	GW D4 153	GW D4 154	GW D4 155
	A[IR]	GW D4 208	-	GW D4 209	-	GW D4 223	-	GW D4 224	-
	A[S]	-	-	GW D4 237	GW D4 238	-	-	GW D4 252	GW D4 253
	F	GW D4 269	-	-	-	GW D4 289	-	-	-
	B	-	-	-	-	GW D4 512 **	-	GW D4 514 **	-
		-	-	-	-	GW D4 537	-	GW D4 539	-
80	AC	GW D4 062	-	-	-	-	-	-	-
	A	GW D4 072	-	-	-	-	-	-	-

GW90967 and GW90969 ARD's can be coupled with RCCB IDP 2 poles.
NOTE: ARD must be supplied with 230 V ac phase-neutral for working.
*Additional accessories not available, **2P 4 Modules, ***RCCB with Neutral on the left.

ReStart RM - Automatic reclosing devices with preventive check of the insulation and of the short circuit

			COUPLED VERSIONS WITH RCBO MDC	
			RM2 - 2 poles	RM2 - 2 poles, PRO version
			3 mod.	
				
			IΔn = 30 mA	
Icn (A)	Curve	In (A)	A type	
4500	C	16	GW D4 227 R	GW D4 227 P
		25	GW D4 229 R	GW D4 229 P

			VERSIONS TO BE COUPLED WITH RCBO MDC 2 POLES		
			RM2 - 2 poles	RM2 - 2 poles, PRO version	
					
			GW D0 991	GW D0 996	GW D0 998
			1 mod.	1 mod.	
			+	+	+
			RCBO MDC 1P+N, 2P		
			2 mod.		
					
			IΔn = 30 mA		IΔn = 300 mA

			AC type		A type		A[IR] type	F type	AC type		A type		A[S] type
Icn (A)	Curve	In (A)	1P+N	2P	1P+N	2P	2P	2P	1P+N	2P	1P+N	2P	2P
4500	C	6	GW 94 005	GW 94 025	GW 94 205	GW 94 225	-	-	GW 94 015	GW 94 035	GW 94 215	GW 94 235	-
		10	GW 94 006	GW 94 026	GW 94 206	GW 94 226	-	-	GW 94 016	GW 94 036	GW 94 216	GW 94 236	-
		13	GW 94 011	GW 94 031	GW 94 211	GW 94 231	-	-	-	-	-	-	-
		16	GW 94 007	GW 94 027	GW 94 207	GW 94 227	-	-	GW 94 017	GW 94 037	GW 94 217	GW 94 237	-
		20	GW 94 008	GW 94 028	GW 94 208	GW 94 228	-	-	GW 94 018	GW 94 038	GW 94 218	GW 94 238	-
		25	GW 94 009	GW 94 029	GW 94 209	GW 94 229	-	-	GW 94 019	GW 94 039	GW 94 219	GW 94 239	-
		32	GW 94 010	GW 94 030	GW 94 210	GW 94 230	-	-	GW 94 020	GW 94 040	GW 94 220	GW 94 240	-
6000	C	6	GW 94 105	GW 94 125	GW 94 305	GW 94 325	GW 95 805	GW 95 935	GW 94 115	GW 94 135	GW 94 315	GW 94 335	-
		10	GW 94 106	GW 94 126	GW 94 306	GW 94 326	GW 95 806	GW 95 936	GW 94 116	GW 94 136	GW 94 316	GW 94 336	-
		13	GW 94 111	GW 94 131	GW 94 311	GW 94 331	GW 95 811	GW 95 941	-	-	-	-	-
		16	GW 94 107	GW 94 127	GW 94 307	GW 94 327	GW 95 807	GW 95 937	GW 94 117	GW 94 137	GW 94 317	GW 94 337	GW 95 847
		20	GW 94 108	GW 94 128	GW 94 308	GW 94 328	GW 95 808	GW 95 938	GW 94 118	GW 94 138	GW 94 318	GW 94 338	GW 95 848
		25	GW 94 109	GW 94 129	GW 94 309	GW 94 329	GW 95 809	GW 95 939	GW 94 119	GW 94 139	GW 94 319	GW 94 339	GW 95 849
		32	GW 94 110	GW 94 130	GW 94 310	GW 94 330	GW 95 810	GW 95 940	GW 94 120	GW 94 140	GW 94 320	GW 94 340	GW 95 850
	B	6	-	-	GW 95 105	GW 95 125	-	GW 95 975	-	-	GW 95 115	GW 95 135	-
		10	-	-	GW 95 106	GW 95 126	-	GW 95 976	-	-	GW 95 116	GW 95 136	-
		13	-	-	GW 95 111	GW 95 131	-	GW 95 981	-	-	-	-	-
		16	-	-	GW 95 107	GW 95 127	-	GW 95 977	-	-	GW 95 117	GW 95 137	-
		20	-	-	GW 95 108	GW 95 128	-	GW 95 978	-	-	GW 95 118	GW 95 138	-
		25	-	-	GW 95 109	GW 95 129	-	GW 95 979	-	-	GW 95 119	GW 95 139	-
		32	-	-	GW 95 110	GW 95 130	-	GW 95 980	-	-	GW 95 120	GW 95 140	-

NOTE: ARD must be supplied with 230 V ac phase-neutral for working.
The automatic reclosing devices ReStart RM can also be coupled with RCBO 2P MDC 100 (Icn=10000A).

			VERSIONS TO BE COUPLED WITH RCBO MDC 4 POLES					
			RM4 - 4 poles, PRO version					
								
			GW 90 986			GW 90 988		
			3 mod.			3 mod.		
			+			+		
			RCBO MDC 4P					
			4 mod.			4 mod.		
								
			IΔn = 30 mA			IΔn = 300 mA		
Icn (A)	**Curve**	**In (A)**	**AC type**	**A type**	**A[IR] type**	**AC type**	**A type**	**A[S] type**
4500	**C**	**6**	GW 94 065	GW 94 265	-	GW 94 075	GW 94 275	-
		10	GW 94 066	GW 94 266	-	GW 94 076	GW 94 276	-
		13	GW 94 071	GW 94 271	-	-	-	-
		16	GW 94 067	GW 94 267	-	GW 94 077	GW 94 277	-
		20	GW 94 068	GW 94 268	-	GW 94 078	GW 94 278	-
		25	GW 94 069	GW 94 269	-	GW 94 079	GW 94 279	-
		32	GW 94 070	GW 94 270	-	GW 94 080	GW 94 280	-
6000	**C**	**6**	GW 94 165	GW 94 365	GW 95 815	GW 94 175	GW 94 375	-
		10	GW 94 166	GW 94 366	GW 95 816	GW 94 176	GW 94 376	-
		13	GW 94 171	GW 94 371	GW 95 821	-	-	-
		16	GW 94 167	GW 94 367	GW 95 817	GW 94 177	GW 94 377	GW 95 857
		20	GW 94 168	GW 94 368	GW 95 818	GW 94 178	GW 94 378	GW 95 858
		25	GW 94 169	GW 94 369	GW 95 819	GW 94 179	GW 94 379	GW 95 859
		32	GW 94 170	GW 94 370	GW 95 820	GW 94 180	GW 94 380	GW 95 860
	B	**6**	-	GW 95 165	-	-	GW 95 175	-
		10	-	GW 95 166	-	-	GW 95 176	-
		13	-	GW 95 171	-	-	-	-
		16	-	GW 95 167	-	-	GW 95 177	-
		20	-	GW 95 168	-	-	GW 95 178	-
		25	-	GW 95 169	-	-	GW 95 179	-
		32	-	GW 95 170	-	-	GW 95 180	-

NOTE: they are also compatible with RCBO 1P+N and 2 poles (MDC 1P+N and 2P).
ARD must be supplied with 230 V ac phase-neutral for working.

ReStart RM TOP - Adjustable reclosing device with/without preventive check of the insulation and/or short-circuits

		VERSION TO BE COUPLED WITH MCB AND ADD-ON RCD 4 POLES		
				
		GW 90 893		
		4 mod.		
		+		
		MCB MT 4 POLES		
		4 mod.		
				
Curve	**In (A)**	**Icn = 6000 A**	**Icn = 10000 A**	**Icn = 25000 A**
C	1	GW 92 081	-	-
	2	GW 92 082	-	-
	3	GW 92 083	-	-
	4	GW 92 084	-	-
	6	GW 92 085	GW 92 685	GW 92 885
	10	GW 92 086	GW 92 686	GW 92 886
	13	GW 92 094	GW 92 694	-
	16	GW 92 087	GW 92 687	GW 92 887
	20	GW 92 088	GW 92 688	GW 92 888
	25	GW 92 089	GW 92 689	GW 92 889
	32	GW 92 090	GW 92 690	GW 92 890
	40	GW 92 091	GW 92 691	GW 92 891
	50	GW 92 092	GW 92 692	GW 92 892
	63	GW 92 093	GW 92 693	GW 92 893
B	6	GW 92 285	GW 92 585	-
	10	GW 92 286	GW 92 586	-
	13	GW 92 294	GW 92 587	-
	16	GW 92 287	GW 92 588	-
	20	GW 92 288	GW 92 589	-
	25	GW 92 289	GW 92 590	-
	32	GW 92 290	GW 92 591	-
	40	GW 92 291	GW 92 592	-
	50	GW 92 292	GW 92 593	-
	63	GW 92 293	GW 92 594	-
D	1	-	GW 92 781	-
	2	-	GW 92 782	-
	3	-	GW 92 783	-
	4	-	GW 92 784	-
	6	GW 92 485	GW 92 785	-
	10	GW 92 486	GW 92 786	-
	13	GW 92 494	GW 92 794	-
	16	GW 92 487	GW 92 787	-
	20	GW 92 488	GW 92 788	-
	25	GW 92 489	GW 92 789	-
	32	GW 92 490	GW 92 790	-
	40	GW 92 491	GW 92 791	-

+

		ADD-ON RESIDUAL CURRENT DEVICES BD 4 POLES			
		3.5 mod.			
					
In (A)	**IΔn (mA)**	**AC type**	**A type**	**A[IR] type**	**A[S] type**
≤25	30	GW 94 422	GW 94 522	-	-
	300	GW 94 423	GW 94 523	-	-
	500	GW 94 424	GW 94 524	-	-
≤63	30	GW 94 432	GW 94 532	GW 94 586	-
	300	GW 94 433	GW 94 533	-	GW 94 583
	500	GW 94 434	GW 94 534	-	-
	1000	-	-	-	GW 94 585

NOTE: they are also compatible with MCB MTC (except for 1P+N), RCBO MDC, MCB MT 1P+N, 2P and 3P and with add-on RCD BD 2P and 3P. ARD must be supplied with 230 V ac phase-neutral for working.

Technical data - ReStart Autotest PRO

TYPE		ReStart with Autotest PRO 2P	ReStart with Autotest PRO 4P
			
Electrical characteristics			
Standards:		**IEC EN 63024, IEC EN 61008-1**	
Distribution system:		TT - TN-S	
Rated operational voltage (Ue):	**(V)**	230 ac [1]	400 ac
Minimum operating voltage (min Ue):	**(V)**	85% Ue	
Maximum operating voltage (max Ue):	**(V)**	110% Ue	
Rated insulation voltage (Ui):	**(V)**	500	
Dielectric strength test voltage between pole and earth:	**(V)**	2500 ac for 1 minute	
Rated impulse withstand voltage (Uimp):	**(kV)**	4	
Overvoltage category:		III	
Rated frequency:	**(Hz)**	50	
Residual making and breaking capacity (IΔm):	**(A)**	630	
Rated conditional residual short-circuit current with fuse (IΔc):	**(A)**	Type A[IR] and A[S] 10000 (gL 63A) for In=25-40A 10000 (gL 80A) for In=63A Type B 10000 (gL 63A) for In=25-40-63A	
Number of poles:		2	4
Type of associated residual current circuit breaker:		A[IR], A[S], B	
Rated current (In):	**(A)**	25 - 40 - 63	
Rated residual operating current (IΔn):	**(mA)**	30 - 300	
Rated non-operating resistance between live parts and earth (Rdo):	**(kΩ)**	8 (30mA) - 2.5 (300mA)	
Rated operating resistance between live parts and earth (Rd):	**(kΩ)**	16 (30mA) - 5 (300mA)	
Power loss at In:	**(W)**	2.2 (25A) - 5.4 (40A) - 6.2 (63A)	3.5 (25A) - 6 (40A) - 12 (63A)
Off-load absorbed power:	**(VA)**	4 (cosϕ=0.2)	
Power absorbed during automatic reclosing:	**(VA)**	41 (cosϕ=0.5)	
Power supply:		from above	
Mechanical characteristics			
Width in DIN modules:		Type A[IR]: 5 - Type B: 7	7
Reclosing time:	**(s)**	10	
Autotest cycle time:	**(s)**	7	
Maximum operational frequency:	**(oper./h)**	30	
Max mechanical endurance (total no. operations):		4000	
Maximum no. of consecutive automatic reclosure operations [2]:		3	
Counter reset time no. of consecutive automatic reclosure operations:	**(s)**	60	
Section of circuit breaker terminals:	**(mm²)**	flexible cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10 rigid cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	
Rated tightening torque:	**(Nm)**	2	
Mounting position:		any	
Degree of protection:		IP20 (terminals) - IP40 (front)	
Pollution degree:		2	
Operating temperature:	**(°C)**	-25 +60 [3]	
Stocking temperature:	**(°C)**	-40 +70	
Tropicalization:		55°C - RH 95%	
Auxiliary contact characteristics			
Type of contact:		Photomos (potential free contact)	
Operating voltage:	**(V)**	5÷230 ac/dc	
Operating current:	**(mA)**	0.6 (min) - 100 cosϕ=1 (max)	
Operating frequency:	**(Hz)**	50	
Category of use:		AC12	
Operating mode:		NO / NC / NC + impulse [4]	
Terminal section:	**(mm²)**	≤ 2.5	
Rated tightening torque:	**(Nm)**	0.4	
Autotest function			
Regular and automatic RCCB test:		•	
Light signalling for autotest cycle in progress:		•	
Light signalling for any device anomaly:		•	
ReStart function			
Automatic reclosure for untimely tripping:		•	
Earth leakage check:		•	
Continuous system check:		•	
Interruption of reclosure operation in the event of a fault:		•	
Signalling of reclosure operation in progress:		•	
Light signalling of failure:		•	
Activation / exclusion of ReStart function:		•	
Auxiliary contact for remote operating status access:		•	
Compatible with ModBus interface module:		•	
Internal electrical protection:		PTC	

[1] 230V phase-neutral power supply [2] In the absence of failure in the system [3] Average daily temperature ≤ +35°C
[4] By setting NC+pulse mode, the auxiliary contact switches for 100ms at the end of each Autotest cycle performed successfully.

Technical data - ReStart RD

TYPE		ReStart RD 2P	ReStart RD PRO 2P	ReStart RD PRO 4P
				
Electrical characteristics				
Standards:		**IEC EN 63024**		
Distribution system:		TT - TN-S		
Rated operational voltage (Ue):	**(V)**	230 ac [1]		
Minimum operating voltage (min Ue):	**(V)**	85% Ue		
Maximum operating voltage (max Ue):	**(V)**	110% Ue		
Rated insulation voltage (Ui):	**(V)**	500		
Dielectric strength test voltage between pole and earth:	**(V)**	2500 ac for 1 minute		
Rated impulse withstand voltage (Uimp):	**(kV)**	4		
Overvoltage category:		III		
Rated frequency:	**(Hz)**	50/60		50
Residual making and breaking capacity (IΔm):	**(A)**	IΔm of the associated circuit breaker		
Rated conditional residual short-circuit current with fuse (IΔc):	**(A)**	IΔc of the associated circuit breaker		
Number of poles:		2P		4P
Type of IDP RCCB:		AC - A - A[IR] - A[S] -F -B		
Rated current (In):	**(A)**	25 - 40 - 63 - 80		
Rated residual operating current (IΔn):	**(mA)**	30 - 100 - 300 - 500		
Rated non-operating resistance between live parts and earth (Rdo):	**(kΩ)**	8 (30mA) - 2.5 (100/300/500mA)		
Rated operating resistance between live parts and earth (Rd):	**(kΩ)**	16 (30mA) - 5 (100/300/500mA)		
Power loss at In:	**(W)**	Power loss of the associated circuit breaker		
Off-load absorbed power:	**(VA)**	3 (cosϕ=0.4)		4 (cosϕ=0.2)
Power absorbed during automatic reclosing:	**(VA)**	18 (cosϕ=0.5)		45 (cosϕ=0.5)
Mechanical characteristics				
Width in DIN modules:		1		3
Reclosing time:	**(s)**	10		
Maximum operational frequency:	**(man/h)**	30		
Max mechanical endurance (total no. operations):		4000		
Maximum no. of consecutive automatic reclosure operations [2]:		3		
Counter reset time no. of consecutive automatic reclosure operations:	**(s)**	60		
Section of circuit breaker terminals:	**(mm²)**	flexible cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10 rigid cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		
Circuit breaker rated tightening torque:	**(Nm)**	3 (IDP) - 2 (IDP NA)		
Mounting position:		any		
Circuit breaker degree of protection:		IP20 (terminals) - IP40 (front)		
Pollution degree:		2		
Operating temperature:	**(°C)**	-5 +40	-5 +60 [3]	-25 +60 [3]
Stocking temperature:	**(°C)**	-40 +70		
Tropicalization:		55°C - UR 95%		
Auxiliary contact characteristics				
Can be fitted with auxiliary:		no	yes (with GWD0951)	already integrated in the ReStart
Type of contact:		-	Photomos (potential free contact)	
Operating voltage:	**(V)**	-	5÷230 ac/dc	
Operating current:	**(mA)**	-	0,6 (min) - 100 cosϕ=1 (max)	
Operating frequency:	**(Hz)**	-	50	
Category of use:		-	AC12	
Operating mode:		-	NO\NC\NO as signal of handle position	
Terminal section:	**(mm²)**	-	≤ 2,5	
Rated tightening torque:	**(Nm)**	-	0.4	
ReStart function				
Automatic reclosure for untimely tripping:		•	•	•
Earth leakage check:		•	•	•
Continuous system check:			•	•
Interruption of reclosure operation in the event of a fault:		•	•	•
Signalling of reclosure operation in progress:		•	•	•
Light signalling of failure:		•	•	•
Activation / exclusion of ReStart function:		•	•	•
Auxiliary contact for remote operating status access:			•	•
Compatible with WiFi/ModBus interface module:			•	•
Internal electrical protection:		PTC	PTC	PTC

[1] Power supply 230V phase-neutral [2] In the absence of a system fault [3] Average daily temperature ≤ +35°C

Technical data - ReStart RM

TYPE		ReStart RM 2P	ReStart RM PRO 2P	ReStart RM PRO 4P	RM TOP	CM
						
Electrical characteristics						
Standards:		IEC EN 63024			-	-
Distribution system:		TT - TN-S			TT - TN - IT [1]	TT - TN - IT
Rated operational voltage (Ue):	**(V)**	230 ac [2]				
Minimum operating voltage (min Ue):	**(V)**	85% Ue				
Maximum operating voltage (max Ue):	**(V)**	110% Ue				
Rated insulation voltage (Ui):	**(V)**	500				
Dielectric strength test voltage between pole and earth:	**(V)**	2500 ac for 1 minute				
Rated impulse withstand voltage (Uimp):	**(kV)**	4				
Overvoltage category:		III				
Rated frequency:	**(Hz)**	50/60		50		
Residual making and breaking capacity (IΔm):	**(A)**	IΔm of the associated circuit breaker				
Number of poles:		2P		4P		
Type of MDC RCBO:		AC - A - A[IR] - A[S] -F				
Type of MT+BD RCBO:		-			AC - A - A[IR] - A[S]	
Rated current (In):	**(A)**	from 6 to 32			from 1 to 63	
Rated residual operating current (IΔn):	**(mA)**	30 - 300			30 - 300 - 500 - 1000	
Rated non-operating resistance between live parts and earth (Rdo):	**(kΩ)**	8 (30mA) - 2.5 (300mA)			8 (30mA) - 2.5 (300/500/1000mA)	-
Rated operating resistance between live parts and earth (Rd):	**(kΩ)**	16 (30mA) - 5 (300mA)			16 (30mA) - 5 (300/500/1000mA)	-
Rated non-operating resistance between live parts (Rcco):	**(Ω)**	0.4		0.3		-
Rated operating resistance between live parts (Rcc):	**(Ω)**	2.3		1.8		-
Power loss at In:	**(W)**	Power loss of the associated circuit				
Off-load absorbed power:	**(VA)**	3 (cosϕ=0.4)		16 (cosϕ=0.2)	15 (cosϕ=0.1)	0 (cosϕ=0.2)
Power absorbed during automatic reclosing:	**(VA)**	18 (cosϕ=0.5)		34 (cosϕ=0.7)	30 (cosϕ=0.6)	30 (cosϕ=0.6)
Reclosing control:		automatic			automatic / remote [3]	remote [3]
Mechanical characteristics						
Width in DIN modules:		1		3	4	2
Reclosing time:	**(s)**	10			3 (without system test) 10 (with system test)	3
Remote control opening time:	**(s)**	-			2	
Maximum operational frequency:	**(man/h)**	30				
Max mechanical endurance (total no. operations):		4000			10000	
Maximum no. of consecutive automatic reclosure operations [4]:		3				-
Counter reset time No. of consecutive automatic reclosure operations:	**(s)**	60				-
Section of circuit breaker terminals:	**(mm²)**	flexible cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10 rigid cable: ≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10				
Circuit breaker rated tightening torque:	**(Nm)**	2				
Mounting position:		any				
Circuit breaker degree of protection:		IP20 (terminals) - IP40 (front)				
Pollution degree:		2				
Operating temperature:	**(°C)**	-5 +40	-5 +60 [5]	-25 +60 [5]		
Stocking temperature:	**(°C)**	-40 +70				
Tropicalization:		55°C - UR 95%				
Auxiliary contact characteristics						
Can be fitted with auxiliary:		no	yes (with GWD0951)	already integrated in the ReStart	already integrated in the ReStart	already integrated in the ReStart	already integrated in the ReStart
Type of contact:		-	Photomos (potential free contact)		Changeover	Photomos (potential free contact)	Changeover
Operating voltage:	**(V)**	-	5÷230 ac/dc		230 ac / 30 dc	5÷230 ac/dc	230 ac / 30 dc
Operating current:	**(mA)**	-	0.6 (min) - 100 cosϕ=1 (max)		1.5 ac / 0.8 dc	0.6 (min) - 100 cosϕ=1 (max)	1.5 ac / 0.8 dc
Operating frequency:	**(Hz)**	-	50				
Category of use:		-	AC12				
Operating mode:		-	NO\NC\NO as signal of handle position		CO	NO/NC/ INTERMITTENT	CO
Terminal section:	**(mm²)**	-	≤ 2.5				
Rated tightening torque:	**(Nm)**	-	0.4				
ReStart Function							
Automatic reclosure for untimely tripping:		●	●	●	●		
Earth leakage check:		●	●	●	●		
Short-circuit check:		●	●	●	●		
Adjustable insulation threshold:					●		
Continuous system check:			●	●	●		
Adjustable reset standby time [6]:					●		
Adjustable reclosing mode:					●		
Interruption of reclosure operation in the event of a fault:		●	●	●	●		
Signalling of reclosure operation in progress:		●	●	●	●		
Light signalling of failure:		●	●	●	●		
Activation / exclusion of ReStart function:		●	●	●	●		●
Auxiliary contact for remote operating status access:			●	●	●		●
Compatible with WiFi/ModBus interface module:			●	●			
Internal electrical protection:		PTC	PTC	PTC	PTC		PTC

[1] For IT system reclosing without fault check
[2] Power supply 230V phase-neutral
[3] Impulse duration ≥ 200ms
[4] In the absence of a system fault
[5] Average daily temperature ≤ +35°C
[6] Automatic reclosure delay time: 0-1h

90 ReStart

Automatic reclosing devices

In the event the switch trips, the ReStart devices, after checking the system status, restore the power supply thereby ensuring maximum continuity of service in complete safety.Available for both residual current circuit breakers and residual current circuit breakers with overcurrent protection, the range is characterized by the Autotest functions, with periodic and automatic control of the residual current protection without interrupting the power supply and PRO with extended control of the system.



RESTART AUTOTEST PRO

ReStart Autotest PRO 2 poles - Versions coupled with RCCB's



GW 90 901 N

Automatic reclosing devices with preventive check of the insulation and automatic test of the residual current circuit breaker

Code	Rated current	Idn	Type of RCCB	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 901 N	25 A	30 mA	A[IR]	230 V	5	1/4
GW 90 911 B	25 A	30 mA	B	230 V	7	1/2
GW 90 902 N	40 A	30 mA	A[IR]	230 V	5	1/4
GW 90 912 B	40 A	30 mA	B	230 V	7	1/2
GW 90 913	63 A	30 mA	A[IR]	230 V	5	1/4
GW 90 913 B	63 A	30 mA	B	230 V	7	1/2
GW 90 917	25 A	300 mA	A[IR]	230 V	5	1/4
GW 90 918	40 A	300 mA	A[IR]	230 V	5	1/4
GW 90 919	63 A	300 mA	A[IR]	230 V	5	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so. In the meantime the integrated configurable auxiliary contact will change state to indicate that the automatic reset did not take place.
Compatible with:
-GW90992 ModBus RS485 interface module.
NOTE: the Autotest function automatically and periodically (every 28 days) tests the RCCB, without interrupting the electric power supply, thus maintaining the performance of the residual current protection over time.
230 V ac power supply, phase-neutral.
RCCB's type B and A[IR] Impulse Resistant presents greater resistance to untimely tripping in comparison to standard residual current circuit breakers. Immunity level 8/20µs: 3000A for IR type, 250A for standard type.

ReStart Autotest PRO 4 poles - Versions coupled with RCCB's



GW 90 921

Automatic reclosing devices with preventive check of the insulation and automatic test of the residual current circuit breaker

Code	Rated current	Idn	Type of RCCB	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 921	25 A	30 mA	A[IR]	400 V	7	1/2
GW 90 921 B	25 A	30 mA	B	400 V	7	1/2
GW 90 922	40 A	30 mA	A[IR]	400 V	7	1/2
GW 90 922 B	40 A	30 mA	B	400 V	7	1/2
GW 90 923	63 A	30 mA	A[IR]	400 V	7	1/2
GW 90 923 B	63 A	30 mA	B	400 V	7	1/2
GW 90 927	25 A	300 mA	A[IR]	400 V	7	1/2
GW 90 927 B	25 A	300 mA	B	400 V	7	1/2
GW 90 928	40 A	300 mA	A[IR]	400 V	7	1/2
GW 90 928 B	40 A	300 mA	B	400 V	7	1/2
GW 90 929	63 A	300 mA	A[IR]	400 V	7	1/2
GW 90 929 B	63 A	300 mA	B	400 V	7	1/2
GW 90 930	63 A	300 mA	A[S]	400 V	7	1/2

CHARACTERISTICS: when the' RCCB switch trips, ReStart performs' the isolation check before the automatic reset. In the event of a ground fault, ReStart does not reset'the switch but continues to check the'system every 2 minutes until, once the safety conditions are restored, it resets the'switch. The auxiliary contact that can be configured and integrated in the meantime switches on to signal the failure of automatic resetting.
Coupled with:
-ModBus RS485 GW90992 interface
module.
NOTE: the SELF-TEST function automatically and periodically (every 28 days) tests the RCCB without cutting off power to the'system to maintain the' efficiency of the RCCB protection over time.
Reinforced Immunity Type A[S], B and A[IR] circuit breakers are equipped with greater resistance to unexpected trips than standard RCCBs. Immunity level 8/20µs: 3000A for IR versions and S, 250A for standard versions.

RESTART RD

ReStart RD 2 poles - versions coupled with RCCB'S IDP



GW D4 817 R

Automatic reclosing devices with preventive check of the insulation

Code	Rated current	Idn	Type of RCCB	Rated voltage	No. of modules EN 50022	Pack Carton
GW D4 817 R	25 A	30 mA	A	230 V	3	1/4
GW D4 827 R	40 A	30 mA	A	230 V	3	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker.
NOTE: the ARD must be supplied at 230 Vac phase-neutral.



GW D4 817 P

Automatic reclosing devices with preventive check of the insulation - PRO version

Code	Rated current	Idn	Type of RCCB	Rated voltage	No. of modules EN 50022	Pack Carton
GW D4 817 P	25 A	30 mA	A	230 V	3	1/4
GW D4 827 P	40 A	30 mA	A	230 V	3	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure.
In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so.
Compatible with:
-GWD0951 auxiliary contact
-GW90992 ModBus RS485 interface module (only if already coupled with GWD0951 auxiliary contact).
NOTE: the ARD must be supplied at 230 Vac phase-neutral.

90 ReStart

ReStart RD 2 poles - versions to be coupled with RCCB'S IDP



GW D0 971

Automatic reclosing devices with preventive check of the insulation

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW D0 971	IDP RCCBs - 2P up to 80 A - 30 mA	230 V	1	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker.
NOTES. cannot be used with 4P RCCBs in 3 modules and type B RCCBs. the ARD must be supplied at 230 Vac phase-neutral.



GW D0 976

Automatic reclosing devices with preventive control of the insulation - PRO version

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW D0 976	IDP RCCBs - 2P up to 80 A - 30 mA	230 V	1	1/4
GW D0 978	IDP RCCBs - 2P up to 63 A - 100/300/500 mA	230 V	1	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so.
Compatible with:
-GWD0951 auxiliary contact
-GW90992 ModBus RS485 interface module (only if already coupled with GWD0951 auxiliary contact)
NOTES: cannot be used with 4P RCCBs in 3 modules and type B RCCBs. The ARD must be supplied at 230 Vac phase-neutral.

ReStart RD 4 poles - versions to be coupled with RCCB'S IDP



GW 90 967

Automatic reclosing devices with preventive control of the insulation - PRO version

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 967	IDP RCCBs - 2P up to 80 A and 4P up to 63 A - 30 mA	230 V	3	1/4
GW 90 969	IDP RCCBs - 2P/4P up to 63 A - 100/300/500 mA	230 V	3	1/4

CHARACTERISTICS: after RCCB has tripped, ReStart checks the insulation prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but willcontinue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so. In the meantime the integrated configurable auxiliary contact will change state to indicate thatthe automatic reset did not take place.
Compatible with:
-GW90992 ModBus RS485 interface module.
NOTES: they cannot be used with 4P RCCBs in 3 modules. 230 V ac power supply, phase-neutral.

RESTART RM

ReStart RM 2 poles - versions coupled with compact RCBO'S MDC



GW D4 229 R

Automatic reclosing devices with preventive check of the insulation and of the short circuit

Code	Rated current	Idn	Type of RCBO	Curve	Rated voltage	No. of modules EN 50022	Pack Carton
Breaking capacity (EN 61009-1): 4500 A							
GW D4 227 R	16 A	30 mA	A	C	230 V	3	1/4
GW D4 229 R	25 A	30 mA	A	C	230 V	3	1/4

CHARACTERISTICS: after RCBO has tripped, ReStart checks the insulation and the short circuit prior to the automatic reclosure.. In the event of a fault (earth leakage or short circuit), ReStart will not reset the circuit breaker.

NOTE: the ARD must be supplied at 230 Vac phase-neutral.



GW D4 229 P

Automatic reclosing devices with preventive check of the insulation and of the short circuit - PRO version

Code	Rated current	Idn	Type of RCBO	Curve	Rated voltage	No. of modules EN 50022	Pack Carton
Breaking capacity (EN 61009-1): 4500 A							
GW D4 227 P	16 A	30 mA	A	C	230 V	3	1/4
GW D4 229 P	25 A	30 mA	A	C	230 V	3	1/4

CHARACTERISTICS: after RCBO has tripped, ReStart checks the insulation and the short circuit prior to the automatic reclosure.

In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so.

Compatible with:

-GWD0951 auxiliary contact

-GW90992 ModBus RS485 interface module (only if already coupled with GWD0951 auxiliary contact).

NOTE: the ARD must be supplied at 230 Vac phase-neutral.

90 ReStart

ReStart RM 2 poles - versions to be coupled with compact RCBO'S MDC



GW D0 991

Automatic reclosing devices with preventive check of the insulation and of the short circuit

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW D0 991	RCBO's MDC - 1P+N/2P - 30 mA	230 V	1	1/4

CHARACTERISTICS: after RCBO has tripped, ReStart checks the insulation and the short circuit prior to the automatic reclosure. In the event of a fault (earth leakage or short circuit), ReStart will not reset the circuit breaker.
NOTE: the ARD must be supplied at 230 Vac phase-neutral.



GW D0 996

Automatic reclosing devices with preventive check of the insulation and of the short circuit - PRO version

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW D0 996	RCBO's MDC - 1P+N/2P - 30 mA	230 V	1	1/4
GW D0 998	RCBO's MDC - 1P+N/2P - 100-300 mA	230 V	1	1/4

CHARACTERISTICS: after RCBO has tripped, ReStart checks the insulation and the short circuit prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so.
Compatible with:
-GWD0951 auxiliary contact
-GW90992 ModBus RS485 interface module (only if already coupled with GWD0951 auxiliary contact).
NOTE: the ARD must be supplied at 230 Vac phase-neutral.

ReStart RM 4 poles - versions to be coupled with compact RCBO'S MDC



GW 90 986

Automatic reclosing devices with preventive check of the insulation and of the short circuit - PRO version

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 986	RCBO's MDC - 1P+N/2P/4P - 30 mA	230 V	3	1/4
GW 90 988	RCBO's MDC - 1P+N/2P/4P - 100 and 300 mA	230 V	3	1/4

CHARACTERISTICS: after RCBO has tripped, ReStart checks the insulation and the short circuit prior to the automatic reclosure. In the event of a fault (earth leakage), ReStart will not reset the circuit breaker but will continue to monitor the circuit every 2 minutes reclosing the circuit breaker when safe to do so. In the meantime the integrated configurable auxiliary contact will change state to indicate that the automatic reset did not take place.
Compatible with:
- GW90992 ModBus RS485 interface module
NOTE: the ARD must be supplied at 230 Vac phase-neutral.

ReStart RM TOP - Version to be coupled with RCBO's MDC/MT+BD or MCB's MTC/MT



GW 90 893

Adjustable automatic reclosing device with/without preventive check of the insulation and/or of the short circuit

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 893	RCBO's MDC/MT+BD and MCB's MTC/MT	230 V	4	1/4

CHARACTERISTICS: The ReStart Rm TOP allows to:
- set the reclosing mode (reclosing with system check, reclosing by attempts, remote reclosing and excluded reclosing)
- adapt the insulation threshold in according to the associated circuit breaker
- regulate the reclosing time dealy.

The device is equipped with 2 integrated auxiliary contacts of position and/or tripped relay.
NOTE: the ARD must be supplied at 230 V ac phase-neutral. The compact miniature circuit breakers MTC 1P+N can not be used with ReStart RM TOP.

ReStart CM - Motor operating device to be coupled with RCBO's MDC/MT+BD or MCB's MTC/MT



GW 90 896

Motor operating device without preventive control of the insulation and of the short circuit

Code	Suitable for	Rated coil voltage	Rated voltage	No. of modules EN 50022	Pack Carton
GW 90 896	RCBO's MDC/MT+BD or MCB's MTC/MT	230 V ac	230 V	2	1/4
GW 90 898	RCBO's MDC/MT+BD or MCB's MTC/MT	12 V dc	230 V	2	1/4

CHARACTERISTICS: the device is equipped with 1 integrated auxiliary position contact or tripped relay.
NOTE: the reclosing device must be supplied at 230 V ac phase-neutral. The compact miniature circuit breakers MTC 1P+N can not be used with ReStart CM.

Electric auxiliary for ReStart devices



GW 96 014

Shunt trip release with simultaneous reclosing

Code	Suitable for	Rated voltage	No. of modules EN 50022	Pack Carton
GW 96 014	ReStart RM TOP/Restart CM	230 V ac	1	1/6

CHARACTERISTICS: when the circuit breaker trips, thanks to GW96014, it can be reclosed remotely by means the ReStart RM TOP or the motor operating ReStart CM, even before the shunt trip release has been reclosed. ReStart RM TOP and ReStart CM activate a remote reclosing of both the circuit breaker lever and the shunt trip release lever simultaneously.
APPLICATIONS: it is used to cause the remote opening of the circuit breaker coupled with the ReStart RM TOP or the motor operating ReStart CM. When using a release associated with ReStart RM TOP, pay attention to the system control and reclose logic set on the ReStart RM TOP.
NOTE: when using a ReStart RM TOP, the shunt trip release must be placed between the ReStart RM TOP device and the circuit breaker.
When using a ReStart CM, the shunt trip release must be placed to the left of the ReStart CM device. A position auxiliary contact or a fault indication switch can also be added to the left of the release GW96014.

RESTART ACCESSORIES

Accessories for ReStart devices



GW D0 951

Auxiliary contact

Code	Suitable for	Voltage operating	Current operating	No. of modules EN 50022	Pack Carton
GW D0 951	ReStart RD PRO 2P (GWD0976 and GWD0978)/ReStart Rm PRO 2P (GWD0996 and GWD0998)	5-230 V ac/dc	0,6-100 mA ac/dc	1	1/4

CHARACTERISTICS: the auxiliary contact, coupled on the right side of ReStart device, will change state to indicate that the automatic reset did not take place because there is a fault in the electrical system.
The auxiliary contact can be set in three operating modes:
- NO (default condition)
- NC
- NO as signal of handle position

NOTE: the auxiliary contacts is free potential type.



GW 90 992

BUS RS485 communication interface module

Code	Suitable for	No. of modules EN 50022	Pack Carton
GW 90 992	ReStart Autotest PRO 2P-4P/ReStart Rd PRO 2P-4P/ ReStart Rm PRO 2P-4P	1	1

CHARACTERISTICS: the BUS module, by means software TEST available on www.gewiss.com website, allows to:
- monitor the status of circuit breaker coupled with ReStart
- control AUTOTEST function remotely
- manage automatic reclosing function remotely.

APPLICATIONS: it allows the installation of ReStart device in monitoring systems with BUS RS485 communication protocol.
NOTE: in case of coupling of the BUS module only with the following codes of the ReStart devices: GWD4817P GWD4827P GWD0976 GWD0978 GWD4227P GWD4229P GWD0996 GWD0998 it is also necessary to couple the auxiliary contact GWD0951 for correct assembly.



90 ReStart



Scan the QR Code and find out all the technical informations.

SAVINGS ON MAINTENANCE COSTS



Automatic solution of involuntary disconnections from the electrical power supply and automated checking of the circuit breaker significantly reduce the need for manual intervention by technicians, which means a reduction in operating costs.

CONTINUOUS POWER SUPPLY



The ReStart devices automatically restore the power supply if the circuit breaker is unexpectedly tripped. This means less interruption of activities and increased continuity of service, especially in environments where a reliable power supply is critical.

IMPROVED SAFETY



The ReStart automatic reclosing devices prevent dangerous situations because they quickly identify faults in the electrical system and restore the power supply under optimal safety conditions only.

Circuit breakers for circuit protection







90 MCB

Modular circuit breakers for circuit protection

p. 438

90 MCB

Miniature circuit breakers

			MINIATURE CIRCUIT BREAKERS				
			MTC				
							
Icn [A] (EN60898)	Curve	In [A]	1P 1 mod.	1P+N (*) 1 mod.	2P 1 mod.	3P 2 mod.	4P 2 mod.
			MTC 45				
4500	C	2	-	GW 90 022	-	-	-
		6	GW 90 005	GW 90 025	GW 90 045	GW 90 065	GW 90 085
		10	GW 90 006	GW 90 026	GW 90 046	GW 90 066	GW 90 086
		13	GW 90 011	GW 90 031	GW 90 051	GW 90 071	GW 90 091
		16	GW 90 007	GW 90 027	GW 90 047	GW 90 067	GW 90 087
		20	GW 90 008	GW 90 028	GW 90 048	GW 90 068	GW 90 088
		25	GW 90 009	GW 90 029	GW 90 049	GW 90 069	GW 90 089
		32	GW 90 010	GW 90 030	GW 90 050	GW 90 070	GW 90 090
		40	-	-	-	-	-
			MTC 60				
6000	C	6	-	GW 90 225	GW 90 245	GW 90 265	GW 90 285
		10	-	GW 90 226	GW 90 246	GW 90 266	GW 90 286
		13	-	GW 90 231	GW 90 251	GW 90 271	GW 90 291
		16	-	GW 90 227	GW 90 247	GW 90 267	GW 90 287
		20	-	GW 90 228	GW 90 248	GW 90 268	GW 90 288
		25	-	GW 90 229	GW 90 249	GW 90 269	GW 90 289
		32	-	GW 90 230	GW 90 250	GW 90 270	GW 90 290
	B	6	-	GW 90 325	GW 90 345	-	-
		10	-	GW 90 326	GW 90 346	-	-
		13	-	GW 90 327	GW 90 347	-	-
		16	-	GW 90 328	GW 90 348	-	-
		20	-	GW 90 329	GW 90 349	-	-
		25	-	GW 90 330	GW 90 350	-	-
		32	-	GW 90 331	GW 90 351	-	-
			MTC 100				
10000	C	6	-	-	GW 90 445	-	-
		10	-	-	GW 90 446	-	-
		13	-	-	GW 90 451	-	-
		16	-	-	GW 90 447	-	-
		20	-	-	GW 90 448	-	-
		25	-	-	GW 90 449	-	-
		32	-	-	GW 90 450	-	-

(*) Versions than cannot be equipped with auxiliary contacts, trip coils, add-on RCD and reclosing devices.

Miniature circuit breakers

			MINIATURE CIRCUIT BREAKERS				
			MT				
							
Icn [A] (EN60898)	Curve	In [A]	1P 1 mod.	1P+N 2 mod.	2P 2 mod.	3P 3 mod.	4P 4 mod.
			MT 4 (*)				
4500	C	6	GW D2 105	GW D2 125	GW D2 145	GW D2 165	GW D2 185
		10	GW D2 106	GW D2 126	GW D2 146	GW D2 166	GW D2 186
		13	GW D2 107	GW D2 127	GW D2 147	GW D2 167	GW D2 187
		16	GW D2 108	GW D2 128	GW D2 148	GW D2 168	GW D2 188
		20	GW D2 109	GW D2 129	GW D2 149	GW D2 169	GW D2 189
		25	GW D2 110	GW D2 130	GW D2 150	GW D2 170	GW D2 190
		32	GW D2 111	GW D2 131	GW D2 151	GW D2 171	GW D2 191
		40	GW D2 112	GW D2 132	GW D2 152	GW D2 172	GW D2 192
		50	GW D2 113	GW D2 133	GW D2 153	GW D2 173	GW D2 193
		63	GW D2 114	GW D2 134	GW D2 154	GW D2 174	GW D2 194
	B	6	GW D2 305	GW D2 325	GW D2 345	GW D2 365	GW D2 385
		10	GW D2 306	GW D2 326	GW D2 346	GW D2 366	GW D2 386
		13	GW D2 307	GW D2 327	GW D2 347	GW D2 367	GW D2 387
		16	GW D2 308	GW D2 328	GW D2 348	GW D2 368	GW D2 388
		20	GW D2 309	GW D2 329	GW D2 349	GW D2 369	GW D2 389
		25	GW D2 310	GW D2 330	GW D2 350	GW D2 370	GW D2 390
		32	GW D2 311	GW D2 331	GW D2 351	GW D2 371	GW D2 391
		40	GW D2 312	GW D2 332	GW D2 352	GW D2 372	GW D2 392
		50	GW D2 313	GW D2 333	GW D2 353	GW D2 373	GW D2 393
		63	GW D2 314	GW D2 334	GW D2 354	GW D2 374	GW D2 394
			MT 6 (*)				
6000	C	6	GW D2 005	GW D2 025	GW D2 045	GW D2 065	GW D2 085
		10	GW D2 006	GW D2 026	GW D2 046	GW D2 066	GW D2 086
		13	GW D2 014	GW D2 034	GW D2 054	GW D2 074	GW D2 094
		16	GW D2 007	GW D2 027	GW D2 047	GW D2 067	GW D2 087
		20	GW D2 008	GW D2 028	GW D2 048	GW D2 068	GW D2 088
		25	GW D2 009	GW D2 029	GW D2 049	GW D2 069	GW D2 089
		32	GW D2 010	GW D2 030	GW D2 050	GW D2 070	GW D2 090
		40	GW D2 011	GW D2 031	GW D2 051	GW D2 071	GW D2 091
		50	GW D2 012	GW D2 032	GW D2 052	GW D2 072	GW D2 092
		63	GW D2 013	GW D2 033	GW D2 053	GW D2 073	GW D2 093
	B	6	GW D2 205	GW D2 225	GW D2 245	GW D2 265	GW D2 285
		10	GW D2 206	GW D2 226	GW D2 246	GW D2 266	GW D2 286
		13	GW D2 214	GW D2 234	GW D2 254	GW D2 274	GW D2 294
		16	GW D2 207	GW D2 227	GW D2 247	GW D2 267	GW D2 287
		20	GW D2 208	GW D2 228	GW D2 248	GW D2 268	GW D2 288
		25	GW D2 209	GW D2 229	GW D2 249	GW D2 269	GW D2 289
		32	GW D2 210	GW D2 230	GW D2 250	GW D2 270	GW D2 290
		40	GW D2 211	GW D2 231	GW D2 251	GW D2 271	GW D2 291
		50	GW D2 212	GW D2 232	GW D2 252	GW D2 272	GW D2 292
		63	GW D2 213	GW D2 233	GW D2 253	GW D2 273	GW D2 293

(*) Versions than cannot be equipped with auxiliary contacts, trip coils, add-on RCD and reclosing devices.

90 MCB

Miniature circuit breakers

Icn [A] (EN60898)	Curve	In [A]	MINIATURE CIRCUIT BREAKERS MT 1P 1 mod.	1P+N 2 mod.	2P 2 mod.	3P 3 mod.	4P 4 mod.
					MT 45		
4500	C	6	GW 92 105	GW 92 125	GW 92 145	GW 92 165	GW 92 185
		10	GW 92 106	GW 92 126	GW 92 146	GW 92 166	GW 92 186
		13	GW 92 107	GW 92 127	GW 92 147	GW 92 167	GW 92 187
		16	GW 92 108	GW 92 128	GW 92 148	GW 92 168	GW 92 188
		20	GW 92 109	GW 92 129	GW 92 149	GW 92 169	GW 92 189
		25	GW 92 110	GW 92 130	GW 92 150	GW 92 170	GW 92 190
		32	GW 92 111	GW 92 131	GW 92 151	GW 92 171	GW 92 191
		40	GW 92 112	GW 92 132	GW 92 152	GW 92 172	GW 92 192
	C	6	GW 92 305	GW 92 325	GW 92 345	GW 92 365	GW 92 385
		10	GW 92 306	GW 92 326	GW 92 346	GW 92 366	GW 92 386
		13	GW 92 307	GW 92 327	GW 92 347	GW 92 367	GW 92 387
		16	GW 92 308	GW 92 328	GW 92 348	GW 92 368	GW 92 388
		20	GW 92 309	GW 92 329	GW 92 349	GW 92 369	GW 92 389
		25	GW 92 310	GW 92 330	GW 92 350	GW 92 370	GW 92 390
		32	GW 92 311	GW 92 331	GW 92 351	GW 92 371	GW 92 391
		40	GW 92 312	GW 92 332	GW 92 352	GW 92 372	GW 92 392
					MT 60		
6000	C	1	GW 92 001	GW 92 021	GW 92 041	GW 92 061	GW 92 081
		2	GW 92 002	GW 92 022	GW 92 042	GW 92 062	GW 92 082
		3	GW 92 003	GW 92 023	GW 92 043	GW 92 063	GW 92 083
		4	GW 92 004	GW 92 024	GW 92 044	GW 92 064	GW 92 084
		6	GW 92 005	GW 92 025	GW 92 045	GW 92 065	GW 92 085
		10	GW 92 006	GW 92 026	GW 92 046	GW 92 066	GW 92 086
		13	GW 92 014	GW 92 034	GW 92 054	GW 92 074	GW 92 094
		16	GW 92 007	GW 92 027	GW 92 047	GW 92 067	GW 92 087
		20	GW 92 008	GW 92 028	GW 92 048	GW 92 068	GW 92 088
		25	GW 92 009	GW 92 029	GW 92 049	GW 92 069	GW 92 089
		32	GW 92 010	GW 92 030	GW 92 050	GW 92 070	GW 92 090
		40	GW 92 011	GW 92 031	GW 92 051	GW 92 071	GW 92 091
		50	GW 92 012	GW 92 032	GW 92 052	GW 92 072	GW 92 092
		63	GW 92 013	GW 92 033	GW 92 053	GW 92 073	GW 92 093
	B	6	GW 92 205	-	GW 92 245	GW 92 265	GW 92 285
		10	GW 92 206	-	GW 92 246	GW 92 266	GW 92 286
		13	GW 92 214	-	GW 92 254	GW 92 274	GW 92 294
		16	GW 92 207	-	GW 92 247	GW 92 267	GW 92 287
		20	GW 92 208	-	GW 92 248	GW 92 268	GW 92 288
		25	GW 92 209	-	GW 92 249	GW 92 269	GW 92 289
		32	GW 92 210	-	GW 92 250	GW 92 270	GW 92 290
		40	GW 92 211	-	GW 92 251	GW 92 271	GW 92 291
		50	GW 92 212	-	GW 92 252	GW 92 272	GW 92 292
		63	GW 92 213	-	GW 92 253	GW 92 273	GW 92 293
	D	6	GW 92 405	-	GW 92 445	GW 92 465	GW 92 485
		10	GW 92 406	-	GW 92 446	GW 92 466	GW 92 486
		13	GW 92 414	-	GW 92 454	GW 92 474	GW 92 494
		16	GW 92 407	-	GW 92 447	GW 92 467	GW 92 487
		20	GW 92 408	-	GW 92 448	GW 92 468	GW 92 488
		25	GW 92 409	-	GW 92 449	GW 92 469	GW 92 489
		32	GW 92 410	-	GW 92 450	GW 92 470	GW 92 490
		40	GW 92 411	-	GW 92 451	GW 92 471	GW 92 491

Miniature circuit breakers

			MINIATURE CIRCUIT BREAKERS							
			MT				MTHP			
										
Icn [A] (EN60898)	Curve	In [A]	1P 1 mod.	2P 2 mod.	3P 3 mod.	4P 4 mod.	1P 1.5 mod.	2P 3 mod.	3P 4.5 mod.	4P 6 mod.
			MT 100							
10000	C	6	GW 92 605	GW 92 645	GW 92 665	GW 92 685	-	-	-	-
		10	GW 92 606	GW 92 646	GW 92 666	GW 92 686	-	-	-	-
		13	GW 92 614	GW 92 654	GW 92 674	GW 92 694	-	-	-	-
		16	GW 92 607	GW 92 647	GW 92 667	GW 92 687	-	-	-	-
		20	GW 92 608	GW 92 648	GW 92 668	GW 92 688	-	-	-	-
		25	GW 92 609	GW 92 649	GW 92 669	GW 92 689	-	-	-	-
		32	GW 92 610	GW 92 650	GW 92 670	GW 92 690	-	-	-	-
		40	GW 92 611	GW 92 651	GW 92 671	GW 92 691	-	-	-	-
		50	GW 92 612	GW 92 652	GW 92 672	GW 92 692	-	-	-	-
		63	GW 92 613	GW 92 653	GW 92 673	GW 92 693	-	-	-	-
	B	6	GW 92 505	GW 92 545	GW 92 565	GW 92 585	-	-	-	-
		10	GW 92 506	GW 92 546	GW 92 566	GW 92 586	-	-	-	-
		13	GW 92 507	GW 92 547	GW 92 567	GW 92 587	-	-	-	-
		16	GW 92 508	GW 92 548	GW 92 568	GW 92 588	-	-	-	-
		20	GW 92 509	GW 92 549	GW 92 569	GW 92 589	-	-	-	-
		25	GW 92 510	GW 92 550	GW 92 570	GW 92 590	-	-	-	-
		32	GW 92 511	GW 92 551	GW 92 571	GW 92 591	-	-	-	-
		40	GW 92 512	GW 92 552	GW 92 572	GW 92 592	-	-	-	-
		50	GW 92 513	GW 92 553	GW 92 573	GW 92 593	-	-	-	-
		63	GW 92 514	GW 92 554	GW 92 574	GW 92 594	-	-	-	-
	D	1	GW 92 701	GW 92 741	GW 92 761	GW 92 781	-	-	-	-
		2	GW 92 702	GW 92 742	GW 92 762	GW 92 782	-	-	-	-
		3	GW 92 703	GW 92 743	GW 92 763	GW 92 783	-	-	-	-
		4	GW 92 704	GW 92 744	GW 92 764	GW 92 784	-	-	-	-
		6	GW 92 705	GW 92 745	GW 92 765	GW 92 785	-	-	-	-
		10	GW 92 706	GW 92 746	GW 92 766	GW 92 786	-	-	-	-
		13	GW 92 714	GW 92 754	GW 92 774	GW 92 794	-	-	-	-
		16	GW 92 707	GW 92 747	GW 92 767	GW 92 787	-	-	-	-
		20	GW 92 708	GW 92 748	GW 92 768	GW 92 788	-	-	-	-
		25	GW 92 709	GW 92 749	GW 92 769	GW 92 789	-	-	-	-
		32	GW 92 710	GW 92 750	GW 92 770	GW 92 790	-	-	-	-
		40	GW 92 711	GW 92 751	GW 92 771	GW 92 791	-	-	-	-
							MTHP 160			
10000 (16kA EN60947-2)	C	80	-	-	-	-	GW 93 307	GW 93 327	GW 93 337	GW 93 347
		100	-	-	-	-	GW 93 308	GW 93 328	GW 93 338	GW 93 348
		125	-	-	-	-	GW 93 309	GW 93 329	GW 93 339	GW 93 349
	D	50	-	-	-	-	GW 93 355	GW 93 375	GW 93 385	GW 93 395
		63	-	-	-	-	GW 93 356	GW 93 376	GW 93 386	GW 93 396
		80	-	-	-	-	GW 93 357	GW 93 377	GW 93 387	GW 93 397
		100	-	-	-	-	GW 93 358	GW 93 378	GW 93 388	GW 93 398
			MT 250				**MTHP 250**			
12500	C	50	GW 92 812	GW 92 852	GW 92 872	GW 92 892	-	-	-	-
		63	GW 92 813	GW 92 853	GW 92 873	GW 92 893	-	-	-	-
15000	C	32	GW 92 810	GW 92 850	GW 92 870	GW 92 890	-	-	-	-
		40	GW 92 811	GW 92 851	GW 92 871	GW 92 891	-	-	-	-
20000	C	25	GW 92 809	GW 92 849	GW 92 869	GW 92 889	-	-	-	-
25000	C	6	GW 92 805	GW 92 845	GW 92 865	GW 92 885	-	-	-	-
		10	GW 92 806	GW 92 846	GW 92 866	GW 92 886	-	-	-	-
		16	GW 92 807	GW 92 847	GW 92 867	GW 92 887	-	-	-	-
		20	GW 92 808	GW 92 848	GW 92 868	GW 92 888	GW 93 201	GW 93 221	GW 93 231	GW 93 241
		25	-	-	-	-	GW 93 202	GW 93 222	GW 93 232	GW 93 242
		32	-	-	-	-	GW 93 203	GW 93 223	GW 93 233	GW 93 243
		40	-	-	-	-	GW 93 204	GW 93 224	GW 93 234	GW 93 244
		50	-	-	-	-	GW 93 205	GW 93 225	GW 93 235	GW 93 245
		63	-	-	-	-	GW 93 206	GW 93 226	GW 93 236	GW 93 246

Technical data - MCB - MTC - MT - MTHP

TYPE					MTC							MT					
					MTC 45			MTC 60			MTC 100	MT 4		MT 45		MT 6	
																	
Standards:					IEC EN 60898-1												
Rated current (In):				(A)	2-32			6-32			6-32	6-63		6-40		6-63	
Utilization category:					A			A			A	A		A		A	
Rated operational voltage (Ue):				(V)	230/400 - 240/415			230/400 - 240/415			230 - 240	230/400 - 240/415		230/400 - 240/415		230/400 - 240/415	
Minimum operating voltage (Ue min):				(V)	12 ac/dc			12 ac/dc			12 ac/dc	12 ac		12 ac/dc		12 ac	
Maximum operating voltage (Ue max):				(V)	440 ac/ 250 dc			440 ac/ 250 dc			253 ac/ 125 dc	440 ac		440 ac/ 250 dc		440 ac	
Insulation voltage (Ui):				(V)	500			500			500	500		500		500	
Rated frequency:				(Hz)	50/60			50/60			50/60	50/60		50/60		50/60	
Rated impulse withstand voltage (Uimp):				(kV)	4			4			4	4		4		4	
Overvoltage category:					III			III			III	III		III		III	
Number of poles:					1P, 1P+N	2P	3P, 4P	1P+N	2P	3P, 4P	2P	1P, 1P+N	2P, 3P, 4P	1P, 1P+N	2P, 3P, 4P	1P, 1P+N	2P, 3P, 4P
Energy limiting class (B and C curve):					3	3	3	3	3	3 (≤16A) 1 (>16A)	3	3	3	3	3	3	3
Breaking capacity																	
Alternating current:	**IEC/EN 60898-1**	**Icn**		(A)	4500			6000 [1]		6000	10000 [1]	4500		4500		6000	
		Ics		(A)	1 Icn			1 Icn			0.75 Icn	1 Icn		1 Icn		1 Icn	
	IEC/EN 60947-2	**Icu**	**230/240 V**	(kA)	4.5	6	6	6	10	10	15	6	6	4,5	6	6	6
			400/415 V	(kA)	-	-	4.5	-	-	6	-	-	6	-	6	-	6
		Ics		(kA)	100% Icu			100% Icu	75% Icu	100% Icu	50% Icu	100% Icu		100% Icu		100% Icu	
Direct current:	**IEC/EN 60947-2**	**Icu (1 pole)**	**72 V**	(kA)	6			10			-	-		6		-	
		Ics			6			10			-	-		6		-	
		Icu (2 poles in series) [2]	**125 V**	(kA)	6			10			10 (15 at 72V)	-		6		-	
		Ics			6			10			10 (15 at 72V)	-		6		-	
		Icu (4 poles in series)	**250 V**	(kA)	4.5			6			-	-		4.5		-	
		Ics			4.5			6			-	-		4.5		-	
Wiring:		**cable section (mm²)** [3]	**rigid**		≤ 1x16 - ≤ 1x10+1x6			≤ 1x16 - ≤ 1x10+1x6			≤ 1x16 - ≤ 1x10+1x6	≤ 1x25 - ≤ 2x10 ≤ 1x16+1x10		≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10		≤ 1x25 - ≤ 2x10 ≤ 1x16+1x10	
			flexible		≤ 1x10- ≤ 2x6			≤ 1x10- ≤ 2x6			≤ 1x10- ≤ 2x6	≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10	
Screwdriver suggested:					PZ2			PZ2			PZ2	PZ2		PZ2		PZ2	
Electrical endurance:					10000			10000			10000	8000		10000		8000	
Mechanical endurance:					20000			20000			20000	20000		20000		20000	
Max. no. of usable modular accessories:					2 [5]			2 [5]			2	-		2		-	
Upline/downline power supply:					yes			yes			yes	yes		yes		yes	
ON/OFF status displayed:					yes			yes			yes	yes		yes		yes	
Mounting position:					any			any			any	any		any		any	
Type of residual current device:					-			-			-	-		Add-on RCB BD		-	
Rated tightening torque:				(Nm)	1.2			1.2			1.2	2		2		2	
Degree of protection:		**terminals**			IP20			IP20			IP20	IP20		IP20		IP20	
		front			IP40			IP40			IP40	IP40		IP40		IP40	
Pollution degree:					2			2			2	2		2		2	
Tropicalization:					55°C - RH 95%			55°C - RH 95%			55°C - RH 95%	55°C - RH 95%		55°C - RH 95%		55°C - RH 95%	
Reference temperature:				(°C)	30			30			30	30		30		30	
Operating temperature:				(°C)	-25 +70 [6]			-25 +70 [6]			-25 +70 [6]	-25 +70 [6]		-25 +70 [6]		-25 +70 [6]	
Stocking temperature:				(°C)	-40 +70			-40 +70			-40 +70	-40 +70		-40 +70		-40 +70	
Double connection (cable+fork busbar):					no			no			no	yes (only downstream)		yes (only downstream)		yes (only downstream)	
Weight:				(g)	135 (per module)			135 (per module)			135 (per module)	115 (per pole)		145 (per pole)		115 (per pole)	
Curve:					C			C	B	D	C	C	B	C	B	C	B
Rated currents available In:				(A)	-			-	-	-	-	-		-		-	
					2			-	-	-	-	-		-		-	
					-			-	-	-	-	-		-		-	
					-			-	-	-	-	-		-		-	
					6			6	6	-	6	6	6	6	6	6	6
					10			10	10	10	10	10	10	10	10	10	10
					13			13	13	-	13	13	13	13	13	13	13
					16			16	16	16	16	16	16	16	16	16	16
					20			20	20	20	20	20	20	20	20	20	20
					25			25	25	25	25	25	25	25	25	25	25
					32			32	32	32	32	32	32	32	32	32	32
					-			-	-	-	-	40	40	40	40	40	40
					-			-	-	-	-	50	50	-		50	50
					-			-	-	-	-	63	63	-		63	63
					-			-	-	-	-	-		-		-	
					-			-	-	-	-	-		-		-	
					-			-	-	-	-	-		-		-	
Grid distance:				(mm)	35			35			35	40		70		40	

[1] Breaking capacity of the single pole Icn1=4500A
[2] 1P+N version not allowed
[3] Minimum cable section is 1mm² for MTC and MT, 1,5mm² for MTHP
[4] ≤95mm² with reduced connection terminal (width flap connection < 17mm)
[5] 1P+N versions cannot be accessorised
[6] With temperatures greater than 30°C, derating of In rated current is expected

	MT																			MTHP		MTHP		
MT 60	**MT 100**							**MT 250**												**MTHP 160**		**MTHP 250**		
																								
	IEC EN 60898-1																			**IEC EN 60898-1**		**IEC EN 60947-2**		
1-63	1-25			32-63				6-20			25			32-40			50-63			50-125		20-63		
A	A			A				A			A			A			A			A		A		
230/400 - 240/415	230/400 - 240/415			230/400 - 240/415				230/400 - 240/415			230/400 - 240/415			230/400 - 240/415			230/400 - 240/415			230/400		230/400		
12 ac/dc	12 ac/dc			12 ac/dc				12 ac/dc			12 ac/dc			12 ac/dc			12 ac/dc			12 ac/dc		12 ac/dc		
440 ac/ 250 dc	440 ac/ 250 dc			440 ac/ 250 dc				440 ac/ 250 dc			440 ac/ 250 dc			440 ac/ 250 dc			440 ac/ 250 dc			440 ac/ 250 dc		440 ac/ 250 dc		
500	500			500				500			500			500			500			500		500		
50/60	50/60			50/60				50/60			50/60			50/60			50/60			50/60		50/60		
4	4			4				4			4			4			4			6		6		
III	III			III				III			III			III			III			IV		IV		
1P, 1P+N	2P, 3P, 4P	1P	2P	3P, 4P	1P	2P	3P, 4P	1P	2P	3P, 4P	1P	2P	3P, 4P	1P	2P	3P, 4P	1P	2P	3P, 4P	1P	2P, 3P, 4P	1P	2P	3P, 4P
3	3	3	3	3	3	3	3	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
6000	10000			10000				25000			20000			15000			12500			10000		25000		
1 Icn	0.75 Icn			0.75 Icn				0.5 Icn			0.5 Icn			0.5 Icn			0.5 Icn			0.75 Icn		0.75 Icn		
10	15	30	25	12.5	25	20	25	50	40	20	40	30	15	30	25	15	25	20	16	20	25	50	30	
-	10	20	15	-	15	12.5	-	30	25	-	25	20	-	20	15	-	15	15	4.5	16	6	25	25	
75% Icu	50% Icu			50% Icu				50% Icu			50% Icu			50% Icu			50% Icu			50% Icu		75% Icu		
10	10			10				20			20			20			20			10		25		
10	10			10				15			15			15			15			10		20		
10	15			15				25			25			25			25			15		30		
6	15			15				20			20			20			20			12		25		
10	15			15				25			25			25			25			15		25		
10	12			12				20			20			20			20			12		20		
≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10	≤1x35 - ≤2x16 - ≤1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10				≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x70 - ≤ 2x25 - ≤ 2x25+1x10		≤ 1x70 - ≤ 2x25 - ≤ 2x25+1x10		
≤ 1x35 - ≤ 2x16 ≤ 1x16+2x10	≤1x35 - ≤2x16 - ≤1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10				≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10			≤ 1x50 [4] - ≤ 2x25 - ≤ 3x16		≤ 1x50 [4] - ≤ 2x25 - ≤ 3x16		
PZ2	PZ2			PZ2				PZ2			PZ2			PZ2			PZ2			PZ2		PZ2		
10000	10000			10000				10000			10000			10000			10000			10000		10000		
20000	20000			20000				20000			20000			20000			20000			20000		20000		
2	2			2				2			2			2			2			2		2		
yes	yes			yes				yes			yes			yes			yes			yes		yes		
yes	yes			yes				yes			yes			yes			yes			yes		yes		
any	any			any				any			any			any			any			any		any		
Add-on RCD BD	Add-on RCD BD			Add-on RCD BD				Add-on RCD BD			Add-on RCD BD			Add-on RCD BD			Add-on RCD BD			Add-on RCD BDHP		Add-on RCD BDHP		
2	2			2				2			2			2			2			3.5 / 3 (terminal)		3.5 / 3 (terminal)		
IP20	IP20			IP20				IP20			IP20			IP20			IP20			IP20		IP20		
IP40	IP40			IP40				IP40			IP40			IP40			IP40			IP40		IP40		
2	2			2				2			2			2			2			2		2		
55°C - RH 95%	55°C - RH 95%			55°C - RH 95%				55°C - RH 95%			55°C - RH 95%			55°C - RH 95%			55°C - RH 95%			55°C - RH 95%		55°C - RH 95%		
30	30			30				30			30			30			30			30		30		
-25 +70 [6]	-25 +70 [6]			-25 +70 [6]				-25 +70 [6]			-25 +70 [6]			-25 +70 [6]			-25 +70 [6]			-25 +70 [6]		-25 +70 [6]		
-40 +70	-40 +70			-40 +70				-40 +70			-40 +70			-40 +70			-40 +70			-40 +70		-40 +70		
yes (only downstream terminals)	yes (only downstream terminals)			yes (only downstream terminals)				yes (only downstream terminals)			yes (only downstream terminals)			yes (only downstream terminals)			yes (only downstream terminals)			no		no		
145 (per pole)	145 (per pole)			145 (per pole)				145 (per pole)			145 (per pole)			145 (per pole)			145 (per pole)			250 (per pole)		250 (per pole)		
C	B		D	C		B	D	C												C	D	C		
1	-		-	-		-	1	-												-	-	-		
2	-		-	-		-	2	-												-	-	-		
3	-		-	-		-	3	-												-	-	-		
4	-		-	-		-	4	-												-	-	-		
6	6		6	6		6	6	6												-	-	-		
10	10		10	10		10	10	10												-	-	-		
13	13		13	13		13	13	-												-	-	-		
16	16		16	16		16	16	16												-	-	-		
20	20		20	20		20	20	20												-	-	20		
25	25		25	25		25	25	25												-	-	25		
32	32		32	32		32	32	32												-	-	32		
40	40		40	40		40	40	40												-	-	40		
50	50		-	50		50	-	50												-	50	50		
63	63		-	63		63	-	63												-	63	63		
-	-		-	-		-	-	-												80	80	-		
-	-		-	-		-	-	-												100	100	-		
-	-		-	-		-	-	-												125	-	-		
70	70			70				70												70				

90 MCB

Modular circuit breakers for circuit protection

The 90 MCB range meets any requirement for protection against overcurrent and shortcircuit, for all domestic, commercial and industrial applications.The range comprises MTC, compact miniature circuit breakers (from 2 to 32 A, curves B and C up to 10 kA) MT traditional miniature circuit breakers (from 1 to 63 A, curves B, C and D up to 25 kA) MTHP High-Power Miniature circuit breakers (from 20 to 125 A, curves C and D up to 25 kA).



MTC - COMPACT MINIATURE CIRCUIT BREAKERS

MTC 45 - C curve - 4500 A (EN 60898) - 4.5 kA (EN 60947-2)









GW 90 046

Compact miniature circuit breakers

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P					
GW 90 005	6 A	230 - 400 V	Yes	1	6/24
GW 90 006	10 A	230 - 400 V	Yes	1	6/24
GW 90 011	13 A	230 - 400 V	Yes	1	6/24
GW 90 007	16 A	230 - 400 V	Yes	1	6/24
GW 90 008	20 A	230 - 400 V	Yes	1	6/24
GW 90 009	25 A	230 - 400 V	Yes	1	6/24
GW 90 010	32 A	230 - 400 V	Yes	1	6/24
No. of poles: 1P+N					
GW 90 022	2 A	230 V	No	1	6/24
GW 90 025	6 A	230 V	No	1	6/24
GW 90 026	10 A	230 V	No	1	6/24
GW 90 031	13 A	230 V	No	1	6/24
GW 90 027	16 A	230 V	No	1	6/24
GW 90 028	20 A	230 V	No	1	6/24
GW 90 029	25 A	230 V	No	1	6/24
GW 90 030	32 A	230 V	No	1	6/24
No. of poles: 1P+N (N-conductor left)					
GW 90 602	2 A	230 V	No	1	6/24
GW 90 605	6 A	230 V	No	1	6/24
GW 90 606	10 A	230 V	No	1	6/24
GW 90 607	16 A	230 V	No	1	6/24
GW 90 608	20 A	230 V	No	1	6/24
GW 90 609	25 A	230 V	No	1	6/24
GW 90 610	32 A	230 V	No	1	6/24
No. of poles: 2P					
GW 90 045	6 A	230 V	Yes	1	6/24
GW 90 046	10 A	230 V	Yes	1	6/24
GW 90 051	13 A	230 V	Yes	1	6/24
GW 90 047	16 A	230 V	Yes	1	6/24
GW 90 048	20 A	230 V	Yes	1	6/24
GW 90 049	25 A	230 V	Yes	1	6/24
GW 90 050	32 A	230 V	Yes	1	6/24
No. of poles: 3P					
GW 90 065	6 A	230 - 400 V	Yes	2	3/12
GW 90 066	10 A	230 - 400 V	Yes	2	3/12
GW 90 071	13 A	230 - 400 V	Yes	2	3/12
GW 90 067	16 A	230 - 400 V	Yes	2	3/12
GW 90 068	20 A	230 - 400 V	Yes	2	3/12
GW 90 069	25 A	230 - 400 V	Yes	2	3/12
GW 90 070	32 A	230 - 400 V	Yes	2	3/12
No. of poles: 4P					
GW 90 085	6 A	230 - 400 V	Yes	2	3/12
GW 90 086	10 A	230 - 400 V	Yes	2	3/12
GW 90 091	13 A	230 - 400 V	Yes	2	3/12
GW 90 087	16 A	230 - 400 V	Yes	2	3/12
GW 90 088	20 A	230 - 400 V	Yes	2	3/12
GW 90 089	25 A	230 - 400 V	Yes	2	3/12
GW 90 090	32 A	230 - 400 V	Yes	2	3/12

MTC 45 - D curve - 4500 A (EN 60898) - 4.5 kA (EN 60947-2)



GW 90 626

Compact miniature circuit breakers

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N (N-conductor left)					
GW 90 626	10 A	230 V	No	1	6/24
GW 90 627	16 A	230 V	No	1	6/24
GW 90 628	20 A	230 V	No	1	6/24
GW 90 629	25 A	230 V	No	1	6/24
GW 90 630	32 A	230 V	No	1	6/24

MTC 60 - C curve - 6000 A (EN 60898) - 6 kA (EN 60947-2)









GW 90 290


Compact miniature circuit breakers


Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 90 225	6 A	230 V	No	1	6/24
GW 90 226	10 A	230 V	No	1	6/24
GW 90 231	13 A	230 V	No	1	6/24
GW 90 227	16 A	230 V	No	1	6/24
GW 90 228	20 A	230 V	No	1	6/24
GW 90 229	25 A	230 V	No	1	6/24
GW 90 230	32 A	230 V	No	1	6/24
No. of poles: 2P					
GW 90 245	6 A	230 V	Yes	1	6/24
GW 90 246	10 A	230 V	Yes	1	6/24
GW 90 251	13 A	230 V	Yes	1	6/24
GW 90 247	16 A	230 V	Yes	1	6/24
GW 90 248	20 A	230 V	Yes	1	6/24
GW 90 249	25 A	230 V	Yes	1	6/24
GW 90 250	32 A	230 V	Yes	1	6/24
No. of poles: 3P					
GW 90 265	6 A	230 - 400 V	Yes	2	3/12
GW 90 266	10 A	230 - 400 V	Yes	2	3/12
GW 90 271	13 A	230 - 400 V	Yes	2	3/12
GW 90 267	16 A	230 - 400 V	Yes	2	3/12
GW 90 268	20 A	230 - 400 V	Yes	2	3/12
GW 90 269	25 A	230 - 400 V	Yes	2	3/12
GW 90 270	32 A	230 - 400 V	Yes	2	3/12
No. of poles: 4P					
GW 90 285	6 A	230 - 400 V	Yes	2	3/12
GW 90 286	10 A	230 - 400 V	Yes	2	3/12
GW 90 291	13 A	230 - 400 V	Yes	2	3/12
GW 90 287	16 A	230 - 400 V	Yes	2	3/12
GW 90 288	20 A	230 - 400 V	Yes	2	3/12
GW 90 289	25 A	230 - 400 V	Yes	2	3/12
GW 90 290	32 A	230 - 400 V	Yes	2	3/12

NEWS

90 MCB

MTC 60 - B curve - 6000 A (EN 60898) - 10 kA (EN 60947-2)








GW 90 326

Compact miniature circuit breakers

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 90 325	6 A	230 V	No	1	6/24
GW 90 326	10 A	230 V	No	1	6/24
GW 90 327	13 A	230 V	No	1	6/24
GW 90 328	16 A	230 V	No	1	6/24
GW 90 329	20 A	230 V	No	1	6/24
GW 90 330	25 A	230 V	No	1	6/24
GW 90 331	32 A	230 V	No	1	6/24
No. of poles: 2P					
GW 90 345	6 A	230 V	Yes	1	6/24
GW 90 346	10 A	230 V	Yes	1	6/24
GW 90 347	13 A	230 V	Yes	1	6/24
GW 90 348	16 A	230 V	Yes	1	6/24
GW 90 349	20 A	230 V	Yes	1	6/24
GW 90 350	25 A	230 V	Yes	1	6/24
GW 90 351	32 A	230 V	Yes	1	6/24

MTC 100 - C curve - 10000 A (EN 60898) - 15 kA (EN 60947-2)





GW 90 446

Compact miniature circuit breakers

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 90 445	6 A	230 V	Yes	1	6/24
GW 90 446	10 A	230 V	Yes	1	6/24
GW 90 451	13 A	230 V	Yes	1	6/24
GW 90 447	16 A	230 V	Yes	1	6/24
GW 90 448	20 A	230 V	Yes	1	6/24
GW 90 449	25 A	230 V	Yes	1	6/24
GW 90 450	32 A	230 V	Yes	1	6/24

MT - MINIATURE CIRCUIT BREAKERS WITHOUT ACCESSORIES

MT 4 - C curve - 4500 A (EN 60898) - 6 kA (EN 60947-2)

BREAKING CAPACITY 1P+N		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	4500 A	6 kA

BREAKING CAPACITY 2P		
230V 400V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	4500 A	6 kA



GW D2 128

Miniature circuit breakers

Code		Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P						
GW D2 105	①	6 A	230 - 400 V	No	1	6/24
GW D2 106	①	10 A	230 - 400 V	No	1	6/24
GW D2 107	①	13 A	230 - 400 V	No	1	6/24
GW D2 108	①	16 A	230 - 400 V	No	1	6/24
GW D2 109	①	20 A	230 - 400 V	No	1	6/24
GW D2 110	①	25 A	230 - 400 V	No	1	6/24
GW D2 111	①	32 A	230 - 400 V	No	1	6/24
GW D2 112	①	40 A	230 - 400 V	No	1	6/24
GW D2 113	①	50 A	230 - 400 V	No	1	6/24
GW D2 114	①	63 A	230 - 400 V	No	1	6/24
No. of poles: 1P+N						
GW D2 125	①	6 A	230 V	No	2	3/12
GW D2 126	①	10 A	230 V	No	2	3/12
GW D2 127	①	13 A	230 V	No	2	3/12
GW D2 128	①	16 A	230 V	No	2	3/12
GW D2 129	①	20 A	230 V	No	2	3/12
GW D2 130	①	25 A	230 V	No	2	3/12
GW D2 131	①	32 A	230 V	No	2	3/12
GW D2 132	①	40 A	230 V	No	2	3/12
GW D2 133	①	50 A	230 V	No	2	3/12
GW D2 134	①	63 A	230 V	No	2	3/12
No. of poles: 2P						
GW D2 145	①	6 A	230 - 400 V	No	2	3/12
GW D2 146	①	10 A	230 - 400 V	No	2	3/12
GW D2 147	①	13 A	230 - 400 V	No	2	3/12
GW D2 148	①	16 A	230 - 400 V	No	2	3/12
GW D2 149	①	20 A	230 - 400 V	No	2	3/12
GW D2 150	①	25 A	230 - 400 V	No	2	3/12
GW D2 151	①	32 A	230 - 400 V	No	2	3/12
GW D2 152	①	40 A	230 - 400 V	No	2	3/12
GW D2 153	①	50 A	230 - 400 V	No	2	3/12
GW D2 154	①	63 A	230 - 400 V	No	2	3/12
No. of poles: 3P						
GW D2 165	①	6 A	230 - 400 V	No	3	2/8
GW D2 166	①	10 A	230 - 400 V	No	3	2/8
GW D2 167	①	13 A	230 - 400 V	No	3	2/8
GW D2 168	①	16 A	230 - 400 V	No	3	2/8
GW D2 169	①	20 A	230 - 400 V	No	3	2/8
GW D2 170	①	25 A	230 - 400 V	No	3	2/8
GW D2 171	①	32 A	230 - 400 V	No	3	2/8
GW D2 172	①	40 A	230 - 400 V	No	3	2/8
GW D2 173	①	50 A	230 - 400 V	No	3	2/8
GW D2 174	①	63 A	230 - 400 V	No	3	2/8
No. of poles: 4P						
GW D2 185	①	6 A	230 - 400 V	No	4	1/3
GW D2 186	①	10 A	230 - 400 V	No	4	1/3
GW D2 187	①	13 A	230 - 400 V	No	4	1/3
GW D2 188	①	16 A	230 - 400 V	No	4	1/3
GW D2 189	①	20 A	230 - 400 V	No	4	1/3
GW D2 190	①	25 A	230 - 400 V	No	4	1/3
GW D2 191	①	32 A	230 - 400 V	No	4	1/3
GW D2 192	①	40 A	230 - 400 V	No	4	1/3
GW D2 193	①	50 A	230 - 400 V	No	4	1/3
GW D2 194	①	63 A	230 - 400 V	No	4	1/3

NEWS

Availability: ① December 2025

MT 4 - B Curve - 4500 A (EN 60898) - 6 kA (EN 60947-2)

BREAKING CAPACITY 1P+N		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	4500 A	6 kA

BREAKING CAPACITY 2P		
230V 400V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	4500 A	6 kA



GW D2 328

Miniature circuit breakers

Code		Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P						
GW D2 305	①	6 A	230 - 400 V	No	1	6/24
GW D2 306	①	10 A	230 - 400 V	No	1	6/24
GW D2 307	①	13 A	230 - 400 V	No	1	6/24
GW D2 308	①	16 A	230 - 400 V	No	1	6/24
GW D2 309	①	20 A	230 - 400 V	No	1	6/24
GW D2 310	①	25 A	230 - 400 V	No	1	6/24
GW D2 311	①	32 A	230 - 400 V	No	1	6/24
GW D2 312	①	40 A	230 - 400 V	No	1	6/24
GW D2 313	①	50 A	230 - 400 V	No	1	6/24
GW D2 314	①	63 A	230 - 400 V	No	1	6/24
No. of poles: 1P+N						
GW D2 325	①	6 A	230 V	No	2	3/12
GW D2 326	①	10 A	230 V	No	2	3/12
GW D2 327	①	13 A	230 V	No	2	3/12
GW D2 328	①	16 A	230 V	No	2	3/12
GW D2 329	①	20 A	230 V	No	2	3/12
GW D2 330	①	25 A	230 V	No	2	3/12
GW D2 331	①	32 A	230 V	No	2	3/12
GW D2 332	①	40 A	230 V	No	2	3/12
GW D2 333	①	50 A	230 V	No	2	3/12
GW D2 334	①	63 A	230 V	No	2	3/12
No. of poles: 2P						
GW D2 345	①	6 A	230 - 400 V	No	2	3/12
GW D2 346	①	10 A	230 - 400 V	No	2	3/12
GW D2 347	①	13 A	230 - 400 V	No	2	3/12
GW D2 348	①	16 A	230 - 400 V	No	2	3/12
GW D2 349	①	20 A	230 - 400 V	No	2	3/12
GW D2 350	①	25 A	230 - 400 V	No	2	3/12
GW D2 351	①	32 A	230 - 400 V	No	2	3/12
GW D2 352	①	40 A	230 - 400 V	No	2	3/12
GW D2 353	①	50 A	230 - 400 V	No	2	3/12
GW D2 354	①	63 A	230 - 400 V	No	2	3/12
No. of poles: 3P						
GW D2 365	①	6 A	230 - 400 V	No	3	2/8
GW D2 366	①	10 A	230 - 400 V	No	3	2/8
GW D2 367	①	13 A	230 - 400 V	No	3	2/8
GW D2 368	①	16 A	230 - 400 V	No	3	2/8
GW D2 369	①	20 A	230 - 400 V	No	3	2/8
GW D2 370	①	25 A	230 - 400 V	No	3	2/8
GW D2 371	①	32 A	230 - 400 V	No	3	2/8
GW D2 372	①	40 A	230 - 400 V	No	3	2/8
GW D2 373	①	50 A	230 - 400 V	No	3	2/8
GW D2 374	①	63 A	230 - 400 V	No	3	2/8
No. of poles: 4P						
GW D2 385	①	6 A	230 - 400 V	No	4	1/3
GW D2 386	①	10 A	230 - 400 V	No	4	1/3
GW D2 387	①	13 A	230 - 400 V	No	4	1/3
GW D2 388	①	16 A	230 - 400 V	No	4	1/3
GW D2 389	①	20 A	230 - 400 V	No	4	1/3
GW D2 390	①	25 A	230 - 400 V	No	4	1/3
GW D2 391	①	32 A	230 - 400 V	No	4	1/3
GW D2 392	①	40 A	230 - 400 V	No	4	1/3
GW D2 393	①	50 A	230 - 400 V	No	4	1/3
GW D2 394	①	63 A	230 - 400 V	No	4	1/3

NEWS

Availability: ① December 2025

MT 6 - C Curve - 6000 A (EN 60898) - 6 kA (EN 60947-2)

BREAKING CAPACITY 1P, 1P+N			BREAKING CAPACITY 2-3-4P		
230V	EN60898 Icn	EN60947-2 Icu	230V 400V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	6000 A	6 kA	In=1÷63 A	6000 A	6 kA



GW D2 027

Miniature circuit breakers

Code		Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P						
GW D2 005	①	6 A	230 - 400 V	No	1	6/24
GW D2 006	①	10 A	230 - 400 V	No	1	6/24
GW D2 014	①	13 A	230 - 400 V	No	1	6/24
GW D2 007	①	16 A	230 - 400 V	No	1	6/24
GW D2 008	①	20 A	230 - 400 V	No	1	6/24
GW D2 009	①	25 A	230 - 400 V	No	1	6/24
GW D2 010	①	32 A	230 - 400 V	No	1	6/24
GW D2 011	①	40 A	230 - 400 V	No	1	6/24
GW D2 012	①	50 A	230 - 400 V	No	1	6/24
GW D2 013	①	63 A	230 - 400 V	No	1	6/24
No. of poles: 1P+N						
GW D2 025	①	6 A	230 V	No	2	3/12
GW D2 026	①	10 A	230 V	No	2	3/12
GW D2 034	①	13 A	230 V	No	2	3/12
GW D2 027	①	16 A	230 V	No	2	3/12
GW D2 028	①	20 A	230 V	No	2	3/12
GW D2 029	①	25 A	230 V	No	2	3/12
GW D2 030	①	32 A	230 V	No	2	3/12
GW D2 031	①	40 A	230 V	No	2	3/12
GW D2 032	①	50 A	230 V	No	2	3/12
GW D2 033	①	63 A	230 V	No	2	3/12
No. of poles: 2P						
GW D2 045	①	6 A	230 - 400 V	No	2	3/12
GW D2 046	①	10 A	230 - 400 V	No	2	3/12
GW D2 054	①	13 A	230 - 400 V	No	2	3/12
GW D2 047	①	16 A	230 - 400 V	No	2	3/12
GW D2 048	①	20 A	230 - 400 V	No	2	3/12
GW D2 049	①	25 A	230 - 400 V	No	2	3/12
GW D2 050	①	32 A	230 - 400 V	No	2	3/12
GW D2 051	①	40 A	230 - 400 V	No	2	3/12
GW D2 052	①	50 A	230 - 400 V	No	2	3/12
GW D2 053	①	63 A	230 - 400 V	No	2	3/12
No. of poles: 3P						
GW D2 065	①	6 A	230 - 400 V	No	3	2/8
GW D2 066	①	10 A	230 - 400 V	No	3	2/8
GW D2 074	①	13 A	230 - 400 V	No	3	2/8
GW D2 067	①	16 A	230 - 400 V	No	3	2/8
GW D2 068	①	20 A	230 - 400 V	No	3	2/8
GW D2 069	①	25 A	230 - 400 V	No	3	2/8
GW D2 070	①	32 A	230 - 400 V	No	3	2/8
GW D2 071	①	40 A	230 - 400 V	No	3	2/8
GW D2 072	①	50 A	230 - 400 V	No	3	2/8
GW D2 073	①	63 A	230 - 400 V	No	3	2/8
No. of poles: 4P						
GW D2 085	①	6 A	230 - 400 V	No	4	1/3
GW D2 086	①	10 A	230 - 400 V	No	4	1/3
GW D2 094	①	13 A	230 - 400 V	No	4	1/3
GW D2 087	①	16 A	230 - 400 V	No	4	1/3
GW D2 088	①	20 A	230 - 400 V	No	4	1/3
GW D2 089	①	25 A	230 - 400 V	No	4	1/3
GW D2 090	①	32 A	230 - 400 V	No	4	1/3
GW D2 091	①	40 A	230 - 400 V	No	4	1/3
GW D2 092	①	50 A	230 - 400 V	No	4	1/3
GW D2 093	①	63 A	230 - 400 V	No	4	1/3

NEWS

Availability: ① December 2025

MT 6 - B Curve - 6000 A (EN 60898) - 6 kA (EN 60947-2)

BREAKING CAPACITY 1P, 1P+N			BREAKING CAPACITY 2-3-4P		
230V	EN60898 Icn	EN60947-2 Icu	230V 400V	EN60898 Icn	EN60947-2 Icu
In=6÷63 A	6000 A	6 kA	In=1÷63 A	6000 A	6 kA



GW D2 227

Miniature circuit breakers


Code		Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P						
GW D2 205	①	6 A	230 - 400 V	No	1	6/24
GW D2 206	①	10 A	230 - 400 V	No	1	6/24
GW D2 214	①	13 A	230 - 400 V	No	1	6/24
GW D2 207	①	16 A	230 - 400 V	No	1	6/24
GW D2 208	①	20 A	230 - 400 V	No	1	6/24
GW D2 209	①	25 A	230 - 400 V	No	1	6/24
GW D2 210	①	32 A	230 - 400 V	No	1	6/24
GW D2 211	①	40 A	230 - 400 V	No	1	6/24
GW D2 212	①	50 A	230 - 400 V	No	1	6/24
GW D2 213	①	63 A	230 - 400 V	No	1	6/24
No. of poles: 1P+N						
GW D2 225	①	6 A	230 V	No	2	3/12
GW D2 226	①	10 A	230 V	No	2	3/12
GW D2 234	①	13 A	230 V	No	2	3/12
GW D2 227	①	16 A	230 V	No	2	3/12
GW D2 228	①	20 A	230 V	No	2	3/12
GW D2 229	①	25 A	230 V	No	2	3/12
GW D2 230	①	32 A	230 V	No	2	3/12
GW D2 231	①	40 A	230 V	No	2	3/12
GW D2 232	①	50 A	230 V	No	2	3/12
GW D2 233	①	63 A	230 V	No	2	3/12
No. of poles: 2P						
GW D2 245	①	6 A	230 - 400 V	No	2	3/12
GW D2 246	①	10 A	230 - 400 V	No	2	3/12
GW D2 254	①	13 A	230 - 400 V	No	2	3/12
GW D2 247	①	16 A	230 - 400 V	No	2	3/12
GW D2 248	①	20 A	230 - 400 V	No	2	3/12
GW D2 249	①	25 A	230 - 400 V	No	2	3/12
GW D2 250	①	32 A	230 - 400 V	No	2	3/12
GW D2 251	①	40 A	230 - 400 V	No	2	3/12
GW D2 252	①	50 A	230 - 400 V	No	2	3/12
GW D2 253	①	63 A	230 - 400 V	No	2	3/12
No. of poles: 3P						
GW D2 265	①	6 A	230 - 400 V	No	3	2/8
GW D2 266	①	10 A	230 - 400 V	No	3	2/8
GW D2 274	①	13 A	230 - 400 V	No	3	2/8
GW D2 267	①	16 A	230 - 400 V	No	3	2/8
GW D2 268	①	20 A	230 - 400 V	No	3	2/8
GW D2 269	①	25 A	230 - 400 V	No	3	2/8
GW D2 270	①	32 A	230 - 400 V	No	3	2/8
GW D2 271	①	40 A	230 - 400 V	No	3	2/8
GW D2 272	①	50 A	230 - 400 V	No	3	2/8
GW D2 273	①	63 A	230 - 400 V	No	3	2/8
No. of poles: 4P						
GW D2 285	①	6 A	230 - 400 V	No	4	1/3
GW D2 286	①	10 A	230 - 400 V	No	4	1/3
GW D2 294	①	13 A	230 - 400 V	No	4	1/3
GW D2 287	①	16 A	230 - 400 V	No	4	1/3
GW D2 288	①	20 A	230 - 400 V	No	4	1/3
GW D2 289	①	25 A	230 - 400 V	No	4	1/3
GW D2 290	①	32 A	230 - 400 V	No	4	1/3
GW D2 291	①	40 A	230 - 400 V	No	4	1/3
GW D2 292	①	50 A	230 - 400 V	No	4	1/3
GW D2 293	①	63 A	230 - 400 V	No	4	1/3


NEWS

Availability: ① December 2025

MT - MINIATURE CIRCUIT BREAKERS

MT 45 - C curve - 4500 A (EN 60898) - 6 kA (EN 60947-2)









GW 92 149

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 105	6 A	230 - 400 V	1	6/24
GW 92 106	10 A	230 - 400 V	1	6/24
GW 92 107	13 A	230 - 400 V	1	6/24
GW 92 108	16 A	230 - 400 V	1	6/24
GW 92 109	20 A	230 - 400 V	1	6/24
GW 92 110	25 A	230 - 400 V	1	6/24
GW 92 111	32 A	230 - 400 V	1	6/24
GW 92 112	40 A	230 - 400 V	1	6/24
No. of poles: 1P+N				
GW 92 125	6 A	230 V	2	3/12
GW 92 126	10 A	230 V	2	3/12
GW 92 127	13 A	230 V	2	3/12
GW 92 128	16 A	230 V	2	3/12
GW 92 129	20 A	230 V	2	3/12
GW 92 130	25 A	230 V	2	3/12
GW 92 131	32 A	230 V	2	3/12
GW 92 132	40 A	230 V	2	3/12
No. of poles: 2P				
GW 92 145	6 A	230 - 400 V	2	3/12
GW 92 146	10 A	230 - 400 V	2	3/12
GW 92 147	13 A	230 - 400 V	2	3/12
GW 92 148	16 A	230 - 400 V	2	3/12
GW 92 149	20 A	230 - 400 V	2	3/12
GW 92 150	25 A	230 - 400 V	2	3/12
GW 92 151	32 A	230 - 400 V	2	3/12
GW 92 152	40 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 165	6 A	230 - 400 V	3	2/8
GW 92 166	10 A	230 - 400 V	3	2/8
GW 92 167	13 A	230 - 400 V	3	2/8
GW 92 168	16 A	230 - 400 V	3	2/8
GW 92 169	20 A	230 - 400 V	3	2/8
GW 92 170	25 A	230 - 400 V	3	2/8
GW 92 171	32 A	230 - 400 V	3	2/8
GW 92 172	40 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 185	6 A	230 - 400 V	4	1/3
GW 92 186	10 A	230 - 400 V	4	1/3
GW 92 187	13 A	230 - 400 V	4	1/3
GW 92 188	16 A	230 - 400 V	4	1/3
GW 92 189	20 A	230 - 400 V	4	1/3
GW 92 190	25 A	230 - 400 V	4	1/3
GW 92 191	32 A	230 - 400 V	4	1/3
GW 92 192	40 A	230 - 400 V	4	1/3

MT 45 - B curve - 4500 A (EN 60898) - 6 kA (EN 60947-2)







GW 92 371

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 305	6 A	230 - 400 V	1	6/24
GW 92 306	10 A	230 - 400 V	1	6/24
GW 92 307	13 A	230 - 400 V	1	6/24
GW 92 308	16 A	230 - 400 V	1	6/24
GW 92 309	20 A	230 - 400 V	1	6/24
GW 92 310	25 A	230 - 400 V	1	6/24
GW 92 311	32 A	230 - 400 V	1	6/24
GW 92 312	40 A	230 - 400 V	1	6/24
No. of poles: 1P+N				
GW 92 325	6 A	230 V	2	3/12
GW 92 326	10 A	230 V	2	3/12
GW 92 327	13 A	230 V	2	3/12
GW 92 328	16 A	230 V	2	3/12
GW 92 329	20 A	230 V	2	3/12
GW 92 330	25 A	230 V	2	3/12
GW 92 331	32 A	230 V	2	3/12
GW 92 332	40 A	230 V	2	3/12
No. of poles: 2P				
GW 92 345	6 A	230 - 400 V	2	3/12
GW 92 346	10 A	230 - 400 V	2	3/12
GW 92 347	13 A	230 - 400 V	2	3/12
GW 92 348	16 A	230 - 400 V	2	3/12
GW 92 349	20 A	230 - 400 V	2	3/12
GW 92 350	25 A	230 - 400 V	2	3/12
GW 92 351	32 A	230 - 400 V	2	3/12
GW 92 352	40 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 365	6 A	230 - 400 V	3	2/8
GW 92 366	10 A	230 - 400 V	3	2/8
GW 92 367	13 A	230 - 400 V	3	2/8
GW 92 368	16 A	230 - 400 V	3	2/8
GW 92 369	20 A	230 - 400 V	3	2/8
GW 92 370	25 A	230 - 400 V	3	2/8
GW 92 371	32 A	230 - 400 V	3	2/8
GW 92 372	40 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 385	6 A	230 - 400 V	4	1/3
GW 92 386	10 A	230 - 400 V	4	1/3
GW 92 387	13 A	230 - 400 V	4	1/3
GW 92 388	16 A	230 - 400 V	4	1/3
GW 92 389	20 A	230 - 400 V	4	1/3
GW 92 390	25 A	230 - 400 V	4	1/3
GW 92 391	32 A	230 - 400 V	4	1/3
GW 92 392	40 A	230 - 400 V	4	1/3

MT 60 - C curve - 6000 A (EN 60898) - 10 kA (EN 60947-2)










GW 92 048


Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 001	1 A	230 - 400 V	1	6/24
GW 92 002	2 A	230 - 400 V	1	6/24
GW 92 003	3 A	230 - 400 V	1	6/24
GW 92 004	4 A	230 - 400 V	1	6/24
GW 92 005	6 A	230 - 400 V	1	6/24
GW 92 006	10 A	230 - 400 V	1	6/24
GW 92 014	13 A	230 - 400 V	1	6/24
GW 92 007	16 A	230 - 400 V	1	6/24
GW 92 008	20 A	230 - 400 V	1	6/24
GW 92 009	25 A	230 - 400 V	1	6/24
GW 92 010	32 A	230 - 400 V	1	6/24
GW 92 011	40 A	230 - 400 V	1	6/24
GW 92 012	50 A	230 - 400 V	1	6/24
GW 92 013	63 A	230 - 400 V	1	6/24
No. of poles: 1P+N				
GW 92 021	1 A	230 V	2	3/12
GW 92 022	2 A	230 V	2	3/12
GW 92 023	3 A	230 V	2	3/12
GW 92 024	4 A	230 V	2	3/12
GW 92 025	6 A	230 V	2	3/12
GW 92 026	10 A	230 V	2	3/12
GW 92 034	13 A	230 V	2	3/12
GW 92 027	16 A	230 V	2	3/12
GW 92 028	20 A	230 V	2	3/12
GW 92 029	25 A	230 V	2	3/12
GW 92 030	32 A	230 V	2	3/12
GW 92 031	40 A	230 V	2	3/12
GW 92 032	50 A	230 V	2	3/12
GW 92 033	63 A	230 V	2	3/12
No. of poles: 2P				
GW 92 041	1 A	230 - 400 V	2	3/12
GW 92 042	2 A	230 - 400 V	2	3/12
GW 92 043	3 A	230 - 400 V	2	3/12
GW 92 044	4 A	230 - 400 V	2	3/12
GW 92 045	6 A	230 - 400 V	2	3/12
GW 92 046	10 A	230 - 400 V	2	3/12
GW 92 054	13 A	230 - 400 V	2	3/12
GW 92 047	16 A	230 - 400 V	2	3/12
GW 92 048	20 A	230 - 400 V	2	3/12
GW 92 049	25 A	230 - 400 V	2	3/12
GW 92 050	32 A	230 - 400 V	2	3/12
GW 92 051	40 A	230 - 400 V	2	3/12
GW 92 052	50 A	230 - 400 V	2	3/12
GW 92 053	63 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 061	1 A	230 - 400 V	3	2/8
GW 92 062	2 A	230 - 400 V	3	2/8
GW 92 063	3 A	230 - 400 V	3	2/8
GW 92 064	4 A	230 - 400 V	3	2/8
GW 92 065	6 A	230 - 400 V	3	2/8
GW 92 066	10 A	230 - 400 V	3	2/8
GW 92 074	13 A	230 - 400 V	3	2/8
GW 92 067	16 A	230 - 400 V	3	2/8
GW 92 068	20 A	230 - 400 V	3	2/8
GW 92 069	25 A	230 - 400 V	3	2/8
GW 92 070	32 A	230 - 400 V	3	2/8
GW 92 071	40 A	230 - 400 V	3	2/8
GW 92 072	50 A	230 - 400 V	3	2/8
GW 92 073	63 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 081	1 A	230 - 400 V	4	1/3
GW 92 082	2 A	230 - 400 V	4	1/3
GW 92 083	3 A	230 - 400 V	4	1/3
GW 92 084	4 A	230 - 400 V	4	1/3
GW 92 085	6 A	230 - 400 V	4	1/3
GW 92 086	10 A	230 - 400 V	4	1/3
GW 92 094	13 A	230 - 400 V	4	1/3
GW 92 087	16 A	230 - 400 V	4	1/3
GW 92 088	20 A	230 - 400 V	4	1/3
GW 92 089	25 A	230 - 400 V	4	1/3
GW 92 090	32 A	230 - 400 V	4	1/3
GW 92 091	40 A	230 - 400 V	4	1/3
GW 92 092	50 A	230 - 400 V	4	1/3
GW 92 093	63 A	230 - 400 V	4	1/3

MT 60 - B curve - 6000 A (EN 60898) - 10 kA (EN 60947-2)









GW 92 292

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 205	6 A	230 - 400 V	1	6/24
GW 92 206	10 A	230 - 400 V	1	6/24
GW 92 214	13 A	230 - 400 V	1	6/24
GW 92 207	16 A	230 - 400 V	1	6/24
GW 92 208	20 A	230 - 400 V	1	6/24
GW 92 209	25 A	230 - 400 V	1	6/24
GW 92 210	32 A	230 - 400 V	1	6/24
GW 92 211	40 A	230 - 400 V	1	6/24
GW 92 212	50 A	230 - 400 V	1	6/24
GW 92 213	63 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 245	6 A	230 - 400 V	2	3/12
GW 92 246	10 A	230 - 400 V	2	3/12
GW 92 254	13 A	230 - 400 V	2	3/12
GW 92 247	16 A	230 - 400 V	2	3/12
GW 92 248	20 A	230 - 400 V	2	3/12
GW 92 249	25 A	230 - 400 V	2	3/12
GW 92 250	32 A	230 - 400 V	2	3/12
GW 92 251	40 A	230 - 400 V	2	3/12
GW 92 252	50 A	230 - 400 V	2	3/12
GW 92 253	63 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 265	6 A	230 - 400 V	3	2/8
GW 92 266	10 A	230 - 400 V	3	2/8
GW 92 274	13 A	230 - 400 V	3	2/8
GW 92 267	16 A	230 - 400 V	3	2/8
GW 92 268	20 A	230 - 400 V	3	2/8
GW 92 269	25 A	230 - 400 V	3	2/8
GW 92 270	32 A	230 - 400 V	3	2/8
GW 92 271	40 A	230 - 400 V	3	2/8
GW 92 272	50 A	230 - 400 V	3	2/8
GW 92 273	63 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 285	6 A	230 - 400 V	4	1/3
GW 92 286	10 A	230 - 400 V	4	1/3
GW 92 294	13 A	230 - 400 V	4	1/3
GW 92 287	16 A	230 - 400 V	4	1/3
GW 92 288	20 A	230 - 400 V	4	1/3
GW 92 289	25 A	230 - 400 V	4	1/3
GW 92 290	32 A	230 - 400 V	4	1/3
GW 92 291	40 A	230 - 400 V	4	1/3
GW 92 292	50 A	230 - 400 V	4	1/3
GW 92 293	63 A	230 - 400 V	4	1/3

MT 60 - D curve - 6000 A (EN 60898) - 10 kA (EN 60947-2)









GW 92 470

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 405	6 A	230 - 400 V	1	6/24
GW 92 406	10 A	230 - 400 V	1	6/24
GW 92 414	13 A	230 - 400 V	1	6/24
GW 92 407	16 A	230 - 400 V	1	6/24
GW 92 408	20 A	230 - 400 V	1	6/24
GW 92 409	25 A	230 - 400 V	1	6/24
GW 92 410	32 A	230 - 400 V	1	6/24
GW 92 411	40 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 445	6 A	230 - 400 V	2	3/12
GW 92 446	10 A	230 - 400 V	2	3/12
GW 92 454	13 A	230 - 400 V	2	3/12
GW 92 447	16 A	230 - 400 V	2	3/12
GW 92 448	20 A	230 - 400 V	2	3/12
GW 92 449	25 A	230 - 400 V	2	3/12
GW 92 450	32 A	230 - 400 V	2	3/12
GW 92 451	40 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 465	6 A	230 - 400 V	3	2/8
GW 92 466	10 A	230 - 400 V	3	2/8
GW 92 474	13 A	230 - 400 V	3	2/8
GW 92 467	16 A	230 - 400 V	3	2/8
GW 92 468	20 A	230 - 400 V	3	2/8
GW 92 469	25 A	230 - 400 V	3	2/8
GW 92 470	32 A	230 - 400 V	3	2/8
GW 92 471	40 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 485	6 A	230 - 400 V	4	1/3
GW 92 486	10 A	230 - 400 V	4	1/3
GW 92 494	13 A	230 - 400 V	4	1/3
GW 92 487	16 A	230 - 400 V	4	1/3
GW 92 488	20 A	230 - 400 V	4	1/3
GW 92 489	25 A	230 - 400 V	4	1/3
GW 92 490	32 A	230 - 400 V	4	1/3
GW 92 491	40 A	230 - 400 V	4	1/3

90 MCB

MT 100 - C curve - 10000 A (EN 60898) - Up to 15 kA (EN 60947-2)

BREAKING CAPACITY 1P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	15 kA
In=32÷63 A	10000 A	12,5 kA

BREAKING CAPACITY 2P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	30 kA
In=32÷63 A	10000 A	25 kA

BREAKING CAPACITY 2P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	20 kA
In=32÷63 A	10000 A	15 kA

BREAKING CAPACITY 3-4P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	25 kA
In=32÷63 A	10000 A	20 kA

BREAKING CAPACITY 3-4P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	15 kA
In=32÷63 A	10000 A	12,5 kA



GW 92 692

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 605	6 A	230 - 400 V	1	6/24
GW 92 606	10 A	230 - 400 V	1	6/24
GW 92 614	13 A	230 - 400 V	1	6/24
GW 92 607	16 A	230 - 400 V	1	6/24
GW 92 608	20 A	230 - 400 V	1	6/24
GW 92 609	25 A	230 - 400 V	1	6/24
GW 92 610	32 A	230 - 400 V	1	6/24
GW 92 611	40 A	230 - 400 V	1	6/24
GW 92 612	50 A	230 - 400 V	1	6/24
GW 92 613	63 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 645	6 A	230 - 400 V	2	3/12
GW 92 646	10 A	230 - 400 V	2	3/12
GW 92 654	13 A	230 - 400 V	2	3/12
GW 92 647	16 A	230 - 400 V	2	3/12
GW 92 648	20 A	230 - 400 V	2	3/12
GW 92 649	25 A	230 - 400 V	2	3/12
GW 92 650	32 A	230 - 400 V	2	3/12
GW 92 651	40 A	230 - 400 V	2	3/12
GW 92 652	50 A	230 - 400 V	2	3/12
GW 92 653	63 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 665	6 A	230 - 400 V	3	2/8
GW 92 666	10 A	230 - 400 V	3	2/8
GW 92 674	13 A	230 - 400 V	3	2/8
GW 92 667	16 A	230 - 400 V	3	2/8
GW 92 668	20 A	230 - 400 V	3	2/8
GW 92 669	25 A	230 - 400 V	3	2/8
GW 92 670	32 A	230 - 400 V	3	2/8
GW 92 671	40 A	230 - 400 V	3	2/8
GW 92 672	50 A	230 - 400 V	3	2/8
GW 92 673	63 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 685	6 A	230 - 400 V	4	1/3
GW 92 686	10 A	230 - 400 V	4	1/3
GW 92 694	13 A	230 - 400 V	4	1/3
GW 92 687	16 A	230 - 400 V	4	1/3
GW 92 688	20 A	230 - 400 V	4	1/3
GW 92 689	25 A	230 - 400 V	4	1/3
GW 92 690	32 A	230 - 400 V	4	1/3
GW 92 691	40 A	230 - 400 V	4	1/3
GW 92 692	50 A	230 - 400 V	4	1/3
GW 92 693	63 A	230 - 400 V	4	1/3

MT 100 - B curve - 10000 A (EN 60898) - Up to 15 kA (EN 60947-2)

BREAKING CAPACITY 1P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	15 kA
In=32÷63 A	10000 A	12,5 kA

BREAKING CAPACITY 2P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	30 kA
In=32÷63 A	10000 A	25 kA

BREAKING CAPACITY 2P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	20 kA
In=32÷63 A	10000 A	15 kA

BREAKING CAPACITY 3-4P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	25 kA
In=32÷63 A	10000 A	20 kA

BREAKING CAPACITY 3-4P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷25 A	10000 A	15 kA
In=32÷63 A	10000 A	12,5 kA





GW 92 549


Miniature circuit breakers


Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 505	6 A	230 - 400 V	1	6/24
GW 92 506	10 A	230 - 400 V	1	6/24
GW 92 507	13 A	230 - 400 V	1	6/24
GW 92 508	16 A	230 - 400 V	1	6/24
GW 92 509	20 A	230 - 400 V	1	6/24
GW 92 510	25 A	230 - 400 V	1	6/24
GW 92 511	32 A	230 - 400 V	1	6/24
GW 92 512	40 A	230 - 400 V	1	6/24
GW 92 513	50 A	230 - 400 V	1	6/24
GW 92 514	63 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 545	6 A	230 - 400 V	2	3/12
GW 92 546	10 A	230 - 400 V	2	3/12
GW 92 547	13 A	230 - 400 V	2	3/12
GW 92 548	16 A	230 - 400 V	2	3/12
GW 92 549	20 A	230 - 400 V	2	3/12
GW 92 550	25 A	230 - 400 V	2	3/12
GW 92 551	32 A	230 - 400 V	2	3/12
GW 92 552	40 A	230 - 400 V	2	3/12
GW 92 553	50 A	230 - 400 V	2	3/12
GW 92 554	63 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 565	6 A	230 - 400 V	3	2/8
GW 92 566	10 A	230 - 400 V	3	2/8
GW 92 567	13 A	230 - 400 V	3	2/8
GW 92 568	16 A	230 - 400 V	3	2/8
GW 92 569	20 A	230 - 400 V	3	2/8
GW 92 570	25 A	230 - 400 V	3	2/8
GW 92 571	32 A	230 - 400 V	3	2/8
GW 92 572	40 A	230 - 400 V	3	2/8
GW 92 573	50 A	230 - 400 V	3	2/8
GW 92 574	63 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 585	6 A	230 - 400 V	4	1/3
GW 92 586	10 A	230 - 400 V	4	1/3
GW 92 587	13 A	230 - 400 V	4	1/3
GW 92 588	16 A	230 - 400 V	4	1/3
GW 92 589	20 A	230 - 400 V	4	1/3
GW 92 590	25 A	230 - 400 V	4	1/3
GW 92 591	32 A	230 - 400 V	4	1/3
GW 92 592	40 A	230 - 400 V	4	1/3
GW 92 593	50 A	230 - 400 V	4	1/3
GW 92 594	63 A	230 - 400 V	4	1/3


MT 100 - D curve - 10000 A (EN 60898) - Up to 15 kA (EN 60947-2)













GW 92 770

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 701	1 A	230 - 400 V	1	6/24
GW 92 702	2 A	230 - 400 V	1	6/24
GW 92 703	3 A	230 - 400 V	1	6/24
GW 92 704	4 A	230 - 400 V	1	6/24
GW 92 705	6 A	230 - 400 V	1	6/24
GW 92 706	10 A	230 - 400 V	1	6/24
GW 92 714	13 A	230 - 400 V	1	6/24
GW 92 707	16 A	230 - 400 V	1	6/24
GW 92 708	20 A	230 - 400 V	1	6/24
GW 92 709	25 A	230 - 400 V	1	6/24
GW 92 710	32 A	230 - 400 V	1	6/24
GW 92 711	40 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 741	1 A	230 - 400 V	2	3/12
GW 92 742	2 A	230 - 400 V	2	3/12
GW 92 743	3 A	230 - 400 V	2	3/12
GW 92 744	4 A	230 - 400 V	2	3/12
GW 92 745	6 A	230 - 400 V	2	3/12
GW 92 746	10 A	230 - 400 V	2	3/12
GW 92 754	13 A	230 - 400 V	2	3/12
GW 92 747	16 A	230 - 400 V	2	3/12
GW 92 748	20 A	230 - 400 V	2	3/12
GW 92 749	25 A	230 - 400 V	2	3/12
GW 92 750	32 A	230 - 400 V	2	3/12
GW 92 751	40 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 761	1 A	230 - 400 V	3	2/8
GW 92 762	2 A	230 - 400 V	3	2/8
GW 92 763	3 A	230 - 400 V	3	2/8
GW 92 764	4 A	230 - 400 V	3	2/8
GW 92 765	6 A	230 - 400 V	3	2/8
GW 92 766	10 A	230 - 400 V	3	2/8
GW 92 774	13 A	230 - 400 V	3	2/8
GW 92 767	16 A	230 - 400 V	3	2/8
GW 92 768	20 A	230 - 400 V	3	2/8
GW 92 769	25 A	230 - 400 V	3	2/8
GW 92 770	32 A	230 - 400 V	3	2/8
GW 92 771	40 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 781	1 A	230 - 400 V	4	1/3
GW 92 782	2 A	230 - 400 V	4	1/3
GW 92 783	3 A	230 - 400 V	4	1/3
GW 92 784	4 A	230 - 400 V	4	1/3
GW 92 785	6 A	230 - 400 V	4	1/3
GW 92 786	10 A	230 - 400 V	4	1/3
GW 92 794	13 A	230 - 400 V	4	1/3
GW 92 787	16 A	230 - 400 V	4	1/3
GW 92 788	20 A	230 - 400 V	4	1/3
GW 92 789	25 A	230 - 400 V	4	1/3
GW 92 790	32 A	230 - 400 V	4	1/3
GW 92 791	40 A	230 - 400 V	4	1/3

MT 250 - C curve - 25000 A (EN 60898) - Up to 25 kA (EN 60947-2)

BREAKING CAPACITY 1P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷20 A	25000 A	25 kA
In=25 A	20000 A	20 kA
In=32÷40 A	15000 A	15 kA
In=50÷63 A	12500 A	15 kA

BREAKING CAPACITY 2P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷20 A	25000 A	50 kA
In=25 A	25000 A	40 kA
In=32÷40 A	25000 A	30 kA
In=50÷63 A	25000 A	25 kA

SCHALTVERMÖGEN 2P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷20 A	25000 A	30 kA
In=25 A	25000 A	25 kA
In=32÷40 A	20000 A	20 kA
In=50÷63 A	15000 A	15 kA

BREAKING CAPACITY 3-4P		
230V	EN60898 Icn	EN60947-2 Icu
In=6÷20 A	25000 A	40 kA
In=25 A	25000 A	30 kA
In=32÷40 A	25000 A	25 kA
In=50÷63 A	20000 A	20 kA

BREAKING CAPACITY 3-4P		
400V	EN60898 Icn	EN60947-2 Icu
In=6÷20 A	25000 A	25 kA
In=25 A	20000 A	20 kA
In=32÷40 A	15000 A	15 kA
In=50÷63 A	12500 A	15 kA



GW 92 892

Miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 92 805	6 A	230 - 400 V	1	6/24
GW 92 806	10 A	230 - 400 V	1	6/24
GW 92 807	16 A	230 - 400 V	1	6/24
GW 92 808	20 A	230 - 400 V	1	6/24
GW 92 809	25 A	230 - 400 V	1	6/24
GW 92 810	32 A	230 - 400 V	1	6/24
GW 92 811	40 A	230 - 400 V	1	6/24
GW 92 812	50 A	230 - 400 V	1	6/24
GW 92 813	63 A	230 - 400 V	1	6/24
No. of poles: 2P				
GW 92 845	6 A	230 - 400 V	2	3/12
GW 92 846	10 A	230 - 400 V	2	3/12
GW 92 847	16 A	230 - 400 V	2	3/12
GW 92 848	20 A	230 - 400 V	2	3/12
GW 92 849	25 A	230 - 400 V	2	3/12
GW 92 850	32 A	230 - 400 V	2	3/12
GW 92 851	40 A	230 - 400 V	2	3/12
GW 92 852	50 A	230 - 400 V	2	3/12
GW 92 853	63 A	230 - 400 V	2	3/12
No. of poles: 3P				
GW 92 865	6 A	230 - 400 V	3	2/8
GW 92 866	10 A	230 - 400 V	3	2/8
GW 92 867	16 A	230 - 400 V	3	2/8
GW 92 868	20 A	230 - 400 V	3	2/8
GW 92 869	25 A	230 - 400 V	3	2/8
GW 92 870	32 A	230 - 400 V	3	2/8
GW 92 871	40 A	230 - 400 V	3	2/8
GW 92 872	50 A	230 - 400 V	3	2/8
GW 92 873	63 A	230 - 400 V	3	2/8
No. of poles: 4P				
GW 92 885	6 A	230 - 400 V	4	1/3
GW 92 886	10 A	230 - 400 V	4	1/3
GW 92 887	16 A	230 - 400 V	4	1/3
GW 92 888	20 A	230 - 400 V	4	1/3
GW 92 889	25 A	230 - 400 V	4	1/3
GW 92 890	32 A	230 - 400 V	4	1/3
GW 92 891	40 A	230 - 400 V	4	1/3
GW 92 892	50 A	230 - 400 V	4	1/3
GW 92 893	63 A	230 - 400 V	4	1/3

MTHP - HIGH PERFORMANCE MINIATURE CIRCUIT BREAKERS

MTHP 160 - C curve - 10000 A (EN 60898) - 16 kA (EN 60947-2)











GW 93 349

High performance miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 93 307	80 A	230 - 400 V	1.5	1/12
GW 93 308	100 A	230 - 400 V	1.5	1/12
GW 93 309	125 A	230 - 400 V	1.5	1/12
No. of poles: 2P				
GW 93 327	80 A	230 - 400 V	3	1/4
GW 93 328	100 A	230 - 400 V	3	1/4
GW 93 329	125 A	230 - 400 V	3	1/4
No. of poles: 3P				
GW 93 337	80 A	230 - 400 V	4.5	1/4
GW 93 338	100 A	230 - 400 V	4.5	1/4
GW 93 339	125 A	230 - 400 V	4.5	1/4
No. of poles: 4P				
GW 93 347	80 A	230 - 400 V	6	1/4
GW 93 348	100 A	230 - 400 V	6	1/4
GW 93 349	125 A	230 - 400 V	6	1/4

ACCESSORIES SUPPLIED: kit for cable terminals wiring and poles separators.

MTHP 160 - D curve - 10000 A (EN 60898) - 16 kA (EN 60947-2)











GW 93 388

High performance miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 93 355	50 A	230 - 400 V	1.5	1/12
GW 93 356	63 A	230 - 400 V	1.5	1/12
GW 93 357	80 A	230 - 400 V	1.5	1/12
GW 93 358	100 A	230 - 400 V	1.5	1/12
No. of poles: 2P				
GW 93 375	50 A	230 - 400 V	3	1/4
GW 93 376	63 A	230 - 400 V	3	1/4
GW 93 377	80 A	230 - 400 V	3	1/4
GW 93 378	100 A	230 - 400 V	3	1/4
No. of poles: 3P				
GW 93 385	50 A	230 - 400 V	4.5	1/4
GW 93 386	63 A	230 - 400 V	4.5	1/4
GW 93 387	80 A	230 - 400 V	4.5	1/4
GW 93 388	100 A	230 - 400 V	4.5	1/4
No. of poles: 4P				
GW 93 395	50 A	230 - 400 V	6	1/4
GW 93 396	63 A	230 - 400 V	6	1/4
GW 93 397	80 A	230 - 400 V	6	1/4
GW 93 398	100 A	230 - 400 V	6	1/4

ACCESSORIES SUPPLIED: kit for cable terminals wiring and poles separators.

MTHP 250 - C curve - 25000 A (EN 60898) - 25 kA (EN 60947-2)













GW 93 222

High performance miniature circuit breakers

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P				
GW 93 201	20 A	230 - 400 V	1.5	1/12
GW 93 202	25 A	230 - 400 V	1.5	1/12
GW 93 203	32 A	230 - 400 V	1.5	1/12
GW 93 204	40 A	230 - 400 V	1.5	1/12
GW 93 205	50 A	230 - 400 V	1.5	1/12
GW 93 206	63 A	230 - 400 V	1.5	1/12
No. of poles: 2P				
GW 93 221	20 A	230 - 400 V	3	1/4
GW 93 222	25 A	230 - 400 V	3	1/4
GW 93 223	32 A	230 - 400 V	3	1/4
GW 93 224	40 A	230 - 400 V	3	1/4
GW 93 225	50 A	230 - 400 V	3	1/4
GW 93 226	63 A	230 - 400 V	3	1/4
No. of poles: 3P				
GW 93 231	20 A	230 - 400 V	4.5	1/4
GW 93 232	25 A	230 - 400 V	4.5	1/4
GW 93 233	32 A	230 - 400 V	4.5	1/4
GW 93 234	40 A	230 - 400 V	4.5	1/4
GW 93 235	50 A	230 - 400 V	4.5	1/4
GW 93 236	63 A	230 - 400 V	4.5	1/4
No. of poles: 4P				
GW 93 241	20 A	230 - 400 V	6	1/4
GW 93 242	25 A	230 - 400 V	6	1/4
GW 93 243	32 A	230 - 400 V	6	1/4
GW 93 244	40 A	230 - 400 V	6	1/4
GW 93 245	50 A	230 - 400 V	6	1/4
GW 93 246	63 A	230 - 400 V	6	1/4

ACCESSORIES SUPPLIED: kit for cable terminals wiring and poles separators.

MINIATURE CIRCUIT BREAKERS WITH ELECTRICAL ARC FAULT DETECTION AFDD

AFDD - C curve - 6000 A (EN 60898) - 7.5 kA (EN 60947-2)







GW 91 928

Miniature circuit breakers AFDD

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 91 925	6 A	230 V	No	2	1/6
GW 91 926	10 A	230 V	No	2	1/6
GW 91 927	13 A	230 V	No	2	1/6
GW 91 928	16 A	230 V	No	2	1/6
GW 91 929	20 A	230 V	No	2	1/6

APPLICATIONS: arc fault protection, short circuit and overload protection.
CHARACTERISTICS: LED for monitoring the operating status of the AFDD.
Test button to check the correct functioning of the AFDD device.
Contact position signalling window to identify contact status (red: closed; green: open).

AFDD - B curve - 6000 A (EN 60898) - 7.5 kA (EN 60947-2)







GW 91 906

Miniature circuit breakers AFDD

Code	Rated current	Rated voltage	Auxiliaries compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 91 906	10 A	230 V	No	2	1/6
GW 91 907	13 A	230 V	No	2	1/6
GW 91 908	16 A	230 V	No	2	1/6
GW 91 909	20 A	230 V	No	2	1/6

APPLICATIONS: device for protection against faults caused by electrical arcing and overcurrents.
CHARACTERISTICS: LED for monitoring the operating status of the AFDD device.
Test button to verify the correct functioning of the AFDD device.
Contact position indicator for identifying the status of the contacts (red: closed; green: open).

NEWS




90 MCB



Scan the QR Code and find out all the technical informations.

REDUCED FOOTPRINT



The compact MCCB protect 2 poles per module, reducing space by up to 50%. This also allows installation of smaller enclosures, for savings on costs.

MAXIMUM SECURITY



To ensure the most secure fastening and protection from possible contact with live parts, the terminals are equipped with a protective, sliding insulating insert. In addition, the double DIN hook provides a more stable fastening and facilitates maintenance operations.

SIMPLIFIED ACCESSORY MANAGEMENT



The 90 MCB range of circuit breakers integrate seamlessly with the 90 range of electrical auxiliaries, providing simplified and streamlined accessory management.

Circuit breakers for residual current protection







90 RCD

Modular circuit breakers for residual current protection

p. 467

Residual current circuit breakers with overcurrent protection and add-on residual current devices

Icn [A] (EN 61009-1)	Curve	Type	In [A]	RCBO							
				IΔn = 30mA				IΔn = 300mA			
											
				1P+N	2P	3P	4P	1P+N	2P	3P	4P
				2 mod.	2 mod.	3 mod.	4 mod.	2 mod.	2 mod.	3 mod.	4 mod.
				MDC 45							
4500	C	AC	6	GW 94 005	GW 94 025	GW 94 045	GW 94 065	GW 94 015	GW 94 035	GW 94 055	GW 94 075
			10	GW 94 006	GW 94 026	GW 94 046	GW 94 066	GW 94 016	GW 94 036	GW 94 056	GW 94 076
			13	GW 94 011	GW 94 031	GW 94 051	GW 94 071	-	-	-	-
			16	GW 94 007	GW 94 027	GW 94 047	GW 94 067	GW 94 017	GW 94 037	GW 94 057	GW 94 077
			20	GW 94 008	GW 94 028	GW 94 048	GW 94 068	GW 94 018	GW 94 038	GW 94 058	GW 94 078
			25	GW 94 009	GW 94 029	GW 94 049	GW 94 069	GW 94 019	GW 94 039	GW 94 059	GW 94 079
			32	GW 94 010	GW 94 030	GW 94 050	GW 94 070	GW 94 020	GW 94 040	GW 94 060	GW 94 080
		A	6	GW 94 205	GW 94 225	GW 94 245	GW 94 265	GW 94 215	GW 94 235	GW 94 255	GW 94 275
			10	GW 94 206	GW 94 226	GW 94 246	GW 94 266	GW 94 216	GW 94 236	GW 94 256	GW 94 276
			13	GW 94 211	GW 94 231	GW 94 251	GW 94 271	-	-	-	-
			16	GW 94 207	GW 94 227	GW 94 247	GW 94 267	GW 94 217	GW 94 237	GW 94 257	GW 94 277
			20	GW 94 208	GW 94 228	GW 94 248	GW 94 268	GW 94 218	GW 94 238	GW 94 258	GW 94 278
			25	GW 94 209	GW 94 229	GW 94 249	GW 94 269	GW 94 219	GW 94 239	GW 94 259	GW 94 279
			32	GW 94 210	GW 94 230	GW 94 250	GW 94 270	GW 94 220	GW 94 240	GW 94 260	GW 94 280
				MDC 60							
6000	C	AC	6	GW 94 105	GW 94 125	GW 94 145	GW 94 165	GW 94 115	GW 94 135	GW 94 155	GW 94 175
			10	GW 94 106	GW 94 126	GW 94 146	GW 94 166	GW 94 116	GW 94 136	GW 94 156	GW 94 176
			13	GW 94 111	GW 94 131	GW 94 151	GW 94 171	-	-	-	-
			16	GW 94 107	GW 94 127	GW 94 147	GW 94 167	GW 94 117	GW 94 137	GW 94 157	GW 94 177
			20	GW 94 108	GW 94 128	GW 94 148	GW 94 168	GW 94 118	GW 94 138	GW 94 158	GW 94 178
			25	GW 94 109	GW 94 129	GW 94 149	GW 94 169	GW 94 119	GW 94 139	GW 94 159	GW 94 179
			32	GW 94 110	GW 94 130	GW 94 150	GW 94 170	GW 94 120	GW 94 140	GW 94 160	GW 94 180
		A	6	GW 94 305	GW 94 325	GW 94 345	GW 94 365	GW 94 315	GW 94 335	GW 94 355	GW 94 375
			10	GW 94 306	GW 94 326	GW 94 346	GW 94 366	GW 94 316	GW 94 336	GW 94 356	GW 94 376
			13	GW 94 311	GW 94 331	GW 94 351	GW 94 371	-	-	-	-
			16	GW 94 307	GW 94 327	GW 94 347	GW 94 367	GW 94 317	GW 94 337	GW 94 357	GW 94 377
			20	GW 94 308	GW 94 328	GW 94 348	GW 94 368	GW 94 318	GW 94 338	GW 94 358	GW 94 378
			25	GW 94 309	GW 94 329	GW 94 349	GW 94 369	GW 94 319	GW 94 339	GW 94 359	GW 94 379
			32	GW 94 310	GW 94 330	GW 94 350	GW 94 370	GW 94 320	GW 94 340	GW 94 360	GW 94 380
		A[IR]	6	-	GW 95 805	-	GW 95 815	-	-	-	-
			10	-	GW 95 806	-	GW 95 816	-	-	-	-
			13	-	GW 95 811	-	GW 95 821	-	-	-	-
			16	-	GW 95 807	-	GW 95 817	-	-	-	-
			20	-	GW 95 808	-	GW 95 818	-	-	-	-
			25	-	GW 95 809	-	GW 95 819	-	-	-	-
			32	-	GW 95 810	-	GW 95 820	-	-	-	-
		A[S]	16	-	-	-	-	-	GW 95 847	-	GW 95 857
			20	-	-	-	-	-	GW 95 848	-	GW 95 858
			25	-	-	-	-	-	GW 95 849	-	GW 95 859
			32	-	-	-	-	-	GW 95 850	-	GW 95 860
		F	6	-	GW 95 935	-	-	-	-	-	-
			10	-	GW 95 936	-	-	-	-	-	-
			13	-	GW 95 941	-	-	-	-	-	-
			16	-	GW 95 937	-	-	-	-	-	-
			20	-	GW 95 938	-	-	-	-	-	-
			25	-	GW 95 939	-	-	-	-	-	-
			32	-	GW 95 940	-	-	-	-	-	-
	B	A	6	GW 95 105	GW 95 125	GW 95 145	GW 95 165	GW 95 115	GW 95 135	GW 95 155	GW 95 175
			10	GW 95 106	GW 95 126	GW 95 146	GW 95 166	GW 95 116	GW 95 136	GW 95 156	GW 95 176
			13	GW 95 111	GW 95 131	GW 95 151	GW 95 171	-	-	-	-
			16	GW 95 107	GW 95 127	GW 95 147	GW 95 167	GW 95 117	GW 95 137	GW 95 157	GW 95 177
			20	GW 95 108	GW 95 128	GW 95 148	GW 95 168	GW 95 118	GW 95 138	GW 95 158	GW 95 178
			25	GW 95 109	GW 95 129	GW 95 149	GW 95 169	GW 95 119	GW 95 139	GW 95 159	GW 95 179
			32	GW 95 110	GW 95 130	GW 95 150	GW 95 170	GW 95 120	GW 95 140	GW 95 160	GW 95 180
		F	6	-	GW 95 975	-	-	-	-	-	-
			10	-	GW 95 976	-	-	-	-	-	-
			13	-	GW 95 981	-	-	-	-	-	-
			16	-	GW 95 977	-	-	-	-	-	-
			20	-	GW 95 978	-	-	-	-	-	-
			25	-	GW 95 979	-	-	-	-	-	-
			32	-	GW 95 980	-	-	-	-	-	-

RCBO

Icn [A] (EN 61009-1)	Curve	Type	In [A]	IΔn = 30mA 2P 2 mod.		IΔn = 30mA 3P 3 mod.	IΔn = 100mA 2P 2 mod.	IΔn = 300mA 2P 2 mod.
								
				MDC 100				
10000	C	AC	6	GW 95 025	GW 95 025 MA*	-	-	GW 95 035
			10	GW 95 026	GW 95 026 MA*	-	-	GW 95 036
			13	GW 95 031	GW 95 031 MA*	-	-	-
			16	GW 95 027	GW 95 027 MA*	-	-	GW 95 037
			20	GW 95 028	GW 95 028 MA*	-	-	GW 95 038
			25	GW 95 029	GW 95 029 MA*	-	-	GW 95 039
			32	GW 95 030	GW 95 030 MA*	-	-	GW 95 040
		A	6	GW 95 225	GW 95 225 MA*	GW 95 245**	GW 95 785	GW 95 235
			10	GW 95 226	GW 95 226 MA*	GW 95 246**	GW 95 786	GW 95 236
			13	GW 95 231	GW 95 231 MA*	-	GW 95 791	-
			16	GW 95 227	GW 95 227 MA*	GW 95 247**	GW 95 787	GW 95 237
			20	GW 95 228	GW 95 228 MA*	GW 95 248**	GW 95 788	GW 95 238
			25	GW 95 229	GW 95 229 MA*	GW 95 249**	GW 95 789	GW 95 239
			32	GW 95 230	GW 95 230 MA*	GW 95 250**	GW 95 790	GW 95 240
		A[IR]	6	GW 95 825		-	-	-
			10	GW 95 826		-	-	-
			13	GW 95 831		-	-	-
			16	GW 95 827		-	-	-
			20	GW 95 828		-	-	-
			25	GW 95 829		-	-	-
			32	GW 95 830		-	-	-
		F	6	GW 95 955		-	-	-
			10	GW 95 956		-	-	-
			13	GW 95 961		-	-	-
			16	GW 95 957		-	-	-
			20	GW 95 958		-	-	-
			25	GW 95 959		-	-	-
			32	GW 95 960		-	-	-
	B	A	6	GW 95 325		-	GW 95 795	GW 95 335
			10	GW 95 326		-	GW 95 796	GW 95 336
			13	GW 95 331		-	GW 95 801	-
			16	GW 95 327		-	GW 95 797	GW 95 337
			20	GW 95 328		-	GW 95 798	GW 95 338
			25	GW 95 329		-	GW 95 799	GW 95 339
			32	GW 95 330		-	GW 95 800	GW 95 340
		A[IR]	6	GW 95 835		-	-	-
			10	GW 95 836		-	-	-
			13	GW 95 841		-	-	-
			16	GW 95 837		-	-	-
			20	GW 95 838		-	-	-
			25	GW 95 839		-	-	-
			32	GW 95 840		-	-	-
		F	6	GW 95 965		-	-	-
			10	GW 95 966		-	-	-
			13	GW 95 971		-	-	-
			16	GW 95 967		-	-	-
			20	GW 95 968		-	-	-
			25	GW 95 969		-	-	-
			32	GW 95 970		-	-	-

* Rated operating voltage equal to 110V ac ** Rated operating voltage equal to 230V ac

ADD-ON RCD

Type	IΔn [mA]	BD 2P 2 mod. In≤25 A	BD 2P 2 mod. In≤63 A	BD 3P 3.5 mod. In≤25 A	BD 3P 3.5 mod. In≤63 A	BD 4P 3.5 mod. In≤25 A	BD 4P 3.5 mod. In≤63 A	BDHP 2P 4 mod. In≤125 A	BDHP 3P 6 mod. In≤125 A	BDHP 4P 6 mod. In≤125 A
										
AC	10	GW 94 401	-	-	-	-	-	-	-	-
	30	GW 94 402	GW 94 412	GW 94 442	GW 94 448	GW 94 422	GW 94 432	-	GW 95 416	GW 95 426
	300	GW 94 403	GW 94 413	GW 94 443	GW 94 449	GW 94 423	GW 94 433	GW 95 408	GW 95 418	GW 95 428
	500	GW 94 404	GW 94 414	GW 94 444	GW 94 450	GW 94 424	GW 94 434	-	-	-
A	30	GW 94 502	GW 94 512	GW 94 542	GW 94 547	GW 94 522	GW 94 532	-	GW 95 446	GW 95 456
	300	GW 94 503	GW 94 513	GW 94 543	GW 94 548	GW 94 523	GW 94 533	GW 95 438	GW 95 448	GW 95 458
	500	GW 94 504	GW 94 514	GW 94 544	GW 94 549	GW 94 524	GW 94 534	-	-	-
A[IR]	30	GW 94 566		GW 94 595		GW 94 586		-	-	-
A[S]	300	GW 94 563		GW 94 598		GW 94 583		GW 95 468	GW 95 478	GW 95 488
	1000	GW 94 565		GW 94 600		GW 94 585		GW 95 470	GW 95 480	GW 95 490
A reg.	300-3000	-		-		-		-	-	GW 95 512

In [A]	Ue [V]	Type	IΔn [mA]	RCD SAFETY SOCKET IP21 White	RCD SAFETY SOCKET IP21 Black	RCD SAFETY SOCKET IP44 White	RCD SAFETY SOCKET IP44 Black	RCD SAFETY UNIT IP41 White	RCD SAFETY UNIT IP41 Black	WALL-MOUNTING BOX White	WALL-MOUNTING BOX Black
16	230	A	10	GW 95 521	GW 95 521N	GW 95 523	GW 95 523N	GW 95 525	GW 95 525N	GW 95 527	GW 95 527N
			30	GW 95 522	GW 95 522N	GW 95 524	GW 95 524N	GW 95 526	GW 95 526N		

Residual current circuit breakers

			RCCB					
			2P		4P			
			IDP NA*	IDP	IDP 4P (3M)	IDP NA*	IDP	
								
In [A]	Type	IΔn [mA]	2 mod.	2 mod.	3 mod.	4 mod.	4 mod.	4 mod.****
25	AC	10	-	GW D4 001	-	-	-	-
		30	GW D4 617	GW D4 002	GW 94 662	GW D4 427	GW D4 102	GW D4 302
		100	-	GW D4 003	-	-	GW D4 103	-
		300	-	GW D4 004	GW 94 664	GW D4 429	GW D4 104	GW D4 304
	A	10	-	GW D4 011	-	-	GW D4 111	-
		30	GW D4 817	GW D4 012 / GW D4 012 MA**	GW 94 867	GW D4 439	GW D4 112	GW D4 312
		100	-	GW D4 013	-	-	GW D4 113	-
		300	-	GW D4 014	GW 94 869	GW D4 441	GW D4 114	GW D4 314
	A[IR]	30	-	GW D4 202	-	-	GW D4 217	GW D4 317
		300	-	GW D4 203	-	-	GW D4 218	-
	F	30	-	GW D4 261	-	-	GW D4 281	-
	B	30	-	GW D4 502 ***	-	-	GW D4 527	-
		300	-	GW D4 504 ***	-	-	GW D4 529	-
40	AC	30	GW D4 627	GW D4 022	GW 94 667	GW D4 431	GW D4 122	GW D4 322
		100	-	GW D4 023	GW 94 668	-	GW D4 123	-
		300	-	GW D4 024	GW 94 669	GW D4 433	GW D4 124	GW D4 324
		500	-	GW D4 025	GW 94 670	-	GW D4 125	-
	A	30	GW D4 827	GW D4 032 / GW D4 032 MA**	GW 94 897	GW D4 443	GW D4 132	GW D4 332
		100	-	GW D4 033	GW 94 898	-	GW D4 133	-
		300	-	GW D4 034	GW 94 899	GW D4 445	GW D4 134	GW D4 334
		500	-	GW D4 035	GW 94 900	-	GW D4 135	-
	A[IR]	30	-	GW D4 205	-	-	GW D4 220	GW D4 337
		300	-	GW D4 206	-	-	GW D4 221	-
	A[S]	300	-	GW D4 234	-	-	GW D4 249	-
		500	-	GW D4 235	-	-	GW D4 250	-
	F	30	-	GW D4 265	-	-	GW D4 285	-
	B	30	-	GW D4 507 ***	-	-	GW D45 32	-
		300	-	GW D4 509 ***	-	-	GW D4 534	-
63	AC	30	-	GW D4 042	-	-	GW D4 142	GW D4 342
		100	-	GW D4 043	-	-	GW D4 143	-
		300	-	GW D4 044	-	-	GW D4 144	GW D4 344
		500	-	GW D4 045	-	-	GW D4 145	-
	A	30	-	GW D4 052 / GW D4 052 MA**	-	-	GW D4 152	GW D4 352
		100	-	GW D4 053	-	-	GW D4 153	-
		300	-	GW D4 054	-	-	GW D4 154	GW D4 354
		500	-	GW D4 055	-	-	GW D4 155	-
	A[IR]	30	-	GW D4 208	-	-	GW D4 223	GW D4 357
		300	-	GW D4 209	-	-	GW D4 224	-
	A[S]	300	-	GW D4 237	-	-	GW D4 252	-
		500	-	GW D4 238	-	-	GW D4 253	-
	F	30	-	GW D4 269	-	-	GW D4 289	-
	B	30	-	GW D4 512 ***	-	-	GW D4 537	-
		300	-	GW D4 514 ***	-	-	GW D4 539	-
80	AC	30	-	GW D4 062	-	-	GW 94 761 K	-
		300	-	-	-	-	GW 94 766 K	-
	A	30	-	GW D4 072	-	-	-	-
100	AC	30	-	-	-	-	GW 94 777 K	-
		300	-	-	-	-	GW 94 779 K	-
	A	30	-	-	-	-	GW 94 957 K	-
		300	-	-	-	-	GW 94 959 K	-
	A[IR]	30	-	-	-	-	GW 95 696 K	-
	A[S]	300	-	-	-	-	GW 94 996 K	-
125	AC	30	-	-	-	-	GW 95 631	-
		300	-	-	-	-	GW 95 633	-
	A	30	-	-	-	-	GW 95 636	-
		300	-	-	-	-	GW 95 638	-
		500	-	-	-	-	GW 95 639	-
	A[S]	300	-	-	-	-	GW 95 640	-

* Version that cannot be completed with auxiliary contacts and trip coils. Version that can be completed with automatic reclosing devices ReStart RD
** Rated operational voltage is 110V ac
*** 4 Modules
**** RCCBs with left neutral

Technical data - RCBO - MDC

TYPE					MDC 45		MDC 60		MDC 100		MDC 100 MA
											
Standards:					**IEC EN 61009-1 IEC EN 61009-2-1**		**IEC EN 61009-1 IEC EN 61009-2-1 IEC EN 62423 (type F)**		**IEC EN 61009-1 IEC EN 61009-2-1 IEC EN 62423 (type F)**		**IEC EN 61009-1 IEC EN 61009-2-1**
Rated current (In):				**(A)**	6-32		6-32		6-32		6-32
Utilization category:					A		A		A		A
Rated operational voltage (Ue):				**(V ac)**	230/400 - 240/415		230/400 - 240/415		230 - 240		110
Insulation voltage (Ui):				**(V)**	500		500		500		500
Rated frequency:				**(Hz)**	50/60		50/60		50/60		50/60
Rated impulse withstand voltage (Uimp):				**(kV)**	4		4		4		4
Overvoltage category:					III		III		III		III
Number of poles:					1P+N, 2P	3P, 4P	1P+N, 2P	3P, 4P	2P, 3P		2P
Energy limiting class (B and C):					3	1	3	1	3		3
Breaking capacity											
Alternating current:	**IEC/EN 61009-1**	**Icn**		**(A)**	4500		6000		10000		10000
		Ics		**(A)**	1 Icn		1 Icn		0.75 Icn		0.75 Icn
	IEC/EN 60947-2	**Icu**	**230/240 V**	**(kA)**	6	-	10	-	15		15
			400/415 V	**(kA)**	-	4,5	-	6	-		-
		Ics		**(kA)**	100% Icu		75% Icu	100% Icu	50% Icu		50% Icu
Rated residual operating current (IΔn)				**(mA)**							
Type:			**AC**		30		30		30		30
					300		300		300		-
			A		30		30		30		30
					-		-		100		-
					300		300		300		-
			A[IR]		-		30		30		-
			A[S]		-		300		-		-
			F		-		30		30		-
Level of immunity (8/20 µs):				**(A)**	250		250 (for AC and A types) 3000 (for A[IR], A[S], F types)		250 (for AC and A types) 3000 (for type A[IR], F)		250
Residual making and breaking capacity (IΔm):				**(A)**	4500		4500		4500		4500
Voltage independent working:					yes		yes		yes		yes
Wiring:	**cable section (mm²)[1]**		**rigid**		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10
			flexible		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10
Electrical endurance:					10000		10000		10000		10000
Mechanical endurance:					20000		20000		20000		20000
Max. no. of usable modular accessories:					2		2		2		2
Upline/Downline power supply:					yes		yes		yes		yes
Status displayed:					yes		yes		yes		yes
Mounting position:					any		any		any		any
Rated tightening torque:				**(Nm)**	2		2		2		2
Screwdriver suggested:					PZ2		PZ2		PZ2		PZ2
Degree of protection:	**terminals**				IP20		IP20		IP20		IP20
	front				IP40		IP40		IP40		IP40
Pollution degree:					2		2		2		2
Tropicalization:					55°C - RH 95%		55°C - RH 95%		55°C - RH 95%		55°C - RH 95%
Reference temperature:				**(°C)**	30		30		30		30
Operating temperature:				**(°C)**	-25 +60 [2]		-25 +60 [2]		-25 +60 [2]		-25 +60 [2]
Stocking temperature:				**(°C)**	-40 +70		-40 +70		-40 +70		-40 +70
Double connection (cable+fork busbar):					yes (only downstream terminals)		yes (only downstream terminals)		yes (only downstream terminals)		yes (only downstream terminals)
Weight per pole:				**(g)**	120		120		120		120
Curve:					C		C	B	C	B	C
Rated currents available (In):				**(A)**	6		6	6	6	6	6
					10		10	10	10	10	10
					13		13	13	13	13	13
					16		16	16	16	16	16
					20		20	20	20	20	20
					25		25	25	25	25	25
					32		32	32	32	32	32

[1] Minimum cable section is 1mm²

[2] With temperatures greater than 30°C, derating of In rated current is expected

Technical data - Add-on RCD - BD - BDHP

TYPE				BD		BDHP	BDHP ADJUSTABLE
							
Standards:				**IEC EN 61009-1 Annex G IEC EN 61009-2-1**		**IEC EN 61009-1 Annex G IEC EN 61009-2-1**	**EN 60947-2 app. B**
Rated current (In):			**(A)**	≤ 25	≤ 63	≤ 125	≤ 125
Rated operational voltage (Ue):			**(V ac)**	230/400		230/400	400
Insulation voltage (Ui):			**(V)**	500		500	500
Rated frequency:			**(Hz)**	50/60		50/60	50
Rated impulse withstand voltage (Uimp):			**(kV)**	4		4	4
Overvoltage category:				III		III	III
Number of poles:				2P, 3P, 4P		2P, 3P, 4P	4P
Rated residual operating current (IΔn)			**(mA)**				
Type:		**AC**		10 [1]	-	-	-
				30	30	30	-
				300	300	300	-
				500	500	-	-
		A		30	30	30	-
				300	300	300	-
				500	500	-	-
		A[IR]		-	30	-	-
		A[S]		-	300	300	-
				-	1000	1000	-
		A[Adj.]		-	-	-	300 - 500 - 1000 - 3000
Adjustable tripping time (t):			**(ms)**	-		-	0 - 60 - 150
Level of immunity (8/20 µs):			**(A)**	250 (for AC and A types) 3000 (for A[IR] and A[S] types)		250 (for AC and A types) 3000 (for A[S] type)	3000
Residual making and breaking capacity (IΔm):			**(A)**	Icn circuit breaker		Icn circuit breaker	Icn circuit breaker
Voltage independent working:				yes		yes	yes
Wiring:	**cable section (mm²)**	**rigid**		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x70 - ≤ 2x25 - ≤ 2x25+1x10	≤ 1x70 - ≤ 2x25 - ≤ 2x25+1x10
		flexible		≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10		≤ 1x50 - ≤ 2x25 - ≤ 3x16	≤ 1x50 - ≤ 2x25 - ≤ 3x16
Upline/Downline power supply:				yes		yes	yes
Mounting position:				any		any	any
Rated tightening torque:			**(Nm)**	2		3.5 / 3 (terminal)	3.5 / 3 (terminal)
Screwdriver suggested:				PZ2		PZ2	PZ2
Degree of protection:	**terminals**			IP20		IP20	IP20
	front			IP40		IP40	IP40
Pollution degree:				2		2	2
Tropicalization:				55°C - RH 95%		55°C - RH 95%	55°C - RH 95%
Reference temperature:			**(°C)**	30		30	30
Operating temperature:			**(°C)**	-25 +40		-25 +40	-25 +40
Stocking temperature:			**(°C)**	-40 +70		-40 +70	-40 +70
Weight per pole:			**(g)**	100		200	200

[1] Only for 2P versions

Technical data - RCCB - IDP

TYPE			IDP NA	IDP	IDP 4P (3M)	SD K	IDP 125A
							
Standard:			IEC EN 61008-1 IEC EN 61008-2-1	IEC EN 61008-1 IEC EN 61008-2-1 IEC 62955 (type A[EV]) IEC EN 62423 (type F and B)	IEC EN 61008-1 IEC EN 61008-2-1	IEC EN 61008-1 IEC EN 61008-2-1	IEC EN 61008-1 IEC EN 61008-2-1
Rated current (In):		**(A)**	25-40-63	25-80	25-40	80-100	125
Rated operational voltage (Ue):		**(V ac)**	230/400 - 240/415	230/400 - 240/415 110 (for MA versions)	400	400 - 415	400
Insulation voltage (Ui):		**(V)**	500	500	500	400	400
Rated impulse withstand voltage (Uimp):		**kV**	4	4	4	4	4
Overvoltage category:			III	III	III	III	III
Rated frequency:		**(Hz)**	50	50/60	50/60	50	50
Poles:			2P (Up to 40A) 4P (Up to 63A)	2P, 4P	4P	4P	4P
Number of modules:			2 (2P) 4 (4P)	2 (2P) 4 (4P) 4 (2P/4P type A[EV] and B)	3	4	4
Rated residual operating current (IΔn)		**(mA)**					
Type:	**AC**		-	10 [1]	-	-	-
			30	30	30	30	30
			-	100	100	-	-
			300	300	300	300	300
			-	500	500	-	-
	A		-	10 [1]	-	-	-
			30	30	30	30	30
			-	100	100	-	-
			300	300	300	300	300
			-	500	500	-	500
	IR - Impulse resistant		-	30	-	30	-
			-	300	-	-	-
	EV - electric vehicles(2)		-	30	-	-	-
	S - Selective		-	300	-	300	300
			-	500	-	-	-
	F		-	30	-	-	-
	B		-	30	-	-	-
			-	300	-	-	-
Level of immunity (8/20μs):		**(A)**	250	250 (Type AC - A) 3000 (type A[IR], A[S], A[EV], F and B)	250	250 (Type AC - A) 3000 (Type A[IR] - A[S])	200 (type AC and A) 3000 (type A[S])
Residual making and breaking capacity (Idm):		**(A)**	10 x In (630A min)	10 x In (630A min)	630	800 (80A) - 1000 (100A)	1250
Making and breaking capacity (Im):		**(A)**	10 x In (630A min)	10 x In (630A min)	630	800 (80A) - 1000 (100A)	1250
Voltage independent working:			yes	yes	yes	yes	yes
Wiring:	**Cable section (mm²) [3]**	**rigid**	≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	≤35	≤50
		flexible	≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	≤ 1x35 - ≤ 2x16 - ≤ 1x16+2x10	≤ 1x25 - ≤ 1x16+1x10 - ≤ 3x6	≤35	≤50
Electrical endurance:			5000	10000	5000	4000	4000
Mechanical endurance:			10000	20000	10000	10000	10000
Upstrem / Downstream supply:			yes	yes	yes	yes	yes
Mounting position:			any	any	any	any	any
Rated tightening torque:		**(Nm)**	2	3	2	2	2,5
Screw type:			PZ2	PZ2	PZ2	PZ2	PZ2
Pollution degree:			2	2	2	2	2
Fire resistance:			Glow wire Test IEC 60695-2-11 according with IEC 61008-1				
IP degree (inside the distribution board):			IP40	IP40	IP40	IP40	IP40
Tropicalization:			55°C - UR 95%	55°C - UR 95%	55°C - UR 95%	55°C - UR 95%	55°C - UR 95%
Installation altitude:		**(m)**	≤ 2000	≤ 2000	≤ 2000	≤ 2000	≤ 2000
Operating temperature (average daily temperature ≤35°C):		**(°C)**	-5 ÷ +40	-25 ÷ +60 [4]	-25 ÷ +40	-25 ÷ +40	-25 ÷ +40
Storage temperature:		**(°C)**	-40 ÷ +70	-40 ÷ +70	-40 ÷ +70	-35 ÷ +60	-35 ÷ +60
Double connection (cable + fork busbar):			no (for 2P) yes (only downstream for 4P)	yes (Upstream and downstream)	yes (Upstream and downstream)	yes (Upstream and downstream)	yes (Upstream and downstream)
Signalization of the relay tripping:			no	yes	no	no	no
Weight of device:		**(g)**	160 (2P), 300 (4P)	175 (2P), 320 (4P) 275 (2P type A[EV] and B) 340 (4P type A[EV] and B)	280	350	350

[1] Up to 25A
[2] Type A[EV] trips in the event of a fault current with smooth residual direct current equal to or above 6mA
[3] Minimum cable section is 1.5mm²
[4] With temperatures greater than 40°C, derating of In rated current is expected

RATED CONDITIONAL RESIDUAL SHORT-CIRCUIT CURRENT IΔc (kA)

Rated current In		25A / 40A (NA)		25A / 40A			63A(NA)	63A	80A		100A	125A
Poles		2P	4P	2P	4P	4P (3M)	2P/4P	2P/4P	2P	4P	4P	4P
Fuse	**gG 63A**	6	6	10	10	6	6	10*	-	-	-	-
	gG 80A	-		-	-	-	-	10	6	10	-	-
	gG 100	-		-	-	-	-	-	-	-	10	-
	gG 125	-		-	-	-	-	-	-	-	-	10
MCB	**MTC 45**	4.5					4.5		-		-	-
	MTC 60	6					6		-		-	-
	MTC 100	10					10		-		-	-
	MT 45	4.5					4.5		-		-	-
	MT 60	6					6		-		-	-
	MT 100	10					10		-		-	-
	MT 250	10					10		-		-	-
	MTHP 160	-					10		10		10	10
	MTHP 250	10					10		-		-	-

* Only A[EV], F and B type RCCBs

Technical data - Local RCCB

TYPE			SAFETY SOCKET WITH RCCB		SAFETY SOCKET WITH RCCB (WATER PROTECTED)		RCCB SAFETY UNIT	
								
Standard:			**IEC EN 61008-1 IEC EN 61008-2-1 IEC 60884-1**		**IEC EN 61008-1 IEC EN 61008-2-1 IEC 60884-1**		**IEC EN 61008-1 IEC EN 61008-2-1**	
Degree of protection:			IP21		IP44		IP41	
Type of installation:			flush-mounting or surface-mounting (when installed inside the box GW 95 527 or GW 95 527 N)					
Codes (white colour):			**GW 95 521**	**GW 95 522**	**GW 95 523**	**GW 95 524**	**GW 95 525**	**GW 95 526**
Codes (black colour):			**GW 95 521 N**	**GW 95 522 N**	**GW 95 523 N**	**GW 95 524 N**	**GW 95 525 N**	**GW 95 526 N**
Rated residual operating current (IΔn):		**(mA)**	10	30	10	30	10	30
Rated current (In):		**(A)**	16					
Rated operational voltage (Ue):		**(V ac)**	230 - 240					
Rated impulse withstand voltage (Uimp):		**(kV)**	4					
Overvoltage category:			III					
Rated frequency:		**(Hz)**	50					
Poles:			1P+N					
RCCB type:			A					
Level of immunity (8/20μs):		**(A)**	250					
Residual making and breaking capacity (Idm):		**(A)**	500					
Making and breaking capacity (Im):		**(A)**	500					
Rated conditional residual short-circuit current (IΔc):		**(A)**	3000 (fuse gG 20A)					
Voltage independent working:			yes					
Wiring:	**cable section (mm²)**	**rigid**	min 1.5 - max 2.5					
		flexible	min 1.5 - max 2.5					
Electrical endurance:			2000					
Mechanical endurance:			4000					
Type of terminal:			Screwless					
Pollution degree:			2					
Tropicalization:			55°C - RH 95%					
Operating temperature:		**(°C)**	-25 ÷ + 40					
Storage temperature:		**(°C)**	-40 ÷ + 70					
Weight:		**(g)**	155		165		145	


90 RCD

Modular circuit breakers for residual current protection



The 90 RCD range meets any ground fault protection requirement for any area of application. The range comprises MDC compact residual current c.b. with overcurrent protection. (from 6 to 32 A, curves B and C, up to 10 kA and IΔn from 30 and 300 mA type AC, A, A[IR] and A[S] and F) BD and BDHP, add-on residual current devices for circuit breakers MT and MTHP (IΔn from 10 mA to 3 A type AC, A, A[IR], A[S] and A adjustable) IDP residual current circuit breakers (up to 125 A, IΔn from 10 to 500 mA type AC, A, A[IR], A[S], F, B).

MDC - MONOBLOC COMPACT RCBO'S



MDC 45 - AC type - C curve - 4500 A (EN 61009-1) - 4.5 kA (EN 60947-2)





GW 94 027

Compact residual current circuit breakers with overcurrent protection


AC


Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 94 005	30 mA	6 A	230 V	2	1/6
GW 94 006	30 mA	10 A	230 V	2	1/6
GW 94 011	30 mA	13 A	230 V	2	1/6
GW 94 007	30 mA	16 A	230 V	2	1/6
GW 94 008	30 mA	20 A	230 V	2	1/6
GW 94 009	30 mA	25 A	230 V	2	1/6
GW 94 010	30 mA	32 A	230 V	2	1/6
GW 94 015	300 mA	6 A	230 V	2	1/6
GW 94 016	300 mA	10 A	230 V	2	1/6
GW 94 017	300 mA	16 A	230 V	2	1/6
GW 94 018	300 mA	20 A	230 V	2	1/6
GW 94 019	300 mA	25 A	230 V	2	1/6
GW 94 020	300 mA	32 A	230 V	2	1/6
No. of poles: 2P					
GW 94 025	30 mA	6 A	230 V	2	1/6
GW 94 026	30 mA	10 A	230 V	2	1/6
GW 94 031	30 mA	13 A	230 V	2	1/6
GW 94 027	30 mA	16 A	230 V	2	1/6
GW 94 028	30 mA	20 A	230 V	2	1/6
GW 94 029	30 mA	25 A	230 V	2	1/6
GW 94 030	30 mA	32 A	230 V	2	1/6
GW 94 035	300 mA	6 A	230 V	2	1/6
GW 94 036	300 mA	10 A	230 V	2	1/6
GW 94 037	300 mA	16 A	230 V	2	1/6
GW 94 038	300 mA	20 A	230 V	2	1/6
GW 94 039	300 mA	25 A	230 V	2	1/6
GW 94 040	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 94 045	30 mA	6 A	400 V	3	1/4
GW 94 046	30 mA	10 A	400 V	3	1/4
GW 94 051	30 mA	13 A	400 V	3	1/4
GW 94 047	30 mA	16 A	400 V	3	1/4
GW 94 048	30 mA	20 A	400 V	3	1/4
GW 94 049	30 mA	25 A	400 V	3	1/4

CONTINUES

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
GW 94 050	30 mA	32 A	400 V	3	1/4
GW 94 055	300 mA	6 A	400 V	3	1/4
GW 94 056	300 mA	10 A	400 V	3	1/4
GW 94 057	300 mA	16 A	400 V	3	1/4
GW 94 058	300 mA	20 A	400 V	3	1/4
GW 94 059	300 mA	25 A	400 V	3	1/4
GW 94 060	300 mA	32 A	400 V	3	1/4
No. of poles: 4P					
GW 94 065	30 mA	6 A	400 V	4	1/3
GW 94 066	30 mA	10 A	400 V	4	1/3
GW 94 071	30 mA	13 A	400 V	4	1/3
GW 94 067	30 mA	16 A	400 V	4	1/3
GW 94 068	30 mA	20 A	400 V	4	1/3
GW 94 069	30 mA	25 A	400 V	4	1/3
GW 94 070	30 mA	32 A	400 V	4	1/3
GW 94 075	300 mA	6 A	400 V	4	1/3
GW 94 076	300 mA	10 A	400 V	4	1/3
GW 94 077	300 mA	16 A	400 V	4	1/3
GW 94 078	300 mA	20 A	400 V	4	1/3
GW 94 079	300 mA	25 A	400 V	4	1/3
GW 94 080	300 mA	32 A	400 V	4	1/3

MDC 45 - A type - C curve - 4500 A (EN 61009-1) - 4.5 kA (EN 60947-2)







GW 94 227

Compact residual current circuit breakers with overcurrent protection



A

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 94 205	30 mA	6 A	230 V	2	1/6
GW 94 206	30 mA	10 A	230 V	2	1/6
GW 94 211	30 mA	13 A	230 V	2	1/6
GW 94 207	30 mA	16 A	230 V	2	1/6
GW 94 208	30 mA	20 A	230 V	2	1/6
GW 94 209	30 mA	25 A	230 V	2	1/6
GW 94 210	30 mA	32 A	230 V	2	1/6
GW 94 215	300 mA	6 A	230 V	2	1/6
GW 94 216	300 mA	10 A	230 V	2	1/6
GW 94 217	300 mA	16 A	230 V	2	1/6
GW 94 218	300 mA	20 A	230 V	2	1/6
GW 94 219	300 mA	25 A	230 V	2	1/6
GW 94 220	300 mA	32 A	230 V	2	1/6
No. of poles: 2P					
GW 94 225	30 mA	6 A	230 V	2	1/6
GW 94 226	30 mA	10 A	230 V	2	1/6
GW 94 231	30 mA	13 A	230 V	2	1/6
GW 94 227	30 mA	16 A	230 V	2	1/6
GW 94 228	30 mA	20 A	230 V	2	1/6
GW 94 229	30 mA	25 A	230 V	2	1/6
GW 94 230	30 mA	32 A	230 V	2	1/6
GW 94 235	300 mA	6 A	230 V	2	1/6
GW 94 236	300 mA	10 A	230 V	2	1/6
GW 94 237	300 mA	16 A	230 V	2	1/6
GW 94 238	300 mA	20 A	230 V	2	1/6
GW 94 239	300 mA	25 A	230 V	2	1/6
GW 94 240	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 94 245	30 mA	6 A	400 V	3	1/4
GW 94 246	30 mA	10 A	400 V	3	1/4
GW 94 251	30 mA	13 A	400 V	3	1/4
GW 94 247	30 mA	16 A	400 V	3	1/4
GW 94 248	30 mA	20 A	400 V	3	1/4
GW 94 249	30 mA	25 A	400 V	3	1/4
GW 94 250	30 mA	32 A	400 V	3	1/4
GW 94 255	300 mA	6 A	400 V	3	1/4
GW 94 256	300 mA	10 A	400 V	3	1/4
GW 94 257	300 mA	16 A	400 V	3	1/4
GW 94 258	300 mA	20 A	400 V	3	1/4
GW 94 259	300 mA	25 A	400 V	3	1/4
GW 94 260	300 mA	32 A	400 V	3	1/4
No. of poles: 4P					
GW 94 265	30 mA	6 A	400 V	4	1/3
GW 94 266	30 mA	10 A	400 V	4	1/3
GW 94 271	30 mA	13 A	400 V	4	1/3
GW 94 267	30 mA	16 A	400 V	4	1/3
GW 94 268	30 mA	20 A	400 V	4	1/3
GW 94 269	30 mA	25 A	400 V	4	1/3
GW 94 270	30 mA	32 A	400 V	4	1/3
GW 94 275	300 mA	6 A	400 V	4	1/3
GW 94 276	300 mA	10 A	400 V	4	1/3
GW 94 277	300 mA	16 A	400 V	4	1/3
GW 94 278	300 mA	20 A	400 V	4	1/3
GW 94 279	300 mA	25 A	400 V	4	1/3
GW 94 280	300 mA	32 A	400 V	4	1/3

MDC 60 - AC type - C curve - 6000 A (EN 61009-1) - 6 kA (EN 60947-2)







GW 94 168

Compact residual current circuit breakers with overcurrent protection

AC

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 94 105	30 mA	6 A	230 V	2	1/6
GW 94 106	30 mA	10 A	230 V	2	1/6
GW 94 111	30 mA	13 A	230 V	2	1/6
GW 94 107	30 mA	16 A	230 V	2	1/6
GW 94 108	30 mA	20 A	230 V	2	1/6
GW 94 109	30 mA	25 A	230 V	2	1/6
GW 94 110	30 mA	32 A	230 V	2	1/6
GW 94 115	300 mA	6 A	230 V	2	1/6
GW 94 116	300 mA	10 A	230 V	2	1/6
GW 94 117	300 mA	16 A	230 V	2	1/6
GW 94 118	300 mA	20 A	230 V	2	1/6
GW 94 119	300 mA	25 A	230 V	2	1/6
GW 94 120	300 mA	32 A	230 V	2	1/6
No. of poles: 2P					
GW 94 125	30 mA	6 A	230 V	2	1/6
GW 94 126	30 mA	10 A	230 V	2	1/6
GW 94 131	30 mA	13 A	230 V	2	1/6
GW 94 127	30 mA	16 A	230 V	2	1/6
GW 94 128	30 mA	20 A	230 V	2	1/6
GW 94 129	30 mA	25 A	230 V	2	1/6
GW 94 130	30 mA	32 A	230 V	2	1/6
GW 94 135	300 mA	6 A	230 V	2	1/6
GW 94 136	300 mA	10 A	230 V	2	1/6
GW 94 137	300 mA	16 A	230 V	2	1/6
GW 94 138	300 mA	20 A	230 V	2	1/6
GW 94 139	300 mA	25 A	230 V	2	1/6
GW 94 140	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 94 145	30 mA	6 A	400 V	3	1/4
GW 94 146	30 mA	10 A	400 V	3	1/4
GW 94 151	30 mA	13 A	400 V	3	1/4
GW 94 147	30 mA	16 A	400 V	3	1/4
GW 94 148	30 mA	20 A	400 V	3	1/4
GW 94 149	30 mA	25 A	400 V	3	1/4
GW 94 150	30 mA	32 A	400 V	3	1/4
GW 94 155	300 mA	6 A	400 V	3	1/4
GW 94 156	300 mA	10 A	400 V	3	1/4
GW 94 157	300 mA	16 A	400 V	3	1/4
GW 94 158	300 mA	20 A	400 V	3	1/4
GW 94 159	300 mA	25 A	400 V	3	1/4
GW 94 160	300 mA	32 A	400 V	3	1/4
No. of poles: 4P					
GW 94 165	30 mA	6 A	400 V	4	1/3
GW 94 166	30 mA	10 A	400 V	4	1/3
GW 94 171	30 mA	13 A	400 V	4	1/3
GW 94 167	30 mA	16 A	400 V	4	1/3
GW 94 168	30 mA	20 A	400 V	4	1/3
GW 94 169	30 mA	25 A	400 V	4	1/3
GW 94 170	30 mA	32 A	400 V	4	1/3
GW 94 175	300 mA	6 A	400 V	4	1/3
GW 94 176	300 mA	10 A	400 V	4	1/3
GW 94 177	300 mA	16 A	400 V	4	1/3
GW 94 178	300 mA	20 A	400 V	4	1/3
GW 94 179	300 mA	25 A	400 V	4	1/3
GW 94 180	300 mA	32 A	400 V	4	1/3

MDC 60 - A type - C curve - 6000 A (EN 61009-1) - 6 kA (EN 60947-2)







GW 94 347


Compact residual current circuit breakers with overcurrent protection




A

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 94 305	30 mA	6 A	230 V	2	1/6
GW 94 306	30 mA	10 A	230 V	2	1/6
GW 94 311	30 mA	13 A	230 V	2	1/6
GW 94 307	30 mA	16 A	230 V	2	1/6
GW 94 308	30 mA	20 A	230 V	2	1/6
GW 94 309	30 mA	25 A	230 V	2	1/6
GW 94 310	30 mA	32 A	230 V	2	1/6
GW 94 315	300 mA	6 A	230 V	2	1/6
GW 94 316	300 mA	10 A	230 V	2	1/6
GW 94 317	300 mA	16 A	230 V	2	1/6
GW 94 318	300 mA	20 A	230 V	2	1/6
GW 94 319	300 mA	25 A	230 V	2	1/6
GW 94 320	300 mA	32 A	230 V	2	1/6
No. of poles: 2P					
GW 94 325	30 mA	6 A	230 V	2	1/6
GW 94 326	30 mA	10 A	230 V	2	1/6
GW 94 331	30 mA	13 A	230 V	2	1/6
GW 94 327	30 mA	16 A	230 V	2	1/6
GW 94 328	30 mA	20 A	230 V	2	1/6
GW 94 329	30 mA	25 A	230 V	2	1/6
GW 94 330	30 mA	32 A	230 V	2	1/6
GW 94 335	300 mA	6 A	230 V	2	1/6
GW 94 336	300 mA	10 A	230 V	2	1/6
GW 94 337	300 mA	16 A	230 V	2	1/6
GW 94 338	300 mA	20 A	230 V	2	1/6
GW 94 339	300 mA	25 A	230 V	2	1/6
GW 94 340	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 94 345	30 mA	6 A	400 V	3	1/4
GW 94 346	30 mA	10 A	400 V	3	1/4
GW 94 351	30 mA	13 A	400 V	3	1/4
GW 94 347	30 mA	16 A	400 V	3	1/4
GW 94 348	30 mA	20 A	400 V	3	1/4
GW 94 349	30 mA	25 A	400 V	3	1/4
GW 94 350	30 mA	32 A	400 V	3	1/4
GW 94 355	300 mA	6 A	400 V	3	1/4
GW 94 356	300 mA	10 A	400 V	3	1/4
GW 94 357	300 mA	16 A	400 V	3	1/4
GW 94 358	300 mA	20 A	400 V	3	1/4
GW 94 359	300 mA	25 A	400 V	3	1/4
GW 94 360	300 mA	32 A	400 V	3	1/4
No. of poles: 4P					
GW 94 365	30 mA	6 A	400 V	4	1/3
GW 94 366	30 mA	10 A	400 V	4	1/3
GW 94 371	30 mA	13 A	400 V	4	1/3
GW 94 367	30 mA	16 A	400 V	4	1/3
GW 94 368	30 mA	20 A	400 V	4	1/3
GW 94 369	30 mA	25 A	400 V	4	1/3
GW 94 370	30 mA	32 A	400 V	4	1/3
GW 94 375	300 mA	6 A	400 V	4	1/3
GW 94 376	300 mA	10 A	400 V	4	1/3
GW 94 377	300 mA	16 A	400 V	4	1/3
GW 94 378	300 mA	20 A	400 V	4	1/3
GW 94 379	300 mA	25 A	400 V	4	1/3
GW 94 380	300 mA	32 A	400 V	4	1/3

MDC 60 - A[IR] type Impulse Resistant - C curve - 6000 A (EN 61009-1) - 6 kA (EN 60947-2)







GW 95 817

Compact residual current circuit breakers with overcurrent protection








Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 805	30 mA	6 A	230 V	2	1/6
GW 95 806	30 mA	10 A	230 V	2	1/6
GW 95 811	30 mA	13 A	230 V	2	1/6
GW 95 807	30 mA	16 A	230 V	2	1/6
GW 95 808	30 mA	20 A	230 V	2	1/6
GW 95 809	30 mA	25 A	230 V	2	1/6
GW 95 810	30 mA	32 A	230 V	2	1/6
No. of poles: 4P					
GW 95 815	30 mA	6 A	400 V	4	1/3
GW 95 816	30 mA	10 A	400 V	4	1/3
GW 95 821	30 mA	13 A	400 V	4	1/3
GW 95 817	30 mA	16 A	400 V	4	1/3
GW 95 818	30 mA	20 A	400 V	4	1/3
GW 95 819	30 mA	25 A	400 V	4	1/3
GW 95 820	30 mA	32 A	400 V	4	1/3

CHARACTERISTICS: type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 60 - A[S] type Selective - C curve - 6000 A (EN 61009-1) - 6 kA (EN 60947-2)







GW 95 850

Compact residual current circuit breakers with overcurrent protection



A S

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 847	300 mA	16 A	230 V	2	1/6
GW 95 848	300 mA	20 A	230 V	2	1/6
GW 95 849	300 mA	25 A	230 V	2	1/6
GW 95 850	300 mA	32 A	230 V	2	1/6
No. of poles: 4P					
GW 95 857	300 mA	16 A	400 V	4	1/3
GW 95 858	300 mA	20 A	400 V	4	1/3
GW 95 859	300 mA	25 A	400 V	4	1/3
GW 95 860	300 mA	32 A	400 V	4	1/3


MDC 60 - F Type - C Curve - 6000 A (EN 61009-1) - 10 kA (EN 60947-2)





GW 95 937

Compact residual current circuit breakers with overcurrent protection



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 935	30 mA	6 A	230 V	2	1/6
GW 95 936	30 mA	10 A	230 V	2	1/6
GW 95 941	30 mA	13 A	230 V	2	1/6
GW 95 937	30 mA	16 A	230 V	2	1/6
GW 95 938	30 mA	20 A	230 V	2	1/6
GW 95 939	30 mA	25 A	230 V	2	1/6
GW 95 940	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: F type presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 60 - A type - B curve - 6000 A (EN 61009-1) - 6 kA (EN 60947-2)







GW 95 168

Compact residual current circuit breakers with overcurrent protection





Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW 95 105	30 mA	6 A	230 V	2	1/6
GW 95 106	30 mA	10 A	230 V	2	1/6
GW 95 111	30 mA	13 A	230 V	2	1/6
GW 95 107	30 mA	16 A	230 V	2	1/6
GW 95 108	30 mA	20 A	230 V	2	1/6
GW 95 109	30 mA	25 A	230 V	2	1/6
GW 95 110	30 mA	32 A	230 V	2	1/6
GW 95 115	300 mA	6 A	230 V	2	1/6
GW 95 116	300 mA	10 A	230 V	2	1/6
GW 95 117	300 mA	16 A	230 V	2	1/6
GW 95 118	300 mA	20 A	230 V	2	1/6
GW 95 119	300 mA	25 A	230 V	2	1/6
GW 95 120	300 mA	32 A	230 V	2	1/6
No. of poles: 2P					
GW 95 125	30 mA	6 A	230 V	2	1/6
GW 95 126	30 mA	10 A	230 V	2	1/6
GW 95 131	30 mA	13 A	230 V	2	1/6
GW 95 127	30 mA	16 A	230 V	2	1/6
GW 95 128	30 mA	20 A	230 V	2	1/6
GW 95 129	30 mA	25 A	230 V	2	1/6
GW 95 130	30 mA	32 A	230 V	2	1/6
GW 95 135	300 mA	6 A	230 V	2	1/6
GW 95 136	300 mA	10 A	230 V	2	1/6
GW 95 137	300 mA	16 A	230 V	2	1/6
GW 95 138	300 mA	20 A	230 V	2	1/6
GW 95 139	300 mA	25 A	230 V	2	1/6
GW 95 140	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 95 145	30 mA	6 A	400 V	3	1/4
GW 95 146	30 mA	10 A	400 V	3	1/4
GW 95 151	30 mA	13 A	400 V	3	1/4
GW 95 147	30 mA	16 A	400 V	3	1/4
GW 95 148	30 mA	20 A	400 V	3	1/4
GW 95 149	30 mA	25 A	400 V	3	1/4
GW 95 150	30 mA	32 A	400 V	3	1/4
GW 95 155	300 mA	6 A	400 V	3	1/4
GW 95 156	300 mA	10 A	400 V	3	1/4
GW 95 157	300 mA	16 A	400 V	3	1/4
GW 95 158	300 mA	20 A	400 V	3	1/4
GW 95 159	300 mA	25 A	400 V	3	1/4
GW 95 160	300 mA	32 A	400 V	3	1/4
No. of poles: 4P					
GW 95 165	30 mA	6 A	400 V	4	1/3
GW 95 166	30 mA	10 A	400 V	4	1/3
GW 95 171	30 mA	13 A	400 V	4	1/3
GW 95 167	30 mA	16 A	400 V	4	1/3
GW 95 168	30 mA	20 A	400 V	4	1/3
GW 95 169	30 mA	25 A	400 V	4	1/3
GW 95 170	30 mA	32 A	400 V	4	1/3
GW 95 175	300 mA	6 A	400 V	4	1/3
GW 95 176	300 mA	10 A	400 V	4	1/3
GW 95 177	300 mA	16 A	400 V	4	1/3
GW 95 178	300 mA	20 A	400 V	4	1/3
GW 95 179	300 mA	25 A	400 V	4	1/3
GW 95 180	300 mA	32 A	400 V	4	1/3

MDC 60 - F Type - B Curve - 6000 A (EN 61009-1) - 10 kA (EN 60947-2)





GW 95 977

Compact residual current circuit breakers with overcurrent protection



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 975	30 mA	6 A	230 V	2	1/6
GW 95 976	30 mA	10 A	230 V	2	1/6
GW 95 981	30 mA	13 A	230 V	2	1/6
GW 95 977	30 mA	16 A	230 V	2	1/6
GW 95 978	30 mA	20 A	230 V	2	1/6
GW 95 979	30 mA	25 A	230 V	2	1/6
GW 95 980	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: F type presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 100 - AC type - C curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 027

Compact residual current circuit breakers with overcurrent protection



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 025	30 mA	6 A	230 V	2	1/6
GW 95 026	30 mA	10 A	230 V	2	1/6
GW 95 031	30 mA	13 A	230 V	2	1/6
GW 95 027	30 mA	16 A	230 V	2	1/6
GW 95 028	30 mA	20 A	230 V	2	1/6
GW 95 029	30 mA	25 A	230 V	2	1/6
GW 95 030	30 mA	32 A	230 V	2	1/6
GW 95 035	300 mA	6 A	230 V	2	1/6
GW 95 036	300 mA	10 A	230 V	2	1/6
GW 95 037	300 mA	16 A	230 V	2	1/6
GW 95 038	300 mA	20 A	230 V	2	1/6
GW 95 039	300 mA	25 A	230 V	2	1/6
GW 95 040	300 mA	32 A	230 V	2	1/6

MDC 100 MA - AC type - C curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 025 MA

Compact residual current circuit breakers with overcurrent protection

AC

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 025 MA	30 mA	6 A	110 V	2	1/6
GW 95 026 MA	30 mA	10 A	110 V	2	1/6
GW 95 031 MA	30 mA	13 A	110 V	2	1/6
GW 95 027 MA	30 mA	16 A	110 V	2	1/6
GW 95 028 MA	30 mA	20 A	110 V	2	1/6
GW 95 029 MA	30 mA	25 A	110 V	2	1/6
GW 95 030 MA	30 mA	32 A	110 V	2	1/6

MDC 100 - A type - C curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)







GW 95 227

Compact residual current circuit breakers with overcurrent protection

A

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 225	30 mA	6 A	230 V	2	1/6
GW 95 226	30 mA	10 A	230 V	2	1/6
GW 95 231	30 mA	13 A	230 V	2	1/6
GW 95 227	30 mA	16 A	230 V	2	1/6
GW 95 228	30 mA	20 A	230 V	2	1/6
GW 95 229	30 mA	25 A	230 V	2	1/6
GW 95 230	30 mA	32 A	230 V	2	1/6
GW 95 785	100 mA	6 A	230 V	2	1/6
GW 95 786	100 mA	10 A	230 V	2	1/6
GW 95 791	100 mA	13 A	230 V	2	1/6
GW 95 787	100 mA	16 A	230 V	2	1/6
GW 95 788	100 mA	20 A	230 V	2	1/6
GW 95 789	100 mA	25 A	230 V	2	1/6
GW 95 790	100 mA	32 A	230 V	2	1/6
GW 95 235	300 mA	6 A	230 V	2	1/6
GW 95 236	300 mA	10 A	230 V	2	1/6
GW 95 237	300 mA	16 A	230 V	2	1/6
GW 95 238	300 mA	20 A	230 V	2	1/6
GW 95 239	300 mA	25 A	230 V	2	1/6
GW 95 240	300 mA	32 A	230 V	2	1/6
No. of poles: 3P					
GW 95 245	30 mA	6 A	230 V	3	1/4
GW 95 246	30 mA	10 A	230 V	3	1/4
GW 95 247	30 mA	16 A	230 V	3	1/4
GW 95 248	30 mA	20 A	230 V	3	1/4
GW 95 249	30 mA	25 A	230 V	3	1/4
GW 95 250	30 mA	32 A	230 V	3	1/4

MDC 100 MA - A type - C curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 225 MA

Compact residual current circuit breakers with overcurrent protection

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 225 MA	30 mA	6 A	110 V	2	1/6
GW 95 226 MA	30 mA	10 A	110 V	2	1/6
GW 95 231 MA	30 mA	13 A	110 V	2	1/6
GW 95 227 MA	30 mA	16 A	110 V	2	1/6
GW 95 228 MA	30 mA	20 A	110 V	2	1/6
GW 95 229 MA	30 mA	25 A	110 V	2	1/6
GW 95 230 MA	30 mA	32 A	110 V	2	1/6

MDC 100 - A[IR] type Impulse Resistant - C curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 827

Compact residual current circuit breakers with overcurrent protection

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 825	30 mA	6 A	230 V	2	1/6
GW 95 826	30 mA	10 A	230 V	2	1/6
GW 95 831	30 mA	13 A	230 V	2	1/6
GW 95 827	30 mA	16 A	230 V	2	1/6
GW 95 828	30 mA	20 A	230 V	2	1/6
GW 95 829	30 mA	25 A	230 V	2	1/6
GW 95 830	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 100 - F Type - C Curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 957

Compact residual current circuit breakers with overcurrent protection

F IR

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 955	30 mA	6 A	230 V	2	1/6
GW 95 956	30 mA	10 A	230 V	2	1/6
GW 95 961	30 mA	13 A	230 V	2	1/6
GW 95 957	30 mA	16 A	230 V	2	1/6
GW 95 958	30 mA	20 A	230 V	2	1/6
GW 95 959	30 mA	25 A	230 V	2	1/6
GW 95 960	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: F type presents greater resistance to mains disturbances and atmospheric discharges rn comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 100 - A type - B curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)






GW 95 327

Compact residual current circuit breakers with overcurrent protection

A

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 325	30 mA	6 A	230 V	2	1/6
GW 95 326	30 mA	10 A	230 V	2	1/6
GW 95 331	30 mA	13 A	230 V	2	1/6
GW 95 327	30 mA	16 A	230 V	2	1/6
GW 95 328	30 mA	20 A	230 V	2	1/6
GW 95 329	30 mA	25 A	230 V	2	1/6
GW 95 330	30 mA	32 A	230 V	2	1/6
GW 95 795	100 mA	6 A	230 V	2	1/6
GW 95 796	100 mA	10 A	230 V	2	1/6
GW 95 801	100 mA	13 A	230 V	2	1/6
GW 95 797	100 mA	16 A	230 V	2	1/6
GW 95 798	100 mA	20 A	230 V	2	1/6
GW 95 799	100 mA	25 A	230 V	2	1/6
GW 95 800	100 mA	32 A	230 V	2	1/6
GW 95 335	300 mA	6 A	230 V	2	1/6
GW 95 336	300 mA	10 A	230 V	2	1/6
GW 95 337	300 mA	16 A	230 V	2	1/6
GW 95 338	300 mA	20 A	230 V	2	1/6
GW 95 339	300 mA	25 A	230 V	2	1/6
GW 95 340	300 mA	32 A	230 V	2	1/6

MDC 100 - A[IR] type Impulse Resistant - B curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 837


Compact residual current circuit breakers with overcurrent protection



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 835	30 mA	6 A	230 V	2	1/6
GW 95 836	30 mA	10 A	230 V	2	1/6
GW 95 841	30 mA	13 A	230 V	2	1/6
GW 95 837	30 mA	16 A	230 V	2	1/6
GW 95 838	30 mA	20 A	230 V	2	1/6
GW 95 839	30 mA	25 A	230 V	2	1/6
GW 95 840	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

MDC 100 - F Type - B Curve - 10000 A (EN 61009-1) - 15 kA (EN 60947-2)





GW 95 967


Compact residual current circuit breakers with overcurrent protection





Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 965	30 mA	6 A	230 V	2	1/6
GW 95 966	30 mA	10 A	230 V	2	1/6
GW 95 971	30 mA	13 A	230 V	2	1/6
GW 95 967	30 mA	16 A	230 V	2	1/6
GW 95 968	30 mA	20 A	230 V	2	1/6
GW 95 969	30 mA	25 A	230 V	2	1/6
GW 95 970	30 mA	32 A	230 V	2	1/6

CHARACTERISTICS: F type presents greater resistance to mains disturbances and atmospheric discharges rn comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

BD - ADD-ON RESIDUAL CURRENT DEVICES FOR MT CIRCUIT BREAKERS


2P


3P


4P

BD - AC type (instantaneous)


GW 94 402

Add-on residual current devices




Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 94 401	10 mA	25 A	230 V	2	1/2
GW 94 402	30 mA	25 A	230 V	2	1/2
GW 94 403	300 mA	25 A	230 V	2	1/2
GW 94 404	500 mA	25 A	230 V	2	1/2
GW 94 412	30 mA	63 A	230 V	2	1/2
GW 94 413	300 mA	63 A	230 V	2	1/2
GW 94 414	500 mA	63 A	230 V	2	1/2
No. of poles: 3P					
GW 94 442	30 mA	25 A	400 V	3.5	1/2
GW 94 443	300 mA	25 A	400 V	3.5	1/2
GW 94 444	500 mA	25 A	400 V	3.5	1/2
GW 94 448	30 mA	63 A	400 V	3.5	1/2
GW 94 449	300 mA	63 A	400 V	3.5	1/2
GW 94 450	500 mA	63 A	400 V	3.5	1/2
No. of poles: 4P					
GW 94 422	30 mA	25 A	400 V	3.5	1/2
GW 94 423	300 mA	25 A	400 V	3.5	1/2
GW 94 424	500 mA	25 A	400 V	3.5	1/2
GW 94 432	30 mA	63 A	400 V	3.5	1/2
GW 94 433	300 mA	63 A	400 V	3.5	1/2
GW 94 434	500 mA	63 A	400 V	3.5	1/2

BD - A type (instantaneous)


GW 94 502

Add-on residual current devices




Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 94 502	30 mA	25 A	230 V	2	1/2
GW 94 503	300 mA	25 A	230 V	2	1/2
GW 94 504	500 mA	25 A	230 V	2	1/2
GW 94 512	30 mA	63 A	230 V	2	1/2
GW 94 513	300 mA	63 A	230 V	2	1/2
GW 94 514	500 mA	63 A	230 V	2	1/2
No. of poles: 3P					
GW 94 542	30 mA	25 A	400 V	3.5	1/2
GW 94 543	300 mA	25 A	400 V	3.5	1/2
GW 94 544	500 mA	25 A	400 V	3.5	1/2
GW 94 547	30 mA	63 A	400 V	3.5	1/2
GW 94 548	300 mA	63 A	400 V	3.5	1/2
GW 94 549	500 mA	63 A	400 V	3.5	1/2
No. of poles: 4P					
GW 94 522	30 mA	25 A	400 V	3.5	1/2
GW 94 523	300 mA	25 A	400 V	3.5	1/2
GW 94 524	500 mA	25 A	400 V	3.5	1/2
GW 94 532	30 mA	63 A	400 V	3.5	1/2
GW 94 533	300 mA	63 A	400 V	3.5	1/2
GW 94 534	500 mA	63 A	400 V	3.5	1/2

90 RCD

BD - A[IR] type (impulse resistant)



GW 94 566

Add-on residual current devices



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 94 566	30 mA	63 A	230 V	2	1/2
No. of poles: 3P					
GW 94 595	30 mA	63 A	400 V	3.5	1/2
No. of poles: 4P					
GW 94 586	30 mA	63 A	400 V	3.5	1/2

CHARACTERISTICS: type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to add-on residual current devices.
Immunity level 8/20 µs is 3000 A.

BD - A[S] type (selective)




GW 94 563

Add-on residual current devices



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 94 563	300 mA	63 A	230 V	2	1/2
GW 94 565	1000 mA	63 A	230 V	2	1/2
No. of poles: 3P					
GW 94 598	300 mA	63 A	400 V	3.5	1/2
GW 94 600	1000 mA	63 A	400 V	3.5	1/2
No. of poles: 4P					
GW 94 583	300 mA	63 A	400 V	3.5	1/2
GW 94 585	1000 mA	63 A	400 V	3.5	1/2

BDHP - ADD-ON RESIDUAL CURRENT DEVICES FOR MTHP CIRCUIT BREAKERS



BDHP - AC type (instantaneous)



GW 95 416

Add-on residual current devices



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 408	300 mA	125 A	230 V	4	1/2
No. of poles: 3P					
GW 95 416	30 mA	125 A	400 V	6	1/2
GW 95 418	300 mA	125 A	400 V	6	1/2
No. of poles: 4P					
GW 95 426	30 mA	125 A	400 V	6	1/2
GW 95 428	300 mA	125 A	400 V	6	1/2

BDHP - A type (instantaneous)

Add-on residual current devices



GW 95 446

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 438	300 mA	125 A	230 V	4	1/2
No. of poles: 3P					
GW 95 446	30 mA	125 A	400 V	6	1/2
GW 95 448	300 mA	125 A	400 V	6	1/2
No. of poles: 4P					
GW 95 456	30 mA	125 A	400 V	6	1/2
GW 95 458	300 mA	125 A	400 V	6	1/2

BDHP - A[S] type (selective)

Add-on residual current devices



GW 95 478

Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 468	300 mA	125 A	230 V	4	1/2
GW 95 470	1000 mA	125 A	230 V	4	1/2
No. of poles: 3P					
GW 95 478	300 mA	125 A	400 V	6	1/2
GW 95 480	1000 mA	125 A	400 V	6	1/2
No. of poles: 4P					
GW 95 488	300 mA	125 A	400 V	6	1/2
GW 95 490	1000 mA	125 A	400 V	6	1/2

BDHP - Type A[IR] Adjustable boosted immunity

Add-on residual current device




GW 95 512

Code	Idn	Adjustable tripping time	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 4P						
GW 95 512	300 - 3000 mA	0 - 60 - 150 ms	125 A	400 V	6	1/2


CHARACTERISTICS: Ida: adjustable 300-500-1000-3000 mA; adjustable tripping time 0-60-150 ms.

Type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard add-on residual current devices. Immunity level 8/20 µs is 3000 A.

IDP NA - RESIDUAL CURRENT CIRCUIT BREAKERS (ACCESSORIES NOT AVAILABLE)



2P



4P - 4 MODULES

IDP NA - AC Type instantaneous


GW D4 617

Residual current circuit breakers

AC

Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 617	25 A	30 mA	230 V	No	Yes	2	1/6
GW D4 627	40 A	30 mA	230 V	No	Yes	2	1/6
No. of poles: 4P							
GW D4 427	25 A	30 mA	400 V	No	No	4	1/3
GW D4 429	25 A	300 mA	400 V	No	No	4	1/3
GW D4 431	40 A	30 mA	400 V	No	No	4	1/3
GW D4 433	40 A	300 mA	400 V	No	No	4	1/3
GW D4 435	63 A	30 mA	400 V	No	No	4	1/3
GW D4 437	63 A	300 mA	400 V	No	No	4	1/3

IDP NA - A Type istantaneous



GW D4 817

Residual current circuit breakers


A

Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 817	25 A	30 mA	230 V	No	Yes	2	1/6
GW D4 827	40 A	30 mA	230 V	No	Yes	2	1/6
No. of poles: 4P							
GW D4 439	25 A	30 mA	400 V	No	No	4	1/3
GW D4 441	25 A	300 mA	400 V	No	No	4	1/3
GW D4 443	40 A	30 mA	400 V	No	No	4	1/3
GW D4 445	40 A	300 mA	400 V	No	No	4	1/3
GW D4 447	63 A	30 mA	400 V	No	No	4	1/3
GW D4 449	63 A	300 mA	400 V	No	No	4	1/3


IDP - RESIDUAL CURRENT CIRCUIT BREAKERS




2P



4P - 3 MODULES



4P - 4 MODULES
NEUTRAL ON LEFT



4P - 4 MODULES

IDP - AC Type instantaneous



GW D4 001

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 001	25 A	10 mA	230 V	Yes	Yes	2	1/6
GW D4 002	25 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 003	25 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 004	25 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 022	40 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 023	40 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 024	40 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 025	40 A	500 mA	230 V	Yes	Yes	2	1/6
GW D4 042	63 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 043	63 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 044	63 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 045	63 A	500 mA	230 V	Yes	Yes	2	1/6
GW D4 062	80 A	30 mA	230 V	Yes	Yes	2	1/6
No. of poles: 4P							
GW 94 662	25 A	30 mA	400 V	Yes	No	3	1/4
GW 94 664	25 A	300 mA	400 V	Yes	No	3	1/4
GW 94 667	40 A	30 mA	400 V	Yes	No	3	1/4
GW 94 668	40 A	100 mA	400 V	Yes	No	3	1/4
GW 94 669	40 A	300 mA	400 V	Yes	No	3	1/4
GW 94 670	40 A	500 mA	400 V	Yes	No	3	1/4
GW D4 102	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 103	25 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 104	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 122	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 123	40 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 124	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 125	40 A	500 mA	400 V	Yes	Yes	4	1/3
GW D4 142	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 143	63 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 144	63 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 145	63 A	500 mA	400 V	Yes	Yes	4	1/3
GW 94 761 K	80 A	30 mA	400 V	No	No	4	1/3
GW 94 766 K	80 A	300 mA	400 V	No	No	4	1/3
GW 94 777 K	100 A	30 mA	400 V	No	No	4	1/3
GW 94 779 K	100 A	300 mA	400 V	No	No	4	1/3
GW 95 631	125 A	30 mA	400 V	Yes	No	4	1
GW 95 633	125 A	300 mA	400 V	Yes	No	4	1
No. of poles: 4P (N-conductor left)							
GW D4 302	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 304	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 322	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 324	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 342	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 344	63 A	300 mA	400 V	Yes	Yes	4	1/3

NEWS

IDP - A Type istantaneous



GW D4 011

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 011	25 A	10 mA	230 V	Yes	Yes	2	1/6
GW D4 012	25 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 012 MA	25 A	30 mA	110 V	Yes	No	2	1/6
GW D4 013	25 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 014	25 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 032	40 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 032 MA	40 A	30 mA	110 V	Yes	No	2	1/6
GW D4 033	40 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 034	40 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 035	40 A	500 mA	230 V	Yes	Yes	2	1/6
GW D4 052	63 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 052 MA	63 A	30 mA	110 V	Yes	No	2	1/6
GW D4 053	63 A	100 mA	230 V	Yes	Yes	2	1/6
GW D4 054	63 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 055	63 A	500 mA	230 V	Yes	Yes	2	1/6
GW D4 072	80 A	30 mA	230 V	Yes	Yes	2	1/6
No. of poles: 4P							
GW 94 867	25 A	30 mA	400 V	Yes	No	3	1/4
GW 94 869	25 A	300 mA	400 V	Yes	No	3	1/4
GW 94 885	40 A	30 mA	230 V	Yes	No	3	1/4
GW 94 897	40 A	30 mA	400 V	Yes	No	3	1/4
GW 94 898	40 A	100 mA	400 V	Yes	No	3	1/4
GW 94 899	40 A	300 mA	400 V	Yes	No	3	1/4
GW 94 900	40 A	500 mA	400 V	Yes	No	3	1/4
GW D4 111	25 A	10 mA	400 V	Yes	Yes	4	1/3
GW D4 112	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 113	25 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 114	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 132	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 133	40 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 134	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 135	40 A	500 mA	400 V	Yes	Yes	4	1/3
GW D4 152	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 153	63 A	100 mA	400 V	Yes	Yes	4	1/3
GW D4 154	63 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 155	63 A	500 mA	400 V	Yes	Yes	4	1/3
GW 94 957 K	100 A	30 mA	400 V	No	No	4	1/3
GW 94 959 K	100 A	300 mA	400 V	No	No	4	1/3
GW 95 636	125 A	30 mA	400 V	Yes	No	4	1
GW 95 638	125 A	300 mA	400 V	Yes	No	4	1
GW 95 639	125 A	500 mA	400 V	Yes	No	4	1
No. of poles: 4P (N-conductor left)							
GW D4 312	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 314	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 332	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 334	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 352	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 354	63 A	300 mA	400 V	Yes	Yes	4	1/3

NEWS

IDP - A[IR] Type (impulse resistant)



GW D4 217

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 202	25 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 203	25 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 205	40 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 206	40 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 208	63 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 209	63 A	300 mA	230 V	Yes	Yes	2	1/6
No. of poles: 4P							
GW D4 217	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 218	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 220	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 221	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 223	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 224	63 A	300 mA	400 V	Yes	Yes	4	1/3
GW 95 696 K	100 A	30 mA	400 V	No	No	4	1/3
No. of poles: 4P (N-conductor left)							
GW D4 317	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 337	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 357	63 A	30 mA	400 V	Yes	Yes	4	1/3

CHARACTERISTICS: type A[IR] presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers. Immunity level 8/20 µs is 3000 A.

IDP - A[S] Type (selective)



GW D4 249

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 234	40 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 235	40 A	500 mA	230 V	Yes	Yes	2	1/6
GW D4 237	63 A	300 mA	230 V	Yes	Yes	2	1/6
GW D4 238	63 A	500 mA	230 V	Yes	Yes	2	1/6
No. of poles: 4P							
GW D4 249	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 250	40 A	500 mA	400 V	Yes	Yes	4	1/3
GW D4 252	63 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 253	63 A	500 mA	400 V	Yes	Yes	4	1/3
GW 94 996 K	100 A	300 mA	400 V	No	No	4	1/3
GW 95 640	125 A	300 mA	400 V	Yes	No	4	1

NEWS

IDP - F Type istantaneous



GW D4 261

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 261	25 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 265	40 A	30 mA	230 V	Yes	Yes	2	1/6
GW D4 269	63 A	30 mA	230 V	Yes	Yes	2	1/6
No. of poles: 4P							
GW D4 281	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 285	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 289	63 A	30 mA	400 V	Yes	Yes	4	1/3
No. of poles: 4P (N-conductor left)							
GW D4 307	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 327	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 347	63 A	30 mA	400 V	Yes	Yes	4	1/3

CHARACTERISTICS: F type presents greater resistance to mains disturbances and atmospheric discharges rn comparison to standard residual current circuit breakers with overcurrent protection. Immunity level 8/20 µs is 3000 A.

IDP - B Type istantaneous



GW D4 539

Residual current circuit breakers



Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 2P							
GW D4 502	25 A	30 mA	230 V	Yes	Yes	4	1/3
GW D4 504	25 A	300 mA	230 V	Yes	Yes	4	1/3
GW D4 507	40 A	30 mA	230 V	Yes	Yes	4	1/3
GW D4 509	40 A	300 mA	230 V	Yes	Yes	4	1/3
GW D4 512	63 A	30 mA	230 V	Yes	Yes	4	1/3
GW D4 514	63 A	300 mA	230 V	Yes	Yes	4	1/3
No. of poles: 4P							
GW D4 527	25 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 529	25 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 532	40 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 534	40 A	300 mA	400 V	Yes	Yes	4	1/3
GW D4 537	63 A	30 mA	400 V	Yes	Yes	4	1/3
GW D4 539	63 A	300 mA	400 V	Yes	Yes	4	1/3

CHARACTERISTICS: type B presents greater resistance to mains disturbances and atmospheric discharges in comparison to standard residual current circuit breakers. Immunity level 8/20 µs is 3000 A.

Socket outlets with residual current protection



GW 95 522

IP21 RCD safety socket outlets - white colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 521	10 mA	16 A	A	230 V	1/2
GW 95 522	30 mA	16 A	A	230 V	1/2

NOTE: RCD socket-outlets can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527 is necessary.



GW 95 524

IP44 RCD safety socket outlets - white colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 523	10 mA	16 A	A	230 V	1/2
GW 95 524	30 mA	16 A	A	230 V	1/2

NOTE: RCD socket-outlets can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527 is necessary.



GW 95 526

IP41 RCD safety unit - white colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 525	10 mA	16 A	A	230 V	1/2
GW 95 526	30 mA	16 A	A	230 V	1/2

NOTE: RCD safety units can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527 is necessary.



GW 95 527

Wall-mounting box - white colour

Code	Outer dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 95 527	80x80x50	6 / 19	117

CHARACTERISTICS: box suitable for all RCD socket-outlets and RCD safety unit types.
NOTE: only for wall-mounting application. The IP protection rating depends on IP of RCD socket-outlet or RCD safety unit chosen.

90 RCD



GW 95 521 N

IP21 RCD safety socket outlets - black colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 521 N	10 mA	16 A	A	230 V	1/2
GW 95 522 N	30 mA	16 A	A	230 V	1/2

NOTE: RCD socket-outlets can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527N is necessary.



GW 95 523 N

IP44 RCD safety socket outlets - black colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 523 N	10 mA	16 A	A	230 V	1/2
GW 95 524 N	30 mA	16 A	A	230 V	1/2

NOTE: RCD socket-outlets can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527N is necessary.



GW 95 525 N

IP41 RCD safety unit - black colour

Code	Idn	Rated current	Type	Rated voltage	Pack Carton
GW 95 525 N	10 mA	16 A	A	230 V	1/2
GW 95 526 N	30 mA	16 A	A	230 V	1/2

NOTE: RCD safety units can be used for flush-mounting or wall-mounting application. Only for wall-mounting application, GW95527N is necessary.



GW 95 527 N

Wall-mounting box - black colour

Code	Outer dim. LxHxD (mm)	Entries No. holes / Ø	Pack Carton
GW 95 527 N	80x80x50	6 / 19	117

CHARACTERISTICS: box suitable for all RCD socket-outlets and RCD safety unit types.
NOTE: only for wall-mounting application. The IP protection rating depends on IP of RCD socket-outlet or RCD safety unit chosen.

NEWS




90 RCD




Scan the QR Code and find out all the technical informations.

A CIRCUIT BREAKER FOR EVERY NEED




The Series 90 RCD meets all the protection requirements against earth leakage in electrical systems with different types of current, from sinusoidal (AC type) and one-way pulse (A type), to variable frequency (F type) and continuous component (B type).

SERVING CONTINUITY



The 90 RCD range also includes IR Reinforced Immunity versions, which are characterised by high resistance to untimely tripping caused by power surges. These versions are particularly suitable in systems where continuity of service is essential.

MAXIMUM PROTECTION IN MINIMUM SPACE



The use of MDC compact residual current circuit breakers reduces the number of modules installed, allowing the installation of smaller, and therefore less costly, enclosures.

Modular accessories





90 AM

Modular accessories

p. 501

90 PV

Products for photovoltaic systems

p. 539

Auxiliaries and accessories for circuit breakers

ELECTRICAL AUXILIARIES FOR CIRCUIT BREAKERS MTC / MT / MTHP / MDC


	Auxiliary contact of open/closed position	Auxiliary contact of fault indicator switch	Adjustable auxiliary contact of fault indicator switch or open/closed position		Shunt trip releases		Under voltage releases (delayed)		
									
Contact rating in AC	6 A (230 V) - 3 A (400 V)			**Rated voltage**	12-48 V ac/dc	110-125 V dc - 110-415 V ac	230 V ac	24 V ac/dc	48 V ac/dc
Contact rating in DC	6 A (24 V) - 2 A (60 V) - 1.5 A (110 V) - 1 A (250 V)			1 mod.	GW 96 011	GW 96 012	GW 96 016	GW 96 017	GW 96 018
Type of contacts	1 changeover								
0.5 mod.	GW 96 001	GW 96 006	GW 96 009						

AUSILIARI ELETTRICI PER INTERRUTTORI DIFFERENZIALI PURI IDP

	Auxiliary contacts of open/closed position			Fault indicator switches		Adjustable auxiliary contact		Shunt trip releases		
										
Suitable for	**IDP 25-80A 2P IDP 25-63A 4P**	**IDP 4P 3 modules**	**IDP 125 A**	**IDP 25-80A 2P IDP 25-63A 4P**	**IDP 4P 3 modules**	**IDP 25-80A 2P IDP 25-63A 4P**	**Suitable for**	**IDP 25-80A 2P IDP 25-63A 4P**	**IDP 25-80A 2P IDP 25-63A 4P**	**IDP 4P 3 modules**
Contact rating in AC	6 A (230 V) 3 A (400 V)	6 A (230 V) 2 A (400 V)	6 A (230 V) 4 A (400 V)	6 A (230 V) 3 A (400 V)	6 A (230 V) 2 A (400 V)	6 A (230 V) 3 A (400 V)	**Rated voltage**	12-48 V ac/dc	110-125 V dc 110-415 V ac	230 V ac
Contact rating in DC	6 A (24 V) - 2 A (60 V) 1.5 A (110 V) - 1 A (250 V)	4 A (24 V) 1 A (110 V)	6 A (24 V) - 3 A (60 V) 1.5 A (110 V) - 1 A (220 V)	6 A (24 V) - 2 A (60 V) 1,5 A (110 V) - 1 A (250 V)	4 A (24 V) 1 A (110 V)	6 A (24 V) - 2 A (60 V) 1,5 A (110 V) - 1 A (250 V)	**0,5 mod.**	-	-	GW 96 015
Type of contacts	1 changeover	1 NO - 1 NC	1 NO - 1 NC	1 changeover	1 NO - 1 NC	1 changeover	**1 mod.**	GW D6 013	GW D6 015	-
0.5 mod.	GW D6 002	GW 96 003	GW 96 008	GW D6 007	GW 96 004	GW D6 010				

ELECTRICAL AUXILIARIES FOR SWITCH DISCONNECTORS WITH ACCESSORY OPTIONS

	Auxiliary contacts of open/closed position		Shunt trip releases		Under voltage releases (delayed)		
							
Contact rating in AC	6 A (230 V) - 3 A (400 V)	**Rated voltage**	12-48 V ac/dc	110-125 V dc - 110-415 V ac	230 V ac	24 V ac/dc	48 V ac/dc
Contact rating in DC	6 A (24 V) - 2 A (60 V) - 1,5 A (110 V) - 1 A (250 V)	**1 mod.**	GW D6 013	GW D6 015	GW D6 019	GW D6 020	GW D6 021
Type of contacts	1 changeover						
0.5 mod.	GW D6 002						

		PIN BUSBARS		FORK BUSBARS		CONNECTION TERMINAL FOR PIN BUSBARS	CLOSING CAPS FOR BUSBARS	TEETH-COVER ROW FOR BUSBARS
								
		12 mod.	**1 metro**	**12 mod.**	**1 metro**			**5 teeth-cover**
For MT/MDC/IDP	1P	GW 96 984	GW 96 988	GW 96 992	GW 96 996	GW 96 961	GW 96 963	GW 96 967
	2P	GW 96 985	GW 96 989	GW 96 993	GW 96 997		GW 96 964	
	3P	GW 96 986	GW 96 990	GW 96 994	GW 96 998		GW 96 965	
	4P	GW 96 987	GW 96 991	GW 96 995	GW 96 999	GW 96 962	GW 96 966	
		13 mod.	**1 metro**					
For MTC	1P (grey)	GW 96 500	-	-		GW 96 503	-	
	1P (blue)	GW 96 501	-	-			-	
	1P (white)	-	GW 96 988	-			-	
		13 mod.						
Type of main: IDP/MDC/MT 2P Type of outgoing: 11 MTC 1P+N/2P		GW 96 507F		-		-	-	

Protection

SURGE PROTECTIVE DEVICES

LST






POP



	TIPO 1+2		TIPO 2				TYPE 1+2	TYPE 2		For telecom and data line	TIPO 2
	1P+N	3P+N	1P		1P+N	3P+N	For photovoltaic applications				1P+N
Imax (kA)	230 Vac	400 Vac	230 Vac	400 Vac	230 Vac	400 Vac	1000 Vdc	600 Vdc	1000 Vdc	50 Vdc	230 Vac
10	-	-	-	-	-	-	-	-	-	GW D6 430 1 mod.	-
15	-	-	-	-	-	-	-	-	-	-	GW D6 461 2 mod.
20	-	-	-	-	GW D6 407 2 mod.	GW D6 409 4 mod.	-	-	-	-	-
40	-	-	GW D6 411 1 mod.	GW D6 413	GW D6 417 2 mod.	GW D6 419 4 mod.	GW D6 429	GW D6 426	GW D6 428	-	-
			GW D6 412* 1 mod.	1 mod.	GW D6 418* 2 mod.	GW D6 420* 4 mod.	3 mod. / Iimp=5kA	3 mod.	3 mod.	-	-
65 (Iimp=12,5kA)	GW D6 401 2 mod.	GW D6 402 4 mod.	-	-	-	-	-	-	-	-	-
100 (Iimp=25kA)	GW D6 404* 4 mod.	GW D6 405* 8 mod.	-	-	-	-	-	-	-	-	-

* With auxiliary

DISCONNECTABLE FUSE-HOLDERS



In (A)	Fuse dim. (mm)	1P	1P+N	2P	3P	3P+N
20	8.3x31.5	GW 96 206 1 mod.	GW 96 216 2 mod.	GW 96 301 2 mod.	GW 96 306 3 mod.	GW 96 311 4 mod.
	10.3x38	GW 96 226* 1 mod.	-	GW 96 227* 2 mod.	-	-
32	10.3x38	GW 96 205 1 mod.	GW 96 215 2 mod.	GW 96 302 2 mod.	GW 96 307 3 mod.	GW 96 312 4 mod.
		-	GW 96 220 1 mod.	-	-	-
50	14x51	GW 96 207 1.5 mod.	GW 96 217 3 mod.	GW 96 303 3 mod.	GW 96 308 4.5 mod.	GW 96 313 6 mod.
100	22x58	-	GW 96 218 4 mod.	-	-	GW 96 314 8 mod.

* For DC applications

MOTOR PROTECTION SWITCHES



In (A)	2.5 mod.
0.1-0.16A	GW D6 501
0.16-0.25A	GW D6 502
0.25-0.4A	GW D6 503
0.4-0.63A	GW D6 504
0.63-1A	GW D6 505
1-1.6A	GW D6 506
1.6-2.5A	GW D6 507
2.5-4A	GW D6 508
4-6.3A	GW D6 509
6.3-10A	GW D6 510
9-14A	GW D6 511
13-18A	GW D6 512
17-23A	GW D6 513
23-27A	GW D6 514
25-32A	GW D6 515

RESIDUAL CURRENT RELAYS WITH SEPARATE TOROID




Type A		Type B	
GW 96 331	3 mod.	GW 96 331 B	3 mod.

+

SEPARATE TOROID FOR RESIDUAL CURRENT RELAYS



Diameter (mm)	In max (A)	Type A	Type B
35	125	GW 96 332	-
	160	-	GW 96 332 B
80	400	GW 96 333	-
	320	-	GW 96 333 B
110	630	GW 96 334	-
	450	-	GW 96 334 B
210	1600	GW 96 335	-
	720	-	GW 96 335 B

Command

SWITCH DISCONNECTORS

AC					AC		DC	
Without accessory option					With accessory option		Without accessory option	
								
	1P	2P	3P	4P	2P	4P	2P	4P
In (A)	1 mod.	2 mod.	3 mod.	4 mod.	2 mod.	4 mod.	3.5 mod.	3.5 mod.
25	-	-	-	-	-	-	GW 96 186	-
32	GW 96 104	GW 96 114	GW 96 124	GW 96 134	-	-	-	GW 96 187
40	GW 96 105	GW 96 115	GW 96 125	GW 96 135	GW 96 182	GW 96 192	-	-
63	GW 96 106	GW 96 116	GW 96 126	GW 96 136	GW 96 183	GW 96 193	-	-
80	GW 96 147	GW 96 157	GW 96 167	GW 96 177	-	GW 96 194	-	-
100	GW 96 148	GW 96 158	GW 96 168	GW 96 178	-	-	-	-
125	GW 96 149	GW 96 159	GW 96 169	GW 96 179	-	-	-	-

ROTARY SWITCHES

Voltmeter switches				Ammeter switch	Line switches		
							
	4 Positions		7 Positions	4 Positions	2 Positions	3 Positions	
						2P	
Characteristics	Phase - Neutral	Phase - Phase	Phase - Phase and Phase - Neutral	-	-	0 central	With 0 return position
In (A)	3 mod.	3 mod.	3 mod.	3 mod.	3 mod.	3 mod.	3 mod.
16	GW 96 851	GW 96 852	GW 96 853	GW 96 856	GW 96 951	GW 96 952	GW 96 953

ISOLATING SWITCHES					ON-OFF SWITCHES		LEVER SWITCHES		
									
	1P	2P	3P	4P	1P	2P	1P	2P	2P (1NO +1NC)
In (A)	1 mod.	1 mod.	1 mod.	1 mod.	1 mod.	1 mod.	1 mod.	1 mod.	1 mod.
16	GW 96 531	GW 96 533	GW 96 535	GW 96 537	GW 96 539	GW 96 541	GW 96 551*	GW 96 552*	GW 96 555***
							GW 96 553**	GW 96 554**	
32	GW 96 532	GW 96 534	GW 96 536	GW 96 538	GW 96 540	GW 96 542	-	-	GW 96 556***

* Change-over switch (1-2) ** 3-way switch (1-0-2) *** 2-way switch (1-2)

INSTALLATION RELAYS RLM



In (A)			16			
Control coil voltage (V)			8 ac	12 ac	24 ac	230 ac
TYPE OF CONTACTS	1 NO	1 mod.	GW D6 601	GW D6 602	GW D6 603	GW D6 604
	2 NO	1 mod.	-	-	-	GW D6 624
	4 NO	2 mod.	-	GW D6 632	GW D6 633	GW D6 634
	1 changeover	1 mod.	GW D6 606	GW D6 608*	GW D6 610*	GW D6 611
	2 changeover	2 mod.	GW D6 626	GW D6 627	GW D6 629*	GW D6 630
	1 NO + 1 NC	1 mod.	-	GW D6 617	GW D6 618	GW D6 619

* Even in DC voltage.

MONITORING RELAYS






Current monitoring relay 1-phase	Phase monitoring relay 3-phase	Under voltage monitoring relay 1-phase AC/DC	Under voltage monitoring relay 3-phase AC
GW 96 906	GW 96 907	GW 96 908	GW 96 909

CONTACTORS CTR



In (A)		20		25		32	40		63	
Control coil voltage (V)		24 ac	230 ac	24 ac/dc	230 ac/dc	12 ac/dc	24 ac/dc	230 ac/dc	24 ac/dc	230 ac/dc
TYPE OF CONTACTS	1 NO	-	GW D6 701 1 mod.	-	-	-	-	-	-	-
	2 NO	GW D6 702 GW D6 741* 1 mod.	GW D6 703 GW D6 742* 1 mod.	GW D6 711 2 mod.	GW D6 712 GW D6 751* 2 mod.	-	-	GW D6 721 3 mod.	-	GW D6 731 3 mod.
	3 NO	-	GW D6 708 2 mod.	-	GW D6 713 GW D6 752* 2 mod.	-	-	GW D6 722 3 mod.	-	GW D6 732 3 mod.
	3 NO + 1 NC	-	-	-	GW D6 718 2 mod.	-	-	-	-	GW D6 735 3 mod.
	4 NO	-	GW D6 709 2 mod.	GW D6 714 GW D6 753* 2 mod.	GW D6 715 GW D6 754* 2 mod.	-	GW D6 723 3 mod.	GW D6 724 3 mod.	GW D6 733 3 mod.	GW D6 734 3 mod.
	2 NC	-	GW D6 705 GW D6 743* 1 mod.	-	-	-	-	-	-	-
	4 NC	-	-	GW D6 716 2 mod.	GW D6 717 2 mod.	-	-	GW D6 726 3 mod.	-	GW D6 736 3 mod.
	1 NO + 1 NC	GW D6 706 1 mod.	GW D6 707 GW D6 744* 1 mod.	-	-	-	-	-	-	-
	2 NO + 2 NC	-	-	-	-	GW D6 755* 2 mod.	-	GW D6 725 3 mod.	-	-

* Manual control contactors

LATCHING RELAY RLB



In (A)			16			
Control coil voltage (V)			8 ac	12 ac	24 ac	230 ac
TYPE OF CONTACTS	1 NO	1 mod.	GW D6 641	GW D6 642	GW D6 643	GW D6 644
	2 NO	1 mod.	-	GW D6 657	GW D6 658	GW D6 659
	4 NO	2 mod.	-	GW D6 667	GW D6 668	GW D6 669
	1 changeover	1 mod.	GW D6 646	GW D6 647	GW D6 648 GW D6 649*	GW D6 650
	2 changeover	2 mod.	-	-	GW D6 663	GW D6 664
	1 NO + 1 NC	1 mod.	-	GW D6 652	GW D6 653	GW D6 654

* DC voltage

LOAD MANAGEMENT RELAY P-COMFORT

			Wired	Zigbee	KNX
					
In (A)			32	32	32
TYPE OF CONTACTS	1 changeover	2 mod.	GW D6 916	GW A1 916	GW A9 916

P-COMFORT - ZIGBEE VERSION

Accessories			Kit	
				
Smart plug (2P+E - 10A)	1-channel actuator	ChoruSmart blank module	No. of Smart plugs	
			1	2
GW A1 526	GW A1 523	GW 1x 750*	GW A1 911	GW A1 912

* GW 10 750: glossy white - GW 12 750: satin black - GW 13 750: satin natural beige - GW 14 750: glossy titanium - GW 15 750: satin white

BIOCOMFORT



In (A)	16
Monitoring voltage (V)	5-230 dc
1 mod.	GW 96 339

90 AM

Programming

TIMERS

					
			Multifunction timer	**Asymmetrical cycle timer**	**Staircase lighting time delay switch**
Rated coil voltage (V)			24-240 ac/dc	12-240 ac/dc	230 ac
Contact rating In (A)			8	8	16
Regulation field			0.05 s - 100 h	0.05 s - 100 h	30 s - 12 min
TYPE OF CONTACTS	**1 changeover**	1 mod.	GW 96 814	GW 96 815	-
	1 NO	1 mod.	-	-	GW 96 809

TIME SWITCHES TMR





Analogue/electromechanical				**Digital**				
GW D6 771	1 NO (daily)	Without charge reserve	1 mod.	GW D6 781	1 NO (daily)	Charge reserve 4 years	-	1 mod.
GW D6 772	1 NO (daily)	Charge reserve 150h	1 mod.	GW D6 782	1 changeover (daily)	Charge reserve 5 years	NFC	2 mod.
GW D6 773	1 changeover (daily)	Charge reserve 150h	2 mod.	GW D6 783	2 changeover (weekly)	Charge reserve 5 years	NFC	2 mod.
GW D6 776	1 changeover (weekly)	Charge reserve 150h	2,5 mod.					

ASTRONOMICAL SWITCHES TMR



Without outdoor probe				
Astronomical switches	GW D6 785	1 changeover	-	2 mod.
	GW D6 786	2 changeover	NFC	2 mod.
Time/ astronomical switches	GW D6 788	1 changeover (weekly)	Bluetooth	2 mod.
	GW D6 789	2 changeover (weekly)	Bluetooth	2 mod.

TWILIGHT SWITCH TMR



With outdoor probe			
GW D6 779	1 NO	1...100 lux	1 mod.

Measurement

VOLTMETERS



Digital		
GW 96 867	0-500V	2 mod.

AMMETERS



Analogue		
GW 96 872	Direct (max 20A)	3 mod.
GW 96 878	Using C.T. / 5A	



Digital		
GW 96 879	Using C.T. (5-999A)	2 mod.

DIGITAL ENERGY METERS



Single-phase				
GW D6 801	40 A	-	-	1 mod.
GW D6 802	40 A	MID	-	
GW D6 803	40 A	MID	Integrated Modbus	



Three-phase				
GW D6 804	Direct (max 80A)	MID	Integrated Modbus	4 mod.
GW D6 805	Using C.T. / 5A	MID	Integrated Modbus	
GW D6 807	Direct (max 80A)	MID	-	
GW D6 809	Using C.T. / 5A	MID	-	

COMMUNICATION INTERFACES



KNX	RS485 MODBUS	LAN-TCP/IP
GW 90 876 1 mod.	GW D6 820 1 mod.	GW D6 821 1 mod.

MEASURING DEVICES



Network analyzer	
GW 96 899	4 mod.



Voltage/Current multimeter	
GW 96 897	2 mod.



Hour counter	
GW D6 911	2 mod.

Signalling

INDICATOR LIGHTS



1 mod.	Un (V)	
LED colour	**12-24-48 ac/dc**	**230 ac**
Red	GW 96 586	GW 96 581
Green	GW 96 587	GW 96 582
Yellow	GW 96 588	GW 96 583
Blue	GW 96 589	GW 96 584
White	GW 96 590	GW 96 585
Double (green/red)	-	GW 96 591
Triple (red/red/red)	-	GW 96 592
Triple (red/green/yellow)	-	GW 96 598

ILLUMINATED PUSH-BUTTONS (WITH LED)



1 mod.		Un (V)	
Type of contact	**LED colour**	**12-24-48 ac/dc**	**230 ac**
1 NO	**Green**	GW 96 570	GW 96 566
1 NC	**Red**	GW 96 571	GW 96 567
1 NO + 1 NC	**Green**	-	GW 96 568
1 NO + 1 NC	**Red**	-	GW 96 569

PUSH-BUTTONS WITHOUT LIGHTING



1 mod.		Un (V)
Type of contact	**Push-button**	**230 ac**
1 NO	**Single**	GW 96 561
1 NC	**Single**	GW 96 562
1 NO + 1 NC	**Single**	GW 96 563
1 NO + 1 NC	**Double (grey/grey)**	GW 96 564
1 NO + 1 NC	**Double (green/red)**	GW 96 565

BELLS AND BUZZERS



Un (V)		12	230
Bells	1 mod.	GW 96 401	-
		-	GW 96 402
	2 mod.	-	GW 96 403
Buzzers	1 mod.	GW 96 406	-
		-	GW 96 407
	2 mod.	-	GW 96 408
Bell + Buzzer + Transformer	2 mod.	-	GW 96 411

BELLS TRANSFORMERS (for discontinuous use)



P (VA)	Secondary voltage (V)		No. of modules
	4 + 8 = 12	**12 + 12 = 24**	
5	GW 96 421	GW 96 422	2 mod.
10	GW 96 423	GW 96 424	
15	GW 96 425	GW 96 426	
30	GW 96 431	GW 96 432	3 mod.
40	GW 96 433	GW 96 434	

SAFETY TRANSFORMERS (for continuous use)



P (VA)	Secondary voltage (V)		No. of modules
	12 + 12 = 24	**24**	
15	GW 96 321	-	3 mod.
25	GW 96 322	-	
40	GW 96 323	-	4 mod.
63	GW 96 324	-	6 mod.
100	-	GW 96 325	8 mod.

90 AM

Modular accessories

The 90 AM range, in addition to auxiliaries common for the all circuit breakers, comprises many modular accessories for the protection, command, programming, measurement and signalling in electrical systems.



AUXILIARIES AND ACCESSORIES FOR MODULAR CIRCUIT BREAKERS

Electrical auxiliaries for circuit breakers MTC / MT / MTHP / MDC



GW 96 001

Auxiliary contact of open/closed position

Code	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW 96 001	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16

APPLICATIONS: signals the position of circuit breaker contacts, when manually open or tripped.
NOTE: up to max. 2 auxiliary contacts can be fitted to each circuit breaker.



GW 96 006

Auxiliary contact of fault indicator switch

Code	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW 96 006	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16

APPLICATIONS: signals the automatic trip of the circuit breaker caused by overloading, short-circuiting or earth leakage.
In the event of manual manoeuvring, it does not indicate the change of position of the contacts.
NOTE: up to max. 2 auxiliary contacts can be fitted to each circuit breaker.



GW 96 009

Adjustable auxiliary contact of fault indicator switch or open/closed position

Code	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW 96 009	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16

APPLICATIONS: using the specific button key, 2 separate functions can be obtained: signalling of automatic trip of the circuit breaker (auxiliary contact of fault indicator switch) or signalling of the circuit breaker contact position (auxiliary contact of position).
NOTE: up to max. 2 auxiliary contacts can be fitted to each circuit breaker.



GW 96 012

Shunt trip releases

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 011	12-48 ac/dc	1	1/8
GW 96 012	110-125 dc 110-415 ac	1	1/8

APPLICATIONS: used for the remote trip of the coupled circuit breaker.
CHARACTERISTICS: minimum operating voltage: 0.7 Vn min. Maximum operating voltage: 1.1 Vn max.
NOTE: up to max. one release (shunt trip or under voltage) can be fitted to each circuit breaker with an auxiliary contact.




GW 96 016

Under voltage releases (delayed)

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 016	230 ac	1	1/8
GW 96 017	24 ac/dc	1	1/8
GW 96 018	48 ac/dc	1	1/8

APPLICATIONS: constantly controls the effective value of the voltage, and trips the coupled circuit breaker when the voltage falls below its minimum value.
The 300 ms delay allows any tiny blackouts to be avoided, preventing the untimely tripping of circuit breaker.
NOTE: up to max. one release (shunt trip or under voltage) can be fitted to each circuit breaker with an auxiliary contact.

Accessories for circuit breakers MTC / MT / MTHP / MDC



GW 96 022

Sealable screw caps

Code	Suitable for	No. of pieces	Pack Carton
GW 96 022	MTC/MT/MDC	1	10/100
GW 96 026	MTHP/BDHP	1	10/100

APPLICATIONS: allows for sealing of terminal screws, preventing access to cable connections.
NOTE: with 1 piece of the GW96022 è it is possible to seal 2 modules, upper or lower, of the MTC, MT and MDC circuit breakers.
With 1 piece of the GW96026 è It is possible to seal 1 module, upper or lower, of the MTHP and BDHP circuit breakers.



GW 96 042

Pole separator

Code	Suitable for	Pack Carton
GW 96 042	MT/MDC	10/100

Electrical auxiliaries for RCCBs IDP

Auxiliary contacts for open/closed position



GW D6 002

Code	Suitable for	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW D6 002	IDP 25-80A 2P / IDP 25-63A 4P	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16
GW 96 003	IDP 4P - 3 modules	6 A (230 V) 2 A (400 V)	4 A (24 V) 1 A (110 V)	1 NO - 1 NC	0.5	1/12
GW 96 008	IDP 125 A	6 A (230 V) 4 A (400 V)	-	2 NO	0.5	1

APPLICATIONS: signals the position of circuit breaker contacts, when manually open or tripped.

Fault indicator switch



GW D6 007

Code	Suitable for	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW D6 007	IDP 25-80A 2P / IDP 25-63A 4P	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16
GW 96 004	IDP 4P - 3 modules	6 A (230 V) 2 A (400 V)	4 A (24 V) 1 A (110 V)	1 NO - 1 NC	0.5	1/12

APPLICATIONS: indicates the automatic trip of the circuit breaker due to an earth leakage. In the event of manual manoeuvring, it does not indicate the change of position of the contacts.

Adjustable auxiliary contact or fault indicator switch



GW D6 010

Code	Suitable for	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW D6 010	IDP 25-80A 2P / IDP 25-63A 4P	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16

APPLICATIONS: using the specific button key, 2 separate functions can be obtained: signalling of automatic trip of the circuit breaker (auxiliary contact of fault indicator switch) or signalling of the circuit breaker contact position (auxiliary contact of position).
NOTE: they cannot be used with 4P RCCBs in 3 modules.

Shunt trip releases



GW D6 015

Code	Suitable for	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 013	IDP 25-80A 2P / IDP 25-63A 4P	12-48 ac/dc	1	1/8
GW D6 015	IDP 25-80A 2P / IDP 25-63A 4P	110-125 dc 110-415 ac	1	1/8
GW 96 015	IDP 4P - 3 modules	230 ac	0.5	1/12

APPLICATIONS: used for the remote trip of the coupled circuit breaker.
CHARATERISTICS: minimum operating voltage: 0.7 Vn min. maximum operating voltage: 1.1 Vn max.

Accessories for RCCB's - IDP

Couple of sealable screw caps



GW D6 026

Code	Suitable for	Pack Carton
GW D6 026	IDP 25-80A 2P	1/50
GW D6 027	IDP 25-63A 4P	1/10
GW 96 038	IDP 4P - 3 modules	1/10

NEWS

Electrical auxiliaries for switch disconnectors with accessory option



GW D6 002

Auxiliary contact of open/closed position

Code	Contact rating in AC	Contact rating in DC	Type of contacts	No. of modules EN 50022	Pack Carton
GW D6 002	6 A (230 V) 3 A (400 V)	6 A (24 V) 2 A (60 V) 1.5 A (110 V) 1 A (250 V)	1 Changeover	0.5	1/16

APPLICATIONS: signals the position of switch disconnector contacts, when manually open.



GW D6 015

Shunt trip releases

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 013	12-48 ac/dc	1	1/8
GW D6 015	110-125 dc 110-415 ac	1	1/8

APPLICATIONS: used for the remote trip of the coupled switch disconnector.
CHARATERISTICS: minimum operating voltage: 0.7 Vn min. maximum operating voltage: 1.1 Vn max.
NOTES: up to max. one release (shunt trip or undervoltage) can be fitted to each switch disconnector with one auxiliary contact.



GW D6 019

Under voltage releases (delayed)

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 019	230 ac	1	1/8
GW D6 020	24 ac/dc	1	1/8
GW D6 021	48 ac/dc	1	1/8

APPLICATIONS: constantly controls the effective value of the voltage, and trips the coupled switch disconnector when the voltage falls below its minimum value. The 300 ms delay allows any momentary voltage drops to be avoided, preventing th e untimely tripping of switch disconnector.
NOTE: up to max. one release (shunt trip or undervoltage) can be fitted to each switch disconnector with an auxiliary contact.

Accessories for switch disconnectors with accessory options

GW D6 026

Couple of sealable screw caps

Code	Suitable for	Pack Carton
GW D6 026	2P isolators	1/50
GW D6 027	4P isolators	1/10

Accessories for modular circuit breakers



GW 96 041

Padlocking lever block

Code	Suitable for	Pack Carton
GW 96 041	MTC/MT/MTHP/MDC/IDP/Switch disconnectors	10/100

APPLICATIONS: to lock the control lever in "ON" or "OFF" positions. For padlocks max Ø 5 mm.

GW D6 766

Spacer insert

Code	No. of modules EN 50022	Pack Carton
GW D6 766	0.5	12

CHARACTERISTICS: it reduces heating when modular devices are installed side-by-side and it allows crossing of wiring cables.

APPLICATIONS: it's suggested the use of spacer insert to separate the elettromechanical devices (e.g. circuit breakers, contactors, latching relays etc...) from electronic devices (e.g. time switches etc...) for optimum operation.

BUSBARS

Monobloc busbars

Monobloc busbars 2P

Code	Type of main	Type of outgoing	Rated current	Pack Carton
Length: 13 modules				
GW 96 507 F	IDP/MDC/MT 2P	11 MTC 1P+N/2P	63 A	1/10

ACCESSORY SUPPLIED: closing plug (to be used only if the busbar is cut); plumbable screw caps with an adhesive indicating voltage presence.
APPLICATIONS: busbars indicated for domestic enclosures.



GW 96 507 F

Busbars for circuit breakers MTC

Pin busbars

Code	Type	Colour	Rated current	Pack Carton
Length: 13 modules				
GW 96 500	1P	Grey	80 A	25
GW 96 501	1P	Blue	80 A	25
Length: 1 meter (56 modules)				
GW 96 988	1P	White	63 A	50

NOTE: not compatible with GW96963 end caps.



GW 96 500

Busbars for circuit breakers MT / MDC / IDP

Pin busbars

Code	Type	Rated current	Pack Carton
Length: 12 modules			
GW 96 984	1P	63 A	50
GW 96 985	2P	63 A	25
GW 96 986	3P	63 A	25
GW 96 987	4P	80 A	20
Length: 1 meter (56 modules)			
GW 96 988	1P	63 A	50
GW 96 989	2P	63 A	20
GW 96 990	3P	63 A	20
GW 96 991	4P	80 A	15

NOTES: 12 module versions complete with end caps.
The 1P versions are not compatible with GW96963 end caps.
Busbars are suitable also for modular switch-disconnectors with red lever.



GW 96 984

Fork busbars

Code	Type	Rated current	Pack Carton
Length: 12 modules			
GW 96 992	1P	63 A	50
GW 96 993	2P	63 A	25
GW 96 994	3P	63 A	25
GW 96 995	4P	80 A	20
Length: 1 meter (56 modules)			
GW 96 996	1P	63 A	50
GW 96 997	2P	63 A	20
GW 96 998	3P	63 A	20
GW 96 999	4P	80 A	15

NOTES: 12 module versions complete with end caps.
Busbars are suitable also for modular switch-disconnectors with red lever.



GW 96 992

Wiring components



GW 96 962

Connection terminals for pin busbars

Code	Suitable for	Type	Length (mm)	Conductors section (mm^2)	Pack Carton
GW 96 503	1P busbar for MTC	-	-	25	50
GW 96 961	1P, 2P, 3P busbar for MT/MDC/IDP	Short	14	25	50
GW 96 962	4P busbar for MT/MDC/IDP	Long	27	25	50



GW 96 963

Closing caps for busbars

Code	Type	Pack Carton
GW 96 963	1P	10
GW 96 964	2P	10
GW 96 965	3P	10
GW 96 966	4P	10

APPLICATIONS: to isolate the ends of the connection busbars.

NOTE: code GW96963 is not compatible with push rod 1P busbars.



GW 96 967

Teeth-cover row for busbars

Code	No. teeth-cover	Pack Carton
GW 96 967	5	10

APPLICATIONS: to insulate the unused busbar teeth.

PROTECTION

Disconnectable fuse-holders



GW 96 312

Disconnectable fuse-holders



Code	Rated current	Fuse dimension (mm)	No. of modules EN 50022	Rated voltage	Pack Carton
No. of poles: 1P					
GW 96 206	20 A	8.5x31.5	1	400 V ac	12
GW 96 226	20 A	10.3x38	1	1000 V dc	12
GW 96 205	32 A	10.3x38	1	690 V ac	12
GW 96 207	50 A	14x51	1.5	690 V ac	12
No. of poles: 1P+N					
GW 96 216	20 A	8.5x31.5	2	400 V ac	6
GW 96 220	32 A	10.3x38	1	690 V ac	12
GW 96 215	32 A	10.3x38	2	690 V ac	6
GW 96 217	50 A	14x51	3	690 V ac	6
GW 96 218	100 A	22x58	4	690 V ac	2
No. of poles: 2P					
GW 96 301	20 A	8.5x31.5	2	400 V ac	6
GW 96 227	20 A	10.3x38	2	1000 V dc	6
GW 96 302	32 A	10.3x38	2	690 V ac	6
GW 96 303	50 A	14x51	3	690 V ac	6
No. of poles: 3P					
GW 96 306	20 A	8.5x31.5	3	400 V ac	4
GW 96 307	32 A	10.3x38	3	690 V ac	4
GW 96 308	50 A	14x51	4.5	690 V ac	4
No. of poles: 3P+N					
GW 96 311	20 A	8.5x31.5	4	400 V ac	3
GW 96 312	32 A	10.3x38	4	690 V ac	3
GW 96 313	50 A	14x51	6	690 V ac	3
GW 96 314	100 A	22x58	8	690 V ac	1

APPLICATIONS: protection against low voltage overcurrents in industrial and advanced tertiary application in case of high short-circuit currents.
NOTES: the products GW96226 and GW96227 are suitable for the protection and isolation of the photovoltaic strings too (Utilization category DC20B)

Fuses



GW 72 105

Cylindrical fuses - Type GG

Code	Rated current	Rated voltage AC	Breaking capacity AC	Pack Carton
Dimensions (mm): Ø 8.5 x 31.5				
GW 72 111	2 A	400 V	50 kA	10/100
GW 72 112	4 A	400 V	50 kA	10/100
GW 72 113	6 A	400 V	50 kA	10/100
GW 72 114	10 A	400 V	50 kA	10/100
GW 72 115	16 A	400 V	50 kA	10/100
GW 72 116	20 A	400 V	50 kA	10/100
GW 72 117	25 A	400 V	50 kA	10/100
Dimensions (mm): Ø 10.3 x 38				
GW 72 104	2 A	500 V	120 kA	10/100
GW 72 105	6 A	500 V	120 kA	10/100
GW 72 107	10 A	500 V	120 kA	10/100
GW 72 101	16 A	500 V	120 kA	10/100
GW 72 108	20 A	500 V	120 kA	10/100
GW 72 109	25 A	500 V	120 kA	10/100
GW 72 110	32 A	400 V	120 kA	10/100
Dimensions (mm): Ø 14 x 51				
GW 72 121	25 A	690 V	80 kA	10/100
GW 72 122	32 A	500 V	80 kA	10/100
GW 72 123	40 A	500 V	80 kA	10/100
GW 72 124	50 A	400 V	80 kA	10/100
Dimensions (mm): Ø 22 x 58				
GW 72 103	63 A	690 V	80 kA	10/30

NOTE: fast fuse type.

Cylindrical fuses - Type GPV



GW 72 131

Code	Rated current	Rated voltage DC	Breaking capacity DC	Pack Carton
Dimensions (mm): Ø 10.3 x 38				
GW 72 131	6 A	1000 V	30 kA	10
GW 72 132	8 A	1000 V	30 kA	10
GW 72 133	10 A	1000 V	30 kA	10
GW 72 134	12 A	1000 V	30 kA	10
GW 72 135	16 A	1000 V	30 kA	10
GW 72 136	20 A	1000 V	30 kA	10

APPLICATIONS: photovoltaic systems.

Motor protection switches



GW D6 509

Motor protection switches SMT

Code	Operating current	Max operating voltage (V)	No. of modules EN 50022	Pack Carton
No. of poles: 3P				
GW D6 501	0.1 - 0.16 A	690 ac	2.5	1
GW D6 502	0.16 - 0.25 A	690 ac	2.5	1
GW D6 503	0.25 - 0.4 A	690 ac	2.5	1
GW D6 504	0.4 - 0.63 A	690 ac	2.5	1
GW D6 505	0.63 - 1 A	690 ac	2.5	1
GW D6 506	1 - 1.6 A	690 ac	2.5	1
GW D6 507	1.6 - 2.5 A	690 ac	2.5	1
GW D6 508	2.5 - 4 A	690 ac	2.5	1
GW D6 509	4 - 6.3 A	690 ac	2.5	1
GW D6 510	6.3 - 10 A	690 ac	2.5	1
GW D6 511	9 - 14 A	690 ac	2.5	1
GW D6 512	13 - 18 A	690 ac	2.5	1
GW D6 513	17 - 23 A	690 ac	2.5	1
GW D6 514	20 - 27 A	690 ac	2.5	1
GW D6 515	25 - 32 A	690 ac	2.5	1

APPLICATIONS: protection of electric motors both in single-phase and 3-phase distribution.

CHARACTERISTICS: fixed tripping magnetic threshold, adjustable thermal. Lockable to block the operating push button in "OFF" position. For padlocks Ø5 mm max.

NOTE: up to a maximum of 2 accessories consisting of 1 auxiliary contact and 1 opening release (shunt trip or undervoltage) can be assembled on each motor protection switch.

NEWS

Accessories for motor protection switches SMT



GW D6 516

Auxiliary contact for motor protection switches

Code	Contacts Description	No. of contacts	Type of contacts	No. of modules EN 50022	Pack Carton
GW D6 516	Position	2	1NO + 1NC	0.5	1



GW D6 517

Shunt trip release for motor protection switches

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 517	230 ac	1	1
GW D6 518	400 ac	1	1



GW D6 519

Under voltage release for motor protection switches

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 519	230 ac	1	1
GW D6 520	400 ac	1	1


NEWS

Surge protective devices LST

Surge protective devices type 1+2



GW D6 405




Code	Impulse current	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
No. of poles: 1P+N						
GW D6 401	12.5 kA	65 kA	230 V	2	No	1
GW D6 404	25 kA	100 kA	230 V	4	Yes	1
No. of poles: 3P+N						
GW D6 402	12.5 kA	65 kA	400 V	4	No	1
GW D6 405	25 kA	100 kA	400 V	8	Yes	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.

Surge protective devices type 2



GW D6 420



Code	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
No. of poles: 1P					
GW D6 411	40 kA	230 V	1	No	1
GW D6 412	40 kA	230 V	1	Yes	1
GW D6 413	40 kA	400 V	1	No	1
No. of poles: 1P+N					
GW D6 407	20 kA	230 V	2	No	1
GW D6 417	40 kA	230 V	2	No	1
GW D6 418	40 kA	230 V	2	Yes	1
No. of poles: 3P+N					
GW D6 409	20 kA	400 V	4	No	1
GW D6 419	40 kA	400 V	4	No	1
GW D6 420	40 kA	400 V	4	Yes	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.

Surge protective devices for photovoltaic applications



GW D6 426



Code	Impulse current	Maximum discharge current	Rated voltage DC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
Type: 1+2						
GW D6 429	5 kA	40 kA	1000 V	3	No	1/4
Type: 2						
GW D6 426	-	40 kA	600 V	3	No	1
GW D6 428	-	40 kA	1000 V	3	No	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.

Surge protective devices for telecom and dataline



GW D6 430



Code	Maximum discharge current	Rated voltage AC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
GW D6 430	10 kA	50 V	1	No	1

NEWS



GW D6 433

Extractable spare cartridges for LST type 1+2

Code	Type	Impulse current	Pack Carton
Suitable for: GWD6401 and GWD6402			
GW D6 451	Phase	12.5 kA	1
GW D6 452	Neutral	25 kA	1
GW D6 453	Neutral	50 kA	1
Suitable for: GWD6404 and GWD6405			
GW D6 433	Phase	25 kA	1
GW D6 434	Neutral	50 kA	1
GW D6 435	Neutral	100 kA	1

CHARACTERISTICS: a fissure on the base of the surge protection devices will help you to insert the cartridges, and prevents the insertion of the phase cartridge in place of the neutral one, or viceversa.



GW D6 436

Extractable spare cartridges for LST type 2

Code	Type	Maximum discharge current	Rated voltage	Pack Carton
Suitable for: from GWD6407 to GWD6420				
GW D6 436	Phase	20 kA	230 V ac	1
GW D6 438	Neutral	20 kA	-	1
GW D6 441	Phase	40 kA	230 V ac	1
GW D6 442	Phase	40 kA	400 V ac	1
GW D6 443	Neutral	40 kA	-	1

CHARACTERISTICS: a fissure on the base of the surge protection devices will help you to insert the cartridges, and prevents the insertion of the phase cartridge in place of the neutral one, or viceversa.



GW D6 446

Extractable spare cartridges for LST for photovoltaic applications

Code	Impulse current	Maximum discharge current	Rated voltage	Pack Carton
Suitable for: GWD6429				
GW D6 449	5 kA	40 kA	1000 V dc	1
Suitable for: GWD6426 and GWD6428				
GW D6 446	-	40 kA	600 V dc	1
GW D6 448	-	40 kA	1000 V dc	1

Permanent and transient surge protective device POP



GW D6 461

Combined SPD+POP

Code	Type of SPD	SPD Maximum discharge current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 1P+N					
GW D6 461	Type 2	15 kA	230 V	2	1/6

NOTES: it is necessary to use a MCB and a shunt trip release for correct working of the device

APPLICATIONS: protection of single-phase electrical system both from voltage transients indirect (produced by discharges from lightning or switching operations on the network) to permanent overvoltages (produced by instable networks or neutral loss). When permanent overvoltages occurs, SPD+POP devices use release coil to open circuit breaker. Instead, when transient overvoltages occurs, SPD+POP device works as a common surge protective device without opening the circuit breaker.

NEWS

Residual current relay type A with separate toroid



GW 96 331

Residual current relay type A with separate toroid

Code	Rated voltage (V)	Type	No. of modules EN 50022	Pack Carton
GW 96 331	230 ac	A	3	1/4

CHARACTERISTICS: the tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0,03 - 0,1 - 0,3 - 0,5 - 1 - 1,5 - 2 - 3 - 5 - 10 - 20 - 30.
dt (s): 0 - 0.25 - 0.5 - 1 - 2 - 3 - 4 - 5 - 6 - 7 - 8 - 10.
NOTE: mounting on DIN rail EN 50022. For the operation of the residual current protection, it is necessary to use: the residual current relay, a suitable toroid, and a release for the associated circuit breaker.



GW 96 332

Separate toroid for residual current relay GW96331

Code	Description	Internal diameter	Operating current Imax	Maximum wire section (3F+N)	Minimum Idn threshold	Pack Carton
GW 96 332	Solid-core toroid	35 mm	160 A	16 mm²	30 mA	1
GW 96 333	Solid-core toroid	80 mm	400 A	70 mm²	30 mA	1
GW 96 334	Solid-core toroid	110 mm	630 A	100 mm²	100 mA	1
GW 96 335	Solid-core toroid	210 mm	1600 A	2x185 mm²	300 mA	1

NOTE: The Imax operating current is the maximum current value that can circulate through the toroid when the set of cables is positioned in the centre, perpendicularly, and occupies less than 60% of the toroid's diameter.

Residual current relay type B with separated toroid



GW 96 331 B

Residual current relay type B with separated toroid

Code	Rated voltage (V)	Type	No. of modules EN 50022	Pack Carton
GW 96 331 B	230 ac	B	3	1

CHARACTERISTICS: the tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0,03 - 0,1 - 0,3 - 0,5 - 1 - 3 - 5 - 10.
dt (s): 0,1 - 0,2 - 0,3 - 0,4 - 0,5 - 0,75 - 1 - 5 - 10.
NOTE: mounting on DIN rail EN 50022. For the operation of the residual current protection, it is necessary to use: the residual current relay, a suitable toroid, and a release for the associated circuit breaker.



GW 96 332 B

Separate toroid for residual current relay GW96331B

Code	Description	Internal diameter	Operating current Imax	Maximum wire section (3F+N)	Minimum Idn threshold	Pack Carton
GW 96 332 B	Solid-core toroid	35 mm	160 A	16 mm²	30 mA	1
GW 96 333 B	Solid-core toroid	80 mm	320 A	70 mm²	30 mA	1
GW 96 334 B	Solid-core toroid	110 mm	450 A	100 mm²	100 mA	1
GW 96 335 B	Solid-core toroid	210 mm	720 A	2x185 mm²	300 mA	1

NOTE: The Imax operating current is the maximum current value that can circulate through the toroid when the set of cables is positioned in the centre, perpendicularly, and occupies less than 60% of the toroid's diameter.

NEWS

COMMAND

Switch disconnectors (EN 60947-3)



GW 96 193

AC switch disconnectors, with accessory option



Code	Rated current	Rated voltage AC	Accessorisable with auxiliary contacts	Accessorisable with opening releases	No. of modules EN 50022	Pack Carton
No. of poles: 2P						
GW 96 182	40 A	415 V	Yes	Yes	2	1/6
GW 96 183	63 A	415 V	Yes	Yes	2	1/6
No. of poles: 4P						
GW 96 192	40 A	415 V	Yes	Yes	4	1/3
GW 96 193	63 A	415 V	Yes	Yes	4	1/3
GW 96 194	80 A	415 V	Yes	Yes	4	1/3

NOTES: can be combined with GWD6002 open/closed position auxiliary contact, with shunt trip release (GWD6013, GWD6015) and undervoltage release (GWD6019, GWD6020, GWD6021). Up to a maximum of 2 accessories consisting of 1 auxiliary contact and 1 opening release (shunt trip or undervoltage) can be assembled on each switch disconector. Lockable with accessory GW96041 to block the operating lever in either the "ON" or "OFF" position. For padlocks Ø5 mm max.



GW 96 134

AC switch disconnectors, without accessory option



Code	Rated current	Rated voltage AC	Accessorisable with auxiliary contacts	Accessorisable with opening releases	No. of modules EN 50022	Pack Carton
No. of poles: 1P						
GW 96 104	32 A	240 V	Yes	No	1	6/24
GW 96 105	40 A	240 V	Yes	No	1	6/24
GW 96 106	63 A	240 V	Yes	No	1	6/24
GW 96 147	80 A	240 V	Yes	No	1	6/24
GW 96 148	100 A	240 V	Yes	No	1	6/24
GW 96 149	125 A	240 V	Yes	No	1	6/24
No. of poles: 2P						
GW 96 114	32 A	415 V	Yes	No	2	3/12
GW 96 115	40 A	415 V	Yes	No	2	3/12
GW 96 116	63 A	415 V	Yes	No	2	3/12
GW 96 157	80 A	415 V	Yes	No	2	3/12
GW 96 158	100 A	415 V	Yes	No	2	3/12
GW 96 159	125 A	415 V	Yes	No	2	3/12
No. of poles: 3P						
GW 96 124	32 A	415 V	Yes	No	3	2/8
GW 96 125	40 A	415 V	Yes	No	3	2/8
GW 96 126	63 A	415 V	Yes	No	3	2/8
GW 96 167	80 A	415 V	Yes	No	3	2/8
GW 96 168	100 A	415 V	Yes	No	3	2/8
GW 96 169	125 A	415 V	Yes	No	3	2/8
No. of poles: 4P						
GW 96 134	32 A	415 V	Yes	No	4	1/3
GW 96 135	40 A	415 V	Yes	No	4	1/3
GW 96 136	63 A	415 V	Yes	No	4	1/3
GW 96 177	80 A	415 V	Yes	No	4	1/3
GW 96 178	100 A	415 V	Yes	No	4	1/3
GW 96 179	125 A	415 V	Yes	No	4	1/3

NOTES: Can ONLY be accessorised with an auxiliary open/closed position contact GW96001.



GW 96 187

DC rotary switch disconnectors

Code	No. of poles	Rated current	Rated voltage DC	No. of modules EN 50022	Pack Carton
GW 96 186	2P	25 A	600 V	3.5	1
GW 96 187	4P	32 A	1000 V	3.5	1

NOTE: utilisation category DC21B. These switch disconnectors cannot be combined.

Isolating switches (EN 60669-2-4)



GW 96 538

Compact isolating switches



Code	Rated current	No. of modules EN 50022	Rated voltage	Pack Carton
No. of poles: 1P				
GW 96 531	16 A	1	250 V	3/12
GW 96 532	32 A	1	250 V	3/12
No. of poles: 2P				
GW 96 533	16 A	1	250 - 415 V	3/12
GW 96 534	32 A	1	250 - 415 V	3/12
No. of poles: 3P				
GW 96 535	16 A	1	250 - 415 V	1/12
GW 96 536	32 A	1	250 - 415 V	1/12
No. of poles: 4P				
GW 96 537	16 A	1	250 - 415 V	1/12
GW 96 538	32 A	1	250 - 415 V	1/12

On-Off switches



GW 96 542

On-off switches with indicator lamp



Code	Rated current	Characteristics	No. of modules EN 50022	Rated voltage	Pack Carton
No. of poles: 1P					
GW 96 539	16 A	With red indicator lamp	1	230 V	3/12
GW 96 540	32 A	With red indicator lamp	1	230 V	1/12
No. of poles: 2P					
GW 96 541	16 A	With red indicator lamp	1	230 V	1/12
GW 96 542	32 A	With red indicator lamp	1	230 V	1/12

ACCESSORIES SUPPLIED: indicator light with LED.

NOTE: they can be padlocked with the accessory GW96041, to lock the operating lever in either the "ON" or "OFF" position. For padlocks with max Ø 5 mm.

Lever switches



GW 96 554

Lever switches



Code	Rated current	No. of poles	No. of modules EN 50022	Rated voltage	Pack Carton
Type: Change-over switch (1-2)					
GW 96 551	16 A	1P	1	250 V	3/12
GW 96 552	16 A	2P	1	250 V	1/12
Type: Three-way switch (1-0-2)					
GW 96 553	16 A	1P	1	250 V	3/12
GW 96 554	16 A	2P	1	250 V	1/12
Type: Two-ways switch (1-2)					
GW 96 555	16 A	2P (1NO+1NC)	1	250 V	3/12
GW 96 556	32 A	2P (1NO+1NC)	1	250 V	1/12

NOTE: they can be padlocked with the accessory GW96041, to lock the operating lever in either the "ON" or "OFF" position. For padlocks with max Ø 5 mm.

Rotary Switches



GW 96 851

Voltmeter switches

Code	Description	Characteristics	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
GW 96 851	4 positions	Phase - Neutral	16 A	690 V	3	1/4
GW 96 852	4 positions	Phase - Phase	16 A	690 V	3	1/4
GW 96 853	7 positions	Phase - Phase and Phase - Neutral	16 A	690 V	3	1/4



GW 96 856

Ammeter switch


Code	Description	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
GW 96 856	4 positions	16 A	690 V	3	1/4

NOTES: the GW96856 can also be used as a single-pole command three-way switch with 4 positions.



GW 96 951

Line switches



Code	Description	Characteristics	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P						
GW 96 951	2 positions	-	16 A	690 V	3	1/4
GW 96 952	3 positions	0 central	16 A	690 V	3	1/4
GW 96 953	3 positions	With 0 return position	16 A	690 V	3	1/4

APPLICATIONS: DIN rail three-way switches usable for motor, pump and fan command.

Contactors CTR



GW D6 703

Contactors



Code	Contacts	Control coil voltage (V)	No. of modules EN 50022	Pack Carton
Rated current (AC-1/AC-7a): 20 A - CTR20				
GW D6 701	1NO	230 ac	1	6/24
GW D6 702	2NO	24 ac	1	6/24
GW D6 703	2NO	230 ac	1	6/24
GW D6 705	2NC	230 ac	1	6/24
GW D6 706	1NO+1NC	24 ac	1	6/24
GW D6 707	1NO+1NC	230 ac	1	6/24
GW D6 708	3NO	230 ac	2	3/12
GW D6 709	4NO	230 ac	2	3/12
Rated current (AC-1/AC-7a): 25 A - CTR25				
GW D6 711	2NO	24 ac/dc	2	3/12
GW D6 712	2NO	230 ac - 220 dc	2	3/12
GW D6 713	3NO	230 ac - 220 dc	2	3/12
GW D6 714	4NO	24 ac/dc	2	3/12
GW D6 715	4NO	230 ac - 220 dc	2	3/12
GW D6 716	4NC	24 ac/dc	2	3/12
GW D6 717	4NC	230 ac - 220 dc	2	3/12
GW D6 718	3NO+1NC	230 ac - 220 dc	2	3/12
Rated current (AC-1/AC-7a): 40 A - CTR40				
GW D6 721	2NO	230 ac - 220 dc	3	2/8
GW D6 722	3NO	230 ac - 220 dc	3	2/8
GW D6 723	4NO	24 ac/dc	3	2/8
GW D6 724	4NO	230 ac - 220 dc	3	2/8
GW D6 725	2NO+2NC	230 ac - 220 dc	3	2/8
GW D6 726	4NC	230 ac - 220 dc	3	2/8
Rated current (AC-1/AC-7a): 63 A - CTR63				
GW D6 731	2NO	230 ac - 220 dc	3	2/8
GW D6 732	3NO	230 ac - 220 dc	3	2/8
GW D6 733	4NO	24 ac/dc	3	2/8
GW D6 734	4NO	230 ac - 220 dc	3	2/8
GW D6 735	3NO+1NC	230 ac - 220 dc	3	2/8
GW D6 736	4NC	230 ac - 220 dc	3	2/8



GW D6 742

Manual control contactors

Code	Contacts	Control coil voltage (V)	No. of modules EN 50022	Pack Carton
Rated current (AC-1/AC-7a): 20 A - CTRM20				
GW D6 741	2NO	24 ac	1	6/24
GW D6 742	2NO	230 ac	1	6/24
GW D6 743	2NC	230 ac	1	6/24
GW D6 744	1NO+1NC	230 ac	1	6/24
Rated current (AC-1/AC-7a): 25 A - CTRM25				
GW D6 751	2NO	230 ac - 220 dc	2	3/12
GW D6 752	3NO	230 ac - 220 dc	2	3/12
GW D6 753	4NO	24 ac/dc	2	3/12
GW D6 754	4NO	230 ac - 220 dc	2	3/12
Rated current (AC-1/AC-7a): 32 A - CTRM32				
GW D6 755	2NO+2NC	12 ac/dc	2	3/12

APPLICATIONS: they have a three positions built-in toggle handle switch (A - O - I) to enable permanent opening or closing manually leaving out normal contactor function

Position A: working as normal contactor

Position O: working as manual control contactor (contacts locked mechanically)

Position I: working as manual control contactor (contacts are switched without control coil voltage). When coil is energized the toggle handle switch is automatically set to position A maintaining the previuos contacts status.

CHARACTERISTICS: they can be combined with auxiliary contacts and sealing terminal covers

NOTE: it's suggested the use of a spacer insert between adjacent contactors to ensure optimum operation.

Installation relays RLM



GW D6 604

Installation relay 16 A



Code	Contacts	Control coil voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 601	1NO	8 ac	1	6/24
GW D6 602	1NO	12 ac	1	6/24
GW D6 603	1NO	24 ac	1	6/24
GW D6 604	1NO	230 ac	1	6/24
GW D6 606	1 Changeover	8 ac	1	6/24
GW D6 608	1 Changeover	12 ac/dc	1	6/24
GW D6 610	1 Changeover	24 ac/dc	1	6/24
GW D6 611	1 Changeover	230 ac	1	6/24
GW D6 617	1NO+1NC	12 ac	1	6/24
GW D6 618	1NO+1NC	24 ac	1	6/24
GW D6 619	1NO+1NC	230 ac	1	6/24
GW D6 624	2NO	230 ac	1	6/24
GW D6 626	2 Changeover	8 ac	2	3/12
GW D6 627	2 Changeover	12 ac	2	3/12
GW D6 629	2 Changeover	24 ac/dc	2	3/12
GW D6 630	2 Changeover	230 ac	2	3/12
GW D6 632	4NO	12 ac	2	3/12
GW D6 633	4NO	24 ac	2	3/12
GW D6 634	4NO	230 ac	2	3/12

CHARACTERISTICS: relay with single stable state; the contacts are maintained in switched position only while the control coil is supplied. they can be combined with auxiliary contacts (except for GWD6608 e GWD6610) and sealing terminal covers.

APPLICATION: command of low voltage circuits with high number of switchovers (lighting, heating and ventilation systems). they have a three positions built-in toggle handle switch (A - O - I) to enable permanent opening or closing manually independently of the external commands:

Position A: automatic operation as a momentary relay.

Position O: operation as a manually commanded momentary relay (contacts locked mechanically in the rest state).

Position I: operation as a manually commanded momentary relay (contacts switched without the need for a remote control with return to automatic on A as soon as the lever is released).

Accessories for CTR contactors and RLM installation relays



GW D6 761

Auxiliary contacts

Code	Contacts	Contact rating in AC-15	No. of modules EN 50022	Pack Carton
GW D6 761	2NO	6 A (230 V) 4 A (400 V)	0.5	1/12
GW D6 762	1NO+1NC	6 A (230 V) 4 A (400 V)	0.5	1/12

APPLICATION: used in order to signal the contacts position (open or closed).

NOTE: each device can be associated with 1 auxiliary contact. Auxiliary contacts cannot be coupled with GWD6608 and GWD6610 installation relays.

GW D6 766

Spacer insert

Code	No. of modules EN 50022	Pack Carton
GW D6 766	0.5	12

APPLICATIONS: used in order to have a better heat dissipation when more contactors/relay are installed in adjacent position.

SUGGESTIONS FOR AN OPTIMAL HEAT DISSIPATION:

- Room temperature up to 40°C: 1 spacer every 3 side-by-side devices.
- Room temperature between 40°C and 55°C: 1 spacer every 2 side-by-side devices.



GW D6 764

Sealing terminal covers

Code	Suitable for contactor	No. of pieces	Pack Carton
GW D6 763	1 mod. width	2	1/10
GW D6 764	2 mod. width	2	1/10
GW D6 765	3 mod. width	2	1/10

APPLICATIONS: they enable to seal terminal screws, preventing access to cable connections.

Latching relay RLB



GW D6 644

Latching relay 16 A



Code	Contacts	Control coil voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 641	1NO	8 ac	1	6/24
GW D6 642	1NO	12 ac	1	6/24
GW D6 643	1NO	24 ac	1	6/24
GW D6 644	1NO	230 ac	1	6/24
GW D6 646	1 Changeover	8 ac	1	6/24
GW D6 647	1 Changeover	12 ac	1	6/24
GW D6 648	1 Changeover	24 ac	1	6/24
GW D6 649	1 Changeover	24 dc	1	6/24
GW D6 650	1 Changeover	230 ac	1	6/24
GW D6 652	1NO+1NC	12 ac	1	6/24
GW D6 653	1NO+1NC	24 ac	1	6/24
GW D6 654	1NO+1NC	230 ac	1	6/24
GW D6 657	2NO	12 ac	1	6/24
GW D6 658	2NO	24 ac	1	6/24
GW D6 659	2NO	230 ac	1	6/24
GW D6 663	2 Changeover	24 ac	2	3/12
GW D6 664	2 Changeover	230 ac	2	3/12
GW D6 667	4NO	12 ac	2	3/12
GW D6 668	4NO	24 ac	2	3/12
GW D6 669	4NO	230 ac	2	3/12

Accessories for latching relay RLB

Auxiliary contacts



GW D6 676

Code	Contacts	Contact rating in AC-15	No. of modules EN 50022	Pack Carton
GW D6 676	1 Changeover	4A (230V)	0.5	1/20
GW D6 677	1NO+1NC	4A (230V)	0.5	1/20
GW D6 678	2NO	4A (230V)	0.5	1/20

APPLICATION: used in order to signal the contacts position (open or closed).
NOTE: it is possible to use 1 auxiliary contact for each contactor. It is not possible to use auxiliary contacts with GWD6649 latching relay.

Centralized command



GW D6 671

Code	Functions	No. of modules EN 50022	Pack Carton
GW D6 671	Central command	0.5	1/20
GW D6 672	Group command	0.5	1/20

NOTE: It is not possible to use them with GWD6649 latching relay.
APPLICATION:
- GWD6671: used to centralize the command in only one point allowing to simultaneously turning ON and OFF 2 or more relays independently by their position. In order to use this function every relay has to mount this accessory.
- GWD6672: used to realize the simultaneously command of 2 or more groups of centralized relays from one point. In order to obtain this function it is necessary to install this accessory for each group of centralized relay.

EXAMPLE: It is possible to centralize the command of a group of latching relay installed on a building floor (every relay has a GWD6671 coupled). With the GWD6672 it is possible to command from one point all groups of centralized relays installed on the different buildings floors.

Spacer insert

GW D6 766

Code	No. of modules EN 50022	Pack Carton
GW D6 766	0.5	12

APPLICATIONS: used in order to have a better heat dissipation when more contactors/relay are installed in adjiacent position.
SUGGESTIONS FOR AN OPTIMAL HEAT DISSIPATION:
- Operating temperature up to 40°C: no limitations.
- Operating temperature between 40°C and 55°C: No limitation for AC coils, 1 spacer every 3 adjacent relays with DC coils:
- Operating temperature between 55°C and 70°C: 1 spacer every 3 adjacent relays with AC coils. It is not possible the adjacent installation of relay with DC coil.

Monitoring relays

Current monitoring relay - 1 phase AC electrical system



GW 96 906

Code	Rated voltage (V)	Controlled current (A)	Output contacts	Contact capacity (A)	No. of modules EN 50022	Pack Carton
GW 96 906	230 ac	10	1 Changeover	5	1	1/8

APPLICATIONS: overcurrent control: the output contact changes status when the measured current exceeds the "MAX" set value.
Undercurrent control: the output contact changes status when the measured current falls below the "MIN" set value.
Window function: the output contact changes status when the measured current is not within the "MIN"-"MAX" set range.
Adjustment of contact switchover delay, from minimum 0.1s to maximum 10s.
For the three operating modes, there is a memory function for exceeding the set threshold.
NOTE: if you need to monitor currents greater than 10A, use a current transformer (CT).
If necessary, connect the output contact with a device (usually a contactor) suitable for the needs of the line to be commanded.

Phase monitoring relay - 3 phase electrical system



GW 96 907

Code	Rated voltage (V)	Controlled voltage (V)	Adjustable asymmetry	Output contacts	Contact capacity (A)	No. of modules EN 50022	Pack Carton
GW 96 907	230/400 ac	230/400 ac	5% ... 25%	1 Changeover	5	1	1/8

APPLICATIONS: phase sequence check: if the check shows that the phases are not in the correct sequence, the output contact will change its status.
Phase and neutral failure: if one of the three phases or the neutral fails, the output contact will change its status.
Asymmetry check: if the measured asymmetry value exceeds the set threshold, the output contact will change its status.
NOTE: if necessary, connect the output contact with a device (usually a contactor) suitable for the needs of the line to be commanded.

Undervoltage monitoring relay - 1 phase AC/DC electrical system



GW 96 908

Code	Rated voltage (V)	Controlled voltage (V)	Output contacts	Contact capacity (A)	No. of modules EN 50022	Pack Carton
GW 96 908	24 ac/dc - 230 ac	24 ac/dc - 230 ac	1 Changeover	5	1	1/8

APPLICATIONS: undervoltage check: when the measured voltage falls below the set value, the output contact will change its status.
The contact switches back again when the measured voltage exceeds the set value plus the hysteresis.
NOTE: if necessary, connect the output contact with a device (usually a contactor) suitable for the needs of the line to be commanded.

Undervoltage monitoring relay - 3 phase AC electrical system



GW 96 909

Code	Rated voltage (V)	Controlled voltage (V)	Output contacts	Contact capacity (A)	No. of modules EN 50022	Pack Carton
GW 96 909	230/400 ac	230/400 ac	1 Changeover	5	1	1/8

APPLICATIONS: undervoltage check with variable threshold: when the measured voltage of one of the phases falls below the set value, the output contact will change its status.
The undervoltage threshold can be adjusted from 160 V to 240 V (Phase - Neutral).
NOTE: if necessary, connect the output contact with a device (usually a contactor) suitable for the needs of the line to be commanded.

Load management relay P-COMFORT



GW D6 916

Load management relay P-Comfort (wire version)

Code	Rated voltage (V)	Rated current	Type relay contact	Capacity relay contact	No. of modules EN 50022	Pack Carton
GW D6 916	230 ac	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

APPLICATION: The P-Comfort relay can be installed in electrical systems up to 6 kW. In the event of overload due to the simultaneous switching of several electric loads, P-Comfort prevents power supply interruption disconnecting the non-preferential loads wired to the relay inside the device. After a time period, P-Comfort automatically power supplies non-preferential loads again, avoiding service interruptions. P-Comfort allows the measurement and visualisation on the display of the active energy values (supplied and absorbed), and instantaneous active power (supplied and absorbed).



GW A1 916

Load management relay P-Comfort RF ZigBee (radio frequency version)

Code	Rated voltage (V)	Rated current	Type relay contact	Capacity relay contact	No. of modules EN 50022	Pack Carton
GW A1 916	230V ac	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

APPLICATION: The P-Comfort relay can be installed in electrical systems up to 6 kW. In the event of overload due to the simultaneous switching of several electric loads, P-Comfort prevents power supply interruption disconnecting the non-preferential loads connected by radio frequency to smart plug RF ZigBee (GWA1526), to flush-mounting actuator RF ZigBee (GWA1523) or wired to the relay inside the device (max 10 devices). The disconnection and connection of preferential loads can be set by Priority (regardless of power consumption) or by Power (depending on the power consumption).



GW A9 916

KNX Secure load management relay P-COMFORT - IP20 - DIN rail mounting

Code	Supply voltage	Rated current	Type relay contact	Capacity relay contact	No. DIN modules	Pack Carton
GW A9 916	230V ac - 50Hz	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

CHARACTERISTICS: load management to control the activation/deactivation of electrical appliances wired to the relay inside the device or connected to KNX actuators, preventing the main line power supply disconnection and avoiding service interruptions. The device supports KNX Secure. To be configured with ETS software.
APPLICATIONS: allows the measurement, the visualisation on the display and the sending on the KNX bus of the active energy (exported and imported), instantaneous active and reactive power (exported and imported), voltage, current, power factor and frequency.
NOTES: equipped with coupling terminal for connection to bus.

Accessories for P-COMFORT RF ZIGBEE (radio frequency version)

Smart plug RF ZIGBEE - German Standard - 230V AC



GW A1 526

Code	Type of plug	Socket-outlet type	Dimensions ØxH (mm)	Colour	Pack Carton
GW A1 526	2P+E - 10A	2P+E - 10A	41x45	White	1/2

CHARACTERISTICS: adapter with side earthing and safety shields. Measures the power consumed of the load connected and sends the data to the P-Comfort RF ZigBee which disconnects the load according to the current setting.

ZigBee 1-channel actuator with power meter



GW A1 523

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 523	230V ac - 50 Hz	1	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via a 230V output contact (NO) with the measure of the instantaneous power. Suitable for commanding incandescent lamps (230Vac): 2300W, loads controlled from toroidal transformers: 450W, loads controlled from electronic transfomers: 600W, compact fluorescent lamps: 150W, LED lamps (230Vac): 150W, motors: 500W. Equipped with 1 input for the local command of the output.
APPLICATIONS: execution of ON-OFF commands, timed commands, priority commands, scene management commands and instantaneous consumption metering (instantaneous power). Measures the power consumed by the connected load and, when combined with a RF ZigBee P-comfort load management relay, can disconnect the load according to the chosen setting of the P-Comfort.
NOTES: installation in flush-mounting boxes, junction boxes or in Chorus blanking modules GW1x750.

Blanking modules for housing ZigBee contacts interfaces and actuators



GW 14 750

Code	Colour	No. modules	Pack Carton
GW 10 750	Glossy white	1	1/12
GW 15 750	Satin White	1	1/12
GW 13 750	Natural satin beige	1	1/12
GW 12 750	Satin black	1	1/12
GW 14 750	Glossy Titanium	1	1/12

CHARACTERISTICS: 1-module blanking module with pad printing. Allows the housing and the fast identification of the ZigBee contacts interfaces and actuators.
NOTES: snap-fit design.

Kit P-COMFORT RF ZIGBEE (radio frequency version)



GW A1 912

Pre-installed kit P-Comfort RF Zigbee and Smart plug

Code	Number of smart plugs included	Pack Carton
GW A1 911	1	1
GW A1 912	2	1

CHARACTERISTICS: P-Comfort RF ZigBee provided with the kit is pre-installed to operate in Priority mode: when the power threshold is exceeded, loads connected to the Smart plug 1 are disconnected, then the loads connected to the Smart plug 2 and after all the loads wired to the relay inside the device. The reconnection of non-preferential loads is done following reverse sequence.

BIOCOMFORT main disconnection switch



GW 96 339

Main disconnection switch with self learning function

Code	Rated voltage (V)	Rated current	Monitoring voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 339	230 ac	16 A	5 - 230 dc	1	1/2

APPLICATIONS: the BIOCOMFORT disconnection switch reduces the voltage of the electrical system when the loads connected to it in the sleeping area are switched off. It is not necessary to manually adjust the relay tripping threshold because the main disconnection switch, thanks to the self-learning function, automatically learns the value of the current absorbed by the loads and applies it as the tripping threshold. During operation of the disconnection switch, the line downstream of BIOCOMFORT is powered by a continuous monitoring voltage (5-230 V dc). This voltage prevents the formation of electromagnetic fields in the sleeping area and is necessary for restoring the mains voltage (230 V ac) at any moment when a load is switched on.



GW 96 340

Base load

Code	Rated voltage (V)	Pack Carton
GW 96 340	230 ac	1/5

NOTE: base load necessary for fluorescent lamps, low consumption lamps, LED lamps, halogen lamps with transformer, dimmers, electronic transformers or loads with absorption lower than 30 mA (e.g. loads with stand-by).

PROGRAMMING

Timers



GW 96 814

Multifunction timer

Code	Rated coil voltage (V)	Regulation field	Type of contacts	Contact rating - In	No. of modules EN 50022	Pack Carton
GW 96 814	24....240 ac/dc	0.05 s - 100 h	1 Changeover	8 A	1	1/8

APPLICATIONS: allows to activate and deactivate the power supply to a load for a time set.
NOTE: cannot be used with illuminated push-buttons.



GW 96 815

Asymmetrical cycle timer

Code	Rated coil voltage (V)	Regulation field	Type of contacts	Contact rating - In	No. of modules EN 50022	Pack Carton
GW 96 815	12....240 ac/dc	0.05 s - 100 h	1 Changeover	8 A	1	1/8

APPLICATIONS: allows to activate and deactivate the power supply to a load, for a time set with different ON and OFF times.
NOTE: cannot be used with illuminated push-buttons.



GW 96 809

Staircase lighting time delay switches

Code	Rated voltage (V)	Regulation field	Type of contacts	Contact rating - In	No. of modules EN 50022	Pack Carton
GW 96 809	230 ac	30 s - 12 min	1 NO	16 A	1	1/8

APPLICATION: timed management of the lights in passageway environments (stairs, corridors, entrances, etc.).
CHARACTERISTICS: the electronic staircase time switch, without switch-off warning, also allow to:
-turn off the lights completely by prolonged pressing of push-button (energy saving function).
-to extend lighting time by rapid and multiple pressing of the push-button (pumping function).

Analogue/electromechanical time switches TMR

Compact daily time switches



GW D6 771

Code	Charge reserve	Type of contacts	Contact rating	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 771	No	1 NO	16 A	230V ac	1	1/12
GW D6 772	150 h	1 NO	16 A	230V ac	1	1/12

APPLICATIONS: command and management of electrical loads according to daily programming; particularly useful for timing control of functions (for example: ventilation, lighting, heating, irrigation), comfort optimization and energy saving.
NOTE: 24 hours quadrant with 96 trippers (minimum adjustment of the time switch: 15 minutes).
CHARACTERISTICS: equipped with the switch for the choice of operating mode:
- OFF permanent mode
- automatic (according to the set programming with the trippers)
- ON permanent mode

Daily time switch



GW D6 773

Code	Charge reserve	Type of contacts	Contact rating	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 773	150 h	1 Changeover	16 A	230V ac	2	1/6

APPLICATIONS: command and management of electrical loads according to daily programming; particularly useful for timing control of functions (for example: ventilation, lighting, heating, irrigation), comfort optimization and energy saving.
NOTE: 24 hours quadrant with 48 trippers (minimum adjustment of the time switch: 30 minutes).
CHARACTERISTICS: equipped with the switch for the choice of operating mode:
- OFF permanent mode
- automatic (according to the set programming with the trippers)
- ON permanent mode

Weekly time switch



GW D6 776

Code	Charge reserve	Type of contacts	Contact rating	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 776	150 h	1 Changeover	16 A	230V ac	2.5	1/4

APPLICATIONS: command and management of electrical loads according to daily programming; particularly useful for timing control of functions (for example: ventilation, lighting, heating, irrigation), comfort optimization and energy saving.
NOTE: 7 days quadrant with 84 trippers (minimum adjustment of the time switch: 2 hours).
CHARACTERISTICS: equipped with the switch for the choice of operating mode:
- OFF permanent mode
- automatic (according to the set programming with the trippers)
- ON permanent mode

Digital time switches TMR

Compact weekly time switch



GW D6 781

Code	Type of contacts	Contact rating	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW D6 781	1 NO	16 A	230V ac	4 years	1	1/6

APPLICATIONS: command and management of electrical loads according to weekly programming; particularly useful for timing control of functions (for example: ventilation, lighting, heating, irrigation), comfort optimization and energy saving.
NOTE: quadrant with 48 virtual trippers (minimum adjustment of the time switch: 30 minutes).

Weekly time switches



GW D6 782

Code	Type of contacts	Contact rating	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW D6 782	1 Changeover	16 A	230V ac	5 years	2	1/3
GW D6 783	2 Changeover	16 A	230V ac	5 years	2	1/3

APPLICATIONS: command and management of electrical loads according to weekly programming; particularly useful for timing control of functions (for example: ventilation, lighting, heating, irrigation), comfort optimization and energy saving.
NOTE: maximum number of programs that can be stored: 120.
CHARACTERISTICS: The NFC interface allows the connection with smartphone and tablet to transfer the programs set on the time swtich by means of the specific APP. Particularly with free of charge Gewiss TimerOn APP you can:
- create programs directly on your smartphone and tablet
- transfer programs created on several time switches
- copy and paste programs among several time switches
- switch channels manually
- obtain settings (date, time, coordinates) automatically and transfer them to the time switch

Twilight switch TMR

Twilight switch (with outdoor probe)



GW D6 779

Code	Type of contacts	Contact rating	Rated voltage (V)	Brightness control	No. of modules EN 50022	Pack Carton
GW D6 779	1 NO	16 A	230V ac	1...100 lux	1	1/3

APPLICATIONS: command the ON/OFF switching of lighting devices according to outdoor lighting measured by outdoor probe.
NOTE: maximum distance beetwen the probe and the twilight switch: 50 m (we reccomend using twisted or double insulated cable).

Outdoor probe for twilight switch



GW D6 780

Code	Suitable for	Pack Carton
GW D6 780	Twilight switch GWD6779	1/4

NOTE: maximum distance beetwen the probe and the twilight switch: 50 m (we reccomend using twisted or double insulated cable).

Astronomical switch TMR



GW D6 785

Astronomical switch with simplified programming

Code	Type of contacts	Contact rating	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW D6 785	1 Changeover	16 A	230V ac	5 years	2	1/4

APPLICATIONS: command ON/OFF switching of lighting devices (without the outdoor probe) according to sunrise and sunset of geographical area.
NOTE: equipped with display with virtual trippers to set one or more OFF switching periods during the night (minimum adjustment of the time switch: 30 minutes). The programming is daily type.



GW D6 786

Astronomical switch

Code	Type of contacts	Contact rating	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW D6 786	2 Changeover	16 A	230V ac	3 years	2	1/3

APPLICATIONS: command ON/OFF switching of lighting devices (without the outdoor probe) according to sunrise and sunset of geographical area.
NOTE: commands the ON/OFF night weekly switching, divided beetwen 2 contacts (maximum number of 120 programs can be stored divided beetwen 2 channels).
CHARACTERISTICS: The NFC interface allows the connection with smartphone and tablet to transfer the programs set on the astronomical swtich by means of the specific APP.
Particularly with free of charge Gewiss TimerOn APP you can:
- create programs directly on your smartphone and tablet
- transfer programs created on several astronomical switches
- copy and paste programs among several astronomical switches
- switch channels manually
- obtain settings (date, time, coordinates) automatically and transfer them to the astronomical switch

Time/astronomical switches TMR



GW D6 788

Time/astronomical switches

Code	Type of contacts	Contact rating	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW D6 788	1 Changeover	16 A	230V ac	5 years	2	1/3
GW D6 789	2 Changeover	16 A	230V ac	5 years	2	1/3

APPLICATIONS: command and management of electrical loads according to weekly or astronomical programming; for GWD6789 code it is possibile to set a different program for each channel (time or astronomical).
NOTE: maximum number of programs that can be stored: 120.
CHARACTERISTICS: The Bluetooth interface allows the connection with smartphone and tablet to transfer the programs set on the time/astronomical swtich by means of the specific APP.
Particularly with free of charge Gewiss TimerOn APP you can:
- create programs directly on your smartphone and tablet
- transfer programs created on several time/astronomical switches
- copy and paste programs among several time/astronomical switches
- switch channels manually
- obtain settings (date, time, coordinates) automatically and transfer them to the time switch

MEASUREMENT

Voltmeters



GW 96 867

Single-phase digital voltmeter with direct connection

Code	Scale	Supply voltage	Accuracy	No. of modules EN 50022	Pack Carton
GW 96 867	0 - 500 V	230 V ac	0.5	2	1/4

Ammeters



GW 96 871

Analogue ammeters - 40/60 Hz

Code	Capacity	Connection	Accuracy	No. of modules EN 50022	Pack Carton
GW 96 872	20 A	Direct	1.5	3	1/4
GW 96 878	5 A	Using C.T./5 A	1.5	3	1/4

NOTE: GW96878 does not have a scale. Select the most suitable interchangeable scale based on the primary current of the C.T..



Interchangeable scales for GW96878 analogue ammeter

Code	Scale (A)	Pack Carton
GW 96 971	40	1/10
GW 96 972	50	1/10
GW 96 973	60	1/10
GW 96 974	100	1/10
GW 96 975	150	1/10
GW 96 976	250	1/10
GW 96 977	400	1/10
GW 96 978	600	1/10
GW 96 979	1000	1/10
GW 96 980	1200	1/10
GW 96 981	1500	1/10



GW 96 879

Digital ammeter for connection using current transformer

Code	Capacity	Supply voltage	Accuracy	No. of modules EN 50022	Pack Carton
GW 96 879	5 - 999 A	230 V ac	0.5	2	1/4

NOTE: connection using a current transformer (up to 1000 A) with secondary of 5 A.

Energy meters



GW D6 801

Single-phase digital energy meters for direct connection

Code	Type MID	Integrated Modbus	Accuracy	I max (A)	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 801	No	No	1	40 A	230 ac	1	1/5
GW D6 802	Yes	No	1	40 A	230 ac	1	1/5
GW D6 803	Yes	Yes	1	40 A	230 ac	1	1/5

APPLICATION: they allow the measurement and visualisation on the display (No. digits: 5 units + 2 decimals) of the active energy values (exported and imported), instantaneous active power (exported and imported), voltage, current, power factor and frequency.
If the GWD6801 and GWD6802 energy meters are used with the KNX GW90876 interface, the measured values can be sent by KNX BUS network.
If the GWD6801 and GWD6802 energy meters are used with the MODBUS GWD6820 interface, the measured values can be sent by Modbus RS485 netwok.
If the GWD6801 and GWD6802 energy meters are used with the LAN-TCP/IP GWD6821 interface, the measured values can be sent by TCP/IP network.
CHARACTERISTICS: the energy meters have an impulse output for remote energy consumption control.



GW D6 809

Three-phase digital energy meters

Code	Type MID	Integrated Modbus	Accuracy	Connection	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 804	Yes	Yes	1 (active energy) 2 (reactive energy)	Direct (I max=80 A)	400 ac	4	1/2
GW D6 805	Yes	Yes	1 (active energy) 2 (reactive energy)	Using C.T./5 A	400 ac	4	1/2
GW D6 807	Yes	No	1 (active energy) 2 (reactive energy)	Direct (I max=80 A)	400 ac	4	1/2
GW D6 809	Yes	No	1 (active energy) 2 (reactive energy)	Using C.T./5 A	400 ac	4	1/2

APPLICATION: they allow the measurement and visualisation on the display (No. digits: 7 units + 2 decimals) of the active and reactive energy values (exported and imported), instantaneous active and reactive power values (exported and imported), apparent power, voltage, current, power factor, frequency, THD voltage and THD current.
If the GWD6807 and GWD6809 energy meters are used with the KNX GW90876 interface, the measured values can be sent by KNX BUS network.
If the GWD6807 and GWD6809 energy meters are used with the MODBUS GWD6820 interface, the measured values can be sent by Modbus RS485 network.
If the GWD6801 and GWD6802 energy meters are used with the LAN-TCP/IP GWD6821 interface, the measured values can be sent by TCP/IP network.
CHARACTERISTICS: the meters have two impulse outputs for remote energy consumption control.



GW 90 876

Communication interfaces for single-phase and three-phase energy meters

Code	Technology	No. of modules EN 50022	Pack Carton
GW 90 876	KNX	1	1/5
GW D6 820	RS485 MODBUS	1	1/5
GW D6 821	LAN-TCP/IP	1	1/5

CHARACTERISTICS: GW90876 to be configured with ETS software.
APPLICATIONS: KNX BUS, MODBUS RS485 or TCP/IP interface send values measured by the energy meters GWD6801, GWD6802, GWD6807 and GWD6809. The interfaces are optically coupled with the energy meters if installed side-by-side.

Hour counter



GW D6 911

Hour counter

Code	N. digit	Accuracy	No. of modules EN 50022	Pack Carton
GW D6 911	5 unit + 2 decimals	1/100 h (36 s.)	2	1/6

APPLICATIONS: computing the operating hours of electrical devices (motors, machines, tools, adjustment devices etc.).

Multimeter



GW 96 897

Voltage/current multimeter

Code	Type of display	Rated voltage (V)	Measured sizes	Accuracy	No. of modules EN 50022	Pack Carton
GW 96 897	LED 3 units on 3 lines	230 ac	V, I	0.5	2	1/4

NOTE: connection using current transformers (up to 1000 A) with secondary of 5 A.

Network analyser



GW 96 899

Network analyser

Code	Type of display	Measured sizes	Accuracy	No. of modules EN 50022	Pack Carton
GW 96 899	LCD	V, I, F, W, VAR, VA, kWH, kVARH, power factor	2	4	1/2

NOTE: connection using current transformers with secondary of 5 A. It allows remote communication of all measured sizes via RS485 (MODBUS RTU).

Current transformers



GW 96 452

Current transformers with 5 A secondary

Code	Primary current	Primary circuit with bar	Primary circuit with cable	Performance	Accuracy	Pack Carton
GW 96 441	15 A	Wound	-	3 VA	1	1
GW 96 442	25 A	Wound	-	3 VA	1	1
GW 96 443	40 A	Busbar 30x10 mm max	Cable Ø 25 mm max	1.5 VA	3	1
GW 96 444	50 A	Busbar 30x10 mm max	Cable Ø 25 mm max	2 VA	3	1
GW 96 445	60 A	Busbar 30x10 mm max	Cable Ø 25 mm max	2 VA	3	1
GW 96 446	100 A	Busbar 30x10 mm max	Cable Ø 25 mm max	2.5 VA	1	1
GW 96 447	150 A	Busbar 30x10 mm max	Cable Ø 25 mm max	3 VA	0.5	1
GW 96 448	250 A	Busbar 30x10 mm max	Cable Ø 25 mm max	5 VA	0.5	1
GW 96 449	400 A	Busbar 30x10 mm max	Cable Ø 25 mm max	6 VA	0.5	1
GW 96 450	600 A	Busbar 40x10 mm max	Cable Ø 32 mm max	10 VA	0.5	1
GW 96 451	1000 A	Busbar 64x20 mm max	Cable Ø 50 mm max	20 VA	0.5	1
GW 96 452	1200 A	Busbar 64x20 mm max	Cable Ø 50 mm max	15 VA	0.5	1
GW 96 453	1500 A	Busbar 64x20 mm max	Cable Ø 50 mm max	20 VA	0.5	1

CHARACTERISTICS: two types of primary circuit: wound type (supplied with busbar or primary terminal already available) and through type (with a hole through which the busbar, or the cable constituting the primary, is passed). Transformers up to 600 A can be installed on DIN rail.

APPLICATIONS: allow the measurement of high currents by analogue and digital ammeters; provide a current to the secondary which is proportional to the primary current.

NOTE: current transformers can be used up to 20% more than the primary current without derating (permanent rated thermal current Icth = 120% Ipr).


SIGNALLING

Indicator lights



GW 96 592

Indicator lights



Code	Type	Colour	No. of modules EN 50022	Pack Carton
Rated voltage: 12-24-48 V ac/dc				
GW 96 586	Single	Red	1	1/12
GW 96 587	Single	Green	1	1/12
GW 96 588	Single	Yellow	1	1/12
GW 96 589	Single	Blue	1	1/12
GW 96 590	Single	White	1	1/12
Rated voltage: 230 V ac				
GW 96 581	Single	Red	1	3/12
GW 96 582	Single	Green	1	3/12
GW 96 583	Single	Yellow	1	3/12
GW 96 584	Single	Blue	1	3/12
GW 96 585	Single	White	1	3/12
GW 96 591	Double	Green/Red	1	1/12
GW 96 592	Triple	Red	1	1/12
GW 96 598	Triple	Red/Green/Yellow	1	1/12


CHARACTERISTICS: indicator light with LED.

Illuminated push-buttons



GW 96 568

Illuminated push-buttons



Code	Contacts	Indicator light colour	Characteristics	Rated current	No. of modules EN 50022	Pack Carton
Rated lamp voltage: 12-24-48 V ac/dc						
GW 96 570	1 NO	Green	Single push-button	16 A	1	1/12
GW 96 571	1 NC	Red	Single push-button	16 A	1	1/12
Rated lamp voltage: 230 V ac						
GW 96 566	1 NO	Green	Single push-button	16 A	1	1/12
GW 96 567	1 NC	Red	Single push-button	16 A	1	1/12
GW 96 568	1 NO + 1 NC	Green	Single push-button	16 A	1	1/12
GW 96 569	1 NO + 1 NC	Red	Single push-button	16 A	1	1/12


CHARACTERISTICS: indicator light with LED.

Push-buttons without lighting



GW 96 565

Push-buttons



Code	Contacts	Characteristics	Rated current	No. of modules EN 50022	Pack Carton
Rated voltage: 230 V ac					
GW 96 561	1 NO	Single push-button	16 A	1	3/12
GW 96 562	1 NC	Single push-button	16 A	1	3/12
GW 96 563	1 NO + 1 NC	Single push-button	16 A	1	1/12
GW 96 564	1 NO / 1 NO	Double push-button (grey / grey)	16 A	1	1/12
GW 96 565	1 NO / 1 NC	Double push-button (green / red)	16 A	1	1/12

Bells and buzzers



GW 96 402

Bells

Code	Rated voltage	Power loss	No. of modules EN 50022	Pack Carton
GW 96 401	12 V	5 VA	1	12
GW 96 402	230 V	10 VA	1	12
GW 96 403	230 V	6.1 VA	2	6

CHARACTERISTICS: GW96403 incorporates a transformer with a very low safety voltage of 24 V~.
APPLICATIONS: acoustic signal of an operation in the domestic and commercial sectors.



GW 96 408

Buzzers

Code	Rated voltage	Power loss	No. of modules EN 50022	Pack Carton
GW 96 406	12 V	5 VA	1	12
GW 96 407	230 V	10 VA	1	12
GW 96 408	230 V	6.1 VA	2	6

CHARACTERISTICS: GW96408 incorporates a transformer with a very low safety voltage of 24 V~.
APPLICATIONS: acoustic signal of an operation in the domestic and commercial sectors.



GW 96 411

Combined transformer-bell-buzzer

Code	Rated voltage	Power loss	No. of modules EN 50022	Pack Carton
GW 96 411	230 V	3.8 VA	2	4

CHARACTERISTICS: GW96411 iincorporates a transformer with a very low safety voltage of 24 V.

Transformers



GW 96 421

Bells transformers (for discontinuous use)

Code	Rated power	Primary voltage	Secondary voltage	No. of modules EN 50022	Pack Carton
GW 96 421	6 VA (12 V) 4 VA (8 V) 2 VA (4 V)	230 V	4+8=12 V	2	6
GW 96 422	6 VA (24 V) 3 VA (12 V)	230 V	12+12=24 V	2	6
GW 96 423	10 VA (12 V)/6.6 VA (8 V)/3.3 VA (4 V)	230 V	4+8=12 V	2	6
GW 96 424	10 VA (24 V)/5 VA (12 V)	230 V	12+12=24 V	2	6
GW 96 425	15 VA (12 V)/10 VA (8 V)/5 VA (4 V)	230 V	4+8=12 V	2	6
GW 96 426	15 VA (24 V)/7.5 VA(12 V)	230 V	12+12=24 V	2	6
GW 96 431	30 VA (12 V)/20 VA (8 V)/10 VA (4 V)	230 V	4+8=12 V	3	4
GW 96 432	30 VA (24 V)/15 VA (12 V)	230 V	12+12=24 V	3	4
GW 96 433	40 VA (12 V)/27 VA (8 V)/13 VA (4 V)	230 V	4+8=12 V	3	4
GW 96 434	40 VA (24 V)/20 VA (12 V)	230 V	12+12=24 V	3	4

APPLICATIONS: distribution and realisation of SELV very low voltage safety circuits, with a value lower or equal to 24 V.
They allow electrical separation between the primary and secondary circuits, thus allowing the supply of bells and similar discontinuous operation signalling devices. They can also be used to supply the shunt trip release GW96011 with a rated voltage up to 24 V ac. To know the maximum number of releases that can be supplied with the transformers, refer to the technical characteristics.



GW 96 781

Transformers for bells and buzzers (switch off type)

Code	Rated power	Primary voltage	Secondary voltage	No. of modules EN 50022	Pack Carton
GW 96 781	8 VA	230 V	8 V	2	1/6



GW 96 323

Safety transformers

Code	Rated power	Primary voltage	Secondary voltage	No. of modules EN 50022	Pack Carton
GW 96 321	15 VA (12/24 V)	230 V	12+12=24 V	3	4
GW 96 322	25 VA (12/24 V)	230 V	12+12=24 V	3	4
GW 96 323	40 VA (12/24 V)	230 V	12+12=24 V	4	1
GW 96 324	63 VA (12/24 V)	230 V	12+12=24 V	6	1
GW 96 325	100 VA (24 V)	230 V	24 V	8	1

OTHER ACCESSORIES

Accessories for mounting on DIN rail EN 50022



GW 96 523

Socket-outlets for mounting on DIN rail EN 50022

Code	No. of poles	Standard	Rated voltage (V)	Rated current	No. of modules EN 50022	Pack Carton
GW 96 522	2P+E	German	250 V ac	16 A	2.5	2/8
GW 96 523	2P+E	German, with lid	250 V ac	16 A	2.5	2/8
GW 96 524	2P+E	French	250 V ac	16 A	2.5	2/8
GW 96 525	2P+E	Italian / German	250 V ac	10/16 A*	2.5	2/8
GW 96 526	2P+E	Danish	250 V ac	16 A	2.5	2/8

* 10 A italian standard / 16 A german standard

CHORUSMART Range components and supports for mounting on DIN rail EN 50022



GW 10 204

Italian/German Standard socket-outlets - 250 V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 10 661

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	Pack Carton
GW 10 661	230 V ac - 50/60 Hz	Ni - Mh	2 h	White LED	1/6

CHARACTERISTICS: equipped with a 3-position selector on the front panel, for anti black-out inhibition and night functioning.
To be inserted in any socket-outlet of the Italian, German or French type. Highly efficient, white LED lamp.



GW 16 841

Supports for assembling CHORUSMART devices on DIN EN 50022 rail

Code	Description	No. DIN modules	Pack Carton
GW 16 841	1 module	1.5	5/300
GW 16 842	2 modules	3	5/150
GW 16 843	3 modules	4	5/50

CHARACTERISTICS: tool-free manual release system for flush-mounting devices.
NOTES: pay attention when using particularly deep devices (two-pole, three-way switches, movement detectors and IR receivers, relays, German standard socket-outlets with front tightening, quick wiring terminals, British standard socket-outlets, interlocked switched sockets-outlets, shaver sockets-outlets, USB power supplies, MCCB and RCCB, anti-black-out and emergency lamps, ringers and buzzers, thermostats and timed thermostats, programmers, water and gas detectors, timers, dimmers, touch commands, electronic soft-click push buttons with interlock, KNX flush-mounting timed thermostats, etc.) as they may interfere with the DIN rail, preventing the correct passage of the wires.

SYSTEM Range components and supports for mounting on DIN rail EN 50022



GW 20 246

Italian/German standard socket-outlets - 250 V ac

Code	Description	Earth pit	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 246	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	30/120

CHARACTERISTICS: with safety shields.




GW 20 833

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Autonomy	Type of lamp	No. SYSTEM modules	Pack Carton
GW 20 833	230 V ac - 50/60 Hz	Ni-Mh	2 h	White LED	2	1/4

CHARACTERISTICS: equipped with inhibition selector on the front. Replaceable batteries (battery pack 4.8 V 40 mAh).
APPLICATION: according to CEI 64-8 (chapter 37).



GW 26 409

Supports for assembling SYSTEM devices on DIN rail EN 50022

Code	Description	No. of modules EN 50022	Pack Carton
GW 26 409	1 module	1.5	5/300
GW 26 410	2 modules	3	5/150



90 AM



Scan the QR Code and find out all the technical informations.

INTELLIGENT LOAD MANAGEMENT



P-COMFORT allows for effective management of the energy consumed or produced in the electrical system, because it can prevent power outages in case of overload or activate non-preferential loads to maximize the self-produced energy of the photovoltaic system.

SIMPLIFIED ACCESSORY MANAGEMENT



Auxiliary contacts and trip coils, common to all circuit breakers, guarantee simplicity, interchangeability, multiple uses and rationalisation of the items.

OVERVOLTAGE UNDER CONTROL



The LST surge protection device range offers maximum protection against intense atmospheric discharges caused by direct and indirect lightning. The easy-to-extract cartridges makes it quicker and more convenient to replace used cartridges.

Prewired string boards and modular devices in DC

PREWIRED STRING BOARDS

	2 STRINGS	
		
String voltage (V)	600 dc	800 dc
In (A)	25	20
No. of board modules	1x12	1x12
No. of rotary switch disconnectors 2P	1	1
No. of surge protective devices	1	1
No. of disconnectable fuse-holders	-	-
	GW D9 901	GW D9 906

ROTARY SWITCH DISCONNECTORS



In (A)	Rated voltage (V)	2P	4P
25	600 DC	GW 96 186	-
		3.5 mod.	
32	1000 DC	-	GW 96 187
			3.5 mod.

SURGE PROTECTIVE DEVICES LST



	TYPE 1+2	TYPE 2	
	For photovoltaic applications		
Imax (kA)	1000 Vdc	600 Vdc	1000 Vdc
40	GW D6 429	GW D6 426	GW D6 428
	3 mod. / Iimp=5kA	3 mod.	3 mod.

DISCONNECTABLE FUSE-HOLDERS



In (A)	Rate voltage (V)	Fuse size (mm)	1P	2P
20	1000 DC	10.3x38	GW 96 226	GW 96 227
			1 mod.	2 mod.

FUSES



Breaking capacity dc (kA)	Rated voltage (V)	Fuse size (mm)	In (A)	GPV type
30	1000 dc	10.3x38	6	GW 72 131
			8	GW 72 132
			10	GW 72 133
			12	GW 72 134
			16	GW 72 135
			20	GW 72 136

90 PV

Products for photovoltaic systems

The 90 PV range comprises 2 versions of string boards able to meet the most varying photovoltaic plant engineering requirements, from the residential context to the commercial/industrial one. In addition to string boards, the range also includes modular products specifically for the DC side of the photovoltaic system.



PREWIRED STRING BOARDS

Prewired string boards



GW D9 901

Prewired string boards

Code	No. of strings	Rated current	No. of board modules	Pack Carton
String voltage: 600 V dc				
GW D9 901	2	25 A	1x12	1
String voltage: 800 V dc				
GW D9 906	2	20 A	1x12	1

ACCESSORIES SUPPLIED: cable glands as spare parts and equipotential terminal blocks.
DC fuses not included. Refer to the fuse code list.

DC MODULAR DEVICES

Switch disconnectors



GW 96 187

DC rotary switch disconnectors

Code	No. of poles	Rated current	Rated voltage DC	No. of modules EN 50022	Pack Carton
GW 96 186	2P	25 A	600 V	3.5	1
GW 96 187	4P	32 A	1000 V	3.5	1

NOTE: utilisation category DC21B. These switch disconnectors cannot be combined.

Surge protective devices LST



GW D6 426

Surge protective devices for photovoltaic applications

Code	Impulse current	Maximum discharge current	Rated voltage DC	No. of modules EN 50022	Aux end-of-life contact	Pack Carton
Type: 1+2						
GW D6 429	5 kA	40 kA	1000 V	3	No	1/4
Type: 2						
GW D6 426	-	40 kA	600 V	3	No	1
GW D6 428	-	40 kA	1000 V	3	No	1

CHARACTERISTICS: SPDs are equipped with extractable cartridges with optic end-of-life signal.

NEWS



GW D6 446

Extractable spare cartridges for LST for photovoltaic applications

Code	Impulse current	Maximum discharge current	Rated voltage	Pack Carton
Suitable for: GWD6429				
GW D6 449	5 kA	40 kA	1000 V dc	1
Suitable for: GWD6426 and GWD6428				
GW D6 446	-	40 kA	600 V dc	1
GW D6 448	-	40 kA	1000 V dc	1

Disconnectable fuse-holders



GW 96 227

Disconnectable fuse-holders

Code	No. of poles	Rated current	Rated voltage	Fuse dimension (mm)	No. of modules EN 50022	Pack Carton
GW 96 226	1P	20 A	1000 V dc	10.3x38	1	12
GW 96 227	2P	20 A	1000 V dc	10.3x38	2	6

NOTE: utilization category DC20B.

Fuses



GW 72 131

Cylindrical fuses - Type GPV

Code	Rated current	Rated voltage DC	Breaking capacity DC	Pack Carton
Dimensions (mm): Ø 10.3 x 38				
GW 72 131	6 A	1000 V	30 kA	10
GW 72 132	8 A	1000 V	30 kA	10
GW 72 133	10 A	1000 V	30 kA	10
GW 72 134	12 A	1000 V	30 kA	10
GW 72 135	16 A	1000 V	30 kA	10
GW 72 136	20 A	1000 V	30 kA	10

APPLICATIONS: photovoltaic systems.

NEWS



90 PV



Scan the QR Code and find out all the technical informations.

READY TO CONNECT RIGHT AWAY



To allow for easy, fast and secure connection, the string boards include cable glands and equipotential terminal blocks. The cable glands are supplied loose, to allow entry of the cables according to your needs (from the top, the bottom or the sides).

ALREADY TESTED AND CERTIFIED



The string distribution boards are tested in GEWISS laboratories, passing and exceeding all tests required by EN 61439-1 and EN 61439-2 for the issue of product certification.

COMPLETENESS OF RANGE



The GEWISS AC protection offer meets all system needs, from residential to tertiary/ industrial, with a wide range of products, including modular devices, moulded case circuit breakers, modular accessories and distribution boards.

Moulded case circuit brakers





MSX

Moulded case circuit breakers for power distribution

p. 553

97 MSS

Rotary switch disconnectors

p. 583

MSXc - Compact moulded case circuit breakers

Release		In [A]	MSX 160c			
						
			16kA		25kA	
			3P	3P+N	3P	3P+N
THERMAL MAGNETIC	Adjustable thermal Fixed magnetic	25	GW D9 001	GW D9 011	GW D9 041	GW D9 051
		40	GW D9 002	GW D9 012	GW D9 042	GW D9 052
		63	GW D9 003	GW D9 013	GW D9 043	GW D9 053
		80	GW D9 004	GW D9 014	GW D9 044	GW D9 054
		100	GW D9 005	GW D9 015	GW D9 045	GW D9 055
		125	GW D9 026	GW D9 036	GW D9 066	GW D9 076
		160	GW D9 027	GW D9 037	GW D9 067	GW D9 077

Release		In [A]	MSX 250c			
						
			16kA		25kA	
			3P	3P+N	3P	3P+N
THERMAL MAGNETIC	Adjustable thermal Adjustable magnetic	160	GW D9 087	GW D9 097	GW D9 107	GW D9 117
		250	GW D9 088	GW D9 098	GW D9 108	GW D9 118

MSX - Moulded case circuit breakers

MSX 125



Release		In [A]	36kA			65kA		
			3P	3P+N	4P	3P	3P+N	4P
THERMAL MAGNETIC	Adjustable thermal Adjustable magnetic	20	GW D9 121	GW D9 131	GW D9 141	GW D9 151	GW D9 161	GW D9 171
		32	GW D9 122	GW D9 132	GW D9 142	GW D9 152	GW D9 162	GW D9 172
		50	GW D9 123	GW D9 233	GW D9 143	GW D9 153	GW D9 263	GW D9 173
		63	GW D9 124	GW D9 134	GW D9 144	GW D9 154	GW D9 164	GW D9 174
		100	GW D9 125	GW D9 135	GW D9 145	GW D9 155	GW D9 165	GW D9 175
		125	GW D9 126	GW D9 136	GW D9 146	GW D9 156	GW D9 166	GW D9 176
	Adjustable magnetic	20	GW D9 201	-	GW D9 211	-	-	-
		32	GW D9 202	-	GW D9 212	-	-	-
		63	GW D9 204	-	GW D9 214	-	-	-
		100	GW D9 205	-	GW D9 215	-	-	-
		125	GW D9 206	-	GW D9 216	-	-	-
	TMG	100	-	-	GW D9 195	-	-	-
		125	-	-	GW D9 196	-	-	-

MSX 160 - MSX 250



Release		In [A]	36kA			65kA		
			3P	3P+N	4P	3P	3P+N	4P
THERMAL MAGNETIC	Adjustable thermal Adjustable magnetic	160	GW D9 127	GW D9 137	GW D9 147	GW D9 157	GW D9 167	GW D9 177
		250	GW D9 128	GW D9 148	GW D9 138	GW D9 158	GW D9 178	GW D9 168
	Adjustable magnetic	160	GW D9 207	-	GW D9 217	-	-	-
		250	GW D9 208	-	GW D9 218	-	-	-
	TMG	160	-	-	GW D9 197	-	-	-
		250	-	-	GW D9 198	-	-	-

MSX 400



Release		In [A]	36kA			50kA			85kA	
			3P	3P+N	4P	3P	3P+N	4P	3P	4P
THERMAL MAGNETIC	Adjustable thermal Adjustable magnetic	400	GW D9 361	GW D9 362	GW D9 363	GW D9 365	GW D9 366	GW D9 367	GW D9 368	GW D9 370

MSXE - Electronic moulded case circuit breakers

MSXE 160 - MSXE 250



Release		In [A]	36kA			65kA			125kA	
			3P	3P+N	4P	3P	3P+N	4P	3P	4P
ELECTRONIC	LSI	40	GW D9 302	GW D9 312	GW D9 322	GW D9 332	GW D9 342	GW D9 352	GW D9 502	GW D9 522
		125	GW D9 306	GW D9 316	GW D9 326	GW D9 336	GW D9 346	GW D9 356	GW D9 506	GW D9 526
		160	GW D9 307	GW D9 317	GW D9 327	GW D9 337	GW D9 347	GW D9 357	GW D9 507	GW D9 527
		250	GW D9 308	GW D9 318	GW D9 328	GW D9 338	GW D9 348	GW D9 358	GW D9 508	GW D9 528

MSXE 400 - MSXE 630



Release		In [A]	36kA			50kA			70kA		85kA	
			3P	3P+N	4P	3P	3P+N	4P	3P	4P	3P	4P
ELECTRONIC	LSI	250	-	-	GW D9 329	-	-	GW D9 359	-	-	-	GW D9 389
		400	GW D9 371	GW D9 372	GW D9 373	GW D9 375	GW D9 376	GW D9 377	-	-	GW D9 531	GW D9 533
		630	GW D9 381	GW D9 382	GW D9 383	GW D9 385	GW D9 386	GW D9 387	GW D9 535	GW D9 537	-	-
	LSIG	400	-	-	GW D9 374	-	-	GW D9 378	-	-	-	GW D9 534
		630	-	-	GW D9 384	-	-	GW D9 388	-	GW D9 538	-	-

MSXE 1000



Release		In [A]	50kA			70kA	
			3P	3P+N	4P	3P	4P
ELECTRONIC	LSI	800	GW D9 401	GW D9 402	GW D9 403	GW D9 561	GW D9 563
		1000	GW D9 406	GW D9 407	GW D9 408	GW D9 565	GW D9 567
	LSIG	800	-	-	GW D9 404	-	GW D9 564
		1000	-	-	GW D9 409	-	GW D9 568

MSXE 1250 - MSXE 1600



Release		In [A]	Terminals	50kA		70kA	
				3P	4P	3P	4P
ELECTRONIC	LSI	1250	front	GW D9 411*	GW D9 415*	GW D9 581	GW D9 583
			rear	GW D9 412*	GW D9 416*	GW D9 585	GW D9 587
		1600	front	GW D9 421*	GW D9 425*	-	-
			rear	GW D9 422*	GW D9 426*	-	-
	LSIG	1250	front	-	GW D9 417*	-	GW D9 584
			rear	-	GW D9 418*	-	GW D9 588
		1600	front	-	GW D9 427*	-	-
			rear	-	GW D9 428*	-	-

* Adding the final letter B at the end of the GW codes in table MSXE 1250 - MSXE 1600 gives the corresponding versions with cable mechanical interlock

MSXD - Thermal magnetic MCCB + RCD

Release		In [A]	MSXD 125			
						
			3P		3P+N	
			25kA	36kA	25kA	36kA
MCCB RCD	Adjustable thermal Fixed Magnetic Adjustable residual current	20	GW D9 241	GW D9 261	GW D9 551	GW D9 571
		32	GW D9 242	GW D9 262	GW D9 552	GW D9 572
		50	GW D9 243	GW D9 263	GW D9 553	GW D9 573
		63	GW D9 244	GW D9 264	GW D9 554	GW D9 574
		100	GW D9 245	GW D9 265	GW D9 555	GW D9 575
		125	GW D9 246	GW D9 266	GW D9 556	GW D9 576

Release		In [A]	MSXD 160 - MSXD 250			
						
			3P		3P+N	
			25kA	36kA	25kA	36kA
MCCB RCD	Adjustable thermal Fixed Magnetic Adjustable residual current	160	GW D9 247	GW D9 267	GW D9 557	GW D9 277
		250	GW D9 248	GW D9 268	GW D9 558	GW D9 278

MSXM - Switch disconnector

		MSXM									
		MSXM 160c		MSXM 250c		MSXM 400 - MSXM 630		MSXM 1000		MSXM 1250 - MSXM 1600	
											
In [A]	Terminals	3P	4P	3P	4P	3P	4P	3P	4P	3P	4P
160	front	GW D9 441	GW D9 442	-	-	-	-	-	-	-	-
250	front	-	-	GW D9 443	GW D9 444	-	-	-	-	-	-
400	front	-	-	-	-	GW D9 445	GW D9 446	-	-	-	-
630	front	-	-	-	-	GW D9 447	GW D9 448	-	-	-	-
800	front	-	-	-	-	-	-	GW D9 449	GW D9 450	-	-
1000	front	-	-	-	-	-	-	GW D9 451	GW D9 452	-	-
1250	front	-	-	-	-	-	-	-	-	GW D9 453*	GW D9 454*
	rear	-	-	-	-	-	-	-	-	GW D9 459*	GW D9 460*
1600	front	-	-	-	-	-	-	-	-	GW D9 455*	GW D9 456*
	rear	-	-	-	-	-	-	-	-	GW D9 457*	GW D9 458*

* Adding the final letter B at the end of the GW codes gives the corresponding versions with cable mechanical interlock

Technical data - MSX moulded case circuit breakers

TYPE			MSX 160c		MSX 250c		MSX 125		MSX 160 - MSX 250		MSXE 160 - MSXE 250		
													
Standard:			**IEC EN 60947-2**		**IEC EN 60947-2**		**IEC EN 60947-2**		**IEC EN 60947-2**		**IEC EN 60947-2**		
Rated current (In):		**(A)**	25, 40, 63, 80, 100, 125, 160		160, 250		20, 32, 50, 63, 100, 125		125, 160, 250		40, 125, 160, 250		
Utilization category:			A		A		A		A		A		
Brief allowable rated current for 0.3s (Icw):		**(kA)**	-		-		-		-		-		
Number of poles:			3P, 3P+N		3P, 3P+N		3P, 3P+N, 4P		3P, 3P+N, 4P		3P, 3P+N, 4P		
Rated frequency:		**(Hz)**	50/60		50/60		50/60		50/60		50/60		
Rated operating voltage (Ui):		**(V)**	525 ac - 250 dc		525 ac - 250 dc		690 ac - 250 dc		690 ac - 250 dc		690 ac		
Rated impulse withstand voltage (Uimp):		**(kV)**	8		8		8		8		8		
Overvoltage category:			IV		IV		IV		IV		IV		
Rated insulation voltage (Ui):		**(V)**	690		800		800		800		800		
Rated breaking capacity (Icu)													
Alternating current:	**220/240V**	**(kA)**	25	35	25	35	50	85	65	85	65	85	150
	400/415V	**(kA)**	**16**	**25**	**16**	**25**	**36**	**65**	**36**	**65**	**36**	**65**	**125**
	440V	**(kA)**	10	15	10	15	25	50	25	50	25	50	120
	525V	**(kA)**	6	7.5	6	7.5	22	25	25	25	25	25	45
	690V	**(kA)**	-	-	-	-	6	6	7.5	7.5	7.5	7.5	20
Direct current:	**250V**	**(kA)**	13	20	13	15	25	40	40	40	-	-	-
Service breaking capacity (Ics)													
Alternating current:	**220/240V**	**(kA)**	13	18	13	27	50	85	65	85	65	85	150
	400/415V	**(kA)**	8	13	8	19	36/30	36/33	36	36	36	36	85
	440V	**(kA)**	5	7.5	5	12	25	25	25	25	25	25	80
	525V	**(kA)**	3	4	3	6	22	22	25	25	25	25	45
	690V	**(kA)**	-	-	-	-	6	6	7.5	7.5	7.5	7.5	15
Direct current:	**250V**	**(kA)**	7	10	7	12	19	40	40	40	-	-	-
Type of protection:			Adjustable thermal Fixed magnetic		Adjustable thermal Adjustable magnetic		Adjustable thermal Adjustable magnetic		Adjustable thermal Adjustable magnetic		Electronic LSI		
Versions:			Fixed		Fixed		Fixed Plug-in		Fixed Plug-in		Fixed Plug-in[1]		
Mounting on DIN rail by means of the accessory:			yes		yes		yes		yes		no		
Mounting position:			any		any		any		any		any		
Upline/downline power supply:			yes		yes		yes		yes		yes		
Terminals:	**Front for cables (FW)**		• (20A÷100A)		-		○		-		-		
	Front (FC)		• (125-160A)		•		•		•		•		
	Front extended (FB)		○ (63÷160A)		○		○		○		○		
	Front extended spread terminals (FB)		○ (63÷160A)		○		-		-		-		
	Rear (RC)		○ (63÷160A)		○		○		○		○		
Electrical life (415V ac):		**(No. cycles)**	14,000 (≤125A) 10,000 (160 A)		6,000		30,000		20,000 (MSX 160) 10,000 (MSX 250)		10,000		
Mechanical life:		**(No. cycles)**	20,000		18,000		30,000		30,000		30,000		
Can be equipped with motor operator:			no		yes		yes		yes		yes		
Interlock type:			-		Lever / Cable		Lever / Cable		Lever / Cable		Lever / Cable		
Operating temperature:		**(°C)**	-5 +65		-5 +65		-5 +65		-5 +65		-5 +65		
Reference temperature:		**(°C)**	50		50		50		50		40		
Storage temperature:		**(°C)**	-20 +65		-20 +65		-20 +65		-20 +65		-20 +65		
Tropicalization:			65°C - RH 95%		65°C - RH 95%		65°C - RH 95%		65°C - RH 95%		65°C - RH 95%		
Dimensions:	**Width (3P / 4P)**	**(mm)**	75 / 100		105 / 140		90 / 120		105 / 140		105 / 140		
	Height	**(mm)**	130		165		155		165		165		
	Depth	**(mm)**	68		68		68		68		103		
Weight (3P / 4P):		**(kg)**	0.8 / 1		1.5 / 1.9		1.1 / 1.4		1.5 / 1.9		2.3 / 3.1		

Key:
• supplied as standard
○ optional
- not available

[1] max 225A
[2] max 536A

MSX 400	MSXE 400	MSXE 630	MSXE 1000	MSXE 1250	MSXE 1600
					
IEC EN 60947-2	IEC EN 60947-2	IEC EN 60947-2	IEC EN 60947-2	IEC EN 60947-2	IEC EN 60947-2
400	250, 400	630	800 | 1000	1250	1600
A	B	A	B | A	B	B
-	5	-	10 | -	15	20
3P, 3P+N, 4P	3P, 3P+N, 4P	3P, 3P+N, 4P	3P, 3P+N, 4P	3P, 4P	3P, 4P
50/60	50/60	50/60	50/60	50/60	50/60
690 ac - 250 dc	690 ac	690 ac	690 ac	690 ac	690 ac
8	8	8	8	8	8
IV	IV	IV	IV	IV	IV
800	800	800	800	800	800
50 | 85 | 100	50 | 85 | 100	50 | 85 | 100	85 | 85 | 100	85 | 100	85
36 | **50** | **85**	**36** | **50** | **85**	**36** | **50** | **70**	**50** | **50** | **70**	**50** | **70**	**50**
30 | 45 | 80	25 | 45 | 80	25 | 45 | 65	50 | 45 | 65	45 | 65	45
22 | 30 | 30	15 | 30 | 30	15 | 30 | 30	30 | 30 | 35	30 | 45	30
15 | 20 | 20	10 | 20 | 20	10 | 20 | 20	20 | 20 | 25	20 | 25	20
40 | 40 | 40	- | - | -	- | - | -	- | - | -	- | -	-
50 | 85 | 85	50 | 85 | 85	85 | 85 | 85	85 | 65 | 75	65 | 75	65
36 | 50 | 85	36 | 50 | 85	50 | 50 | 50	50 | 38 | 50	38 | 50	38
30 | 45 | 80	25 | 45 | 80	50 | 45 | 50	50 | 34 | 50	34 | 50	34
22 | 30 | 30	15 | 30 | 30	30 | 30 | 30	30 | 23 | 30	23 | 34	23
15 | 15 | 15	10 | 15 | 15	15 | 15 | 15	20 | 15 | 20	15 | 20	15
40 | 40 | 40	- | - | -	- | - | -	- | - | -	- | -	-
Adjustable thermal Adjustable magnetic	Electronic LSI Electronic LSIG	Electronic LSI Electronic LSIG	Electronic LSI Electronic LSIG	Electronic LSI Electronic LSIG	Electronic LSI Electronic LSIG
Fixed Plug-in	Fixed Plug-in[2]	Fixed Plug-in[2]	Fixed, Plug-in | Fixed	Fixed	Fixed
no	no	no	no	no	no
any	any	any	any	any	any
yes	yes	yes	yes	yes	yes
-	-	-	- | -	-	-
•	•	•	• | -	-	-
○	○	○	○ | •	•	•
○	○	○	- | -	-	-
○	○	○	○ | ○	•	•
4,500	4,500	4,500	4,000	4,000	2,000
15,000	15,000	15,000	10,000	5,000	5,000
yes	yes	yes	yes	yes	yes
Lever / Cable	Lever / Cable	Lever / Cable	Lever / Cable	Cable	Cable
-5 +65	-5 +65	-5 +65	-5 +65	-5 +65	-5 +65
50	40	40	40	40	40
-20 +65	-20 +65	-20 +65	-20 +65	-20 +65	-20 +65
65°C - RH 95%	65°C - RH 95%	65°C - RH 95%	65°C - RH 95%	65°C - RH 95%	65°C - RH 95%
140 / 185	140 / 185	140 / 185	210 / 280	210 / 280	210 / 280
260	260	260	273	370	370
103	103	103	103	120	140
4.3 / 5.6	4.3 / 5.7	5 / 6.5	9.1 / 12.3 | 11 / 14.8	19.8 / 25	27 / 35

Technical data - Switch disconnectors MSXM

TYPE			MSXM 160c	MSXM 250c	MSXM 400 - MSXM 630
					
Standard:			**IEC EN 60947-3**	**IEC EN 60947-3**	**IEC EN 60947-3**
Rated uninterrupted current (Iu):		**(A)**	160	250	400, 630
Utilization category:			AC-23A DC-22A	AC-23A DC-22A	AC-23A DC-22A
Number of poles:			3P, 4P	3P, 4P	3P, 4P
Rated frequency:		**(Hz)**	50/60	50/60	50/60
Rated operating voltage (Ui):		**(V)**	690 ac - 250 dc	690 ac - 250 dc	690 ac - 250 dc
Rated impulse withstand voltage (Uimp):		**(kV)**	8	8	8
Overvoltage category:			IV	IV	IV
Rated insulation voltage (Ui):		**(V)**	690	800	800
Rated short-circuit making capacity (Icm):		**(kA)**	2.8	6	9
Brief allowable rated current for 0.3s (Icw):		**(kA)**	2	3	5
Versions:		**(kA)**	Fixed	Fixed	Fixed Plug-in[1]
Mounting on DIN rail by means of the accessory:			yes	yes	no
Mounting position:			any	any	any
Upline/downline power supply:			yes	yes	yes
Terminals:	**Front for cables (FW)**		-	-	-
	Front (FC)		•	•	•
	Front extended (FB)		○	○	○
	Front extended spread terminals (FB)		○	○	○
	Rear (RC)		○	○	○
Electrical life (415V ac):		**(No. cycles)**	10,000	6,000	4,500
Mechanical life:		**(No. cycles)**	20,000	18,000	15,000
Can be equipped with motor operator:			no	yes	yes
Interlock type:			-	Lever / Cable	Lever / Cable
Operating temperature:		**(°C)**	-5 +65	-5 +65	-5 +65
Reference temperature:		**(°C)**	50	50	50
Storage temperature:		**(°C)**	-20 +65	-20 +65	-20 +65
Tropicalization:			65°C - RH 95%	65°C - RH 95%	65°C - RH 95%
Dimensions:	**Width (3P / 4P)**	**(mm)**	75 / 100	105 / 140	140 / 185
	Height	**(mm)**	130	165	260
	Depth	**(mm)**	68	68	103
Weight (3P / 4P):		**(kg)**	0.7 / 0.9	1.5 / 1.9	4.2 / 5.6 (MSXM 400) 4.4 / 5.8 (MSXM 630)

Key:
• supplied as standard
○ optional
- not available

[1] max 536A

MSXM 1000		MSXM 1250	MSXM 1600
			
IEC EN 60947-3		**IEC EN 60947-3**	**IEC EN 60947-3**
800	1000	1250	1600
AC-23A DC-22A		AC-23A DC-22A	AC-23A DC-22A
3P, 4P		3P, 4P	3P, 4P
50/60		50/60	50/60
690 ac - 250 dc		690 ac - 250 dc	690 ac - 250 dc
8		8	8
IV		IV	IV
800		800	800
17		32	45
10		15	20
Fixed, Plug-in	Fixed	Fixed	Fixed
no		no	no
any		any	any
yes		yes	yes
-	-	-	-
•	-	-	-
○	•	•	•
-	-	-	-
○	○	-	•
4,000		4,000	2,000
10,000		5,000	5,000
yes		yes	yes
Lever / Cable		Cable	Cable
-5 +65		-5 +65	-5 +65
50		50	50
-20 +65		-20 +65	-20 +65
65°C - RH 95%		65°C - RH 95%	65°C - RH 95%
210 / 280		210 / 280	210 / 280
273		370	370
103		120	140
8.5 / 11.5	10.4 / 14	18.2 / 23.4	24.9 / 32.9

Technical data - MSXD MCCB with residual current protection

TYPE			MSXD 125		MSXD 160 - MSXD 250	
						
Standard:			IEC 60947-1 IEC 60947-2 IEC 60755		IEC 60947-1 IEC 60947-2 IEC 60755	
Rated current (In):		(A)	20, 32, 50, 63, 100, 125		160, 250	
Utilization category:			A		A	
Number of poles:			3P, 3P+N		3P, 3P+N	
Rated frequency:		(Hz)	50/60		50/60	
Rated operating voltage (Ui):		(V)	525 ac		525 ac	
Rated impulse withstand voltage (Uimp):		(kV)	8		8	
Overvoltage category:			IV		IV	
Rated insulation voltage (Ui):		(V)	525		525	
Rated breaking capacity (Icu)						
Alternating current:	220/240V	(kA)	35	50	35	65
	400/415V	(kA)	**25**	**36**	**25**	**36**
	440V	(kA)	15	25	15	25
	525V	(kA)	8	22	10	25
Service breaking capacity (Ics)						
Alternating current:	220/240V	(kA)	27	50	27	65
	400/415V	(kA)	19	36/30	19	36
	440V	(kA)	12	25	12	25
	525V	(kA)	6	22	7.5	25
Type of protection:			Adjustable thermal Fixed magnetic		Adjustable thermal Fixed magnetic	
Versions:			Fixed		Fixed	
Mounting on DIN rail by means of the accessory:			yes		yes	
Mounting position:			any		any	
Upline/downline power supply:			yes		yes	
Terminals:	Front for cables (FW)		○		-	
	Front (FC)		•		•	
	Front extended (FB)		○		○	
	Front extended spread terminals (FB)		-		-	
	Rear (RC)		○		○	
Electrical life (415V ac):		(No. cycles)	30,000		10,000	
Mechanical life:		(No. cycles)	30,000		10,000	
Can be equipped with motor operator:			yes		yes	
Interlock type:			-		-	
Operating temperature:		(°C)	-5 +65		-5 +65	
Reference temperature:		(°C)	50		50	
Storage temperature:		(°C)	-20 +65		-20 +65	
Tropicalization:			65°C - RH 95%		65°C - RH 95%	
Dimensions:	Width (3P / 4P)	(mm)	68 / 120		68 / 140	
	Height	(mm)	155		165	
	Depth	(mm)	68		68	
Weight (3P / 4P):		(kg)	1.4		1.9	

Key:
• supplied as standard
○ optional
- not available

Coordination between switch disconnectors and MCCB - 400/415V ac

			SWITCH DISCONNECTORS							
CIRCUIT BREAKERS	RANGE	Icu [kA]	MSXM 160c	MSXM 250c	MSXM 400	MSXM 630	MSXM 1000 (800A)	MSXM 1000 (1000A)	MSXM 1250	MSXM 1600
	MSX 160c	16	16							
		25	25							
	MSX 250c	16		16						
		25		25						
	MSX/E/D 160	25		25						
		36		36						
		65		36						
	MSX/E/D 250	25		25						
		36		36						
		65		36						
	MSX/E 400	36			36					
		50			50					
		85			85					
	MSX/E 630	36				36				
		50				50				
		70				70				
	MSXE 1000 (800A)	50					50			
		70					70			
	MSXE 1000 (1000A)	50						50		
		70						70		
	MSXE 1250	50							50	
		70							70	
	MSXE 1600	50								50

MSX

Moulded case circuit breakers for power distribution

The moulded case circuit breakers MSX range is made up of circuit breakers with thermo-magnetic release, circuit breakers with thermo-magnetic release and Overcurrent Protection, circuit breakers with electronic release and switch disconnectors.



MSXc - COMPACT MOULDED CASE CIRCUIT BREAKERS

MSX 160c - Compact moulded case circuit breakers up to 160 A - 16 kA



GW D9 037

Adjustable thermal and fixed magnetic release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 001	25 A	525 V	1
GW D9 002	40 A	525 V	1
GW D9 003	63 A	525 V	1
GW D9 004	80 A	525 V	1
GW D9 005	100 A	525 V	1
GW D9 026	125 A	525 V	1
GW D9 027	160 A	525 V	1
No. of poles: 3P+N			
GW D9 011	25 A	525 V	1
GW D9 012	40 A	525 V	1
GW D9 013	63 A	525 V	1
GW D9 014	80 A	525 V	1
GW D9 015	100 A	525 V	1
GW D9 036	125 A	525 V	1
GW D9 037	160 A	525 V	1

NOTES: or mounting on EN 50022 DIN rail, choose the fixing bracket GWD8875.
The space taken up on the EN 50022 DIN rail is approximately 4 modules for 3P versions and 6 modules for 3P+N versions.
ACCESSORIES SUPPLIED: 25A ÷ 100A versions supplied with front terminals for copper cables (FW).
125A and 160A versions supplied with front terminals (FC).
CHARACTERISTICS: adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii:
25A-40A: Ii = 600A
63A-80A: Ii = 1000A
100-125A: Ii = 1500A
160A: Ii = 1600A

MSX 160c - Compact moulded case circuit breakers up to 160 A - 25 kA



GW D9 053

Adjustable thermal and fixed magnetic release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 041	25 A	525 V	1
GW D9 042	40 A	525 V	1
GW D9 043	63 A	525 V	1
GW D9 044	80 A	525 V	1
GW D9 045	100 A	525 V	1
GW D9 066	125 A	525 V	1
GW D9 067	160 A	525 V	1
No. of poles: 3P+N			
GW D9 051	25 A	525 V	1
GW D9 052	40 A	525 V	1
GW D9 053	63 A	525 V	1
GW D9 054	80 A	525 V	1
GW D9 055	100 A	525 V	1
GW D9 076	125 A	525 V	1
GW D9 077	160 A	525 V	1

NOTES: or mounting on EN 50022 DIN rail, choose the fixing bracket GWD8875.

The space taken up on the EN 50022 DIN rail is approximately 4 modules for 3P versions and 6 modules for 3P+N versions.

ACCESSORIES SUPPLIED: 25A ÷ 100A versions supplied with front terminals for copper cables (FW).

125A and 160A versions supplied with front terminals (FC).

CHARACTERISTICS: adjustable thermal release Ir = 0.63 - 0,8 - 1 x In

Fixed magnetic release Ii:

25A-40A: Ii = 600A

63A-80A: Ii = 1000A

100-125A: Ii = 1500A

160A: Ii = 1600A

MSX 250c - Compact moulded case circuit breakers up to 250 A - 16 kA



GW D9 098

Adjustable thermal and adjustable magnetic release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 087	160 A	525 V	1
GW D9 088	250 A	525 V	1
No. of poles: 3P+N			
GW D9 097	160 A	525 V	1
GW D9 098	250 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 3P+N versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Adjustable magnetic release Ii:
160A: Ii = 5 - 8 - 10 - 13 x In
250A: Ii = 5 - 7 - 9 - 11 x In

MSX 250c - Compact moulded case circuit breakers up to 250 A - 25 kA



GW D9 118

Adjustable thermal and adjustable magnetic release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 107	160 A	525 V	1
GW D9 108	250 A	525 V	1
No. of poles: 3P+N			
GW D9 117	160 A	525 V	1
GW D9 118	250 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 3P+N versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Adjustable magnetic release Ii:
160A: Ii = 5 - 8 - 10 - 13 x In
250A: Ii = 5 - 7 - 9 - 11 x In

MSX - MCCB'S

MSX 125 - MCCB'S 125A - 36kA



GW D9 145

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 121	20 A	690 V	1
GW D9 122	32 A	690 V	1
GW D9 123	50 A	690 V	1
GW D9 124	63 A	690 V	1
GW D9 125	100 A	690 V	1
GW D9 126	125 A	690 V	1
No. of poles: 3P+N			
GW D9 131	20 A	690 V	1
GW D9 132	32 A	690 V	1
GW D9 133	50 A	690 V	1
GW D9 134	63 A	690 V	1
GW D9 135	100 A	690 V	1
GW D9 136	125 A	690 V	1
No. of poles: 4P			
GW D9 141	20 A	690 V	1
GW D9 142	32 A	690 V	1
GW D9 143	50 A	690 V	1
GW D9 144	63 A	690 V	1
GW D9 145	100 A	690 V	1
GW D9 146	125 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 5 modules for 3P versions and 7 modules for 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Adjustable magnetic release Ii:
20A ÷100A: Ii = 6 - 8 - 10 - 12 x In
125A: Ii = 6 - 8 - 10 x In



GW D9 215

Magnetic adjustable for motors protection

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 201	20 A	690 V	1
GW D9 202	32 A	690 V	1
GW D9 204	63 A	690 V	1
GW D9 205	100 A	690 V	1
GW D9 206	125 A	690 V	1
No. of poles: 4P			
GW D9 211	20 A	690 V	1
GW D9 212	32 A	690 V	1
GW D9 214	63 A	690 V	1
GW D9 215	100 A	690 V	1
GW D9 216	125 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 5 modules for 3P versions and 7 modules for 4P versions.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: adjustable magnetic release Ii:
20A ÷ 100A: Ii = 6 - 8 - 10 - 12 x In
125A: Ii = 6 - 8 - 10 x In.



GW D9 196

Adjustable thermal protection and fixed magnetic for generators protection (TMG)

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 4P			
GW D9 195	100 A	690 V	1
GW D9 196	125 A	690 V	1

NOTESS: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 7 modules.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustment thermal release Ir = 0,63 - 0,8 - 1 x In.
fixed magnetic release Ii = 3 x In.

NEWS

MSX 125 - MCCB'S 125A - 65kA



GW D9 175

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 151	20 A	690 V	1
GW D9 152	32 A	690 V	1
GW D9 153	50 A	690 V	1
GW D9 154	63 A	690 V	1
GW D9 155	100 A	690 V	1
GW D9 156	125 A	690 V	1
No. of poles: 3P+N			
GW D9 161	20 A	690 V	1
GW D9 162	32 A	690 V	1
GW D9 163	50 A	690 V	1
GW D9 164	63 A	690 V	1
GW D9 165	100 A	690 V	1
GW D9 166	125 A	690 V	1
No. of poles: 4P			
GW D9 171	20 A	690 V	1
GW D9 172	32 A	690 V	1
GW D9 173	50 A	690 V	1
GW D9 174	63 A	690 V	1
GW D9 175	100 A	690 V	1
GW D9 176	125 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.

The space taken up on the EN 50022 DIN rail is approximately 5 modules for 3P versions and 7 modules for 4P versions.

ACCESSORIES SUPPLIED: supplied with front terminals (FC).

CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In

Adjustable magnetic release Ii:

20A ÷100A: Ii = 6 - 8 - 10 - 12 x In

125A: Ii = 6 - 8 - 10 x In

NEWS

MSX 160 - MCCB'S 160A - 36kA



GW D9 147

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 127	160 A	690 V	1
No. of poles: 3P+N			
GW D9 137	160 A	690 V	1
No. of poles: 4P			
GW D9 147	160 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Adjustable magnetic release: Ii = 6 - 8 - 10 - 13 x In



GW D9 217

Magnetic adjustable for motors protection

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 207	160 A	690 V	1
No. of poles: 4P			
GW D9 217	160 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable magnetic release: Ii = 6 - 8 - 10 - 13 x In.



GW D9 197

Adjustable thermal protection and fixed magnetic for generators protection (TMG)

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 4P			
GW D9 197	160 A	690 V	1

NOTESS: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustment thermal release Ir = 0,63 - 0,8 - 1 x In.
fixed magnetic release Ii = 3 x In.

MSX 160 - MCCB'S 160A - 65kA



GW D9 177

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 157	160 A	690 V	1
No. of poles: 3P+N			
GW D9 167	160 A	690 V	1
No. of poles: 4P			
GW D9 177	160 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Adjustable magnetic release: Ii = 6 - 8 - 10 - 13 x In

NEWS

MSX 250 - MCCB'S 250A - 36kA



GW D9 138

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 128	250 A	690 V	1
No. of poles: 3P+N			
GW D9 148	250 A	690 V	1
No. of poles: 4P			
GW D9 138	250 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0,63 - 0,8 - 1 x In
Adjustable magnetic release: Ii = 6 - 8 - 10 x In



GW D9 218

Magnetic adjustable for motors protection

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 208	250 A	690 V	1
No. of poles: 4P			
GW D9 218	250 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable magnetic release: Ii = 6 - 8 - 10 x In.



GW D9 198

Adjustable thermal protection and fixed magnetic for generators protection (TMG)

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 4P			
GW D9 198	250 A	690 V	1

NOTESS: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876. The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustment thermal release Ir = 0,63 - 0,8 - 1 x In.
fixed magnetic release Ii = 3 x In.

MSX 250 - MCCB'S 250A - 65kA



GW D9 168

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 158	250 A	690 V	1
No. of poles: 3P+N			
GW D9 178	250 A	690 V	1
No. of poles: 4P			
GW D9 168	250 A	690 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for 3P versions and 8 modules for 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0,63 - 0,8 - 1 x In
Adjustable magnetic release: Ii = 6 - 8 - 10 x In

NEWS

MSX 400 - MCCB'S 400A - 36kA



GW D9 363

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 361	400 A	690 V	1
No. of poles: 3P+N			
GW D9 362	400 A	690 V	1
No. of poles: 4P			
GW D9 363	400 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustable thermal release Ir = 0,63 - 0,8 - 1 x In
Adjustable magnetic release Ii = 6 - 7 - 8 - 9 - 10 - 11 - 12 x In

MSX 400 - MCCB'S 400A - 50kA



GW D9 366

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 365	400 A	690 V	1
No. of poles: 3P+N			
GW D9 366	400 A	690 V	1
No. of poles: 4P			
GW D9 367	400 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustable thermal release Ir = 0,63 - 0,8 - 1 x In
Adjustable magnetic release Ii = 6 - 7 - 8 - 9 - 10 - 11 - 12 x In

MSX 400 - MCCB'S 400A - 85kA



GW D9 370

Thermal and magnetic adjustable release

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 368	400 A	690 V	1
No. of poles: 4P			
GW D9 370	400 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: adjustment thermal release Ir = 0,63 - 0,8 - 1 x In.
adjustment magnetic release Ii = 6 - 7 - 8 - 9 - 10 - 11 - 12 x In

NEWS

MSXD - MCCB'S WITH RESIDUAL CURRENT PROTECTION

MSXD 125 - MCCB'S with residual current protection up to 125A - 25kA



GW D9 556

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 241	20 A	525 V	1
GW D9 242	32 A	525 V	1
GW D9 243	50 A	525 V	1
GW D9 244	63 A	525 V	1
GW D9 245	100 A	525 V	1
GW D9 246	125 A	525 V	1
No. of poles: 3P+N			
GW D9 551	20 A	525 V	1
GW D9 552	32 A	525 V	1
GW D9 553	50 A	525 V	1
GW D9 554	63 A	525 V	1
GW D9 555	100 A	525 V	1
GW D9 556	125 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 7 modules.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii:
20A ÷ 100A: Ii = 12 x In
125A: Ii = 10 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

MSXD 125 - MCCB'S with residual current protection up to 125A - 36kA



GW D9 576

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 261	20 A	525 V	1
GW D9 262	32 A	525 V	1
GW D9 263	50 A	525 V	1
GW D9 264	63 A	525 V	1
GW D9 265	100 A	525 V	1
GW D9 266	125 A	525 V	1
No. of poles: 3P+N			
GW D9 571	20 A	525 V	1
GW D9 572	32 A	525 V	1
GW D9 573	50 A	525 V	1
GW D9 574	63 A	525 V	1
GW D9 575	100 A	525 V	1
GW D9 576	125 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 7 modules.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii:
20A ÷ 100A: Ii = 12 x In
125A: Ii = 10 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

NEWS

MSXD 160 - MCCB'S with residual current protection 160A - 25kA



GW D9 557

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 247	160 A	525 V	1
No. of poles: 3P+N			
GW D9 557	160 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii = 13 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

MSXD 160 - MCCB'S with residual current protection 160A - 36kA



GW D9 277

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 267	160 A	525 V	1
No. of poles: 3P+N			
GW D9 277	160 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii = 13 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

MSXD 250 - MCCB'S with residual current protection 250A - 25kA



GW D9 558

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 248	250 A	525 V	1
No. of poles: 3P+N			
GW D9 558	250 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii = 13 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

MSXD 250 - MCCB'S with residual current protection 250A - 36kA



GW D9 278

NEWS

Thermal and residual current release adjustable, fixed magnetic

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 268	250 A	525 V	1
No. of poles: 3P+N			
GW D9 278	250 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 8 modules.
ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: Adjustable thermal release Ir = 0.63 - 0,8 - 1 x In
Fixed magnetic release Ii = 13 x In
Residual current circuit breaker tripping (Idn) and delay (dt) thresholds are adjustable:
Idn (A): 0.03 - 0.1 - 0.3 - 0.5 - 1 - 3
dt (ms): 0 - 60 - 200 - 400 - 700

MSXE - MCCB'S WITH ELECTRONIC RELEASE

MSXE 160 - MCCB'S with electronic release up to 160A - 36kA



GW D9 317

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 302	40 A	LSI	690 V	1
GW D9 306	125 A	LSI	690 V	1
GW D9 307	160 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 312	40 A	LSI	690 V	1
GW D9 316	125 A	LSI	690 V	1
GW D9 317	160 A	LSI	690 V	1
No. of poles: 4P				
GW D9 322	40 A	LSI	690 V	1
GW D9 326	125 A	LSI	690 V	1
GW D9 327	160 A	LSI	690 V	1

NOTES: it is not possible mounting on EN 50022 DIN rail.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 x In.
Neutral 100% protected for 4P circuit breakers.

MSXE 160 - MCCB'S with electronic release up to 160A - 65kA



GW D9 347

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 332	40 A	LSI	690 V	1
GW D9 336	125 A	LSI	690 V	1
GW D9 337	160 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 342	40 A	LSI	690 V	1
GW D9 346	125 A	LSI	690 V	1
GW D9 347	160 A	LSI	690 V	1
No. of poles: 4P				
GW D9 352	40 A	LSI	690 V	1
GW D9 356	125 A	LSI	690 V	1
GW D9 357	160 A	LSI	690 V	1

NOTES: it is not possible mounting on EN 50022 DIN rail.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% protected for 4P circuit breakers.

MSXE 160 - MCCB'S with electronic release up to 160A - 125kA



GW D9 527

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 502	40 A	LSI	690 V	1
GW D9 506	125 A	LSI	690 V	1
GW D9 507	160 A	LSI	690 V	1
No. of poles: 4P				
GW D9 522	40 A	LSI	690 V	1
GW D9 526	125 A	LSI	690 V	1
GW D9 527	160 A	LSI	690 V	1

NOTESS: it is not possible mounting on EN 50022 DIN rail.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In
Neutral 100% protected for 4P circuit breakers.

NEWS

MSXE 250 - MCCB'S with electronic release 250A - 36kA



GW D9 318

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 308	250 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 318	250 A	LSI	690 V	1
No. of poles: 4P				
GW D9 328	250 A	LSI	690 V	1

NOTES: it is not possible mounting on EN 50022 DIN rail.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% protected for 4P circuit breakers.

MSXE 250 - MCCB'S with electronic release 250A - 65kA



GW D9 348

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 338	250 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 348	250 A	LSI	690 V	1
No. of poles: 4P				
GW D9 358	250 A	LSI	690 V	1

NOTES: it is not possible mounting on EN 50022 DIN rail.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 9,95 - 1 x In.
Neutral 100% protected for 4P circuit breakers.

MSXE 250 - MCCB'S with electronic release 250A - 125kA



GW D9 528

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 508	250 A	LSI	690 V	1
No. of poles: 4P				
GW D9 528	250 A	LSI	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC)
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% protected for 4P circuit breakers.

NEWS

MSXE 400 - MCCB'S with electronic release up to 400A - 36kA



GW D9 372

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 371	400 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 372	400 A	LSI	690 V	1
No. of poles: 4P				
GW D9 329	250 A	LSI	690 V	1
GW D9 373	400 A	LSI	690 V	1
GW D9 374	400 A	LSIG	690 V	1

ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

MSXE 400 - MCCB'S with electronic release up to 400A - 50kA



GW D9 376

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 375	400 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 376	400 A	LSI	690 V	1
No. of poles: 4P				
GW D9 359	250 A	LSI	690 V	1
GW D9 377	400 A	LSI	690 V	1
GW D9 378	400 A	LSIG	690 V	1

ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

MSXE 400 - MCCB'S with electronic release up to 400A - 85kA



GW D9 533

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 531	400 A	LSI	690 V	1
No. of poles: 4P				
GW D9 389	250 A	LSI	690 V	1
GW D9 533	400 A	LSI	690 V	1
GW D9 534	400 A	LSIG	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC)
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

NEWS

MSXE 630 - MCCB'S with electronic release 630A - 36kA



GW D9 382

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 381	630 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 382	630 A	LSI	690 V	1
No. of poles: 4P				
GW D9 383	630 A	LSI	690 V	1
GW D9 384	630 A	LSIG	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,85 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

MSXE 630 - MCCB'S with electronic release 630A - 50kA



GW D9 386

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 385	630 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 386	630 A	LSI	690 V	1
No. of poles: 4P				
GW D9 387	630 A	LSI	690 V	1
GW D9 388	630 A	LSIG	690 V	1

ACCESSORIES: supplied with front terminals (FC).
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,85 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

MSXE 630 - MCCB'S with electronic release 630A - 70kA



GW D9 537

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 535	630 A	LSI	690 V	1
No. of poles: 4P				
GW D9 537	630 A	LSI	690 V	1
GW D9 538	630 A	LSIG	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC)
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,85 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

NEWS

MSXE 1000 - MCCB'S with electronic release up to 1000A - 50kA



GW D9 408

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 401	800 A	LSI	690 V	1
GW D9 406	1000 A	LSI	690 V	1
No. of poles: 3P+N				
GW D9 402	800 A	LSI	690 V	1
GW D9 407	1000 A	LSI	690 V	1
No. of poles: 4P				
GW D9 403	800 A	LSI	690 V	1
GW D9 408	1000 A	LSI	690 V	1
GW D9 404	800 A	LSIG	690 V	1
GW D9 409	1000 A	LSIG	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC) for 800A versions. Supplied with extended front terminals (FB) for 1000A versions. Operating lever extension for manual closing and opening operations.
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breaker.

MSXE 1000 - MCCB'S with electronic release up to 1000A - 70kA



GW D9 567

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Pack Carton
No. of poles: 3P				
GW D9 561	800 A	LSI	690 V	1
GW D9 565	1000 A	LSI	690 V	1
No. of poles: 4P				
GW D9 563	800 A	LSI	690 V	1
GW D9 567	1000 A	LSI	690 V	1
GW D9 564	800 A	LSIG	690 V	1
GW D9 568	1000 A	LSIG	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC) for 800A versions.
supplied with extended front terminals (FB) for 1000A versions.
operating lever extension for manual closing and opening operations.
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In
Neutral 100% or 50% protected for 4P circuit breakers.

NEWS

MSXE 1250 - MCCB'S with electronic release 1250A - 50kA



GW D9 415

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Terminal type	Interlocked	Pack Carton
No. of poles: 3P						
GW D9 411	1250 A	LSI	690 V	Front	No	1
GW D9 411 B	1250 A	LSI	690 V	Front	Yes	1
GW D9 412	1250 A	LSI	690 V	Rear	No	1
GW D9 412 B	1250 A	LSI	690 V	Rear	Yes	1
No. of poles: 4P						
GW D9 415	1250 A	LSI	690 V	Front	No	1
GW D9 415 B	1250 A	LSI	690 V	Front	Yes	1
GW D9 416	1250 A	LSI	690 V	Rear	No	1
GW D9 416 B	1250 A	LSI	690 V	Rear	Yes	1
GW D9 417	1250 A	LSIG	690 V	Front	No	1
GW D9 417 B	1250 A	LSIG	690 V	Front	Yes	1
GW D9 418	1250 A	LSIG	690 V	Rear	No	1
GW D9 418 B	1250 A	LSIG	690 V	Rear	Yes	1

NOTES: tthe codes with the final letter B indicate circuit breaker with cable mechanical interlock already fitted on it (cable for mechanical interlock to be ordered separately).
ACCESSORIES SUPPLIED: operating lever extension for manual closing and opening operations.
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breaker.

MSXE 1250 - MCCB'S with electronic release 1250A - 70kA



GW D9 583

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Terminal type	Interlocked	Pack Carton
No. of poles: 3P						
GW D9 581	1250 A	LSI	690 V	Front	No	1
GW D9 585	1250 A	LSI	690 V	Rear	No	1
No. of poles: 4P						
GW D9 583	1250 A	LSI	690 V	Front	No	1
GW D9 587	1250 A	LSI	690 V	Rear	No	1
GW D9 584	1250 A	LSIG	690 V	Front	No	1
GW D9 588	1250 A	LSIG	690 V	Rear	No	1

ACCESSORIES SUPPLIED: operating lever extension for manual closing and opening operations.
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breakers.

MSXE 1600 - MCCB'S with electronic release 1600A - 50kA



GW D9 426

Electronic release

Code	Rated current	Electronic release type	Rated voltage	Terminal type	Interlocked	Pack Carton
No. of poles: 3P						
GW D9 421	1600 A	LSI	690 V	Front	No	1
GW D9 421 B	1600 A	LSI	690 V	Front	Yes	1
GW D9 422	1600 A	LSI	690 V	Rear	No	1
GW D9 422 B	1600 A	LSI	690 V	Rear	Yes	1
No. of poles: 4P						
GW D9 425	1600 A	LSI	690 V	Front	No	1
GW D9 425 B	1600 A	LSI	690 V	Front	Yes	1
GW D9 426	1600 A	LSI	690 V	Rear	No	1
GW D9 426 B	1600 A	LSI	690 V	Rear	Yes	1
GW D9 427	1600 A	LSIG	690 V	Front	No	1
GW D9 427 B	1600 A	LSIG	690 V	Front	Yes	1
GW D9 428	1600 A	LSIG	690 V	Rear	No	1
GW D9 428 B	1600 A	LSIG	690 V	Rear	Yes	1

NOTES: tthe codes with the final letter B indicate circuit breaker with cable mechanical interlock already fitted on it (cable for mechanical interlock to be ordered separately).
ACCESSORIES SUPPLIED: operating lever extension for manual closing and opening operations.
CHARACTERISTICS: current regulation field Ir = 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In.
Neutral 100% or 50% protected for 4P circuit breaker.

NEWS

MSXM - SWITCH DISCONNECTORS

MSXM 160c - Switch disconnectors 160 A



GW D9 442

Switch-disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 441	160 A	525 V	1
No. of poles: 4P			
GW D9 442	160 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8875.
The space taken up on the EN 50022 DIN rail is approximately 4 modules for the 3P versions and 6 modules for the 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).

MSXM 250c - Switch disconnectors 250 A



GW D9 444

Switch-disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 443	250 A	525 V	1
No. of poles: 4P			
GW D9 444	250 A	525 V	1

NOTES: for mounting on EN 50022 DIN rail, choose the fixing bracket GWD8876.
The space taken up on the EN 50022 DIN rail is approximately 6 modules for the 3P versions and 8 modules for the 4P versions.
ACCESSORIES SUPPLIED: supplied with front terminals (FC).

MSXM 400 - Switch disconnectors 400 A



GW D9 446

Switch-disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 445	400 A	690 V	1
No. of poles: 4P			
GW D9 446	400 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).

MSXM 630 - Switch disconnectors 630 A



GW D9 448

Switch-disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 447	630 A	690 V	1
No. of poles: 4P			
GW D9 448	630 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC).

MSXM 1000 - Switch disconnectors up to 1000 A



GW D9 450

Switch-disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW D9 449	800 A	690 V	1
GW D9 451	1000 A	690 V	1
No. of poles: 4P			
GW D9 450	800 A	690 V	1
GW D9 452	1000 A	690 V	1

ACCESSORIES SUPPLIED: supplied with front terminals (FC). Operating lever extension for manual closing and opening operations.

MSXM 1250 - Switch disconnectors 1250 A



GW D9 454

Switch-disconnectors

Code	Rated current	Rated voltage	Terminal type	Interlocked	Pack Carton
No. of poles: 3P					
GW D9 453	1250 A	690 V	Front	No	1
GW D9 453 B	1250 A	690 V	Front	Yes	1
GW D9 459	1250 A	690 V	Rear	No	1
GW D9 459 B	1250 A	690 V	Rear	Yes	1
No. of poles: 4P					
GW D9 454	1250 A	690 V	Front	No	1
GW D9 454 B	1250 A	690 V	Front	Yes	1
GW D9 460	1250 A	690 V	Rear	No	1
GW D9 460 B	1250 A	690 V	Rear	Yes	1

NOTES: the codes with the final letter B indicate MMCB's with mechanical interlock wire already mounted (interlock cable to be ordered separately).
EQUIPMENT: operating lever extension for manual closing and opening operations.

MSXM 1600 - Switch disconnectors 1600 A



GW D9 457

Switch-disconnectors

Code	Rated current	Rated voltage	Terminal type	Interlocked	Pack Carton
No. of poles: 3P					
GW D9 455	1600 A	690 V	Front	No	1
GW D9 455 B	1600 A	690 V	Front	Yes	1
GW D9 457	1600 A	690 V	Rear	No	1
GW D9 457 B	1600 A	690 V	Rear	Yes	1
No. of poles: 4P					
GW D9 456	1600 A	690 V	Front	No	1
GW D9 456 B	1600 A	690 V	Front	Yes	1
GW D9 458	1600 A	690 V	Rear	No	1
GW D9 458 B	1600 A	690 V	Rear	Yes	1

NOTES: the codes with the final letter B indicate MMCB's with mechanical interlock wire already mounted (interlock cable to be ordered separately).
ACCESSORIES SUPPLIED: operating lever extension for manual closing and opening operations.

ACCESSORIES FOR MOULDED CASE CIRCUIT BREAKERS

Auxiliary contacts



GW D8 501

Auxiliary contacts of open/closed position

Code	Type of contact	Pack Carton
Suitable for: MSX/M160c-250c		
GW D8 501	1 Changeover	1
Suitable for: MSX/D/E/M125-1600		
GW D8 504	1 Changeover	1

APPLICATIONS: used in order to signal the position ON or OFF of the MCCB's.
CHARACTERISTICS: they are identified by the grey colour and with the AX symbol on the product.



GW D8 502

Auxiliary contacts of fault indicator switch

Code	Type of contact	Assembly position	Pack Carton
Suitable for: MSX/M160c-250c			
GW D8 502	1 Changeover	Left	1
GW D8 503	1 Changeover	Right	1
Suitable for: MSX/D/E/M125-1600			
GW D8 505	1 Changeover	-	1

APPLICATIONS: used in order to indicate the circuit breaker tripping status.
NOTES: GWD8502 must be placed to the left of the circuit breaker lever.
GWD8503 must be placed to the right of the circuit breaker lever.
CHARACTERISTICS: they are identified by the grey and black colours and with the AL symbol on the product.

Opening releases



GW D8 512

Shunt trip releases

Code	Rated voltage (V)	Pack Carton
Suitable for: MSX/M160c-250c		
GW D8 512	200 - 240 V ac	1
GW D8 513	380 - 450 V ac	1
GW D8 514	24V ac/dc	1
Suitable for: MSX/E/M125-1000		
GW D8 519	200 - 240 V ac	1
GW D8 520	380 - 450 V ac	1
GW D8 522	24V ac/dc	1
Suitable for: MSXE/M1250-1600		
GW D8 527	200 - 240 V ac	1
GW D8 528	380 - 450 V ac	1
GW D8 529	24V ac/dc	1

APPLICATIONS: allows the remote release of a MCCB'S when a certain voltage is applied to its terminals. When the release is powered, the contacts and the operating lever of the MCCB's assume the tripped position.
NOTE: The operating voltage range is 85% to 110% in AC and 75% to 125% in DC.
CHARACTERISTICS: they are identified by the grey colour and the SH symbol on the product.



GW D8 510

Remote tripping device for MSXD

Code	Suitable for	Pack Carton
GW D8 510	MSXD125-160-250	1

APPLICATIONS: allows the remote tripping of a RCBO's of MSXD series via NO push button connected.
NOTE: voltage-independent release unit.
The release unit must be positioned external on the right side of the MCCB's.



GW D8 542

Under voltage releases (UV)

Code	Rated voltage (V)	Pack Carton
Suitable for: MSX/M160c-250c		
GW D8 542	200 - 240 V ac	1
GW D8 545	380 - 450 V ac	1
GW D8 546	24 V dc	1
Suitable for: MSX/E/M125-630		
GW D8 552	200 - 240 V ac	1
GW D8 554	380 - 450 V ac	1
GW D8 557	24 V dc	1
Suitable for: MSXE/M1000-1600		
GW D8 564	200 - 240 V ac	1
GW D8 567	380 - 415 V ac	1
GW D8 571	24 V dc	1

APPLICATIONS: allows the remote release of a MCCB'S when the voltage applied to its terminals is between 35% and 70% of its rated voltage. When the release is not powered, the contacts and the circuit breaker operating lever assume the tripped position.

NOTE: they prevent the circuit breaker from closing until the voltage is greater than at least 85% of its rated voltage.

CHARACTERISTICS: They are identified by grey and black colours and with the UV symbol on the product.



GW D8 544

Delayed under voltage releases (UV)

Code	Rated voltage (V)	Pack Carton
Suitable for: MSX/M160c-250c		
GW D8 544	200 - 240 V ac	1
GW D8 548	24 V dc	1
Suitable for: MSX/E/M125-630		
GW D8 553	200 - 240 V ac	1
GW D8 555	380 - 415 V ac	1
GW D8 558	24 V dc	1
Suitable for: MSXE/M1000		
GW D8 565	220 - 240 V ac	1
GW D8 568	380 - 415 V ac	1
GW D8 572	24 V dc	1
Suitable for: MSXE/M1250-1600		
GW D8 566	220 - 240 V ac	1
GW D8 569	380 - 415 V ac	1
GW D8 573	24 V dc	1

APPLICATIONS: n order to allow remotely tripping of a circuit breaker when the voltage applied to its terminals is between 35% and 70% of its rated voltage. When the undervoltage release is not supplied, the contacts and the circuit breaker lever assume the circuit breaker tripping status.

NOTE : they prevent the closing of circuit breaker until the voltage exceeds at least 85% of its rated voltage.

The undervoltage release must be mounted outside, to the right of the crcuit breaker.

CHARACTERISTICS: They have 500ms delay time.

Motor operating devices



GW D8 590

Motor operating devices

Code	Rated voltage (V)	Pack Carton
Suitable for: MSX/M250c		
GW D8 581	230 - 240 V ac	1
GW D8 582	24 V dc	1
Suitable for: MSX/D125		
GW D8 584	230 - 240 V ac	1
GW D8 585	24 V dc	1
Suitable for: MSX/D/E160-250		
GW D8 590	230 - 240 V ac	1
GW D8 591	24 V dc	1
Suitable for: MSX/E/M400-630		
GW D8 595	110 - 240 V ac	1
GW D8 596	24 - 48 V dc	1
Suitable for: MSX/E/M1000		
GW D8 598	110 - 240 V ac	1
GW D8 599	24 - 48 V dc	1
Suitable for: MSX/E/M1250-1600		
GW D8 602	230 - 240 V ac	1
GW D8 603	24 V dc	1

APPLICATIONS: allows the MCCB'S remote opening and closing depending on the electrical signals received.

CHARACTERISTICS: to be mounted on the front of the MCCB's.

Rotary handles



GW D8 618

Direct rotary handle

Code	Suitable for	Pack Carton
GW D8 618	MSX/M160c	1
GW D8 619	MSX/M250c	1
GW D8 620	MSX/D125	1
GW D8 621	MSX/D/E160-250	1
GW D8 622	MSX/E/M400-630	1
GW D8 623	MSXE/M1000	1
GW D8 624	MSXE/M1250-1600	1



GW D8 630

Extended rotary handle

Code	Colour	Pack Carton
Suitable for: MSX/M160c		
GW D8 625	Black	1
Suitable for: MSX/M250c		
GW D8 626	Black	1
GW D8 627	Red - emergency	1
Suitable for: MSX/D125		
GW D8 628	Black	1
GW D8 629	Red - emergency	1
Suitable for: MSX/D/E160-250		
GW D8 630	Black	1
GW D8 631	Red - emergency	1
Suitable for: MSX/E/M400-630		
GW D8 632	Black	1
GW D8 633	Red - emergency	1
Suitable for: MSXE/M1000		
GW D8 634	Black	1
GW D8 635	Red - emergency	1
Suitable for: MSXE/M1250-1600		
GW D8 636	Black	1
GW D8 637	Red - emergency	1

Mechanical interlock



Lever mechanical interlocks type

Code	Type	Pack Carton
Suitable for: MSX/M250c		
GW D8 641	Right mechanical interlock	1
GW D8 643	Left mechanical interlock	1
Suitable for: MSX125		
GW D8 644	Right mechanical interlock	1
GW D8 646	Left mechanical interlock	1
Suitable for: MSX/E160-250		
GW D8 647	Right mechanical interlock	1
GW D8 649	Left mechanical interlock	1
Suitable for: MSX/E/M400-630		
GW D8 650	Right mechanical interlock	1
GW D8 652	Left mechanical interlock	1
Suitable for: MSXE/M1000		
GW D8 653	Right mechanical interlock	1
GW D8 655	Left mechanical interlock	1

NOTE: to create the lever interlock system it is necessary to provide and install both the left and right interlocks, depending on the size of the switch. It is suggested to use rotary handles or motor operators for circuit breakers MSX/E/M 400-630 and MSXE/M 1000.
CHARACTERISTICS: mechanism to be fixed on the front of both equal size 3 or 4 poles circuit breakers.



GW D8 661

Cable mechanical interlocks type

Code	Suitable for	Pack Carton
GW D8 661	MSX/M250c	1
GW D8 662	MSX125	1
GW D8 663	MSX/E160-250	1
GW D8 664	MSX/E/M400-630	1
GW D8 665	MSXE/M1000	1

NOTE: the wire interlock consists of two mechanisms connected by a steel cable. The mechanisms are fixed on two circuit breakers, limited by the length and bending capacity of the wire. To create the wire interlock system it is necessary to provide and install a mechanism for each interlocked circuit breaker.
The cable is to be ordered separately. It is suggested to use rotary handles or motor operators for circuit breakers MSX/E/M 400-630 and MSXE/M 1000.
CHARACTERISTICS: mechanism to be fixed on the front of both 3 or 4 pole circuit breakers (also with different sizes).
The circuit breakers can be placed in separate cubicles and at different heights.



GW D8 666

Cables for mechanical interlock

Code	Suitable for	Pack Carton
GW D8 666	MSX/D/E/M/c125-1000	1
GW D8 668	MSXE/M1250-1600	1

CHARACTERISTICS:cable length 1m

Mechanical block




GW D8 671

Padlocks lever lock

Code	Suitable for	Pack Carton
GW D8 671	MSX/M160c-250c	1
GW D8 672	MSX/D/E125-250	1
GW D8 673	MSX/E/M400-1000	1
GW D8 674	MSXE/M1250-1600	1

APPLICATIONS: allows the circuit breaker lever to be locked in the ON or OFF status using up to 3 padlocks.
NOTE: tthe locking devices for models 125A, 160A and 250A accept padlocks with a diameter of 5mm.
Locking devices for models from 400A to 1600A accept padlocks with a diameter of 8mm.

Plug-in versions



GW D8 681

Fixed part for plug-in MCCB

Code	Suitable for MCCB	Pack Carton
Suitable for: MSX125		
GW D8 681	3P	1
GW D8 682	4P	1
Suitable for: MSX/E160-250		
GW D8 683	3P	1
GW D8 684	4P	1
Suitable for: MSX/E/M400-630		
GW D8 685	3P	1
GW D8 686	4P	1
Suitable for: MSXE/M1000 (800A)		
GW D8 687	3P	1
GW D8 688	4P	1

APPLICATIONS: allows the quick replacement of the switch, without the need to interfere with the connections.
NOTE: to obtain the circuit-breaker in plug-in version, in addition to its fixes base, you need to provide the conversion kit.
CHARACTERISTICS: the circuit breaker in the plug-in version is automatically locked in the base when the operating lever is in the ON position. It can't be removed until the operating lever is in the OFF or tripped position.



GW D8 694

Conversion kit from fixed to plug-in version

Code	Suitable for MCCB	Pack Carton
Suitable for: MSX125		
GW D8 691	3P	1
GW D8 692	4P	1
Suitable for: MSX160-250		
GW D8 693	3P	1
GW D8 694	4P	1
Suitable for: MSXE160-250		
GW D8 695	3P	1
GW D8 696	4P	1
Suitable for: MSX/E/M400		
GW D8 697	3P	1
GW D8 698	4P	1
Suitable for: MSXE/M630		
GW D8 699	3P	1
GW D8 700	4P	1
Suitable for: MSXE/M1000 (800A)		
GW D8 701	3P	1
GW D8 702	4P	1

APPLICATIONS: allows the quick replacement of the of the MCCB's without the need to work on the connections.
NOTE: tto obtain the circuit-breaker in plug-in version, in addition to the transformation kit, you need to provide its fixed base.

Terminals for fixed part




GW D8 714

Code	No. of pieces	Pack Carton
Suitable for: MSX125		
GW D8 711	3	1
GW D8 712	4	1
Suitable for: MSX/E160-250		
GW D8 713	3	1
GW D8 714	4	1
Suitable for: MSX/E/M400-630		
GW D8 715	3	1
GW D8 716	4	1
Suitable for: MSXE/M1000 (800A)		
GW D8 717	3	1
GW D8 718	4	1

NOTE: they can be oriented and used as front or rear terminals


Terminal covers for fixed part terminals



GW D8 722

Code	Suitable for MCCB	No. of pieces	Pack Carton
Suitable for: MSX125			
GW D8 719	3P	1	1
GW D8 720	4P	1	1
Suitable for: MSX/E160-250			
GW D8 721	3P	1	1
GW D8 722	4P	1	1
Suitable for: MSX/E/M400-630			
GW D8 723	3P	1	1
GW D8 724	4P	1	1
Suitable for: MSXE/M1000 (800A)			
GW D8 725	3P	1	1
GW D8 726	4P	1	1

Plugs for internal accessories mounted on plug-in MCCB's




GW D8 733

Code	Suitable for	Pack Carton
Suitable for: MSX125-630		
GW D8 733	Auxiliary contacts	1
GW D8 734	Opening release	1
Suitable for: MSXE/M1000		
GW D8 735	Auxiliary contacts	1
GW D8 736	Opening release	1

APPLICATIONS: to be considered in case of a MCCB's in plug-in version with internal accessories. Requires 1 plug for each internal accessory (auxiliary contact or opening release).
NOTE: tto obtain the MCCB'S in plug-in version with internal accessories, in addition to the socket, a plug must be installed inside the fixed base.

Sockets for internal accessories mounted on plug-in MCCB's



GW D8 731

Code	Suitable for	Pack Carton
GW D8 731	MSX125-1000	1

APPLICATIONS: to be considered in case of a MCCB's in plug-in version with internal accessories. Requires 1 plug for each internal accessory (auxiliary contact or opening trip unit). Identical socket for each accessory type.
NOTE: to obtain the MCCB'S in plug-in version with internal accessories, in addition to the socket, a plug must be installed inside the fixed base.

Connection terminals

Extended front terminals FC



GW D8 742

Code	No. of pieces	Pack Carton
Suitable for: MSX/M160c		
GW D8 741	3	1
GW D8 742	4	1
Suitable for: MSX/M250c		
GW D8 743	3	1
GW D8 744	4	1
Suitable for: MSX/D125		
GW D8 745	3	1
GW D8 746	4	1
Suitable for: MSX/D/E160-250		
GW D8 747	3	1
GW D8 748	4	1
Suitable for: MSX/E/M400		
GW D8 749	3	1
GW D8 750	4	1
Suitable for: MSXE/M630		
GW D8 751	3	1
GW D8 752	4	1
Suitable for: MSXE/M1000 (800A)		
GW D8 754	3	1
GW D8 756	4	1

APPLICATIONS: terminals for the front connection of busbars or cable terminals.

Extended divaricated front terminals FB



GW D8 761

Code	No. of pieces	Pack Carton
Suitable for: MSX/M160c		
GW D8 761	3	1
GW D8 762	4	1
Suitable for: MSX/M250c		
GW D8 763	3	1
GW D8 764	4	1
Suitable for: MSX/E/M400		
GW D8 765	3	1
GW D8 766	4	1
Suitable for: MSXE/M630		
GW D8 767	3	1
GW D8 768	4	1

APPLICATIONS: terminals for the rear connection of busbars or cable terminals.

Front terminals for cables FW



GW D8 772

Code	No. of pieces	Pack Carton
Suitable for: MSX/D125		
GW D8 771	3	1
GW D8 772	4	1

APPLICATIONS: terminals for the front connection of bare wires.

Rear terminals RC



GW D8 784

Code	No. of pieces	Pack Carton
Suitable for: MSX/M160c		
GW D8 783	3	1
GW D8 784	4	1
Suitable for: MSX/M250c		
GW D8 785	3	1
GW D8 786	4	1
Suitable for: MSX/D125		
GW D8 787	3	1
GW D8 788	4	1
Suitable for: MSX/D160-250		
GW D8 789	3	1
GW D8 790	4	1
Suitable for: MSXE160-250		
GW D8 791	3	1
GW D8 792	4	1
Suitable for: MSX/E/M400		
GW D8 793	3	1
GW D8 794	4	1
Suitable for: MSXE/M630		
GW D8 795	3	1
GW D8 796	4	1
Suitable for: MSXE/M1000 (800A)		
GW D8 797	3	1
GW D8 798	4	1
Suitable for: MSXE/M1000 (1000A)		
GW D8 799	3	1
GW D8 800	4	1

APPLICATIONS: terminals for the rear connection of busbars or cable terminals.



GW D8 812

Terminal covers

Code	For terminals	Suitable for	No. of pieces	Pack Carton
Suitable for: MSX/M160c				
GW D8 811	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 812	Front FC and front extended FB	MCCB's 4P	1	1
GW D8 813	Front extended spread FB	MCCB's 3P	1	1
GW D8 814	Front extended spread FB	MCCB's 4P	1	1
GW D8 815	Rear RC	MCCB's 3P	1	1
GW D8 816	Rear RC	MCCB's 4P	1	1
Suitable for: MSX/M250c				
GW D8 817	Front FC	MCCB's 3P	1	1
GW D8 818	Front FC	MCCB's 4P	1	1
GW D8 819	Front extended FB	MCCB's 3P	1	1
GW D8 820	Front extended FB	MCCB's 4P	1	1
GW D8 821	Front extended spread FB	MCCB's 3P	1	1
GW D8 822	Front extended spread FB	MCCB's 4P	1	1
GW D8 823	Rear RC	MCCB's 3P	1	1
GW D8 824	Rear RC	MCCB's 4P	1	1
Suitable for: MSX/D125				
GW D8 825	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 826	Front FC and front extended FB	MCCB's 4P	1	1
GW D8 827	Front for cables FW	MCCB's 3P	1	1
GW D8 828	Front for cables FW	MCCB's 4P	1	1
GW D8 829	Rear RC	MCCB's 3P	1	1
GW D8 830	Rear RC	MCCB's 4P	1	1
Suitable for: MSX/D160-250				
GW D8 831	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 832	Front FC and front extended FB	MCCB's 4P	1	1
Suitable for: MSX/D/E160-250				
GW D8 835	Rear RC	MCCB's 3P	1	1
GW D8 836	Rear RC	MCCB's 4P	1	1
Suitable for: MSXE160-250				
GW D8 837	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 838	Front FC and front extended FB	MCCB's 4P	1	1
Suitable for: MSX/E/M400-630				
GW D8 839	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 840	Front FC and front extended FB	MCCB's 4P	1	1
GW D8 841	Front extended spread FB	MCCB's 3P	1	1
GW D8 842	Front extended spread FB	MCCB's 4P	1	1
GW D8 843	Rear RC	MCCB's 3P	1	1
GW D8 844	Rear RC	MCCB's 4P	1	1
Suitable for: MSXE/M1000				
GW D8 845	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 846	Front FC and front extended FB	MCCB's 4P	1	1
GW D8 847	Rear RC	MCCB's 3P	1	1
GW D8 848	Rear RC	MCCB's 4P	1	1
Suitable for: MSXE/M1250				
GW D8 849	Front FC and front extended FB	MCCB's 3P	1	1
GW D8 850	Front FC and front extended FB	MCCB's 4P	1	1

APPLICATIONS: prevent direct contact with the under voltage terminals of a circuit breaker.

NOTE: they cannot be mounted together with dividers.



GW D8 862

Seals for terminal covers

Code	Suitable for	Pack Carton
GW D8 862	MSX/M250c	1
GW D8 863	MSX/D/E/M125-630	1



GW D8 871

Dividers

Code	Suitable for	No. of pieces	Pack Carton
GW D8 871	MSX/M160c	1	1
GW D8 870	MSX/M250c	1	1
GW D8 872	MSX/D125	1	1
GW D8 869	MSX/D160-250	1	1
GW D8 873	MSXE160-250	1	1
GW D8 874	MSX/E/M400-1600	1	1

APPLICATIONS: ensure insulation between the phases of the circuit breaker terminals.
NOTE: they cannot be mounted with terminal covers.
Dividers are supplied for each circuit breaker (2 pieces for 3P MCCBs and 3 pieces for 3P+N and 4P MCCBs). Additional divider can be ordered individually. All dividers can be mounted on either side (line and load) of a circuit breaker.

Brackets for fixing on din rail



GW D8 876

Brackets for fixing on din rail

Code	Suitable for	Pack Carton
GW D8 875	MSX/M160c	1
GW D8 876	MSX/D/M/c125-250	1

APPLICATIONS: allow to install the MCCB'S on DIN rail.

Automatic switchover control unit



GW D8 886

Automatic switchover control unit

Code	Voltage operating	Installation	Pack Carton
GW D8 886	8V ÷ 35V dc	Pannel	1

APPLICATIONS: allows automatic switchover between the power supply network (single-phase or three-phase) and the generator line.
NOTE: for the correct functioning of the switchover control unit it is necessary
: -the power supply GWD8887
- 1 two positions built-in toggle handle switch with 2 contacts 1NO+1NC (preferably key)
- 2 fuse holders 3P+N (fuses 10.3x38) GW96312
- 2 fuse holders 2P (fuses 10.3x38) GW96302
- 1 contactor 2NO+2NC GWD6725
In addition, circuit breakers for protection of the power supply network and the generator line must each have the following accessories
: - 1 mechanical interlock (lever or cable)
- 1 motor operator
- 2 auxiliary contacts of position (AX)
- 1 auxiliary contact of fault indicator switch (AL)
CHARACTERISTICS: equipped with a 4-line backlit display.



GW D8 887

Automatic switchover control unit

Code	Input voltage	Output current	Pack Carton
GW D8 887	90V ÷ 305V ac	1A a 24V dc	1

APPLICATIONS: supplies direct current power to the automatic switchover control unit GWD8886 when the power supply network fails by taking power from the generator or from the battery (optional).
CHARACTERISTICS: the device can be mounted on DIN rail or plate.



MSX



Scan the QR Code and find out all the technical informations.

AN IDEAL RANGE FOR EVERY REQUIREMENT



The MSX moulded case circuit breaker range includes MCBs, RCCBs, electronic circuit breakers, and rotary disconnect switches.

INTEGRATED RCCB



The MSXD range, with integrated residual current protection, are similar in size to circuit breakers, but with no need for external relays or additional blocks.

DEDICATED AND COMPLETE ACCESSORIES



The MSX range includes a wide range of common accessories that allow streamlined installation and additional features such as remote opening, remote operation, motor control and more.

Rotary switch disconnectors

SWITCH DISCONNECTORS

	MSS 125		MSS 160		MSS 250		MSS 630		MSS125 THREE-WAY SWITCH (I 0 II)	MSS ATS 160 AUTOMATIC THREE-WAY SWITCH
										
In [A]	**3P**	**4P**	**3P**	**4P**	**3P**	**4P**	**3P**	**4P**	**4P**	**4P**
63	GW 97 721	GW 97 724	-	-	-	-	-	-	GW 97 758	GW 97 762
100	GW 97 722	GW 97 725	-	-	-	-	-	-	GW 97 760	GW 97 764
125	GW 97 723	GW 97 726	-	-	-	-	-	-	GW 97 761	-
160	-	-	GW 97 727	GW 97 728	-	-	-	-	-	GW 97 767
250	-	-	-	-	GW 97 729	GW 97 730	-	-	-	-
400	-	-	-	-	-	-	GW 97 731	GW 97 733	-	-
630	-	-	-	-	-	-	GW 97 732	GW 97 734	-	-

DOOR COUPLING ROTARY HANDLES - IP65



MSS 125 - MSS 160		MSS 250 - MSS 630		MSS 125 - THREE-WAY SWITCH (I 0 II)
Black handle	**Red handle**	**Black handle**	**Red handle**	**Black handle**
GW 98 521	GW 98 524	GW 98 522	GW 98 525	GW 98 523

Note: all the rotary handles include transmission rods.

REPLACEMENT HANDLES

			
MSS 125	**MSS 160**	**MSS 250 - MSS 630**	**MSS 125 - THREE-WAY SWITCH (I 0 II)**
GW 98 526	GW 98 527	GW 98 528	GW 98 529

AUXILIARY CONTACTS

			
MSS 125 - MSS 160	**MSS 250 - MSS 630**	**MSS 125 THREE-WAY SWITCH (I 0 II)**	**MSS 160 ATS AUTOMATIC THREE-WAY SWITCH**
GW 98 514	GW 98 515	GW 98 516	GW 97 774

TERMINAL COVERS (1 CODE = 1 PIECE)



MSS 160	MSS 250		MSS 630		MSS 160 ATS AUTOMATIC THREE-WAY SWITCH
3P - 4P	**3P**	**4P**	**3P**	**4P**	**4P**
GW 98 508	GW 98 509	GW 98 510	GW 98 511	GW 98 512	GW 97 773

97 MSS

Rotary switch disconnectors

The MSS rotary control switch disconnectors guarantee robustness and reliability in the control and isolation of circuits up to 630 A.The range consists of four different sizes depending on the current with high performance both in alternating current and in direct current.



MSS - ROTARY SWITCH DISCONNECTORS UP TO 630 A

MSS 125 - Switch disconnectors



GW 97 724

Switch disconnectors

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 3P				
GW 97 721	63 A	400 V	6	1
GW 97 722	100 A	400 V	6	1
GW 97 723	125 A	400 V	6	1
No. of poles: 4P				
GW 97 724	63 A	400 V	6	1
GW 97 725	100 A	400 V	6	1
GW 97 726	125 A	400 V	6	1

NOTE: mounting on DIN rail EN 50022 or on plate.

MSS 160 - Switch disconnectors




GW 97 728

Switch disconnectors

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 3P				
GW 97 727	160 A	400 V	8	1
No. of poles: 4P				
GW 97 728	160 A	400 V	8	1

NOTE: mounting on DIN rail EN 50022 or on plate.

MSS 250 - Switch disconnectors



GW 97 730

Switch disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW 97 729	250 A	400 V	1
No. of poles: 4P			
GW 97 730	250 A	400 V	1

NOTE: mounting on plate.

MSS 630 - Switch disconnectors



GW 97 734

Switch disconnectors

Code	Rated current	Rated voltage	Pack Carton
No. of poles: 3P			
GW 97 731	400 A	400 V	1
GW 97 732	630 A	400 V	1
No. of poles: 4P			
GW 97 733	400 A	400 V	1
GW 97 734	630 A	400 V	1

NOTE: mounting on plate.

MSS 125 - Three-way switch disconnector (I 0 II)



GW 97 761

Three-way switch disconnector (I 0 II)



Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 4P				
GW 97 758	63 A	400 V	12	1
GW 97 760	100 A	400 V	12	1
GW 97 761	125 A	400 V	12	1

NOTE: mounting on DIN rail EN 50022 or on plate.

MSS 160 ATS - Automatic three-way switch disconnectors



GW 97 767

Monobloc automatic switchover system with 3 positions

Code	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 4P				
GW 97 762	63 A	230 V	19	1
GW 97 764	100 A	230 V	19	1
GW 97 767	160 A	230 V	19	1

APPLICATIONS:

-line switchover via remote control;

-automatic inversion - while charged - of the source of two low voltage networks;

-management of power supply rescue systems, with interruption of the supply to the load during transfer.

It is possible to force operation in manual mode, via the AUTO/MAN selector.

NOTE: mounting on DIN rail EN 50022 or on plate.

Door coupling rotary handles - IP65



GW 98 522

Door coupling rotary handles - IP65

Code	Handle colour	Length shaft	Pack Carton
Suitable for: MSS 125 / MSS 160			
GW 98 521	Black	200 mm	1
GW 98 524	Red - emergency	200 mm	1
Suitable for: MSS 250 / MSS 630			
GW 98 522	Black	320 mm	1
GW 98 525	Red - emergency	320 mm	1
Suitable for: MSS 125 - Three-way switch disconnector			
GW 98 523	Black	200 mm	1

NOTE: all the rotary coupling handles include a shaft extension.

APPLICATIONS: the rotary coupling handles include a door locking function.

Auxiliary contacts



GW 98 516

Auxiliary contacts

Code	No. of pieces	Max no. of pieces per switch	No. and type of contact	Contact rating	Pack Carton
Suitable for: MSS 125 / MSS 160					
GW 98 514	1	2	1 Changeover	5 A - 250 V	1
Suitable for: MSS 250 / MSS 630					
GW 98 515	1	1	1 Changeover	16 A - 250 V	1
Suitable for: MSS 125 - Three-way switch disconnector					
GW 98 516	2	2	1 Changeover	5 A - 250 V	1
Suitable for: MSS 160 ATS - Automatic three-way switch disconnector					
GW 97 774	1	2	3 Changeover	5 A - 250 V	1

NOTE: auxiliary contacts are of the early closing type.



GW 97 775

Socket-outlet clamp

Code	No. of elements	Pack Carton
Suitable for: MSS 160 ATS - Automatic three-way switch disconnector		
GW 97 775	2	1

APPLICATION: makes 2 connection terminals available for wires with a section <= 1.5 mm and 2 single-pole.
Can be assembled in all terminals, without altering the capacity of the power terminals.

Terminal covers



GW 98 508

Terminal covers

Code	No. of poles	Number of terminal covers	Pack Carton
Suitable for: MSS 160			
GW 98 508	3P - 4P	1	1
Suitable for: MSS 250			
GW 98 509	3P	1	1
GW 98 510	4P	1	1
Suitable for: MSS 630			
GW 98 511	3P	1	1
GW 98 512	4P	1	1
Suitable for: MSS 160 ATS - Automatic three-way switch disconnector			
GW 97 773	4P	2	1

NOTE: for upstream and downstream protection, order 2 items with this code.

Installation accessories



GW 98 517

Common output point busbar

Code	No. of poles	Pack Carton
Suitable for: MSS 125 - Three-way switch disconnector		
GW 98 517	4P	1
Suitable for: MSS 160 ATS - Automatic three-way switch disconnector		
GW 97 772	4P	1

APPLICATION: facilitate the creation of a common point upstream or downstream for MSS 125 (GW98517), and output only for MSS 160 ATS (GW97772), avoiding the use of cables. The use of this accessory does not alter the capacity of the power terminals.



GW 98 528

Spare part handles for direct rotary operation

Code	Suitable for	Rated current	Pack Carton
GW 98 526	MSS 125	63 A - 100 A - 125 A	1
GW 98 527	MSS 160	160 A	1
GW 98 528	MSS 250 / MSS 630	250 A - 400 A - 630 A	1
GW 98 529	MSS 125 - Three-way switch disconnector (I - 0 - II)	63 A - 100 A - 125 A	1




97 MSS



Scan the QR Code and find out all the technical informations.

FULL RANGE OF ACCESSORIES



To meet the most specific needs, the rotary switches can be combined with IP65 watertight reset rotary switches (including reset rods), auxiliary contacts, terminal covers and parallel connections.

HIGH PERFORMANCE



The MSS rotary disconnect switches guarantee performance in both AC and DC and ensure maximum robustness, both in the case of short circuits and of numerous operations in critical conditions of use.

SEAMLESS INTEGRATION



With dedicated mounting kits, the MSS disconnect switches integrate seamlessly with all QDX range enclosures. The exceptional installation versatility of the MSS rotary disconnect switches makes them fully compatible with the 46 range distribution boards.

Electrical distribution boards







47 CVX 160 I

Flush-mounting distribution boards up to 160 A

p. 593

47 CVX 160 E

Wall-mounting distribution boards up to 160 A with extractable frame

p. 602

QDX 630 L

Modular distribution boards up to 630 A - IP43

p. 619



QDX 630 H

Monobloc and modular distribution boards up to 630 A - IP55


p. 639



QDX 1600 H

Modular enclosures up to 1600 A - IP55

p. 660



BUSBAR

Distribution systems for distribution boards



p. 684

General characteristics

DISTRIBUTION BOARDS AND CABINETS

	 **CVX 160I**	 **CVX 160E**	 **QDX 630L**	 **QDX 630H**	 **QDX 1600H**
Rated current In (A)	160	160	400 (wall-mounting) 630 (floor-mounting)	250 (wall-mounting) 630 (floor-mounting)	1600
Structure	Monobloc (panels and DIN rails included)	monobloc	modular	monobloc (wall-mounting) modular (floor-mounting)	modular
Version	flush-mounting	wall-mounting	wall and floor-mounting	wall and floor-mounting	floor-mounting
External cable compartment			yes	yes	yes
Extractable frame	yes	yes			
Degree of protection (IP)	30-40	30-40-55-65	30-43	30-55	30-55
Front panels	plastic	plastic	metal	metal	metal
Functional height (mm)	600 - 800 - 1000	600 - 800 - 1000 - 1200	1000 - 1200 1600 - 1800 - 2000	1000 - 1200 1600 - 1800 - 2000	1800 - 2000
Functional lenght (mm)	600	600	300 - 600 - 850 (wall-mounting) 400 - 600 - 850 (floor-mounting)	600 - 850 - 600+200 (wall-mounting) 400 - 600 - 850 - 600+300 (floor-mounting)	400 - 600 - 850 - 600+300
Functional depth (mm)	105	140 (without door) 170 (with solid door) 180 (with glass door)	200 - 300	200 - 300 (wall-mounting) 250 - 400 (floor-mounting)	600 - 800
Separation forms	1	1	1 - 2a	1 (wall-mounting) 1 - 2a (floor-mounting)	1-2a

CVX 160 I distribution boards

CVX 160 I STRUCTURES				
BOARDS WITH DIN RAILS, FRONT PANELS AND ALL FIXING ACCESSORIES INCLUDED				
STRUCTURES				
FUNCTIONAL DIM. (LxH)		600x600 mm	600x800 mm	600x1000 mm
GENERAL CHARACTERISTICS **In: up to 160A** **Capacity: 24 modules * per row** **Installation: indoor environments** **Colour: RAL 7035 grey**		**No. MODULES EN 50022 (17,5 mm)**		
		96	**120**	**144**
No. rows x No. modules		4 rows x 24 modules	5 rows x 24 modules	6 rows x 24 modules
				
Front panels with window height:	**(mm)**	150	200 (first row) 150 (other rows)	200 (first and second row) 150 (other rows)
IP 30	 **without door**	GW 47 072	GW 47 073	GW 47 074
IP 40	 **glass door**	GW 47 082	GW 47 083	GW 47 084
	 **solid door**	GW 47 087	GW 47 088	GW 47 089

* EN 50022 modules (17.5 mm)

CVX 160 I distribution boards

CVX 160 I DISTRIBUTION BOARD CONFIGURATION

Front panel height (mm)	FRONT PANELS			DIN RAIL KIT		
	Window panels	Solid panels	Pairs of hinges	EN 50022 rail	Double EN 50022 rail (aluminium)	EN 50035 rail
						
50	-	GW 47 173	-	-	-	-
150	GW 47 178	GW 47 174	GW 47 191	GW 47 251	GW 47 252	GW 47 253
200	GW 47 179	GW 47 175				

COMPLEMENTARY ITEMS

Earth bar	Wiring trunking supports	Nuts in cage	Module mask	Document pocket	Security lock with key
					
GW 47 193	GW 47 194 E	GW 47 195	GW 47 291	GW 46 447	GW 47 192

Board functional height (mm)	SPARE DOORS only for IP 40	
	glass door	solid door
		
600	GW 47 116	GW 47 121
800	GW 47 117	GW 47 122
1000	GW 47 118	GW 47 123

47 CVX 160 I

Flush-mounting distribution boards up to 160 A

The CVX 160 I range of pre-assembled flush-mounting distribution boards up to 160A allows configurations to be made to suit your needs, from a minimum capacity of 96 modules up to a maximum of 144, with three different heights from 600 mm to 1000 mm.



STRUCTURES

IP30 distribution boards



GW 47 072

Preassembled distribution boards in painted sheet steel - Colour grey RAL 7035 - Complete with outfit for modular devices - Without door

Code	Functional dim. LxHxD (mm)	Box dimensions BxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022	Pack Carton
GW 47 072	600x600x105	680x670x105	730x706x25	96 (24x4)	1
GW 47 073	600x800x105	680x870x105	730x906x25	120 (24x5)	1
GW 47 074	600x1000x105	680x1070x105	730x1106x25	144 (24x6)	1

ACCESSORIES SUPPLIED: mortar guard. Service identification label. Self-adhesive label to be filled out for certification in accordance with standard CEI 23-51.
Front panels complete with EN 50022 rail (DIN 35) and fixing accessories. Blanking module profile.
NOTES: IP30 distribution boards cannot be fitted with glass or solid doors.

IP40 distribution boards



GW 47 082

Preassembled distribution boards in painted sheet steel - Colour grey RAL 7035 - Complete with outfit for modular devices - Flat smoked tempered safety glass door with 2 locks

Code	Functional dim. LxHxD (mm)	Box dimensions BxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022	Pack Carton
GW 47 082	600x600x105	680x670x105	730x706x65	96 (24x4)	1
GW 47 083	600x800x105	680x870x105	730x906x65	120 (24x5)	1
GW 47 084	600x1000x105	680x1070x105	730x1106x65	144 (24x6)	1

ACCESSORIES SUPPLIED: mortar guard. Service identification label. Self-adhesive label to be filled out for certification according to standard CEI 23-52.
Front panels complete with EN 50022 rail (DIN 35) and fixing accessories. Blanking module profile. 2 double-fin keys.



GW 47 087

Preassembled distribution boards in painted sheet steel - Colour grey RAL 7035 - Complete with outfit for modular devices - Blank door in sheet metal with 2 locks

Code	Functional dim. LxHxD (mm)	Box dimensions BxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022	Pack Carton
GW 47 087	600x600x105	680x670x105	730x706x34	96 (24x4)	1
GW 47 088	600x800x105	680x870x105	730x906x34	120 (24x5)	1
GW 47 089	600x1000x105	680x1070x105	730x1106x34	144 (24x6)	1

ACCESSORIES SUPPLIED: mortar guard. Service identification label. Self-adhesive label to be filled out for certification according to standard CEI 23-51.
Front panels complete with EN 50022 rail (DIN 35) and fixing accessories. Blanking module profile. 2 double-fin keys.

47 CVX 160 I

FRONT CONFIGURATION

Front panels



GW 47 179

Front panels with window for modular devices

Code	External dim. LxH (mm)	Pack Carton
Modules: 24		
GW 47 178	600x150	1/10
GW 47 179	600x200	1/10

ACCESSORIES SUPPLIED: blanking module profile, pair of hinges.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 grip, prearrangement of the panels for rotation hinges (included).



GW 47 175

Blank front panels

Code	External dim. LxH (mm)	Pack Carton
Modules: 24		
GW 47 173	600x50	1/10
GW 47 174	600x150	1/10
GW 47 175	600x200	1/10

ACCESSORIES SUPPLIED: pair of hinges.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 grip, prearrangement of the panels, except GW47173, for rotation hinges (included).

DIN rail kit



GW 47 251

DIN rails for modular devices (90 range) and moulded case circuit breakers up to 160 A (MSX/M 160c, MSX/D 125, MSX/D 160 range) - Complete with brackets and supports for assembly

Code	Section dim. HxD (mm)	Profile	Material	Pack Carton
Modules: 24				
GW 47 251	35x15	EN 50022 (DIN 35)	Galvanized metal	1/10
GW 47 252	2x(35x7.5)	Double EN 50022 (DIN 35)	Aluminium	1/10
GW 47 253	32x15	EN 50035 (G 32)	Galvanized metal	1/10

NOTES: for the assembly of the MSX moulded case circuit breakers on DIN rail, order the appropriate fixingl kit.
Depth adapter GWD3317 is necessary if modular devices are mounted close to MCCB on the same DIN rail.

COMPLEMENTARY ITEMS

Accessories



GW 47 191

Pair of hinges for front panels

Code	Fixing type	Opening angle	Suitable for	Pack Carton
GW 47 191	Clip	90°	For panels H higher than 50 mm	1/20

ACCESSORIES SUPPLIED: 1 panel closing cap.



GW 47 194 E

Pair of supports for the fixing of wiring trunking

Code	Fixing type	Quantity	Pack Carton
GW 47 194 E	Clip on functional profile	2 pieces	1/20

APPLICATIONS: assembly of wiring trunking up to 60 mm in width vertically and up to 40 mm horizontally.




GW 47 291

Blanking module profile in plastic material - Colour grey RAL 7035

Code	No. of modules EN 50022	Pack Carton
GW 47 291	24	10

CHARACTERISTICS: clip fixing on DIN perforated front panels.



GW D3 317

Depth adapter

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).

Perforated and threaded earth busbar

Code	Dimensions LxHxD (mm)	N./diam. of threaded holes	Step drilling	For distribution boards	Pack Carton
GW 47 193	575x20x5	24xM6	18 mm	Flush and surface mounting	1/5

ACCESSORIES SUPPLIED: fixing accessories. (2 screws and 2 nuts in cage M6) 24 tin-plated screws M6.



GW 47 193

Adhesive document pocket

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10



GW 46 447

Security lock

Code	Characteristics	Pack Carton
GW 47 192	Yale type	1/10

NOTE: the lock is supplied with identical keys.



GW 47 192

Nut in cage

Code	Characteristics	Pack Carton
GW 47 195	Galvanised steel	10/100

APPLICATIONS: it is suitable for mounting wiring trunking and accessories on functional profile.



GW 47 195

Set of 4 metal brackets

Code	Characteristics	Pack Carton
GW 47 197	For fixing on plasterboard	1/10



GW 47 197

47 CVX 160 I

Spare parts



GW 47 116

Tempered smoked-glass flat safety doors for IP40 enclosures

Code	For boards LxH (mm)	Pack Carton
GW 47 116	600x600	1
GW 47 117	600x800	1
GW 47 118	600x1000	1

ACCESSORIES SUPPLIED: 2 mounting pins. 2 double-fin keys.



GW 47 121

Solid doors in painted sheet metal for IP40 distribution boards

Code	For boards LxH (mm)	Pack Carton
GW 47 121	600x600	1
GW 47 122	600x800	1
GW 47 123	600x1000	1

ACCESSORIES SUPPLIED: 2 mounting pins. 2 double-fin keys.




47 CVX 160 I



Scan the QR Code and find out all the technical informations.

SCREW AND TOOL-FREE MOUNTING



The rail brackets have been designed for screw-free fitting thanks to coupling on functional profiles. In addition, the innovative support allows the rails to be attached to the brackets and adjusted in depth without the use of screws and tools.

FAST FIXING OF INSULATION PANELS



The plastic front panels allow quick fitting via two ¼ turn inserts and require no grounding. A kit is included throughout the range to enable the panels to be hinged.

COMPLETE WITH ACCESSORIES



Once the distribution board size is chosen, a single order code includes the DIN rails and front insulation panels, as well as the metal case and door.

47 CVX 160 E







CVX 160 E distribution boards

CVX 160 E STRUCTURES

GENERAL CHARACTERISTICS In: up to 160 A Capacity: 24 modules per row Installation: indoor environments Colour: RAL 7035 grey		STRUCTURES			
FUNCTIONAL DIM. (LxH)		600x600 mm	600x800 mm	600x1000 mm	600x1200 mm
IP 30	**Without door** 	GW 47 001 E	GW 47 002 E	GW 47 003 E	GW 47 004 E
IP 40	**Glass door** 	GW 47 011 E	GW 47 012 E	GW 47 013 E	GW 47 014 E
	Solid door 	GW 47 021 E	GW 47 022 E	GW 47 023 E	GW 47 024 E
IP 55	**Glass door** 	GW 47 031 E	GW 47 032 E	GW 47 033 E	GW 47 034 E
	Solid door 	GW 47 041 E	GW 47 042 E	GW 47 043 E	GW 47 044 E
IP 65	**Solid door** 	-	GW 47 062 E	GW 47 063 E	GW 47 064 E


NOTE: the codes do not include DIN rail and front panels.

EXAMPLES OF BOARD CONFIGURATIONS

NO.ROWS / NO.MODULES MAX					
	Pitch 150 mm	 4 rows - 96 modules*	 5 rows - 120 modules*	 6 rows - 144 modules*	 8 rows - 192 modules*
	Pitch 200 mm	 3 rows - 72 modules*	 4 rows - 96 modules*	 5 rows - 120 modules*	 6 rows - 144 modules*

* EN 50022 modules (17.5 mm)

CVX 160 E DISTRIBUTION BOARD CONFIGURATION

Front panel height (mm)	KIT FOR INSTALLATION OF DEVICE ON DIN RAIL AND FRONT PANELS				DIN RAIL KIT			MOULDED CASE INSTALLATION KIT
	Window panels with EN 50022 rail	Window panels	Solid panels	Pairs of hinges	EN 50022 rail	Double EN 50022 rail (aluminium)	Double EN 50022 rail (aluminium)	For moulded case circuit breakers
								
50	-	-	GW 47 173	-	-	-	-	-
150	GW 47 171	GW 47 178	GW 47 174	GW 47 191	GW 47 181	GW 47 183	GW 47 182	GW 47 297 (MSX/M 160c)
200	GW 47 172	GW 47 179	GW 47 175					GW 47 298 (MSX/D 125)
								GW 47 299 (MSX/D 160)

COMPLEMENTARY ITEMS

Earth bar	Wiring trunking supports	Caged nuts	Cable gland plate	Module mask	Document pocket	Security lock with key	Earth terminal blocks
							
GW 47 193	GW 47 194 E	GW 47 195	GW 47 198 (Higher - Lower)	GW 47 291	GW 46 447	GW 47 192*	GW 45 538

*Not suitable for boards with IP65 protection degree

SPARE DOORS

Board functional height (mm)	IP 40		IP 55		IP 65
	Glass door	Solid door	Glass door	Solid door	Solid door
					
600	GW 47 116	GW 47 121	GW 47 136	GW 47 141	-
800	GW 47 117	GW 47 122	GW 47 137	GW 47 142	GW 47 162
1000	GW 47 118	GW 47 123	GW 47 138	GW 47 143	GW 47 163
1200	GW 47 119	GW 47 124	GW 47 139	GW 47 144	GW 47 164

47 CVX 160 E

Wall-mounting distribution boards up to 160 A with extractable frame



The CVX 160 E range of surface-mounted distribution boards up to 160A can be configured according to any requirement, from a minimum capacity of 72 modules up to a maximum of 192, using the appropriate choice of installation kits with holes every 150 mm or 200 mm.

STRUCTURES

IP30 distribution boards



GW 47 001 E

Monobloc distribution boards in painted sheet steel - Colour grey RAL 7035 - Without door - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 001 E	600x600x140	700x700x140	1
GW 47 002 E	600x800x140	700x900x140	1
GW 47 003 E	600x1000x140	700x1100x140	1
GW 47 004 E	600x1200x140	700x1300x140	1

ACCESSORIES SUPPLIED: 4pcs brackets complete with screws for wall fixing, 2pcs cable gland plates (upper and lower) complete with fixing screws.
NOTES: IP30 distribution boards cannot be fitted with glass or solid doors.

IP40 distribution boards



GW 47 011 E

Monobloc distribution boards in painted sheet steel - Colour grey RAL 7035 - Smoked flat tempered safety glass door equipped with 2 locks - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 011 E	600x600x180	700x700x180	1
GW 47 012 E	600x800x180	700x900x180	1
GW 47 013 E	600x1000x180	700x1100x180	1
GW 47 014 E	600x1200x180	700x1300x180	1

ACCESSORIES SUPPLIED: 4 brackets complete with screws for wall mounting. 2 cable gland plates (upper and lower) complete with fixing screws. 2 double-fin keys.



GW 47 021 E

Monobloc distribution boards in painted sheet steel - Colour grey RAL 7035 - Solid sheet metal door equipped with 2 locks - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 021 E	600x600x170	700x700x170	1
GW 47 022 E	600x800x170	700x900x170	1
GW 47 023 E	600x1000x170	700x1100x170	1
GW 47 024 E	600x1200x170	700x1300x170	1

ACCESSORIES SUPPLIED: 4 brackets complete with screws for wall mounting. 2 cable gland plates (upper and lower) complete with fixing screws. 2 double-fin keys.

IP55 distribution boards



GW 47 031 E

Monobloc distribution boards in painted sheet steel - Colour grey RAL 7035 Smoked flat tempered safety glass door equipped with 2 locks - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 031 E	600x600x180	700x700x180	1
GW 47 032 E	600x800x180	700x900x180	1
GW 47 033 E	600x1000x180	700x1100x180	1
GW 47 034 E	600x1200x180	700x1300x180	1

ACCESSORIES SUPPLIED: 4 brackets complete with screws for wall mounting. 2 cable gland plates (upper and lower) complete with fixing screws. 2 double-fin keys.
CHARACTERISTICS: sealing gaskets applied on the door and the cable gland plates.



GW 47 041 E

Monobloc distribution boards in painted sheet steel - Colour grey RAL 7035 - Solid sheet metal door equipped with 2 locks - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 041 E	600x600x170	700x700x170	1
GW 47 042 E	600x800x170	700x900x170	1
GW 47 043 E	600x1000x170	700x1100x170	1
GW 47 044 E	600x1200x170	700x1300x170	1

ACCESSORIES SUPPLIED: 4 brackets complete with screws for wall mounting. 2 cable gland plates (upper and lower) complete with fixing screws. 2 double-fin keys.
CHARACTERISTICS: sealing gaskets applied on the door and the cable gland plates.

IP65 distribution boards



GW 47 064 E

Monobloc distribution boards in painted sheet steel - Colour Grey RAL 7035 - Solid sheet metal door equipped with rod-mechanism lock - With extractable frame

Code	Functional dim. LxHxD (mm)	Outer dim. LxHxD (mm)	Pack Carton
GW 47 062 E	600x800x170	700x900x170	1
GW 47 063 E	600x1000x170	700x1100x170	1
GW 47 064 E	600x1200x170	700x1300x170	1

ACCESSORIES SUPPLIED: 4 brackets complete with screws for wall mounting. Key in zama.
CHARACTERISTICS: sealing gaskets applied on the door. Single lock with rod-mechanism lock with 4 mounting pins.

47 CVX 160 E

FRONT CONFIGURATION

Installation kit for devices on DIN rail




GW 47 172

Installation kit for modular devices (90 range) and moulded case devices up to 160 A (MSX/M 160c, MSX/D 125, MSX/D 160 range) - Complete with front panels with windows and standard DIN rail EN 50022 (DIN 35)

Code	Dimensions LxH (mm)	Section dim. HxD (mm)	Pack Carton
Modules: 24			
GW 47 171	600x150	35x15	1/10
GW 47 172	600x200	35x15	1/8

ACCESSORIES SUPPLIED: blanking module profile; pair of hinges; Standard EN 50022 (DIN 35) DIN rail in galvanised sheet metal with depth adjustment.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 grip. Option on the panels for rotation hinges (included).
NOTES: for the assembly of the MSX moulded case circuit breakers on DIN rail, order the appropriate fixingl kit.
Depth adapter GWD3317 is necessary if modular devices are mounted close to MCCB on the same DIN rail.

Installation kit for fixed MCCB's on plate



GW 47 297

Installation kit for a boxed RCD up to 160A (MSX/M 160c, MSX/D 125, MSX/D 160 series) complete with drilled front panels and attachment plates

Code	Dimensions LxH (mm)	For MCCB	No. of poles	Installation	Pack Carton
Modules: 24					
GW 47 297	600x200	MSX/M160c	3P - 4P	Horizontal	1/5
GW 47 298	600x200	MSX/D125	3P - 4P	Horizontal	1/5
GW 47 299	600x200	MSX/D160	3P - 4P	Horizontal	1/5

COMPONENTS: The kit consists of 1 galvanised steel plate, 1 plastic front panel with 1 pair of hinges and attachment accessories.
CHARACTERISTICS: RAL 7035 Grey front panel, in quick-coupling insulating material with ergonomic RAL 5003 Blue handle.

Front panels



GW 47 179

Front panels with window for modular devices

Code	Dimensions LxH (mm)	Pack Carton
Modules: 24		
GW 47 178	600x150	1/10
GW 47 179	600x200	1/10

ACCESSORIES SUPPLIED: blanking module profile. Pair of hinges.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 grip; prearrangement of the panels for rotation hinges (included).



GW 47 175


Blank front panels

Code	Dimensions LxH (mm)	Pack Carton
Modules: 24		
GW 47 173	600x50	1/10
GW 47 174	600x150	1/10
GW 47 175	600x200	1/10

ACCESSORIES SUPPLIED: pair of hinges.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 grip. Prearrangement of the panels, except GW47173, for rotation hinges (included)

INTERNAL CONFIGURATION

DIN rail kit



GW 47 181

DIN rails for modular devices (90 range) and moulded case circuit breakers up to 160 A (MSX/M 160c, MSX/D 125, MSX/D 160 range) - Complete with brackets and supports for assembly

Code	Section dim. HxD (mm)	Profile	Material	Pack Carton
Modules: 24				
GW 47 181	35x15	EN 50022 (DIN 35)	Galvanized metal	1/10
GW 47 183	2x(35x7.5)	Double EN 50022 (DIN 35)	Aluminium	1/10
GW 47 182	32x15	EN 50035 (G 32)	Galvanized metal	1/10

NOTES: To mount the MSX moulded case circuit breakers, order the appropriate DIN rail mounting kit.
Stacking of modular and moulded case devices requires the depth adapter GWD3317.

Back-mounting plates



GW 47 186

Back-mounting plates for non-modular devices complete with mounting supports

Code	Dimensions LxH (mm)	No. mounting straps	Pack Carton
Modules: 24			
GW 47 186	600x200	2	1/5
GW 47 187	600x400	4	1/5

ACCESSORIES SUPPLIED: support brackets and relative fixing accessories.
CHARACTERISTICS: possibility to adjust the depth of the plate; hot galvanised sheet metal plate 15/10 mm thick.

47 CVX 160 E

COMPLEMENTARY ITEMS

Accessories



GW 47 191

Pair of hinges for front panels

Code	Fixing type	Opening angle	Suitable for	Pack Carton
GW 47 191	Clip	90°	For panels H higher than 50 mm	1/20

ACCESSORIES SUPPLIED: 1 panel closing cap.



GW 47 194 E

Pair of supports for the fixing of wiring trunking

Code	Fixing type	Quantity	Pack Carton
GW 47 194 E	Clip on functional profile	2 pieces	1/20

APPLICATIONS: assembly of wiring trunking up to 60 mm in width vertically and up to 40 mm horizontally.




GW 47 291

Blanking module profile in plastic material - Colour grey RAL 7035

Code	No. of modules EN 50022	Pack Carton
GW 47 291	24	10

CHARACTERISTICS: clip fixing on DIN perforated front panels.



GW D3 317

Depth adapter

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).

Perforated and threaded earth busbar

Code	Dimensions LxHxD (mm)	N./diam. of threaded holes	Step drilling	For distribution boards	Pack Carton
GW 47 193	575x20x5	24xM6	18 mm	Flush and surface mounting	1/5

ACCESSORIES SUPPLIED: fixing accessories. (2 screws and 2 nuts in cage M6) 24 tin-plated screws M6.



GW 47 193

Earth terminal blocks

Code	N. terminal and section (mm²)	Pack Carton
GW 45 538	2x(1x35+11x16+13x10)	1

CHARACTERISTICS: copper bar with a 20 x 5 section and 6.5 mm hole spacing.



GW 45 538

Adhesive document pocket

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10



GW 46 447

47 CVX 160 E



GW 47 192

Security lock

Code	Characteristics	Pack Carton
GW 47 192	Yale type	1/10

NOTE: the lock is supplied with identical keys.
It's not suited for IP65 version.



GW 47 195

Nut in cage

Code	Characteristics	Pack Carton
GW 47 195	Galvanised steel	10/100

APPLICATIONS: it is suitable for mounting wiring trunking and accessories on functional profile.

Spare parts



GW 47 116

Tempered smoked-glass flat safety doors for IP40 enclosures

Code	For boards LxH (mm)	Pack Carton
GW 47 116	600x600	1
GW 47 117	600x800	1
GW 47 118	600x1000	1
GW 47 119	600x1200	1

ACCESSORIES SUPPLIED: 2 mounting pins. 2 double-fin keys.



GW 47 121

Solid doors in painted sheet metal for IP40 distribution boards

Code	For boards LxH (mm)	Pack Carton
GW 47 121	600x600	1
GW 47 122	600x800	1
GW 47 123	600x1000	1
GW 47 124	600x1200	1

ACCESSORIES SUPPLIED: 2 mounting pins, 2 double-fin keys.



GW 47 136

Tempered smoked-glass flat safety doors for IP55 enclosures

Code	For boards LxH (mm)	Pack Carton
GW 47 136	600x600	1
GW 47 137	600x800	1
GW 47 138	600x1000	1
GW 47 139	600x1200	1

ACCESSORIES SUPPLIED: 2 mounting pins. 2 double-fin keys.



GW 47 141

Solid doors in painted sheet metal for IP55 distribution boards

Code	For boards LxH (mm)	Pack Carton
GW 47 141	600x600	1
GW 47 142	600x800	1
GW 47 143	600x1000	1
GW 47 144	600x1200	1

ACCESSORIES SUPPLIED: 2 mounting pins, 2 double-fin keys.

47 CVX 160 E



GW 47 164

Solid doors in painted sheet steel for IP65 distribution boards equipped with rod-mechanism closures

Code	For boards LxH (mm)	Pack Carton
GW 47 162	600x800	1
GW 47 163	600x1000	1
GW 47 164	600x1200	1

ACCESSORIES SUPPLIED: 4 mounting pins. Key in zama.



GW 47 198

Cable gland plate - Colour Blue RAL 5003

Code	Description	No. of pieces	Material	Pack Carton
GW 47 198	Top/Bottom plate	1	Plastic	1/10




47 CVX 160 E



Scan the QR Code and find out all the technical informations.

SCREW AND TOOL-FREE MOUNTING



The rail brackets have been designed for screw-free fitting thanks to coupling on functional profiles. In addition, the innovative support allows the rails to be attached to the brackets and adjusted in depth without the use of screws and tools.

FAST FIXING OF INSULATION PANELS



The plastic front panels allow quick fitting via two ¼ turn inserts and require no grounding. A kit is included throughout the range to enable the panels to be hinged.

FACILITATED WIRING



The removable frame makes it easier to connect the switches, allowing convenient bench wiring first and then installation in the finished circuit box.

QDX 630 L

QDX 630 L distribution boards

QDX 630 L WALL-MOUNTING STRUCTURES

FUNCTIONAL DIM. (LxH)		600x1000 mm		600x1200 mm		850x1000 mm			
DEPTH		200 mm	300 mm	200 mm	300 mm	200 mm		300 mm	
Modular Capacity	Pitch 150 mm	144 mod. (24x6)		192 mod. (24x8)		144 mod. (24x6)	210 mod. (35x6)	144 mod. (35x6)	210 mod. (35x6)
	Pitch 200 mm	120 mod. (24x5)		144 mod. (24x6)		120 mod. (24x5)	175 mod. (35x5)	120 mod. (24x5)	175 mod. (35x5)
Rear Frames		GW D3 015		GW D3 016		GW D3 017			
Bases and headboards		GW D3 001	GW D3 004	GW D3 001	GW D3 004	GW D3 002		GW D3 005	
Front uprights		GW D3 007		GW D3 008		GW D3 007			
Side panels		GW D3 011	GW D3 013	GW D3 012	GW D3 014	GW D3 011		GW D3 013	
Glass doors		GW D3 605		GW D3 606		GW D3 607			
Blind doors		GW D3 609		GW D3 610		GW D3 611			
Internal compartment		-		-		GW D3 031		GW D3 032	
Side-by-side kit									

NOTE: 850mm wide structures can be used as 24-module structures plus internal compartment, adding the appropriate internal compartment kit.
NOTE: 300mm wide structures are external compartments dedicated to the cables, terminal block or busbar system.

QDX 630 L WALL-MOUNTING STRUCTURES

850x1200 mm				300x1000 mm		300x1200 mm	
200 mm		300 mm		200 mm	300 mm	200 mm	300 mm
192 mod. (24x8)	280 mod. (35x8)	192 mod. (24x8)	280 mod. (35x8)	-		-	
144 mod. (24x6)	210 mod. (35x6)	144 mod. (24x6)	210 mod. (35x6)	-		-	
GW D3 018				GW D3 019		GW D3 020	
GW D3 002		GW D3 005		GW D3 003	GW D3 006	GW D3 003	GW D3 006
GW D3 008				GW D3 009		GW D3 010	
GW D3 012		GW D3 014		GW D3 011	GW D3 013	GW D3 012	GW D3 014
GW D3 608				-		-	
GW D3 612				GW D3 613		GW D3 614	
GW D3 033		GW D3 034		-		-	
GW D3 035							

QDX 630 L

QDX 630 L distribution boards

QDX 630 L FLOOR-MOUNTING STUCTURES

FUNCTIONAL DIM. (LxH)		600x1600 mm		600x1800 mm		600x2000 mm	
DEPTH		200 mm	300 mm	200 mm	300 mm	200 mm	300 mm
Modular Capacity	Pitch 150 mm	240 mod. (24x10)		288 mod. (24x12)		312 mod. (24x13)	
	Pitch 200 mm	192 mod. (24x8)		216 mod. (24x9)		240 mod. (24x10)	
Rear Frames		GW D3 059		GW D3 060		GW D3 061	
Bases and headboards		GW D3 615	GW D3 616	GW D3 615	GW D3 616	GW D3 615	GW D3 616
Front uprights		GW D3 047		GW D3 048		GW D3 049	
Side panels		GW D3 053	GW D3 054	GW D3 055	GW D3 056	GW D3 057	GW D3 058
Glass doors		GW D3 627		GW D3 628		GW D3 629	
Blind doors		GW D3 633		GW D3 634		GW D3 635	
Internal compartment		-		-		-	
Side-by-side kit							

NOTE: 850mm wide structrures can be used as 24-module structures plus internal compartment, adding the appropriate internal compartment kit.

QDX 630 L FLOOR-MOUNTING STUCTURES

850x1600 mm				850x1800 mm				850x2000 mm			
200 mm		300 mm		200 mm		300 mm		200 mm		300 mm	
240 mod. (24x10)	350 mod. (35x10)	240 mod. (24x10)	350 mod. (35x10)	288 mod. (24x12)	420 mod. (35x12)	288 mod. (24x12)	420 mod. (35x12)	312 mod. (24x13)	455 mod. (35x13)	312 mod. (24x13)	455 mod. (35x13)
192 mod. (24x8)	280 mod. (35x8)	192 mod. (24x8)	280 mod. (35x8)	216 mod. (24x9)	315 mod. (35x9)	216 mod. (24x9)	315 mod. (35x9)	240 mod. (24x10)	350 mod. (35x10)	240 mod. (24x10)	350 mod. (35x10)
GW D3 062				GW D3 063				GW D3 064			
GW D3 617		GW D3 618		GW D3 617		GW D3 618		GW D3 617		GW D3 618	
GW D3 047				GW D3 048				GW D3 049			
GW D3 053		GW D3 054		GW D3 055		GW D3 056		GW D3 057		GW D3 058	
GW D3 630				GW D3 631				GW D3 632			
GW D3 636				GW D3 637				GW D3 638			
GW D3 083		GW D3 084		GW D3 085		GW D3 086		GW D3 087		GW D3 088	


GW D3 035

QDX 630 L

QDX 630 L distribution boards


QDX 630 L EXTERNAL COMPARTMENT							
FUNCTIONAL DIM. (LxH)		400x1600 mm		400x1800 mm		400x2000 mm	
DEPTH		200 mm	300 mm	200 mm	300 mm	200 mm	300 mm
Rear Frames		GW D3 065		GW D3 066		GW D3 067	
Bases and headboards		GW D3 619	GW D3 620	GW D3 619	GW D3 620	GW D3 619	GW D3 620
Front uprights		GW D3 050		GW D3 051		GW D3 052	
Side panels		GW D3 053	GW D3 054	GW D3 055	GW D3 056	GW D3 057	GW D3 058
Blind doors		GW D3 639		GW D3 640		GW D3 641	

QDX 630 L configurations




Wall-mounting board IP43 QDX 630 L
Functional dimension (LxHxD): 600x1200x300 mm
External dimension (LxHxD): 680x1260x295 mm

Quantity	Code	Description
1	GW 45 413	DIN35 PROFILE B600 QDX630L/H/1600H
1	GW D3 004	QDX 630L WALL MOUNT. BASE-HEADBOARD 600x300
1	GW D3 008	QDX 630L WALL MOUNT. FRONT UPRIGHTS B600/850 H1200
1	GW D3 014	QDX 630L WALL MOUNT. SIDE PANELS 1200x300
1	GW D3 016	QDX 630L WALL MOUNT. REAR FRAME 600x1200
1	GW D3 606	QDX 630L WALL MOUNT. GLASS DOOR 600x1200 AR
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
1	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR



Wall-mounting board IP43 QDX 630 L with external compartment
Functional dimension (LxHxD): (600+300)x1000x200 mm
External dimension (LxHxD): 970x1060x205 mm


Quantity	Code	Description
1	GW 47 691	GUIDE EN 50 022 - DIN 35
1	GW D3 001	QDX 630L WALL MOUNT. BASE-HEADBOARD 600x200
1	GW D3 003	QDX 630L WALL MOUNT. BASE-HEADBOARD 300x200
1	GW D3 007	QDX 630L WALL MOUNT. FRONT UPRIGHTS B600/850 H1000
1	GW D3 009	QDX 630L WALL MOUNT. FRONT UPRIGHTS B300 H1000
1	GW D3 011	QDX 630L WALL MOUNT. SIDE PANELS 1000x200
1	GW D3 015	QDX 630L WALL MOUNT. REAR FRAME 600x1000
1	GW D3 019	QDX 630L WALL MOUNT. REAR FRAME 300x1000
1	GW D3 605	QDX 630L WALL MOUNT. GLASS DOOR 600x1000 AR
1	GW D3 613	QDX 630L WALL MOUNT. BLIND DOOR 300x1000 AR
1	GW D3 035	QDX 630L WALL/FLOOR MOUNT. SIDE-BY-SIDE KIT
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 311	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 125mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm



Floor-mounting board IP43 QDX 630 L
Functional dimension (LxHxD): 600x1600x200 mm
External dimension (LxHxD): 680x1760x230 mm


Quantity	Code	Description
1	GW 45 413	DIN35 PROFILE B600 QDX630L/H/1600H
1	GW 45 545	HORIZ. FOUR-POLE DIVIDER 250A 24M 21 CONN. - QDX630-1600
1	GW D3 615	QDX 630L FLOOR MOUNT. BASE-HEADBOARD 600x200 GR
1	GW D3 047	QDX 630L FLOOR MOUNT. FRONT UPRIGHTS B600/850 H1600
1	GW D3 053	QDX 630L FLOOR MOUNT. SIDE PANELS 1600x200
1	GW D3 059	QDX 630L FLOOR MOUNT. REAR FRAME 600x1600
1	GW D3 627	QDX 630L FLOOR MOUNT. GLASS DOOR 600x1600 AR
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 311	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 125mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
3	GW D3 323	QDX BLIND FRONT PANEL 600x200
1	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR

QDX 630 L configurations



Floor-mounting board IP43 QDX 630 L with internal compartment
Functional dimension (LxHxD): 850x2000x300 mm
External dimension (LxHxD): 880x2160x320 mm

Quantity	Code	Description
1	GW 45 413	DIN35 PROFILE B600 QDX630L/H/1600H
2	GW 45 557	2 COPPER FLAT BARS 400 A 30x5 2000mm
1	GW D3 618	QQDX 630L FLOOR MOUNT. BASE-HEADBOARD 850X300 GR
1	GW D3 049	QQDX 630L FLOOR MOUNT. FRONT UPRIGHTS B600/850 H2000
1	GW D3 058	QQDX 630L FLOOR MOUNT. SIDE PANELS 2000x300
1	GW D3 064	QQDX 630L FLOOR MOUNT. REAR FRAME 850x2000
1	GW D3 632	QQDX 630L FLOOR MOUNT. GLASS DOOR 850x2000 AR
1	GW D3 088	QQDX 630L FLOOR MOUNT. INTERN.COMPART. 2000x300
6	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
6	GW D3 313	QQDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QQDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QQDX BLANKING MODULES PROFILE 1000mm
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
1	GW D3 324	QQDX BLIND FRONT PANEL 600x300
1	GW D3 428	QQDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
1	GW D3 471	QQDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR
1	GW D3 505	QKIT MSX/E/M400-630 600x300 HORIZ FIX
2	GW D3 709	QDX630L BUSBAR-HOLDER INT.COMPARTMENT D300



Floor-mounting board IP43 QDX 630 L with external compartment
Functional dimension (LxHxD): 600+400x2000x300 mm
External dimension (LxHxD): 1080x2160x320 mm

Quantity	Code	Description
2	GW 45 558	2 COPPER FLAT BARS 630 A 30x10 2000mm
1	GW D3 035	QDX 630L WALL/FLOOR MOUNT. SIDE-BY-SIDE KIT
1	GW D3 616	QDX 630L FLOOR MOUNT. BASE-HEADBOARD 600x300 GR
1	GW D3 620	QDX 630L FLOOR MOUNT. BASE-HEADBOARD 400X300 GR
1	GW D3 049	QDX 630L FLOOR MOUNT. FRONT UPRIGHTS B600/850 H2000
1	GW D3 052	QDX 630L FLOOR MOUNT. FRONT UPRIGHTS B400 H2000
1	GW D3 058	QDX 630L FLOOR MOUNT. SIDE PANELS 2000x300
1	GW D3 061	QDX 630L FLOOR MOUNT. REAR FRAME 600x2000
1	GW D3 067	QDX 630L FLOOR MOUNT. REAR FRAME 400x2000
1	GW D3 629	QDX 630L FLOOR MOUNT. GLASS DOOR 600x2000 AR
1	GW D3 641	QDX 630L FLOOR MOUNT. BLIND DOOR 400x2000 AR
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 321	QDX BLIND FRONT PANEL 600x100
1	GW D3 326	QDX BLIND FRONT PANEL 600x600
1	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
1	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
2	GW D3 708	QDX630L BUSBAR-HOLDER EXT.COMPARTMENT D300

QDX 630 L

Modular distribution boards up to 630 A - IP43

The QDX 630 L series of modular boards is available in both wall and floor versions. Both solutions share the same concept, accessories and quick and easy wiring modes. In fact, wiring is possible with the “structure completely open” and subsequently, the assembly of the board is completed.



STRUCTURES - DEGREE OF PROTECTION WITH DOOR IP43

Wall-mounting distribution boards



GW D3 002

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 001	600x200	650x205	1
GW D3 002	850x200	850x205	1
GW D3 004	600x300	650x295	1
GW D3 005	850x300	850x295	1

EQUIPMENT: no. 4 wall mounting brackets.



GW D3 018

Rear frames

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 015	600x1000	1
GW D3 016	600x1200	1
GW D3 017	850x1000	1
GW D3 018	850x1200	1


CHARACTERISTICS: bottom of the panel equipped with removable functional frames to create the internal compartment (internal compartment kit must be ordered separately).
IP43 gasket already applied on the bottom.



GW D3 008

Pair of front uprights

Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 007	1000	1060	1
GW D3 008	1200	1260	1




GW D3 012

Pair of side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 011	1000x200	1
GW D3 012	1200x200	1
GW D3 013	1000x300	1
GW D3 014	1200x300	1

QDX 630 L

Floor-mounting distribution boards



GW D3 618

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 615	600x200	650x230	1
GW D3 616	600x300	650x320	1
GW D3 617	850x200	850x230	1
GW D3 618	850x300	850x320	1

ACCESSORIES SUPPLIED: no. 2 wall mounting brackets.
Inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height.




GW D3 064

Rear frames

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 059	600x1600	1
GW D3 060	600x1800	1
GW D3 061	600x2000	1
GW D3 062	850x1600	1
GW D3 063	850x1800	1
GW D3 064	850x2000	1

CHARACTERISTICS: bottom of the panel equipped with removable functional frames to create the internal compartment (internal compartment kit must be ordered separately).
IP43 gasket already applied on the bottom.



GW D3 049

Pair of front uprights


Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 047	1600	1660	1
GW D3 048	1800	1860	1
GW D3 049	2000	2060	1



GW D3 058

Pair of side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 053	1600x200	1
GW D3 054	1600x300	1
GW D3 055	1800x200	1
GW D3 056	1800x300	1
GW D3 057	2000x200	1
GW D3 058	2000x300	1



GW D3 089

Pair of ventilated side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 089	1600x300	1
GW D3 090	1800x300	1
GW D3 091	2000x300	1

NOTES: In the case of the installation of aerated side panels, the enclosure protection rating is IP30.
Each side panel has 2 surfaces with slots drilling (one lower and one upper) each 58 cm² in size.

NEWS

Doors



GW D3 632

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 605	600x1000	1
GW D3 606	600x1200	1
GW D3 607	850x1000	1
GW D3 608	850x1200	1
GW D3 627	600x1600	1
GW D3 628	600x1800	1
GW D3 629	600x2000	1
GW D3 630	850x1600	1
GW D3 631	850x1800	1
GW D3 632	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Tempered glass.




GW D3 638

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 609	600x1000	1
GW D3 610	600x1200	1
GW D3 611	850x1000	1
GW D3 612	850x1200	1
GW D3 633	600x1600	1
GW D3 634	600x1800	1
GW D3 635	600x2000	1
GW D3 636	850x1600	1
GW D3 637	850x1800	1
GW D3 638	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

Internal compartment



GW D3 088

Internal compartments

Code	Suitable for structures LxHxD (mm)	Pack Carton
GW D3 031	850x1000x200	1
GW D3 032	850x1000x300	1
GW D3 033	850x1200x200	1
GW D3 034	850x1200x300	1
GW D3 083	850x1600x200	1
GW D3 084	850x1600x300	1
GW D3 085	850x1800x200	1
GW D3 086	850x1800x300	1
GW D3 087	850x2000x200	1
GW D3 088	850x2000x300	1

COMPONENTS: Triangular panel key for opening the internal compartment door, 3 crosspieces for attaching cables.
CHARACTERISTICS: Can be mounted on the right or left-hand side of board, B = 850 mm.

NEWS

QDX 630 L

External compartment



GW D3 620

Bases and headboards

Code	Suitable for	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 003	Wall-mounting distr. boards	300x200	290x205	1
GW D3 006	Wall-mount cabinet	300x300	290x295	1
GW D3 619	Floor-mounting distribution boards	400x200	400x230	1
GW D3 620	Floor-mounting distribution boards	400x300	400x320	1

COMPONENTS: 3 crosspieces for attaching cables.
4 wall attachment brackets for GWD3003 and GWD3006; 2 wall attachment brackets for GWD3619 and GWD3620.
Inspectable base for GWD3619 and GWD3620, supplied loose inside the package.
NOTES: Base height = 100 mm.
Associating the external compartment with the structure can be carried out using the side attachment kit, to be ordered separately.



GW D3 067

Rear frames

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 019	300x1000	1
GW D3 020	300x1200	1
GW D3 065	400x1600	1
GW D3 066	400x1800	1
GW D3 067	400x2000	1

CHARACTERISTICS: IP43 gasket already applied at bottom.



GW D3 009

Pair of front uprights

Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 009	1000	1060	1
GW D3 010	1200	1260	1
GW D3 050	1600	1660	1
GW D3 051	1800	1860	1
GW D3 052	2000	2060	1



GW D3 641

Blind doors


Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 613	300x1000	1
GW D3 614	300x1200	1
GW D3 639	400x1600	1
GW D3 640	400x1800	1
GW D3 641	400x2000	1

ACCESSORIES SUPPLIED: triangular insert key for opening the external compartment door.
CHARACTERISTICS: reversible door opening (right/left).

NEWS

FRONT CONFIGURATION

Device installation on DIN rail




GW D3 302

Window panels with DIN rail

Code	Functional dim. LxH (mm)	Pack Carton
No. modules: 24		
GW D3 301	600x150	1
GW D3 302	600x200	1
GW D3 303	600x300	1
No. modules: 35		
GW D3 304	850x150	1
GW D3 305	850x200	1
GW D3 306	850x300	1

COMPONENTS: Aluminium EN 50022 double rail (DIN 35).
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: Mounting the DIN rail requires brackets (bracket type depends on the depth of the panel), to be ordered separately.




GW D3 311

Pair of DIN rail mounting brackets

Code	Suitable for structures D (mm)	Suitable for	Pack Carton
GW D3 311	200	Modular devices range 90	1
GW D3 312	200	MCCB's MSX/D/M/c 160-250	1
GW D3 313	300	Modular devices range 90	1
GW D3 314	300	MCCB's MSX/D/M/c 160-250	1

ACCESSORIES SUPPLIED: no. 1 horizontal wiring trunking support for GWD3311 and no. 2 for horizontal wiring trunking supports for GWD3313. The supports must be mounted on the back of the of the double EN 50022 (DIN 35) rail.

MSX moulded case circuit breakers installation on plate




GW D3 504

Installation kit for MCCB's up to 630 A in horizontal position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 501	Horizontal	MSX/M160c	600x200	1
GW D3 502	Horizontal	MSX/D125	600x200	1
GW D3 503	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 504	Horizontal	MSXE160-250	600x200	1
GW D3 505	Horizontal	MSX/E/M400-630	600x300	1
Functional width: 850 mm				
GW D3 509	Horizontal	MSX/M160c	850x200	1
GW D3 510	Horizontal	MSX/D125	850x200	1
GW D3 511	Horizontal	MSX/D/M/c 160-250	850x200	1
GW D3 512	Horizontal	MSXE160-250	850x200	1
GW D3 513	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS:RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.



GW D3 517

Installation kit for MCCB's up to 630 A in vertical position fixed version


Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 555	Vertical	MSX/D125	600x300	1
GW D3 517	Vertical	MSX/D/M/c 160-250	600x300	1
GW D3 518	Vertical	MSXE160-250	600x300	1
GW D3 519	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 556	Vertical	MSX/D125	600x300	1
GW D3 523	Vertical	MSX/D/M/c 160-250	850x300	1
GW D3 524	Vertical	MSXE160-250	850x300	1
GW D3 525	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

NEWS

QDX 630 L

Horizontal installation kit for fixed version MSX up to 630A with direct rotary handle




GW D3 568

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 531	Horizontal	MSX/M160c	600x200	1
GW D3 532	Horizontal	MSX/M250c	600x200	1
GW D3 533	Horizontal	MSX/D125	600x200	1
GW D3 534	Horizontal	MSX/D160-250	600x200	1
GW D3 535	Horizontal	MSXE160-250	600x200	1
GW D3 536	Horizontal	MSX/E/M400-630	600x300	1
GW D3 568	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Installation kit for vertical MCCB'S up to 630A on plate with direct rotary handle




GW D3 569

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 569	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 570	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

Horizontal installation kit for fixed version MSX up to 630A with motor operating device




GW D3 557

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 541	Horizontal	MSX/D125	600x200	1
GW D3 542	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 543	Horizontal	MSXE160-250	600x200	1
GW D3 544	Horizontal	MSX/E/M400-630	600x300	1
GW D3 557	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanized sheet metal support plate, overhead brackets (if required) and pre-cut panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotating hinges and 1/4 turn locks.
NOTES: the kits are suitable for 3P and 4P switches.

Installation kit for vertical MCCB'S up to 630A on plate with motor operating device



GW D3 558

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 558	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 559	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: piastra di supporto in lamiera zincata, staffe di rialzo (se necessarie) e pannello pretranciato.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

NEWS

MSS switch disconnectors installation on plate




GW D3 553

Installation kit for switch disconnectors up to 630 A fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 551	Horizontal/Vertical	MSS 250	600x300	1
GW D3 553	Horizontal/Vertical	MSS 630	600x400	1
Functional width: 850 mm				
GW D3 552	Horizontal/Vertical	MSS 250	850x300	1
GW D3 554	Horizontal/Vertical	MSS 630	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Front panels




GW D3 324

Blind front panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 321	600x100	1
GW D3 322	600x150	1
GW D3 323	600x200	1
GW D3 324	600x300	1
GW D3 325	600x400	1
GW D3 326	600x600	1
GW D3 327	850x100	1
GW D3 328	850x150	1
GW D3 329	850x200	1
GW D3 330	850x300	1
GW D3 331	850x400	1
GW D3 332	850x600	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.



GW D3 333

Aeration front panels


Code	Functional dim. LxH (mm)	Pack Carton
GW D3 333	600x200	1
GW D3 334	850x200	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.

QDX 630 L

INTERNAL CONFIGURATION

Back-mounting plates



GW D3 336

Back-mounting plate for non-modular devices

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 336	600x200	1
GW D3 337	600x400	1
GW D3 338	600x600	1
GW D3 339	600x800	1
GW D3 340	600x1000	1
GW D3 341	850x200	1
GW D3 342	850x400	1
GW D3 343	850x600	1
GW D3 344	850x800	1
GW D3 345	850x1000	1

Dividers



GW D3 351

Vertical dividers

Code	Suitable for structures HxD (mm)	No. of pieces	Pack Carton
GW D3 351	1000x200	1	1
GW D3 352	1200x200	1	1
GW D3 353	1000x300	1	1
GW D3 354	1200x300	1	1
GW D3 355	1600x200	1	1
GW D3 356	1800x200	1	1
GW D3 357	2000x200	1	1
GW D3 358	1600x300	1	1
GW D3 359	1800x300	1	1
GW D3 360	2000x300	1	1

CHARACTERISTICS: plastic dividers to realize Form 2 configuration in the case of busbars mounted in the internal and external compartment.



GW D3 361

Horizontal dividers

Code	Suitable for structures LxD (mm)	No. of pieces	Pack Carton
GW D3 361	600x200	1	1
GW D3 362	850x200	1	1
GW D3 363	600x300	1	1
GW D3 364	850x300	1	1

CHARACTERISTICS: metal dividers used to divide the distribution board into sections.

COMPLEMENTARY ITEMS

Accessories

DIN rail mounting tool




GW D3 821

Code	Suitable for	Pack Carton
GW D3 821	Wall and floor boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.

Depth adapter



GW D3 317

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).

Pair of hole din row cover



GW D3 318

Code	Length (mm)	No. of pieces	Pack Carton
GW D3 318	1000	2	1

CHARACTERISTICS: clip fixing on window panels.

DIN profiles




Code	Section dim. HxD (mm)	Profile	Pack Carton
Length: 24 modules			
GW 45 413	35x15	EN 50022 (DIN 35)	1
GW 45 414	35x15	EN 50035 (G 32)	1
Length: 35 modules			
GW 45 418	35x15	EN 50022 (DIN 35)	1
GW 45 419	35x15	EN 50035 (G 32)	1
Length: 2000 mm			
GW 47 691	35x15	EN 50022 (DIN 35)	1/5
GW 47 692	32x15	EN 50035 (G 32)	1/5

NOTE: 24 and 35 modules DIN guides have fixing holess.
The 2000 mm DIN guides have no fixing holes.

NEWS

QDX 630 L




GW D3 426

Wiring vertical trunking supports

Code	No. of pieces	Pack Carton
GW D3 426	4	1
GW D3 428	8	1

CHARACTERISTICS: allows the installation of vertical wiring trunking with heights H=40 mm, H=60 mm or H=80 mm.
NOTES: not suitable for distribution boards with functional depth P=200 mm.



GW D3 471

Pair of supports for horizontal terminal block and earth bar

Code	Suitable for	Pack Carton
GW D3 471	Distribution boards L=600/850 mm	1



GW 46 448

Ventilation kit

Code	IP degree	Rated voltage	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 448	IP44	230 V - 50 / 60 Hz	125x117	123x115	1/2

CHARACTERISTICS: the fan takes in air from the outside and introduces it into the distribution board, creating a slight overpressure that prevents foreign particles from entering. Max fan capacity 60 m³/h. Absorbed power equal to 20 W.
APPLICATIONS: forced ventilation in critical thermal conditions.
ACCESSORIES SUPPLIED: drilling template.



GW 46 471

Aeration kit

Code	IP degree	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 471	IP44	125x117	123x115	1/10

ACCESSORIES SUPPLIED: drilling template.



Additional plinths

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 822	400x200	1
GW D3 823	600x200	1
GW D3 824	850x200	1
GW D3 825	400x300	1
GW D3 826	600x300	1
GW D3 827	850x300	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board

NEWS

Kit for side-by-side coupling




GW D3 035

Code	Suitable for	Pack Carton
GW D3 035	Wall and floor boards	1

ACCESSORIES SUPPLIED: fixing screws and gasket.

Copper earth busbars



GW 45 565

Code	Suitable for	Installation	Section (mm²)	Length (mm)	N./diam. of holes	Pack Carton
GW 45 565	Structures L=600 mm	Horizontal	25x4	420	13 Holes M6 and 2 holes ø 6 mm	1
GW 45 566	Structures L=850 mm	Horizontal	25x4	620	21 Holes M6 and 2 holes ø 6 mm	1
GW 45 559	Internal / external compartment	Vertical	20x5	1750	68 Holes M6 and 2 holes M12	1

Earth terminal blocks



GW 45 568

Code	Suitable for structures L (mm)	N. terminal and section (mm²)	Pack Carton
GW 45 568	600	2x(1x35+11x16+13x10)	1
GW 45 569	850	2x(1x35+11x16+13x10)	1

CHARACTERISTICS: copper busbars with a 20 x 5 section and 6.5 mm hole spacing.

Document holder pocket in self-adhesive insulating material with kit of blank labels




GW 46 447

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10

CHARACTERISTICS: can be inserted in all GEWISS enclosures from dimension 405x500x200 mm upwards.

Lifting eyebolts




GW D3 441

Code	Suitable for structures D (mm)	Pack Carton
GW D3 441	200	1
GW D3 442	300	1

NOTES: suitable for wall and floor mounting distribution boards.

QDX 630 L

Spare parts



GW D3 845

Spare part lock

Code	Suitable for	Pack Carton
GW D3 844	External compartment door	1
GW D3 845	Glass door / blind door	1


ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 439

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 439	Yale	Wall / floor mounting distribution boards	1
GW D3 852	Triangular	Internal / external compartment	1/10



GW D3 452

Spare part wall fixing brackets

Code	Suitable for	Pack Carton
GW D3 452	Wall-mounting distribuion boards	1
GW D3 453	Floor-mounting distribution boards	1



GW D3 454

Spare part screws

Code	Screws type	Pack Carton
GW D3 454	M6x10 (25 pcs)	1
GW D3 455	M6x12 (25 pcs)	1



GW D3 457

1/4 turn locks and spare part hinges

Code	Suitable for	No. of pieces	Pack Carton
GW D3 457	Front panels	4 pcs (locks) and 4 pcs (hinges)	1

NEWS



QDX 630 L



Scan the QR Code and find out all the technical informations.

DIN RAIL: QUICK ASSEMBLY AND DISASSEMBLY



The screw-free snap-in system is simple and immediate thanks to the quick assembly and disassembly of the dual aluminium DIN rails.

FACILITATED MAINTENANCE



The independent fixing of the front part and the removable sidewalls ensure the best working conditions for the operator.

INTEGRATED GASKET



The IP43 rated seal is already fitted in the distribution board, with no need for an external roll.

QDX 630 H

QDX 630 H distribution boards

QDX 630 H WALL-MOUNTING STRUCTURES

FUNCTIONAL DIM. (LxH)		600x1000 mm		600x1200 mm	
DEPTH		200 mm	300 mm	200 mm	300 mm
Modular Capacity	Pitch 150mm	144 mod. (24x6)		192 mod. (24x8)	
	Pitch 200 mm	120 mod. (24x5)		144 mod. (24x6)	
Monobloc structures		GW D3 101	GW D3 107	GW D3 102	GW D3 108
Glass doors		GW D3 651		GW D3 652	
Blind doors		GW D3 655		GW D3 656	
Vertical coupling kit		GW D3 121	GW D3 124	GW D3 121	GW D3 124

* Structures equipped with a side compartment (200 mm wide) dedicated to cables, terminal block or busbar system.


QDX 630 H WALL-MOUNTING STRUCTURES

(600+200)x1000 mm		(600+200)x1200 mm		850x1000 mm		850x1200 mm	
200 mm	**300 mm**	**200 mm**	**300 mm**	**200 mm**	**300 mm**	**200 mm**	**300 mm**
144 mod. (24x6)		192 mod. (24x8)		210 mod. (35x6)		280 mod. (35x8)	
120 mod. (24x5)		144 mod. (24x6)		175 mod. (35x5)		180 mod. (35x6)	
GW D3 103 *	GW D3 109 *	GW D3 104 *	GW D3 110 *	GW D3 105	GW D3 111	GW D3 106	GW D3 112
GW D3 651		GW D3 652		GW D3 653		GW D3 654	
GW D3 655		GW D3 656		GW D3 657		GW D3 658	
GW D3 122	GW D3 125	GW D3 122	GW D3 125	GW D3 123	GW D3 126	GW D3 123	GW D3 126

QDX 630 H

QDX 630 H distribution boards

QDX 630 H FLOOR-MOUNTING STRUCTURES

FUNCTIONAL DIM. (LxH)		600x1600 mm		600x1800 mm		600x2000 mm	
DEPTH		250 mm	400 mm	250 mm	400 mm	250 mm	400 mm
Modular Capacity	Pitch 150mm	240 mod. (24x10)		288 mod. (24x12)		312 mod. (24x13)	
	Pitch 200 mm	192 mod. (24x8)		216 mod. (24x9)		240 mod. (24x10)	
Bases and headboards		GW D3 659	GW D3 660	GW D3 659	GW D3 660	GW D3 659	GW D3 660
Front uprights		GW D3 147	GW D3 148	GW D3 149	GW D3 150	GW D3 152	GW D3 153
Rear uprights and functional frames							
Side panels		GW D3 675	GW D3 676	GW D3 677	GW D3 678	GW D3 680	GW D3 681
Rear panels		GW D3 684		GW D3 685		GW D3 686	
Glass doors		GW D3 696		GW D3 697		GW D3 698	
Blind doors		GW D3 803		GW D3 804		GW D3 805	
Blind doors for side compartment		-		-		-	
Side-by-side kit							

NOTE: the 600+300mm wide structures have a side compartment (300 mm wide) dedicated to the cables, terminal block or busbar system.


QDX 630 H FLOOR-MOUNTING STRUCTURES

(600+300)x1600 mm		(600+300)x1800 mm		(600+300)x2000 mm		850x1600 mm		850x1800 mm		850x2000 mm	
250 mm	**400 mm**	**250 mm**	**400 mm**	**250 mm**	**400 mm**	**250 mm**	**400 mm**	**250 mm**	**400 mm**	**250 mm**	**400 mm**
240 mod. (24x10)		288 mod. (24x12)		312 mod. (24x13)		350 mod. (35x10)		420 mod. (35x12)		455 mod. (35x13)	
192 mod. (24x8)		216 mod. (24x9)		240 mod. (24x10)		280 mod. (35x8)		315 mod. (35x9)		350 mod. (35x10)	
GW D3 663	GW D3 664	GW D3 663	GW D3 664	GW D3 663	GW D3 664	GW D3 667	GW D3 668	GW D3 667	GW D3 668	GW D3 667	GW D3 668
GW D3 170	GW D3 156 GW D3 171	GW D3 172	GW D3 158 GW D3 173	GW D3 175	GW D3 161 GW D3 176	GW D3 147	GW D3 148	GW D3 149	GW D3 150	GW D3 152	GW D3 153
GW D3 675	GW D3 676	GW D3 677	GW D3 678	GW D3 680	GW D3 681	GW D3 675	GW D3 676	GW D3 677	GW D3 678	GW D3 680	GW D3 681
GW D3 687		GW D3 688		GW D3 689		GW D3 690		GW D3 691		GW D3 692	
GW D3 696		GW D3 697		GW D3 698		GW D3 699		GW D3 801		GW D3 802	
GW D3 803		GW D3 804		GW D3 805		GW D3 806		GW D3 807		GW D3 808	
GW D3 812		GW D3 813		GW D3 814		-		-		-	


GW D3 217

QDX 630 H

QDX 630 H distribution boards


QDX 630 H EXTERNAL COMPARTMENT							
FUNCTIONAL DIM. (LxH)		400x1600 mm		400x1800 mm		400x2000 mm	
DEPTH		250 mm	400 mm	250 mm	400 mm	250 mm	400 mm
Bases and headboards		GW D3 671	GW D3 672	GW D3 671	GW D3 672	GW D3 671	GW D3 672
Uprights		GW D3 163		GW D3 164		GW D3 166	
Side panels		GW D3 675	GW D3 676	GW D3 677	GW D3 678	GW D3 680	GW D3 681
Rear panels		GW D3 693		GW D3 694		GW D3 695	
Blind doors		GW D3 809		GW D3 810		GW D3 811	

QDX 630 H configurations




Wall-mounting board IP55 QDX 630 H
Functional dimension (LxHxD): 600x1000x200 mm
External dimension (LxHxD): 620x1060x215 mm

Quantity	Code	Description
1	GW 45 413	DIN35 PROFILE B600 QDX630L/H/1600H
1	GW D3 101	QDX 630H WALL MOUNT. CASE 600x1000x200
1	GW D3 651	QDX 630H WALL MOUNT. GLASS DOOR 600x1000 AR
4	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
4	GW D3 311	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 125mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
1	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR



Wall-mounting board IP55 QDX 630 H with side compartment
Functional dimension (LxHxD): (600+200)x1200x300 mm
External dimension (LxHxD): 840x1260x305 mm


Quantity	Code	Description
1	GW 45 545	HORIZ. FOUR-POLE DIVIDER 250A 24M 21 CONN. - QDX630-1600
1	GW 47 691	GUIDE EN 50 022 - DIN 35
1	GW D3 110	QDX 630H WALL MOUNT. CASE 600+200x1200x300
1	GW D3 652	QDX 630H WALL MOUNT. GLASS DOOR 600x1200 AR
2	GW D3 301	QDX WINDOW PANEL WITH DIN RAIL 600x150
2	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
4	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
2	GW D3 467	HORIZ. CROSS PIECES B600+200 PARETE QDX630H
1	GW D3 551	KIT MSS250 600x300 HORIZ/VERT



Floor-mounting board IP55 QDX 630 H
Functional dimension (LxHxD): 850x1800x250 mm
External dimension (LxHxD): 900x2000x250 mm


Quantity	Code	Description
1	GW 45 418	DIN35 PROFILE B850 QDX630L/H/1600H
2	GW 45 551	2 COPPER FLAT BARS 250 A 20x5 1000mm
1	GW D3 667	QDX 630H FLOOR MOUNT. BASE-HEADBOARD 850x250 GR
1	GW D3 149	QDX 630H FLOOR MOUNT. UPRIGHTS 600/850x1800x250
1	GW D3 677	QDX 630H FLOOR MOUNT. SIDE PANELS 1800x250 GR
1	GW D3 691	QDX 630H FLOOR MOUNT. REAR PANEL 850x1800 GR
1	GW D3 801	QDX 630H FLOOR MOUNT. GLASS DOOR 850x1800 AR
3	GW D3 305	QDX WINDOW PANEL WITH DIN RAIL 850x200
3	GW D3 311	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 125mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 327	QDX BLIND FRONT PANEL 850x100
1	GW D3 329	QDX BLIND FRONT PANEL 850x200
1	GW D3 332	QDX BLIND FRONT PANEL 850x850
1	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR
1	GW D3 552	KIT MSS250 850x300 HORIZ/VERT
1	GW D3 722	QDX630H/1600H BUSBAR-HOLDER 250-400A L850

QDX 630 H configurations



Floor-mounting board IP55 QDX 630 H with side compartment
Functional dimension (LxHxD): (600+300)x2000x400 mm
External dimension (LxHxD): 995x2200x400 mm

Quantity	Code	Description
2	GW 45 558	2 COPPER FLAT BARS 630 A 30x10 2000mm
1	GW D3 664	QDX 630H FLOOR MOUNT. BASE-HEADBOARD 600+300x400 GR
1	GW D3 161	QDX 630H FLOOR MOUNT. FRONT UPRIGHTS 600/+300x2000
1	GW D3 176	QDX 630H FLOOR MOUNT. UPRIGHTS 600/+300x2000
1	GW D3 681	QDX 630H FLOOR MOUNT. SIDE PANELS 2000x400 GR
1	GW D3 689	QDX 630H FLOOR MOUNT. REAR PANEL 600+300x2000 GR
1	GW D3 698	QDX 630H FLOOR MOUNT. GLASS DOOR 600x2000 AR
1	GW D3 814	QDX 630H FLOOR MOUNT. SIDE COMPART.DOOR 600+300x2000 GR
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 321	QDX BLIND FRONT PANEL 600x100
1	GW D3 326	QDX BLIND FRONT PANEL 600x600
1	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
1	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
2	GW D3 727	QDX630H BUSBAR-HOLDER INT.COMPART. 630-800A D400



Floor-mounting board IP55 QDX 630 H with external compartment
Functional dimension (LxHxD): (600+400)x2000x400 mm
External dimension (LxHxD): 1100x2200x400 mm

Quantity	Code	Description
1	GW 45 413	DIN35 PROFILE B600 QDX630L/H/1600H
1	GW D3 660	QDX 630H FLOOR MOUNT. BASE-HEADBOARD 600x400 GR
1	GW D3 672	QDX 630H FLOOR MOUNT. BASE-HEADBOARD 400x400 GR
1	GW D3 153	QDX 630H FLOOR MOUNT. UPRIGHTS 600/850x2000x400
1	GW D3 166	QDX 630H FLOOR MOUNT. UPRIGHTS 400x2000
1	GW D3 681	QDX 630H FLOOR MOUNT. SIDE PANELS 2000x400 GR
1	GW D3 686	QDX 630H FLOOR MOUNT. REAR PANEL 600x2000 GR
1	GW D3 695	QDX 630H FLOOR MOUNT. REAR PANEL 400x2000 GR
1	GW D3 698	QDX 630H FLOOR MOUNT. GLASS DOOR 600x2000 AR
1	GW D3 811	QDX 630H FLOOR MOUNT. BLIND DOOR 400x2000 AR
1	GW D3 217	QDX 630-1600H FLOOR MOUNT. SIDE-BY-SIDE KIT
6	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
6	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
1	GW D3 324	QDX BLIND FRONT PANEL 600x300
1	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
2	GW D3 468	HORIZ. CROSS PIECES B400 QDX630H
1	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR
1	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
2	GW D3 754	QDX630H/1600H SHAPED BUSBAR-HOLDER AL
2	GW D3 791	QDX ALUMINIUM SHAPED BUSBARS 630A 30x40

QDX 630 H

Monobloc and modular distribution boards up to 630 A - IP55

The QDX 630 H range of boards is available in two distinct solutions, wall and floor mounting. Monobloc structure in welded sheet metal for wall mounting version and modular structure with fully removable front for floor mounting version. It is ideal in all those applications where maximum protection from external agents is needed.



STRUCTURES - DEGREE OF PROTECTION WITH DOOR IP55

Wall-mounting distribution boards



GW D3 101

Case

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 101	600x1000x200	620x1060x215	1
GW D3 102	600x1200x200	620x1260x215	1
GW D3 103	(600+200)x1000x200	840x1060x215	1
GW D3 104	(600+200)x1200x200	840x1260x215	1
GW D3 105	850x1000x200	820x1060x215	1
GW D3 106	850x1200x200	820x1260x215	1
GW D3 107	600x1000x300	620x1060x305	1
GW D3 108	600x1200x300	620x1260x305	1
GW D3 109	(600+200)x1000x300	840x1060x305	1
GW D3 110	(600+200)x1200x300	840x1260x305	1
GW D3 111	850x1000x300	820x1060x305	1
GW D3 112	850x1200x300	820x1260x305	1

EQUIPMENT: no. 4 wall mounting brackets.

NOTES: The GWD3103, GWD3104, GWD3109 and GWD3110 cases are equipped with an associated side compartment (200 mm wide) for the cables, terminal block or bar system. To secure the cables in the side compartment, use the pair of GWD3467 crosspieces, to be ordered separately.

The doors of the side compartment for codes GWD3103, GWD3104, GWD3109 and GWD3110 are supplied pre-mounted on the case.



GW D3 651

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 651	600x1000	1
GW D3 652	600x1200	1
GW D3 653	850x1000	1
GW D3 654	850x1200	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.

CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

Tempered glass.



GW D3 655

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 655	600x1000	1
GW D3 656	600x1200	1
GW D3 657	850x1000	1
GW D3 658	850x1200	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.

CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

NEWS

QDX 630 H

Floor mounting distribution boards - Single board

Base and headboard



GW D3 659

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 659	600x250	650x250	1
GW D3 660	600x400	650x400	1
GW D3 667	850x250	850x250	1
GW D3 668	850x400	850x400	1

ACCESSORIES SUPPLIED: no. 2 wall mounting brackets.
Inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height.

Uprights and functional frames



GW D3 152

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 147	1600x250	1700x250	1
GW D3 148	1600x400	1700x400	1
GW D3 149	1800x250	1900x250	1
GW D3 150	1800x400	1900x400	1
GW D3 152	2000x250	2100x250	1
GW D3 153	2000x400	2100x400	1

Pair of side panels



GW D3 680

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 675	1600x250	1
GW D3 676	1600x400	1
GW D3 677	1800x250	1
GW D3 678	1800x400	1
GW D3 680	2000x250	1
GW D3 681	2000x400	1

Pair of ventilated side panels



GW D3 218

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 815	1600x400	1
GW D3 816	1800x400	1
GW D3 817	2000x400	1

NOTES: In the case of installation of aerated side panels, the enclosure protection rating is IP30.
Each side panel has 2 surfaces with slits (one lower and one upper) each 58 cm² in size.

Rear panels



GW D3 686

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 684	600x1600	1
GW D3 685	600x1800	1
GW D3 686	600x2000	1
GW D3 690	850x1600	1
GW D3 691	850x1800	1
GW D3 692	850x2000	1

NEWS

Floor-mounting distribution boards with side compartment




GW D3 664

Bases and headboard

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 663	(600+300)x250	945x250	1
GW D3 664	(600+300)x400	945x400	1

CHARACTERISTICS: Structures are equipped with an associated side compartment (300 mm wide) for the cables, terminal block or bar system.
COMPONENTS: 2 wall mounting brackets and 4 crosspieces for attaching cables.
Inspectable base supplied loose inside the package.
NOTES: Base height = 100 mm.




GW D3 175

Uprights and functional frames

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 170	1600x250	1700x250	1
GW D3 172	1800x250	1900x250	1
GW D3 175	2000x250	2100x250	1

NOTES: uprights and functional frames suitable only for floor-mounting distribution boards with side compartment with functional depth P=250 mm.




GW D3 161

Front uprights

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 156	1600x400	1700x400	1
GW D3 158	1800x400	1900x400	1
GW D3 161	2000x400	2100x400	1

NOTES: uprights suitable only for floor-mounting distribution boards with side compartment with functional depth P=400 mm.
To complete the structure you need the rear uprights and functional frames to be ordered separately.



GW D3 176

Rear uprights and rear functional frames

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 171	1600x400	1700x400	1
GW D3 173	1800x400	1900x400	1
GW D3 176	2000x400	2100x400	1

NOTES: uprights and functional frames suitable only for floor-mounting distribution boards with side compartment with functional depth P=400 mm.
To complete the structure you need the front uprights and functional frames to be ordered separately.



GW D3 689

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 687	(600+300)x1600	1
GW D3 688	(600+300)x1800	1
GW D3 689	(600+300)x2000	1

NEWS

QDX 630 H



GW D3 814

Blind doors for side compartment

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 812	(600+300)x1600	1
GW D3 813	(600+300)x1800	1
GW D3 814	(600+300)x2000	1

ACCESSORIES SUPPLIED: triangular insert key for opening side compartment door.

Doors



GW D3 698

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 696	600x1600	1
GW D3 697	600x1800	1
GW D3 698	600x2000	1
GW D3 699	850x1600	1
GW D3 801	850x1800	1
GW D3 802	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Tempered glass.



GW D3 805

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 803	600x1600	1
GW D3 804	600x1800	1
GW D3 805	600x2000	1
GW D3 806	850x1600	1
GW D3 807	850x1800	1
GW D3 808	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

NEWS

External compartment

Bases and headboards



GW D3 672

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 671	400x250	400x250	1
GW D3 672	400x400	400x400	1

COMPONENTS: 2 wall mounting brackets.
Inspectable base supplied loose inside the package.
NOTES: Base height = 100 mm.
Associating the external compartment with the structure can be carried out using the side attachment kit, to be ordered separately.
To secure the cables in the outer compartment, use the pair of GWD3468 crosspieces, to be ordered separately.


Uprights and functional frames



GW D3 166

Code	Functional dim. LxH (mm)	External dim. HxD (mm)	Pack Carton
GW D3 163	400x1600	400x1700	1
GW D3 164	400x1800	400x1900	1
GW D3 166	400x2000	400x2100	1

Rear panels



GW D3 695

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 693	400x1600	1
GW D3 694	400x1800	1
GW D3 695	400x2000	1

Blind doors



GW D3 811

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 809	400x1600	1
GW D3 810	400x1800	1
GW D3 811	400x2000	1


ACCESSORIES SUPPLIED: door with triangular panel locks.
CHARACTERISTICS:possibility of mounting the door with reversible opening (right/left).

NEWS

QDX 630 H

FRONT CONFIGURATION

Device installation on DIN rail




GW D3 302

Window panels with DIN rail

Code	Functional dim. LxH (mm)	Pack Carton
No. modules: 24		
GW D3 301	600x150	1
GW D3 302	600x200	1
GW D3 303	600x300	1
No. modules: 35		
GW D3 304	850x150	1
GW D3 305	850x200	1
GW D3 306	850x300	1

COMPONENTS: Aluminium EN 50022 double rail (DIN 35).
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: Mounting the DIN rail requires brackets (bracket type depends on the depth of the panel), to be ordered separately.




GW D3 313

Pair of DIN rail mounting brackets

Code	Suitable for structures D (mm)	Suitable for	Pack Carton
GW D3 311	200 / 250	Modular devices range 90	1
GW D3 312	200 / 250	MCCB's MSX/D/M/c 160-250	1
GW D3 313	400	Modular devices range 90	1
GW D3 314	400	MCCB's MSX/D/M/c 160-250	1

ACCESSORIES SUPPLIED: no. 1 horizontal wiring trunking support for GWD3311 and no. 2 for horizontal wiring trunking supports for GWD3313. The supports must be mounted on the back of the of the double EN 50022 (DIN 35) rail.

MSX moulded case circuit breakers installation on plate




GW D3 504

Installation kit for MCCB's up to 630 A in horizontal position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 501	Horizontal	MSX/M160c	600x200	1
GW D3 502	Horizontal	MSX/D125	600x200	1
GW D3 503	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 504	Horizontal	MSXE160-250	600x200	1
GW D3 505	Horizontal	MSX/E/M400-630	600x300	1
Functional width: 850 mm				
GW D3 509	Horizontal	MSX/M160c	850x200	1
GW D3 510	Horizontal	MSX/D125	850x200	1
GW D3 511	Horizontal	MSX/D/M/c 160-250	850x200	1
GW D3 512	Horizontal	MSXE160-250	850x200	1
GW D3 513	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS:RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.



GW D3 517


Installation kit for MCCB's up to 630 A in vertical position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 555	Vertical	MSX/D125	600x300	1
GW D3 517	Vertical	MSX/D/M/c 160-250	600x300	1
GW D3 518	Vertical	MSXE160-250	600x300	1
GW D3 519	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 556	Vertical	MSX/D125	600x300	1
GW D3 523	Vertical	MSX/D/M/c 160-250	850x300	1
GW D3 524	Vertical	MSXE160-250	850x300	1
GW D3 525	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

NEWS

Horizontal installation kit for fixed version MSX up to 630A with direct rotary handle




GW D3 568

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 531	Horizontal	MSX/M160c	600x200	1
GW D3 532	Horizontal	MSX/M250c	600x200	1
GW D3 533	Horizontal	MSX/D125	600x200	1
GW D3 534	Horizontal	MSX/D160-250	600x200	1
GW D3 535	Horizontal	MSXE160-250	600x200	1
GW D3 536	Horizontal	MSX/E/M400-630	600x300	1
GW D3 568	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Installation kit for vertical MCCB'S up to 630A on plate with direct rotary handle




GW D3 569

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 569	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 570	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

Horizontal installation kit for fixed version MSX up to 630A with motor operating device




GW D3 557

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 541	Horizontal	MSX/D125	600x200	1
GW D3 542	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 543	Horizontal	MSXE160-250	600x200	1
GW D3 544	Horizontal	MSX/E/M400-630	600x300	1
GW D3 557	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanized sheet metal support plate, overhead brackets (if required) and pre-cut panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotating hinges and 1/4 turn locks.
NOTES: the kits are suitable for 3P and 4P switches.

Installation kit for vertical MCCB'S up to 630A on plate with motor operating device



GW D3 558

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 558	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 559	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: piastra di supporto in lamiera zincata, staffe di rialzo (se necessarie) e pannello pretranciato.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

NEWS

QDX 630 H

MSS switch disconnectors installation on plate




GW D3 553

Installation kit for switch disconnectors up to 630 A fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 551	Horizontal/Vertical	MSS 250	600x300	1
GW D3 553	Horizontal/Vertical	MSS 630	600x400	1
Functional width: 850 mm				
GW D3 552	Horizontal/Vertical	MSS 250	850x300	1
GW D3 554	Horizontal/Vertical	MSS 630	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Front panels




GW D3 324

Blind front panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 321	600x100	1
GW D3 322	600x150	1
GW D3 323	600x200	1
GW D3 324	600x300	1
GW D3 325	600x400	1
GW D3 326	600x600	1
GW D3 327	850x100	1
GW D3 328	850x150	1
GW D3 329	850x200	1
GW D3 330	850x300	1
GW D3 331	850x400	1
GW D3 332	850x600	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.



GW D3 333


Aeration front panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 333	600x200	1
GW D3 334	850x200	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.

INTERNAL CONFIGURATION

Back-mounting plates



GW D3 336

Back-mounting plate for non-modular devices

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 336	600x200	1
GW D3 337	600x400	1
GW D3 338	600x600	1
GW D3 339	600x800	1
GW D3 340	600x1000	1
GW D3 341	850x200	1
GW D3 342	850x400	1
GW D3 343	850x600	1
GW D3 344	850x800	1
GW D3 345	850x1000	1
GW D3 346	600x1800	1
GW D3 347	600x2000	1
GW D3 348	850x1800	1
GW D3 349	850x2000	1

CHARACTERISTICS: The GWD3346, GWD3347, GWD3348 and GWD3349 bottom plates replace the functional frames and can be adjusted in depth.
NOTES: The GWD3346, GWD3347, GWD3348 and GWD3349 bottom plates are not suitable for boards with a functional depth of 250 mm.

Dividers



GW D3 366

Vertical dividers

Code	Suitable for structures HxD (mm)	No. of pieces	Pack Carton
GW D3 365	1600x250	1	1
GW D3 366	1800x250	1	1
GW D3 367	2000x250	1	1
GW D3 368	1600x400	1	1
GW D3 369	1800x400	1	1
GW D3 370	2000x400	1	1

CHARACTERISTICS: plastic dividers to realize Form 2 configuration in the case of busbars mounted in the side and external compartment.
NOTES: segregation not suitable for wall-mounting boards.



GW D3 375

Horizontal dividers

Code	Suitable for structures LxD (mm)	No. of pieces	Pack Carton
GW D3 375	600x200/250	1	1
GW D3 376	850x200/250	1	1
GW D3 377	600x400	1	1
GW D3 378	850x400	1	1

CHARACTERISTICS: metal dividers used to divide the distribution board into sections.
NOTES: GWD3377 and GWD3378 are not suitable for wall-mounting distribution boards.

COMPLEMENTARY ITEMS

Accessories




GW D3 821

DIN rail mounting tool

Code	Suitable for	Pack Carton
GW D3 821	Wall and floor boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.



GW D3 317

Depth adapter

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).



GW D3 318

Pair of hole din row cover

Code	Length (mm)	No. of pieces	Pack Carton
GW D3 318	1000	2	1

CHARACTERISTICS: clip fixing on window panels.



GW D3 226

Metal front finishing profiles for IP30 enclosures without door

Code	Suitable for structures	No. of pieces	Pack Carton
Profile: Horizontal			
GW D3 224	L=600 mm	2	1
GW D3 225	L=850 mm	2	1
Profile: Vertical			
GW D3 226	H=1600 mm	2	1
GW D3 227	H=1800 mm	2	1
GW D3 228	H=2000 mm	2	1

NEWS

DIN profiles




GW 45 413

Code	Section dim. HxD (mm)	Profile	Pack Carton
Length: 24 modules			
GW 45 413	35x15	EN 50022 (DIN 35)	1
GW 45 414	35x15	EN 50035 (G 32)	1
Length: 35 modules			
GW 45 418	35x15	EN 50022 (DIN 35)	1
GW 45 419	35x15	EN 50035 (G 32)	1
Length: 2000 mm			
GW 47 691	35x15	EN 50022 (DIN 35)	1/5
GW 47 692	32x15	EN 50035 (G 32)	1/5

NOTE: 24 and 35 modules DIN guides have fixing holess.
The 2000 mm DIN guides have no fixing holes.

Wiring vertical trunking supports




GW D3 426

Code	No. of pieces	Pack Carton
GW D3 426	4	1
GW D3 428	8	1

CHARACTERISTICS: allows the installation of vertical wiring trunkings with heights H=40 mm, H=60 mm or H=80 mm.
NOTES: not suitable for distribution boards with functional depth P= 200/ 250 mm.

Pair of supports for horizontal terminal block and earth bar



GW D3 471

Code	Suitable for	Pack Carton
GW D3 471	Distribution boards L=600/850 mm	1

Ventilation kit



GW 46 448

Code	IP degree	Rated voltage	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 448	IP44	230 V - 50 / 60 Hz	125x117	123x115	1/2

CHARACTERISTICS: the fan takes in air from the outside and introduces it into the distribution board, creating a slight overpressure that prevents foreign particles from entering. Max fan capacity 60 m³/h. Absorbed power equal to 20 W.
APPLICATIONS: forced ventilation in critical thermal conditions.
ACCESSORIES SUPPLIED: drilling template.

Aeration kit



GW 46 471

Code	IP degree	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 471	IP44	125x117	123x115	1/10

ACCESSORIES SUPPLIED: drilling template.

QDX 630 H



Additional plinths

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 828	400x250	1
GW D3 829	600x250	1
GW D3 830	850x250	1
GW D3 831	(600+300)x250	1
GW D3 832	400x400	1
GW D3 833	600x400	1
GW D3 834	850x400	1
GW D3 835	(600+300)x400	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board

Kit for side-by-side coupling



GW D3 217

Code	Suitable for	Pack Carton
GW D3 217	Floor-mounting distribution boards	1

ACCESSORIES SUPPLIED: fixing screws and gasket.

Overlay kit for wall-mounted boards




GW D3 121

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 121	600x200	1
GW D3 122	(600+200)x200	1
GW D3 123	850x200	1
GW D3 124	600x300	1
GW D3 125	(600+200)x300	1
GW D3 126	850x300	1

NOTES: not suitable for floor-mounting distribution boards.

Copper earth busbars



GW 45 565

Code	Suitable for	Installation	Section (mm²)	Length (mm)	N./diam. of holes	Pack Carton
GW 45 565	Structures L=600 mm	Horizontal	25x4	420	13 Holes M6 and 2 holes ø 6 mm	1
GW 45 566	Structures L=850 mm	Horizontal	25x4	620	21 Holes M6 and 2 holes ø 6 mm	1
GW 45 559	Side compartment/external	Vertical	20x5	1750	68 Holes M6 and 2 holes M12	1

Earth terminal blocks



GW 45 568

Code	Suitable for structures L (mm)	N. terminal and section (mm²)	Pack Carton
GW 45 568	600	2x(1x35+11x16+13x10)	1
GW 45 569	850	2x(1x35+11x16+13x10)	1

CHARACTERISTICS: copper busbars with a 20 x 5 section and 6.5 mm hole spacing.

NEWS




GW 46 447

Document holder pocket in self-adhesive insulating material with kit of blank labels

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10

CHARACTERISTICS: can be inserted in all GEWISS enclosures from dimension 405x500x200 mm upwards.



GW D3 443

Lifting eyebolts

Code	Suitable for structures D (mm)	Pack Carton
GW D3 443	250	1
GW D3 444	400	1

NOTES: Not suitable for wall-mounting distribution boards.
To lift the wal-mounting distribution boards use the supplied wall mounting brackets.




GW D3 467

Pair of crosspieces for attachment

Code	Type	Suitable for	Pack Carton
GW D3 467	Horizontal	Wall-mounted distribution board with associated side compartment	1
GW D3 468	Horizontal	External compartment	1

Spare parts




GW D3 847

Spare part locks for wall-mounting distribution boards

Code	Suitable to	Pack Carton
GW D3 847	Glass door / blind door	1
GW D3 848	Side compartment door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 851

Spare part locks for floor-mounting distribution boards

Code	Suitable to	Pack Carton
GW D3 850	External compartment door	1
GW D3 851	Glass door / blind door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.

NEWS

QDX 630 H

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 439	Yale	Wall / floor mounting distribution boards	1
GW D3 852	Triangular	Side / external compartment	1/10



GW D3 439

Spare part wall fixing brackets

Code	Suitable for	Pack Carton
GW D3 451	Wall-mounting distribuion boards	1
GW D3 453	Floor-mounting distribution boards	1



GW D3 451

Spare part screws

Code	Screws type	Pack Carton
GW D3 454	M6x10 (25 pcs)	1
GW D3 455	M6x12 (25 pcs)	1



GW D3 454

Inserts for screws

Code	Suitable for	No. of pieces	Pack Carton
GW D3 853	Side panels	10	1


NOTES: Not suitable for wall-mounting distribution boards.



GW D3 853

1/4 turn locks and spare part hinges

Code	Suitable for	No. of pieces	Pack Carton
GW D3 457	Front panels	4 pcs (locks) and 4 pcs (hinges)	1
GW D3 458	Doors for wall-mounting boards	5 pcs (hinges)	1



GW D3 457

NEWS



QDX 630 H



Scan the QR Code and find out all the technical informations.

DIN RAIL: QUICK ASSEMBLY AND DISASSEMBLY



The screw-free snap-in system is simple and immediate thanks to the quick assembly and disassembly of the dual aluminium DIN rails.

EASIER ASSEMBLY AND MAINTENANCE



The side and rear panels can be easily removed in complete safety. The removable front, and fully removable side and rear panels allow the operator to assemble the structure upright.

BUSBAR SYSTEM IN EACH POSITION




The linear bar system (in the switch zone at the bottom of the distribution board) or sloped busbar system (in the cable compartment) is also available in aluminium.

QDX 1600 H

QDX 1600 H cabinets

QDX 1600 H FLOOR-MOUNTING STUCTURES

FUNCTIONAL DIM. (LxH)		600x1800 mm	600x2000 mm	
DEPTH		600 mm	600 mm	800 mm
Modular Capacity	Pitch 150mm	288 mod. (24x12)	312 mod. (24x13)	
	Pitch 200 mm	216 mod. (24x9)	240 mod. (24x10)	
Bases and headboards		GW D3 661	GW D3 661	GW D3 662
Front uprights		GW D3 168	GW D3 169	
Rear uprights and functional frames				
Short rear uprights and functional frames*		GW D3 168R	GW D3 169R6	-
Side panels		GW D3 679	GW D3 682	GW D3 683
Rear panels		GW D3 685	GW D3 686	
Glass doors		GW D3 697	GW D3 698	
Blind doors		GW D3 804	GW D3 805	
Blind doors for side compartment		-	-	-
Side-by-side kit				

NOTE: the 600+300mm wide structures have a side compartment (300 mm wide) dedicated to the cables, terminal block or busbar system.
* Short rear uprights and functional frames are only required in the case of busbars mounted horizontally at the headboard or base


QDX 1600 H FLOOR-MOUNTING STUCTURES

(600+300)x1800 mm	(600+300)x2000 mm		850x1800 mm	850x2000 mm	
600 mm	**600 mm**	**800 mm**	**600 mm**	**600 mm**	**800 mm**
288 mod. (24x12)	312 mod. (24x13)		420 mod. (35x12)	455 mod. (35x13)	
216 mod. (24x9)	240 mod. (24x10)		315 mod. (35x9)	350 mod. (35x10)	
GW D3 665	GW D3 665	GW D3 666	GW D3 669	GW D3 669	GW D3 670
GW D3 159	GW D3 162		GW D3 168	GW D3 169	
GW D3 174	GW D3 177				
GW D3 174R	GW D8 177R6	-	GW D3 168R	GW D3 169R6	-
GW D3 679	GW D3 682	GW D3 683	GW D3 679	GW D3 682	GW D3 683
GW D3 688	GW D3 689		GW D3 691	GW D3 692	
GW D3 697	GW D3 698		GW D3 801	GW D3 802	
GW D3 804	GW D3 805		GW D3 807	GW D3 808	
GW D3 813	GW D3 814		-	-	-


GW D3 217

QDX 1600 H

QDX 1600 H cabinets

QDX 1600 H EXTERNAL COMPARTMENT				
FUNCTIONAL DIM. (LxH)		**400x1800 mm**	**400x2000 mm**	
DEPTH		**600 mm**	**600 mm**	**800 mm**
Bases and headboards		GW D3 673	GW D3 673	GW D3 674
Uprights and functional frames		GW D3 165	GW D3 167	
Side panels		GW D3 679	GW D3 682	GW D3 683
Rear panels		GW D3 694	GW D3 695	
Blind doors		GW D3 810	GW D3 811	


QDX 1600 H configurations



Floor-mounting cabinet IP55 QDX 1600 H with side and external compartment
Functional dimension (LxHxD): 400+(600+300)x2000x600 mm
External dimension (LxHxD): 1395x2200x625 mm

Quantity	Code	Description
2	GW 45 558	2 COPPER FLAT BARS 630 A 30x10 2000mm
1	GW 47 691	GUIDE EN 50 022 - DIN 35
1	GW D3 665	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 600+300x600 GR
1	GW D3 673	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 400x600 GR
1	GW D3 162	QDX 1600H FLOOR MOUNT. FRONT UPRIGHTS 600+300x2000
1	GW D3 167	QDX 1600H FLOOR MOUNT. UPRIGHTS 400x2000
1	GW D3 177	DX 1600H FLOOR MOUNT. UPRIGHTS 600+300x2000
1	GW D3 682	QDX 630H FLOOR MOUNT. SIDE PANELS 2000x625 GR
1	GW D3 689	QDX 630H FLOOR MOUNT. REAR PANEL 600+300x2000 GR
1	GW D3 695	QDX 630H FLOOR MOUNT. REAR PANEL 400x2000 GR
1	GW D3 698	QDX 630H FLOOR MOUNT. GLASS DOOR 600x2000 AR
1	GW D3 811	QDX 630H FLOOR MOUNT. BLIND DOOR 400x2000 AR
1	GW D3 814	QDX 630H FLOOR MOUNT. SIDE COMPART.DOOR 600+300x2000 GR
1	GW D3 217	QDX 630-1600H FLOOR MOUNT. SIDE-BY-SIDE KIT
5	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
5	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 321	QDX BLIND FRONT PANEL 600x100
1	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
5	GW D3 472	QDX1600H SUPPORTS FOR HORIZ. TERMIN.BLOCK P600
1	GW D3 501	KIT MSX/M160c 600x200 HORIZ FIX
2	GW D3 503	KIT MSX/D/M/c160-250 600x200 HORIZ FIX
1	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
6	GW D3 714	QDX N.20 SCREWS FOR SHAPED BUSBARS M8X25
2	GW D3 734	QDX1600H BUSBAR-HOLDER INT/EXT.COMP. 630-800A D600

QDX 1600 H configurations




Floor-mounting cabinet IP55 QDX 1600 H
2 columns with side and external compartment
Functional dimension (LxHxD): 400+(600+300)+850x2000x600 mm
External dimension (LxHxD): 2245x2200x625 mm

Quantity	Code	Description
2	GW 45 418	DIN35 PROFILE B850 QDX630L/H/1600H
1	GW 47 691	GUIDE EN 50 022 - DIN 35
1	GW D3 665	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 600+300x600 GR
1	GW D3 669	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 850x600 GR
1	GW D3 673	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 400x600 GR
1	GW D3 162	QDX 1600H FLOOR MOUNT. FRONT UPRIGHTS 600+300x2000
1	GW D3 167	QDX 1600H FLOOR MOUNT. UPRIGHTS 400x2000
1	GW D3 169	QDX 1600H FLOOR MOUNT. UPRIGHTS 600/850x2000
1	GW D3 177	QDX 1600H FLOOR MOUNT. UPRIGHTS 600+300x2000
1	GW D3 682	QDX 630H FLOOR MOUNT. SIDE PANELS 2000x625 GR
1	GW D3 689	QDX 630H FLOOR MOUNT. REAR PANEL 600+300x2000 GR
1	GW D3 692	QDX 630H FLOOR MOUNT. REAR PANEL 850x2000 GR
1	GW D3 695	QDX 630H FLOOR MOUNT. REAR PANEL 400x2000 GR
1	GW D3 698	QDX 630H FLOOR MOUNT. GLASS DOOR 600x2000 AR
1	GW D3 802	QDX 630H FLOOR MOUNT. GLASS DOOR 850x2000 AR
1	GW D3 811	QDX 630H FLOOR MOUNT. BLIND DOOR 400x2000 AR
1	GW D3 814	QDX 630H FLOOR MOUNT. SIDE COMPART.DOOR 600+300x2000 GR
2	GW D3 217	QDX 630-1600H FLOOR MOUNT. SIDE-BY-SIDE KIT

Quantity	Code	Description
2	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
8	GW D3 305	QDX WINDOW PANEL WITH DIN RAIL 850x200
10	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
2	GW D3 329	QDX BLIND FRONT PANEL 850x200
2	GW D3 372	QDX1600H VERTICAL DIVIDER 2000x625
2	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
2	GW D3 471	QDX SUPPORTS FOR HORIZ. TERMIN.BLOCK/EARTH BAR
5	GW D3 472	QDX1600H SUPPORTS FOR HORIZ. TERMIN.BLOCK P600
1	GW D3 501	KIT MSX/M160c 600x200 HORIZ FIX
2	GW D3 503	KIT MSX/D/M/c160-250 600x200 HORIZ FIX
2	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
1	GW D3 507	KIT MSX/E/M1250 600x400 HORIZ FIX
6	GW D3 714	QDX N.20 SCREWS FOR SHAPED BUSBARS M8X25
2	GW D3 760	QDX1600H SHAPED BUSBAR-HOLDER AL INT/EXT.COMP. 1600A
2	GW D3 794	QDX ALUMINIUM SHAPED BUSBARS 1600A 60x30

QDX 1600 H configurations



Floor-mounting cabinet IP55 QDX 1600 H
2 columns with side and external compartment
Functional dimension (LxHxD): 400+600+400+(600+300)x2000x800 mm
External dimension (LxHxD): 2445x2200x800 mm

Quantity	Code	Description
2	GW 47 691	GUIDE EN 50 022 - DIN 35
1	GW D3 662	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 600x800 GR
1	GW D3 666	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 600+300x800 GR
2	GW D3 674	QDX 1600H FLOOR MOUNT. BASE-HEADBOARD 400x800
1	GW D3 162	QDX 1600H FLOOR MOUNT. FRONT UPRIGHTS 600+300x2000
2	GW D3 167	QDX 1600H FLOOR MOUNT. UPRIGHTS 400x2000
1	GW D3 169	QDX 1600H FLOOR MOUNT. UPRIGHTS 600/850x2000
1	GW D3 177	QDX 1600H FLOOR MOUNT. UPRIGHTS 600+300x2000
1	GW D3 683	QDX 630H FLOOR MOUNT. SIDE PANELS 2000x800 GR
1	GW D3 686	QDX 630H FLOOR MOUNT. REAR PANEL 600x2000 GR
1	GW D3 689	QDX 630H FLOOR MOUNT. REAR PANEL 600+300x2000 GR
2	GW D3 695	QDX 630H FLOOR MOUNT. REAR PANEL 400x2000 GR
2	GW D3 698	QDX 630H FLOOR MOUNT. GLASS DOOR 600x2000 AR
2	GW D3 811	QDX 630H FLOOR MOUNT. BLIND DOOR 400x2000 AR
1	GW D3 814	QDX 630H FLOOR MOUNT. SIDE COMPART.DOOR 600+300x2000 GR
3	GW D3 217	QDX 630-1600H FLOOR MOUNT. SIDE-BY-SIDE KIT
4	GW D3 302	QDX WINDOW PANEL WITH DIN RAIL 600x200
4	GW D3 313	QDX DIN RAIL MOUNT.BRACKETS 90 RANGE - 220mm

Quantity	Code	Description
1	GW D3 821	QDX DIN RAIL MOUNTING TOOL GR
1	GW D3 318	QDX BLANKING MODULES PROFILE 1000mm
1	GW D3 321	QDX BLIND FRONT PANEL 600x100
1	GW D3 323	QDX BLIND FRONT PANEL 600x200
2	GW D3 428	QDX WIRING TRUNKING VERTICAL SUPPORTS 8 PIECES
2	GW D3 472	QDX1600H SUPPORTS FOR HORIZ. TERMIN.BLOCK P600
6	GW D3 473	QDX1600H SUPPORTS FOR HORIZ. TERMIN.BLOCK P800
5	GW D3 501	KIT MSX/M160c 600x200 HORIZ FIX
3	GW D3 503	KIT MSX/D/M/c160-250 600x200 HORIZ FIX
2	GW D3 505	KIT MSX/E/M400-630 600x300 HORIZ FIX
1	GW D3 522	KIT MSX/E/M1600 600x700 VERT FIX
4	GW D3 714	QDX N.20 SCREWS FOR SHAPED BUSBARS M8X25
2	GW D3 762	QDX1600H SHAPED BUSBAR-HOLDER AL INT/EXT.COMP. 1600A
2	GW D3 763	QDX1600H SHAPED BUSBAR-HOLDER AL 1600A D600-800
1	GW D3 767	HORIZ. BARS CROSSPIECES QDX1600H L600
1	GW D3 769	HORIZ. BARS CROSSPIECES EXT CABLE COMP. QDX1600H
1	GW D3 774	QDX1600H N.4 JOINTS ALUM. SHAPED BUSBARS 1250/1600A
4	GW D3 794	QDX ALUMINIUM SHAPED BUSBARS 1600A 60x30

QDX 1600 H


Modular enclosures up to 1600 A - IP55

The QDX 1600 H series of cabinets makes robustness its strong point, specifically in all those applications where both a high level of protection from external agents and a high breaking power from the short circuit are required.



STRUCTURES - DEGREE OF PROTECTION WITH DOOR IP55

Floor-mounting distributon boards - Single board



GW D3 662

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 661	600x600	650x625	1
GW D3 662	600x800	650x800	1
GW D3 669	850x600	850x625	1
GW D3 670	850x800	850x800	1

ACCESSORIES: inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height.



GW D3 169

Uprights and functional frames

Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 168	1800	1900	1
GW D3 169	2000	2100	1



GW D3 168 R

Reduced uprights and reduced functional frames

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 168 R	1800x600	1900x625	1
GW D3 169 R6	2000x600	2100x625	1

NOTES: uprights and functional frames to be used only in the case of busbars positioned horizontally at the top or bottom of the distribution board.

NEWS



GW D3 682

Pair of side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 679	1800x600	1
GW D3 682	2000x600	1
GW D3 683	2000x800	1



GW D3 222

Pair of ventilated side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 818	1800x600	1
GW D3 819	2000x600	1
GW D3 820	2000x800	1

NOTES: In the case of installation of aerated side panels, the enclosure protection rating is IP30.
Each side panel has 2 surfaces with slits (one lower and one upper) each 58 cm² in size.




GW D3 686

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 685	600x1800	1
GW D3 686	600x2000	1
GW D3 691	850x1800	1
GW D3 692	850x2000	1

NEWS

Floor-mounting distribution boards with side compartment




GW D3 666

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 665	(600+300)x600	945x625	1
GW D3 666	(600+300)x800	945x800	1

CHARACTERISTICS: Structures are equipped with an associated side compartment (300 mm wide) for the cables, terminal block or bar system.
COMPONENTS: to secure the cables in the side compartment, use the pair of GWD3461 crosspieces, to be ordered separately.
Inspectable base supplied loose inside the package.
NOTES: Base height = 100 mm.




GW D3 162

Front uprights

Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 159	1800	1900	1
GW D3 162	2000	2100	1

NOTES: to complete the structure you need the rear uprights and functional frames to be ordered separately.




GW D3 177

Rear uprights and rear functional frames

Code	Functional dim. H (mm)	External dim H (mm)	Pack Carton
GW D3 174	1800	1900	1
GW D3 177	2000	2100	1

NOTES: to complete the structure you need the front uprights to be ordered separately.



GW D3 177 R6

Reduced uprights and reduced functional frames

Code	Functional dim. HxD (mm)	External dim. HxD (mm)	Pack Carton
GW D3 174 R	1800x600	1900x625	1
GW D3 177 R6	2000x600	2100x625	1

NOTES: uprights and functional frames to be used only in the case of busbars positioned horizontally at the top or bottom of the distribution board.

NEWS



GW D3 689

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 688	(600+300)x1800	1
GW D3 689	(600+300)x2000	1



GW D3 814

Blind doors for side compartment

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 813	(600+300)x1800	1
GW D3 814	(600+300)x2000	1

ACCESSORIES SUPPLIED: triangular insert key for opening side compartment door.

Doors



GW D3 698

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 697	600x1800	1
GW D3 698	600x2000	1
GW D3 801	850x1800	1
GW D3 802	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Smoked tempered glass.



GW D3 805

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 804	600x1800	1
GW D3 805	600x2000	1
GW D3 807	850x1800	1
GW D3 808	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

NEWS

QDX 1600 H

External compartment



GW D3 674

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 673	400x600	400x625	1
GW D3 674	400x800	400x850	1


ACCESSORIES SUPPLIED : to fix the cables in the external compartment, use the pair of crosspieces GWD3462 to be ordered separately. Inspectable plinth (supplied loose) inside the package. NOTES: H=100 mm plinth height. The external compartment can be put together with the structure by using the special side kit to be ordered separately.



GW D3 167

Uprights and functional frames

Code	Functional dim. LxH (mm)	External dim. LxH (mm)	Pack Carton
GW D3 165	400x1800	400x1900	1
GW D3 167	400x2000	400x2100	1



GW D3 695

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 694	400x1800	1
GW D3 695	400x2000	1



GW D3 811

Blind doors


Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 810	400x1800	1
GW D3 811	400x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

NEWS

FRONT CONFIGURATION

Devices installation on DIN rail




GW D3 302

Window panels with DIN rail

Code	Functional dim. LxH (mm)	Pack Carton
No. modules: 24		
GW D3 301	600x150	1
GW D3 302	600x200	1
GW D3 303	600x300	1
No. modules: 35		
GW D3 304	850x150	1
GW D3 305	850x200	1
GW D3 306	850x300	1

ACCESSORIES SUPPLIED: double EN 50022 (DIN 35) rail in aluminium.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock. **NOTES:** mounting of DIN rail requires brackets (bracket type depends on the depth of the board) to be ordered separately.




GW D3 313

Pair of DIN rail mounting brackets

Code	Suitable for structure D (mm)	Suitable for	Pack Carton
GW D3 313	600 / 800	Modular devices range 90	1
GW D3 314	600 / 800	MCCB's MSX/D/M/c 160-250	1

ACCESSORIES SUPPLIED: no. 2 horizontal wiring trunking supports for GWD3313. The supports must be mounted on the back of the of the double EN 50022 (DIN 35) rail.

Installation MSX moulded case circuit breaker on plate



GW D3 504

Installation kit for MCCB's up to 630 A in horizontal position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 501	Horizontal	MSX/M160c	600x200	1
GW D3 502	Horizontal	MSX/D125	600x200	1
GW D3 503	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 504	Horizontal	MSXE160-250	600x200	1
GW D3 505	Horizontal	MSX/E/M400-630	600x300	1
Functional width: 850 mm				
GW D3 509	Horizontal	MSX/M160c	850x200	1
GW D3 510	Horizontal	MSX/D125	850x200	1
GW D3 511	Horizontal	MSX/D/M/c 160-250	850x200	1
GW D3 512	Horizontal	MSXE160-250	850x200	1
GW D3 513	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS:RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.




GW D3 506

Installation kit for MCCB's up to 1600 A in horizontal position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 506	Horizontal	MSXE/M1000	600x400	1
GW D3 507	Horizontal	MSXE/M1250	600x400	1
GW D3 508	Horizontal	MSXE/M 1600	600x400	1
Functional width: 850 mm				
GW D3 514	Horizontal	MSXE/M1000	850x400	1
GW D3 515	Horizontal	MSXE/M1250	850x400	1
GW D3 516	Horizontal	MSXE/M 1600	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS:RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

QDX 1600 H




GW D3 517

Installation kit for MCCB's up to 630 A in vertical position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 555	Vertical	MSX/D125	600x300	1
GW D3 517	Vertical	MSX/D/M/c 160-250	600x300	1
GW D3 518	Vertical	MSXE160-250	600x300	1
GW D3 519	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 556	Vertical	MSX/D125	600x300	1
GW D3 523	Vertical	MSX/D/M/c 160-250	850x300	1
GW D3 524	Vertical	MSXE160-250	850x300	1
GW D3 525	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.




GW D3 520

Installation kit for MCCB'S up to 1600A in vertical position fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 520	Vertical	MSXE/M1000	600x600	1
GW D3 521	Vertical	MSXE/M1250	600x700	1
GW D3 522	Vertical	MSXE/M 1600	600x700	1
Functional width: 850 mm				
GW D3 526	Vertical	MSXE/M1000	850x600	1
GW D3 527	Vertical	MSXE/M1250	850x700	1
GW D3 528	Vertical	MSXE/M 1600	850x700	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS:RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.




GW D3 568

Horizontal installation kit for fixed version MSX up to 630A with direct rotary handle

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 531	Horizontal	MSX/M160c	600x200	1
GW D3 532	Horizontal	MSX/M250c	600x200	1
GW D3 533	Horizontal	MSX/D125	600x200	1
GW D3 534	Horizontal	MSX/D160-250	600x200	1
GW D3 535	Horizontal	MSXE160-250	600x200	1
GW D3 536	Horizontal	MSX/E/M400-630	600x300	1
GW D3 568	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.



GW D3 569


Installation kit for vertical MCCB'S up to 630A on plate with direct rotary handle

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 569	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 570	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

NEWS

Horizontal installation kit for fixed version MSX up to 1600A with direct rotary handle




GW D3 537

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 537	Horizontal	MSXE/M1000	600x400	1
GW D3 538	Horizontal	MSXE/M1250	600x400	1
GW D3 571	Horizontal	MSX/E/M1000	850x400	1
GW D3 574	Horizontal	MSXE/M1250	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Installation kit for vertical MCCB'S up to 1600A on plate with direct rotary handle




GW D3 572

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 572	Vertical	MSX/E/M1000	600x600	1
GW D3 575	Vertical	MSXE/M1250	600x700	1
GW D3 539	Vertical	MSXE/M 1600	600x700	1
Functional width: 850 mm				
GW D3 573	Vertical	MSXE/M1000	850x600	1
GW D3 576	Vertical	MSXE/M1250	850x700	1
GW D3 578	Vertical	MSXE/M 1600	850x700	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

Horizontal installation kit for fixed version MSX up to 630A with motor operating device




GW D3 557

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 541	Horizontal	MSX/D125	600x200	1
GW D3 542	Horizontal	MSX/D/M/c 160-250	600x200	1
GW D3 543	Horizontal	MSXE160-250	600x200	1
GW D3 544	Horizontal	MSX/E/M400-630	600x300	1
GW D3 557	Horizontal	MSX/E/M400-630	850x300	1

ACCESSORIES SUPPLIED: galvanized sheet metal support plate, overhead brackets (if required) and pre-cut panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotating hinges and 1/4 turn locks.
NOTES: the kits are suitable for 3P and 4P switches.

Installation kit for vertical MCCB'S up to 630A on plate with motor operating device




GW D3 558

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 558	Vertical	MSX/E/M400-630	600x500	1
Functional width: 850 mm				
GW D3 559	Vertical	MSX/E/M400-630	850x500	1

ACCESSORIES SUPPLIED: piastra di supporto in lamiera zincata, staffe di rialzo (se necessarie) e pannello pretranciato.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

Horizontal installation kit for fixed version MSX up to 1600A with motor operating device




GW D3 545

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 545	Horizontal	MSXE/M1000	600x400	1
GW D3 546	Horizontal	MSXE/M1250	600x400	1
Functional width: 850 mm				
GW D3 560	Horizontal	MSX/E/M1000	850x400	1
GW D3 563	Horizontal	MSXE/M1250	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

NEWS

QDX 1600 H



GW D3 561

Vertical installation kit for fixed version MSX up to 1600A with motor operating device

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 561	Vertical	MSX/E/M1000	600x600	1
GW D3 564	Vertical	MSXE/M1250	600x700	1
GW D3 547	Vertical	MSXE/M 1600	600x700	1
Functional width: 850 mm				
GW D3 562	Vertical	MSXE/M1000	850x600	1
GW D3 565	Vertical	MSXE/M1250	850x700	1
GW D3 567	Vertical	MSXE/M 1600	850x700	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTES: The kits are suitable for 3P and 4P MCCB's.

Installation MSS switch disconnectors on plate



GW D3 553

Installation kit for switch disconnectors up to 630 A fixed version

Code	Installation	Suitable for	Functional dim. LxH (mm)	Pack Carton
Functional width: 600 mm				
GW D3 551	Horizontal/Vertical	MSS 250	600x300	1
GW D3 553	Horizontal/Vertical	MSS 630	600x400	1
Functional width: 850 mm				
GW D3 552	Horizontal/Vertical	MSS 250	850x300	1
GW D3 554	Horizontal/Vertical	MSS 630	850x400	1

ACCESSORIES SUPPLIED: galvanised sheet metal support plate, raiser brackets and pre-drilled panel.
CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.
NOTE: The kits are suitable for 3P and 4P MCCB's.

Front panels




GW D3 324

Blind front panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 321	600x100	1
GW D3 322	600x150	1
GW D3 323	600x200	1
GW D3 324	600x300	1
GW D3 325	600x400	1
GW D3 326	600x600	1
GW D3 327	850x100	1
GW D3 328	850x150	1
GW D3 329	850x200	1
GW D3 330	850x300	1
GW D3 331	850x400	1
GW D3 332	850x600	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.



GW D3 333

Aeration front panels


Code	Functional dim. LxH (mm)	Pack Carton
GW D3 333	600x200	1
GW D3 334	850x200	1

CHARACTERISTICS: RAL 7035 grey painted sheet metal panels equipped with rotation hinges and 1/4 turn lock.

NEWS

INTERNAL CONFIGURATION

Back-mounting plates



GW D3 336

Back-mounting plate for non-modular devices

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 336	600x200	1
GW D3 337	600x400	1
GW D3 338	600x600	1
GW D3 339	600x800	1
GW D3 340	600x1000	1
GW D3 341	850x200	1
GW D3 342	850x400	1
GW D3 343	850x600	1
GW D3 344	850x800	1
GW D3 345	850x1000	1
GW D3 346	600x1800	1
GW D3 347	600x2000	1
GW D3 348	850x1800	1
GW D3 349	850x2000	1

CHARACTERISTICS: The GWD3346, GWD3347, GWD3348 and GWD3349 bottom plates replace the functional frames and can be adjusted in depth.

Dividers



GW D3 371

Vertical dividers

Code	Suitable for structures HxD (mm)	No. of pieces	Pack Carton
GW D3 371	1800x600	1	1
GW D3 372	2000x600	1	1
GW D3 374	2000x800	1	1

CHARACTERISTICS: metal dividers to realize Form 2 segregation in the case of busbars mounted in the side and external compartment.



GW D3 377

Horizontal dividers

Code	Suitable for structures LxD (mm)	No. of pieces	Pack Carton
GW D3 377	600x400	1	1
GW D3 378	850x400	1	1

CHARACTERISTICS: metal dividers used to divide the distribution board into sections.



GW D3 379

Horizontal busbars segregations

Code	Suitable for structures LxD (mm)	Installation	No. of pieces	Pack Carton
GW D3 379	600x600	Base and head	1	1
GW D3 380	600x800	Base and head	1	1
GW D3 381	850x600	Base and head	1	1
GW D3 382	850x800	Base and head	1	1
GW D3 383	600x800	At any height	1	1
GW D3 384	850x800	At any height	1	1

CHARACTERISTICS: metal dividers to realize Form 2 segregation in the case of busbars horizontally mounted.

NEWS

COMPLEMENTARY ITEMS

Accessories




GW D3 821

DIN rail mounting tool

Code	Suitable for	Pack Carton
GW D3 821	Floor-mounting distribution boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.



GW D3 317

Depth adapter

Code	Length (mm)	Pack Carton
GW D3 317	600	1

CHARACTERISTICS: plastic adapter for compensation of the different installation depths on DIN rail EN 50022 of the modular devices (90 range) and moulded case circuit breakers (MSX range).




GW D3 318

Pair of hole din row cover

Code	Length (mm)	No. of pieces	Pack Carton
GW D3 318	1000	2	1

CHARACTERISTICS: clip fixing on window panels.



GW D3 228

Metal front finishing profiles for IP30 enclosures without door

Code	Suitable for structures	No. of pieces	Pack Carton
Profile: Horizontal			
GW D3 224	L=600 mm	2	1
GW D3 225	L=850 mm	2	1
Profile: Vertical			
GW D3 227	H=1800 mm	2	1
GW D3 228	H=2000 mm	2	1

NEWS

DIN profiles




GW 45 413

Code	Section dim. HxD (mm)	Profile	Pack Carton
Length: 24 modules			
GW 45 413	35x15	EN 50022 (DIN 35)	1
GW 45 414	35x15	EN 50035 (G 32)	1
Length: 35 modules			
GW 45 418	35x15	EN 50022 (DIN 35)	1
GW 45 419	35x15	EN 50035 (G 32)	1
Length: 2000 mm			
GW 47 691	35x15	EN 50022 (DIN 35)	1/5
GW 47 692	32x15	EN 50035 (G 32)	1/5

NOTE: 24 and 35 modules DIN guides have fixing holess.
The 2000 mm DIN guides have no fixing holes.

Wiring vertical trunking supports




GW D3 426

Code	No. of pieces	Pack Carton
GW D3 426	4	1
GW D3 428	8	1

CHARACTERISTICS: allows the installation of vertical wiring trunking with heights H=40 mm, H=60 mm or H=80 mm.

Pair of supports for horizontal terminal block and earth bar



GW D3 471

Code	Suitable for	Pack Carton
GW D3 471	Distribution boards L=600/850 mm	1

Pair of supports for vertical terminal block



GW D3 472

Code	Suitable for structures D (mm)	Pack Carton
GW D3 472	600	1
GW D3 473	800	1

Ventilation kit



GW 46 448

Code	IP degree	Rated voltage	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 448	IP44	230 V - 50 / 60 Hz	125x117	123x115	1/2

CHARACTERISTICS: the fan takes in air from the outside and introduces it into the distribution board, creating a slight overpressure that prevents foreign particles from entering. Max fan capacity 60 m³/h. Absorbed power equal to 20 W.
APPLICATIONS: forced ventilation in critical thermal conditions.
ACCESSORIES SUPPLIED: drilling template.

QDX 1600 H

Aeration kit



GW 46 471

Code	IP degree	Fixing hole (mm)	Screws centre distance (mm)	Pack Carton
GW 46 471	IP44	125x117	123x115	1/10

ACCESSORIES SUPPLIED: drilling template.

Additional plinths



Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 836	400x600	1
GW D3 837	600x600	1
GW D3 838	850x600	1
GW D3 839	(600+300)x600	1
GW D3 840	400x800	1
GW D3 841	600x800	1
GW D3 842	850x800	1
GW D3 843	(600+300)x800	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board

Kit for side-by-side coupling




GW D3 217

Code	Suitable for	Pack Carton
GW D3 217	Floor-mounting distribution boards	1

ACCESSORIES SUPPLIED: fixing screws and gasket.

Copper earth busbars



GW 45 565

Code	Suitable for	Installation	Section (mm²)	Length (mm)	N./diam. of holes	Pack Carton
GW 45 565	Structures L=600 mm	Horizontal	25x4	420	13 Holes M6 and 2 holes ø 6 mm	1
GW 45 566	Structures L=850 mm	Horizontal	25x4	620	21 Holes M6 and 2 holes ø 6 mm	1
GW 45 560	Side compartment/external	Vertical	60x5	1750	140 holes Ø 10,5 mm	1

Earth terminal blocks



GW 45 568

Code	Suitable for structures L (mm)	N. terminal and section (mm²)	Pack Carton
GW 45 568	600	2x(1x35+11x16+13x10)	1
GW 45 569	850	2x(1x35+11x16+13x10)	1

CHARACTERISTICS: copper busbars with a 20 x 5 section and 6.5 mm hole spacing.

NEWS

Document holder pocket in self-adhesive insulating material with kit of blank labels




GW 46 447

Code	Dimensions LxH (mm)	Pack Carton
GW 46 447	230x310	1/10

CHARACTERISTICS: can be inserted in all GEWISS enclosures from dimension 405x500x200 mm upwards.

Lifting eyebolts



GW D3 445

Code	Suitable for structures D (mm)	Pack Carton
GW D3 445	600 / 800	1

Pair of fixing crosspieces



GW D3 461

Code	Type	Suitable for	Pack Carton
GW D3 461	Horizontal	Side compartment	1
GW D3 462	Horizontal	External compartment	1
GW D3 463	Horizontal	Structures L=600	1
GW D3 464	Horizontal	Structures L=850	1
GW D3 465	Lateral	Structures D=600	1
GW D3 466	Lateral	Structures D=800	1

QDX 1600 H

Spare parts



GW D3 850

Spare part lock

Code	Suitable to	Pack Carton
GW D3 850	External compartment door	1
GW D3 851	Glass door / blind door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 439

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 439	Yale	Floor-mounting distribution boards	1
GW D3 852	Triangular	Side / external compartment	1/10



GW D3 454

Spare part screws

Code	Screws type	Pack Carton
GW D3 454	M6x10 (25 pcs)	1
GW D3 455	M6x12 (25 pcs)	1



GW D3 853

Inserts for screws

Code	Suitable for	No. of pieces	Pack Carton
GW D3 853	Side panels	10	1



GW D3 457

1/4 turn locks and spare part hinges

Code	Suitable for	No. of pieces	Pack Carton
GW D3 457	Front panels	4 pcs (locks) and 4 pcs (hinges)	1

NEWS



QDX 1600 H



Scan the QR Code and find out all the technical informations.

DIN RAIL: QUICK ASSEMBLY AND DISASSEMBLY



The screw-free snap-in system is simple and immediate thanks to the quick assembly and disassembly of the dual aluminium DIN rails.

EASIER ASSEMBLY AND MAINTENANCE



The side panels and the rear panel can be easily removed in complete safety. The removable front and fully removable side and rear panels allow the operator to assemble the structure upright.

BUSBAR SYSTEM IN EACH POSITION





Fast, cost-effective and versatile, the universal aluminium busbar system allows the maximum customisation of GEWISS panels, thanks to the various positioning configurations.


BUSBAR

QDX 630 L wall-mounting and floor-mounting distribution boards

FLAT COPPER BUSBARS









BUSBAR (1 CODE= 2 PIECES)					CENTRE DISTANCE					BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES) DEPTH 200 MM		
Capacity (A) depending on IP rating					Maximum centre distance between busbar holders (mm) depending on max.Icc (kA)					Internal compartment	External compartment	
IP30	IP43	Code	Cross-section BxH (mm)	N. bars per phase	6kA	10kA	16kA	20kA	25kA	B=850 mm	B=300 mm	B=400 mm
300	250	GW 45 551 (1000 mm) GW 45 555 (1750 mm)	20x5 M6	1	900	500	300	250	-	GW D3 701	GW D3 702	GW D3 707
450	400	GW 45 553 (1000 mm) GW 45 557 (1750 mm)	30x5 M6	1	1000	650	400	300	-			
730	630	GW 45 554 (1000 mm) GW 45 558 (1750 mm)	30x10 M6	1	1000	1000	950	750	600	-	-	-

(1) Only form 1

QDX 630 H wall-mounting distribution boards

FLAT COPPER BUSBARS








BUSBAR (1 CODE= 2 PIECES)						CENTRE DISTANCE				BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES) DEPTH 200 MM
Capacity (A) depending on IP rating						Maximum centre distance between busbar holders (mm) depending on max.Icc (kA)				Side compartment
IP30	IP55	Type	Code	Cross-section BxH (mm)	N. bars per phase	6kA	10kA	16kA	20kA	B=600+200 mm
300	250	Flat	GW 45 551 (1000 mm) GW 45 555 (1750 mm)	20x5 M6	1	900	500	300	250	GW D3 702
450	400	Flat	GW 45 553 (1000 mm) GW 45 557 (1750 mm)	30x5 M6	1	1000	650	400	300	

FLAT COPPER BUSBARS


BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES)

DEPTH 300 MM

			
Single distribution board [1]		**Internal compartment**	**External compartment**
B=600 mm	**B=850 mm**	**B=850 mm**	**B=400 mm**
GW D3 703	GW D3 705	GW D3 709	GW D3 707
GW D3 704	GW D3 706	-	GW D3 708

BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES)

DEPTH 300 MM



Side compartment


B=600+200 mm


GW D3 702


BUSBAR


QDX 630 H floor-mounting distribution boards

FLAT COPPER BUSBARS












BUSBAR (1 CODE= 2 PIECES)						CENTRE DISTANCE					BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES) DEPTH 250 MM			
Capacity (A) depending on IP rating						Maximum centre distance between busbar holders (mm) depending on max.Icc (kA)					Single distribution board [1]		Side	External compartment
IP30	IP55	Type	Code	Cross-section BxH (mm)	N. bars per phase	6kA	10kA	16kA	20kA	25kA	B=600 mm	B=850 mm	B=600+300 mm	B=400 mm
300	250	Flat	GW 45 551 (1000 mm) GW 45 555 (1750 mm)	20x5 M6	1	900	500	300	250	-	GW D3 721	GW D3 722	GW D3 723	GW D3 724
450	400	Flat	GW 45 553 (1000 mm) GW 45 557 (1750 mm)	30x5 M6	1	1000	650	400	300	-				
730	630	Flat	GW 45 554 (1000 mm) GW 45 558 (1750 mm)	30x10 M6	1	1000	1000	950	750	600	-	-	-	-

[1] Only form 1

FLAT COPPER BUSBARS

BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES)


DEPTH 400 MM


			
Single distribution board [1]		**Side**	**External compartment**
B=600 mm	**B=850 mm**	**B=600+300 mm**	**B=400 mm**
GW D3 721	GW D3 722	GW D3 723	GW D3 724
GW D3 725	GW D3 726	GW D3 727	GW D3 728


BUSBAR


QDX 1600 H floor-mounting cabinets


FLAT AND SHAPED COPPER BARS
















BUSBAR (1 CODE= 2 PIECES)						CENTRE DISTANCE								BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES) DEPTH 600 MM			
Capacity (A) depending on IP rating						Maximum centre distance between busbar holders (mm) depending on max.Icc (kA)								Single distribution board [1]		Side compartment	External compartment
IP30	IP55	Busbar Type	Code	Cross-section BxH (mm)	N. bars per phase	6kA	10kA	16kA	20kA	25kA	35kA	50kA	70kA	85kA	B=600 mm	B=850 mm	B=600+300 mm	B=400 mm
300	250	Flat	GW 45 551 (1000 mm) GW 45 555 (1750 mm)	20x5 M6	1	900	500	300	250	-	-	-	-	-	GW D3 721	GW D3 722	GW D3 733	
450	400	Flat	GW 45 553 (1000 mm) GW 45 557 (1750 mm)	30x5 M6	1	1000	650	400	300	-	-	-	-	-				
730	630	Flat	GW 45 554 (1000 mm) GW 45 558 (1750 mm)	30x10 M6	1	1000	1000	950	750	600	-	-	-	-	GW D3 729	GW D3 731	GW D3 734	
900	800	Flat	GW 49 678 (1750 mm)	60x5 Ø10,5	1	-	-	650	500	400	250	200	-	-	GW D3 730	GW D3 732	GW D3 735	
1350	1250	Flat	GW 49 679 (1750 mm)	100x5 Ø10,5	1	-	-	850	700	500	350	250	-	-				
1700	1600	Flat	GW 49 680 (1750 mm)	100x10 Ø10,5	1	-	-	900	900	900	750	500	350	300				
900	800	Shaped	GW D3 781 (1830 mm)	50x30 M8 sealing drive-screws	1	-	-	1000	900	750	500	350	-	-	GW 3741	GW 3742	GW D3 743	
1350	1250	Shaped	GW D3 782 (1830 mm)	50x30 M8 sealing drive-screws	1	-	-	1000	1000	900	650	450	300	-				
1700	1600	Shaped	GW D3 783 (1830 mm)	50x30 M8 sealing drive-screws	1	-	-	1000	1000	1000	800	550	400	-				

[1] Only form 1


FLAT AND SHAPED COPPER BARS


BUSBAR HOLDERS AND CROSSPIECES (1 CODE = 2 PIECES)


DEPTH 800 MM				DEPTH 600/800 MM				DEPTH 800 MM			
											
Single distribution board [1]		Side compartment	External compartment	Busbar holder	Crosspieces			Busbar holder	Crosspieces		
B=600 mm	B=850 mm	B=600+300 mm	B=400 mm	-	B=600 / 600+300 mm	B=850 mm	B=400 mm	-	B=600 mm	B=850 mm	B=400 mm
GW D3 721	GW D3 722	GW D3 736		-	-	-	-	-	-	-	-
GW D3 729	GW D3 731	GW D3 737		-	-	-	-	-	-	-	-
GW D3 730	GW D3 732	GW D3 738		GW D3 745	GW D3 747	GW D3 748	GW D3 749	GW D3 745	GW D3 767	GW D3 768	GW D3 769
GW D3 741	GW D3 742	GW D3 744		GW D3 746	GW D3 747	GW D3 748	GW D3 749	GW D3 746	GW D3 767	GW D3 768	GW D3 769


QDX 630 H floor-mounting distribution boards - QDX 1600 H cabinets

SHAPED ALUMINIUM BUSBARS














BUSBAR (1 CODE= 2 PIECES)						CENTRE DISTANCE						BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES) DEPTH 400 MM			
Capacity (A) depending on IP rating						Maximum centre distance between busbar holders (mm) depending on max.Icc (kA)						Single distribution board [1]		Side compartment	External compartment
IP30	IP55	Busbar Type	Code	Cross-section BxH (mm)	N. bars per phase	16kA	20kA	25kA	35kA	50kA	70kA	B=600 mm	B=850 mm	B=600+300 mm	B=400 mm
730	630	Shaped	GW D3 791 (1734 mm)	30x40 M8 sealing drivescrews	1	850	850	850	600	-	-	GW D3 751	GW D3 752	-	-
												-	-	GW D3 753	GW D3 754
900	800	Shaped	GW D3 792 (1734 mm)	30x40 M8 sealing drivescrews	1	850	850	850	600	350	-	-	-	-	-
												-	-	-	-
1350	1250	Shaped	GW D3 793 (1734 mm)	60x30 M8 sealing drivescrews	1	850	850	850	600	350	250	-	-	-	-
1700	1600	Shaped	GW D3 794 (1734 mm)	60x30 M8 sealing drivescrews	1	850	850	850	600	350	250	-	-	-	-

[1] Only form 1

SHAPED ALUMINIUM BUSBARS


BUSBAR HOLDER WITH CROSSPIECE (1 CODE = 2 PIECES)

DEPTH 600/800 MM				DEPTH 600/800 MM				DEPTH 800 MM			
											
Single distribution board [1]		Side compartment	External compartment	Busbar holder	Crosspieces			Busbar holder	Crosspieces		
B=600 mm	B=850 mm	B=600+300 mm	B=400 mm	-	B=600 / 600+300 mm	B=850 mm	B=400 mm	-	B=600 mm	B=850 mm	B=400 mm
GW D3 755	GW D3 757	-		-	-	-	-	-	-	-	-
-	-	GW D3 759 (for 600 mm depth) GW D3 761 (for 800 mm depth)		GW D3 754	GW D3 764	GW D3 765	GW D3 766	GW D3 754	GW D3 767	GW D3 768	GW D3 769
GW D3 755	GW D3 757	-		-	-	-	-	-	-	-	-
-	-	GW D3 759 (for 600 mm depth) GW D3 761 (for 800 mm depth)		GW D3 754	GW D3 764	GW D3 765	GW D3 766	GW D3 754	GW D3 767	GW D3 768	GW D3 769
GW D3 756	GW D3 758	GW D3 760 (for 600 mm depth) GW D3 762 (for 800 mm depth)		GW D3 763	GW D3 764	GW D3 765	GW D3 766	GW D3 763	GW D3 767	GW D3 768	GW D3 769

BUSBAR


Distribution systems for distribution boards

The BUSBAR range, in addition to distribution terminal blocks, consists of flat and shaped busbars in copper and aluminium in order to make distribution system inside QDX boards.



DISTRIBUTION TERMINAL BLOCKS

Horizontal divider



GW 44 700

Horizontal four-pole divider 250 A with pre-drilled threaded M6 busbars

Code	No. of modules EN 50022	Installation	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
For boards: QDX 630L/H - 1600H						
GW 44 700	16	On profile EN 50022	1xM12	10xM6	17 kA	1/2
GW 45 545	24	On functional profile	1xM8+2xM6	21xM6	23 kA	1
GW 45 546	35	On functional profile	1xM8+2xM6	32xM6	20 kA	1

CHARACTERISTICS: the connection capacity indicated is "per pole"; can also be fixed on the back-mounting plate.
ACCESSORIES SUPPLIED: fixing brackets on functional profile. Complete with protection shield and bolts and screws for cable input and output connections.
NOTES: usable with front panel of a height greater than, or equal to, 200mm.



GW 45 547

Horizontal four-pole divider 400 A with pre-drilled threaded M6 busbars

Code	No. of modules EN 50022	Installation	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
For boards: QDX 630L/H - 1600H						
GW 45 547	24	On functional profile	1xM8+2xM6	21xM6	23 kA	1
GW 45 548	35	On functional profile	1xM8+2xM6	32xM6	20 kA	1

CHARACTERISTICS: the indicated connection capacity is "per pole"; can also be fixed on the back-mounting plate.
ACCESSORIES SUPPLIED: fixing brackets on functional profile. Complete with protection shield and bolts and screws for cable input and output connections.
NOTES: an be used with front panel of a height greater than, or equal to, 200mm.
GW45547 and GW45548 are not suitable for P=200 mm QDX 630L and P=250 mm QDX630H distribution boards.

Modular dividers




GW 44 693

Two-pole distribution terminal blocks with transparent protection cover - fixing on plate or DIN rail EN 50022 - 750V - T 85°C

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 691	68x47x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/40
Rated current (A): 125						
GW 44 693	134x47x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/12

CHARACTERISTICS: the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".



GW 44 699


Four-pole distribution terminal blocks with transparent protection cover. Fixing on plate or DIN rail EN 50022 - 750V - T 85°C

Code	Outer dim. LxHxD (mm)	No. of modules EN 50022	Input connecting capacity	Output connecting capacity	Icw (1s)	Pack Carton
Rated current (A): 100						
GW 44 696	72x98x45	4	1x(6-35) mm²	[1x(4-25) + 5x(1.5-10)] mm²	6 kA	1/20
Rated current (A): 125						
GW 44 698	138x98x45	8	1x(6-35) mm²	[2x(4-25) + 2x(4-16) + 10x(1.5-10)] mm²	6 kA	1/10
Rated current (A): 160						
GW 44 699	186x136x70	11	1x(16-50) mm²	[2x(10-35) + 2x(6-25) + 8x(4-16)] mm²	10 kA	1/12

CHARACTERISTICS: terminal tightening torque: input cables 4 Nm, output cables 1.5 Nm.
the indicated connection capacity is "per pole" and refers to the fitting of cables with "test prods".

FLAT BUS-BAR DISTRIBUTION SYSTEMS

Flat busbar distribution systems




2 flat busbars in pre-drilled electrolytic copper

Code	Rated current	Section (mm²)	Length (mm)	Pack Carton
GW 45 551	250 A	20x5	1000	1
GW 45 553	400 A	30x5	1000	1
GW 45 554	630 A	30x10	1000	1
GW 45 555	250 A	20x5	1750	1
GW 45 557	400 A	30x5	1750	1
GW 45 558	630 A	30x10	1750	1
GW 49 678	800 A	60x5	1750	1
GW 49 679	1250 A	100x5	1750	1
GW 49 680	1600 A	100x10	1750	1

NOTE: from GW45551 to GW45558: M6 threaded busbars. GW49678 and GW49680: 10.5 mm through hole busbars.

Busbar-holder for flat busbars




GW D3 706

Pair of busbar-holders with crosspieces for vertical flat busbars for QDX 630L distribution boards

Code	Rated current	Section busbars (mm²)	For boards	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 701	250 A - 400 A	20x5 - 30x5	Wall and floor	200	Internal compartment	1
GW D3 702	250 A - 400 A	20x5 - 30x5	Wall mounting	200	External compartment	1
GW D3 703	250 A - 400 A	20x5 - 30x5	Floor-mounting	300	Structures L=600	1
GW D3 704	630 A	30x10	Floor-mounting	300	Structures L=600	1
GW D3 705	250 A - 400 A	20x5 - 30x5	Floor-mounting	300	Structures L=850	1
GW D3 706	630 A	30x10	Floor-mounting	300	Structures L=850	1
GW D3 707	250 A - 400 A	20x5 - 30x5	Floor-mounting	200 - 300	External compartment	1
GW D3 708	630 A	30x10	Floor-mounting	300	External compartment	1
GW D3 709	250 A - 400 A	20x5 - 30x5	Floor-mounting	300	Internal compartment	1

ACCESSORIES SUPPLIED: Crosspieces and fixing screw to the structure.



GW D3 724

Pair of busbar-holders with crosspieces for vertical flat busbars for QDX 630H distribution boards

Code	Rated current	Section busbars (mm²)	For boards	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 702	250 A - 400 A	20x5 - 30x5	Wall mounting	250 - 300	Side compartment	1
GW D3 721	250 A - 400 A	20x5 - 30x5	Floor-mounting	250 - 400	Structures L=600	1
GW D3 722	250 A - 400 A	20x5 - 30x5	Floor-mounting	250 - 400	Structures L=850	1
GW D3 723	250 A - 400 A	20x5 - 30x5	Floor-mounting	250 - 400	Side compartment	1
GW D3 724	250 A - 400 A	20x5 - 30x5	Floor-mounting	250 - 400	External compartment	1
GW D3 725	630 A	30x10	Floor-mounting	400	Structures L=600	1
GW D3 726	630 A	30x10	Floor-mounting	400	Structures L=850	1
GW D3 727	630 A	30x10	Floor-mounting	400	Side compartment	1
GW D3 728	630 A	30x10	Floor-mounting	400	External compartment	1

ACCESSORIES SUPPLIED: Crosspieces and fixing screw to the structure.



GW D3 729

Pair of busbar-holders with crosspieces for vertical flat busbars for QDX 1600H distribution boards

Code	Rated current	Section busbars (mm²)	For boards	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 721	250 A - 400 A	20x5 - 30x5	Floor-mounting	600 - 800	Structures L=600	1
GW D3 722	250 A - 400 A	20x5 - 30x5	Floor-mounting	600 - 800	Structures L=850	1
GW D3 729	630 A	30x10	Floor-mounting	600 - 800	Structures L=600	1
GW D3 730	800 A - 1250 A - 1600 A	60x5 - 100x5 - 100x10	Floor-mounting	600 - 800	Structures L=600	1
GW D3 731	630 A	30x10	Floor-mounting	600 - 800	Structures L=850	1
GW D3 732	800 A - 1250 A - 1600 A	60x5 - 100x5 - 100x10	Floor-mounting	600 - 800	Structures L=850	1
GW D3 733	250 A - 400 A	20x5 - 30x5	Floor-mounting	600	Side by side / external compartment	1
GW D3 734	630 A	30x10	Floor-mounting	600	Side by side / external compartment	1
GW D3 735	800 A - 1250 A - 1600 A	60x5 - 100x5 - 100x10	Floor-mounting	600	Side by side / external compartment	1
GW D3 736	250 A - 400 A	20x5 - 30x5	Floor-mounting	800	Side by side / external compartment	1
GW D3 737	630 A	30x10	Floor-mounting	800	Side by side / external compartment	1
GW D3 738	800 A - 1250 A - 1600 A	60x5 - 100x5 - 100x10	Floor-mounting	800	Side by side / external compartment	1



GW D3 745

Pair of busbar-holders for horizontal flat busbars for QDX 1600H distributions boards

Code	Rated current	Section busbars (mm²)	For boards	Suitable for structures D (mm)	Pack Carton
GW D3 745	800 A - 1250 A - 1600 A	60x5 - 100x5 - 100x10	Floor-mounting	600 - 800	1



GW D3 748

Pair of crosspieces for horizontal flat busbars for QDX 1600H distributions boards



Code	For busbar holder	Busbars position	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 747	GWD3745	Horizontal base/headboard Position 1	600 - 800	Structure B=600, side by side compartment	1
GW D3 748	GWD3745	Horizontal base/headboard Position 1	600 - 800	Structures L=850	1
GW D3 749	GWD3745	Horizontal base/headboard Position 1	600 - 800	External compartment	1
GW D3 767	GWD3745	Horizontal at any height Position 2	800	Structures L=600	1
GW D3 768	GWD3745	Horizontal at any height Position 2	800	Structures L=850	1
GW D3 769	GWD3745	Horizontal at any height Position 2	800	External compartment	1

Copper shaped busbars



GW D3 781

Pair of copper shaped busbars for QDX 1600H distribution boards

Code	Rated current	Section busbars (mm²)	Length (mm)	Pack Carton
GW D3 781	800 A	50x15	1830	1
GW D3 782	1250 A	50x31	1830	1
GW D3 783	1600 A	50x32	1830	1


Busbar holders for copper shaped busbars



GW D3 741

Pair of busbar-holders for vertical copper shaped busbars for QDX 1600H distribution boards

Code	Rated current	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 741	800 A - 1250 A - 1600 A	600 - 800	Structures L=600	1
GW D3 742	800 A - 1250 A - 1600 A	600 - 800	Structures L=850	1
GW D3 743	800 A - 1250 A - 1600 A	600	Side by side / external compartment	1
GW D3 744	800 A - 1250 A - 1600 A	800	Side by side / external compartment	1



GW D3 746

Pair of busbar-holders for horizontal copper shaped busbars for QDX 1600H distribution boards

Code	Rated current	Suitable for structures D (mm)	Pack Carton
GW D3 746	800 A - 1250 A - 1600 A	600 - 800	1



GW D3 747

Pair of crosspieces for horizontal shaped busbars for QDX 1600H distribution boards



Code	For busbar holder	Busbars position	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 747	GWD3746	Horizontal base/headboard Position 1	600 - 800	Structure B=600, side by side compartment	1
GW D3 748	GWD3746	Horizontal base/headboard Position 1	600 - 800	Structures L=850	1
GW D3 749	GWD3746	Horizontal base/headboard Position 1	600 - 800	External compartment	1
GW D3 767	GWD3746	Horizontal at any height Position 2	800	Structures L=600	1
GW D3 768	GWD3746	Horizontal at any height Position 2	800	Structures L=850	1
GW D3 769	GWD3746	Horizontal at any height Position 2	800	External compartment	1

Aluminium shaped busbars



GW D3 791

Pair of aluminium shaped busbars for QDX 630H- 1600H distribution boards

Code	Rated current	Section busbars (mm²)	Length (mm)	Pack Carton
GW D3 791	630 A	30x40	1734	1
GW D3 792	800 A	30x40	1734	1
GW D3 793	1250 A	60x30	1734	1
GW D3 794	1600 A	60x30	1734	1

CHARACTERISTICS: anodised aluminium busbars and nickel contact surface, applied with cold spray technology, in order to allow the connection with cables, flexible and rigid busbars.

Busbar holders for alluminium shaped busbars



GW D3 751

Pair of busbar-holders for vertical aluminium shaped busbars for QDX 630H distribution boards

Code	Rated current	For boards	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 751	630 A	Floor-mounting	400	Structures L=600	1
GW D3 752	630 A	Floor-mounting	400	Structures L=850	1
GW D3 753	630 A	Floor-mounting	400	Side compartment	1
GW D3 754	630 A	Floor-mounting	400	External compartment	1



GW D3 755

Pair of busbar-holders for vertical aluminium shaped busbars for QDX 1600H distribution boards

Code	Rated current	For boards	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 755	630 A - 800 A	Floor-mounting	600 - 800	Structures L=600	1
GW D3 756	1250 A - 1600 A	Floor-mounting	600 - 800	Structures L=600	1
GW D3 757	630 A - 800 A	Floor-mounting	600 - 800	Structures L=850	1
GW D3 758	1250 A - 1600 A	Floor-mounting	600 - 800	Structures L=850	1
GW D3 759	630 A - 800 A	Floor-mounting	600	Side by side / external compartment	1
GW D3 760	1250 A - 1600 A	Floor-mounting	600	Side by side / external compartment	1
GW D3 761	630 A - 800 A	Floor-mounting	800	Side by side / external compartment	1
GW D3 762	1250 A - 1600 A	Floor-mounting	800	Side by side / external compartment	1



GW D3 763

Pair of busbar-holders for horizontal aluminium shaped busbars for QDX 1600H distribution boards

Code	Rated current	Suitable for structures D (mm)	Pack Carton
GW D3 754	630 A - 800 A	600 - 800	1
GW D3 763	1250 A - 1600 A	600 - 800	1



GW D3 764

Pair of crosspieces for horizontal aluminium shaped busbars for QDX 1600H distribution boards



Code	For busbar-holders	Busbars position	Suitable for structures D (mm)	Installation	Pack Carton
GW D3 764	GWD3754, GWD3763	Horizontal base/headboard Position 1	600 - 800	Structure B=600, side by side compartment	1
GW D3 765	GWD3754, GWD3763	Horizontal base/headboard Position 1	600 - 800	Structures L=850	1
GW D3 766	GWD3754, GWD3763	Horizontal base/headboard Position 1	600 - 800	External compartment	1
GW D3 767	GWD3754, GWD3763	Horizontal at any height Position 2	800	Structures L=600	1
GW D3 768	GWD3754, GWD3763	Horizontal at any height Position 2	800	Structures L=850	1
GW D3 769	GWD3754, GWD3763	Horizontal at any height Position 2	800	External compartment	1

Flexible straps



GW 47 652

Copper flexible busbars - Length: 2 metres per piece

Code	Rated current	Quantity	Dimensions (mm)	Section (mm²)	Pack Carton
GW 47 650	160 A	2	2x15.5x0.8	24,8	1
GW 47 652	250 A	2	3x20x1	60	1
GW 47 653	400 A	2	5x20x1	100	1
GW 47 654	630 A	2	8x24x1	192	1
GW 47 655	1000 A	2	8x40x1	320	1

CHARACTERISTICS: conductor in electrolytic copper with high resistance compound vinyl insulation (duty voltage 1000 V).

Accessories for busbars



GW D3 771

Joints for copper shapehd busbars

Code	For bars (In)	No. of pieces	Pack Carton
GW D3 771	800 A	4	1
GW D3 772	1250/1600 A	4	1

APPLICATIONS: joints for connecting vertical and horizontal busbars.
CHARACTERISTICS: kit consisting of
: - 4 copper joints (section 50x10) of length 100 mm
- no. 32 hammer screws, washers and nuts.



GW D3 773

Joints for alluminium shapehd busbars

Code	For bars (In)	Section (mm)	No. of pieces	Pack Carton
GW D3 773	630/800 A	40x8	4	1
GW D3 774	1250/1600 A	80x10	4	1

APPLICATIONS: joints for connecting vertical and horizontal busbars.
CHARACTERISTICS: kit consisting of
: - 4 aluminium joints of length
: - 95 mm (phase 1)
- 125 mm (phase 2)
- 155 mm (phase 3)
- 185 mm (neutral)
- no. 12 hammer screws, washers and nuts for GWD3773 or no. 20 hammer screws, washers and nuts for GWD3774.



GW D3 775

Cut-out coupling elements for shaped busbars

Code	No. of pieces	Pack Carton
GW D3 775	4	1

APPLICATIONS: joints for connecting the shaped bars (copper and aluminium) with cables with cable terminals.
CHARACTERISTICS: kit consisting of
:- no. 4 M6 drilled busbars
- no. 8 25x8 hammer screws, washers and nuts for fixing joints on the bars.

BUSBAR



GW D3 776

Support bases for copper shaped busbars

Code	Suitable for QDX 1600H structures	No. of pieces	Pack Carton
GW D3 776	B=600 mm	4	1
GW D3 777	B=850 mm	4	1
GW D3 778	P=600 mm	4	1
GW D3 779	P=800 mm	4	1

APPLICATIONS: brackets to hold the bars in vertical position.
CHARACTERISTICS: kit consisting of
:- 1 metal bracket
- 4 plastic bases
- 8 fixing screws
- 1 mounting crosspiece (one different for each code).



GW D3 713

Adhesives for shaped busbars

Code	No. pieces per phase (L1 - L2 - L3 - N)	Pack Carton
GW D3 713	10	1

APPLICATIONS: adhesives to identify the phases (L1-L2-L3) and neutral (N) to be applied on copper and aluminium shaped bars.
NOTE: Quantities (10 pieces) refer to each individual phase for a total of 40 pieces.



GW D3 714

M8 drive-screws for shaped busbars

Code	Length (mm)	For bars (In)	No. of pieces	Pack Carton
GW D3 714	25	Aluminium (630A-800A-1250A-1600A) & copper (800A-1250A)	20	1
GW D3 715	35	Copper (1600A)	20	1

NOTE: no. 20 hammer screws, washers and nuts.

Spare accessories for busbars



GW D3 712


Phase Compensators for linear busbar holders

Code	Thickness (mm)	No. of pieces	Pack Carton
GW D3 711	5	4	1
GW D3 712	10	4	1

NOTE: GWD3711 suitable for bars with 5mm thickness for linear bar holders.
GWD3712 suitable for 10mm thick busbars for linear busbar holders.



BUSBAR



Scan the QR Code and find out all the technical informations.

QUICK CONNECT



Connections to the busbar system are facilitated by the special shape of the contoured busbar section, with a special sliding hammer screw in the profile that allows the connection of junctions at any point on the busbar, avoiding the need to drill holes.

ALUMINUM BAR SYSTEM



Quick, inexpensive, versatile, the universal aluminum bar system allows for maximum customization of GEWISS switchboards, thanks to different positioning configurations.


FLEXIBILITY OF USE



The pre-drilled holes, with 25 mm spacing, on the flat bars allows for quick bar, strap or cable connection. In addition, junctions between flat bars and contoured busbars can be made easily using special joints.

Building





ChoruSmart

Innovative domestic range characterized by a wide choice of materials, shapes and finishes, able to satisfy any need. Five styles of plates (ONE, GEO, EGO / EGO SMART, LUX, ICE / ICE Touch) made in different colors and materials, with modular devices in six color variants with three glossy finishes (white, ivory and painted titanium) and three satin finishes (white, natural beige and black) and three different sizes (½ module, 1, 2 modules). Available for flush- and wall-mounted installations, ChoruSmart can be integrated with Smart Home & Building solutions.



System

A range of modular devices ideal for flush-mounted (for rectangular or square boxes), wall-mounted and for special applications. The SYSTEM domestic range stands out for its glossy white or satin black finish devices and the plates in 14 colors and in two different shapes, modern or classic, with a glossy finish. The line includes controls, sockets, protections, indicators, connectors and devices for control, safety and home comfort.



27 Combi

A complete and versatile system of modular containers, which can be perfectly integrated into the SYSTEM domestic range, which is able to meet the high protection installation needs of the residential sectors, tertiary and industrial sectors. The 27 COMBI series is available both in the IP40 version and in the watertight versions with IP55 and IP65 degree of protection, recommended for all outdoor applications subject to severe atmospheric conditions.



Playbus

A range of modular devices for domestic and similar uses, which can be assembled on supports for rectangular flush-mounted boxes up to 18 modules. The domestic range is distinguished by the satin black devices and the plates in two different shapes, modern or classic, with glossy or matt finishes. The line includes controls, sockets, protections, indicators, connectors and devices for control, safety and home comfort.



Dahlia

A wide choice of plates, realized in technopolymer in seven colors with glossy finish: white, ivory, hemp, cream, light grey, dark grey, anthracite grey. Plates available in different modularities, from 1 to 5 gang, installable indifferently in horizontal or in vertical position.



Smart home & building solutions


The GEWISS offer makes it possible to create a wide range of home automation functions (light control, movement roller shutters, climate control, comfort, safety, energy saving, load management, remote control with smartphone/tablet) in the residential and tertiary sector, exploiting various technologies: traditional, wireless ZigBee (Connected Smart Home), KNX bus (Home & Building Pro).



Data and energy distribution

The speed and reliability of the networks play an ever more important role in the communication sector. For this reason, GEWISS has created Data Center: a complete, integrated range of products for LAN structured network cabling. A solution that stands out for the extreme flexibility it offers in terms of office workstation configuration, as well as the simplicity and speed of wiring and the superior reliability of the connections. GEWISS also offers an extensive range of power take-offs, with plugs, socket-outlets and adapters.

ChoruSmart



Domestic range

Plates

p. 697







Domestic range

Installation accessories

p. 769

Domestic range

Modular devices

p. 788

Domestic range

Antibacterial range

p. 971

ONE International plates


Technopolymer

WHITE



GW 16 122 TB	2 modules
GW 16 123 TB	2+2 modules horiz.
GW 16 124 TB	2+2 modules vert.
GW 16 126 TB	2+2+2 modules horiz.
GW 16 127 TB	2+2+2 modules vert.
GW 16 128 TB	2+2+2+2 modules horiz.
GW 16 129 TB	2+2+2+2 modules vert.

TONER BLACK



GW 16 122 TN	2 modules
GW 16 123 TN	2+2 modules horiz.
GW 16 124 TN	2+2 modules vert.
GW 16 126 TN	2+2+2 modules horiz.
GW 16 127 TN	2+2+2 modules vert.
GW 16 128 TN	2+2+2+2 modules horiz.
GW 16 129 TN	2+2+2+2 modules vert.

IVORY



GW 16 122 TI	2 modules
GW 16 123 TI	2+2 modules horiz.
GW 16 124 TI	2+2 modules vert.
GW 16 126 TI	2+2+2 modules horiz.
GW 16 127 TI	2+2+2 modules vert.
GW 16 128 TI	2+2+2+2 modules horiz.
GW 16 129 TI	2+2+2+2 modules vert.

HEMP



GW 16 122 TC	2 modules
GW 16 123 TC	2+2 modules horiz.
GW 16 124 TC	2+2 modules vert.
GW 16 126 TC	2+2+2 modules horiz.
GW 16 127 TC	2+2+2 modules vert.
GW 16 128 TC	2+2+2+2 modules horiz.
GW 16 129 TC	2+2+2+2 modules vert.

Painted technopolymer

SATIN WHITE



GW 16 122 VW	2 modules
GW 16 123 VW	2+2 modules horiz.
GW 16 124 VW	2+2 modules vert.
GW 16 126 VW	2+2+2 modules horiz.
GW 16 127 VW	2+2+2 modules vert.
GW 16 128 VW	2+2+2+2 modules horiz.
GW 16 129 VW	2+2+2+2 modules vert.

NATURAL BEIGE



GW 16 122 VL	2 modules
GW 16 123 VL	2+2 modules horiz.
GW 16 124 VL	2+2 modules vert.
GW 16 126 VL	2+2+2 modules horiz.
GW 16 127 VL	2+2+2 modules vert.
GW 16 128 VL	2+2+2+2 modules horiz.
GW 16 129 VL	2+2+2+2 modules vert.

SATIN BLACK



GW 16 122 VN	2 modules
GW 16 123 VN	2+2 modules horiz.
GW 16 124 VN	2+2 modules vert.
GW 16 126 VN	2+2+2 modules horiz.
GW 16 127 VN	2+2+2 modules vert.
GW 16 128 VN	2+2+2+2 modules horiz.
GW 16 129 VN	2+2+2+2 modules vert.

TITANIUM ▲



GW 16 122 VT	2 modules
GW 16 123 VT	2+2 modules horiz.
GW 16 124 VT	2+2 modules vert.
GW 16 126 VT	2+2+2 modules horiz.
GW 16 127 VT	2+2+2 modules vert.
GW 16 128 VT	2+2+2+2 modules horiz.
GW 16 129 VT	2+2+2+2 modules vert.

TUSCAN RED



GW 16 122 VD	2 modules
GW 16 123 VD	2+2 modules horiz.
GW 16 124 VD	2+2 modules vert.
GW 16 126 VD	2+2+2 modules horiz.
GW 16 127 VD	2+2+2 modules vert.
GW 16 128 VD	2+2+2+2 modules horiz.
GW 16 129 VD	2+2+2+2 modules vert.

TEAL



GW 16 122 VZ	2 modules
GW 16 123 VZ	2+2 modules horiz.
GW 16 124 VZ	2+2 modules vert.
GW 16 126 VZ	2+2+2 modules horiz.
GW 16 127 VZ	2+2+2 modules vert.
GW 16 128 VZ	2+2+2+2 modules horiz.
GW 16 129 VZ	2+2+2+2 modules vert.

SOFT COPPER ▲



GW 16 122 VX	2 modules
GW 16 123 VX	2+2 modules horiz.
GW 16 124 VX	2+2 modules vert.
GW 16 126 VX	2+2+2 modules horiz.
GW 16 127 VX	2+2+2 modules vert.
GW 16 128 VX	2+2+2+2 modules horiz.
GW 16 129 VX	2+2+2+2 modules vert.


GOLD ▲



GW 16 122 VO	2 modules
GW 16 123 VO	2+2 modules horiz.
GW 16 124 VO	2+2 modules vert.
GW 16 126 VO	2+2+2 modules horiz.
GW 16 127 VO	2+2+2 modules vert.
GW 16 128 VO	2+2+2+2 modules horiz.
GW 16 129 VO	2+2+2+2 modules vert.

Modularity

Centre distance 71 mm



▲ Metallic effect

For customized plates please contact our GEWISS Sales Organization

ChoruSmart

ONE International plates

Informal in appearance and classic in geometry, ONE is the ChoruSmart system's range of plates dedicated to those who want to furnish their homes with simple touches. ONE's understated and discreet design enhances any space, bringing harmony and aesthetic consistency to every room. Available in a wide range of colours, ONE comes in every shade you need to give free rein to your imagination.



ONE INTERNATIONAL PLATES

Technopolymer



GW 16 122 TB

ONE International - White

Code	Description	Type	Pack Carton
GW 16 122 TB	2 modules	-	12
GW 16 123 TB	2+2 modules	Horizontal	12
GW 16 124 TB	2+2 modules	Vertical	12
GW 16 126 TB	2+2+2 modules	Horizontal	6
GW 16 127 TB	2+2+2 modules	Vertical	6
GW 16 128 TB	2+2+2+2 modules	Horizontal	1
GW 16 129 TB	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.



GW 16 122 TN

ONE International - Toner black

Code	Description	Type	Pack Carton
GW 16 122 TN	2 modules	-	12
GW 16 123 TN	2+2 modules	Horizontal	12
GW 16 124 TN	2+2 modules	Vertical	12
GW 16 126 TN	2+2+2 modules	Horizontal	6
GW 16 127 TN	2+2+2 modules	Vertical	6
GW 16 128 TN	2+2+2+2 modules	Horizontal	1
GW 16 129 TN	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.



GW 16 122 TI

ONE International - Ivory

Code	Description	Type	Pack Carton
GW 16 122 TI	2 modules	-	12
GW 16 123 TI	2+2 modules	Horizontal	12
GW 16 124 TI	2+2 modules	Vertical	12
GW 16 126 TI	2+2+2 modules	Horizontal	6
GW 16 127 TI	2+2+2 modules	Vertical	6
GW 16 128 TI	2+2+2+2 modules	Horizontal	1
GW 16 129 TI	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.



GW 16 122 TC

ONE International - Hemp

Code	Description	Type	Pack Carton
GW 16 122 TC	2 modules	-	12
GW 16 123 TC	2+2 modules	Horizontal	12
GW 16 124 TC	2+2 modules	Vertical	12
GW 16 126 TC	2+2+2 modules	Horizontal	6
GW 16 127 TC	2+2+2 modules	Vertical	6
GW 16 128 TC	2+2+2+2 modules	Horizontal	1
GW 16 129 TC	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.

ChoruSmart - Plates

Painted technopolymer



GW 16 122 VW

ONE International - Satin white

Code	Description	Type	Pack Carton
GW 16 122 VW	2 modules	-	12
GW 16 123 VW	2+2 modules	Horizontal	12
GW 16 124 VW	2+2 modules	Vertical	12
GW 16 126 VW	2+2+2 modules	Horizontal	6
GW 16 127 VW	2+2+2 modules	Vertical	6
GW 16 128 VW	2+2+2+2 modules	Horizontal	1
GW 16 129 VW	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 122 VL

ONE International - Natural beige

Code	Description	Type	Pack Carton
GW 16 122 VL	2 modules	-	12
GW 16 123 VL	2+2 modules	Horizontal	12
GW 16 124 VL	2+2 modules	Vertical	12
GW 16 126 VL	2+2+2 modules	Horizontal	6
GW 16 127 VL	2+2+2 modules	Vertical	6
GW 16 128 VL	2+2+2+2 modules	Horizontal	1
GW 16 129 VL	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 122 VN

ONE International - Satin black

Code	Description	Type	Pack Carton
GW 16 122 VN	2 modules	-	12
GW 16 123 VN	2+2 modules	Horizontal	12
GW 16 124 VN	2+2 modules	Vertical	12
GW 16 126 VN	2+2+2 modules	Horizontal	6
GW 16 127 VN	2+2+2 modules	Vertical	6
GW 16 128 VN	2+2+2+2 modules	Horizontal	12
GW 16 129 VN	2+2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 122 VT

ONE International - Titanium

Code	Description	Type	Pack Carton
GW 16 122 VT	2 modules	-	12
GW 16 123 VT	2+2 modules	Horizontal	12
GW 16 124 VT	2+2 modules	Vertical	12
GW 16 126 VT	2+2+2 modules	Horizontal	6
GW 16 127 VT	2+2+2 modules	Vertical	6
GW 16 128 VT	2+2+2+2 modules	Horizontal	1
GW 16 129 VT	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 122 VD

ONE International - Tuscan red

Code	Description	Type	Pack Carton
GW 16 122 VD	2 modules	-	12
GW 16 123 VD	2+2 modules	Horizontal	12
GW 16 124 VD	2+2 modules	Vertical	12
GW 16 126 VD	2+2+2 modules	Horizontal	6
GW 16 127 VD	2+2+2 modules	Vertical	6
GW 16 128 VD	2+2+2+2 modules	Horizontal	1
GW 16 129 VD	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 122 VZ

ONE International - Teal

Code	Description	Type	Pack Carton
GW 16 122 VZ	2 modules	-	12
GW 16 123 VZ	2+2 modules	Horizontal	12
GW 16 124 VZ	2+2 modules	Vertical	12
GW 16 126 VZ	2+2+2 modules	Horizontal	6
GW 16 127 VZ	2+2+2 modules	Vertical	6
GW 16 128 VZ	2+2+2+2 modules	Horizontal	1
GW 16 129 VZ	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.

ChoruSmart - Plates



GW 16 122 VX

ONE International - Soft copper

Code	Description	Type	Pack Carton
GW 16 122 VX	2 modules	-	12
GW 16 123 VX	2+2 modules	Horizontal	12
GW 16 124 VX	2+2 modules	Vertical	12
GW 16 126 VX	2+2+2 modules	Horizontal	6
GW 16 127 VX	2+2+2 modules	Vertical	6
GW 16 128 VX	2+2+2+2 modules	Horizontal	1
GW 16 129 VX	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 122 VO

ONE International - Gold

Code	Description	Type	Pack Carton
GW 16 122 VO	2 modules	-	12
GW 16 123 VO	2+2 modules	Horizontal	12
GW 16 124 VO	2+2 modules	Vertical	12
GW 16 126 VO	2+2+2 modules	Horizontal	6
GW 16 127 VO	2+2+2 modules	Vertical	6
GW 16 128 VO	2+2+2+2 modules	Horizontal	1
GW 16 129 VO	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



ChoruSmart



Scan the QR Code and find out all the technical informations.

REFINED DESIGN



Minimal in shape, classic in style: ONE International plates enhance any room, bringing harmony and beauty to every corner of the house.

FINISHES



The ONE International plate, with its minimal appearance, is available in various colours and in 2 finishes: glossy and satin, for every need.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

GEO International plates

Technopolymer

WHITE

GW 16 422 TB	2 modules
GW 16 423 TB	2+2 modules horiz.
GW 16 424 TB	2+2 modules vert.
GW 16 426 TB	2+2+2 modules horiz.
GW 16 427 TB	2+2+2 modules vert.

TONER BLACK



GW 16 422 TN	2 modules
GW 16 423 TN	2+2 modules horiz.
GW 16 424 TN	2+2 modules vert.
GW 16 426 TN	2+2+2 modules horiz.
GW 16 427 TN	2+2+2 modules vert.

IVORY

GW 16 422 TI	2 modules
GW 16 423 TI	2+2 modules horiz.
GW 16 424 TI	2+2 modules vert.
GW 16 426 TI	2+2+2 modules horiz.
GW 16 427 TI	2+2+2 modules vert.

HEMP



GW 16 422 TC	2 modules
GW 16 423 TC	2+2 modules horiz.
GW 16 424 TC	2+2 modules vert.
GW 16 426 TC	2+2+2 modules horiz.
GW 16 427 TC	2+2+2 modules vert.

Painted technopolymer

SATIN WHITE

GW 16 422 VW	2 modules
GW 16 423 VW	2+2 modules horiz.
GW 16 424 VW	2+2 modules vert.
GW 16 426 VW	2+2+2 modules horiz.
GW 16 427 VW	2+2+2 modules vert.

NATURAL BEIGE



GW 16 422 VL	2 modules
GW 16 423 VL	2+2 modules horiz.
GW 16 424 VL	2+2 modules vert.
GW 16 426 VL	2+2+2 modules horiz.
GW 16 427 VL	2+2+2 modules vert.

SATIN BLACK



GW 16 422 VN	2 modules
GW 16 423 VN	2+2 modules horiz.
GW 16 424 VN	2+2 modules vert.
GW 16 426 VN	2+2+2 modules horiz.
GW 16 427 VN	2+2+2 modules vert.

TITANIUM ▲



GW 16 422 VT	2 modules
GW 16 423 VT	2+2 modules horiz.
GW 16 424 VT	2+2 modules vert.
GW 16 426 VT	2+2+2 modules horiz.
GW 16 427 VT	2+2+2 modules vert.

TUSCAN RED



GW 16 422 VD	2 modules
GW 16 423 VD	2+2 modules horiz.
GW 16 424 VD	2+2 modules vert.
GW 16 426 VD	2+2+2 modules horiz.
GW 16 427 VD	2+2+2 modules vert.

TEAL



GW 16 422 VZ	2 modules
GW 16 423 VZ	2+2 modules horiz.
GW 16 424 VZ	2+2 modules vert.
GW 16 426 VZ	2+2+2 modules horiz.
GW 16 427 VZ	2+2+2 modules vert.

SOFT COPPER ▲



GW 16 422 VX	2 modules
GW 16 423 VX	2+2 modules horiz.
GW 16 424 VX	2+2 modules vert.
GW 16 426 VX	2+2+2 modules horiz.
GW 16 427 VX	2+2+2 modules vert.


GOLD ▲



GW 16 422 VO	2 modules
GW 16 423 VO	2+2 modules horiz.
GW 16 424 VO	2+2 modules vert.
GW 16 426 VO	2+2+2 modules horiz.
GW 16 427 VO	2+2+2 modules vert.

Modularity

Centre distance 71 mm



▲ Metallic effect

For customized plates please contact our GEWISS Sales Organization

ChoruSmart

GEO International plates

The GEO plate with clean, regular lines fits perfectly into any environment with its simplicity and style. The materials and colours contribute to creating the right harmony that stands the test of time. Made from technopolymer, GEO resists the impact and stresses of everyday use. The different colours and the simple and light shapes make GEO a young and informal furnishing element that conveys a minimalist style in any space.



GEO INTERNATIONAL PLATES

Technopolymer

GW 16 422 TB

GEO International - White

Code	Description	Type	Pack Carton
GW 16 422 TB	2 modules	-	12
GW 16 423 TB	2+2 modules	Horizontal	12
GW 16 424 TB	2+2 modules	Vertical	12
GW 16 426 TB	2+2+2 modules	Horizontal	6
GW 16 427 TB	2+2+2 modules	Vertical	6

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.



GW 16 422 TN

GEO International - Toner black

Code	Description	Type	Pack Carton
GW 16 422 TN	2 modules	-	12
GW 16 423 TN	2+2 modules	Horizontal	12
GW 16 424 TN	2+2 modules	Vertical	12
GW 16 426 TN	2+2+2 modules	Horizontal	6
GW 16 427 TN	2+2+2 modules	Vertical	6

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.

GW 16 422 TI

GEO International - Ivory

Code	Description	Type	Pack Carton
GW 16 422 TI	2 modules	-	12
GW 16 423 TI	2+2 modules	Horizontal	12
GW 16 424 TI	2+2 modules	Vertical	12
GW 16 426 TI	2+2+2 modules	Horizontal	6
GW 16 427 TI	2+2+2 modules	Vertical	6

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.



GW 16 422 TC

GEO International - Hemp

Code	Description	Type	Pack Carton
GW 16 422 TC	2 modules	-	12
GW 16 423 TC	2+2 modules	Horizontal	12
GW 16 424 TC	2+2 modules	Vertical	12
GW 16 426 TC	2+2+2 modules	Horizontal	6
GW 16 427 TC	2+2+2 modules	Vertical	6

CHARACTERISTICS: glossy finish.
NOTES: centre distance 71 mm.

ChoruSmart - Plates

Painted technopolymer

GW 16 422 VW

GEO International - Satin white

Code	Description	Type	Pack Carton
GW 16 422 VW	2 modules	-	12
GW 16 423 VW	2+2 modules	Horizontal	12
GW 16 424 VW	2+2 modules	Vertical	12
GW 16 426 VW	2+2+2 modules	Horizontal	6
GW 16 427 VW	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 422 VL

GEO international - Natural beige

Code	Description	Type	Pack Carton
GW 16 422 VL	2 modules	-	12
GW 16 423 VL	2+2 modules	Horizontal	12
GW 16 424 VL	2+2 modules	Vertical	12
GW 16 426 VL	2+2+2 modules	Horizontal	6
GW 16 427 VL	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 422 VN

GEO international - Satin black

Code	Description	Type	Pack Carton
GW 16 422 VN	2 modules	-	12
GW 16 423 VN	2+2 modules	Horizontal	12
GW 16 424 VN	2+2 modules	Vertical	12
GW 16 426 VN	2+2+2 modules	Horizontal	6
GW 16 427 VN	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 422 VT

GEO International - Titanium

Code	Description	Type	Pack Carton
GW 16 422 VT	2 modules	-	12
GW 16 423 VT	2+2 modules	Horizontal	12
GW 16 424 VT	2+2 modules	Vertical	12
GW 16 426 VT	2+2+2 modules	Horizontal	6
GW 16 427 VT	2+2+2 modules	Vertical	6

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 422 VD

GEO International - Tuscan red

Code	Description	Type	Pack Carton
GW 16 422 VD	2 modules	-	12
GW 16 423 VD	2+2 modules	Horizontal	12
GW 16 424 VD	2+2 modules	Vertical	12
GW 16 426 VD	2+2+2 modules	Horizontal	6
GW 16 427 VD	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.



GW 16 422 VZ

GEO International - Teal

Code	Description	Type	Pack Carton
GW 16 422 VZ	2 modules	-	12
GW 16 423 VZ	2+2 modules	Horizontal	12
GW 16 424 VZ	2+2 modules	Vertical	12
GW 16 426 VZ	2+2+2 modules	Horizontal	6
GW 16 427 VZ	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.

ChoruSmart - Plates



GW 16 422 VX

GEO International - Soft copper

Code	Description	Type	Pack Carton
GW 16 422 VX	2 modules	-	12
GW 16 423 VX	2+2 modules	Horizontal	12
GW 16 424 VX	2+2 modules	Vertical	12
GW 16 426 VX	2+2+2 modules	Horizontal	6
GW 16 427 VX	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 422 VO

GEO International - Gold

Code	Description	Type	Pack Carton
GW 16 422 VO	2 modules	-	12
GW 16 423 VO	2+2 modules	Horizontal	12
GW 16 424 VO	2+2 modules	Vertical	12
GW 16 426 VO	2+2+2 modules	Horizontal	6
GW 16 427 VO	2+2+2 modules	Vertical	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



ChoruSmart



Scan the QR Code and find out all the technical informations.

MINIMAL DESIGN



The colours and simple, light shapes make GEO International a youthful and informal furnishing item that expresses a minimalist style wherever it is placed.

FINISHES



The GEO International plate, simple and youthful, is available in various colours and in 2 finishes: glossy and satin, for every need.


HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

EGO International plates

Painted technopolymer

SATIN WHITE



GW 16 022 PW	2 modules
GW 16 023 PW	2+2 modules horiz.
GW 16 024 PW	2+2 modules vert.
GW 16 026 PW	2+2+2 modules horiz.

CLAY



GW 16 022 CY	2 modules
GW 16 023 CY	2+2 modules horiz.
GW 16 024 CY	2+2 modules vert.
GW 16 026 CY	2+2+2 modules horiz.

NATURAL BEIGE




GW 16 022 NB	2 modules
GW 16 023 NB	2+2 modules horiz.
GW 16 024 NB	2+2 modules vert.
GW 16 026 NB	2+2+2 modules horiz.

DARK SAND



GW 16 022 DS	2 modules
GW 16 023 DS	2+2 modules horiz.
GW 16 024 DS	2+2 modules vert.
GW 16 026 DS	2+2+2 modules horiz.

SATIN BLACK



GW 16 022 DB	2 modules
GW 16 023 DB	2+2 modules horiz.
GW 16 024 DB	2+2 modules vert.
GW 16 026 DB	2+2+2 modules horiz.

MAGNETIC GRAY ▲



GW 16 022 GR	2 modules
GW 16 023 GR	2+2 modules horiz.
GW 16 024 GR	2+2 modules vert.
GW 16 026 GR	2+2+2 modules horiz.

LIGHT BRONZE ▲




GW 16 022 BR	2 modules
GW 16 023 BR	2+2 modules horiz.
GW 16 024 BR	2+2 modules vert.
GW 16 026 BR	2+2+2 modules horiz.

STEEL ▲




GW 16 022 ST	2 modules
GW 16 023 ST	2+2 modules horiz.
GW 16 024 ST	2+2 modules vert.
GW 16 026 ST	2+2+2 modules horiz.

SOFT COPPER ▲



GW 16 022 CS	2 modules
GW 16 023 CS	2+2 modules horiz.
GW 16 024 CS	2+2 modules vert.
GW 16 026 CS	2+2+2 modules horiz.

GOLD ▲



GW 16 022 SG	2 modules
GW 16 023 SG	2+2 modules horiz.
GW 16 024 SG	2+2 modules vert.
GW 16 026 SG	2+2+2 modules horiz.

COPPER ▲




GW 16 022 CP	2 modules
GW 16 023 CP	2+2 modules horiz.
GW 16 024 CP	2+2 modules vert.
GW 16 026 CP	2+2+2 modules horiz.

BROWN SHADE ▲



GW 16 022 BS	2 modules
GW 16 023 BS	2+2 modules horiz.
GW 16 024 BS	2+2 modules vert.
GW 16 026 BS	2+2+2 modules horiz.

Modularity




▲ Metallic effect

For customized plates please contact our GEWISS Sales Organization

ChoruSmart


EGO International plates

With their clean, compact lines, EGO plates make the right impression. Modern shapes with slightly curved surfaces that taper towards the edges convey balance and simplicity. The opalescent profiles inside the plate, in aesthetic continuity with the EGO SMART versions, add a subtle element of unique identity. Every detail is designed to ensure appeal and personality.



EGO INTERNATIONAL PLATES

Painted technopolymer




GW 16 022 PW

EGO International - Satin white

Code	Description	Type	Pack Carton
GW 16 022 PW	2 modules	-	12
GW 16 023 PW	2+2 modules	Horizontal	12
GW 16 024 PW	2+2 modules	Vertical	12
GW 16 026 PW	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.




GW 16 022 CY

EGO International - Clay

Code	Description	Type	Pack Carton
GW 16 022 CY	2 modules	-	12
GW 16 023 CY	2+2 modules	Horizontal	12
GW 16 024 CY	2+2 modules	Vertical	12
GW 16 026 CY	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.




GW 16 022 NB

EGO International - Natural beige

Code	Description	Type	Pack Carton
GW 16 022 NB	2 modules	-	12
GW 16 023 NB	2+2 modules	Horizontal	12
GW 16 024 NB	2+2 modules	Vertical	12
GW 16 026 NB	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.

ChoruSmart - Plates




GW 16 022 DS

EGO International - Dark sand

Code	Description	Type	Pack Carton
GW 16 022 DS	2 modules	-	12
GW 16 023 DS	2+2 modules	Horizontal	12
GW 16 024 DS	2+2 modules	Vertical	12
GW 16 026 DS	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.




GW 16 022 DB

EGO International - Satin black

Code	Description	Type	Pack Carton
GW 16 022 DB	2 modules	-	12
GW 16 023 DB	2+2 modules	Horizontal	12
GW 16 024 DB	2+2 modules	Vertical	12
GW 16 026 DB	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish.
NOTES: centre distance 71 mm.




GW 16 022 GR

EGO International - Magnetic gray

Code	Description	Type	Pack Carton
GW 16 022 GR	2 modules	-	12
GW 16 023 GR	2+2 modules	Horizontal	12
GW 16 024 GR	2+2 modules	Vertical	12
GW 16 026 GR	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 022 BR

EGO International - Light bronze

Code	Description	Type	Pack Carton
GW 16 022 BR	2 modules	-	12
GW 16 023 BR	2+2 modules	Horizontal	12
GW 16 024 BR	2+2 modules	Vertical	12
GW 16 026 BR	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.




GW 16 022 ST

EGO International - Steel

Code	Description	Type	Pack Carton
GW 16 022 ST	2 modules	-	12
GW 16 023 ST	2+2 modules	Horizontal	12
GW 16 024 ST	2+2 modules	Vertical	12
GW 16 026 ST	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.




GW 16 022 CS

EGO International - Soft copper

Code	Description	Type	Pack Carton
GW 16 022 CS	2 modules	-	12
GW 16 023 CS	2+2 modules	Horizontal	12
GW 16 024 CS	2+2 modules	Vertical	12
GW 16 026 CS	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.

ChoruSmart - Plates




GW 16 022 SG

EGO International - Gold

Code	Description	Type	Pack Carton
GW 16 022 SG	2 modules	-	12
GW 16 023 SG	2+2 modules	Horizontal	12
GW 16 024 SG	2+2 modules	Vertical	12
GW 16 026 SG	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 022 CP

EGO International - Copper

Code	Description	Type	Pack Carton
GW 16 022 CP	2 modules	-	12
GW 16 023 CP	2+2 modules	Horizontal	12
GW 16 024 CP	2+2 modules	Vertical	12
GW 16 026 CP	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.



GW 16 022 BS

EGO International - Brown shade


Code	Description	Type	Pack Carton
GW 16 022 BS	2 modules	-	12
GW 16 023 BS	2+2 modules	Horizontal	12
GW 16 024 BS	2+2 modules	Vertical	12
GW 16 026 BS	2+2+2 modules	Horizontal	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: centre distance 71 mm.






ChoruSmart




Scan the QR Code and find out all the technical informations.

ATTENTION TO DETAIL



Three thematic lines of plates to match perfectly with ChoruSmart devices. A total of 12 colours, all with satin finishes.

INNOVATION



EGO International was designed as a modern plate and has evolved in the EGO SMART International version, an innovative concept of SMART HOME.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

EGO SMART International plates

Painted technopolymer

SATIN WHITE



GW 16 022 S PW 2 modules

CLAY



GW 16 022 S CY 2 modules

NATURAL BEIGE



GW 16 022 S NB 2 modules

DARK SAND



GW 16 022 S DS 2 modules

SATIN BLACK



GW 16 022 S DB 2 modules

MAGNETIC GRAY ▲



GW 16 022 S GR 2 modules

LIGHT BRONZE ▲



GW 16 022 S BR 2 modules

STEEL ▲



GW 16 022 S ST 2 modules

SOFT COPPER ▲



GW 16 022 S CS 2 modules

GOLD ▲



GW 16 022 S SG 2 modules

COPPER ▲




GW 16 022 S CP 2 modules

BROWN SHADE ▲



GW 16 022 S BS 2 modules

Modularity



2 modules

▲ Metallic effect

For customized plates please contact our GEWISS Sales Organization

ChoruSmart

EGO SMART International plates

The EGO SMART plates go beyond pure aesthetics to become an element of interaction with the user and with other ChoruSmart system connected devices. Through RGB LED edge strips and a graphic display, the plates communicate operating statuses and alarms detected by other smart functions controlling your home. The EGO SMART and EGO plates, with their harmonious aesthetics, can be installed within the same system for a seamlessly designed look throughout the interior environment.



EGO SMART INTERNATIONAL PLATES

Painted technopolymer



GW 16 022 SPW

EGO SMART International - Satin white

Code	Description	For support codes	Pack Carton
GW 16 022 SPW	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SCY

EGO SMART International - Clay

Code	Description	For support codes	Pack Carton
GW 16 022 SCY	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SNB

EGO SMART International - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 022 SNB	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

ChoruSmart - Plates



GW 16 022 SDS

EGO SMART International - Dark sand

Code	Description	For support codes	Pack Carton
GW 16 022 SDS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SDB

EGO SMART International - Satin black

Code	Description	For support codes	Pack Carton
GW 16 022 SDB	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SGR

EGO SMART International - Magnetic gray

Code	Description	For support codes	Pack Carton
GW 16 022 SGR	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SBR

EGO SMART International - Light bronze

Code	Description	For support codes	Pack Carton
GW 16 022 SBR	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SST

EGO SMART International - Steel

Code	Description	For support codes	Pack Carton
GW 16 022 SST	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SCS

EGO SMART International - Soft copper

Code	Description	For support codes	Pack Carton
GW 16 022 SCS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

ChoruSmart - Plates



GW 16 022 SSG

EGO SMART International - Gold

Code	Description	For support codes	Pack Carton
GW 16 022 SSG	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SCP

EGO SMART International - Copper

Code	Description	For support codes	Pack Carton
GW 16 022 SCP	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SBS

EGO SMART International - Brown shade

Code	Description	For support codes	Pack Carton
GW 16 022 SBS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



ChoruSmart




Scan the QR Code and find out all the technical informations.

INNOVATION



The plate communicates with the user through simple and immediate visual feedback. The display is dynamic: text messages scroll and icons change shape to indicate the activation and operation of the commanded loads. The edges are illuminated with a coloured beam of light: each colour corresponds to a different signal.

SIMPLICITY



To recognise the associated function, each command can be linked to a different graphic. Lighting icons, messages and colours can be selected from the Home Gateway App with a wide variety of choices.

DOUBLED FUNCTIONS



The EGO SMART plates expands the functions managed from the control point. The manually activated proximity sensor enables the Shift mode on the plate, doubling the functions of the control units installed, without taking up additional space.

LUX International plates

Technopolymer

WHITE



GW 16 222 TB	2 modules
GW 16 223 TB	2+2 modules horiz.
GW 16 224 TB	2+2 modules vert.
GW 16 226 TB	2+2+2 modules horiz.
GW 16 227 TB	2+2+2 modules vert.
GW 16 228 TB	2+2+2+2 modules orizzont.
GW 16 229 TB	2+2+2+2 modules vert.

WHITE MONOCHROME



GW 16 222 YB	2 modules
GW 16 223 YB	2+2 modules horiz.
GW 16 224 YB	2+2 modules vert.
GW 16 226 YB	2+2+2 modules horiz.
GW 16 227 YB	2+2+2 modules vert.
GW 16 228 YB	2+2+2+2 modules orizzont.
GW 16 229 YB	2+2+2+2 modules vert.

TONER BLACK



GW 16 222 TN	2 modules
GW 16 223 TN	2+2 modules horiz.
GW 16 224 TN	2+2 modules vert.
GW 16 226 TN	2+2+2 modules horiz.
GW 16 227 TN	2+2+2 modules vert.
GW 16 228 TN	2+2+2+2 modules orizzont.
GW 16 229 TN	2+2+2+2 modules vert.

TONER BLACK LAVY



GW 16 222 YN	2 modules
GW 16 223 YN	2+2 modules horiz.
GW 16 224 YN	2+2 modules vert.
GW 16 226 YN	2+2+2 modules horiz.
GW 16 227 YN	2+2+2 modules vert.
GW 16 228 YN	2+2+2+2 modules orizzont.
GW 16 229 YN	2+2+2+2 modules vert.

Painted technopolymer

TITANIUM ▲



GW 16 222 VT	2 modules
GW 16 223 VT	2+2 modules horiz.
GW 16 224 VT	2+2 modules vert.
GW 16 226 VT	2+2+2 modules horiz.
GW 16 227 VT	2+2+2 modules vert.
GW 16 228 VT	2+2+2+2 modules horiz.
GW 16 229 VT	2+2+2+2 modules vert.

TITANIUM MONOCHROME



GW 16 222 YT	2 modules
GW 16 223 YT	2+2 modules horiz.
GW 16 224 YT	2+2 modules vert.
GW 16 226 YT	2+2+2 modules horiz.
GW 16 227 YT	2+2+2 modules vert.
GW 16 228 YT	2+2+2+2 modules horiz.
GW 16 229 YT	2+2+2+2 modules vert.

SLATE ▲



GW 16 222 VA	2 modules
GW 16 223 VA	2+2 modules horiz.
GW 16 224 VA	2+2 modules vert.
GW 16 226 VA	2+2+2 modules horiz.
GW 16 227 VA	2+2+2 modules vert.
GW 16 228 VA	2+2+2+2 modules horiz.
GW 16 229 VA	2+2+2+2 modules vert.

ABSOLUTE SLATE ▲



GW 16 222 YA	2 modules
GW 16 223 YA	2+2 modules horiz.
GW 16 224 YA	2+2 modules vert.
GW 16 226 YA	2+2+2 modules horiz.
GW 16 227 YA	2+2+2 modules vert.
GW 16 228 YA	2+2+2+2 modules horiz.
GW 16 229 YA	2+2+2+2 modules vert.

▲ Metallic effect

For customized plates please contact our GEWISS Sales Organization

Metal

SATIN WHITE MONOCHROME



GW 16 222 XW	2 modules
GW 16 223 XW	2+2 modules horiz.
GW 16 224 XW	2+2 modules vert.
GW 16 226 XW	2+2+2 modules horiz.
GW 16 227 XW	2+2+2 modules vert.
GW 16 228 XW	2+2+2+2 modules horiz.
GW 16 229 XW	2+2+2+2 modules vert.

NATURAL BEIGE MONOCHROME



GW 16 222 XL	2 modules
GW 16 223 XL	2+2 modules horiz.
GW 16 224 XL	2+2 modules vert.
GW 16 226 XL	2+2+2 modules horiz.
GW 16 227 XL	2+2+2 modules vert.
GW 16 228 XL	2+2+2+2 modules horiz.
GW 16 229 XL	2+2+2+2 modules vert.

SATIN BLACK MONOCHROME



GW 16 222 XM	2 modules
GW 16 223 XM	2+2 modules horiz.
GW 16 224 XM	2+2 modules vert.
GW 16 226 XM	2+2+2 modules horiz.
GW 16 227 XM	2+2+2 modules vert.
GW 16 228 XM	2+2+2+2 modules horiz.
GW 16 229 XM	2+2+2+2 modules vert.

BRUSHED ALUMINIUM



GW 16 222 XS	2 modules
GW 16 223 XS	2+2 modules horiz.
GW 16 224 XS	2+2 modules vert.
GW 16 226 XS	2+2+2 modules horiz.
GW 16 227 XS	2+2+2 modules vert.
GW 16 228 XS	2+2+2+2 modules horiz.
GW 16 229 XS	2+2+2+2 modules vert.

BRUSHED ALUMINIUM LAVY



GW 16 222 WS	2 modules
GW 16 223 WS	2+2 modules horiz.
GW 16 224 WS	2+2 modules vert.
GW 16 226 WS	2+2+2 modules horiz.
GW 16 227 WS	2+2+2 modules vert.
GW 16 228 WS	2+2+2+2 modules horiz.
GW 16 229 WS	2+2+2+2 modules vert.

GOLD



GW 16 222 XG	2 modules
GW 16 223 XG	2+2 modules horiz.
GW 16 224 XG	2+2 modules vert.
GW 16 226 XG	2+2+2 modules horiz.
GW 16 227 XG	2+2+2 modules vert.
GW 16 228 XG	2+2+2+2 modules horiz.
GW 16 229 XG	2+2+2+2 modules vert.


ANTIQUE BRASS



GW 16 222 XQ	2 modules
GW 16 223 XQ	2+2 modules horiz.
GW 16 224 XQ	2+2 modules vert.
GW 16 226 XQ	2+2+2 modules horiz.
GW 16 227 XQ	2+2+2 modules vert.
GW 16 228 XQ	2+2+2+2 modules horiz.
GW 16 229 XQ	2+2+2+2 modules vert.

Modularity

Centre distance 71 mm



ChoruSmart

LUX International plates

LUX plates, with their modern, refined lines, marry the high-tech spirit of modernity with the refined and elegant taste of tradition. Glass and metal versions are added to the classic technopolymer plates. With monochrome variants of the LUX plates, uniformity of colour becomes the distinctive character of each ChoruSmart lighting device.



LUX INTERNATIONAL PLATES

Technopolymer



GW 16 222 TB

LUX International - White

Code	Description	Type	Pack Carton
GW 16 222 TB	2 modules	-	12
GW 16 223 TB	2+2 modules	Horizontal	6
GW 16 224 TB	2+2 modules	Vertical	6
GW 16 226 TB	2+2+2 modules	Horizontal	1
GW 16 227 TB	2+2+2 modules	Vertical	1
GW 16 228 TB	2+2+2+2 modules	Horizontal	1
GW 16 229 TB	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: inner frame chromed. Centre distance 71 mm.



GW 16 222 YB

Lux International - Monochrome white

Code	Description	Type	Pack Carton
GW 16 222 YB	2 modules	-	12
GW 16 223 YB	2+2 modules	Horizontal	6
GW 16 224 YB	2+2 modules	Vertical	6
GW 16 226 YB	2+2+2 modules	Horizontal	1
GW 16 227 YB	2+2+2 modules	Vertical	1
GW 16 228 YB	2+2+2+2 modules	Horizontal	1
GW 16 229 YB	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: inner frame in the same white colour as the plate. Glossy finish. Centre distance 71 mm.



GW 16 222 TN

LUX International - Toner black

Code	Description	Type	Pack Carton
GW 16 222 TN	2 modules	-	12
GW 16 223 TN	2+2 modules	Horizontal	6
GW 16 224 TN	2+2 modules	Vertical	6
GW 16 226 TN	2+2+2 modules	Horizontal	1
GW 16 227 TN	2+2+2 modules	Vertical	1
GW 16 228 TN	2+2+2+2 modules	Horizontal	1
GW 16 229 TN	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: inner frame chromed. Centre distance 71 mm.



GW 16 222 YN

LUX International - Toner black lavy

Code	Description	Type	Pack Carton
GW 16 222 YN	2 modules	-	12
GW 16 223 YN	2+2 modules	Horizontal	6
GW 16 224 YN	2+2 modules	Vertical	6
GW 16 226 YN	2+2+2 modules	Horizontal	1
GW 16 227 YN	2+2+2 modules	Vertical	1
GW 16 228 YN	2+2+2+2 modules	Horizontal	1
GW 16 229 YN	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish.
NOTES: inner frame in the same black colour as the plate, matt finish. Centre distance 71 mm.

Painted technopolymer



GW 16 222 VT

LUX International - Titanium

Code	Description	Type	Pack Carton
GW 16 222 VT	2 modules	-	12
GW 16 223 VT	2+2 modules	Horizontal	6
GW 16 224 VT	2+2 modules	Vertical	6
GW 16 226 VT	2+2+2 modules	Horizontal	1
GW 16 227 VT	2+2+2 modules	Vertical	1
GW 16 228 VT	2+2+2+2 modules	Horizontal	1
GW 16 229 VT	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame chromed. Centre distance 71 mm.



GW 16 222 YT

LUX International - Monochrome titanium

Code	Description	Type	Pack Carton
GW 16 222 YT	2 modules	-	12
GW 16 223 YT	2+2 modules	Horizontal	6
GW 16 224 YT	2+2 modules	Vertical	6
GW 16 226 YT	2+2+2 modules	Horizontal	1
GW 16 227 YT	2+2+2 modules	Vertical	1
GW 16 228 YT	2+2+2+2 modules	Horizontal	1
GW 16 229 YT	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame in the same titanium colour as the plate, glossy finish. Centre distance 71 mm.



GW 16 222 VA

LUX International - Slate

Code	Description	Type	Centre distance	Pack Carton
GW 16 222 VA	2 modules	-	-	12
GW 16 223 VA	2+2 modules	Horizontal	71 mm	6
GW 16 224 VA	2+2 modules	Vertical	71 mm	6
GW 16 226 VA	2+2+2 modules	Horizontal	71 mm	1
GW 16 227 VA	2+2+2 modules	Vertical	71 mm	1
GW 16 228 VA	2+2+2+2 modules	Horizontal	71 mm	1
GW 16 229 VA	2+2+2+2 modules	Vertical	71 mm	1

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame chromed. Centre distance 71 mm.



GW 16 222 YA

LUX International - Absolute slate

Code	Description	Type	Pack Carton
GW 16 222 YA	2 modules	-	12
GW 16 223 YA	2+2 modules	Horizontal	6
GW 16 224 YA	2+2 modules	Vertical	6
GW 16 226 YA	2+2+2 modules	Horizontal	1
GW 16 227 YA	2+2+2 modules	Vertical	1
GW 16 228 YA	2+2+2+2 modules	Horizontal	1
GW 16 229 YA	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame in the same slate colour as the plate, glossy finish. Centre distance 71 mm.

ChoruSmart - Plates

Metal



GW 16 222 XW

LUX International - Monochrome satin white

Code	Description	Type	Pack Carton
GW 16 222 XW	2 modules	-	1
GW 16 223 XW	2+2 modules	Horizontal	1
GW 16 224 XW	2+2 modules	Vertical	1
GW 16 226 XW	2+2+2 modules	Horizontal	1
GW 16 227 XW	2+2+2 modules	Vertical	1
GW 16 228 XW	2+2+2+2 modules	Horizontal	1
GW 16 229 XW	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in same white colour as the plate, matt finish. Centre distance 71 mm.



GW 16 222 XL

LUX International - Monochrome natural beige

Code	Description	Type	Pack Carton
GW 16 222 XL	2 modules	-	1
GW 16 223 XL	2+2 modules	Horizontal	1
GW 16 224 XL	2+2 modules	Vertical	1
GW 16 226 XL	2+2+2 modules	Horizontal	1
GW 16 227 XL	2+2+2 modules	Vertical	1
GW 16 228 XL	2+2+2+2 modules	Horizontal	1
GW 16 229 XL	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in same natural beige colour as the plate, matt finish. Centre distance 71 mm.



GW 16 222 XM

LUX International - Monochrome satin black

Code	Description	Type	Pack Carton
GW 16 222 XM	2 modules	-	1
GW 16 223 XM	2+2 modules	Horizontal	1
GW 16 224 XM	2+2 modules	Vertical	1
GW 16 226 XM	2+2+2 modules	Horizontal	1
GW 16 227 XM	2+2+2 modules	Vertical	1
GW 16 228 XM	2+2+2+2 modules	Horizontal	1
GW 16 229 XM	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in same black colour as the plate, matt finish. Centre distance 71 mm.



GW 16 222 XS

LUX International - Brushed aluminium

Code	Description	Type	Pack Carton
GW 16 222 XS	2 modules	-	1
GW 16 223 XS	2+2 modules	Horizontal	1
GW 16 224 XS	2+2 modules	Vertical	1
GW 16 226 XS	2+2+2 modules	Horizontal	1
GW 16 227 XS	2+2+2 modules	Vertical	1
GW 16 228 XS	2+2+2+2 modules	Horizontal	1
GW 16 229 XS	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: inner frame in light bronze colour, matt finish. Centre distance 71 mm.



GW 16 222 WS

LUX International - Brushed aluminium lavy

Code	Description	Type	Pack Carton
GW 16 222 WS	2 modules	-	1
GW 16 223 WS	2+2 modules	Horizontal	1
GW 16 224 WS	2+2 modules	Vertical	1
GW 16 226 WS	2+2+2 modules	Horizontal	1
GW 16 227 WS	2+2+2 modules	Vertical	1
GW 16 228 WS	2+2+2+2 modules	Horizontal	1
GW 16 229 WS	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.
NOTES: inner frame in black colour, matt finish. Centre distance 71 mm.




GW 16 222 XG

LUX International - Gold

Code	Description	Type	Pack Carton
GW 16 222 XG	2 modules	-	1
GW 16 223 XG	2+2 modules	Horizontal	1
GW 16 224 XG	2+2 modules	Vertical	1
GW 16 226 XG	2+2+2 modules	Horizontal	1
GW 16 227 XG	2+2+2 modules	Vertical	1
GW 16 228 XG	2+2+2+2 modules	Horizontal	1
GW 16 229 XG	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in the same gold colour as the plate, matt finish. Centre distance 71 mm.

ChoruSmart - Plates




GW 16 222 XQ

LUX International - Antique brass

Code	Description	Type	Pack Carton
GW 16 222 XQ	2 modules	-	1
GW 16 223 XQ	2+2 modules	Horizontal	1
GW 16 224 XQ	2+2 modules	Vertical	1
GW 16 226 XQ	2+2+2 modules	Horizontal	1
GW 16 227 XQ	2+2+2 modules	Vertical	1
GW 16 228 XQ	2+2+2+2 modules	Horizontal	1
GW 16 229 XQ	2+2+2+2 modules	Vertical	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in dark bronze colour, matt finish. Centre distance 71 mm.



ChoruSmart



Scan the QR Code and find out all the technical informations.

CONTEMPORARY STYLE



The LUX International plate, with its modern shapes, is the perfect blend of modernity and the elegant aesthetics of tradition.

MATERIALS AND FINISHES



Classic and elegantly designed, LUX International plates are available in the metal and technopolymer versions, in a variety of colours and in 2 finishes: glossy and satin, to satisfy every aesthetic and installation need.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

ONE plates

Technopolymer

WHITE



GW 16 101 TB	1 module
GW 16 102 TB	2 modules
GW 16 103 TB	3 modules
GW 16 104 TB	4 modules
GW 16 106 TB	6 modules
GW 16 109 TB	6 modules large
GW 16 108 TB	4+4 modules
GW 16 112 TB	6+6 modules

TONER BLACK



GW 16 101 TN	1 module
GW 16 102 TN	2 modules
GW 16 103 TN	3 modules
GW 16 104 TN	4 modules
GW 16 106 TN	6 modules

IVORY



GW 16 101 TI	1 module
GW 16 102 TI	2 modules
GW 16 103 TI	3 modules
GW 16 104 TI	4 modules
GW 16 106 TI	6 modules

HEMP



GW 16 101 TC	1 module
GW 16 102 TC	2 modules
GW 16 103 TC	3 modules
GW 16 104 TC	4 modules
GW 16 106 TC	6 modules

Painted technopolymer

SATIN WHITE




GW 16 101 VW	1 module
GW 16 102 VW	2 modules
GW 16 103 VW	3 modules
GW 16 104 VW	4 modules
GW 16 106 VW	6 modules
GW 16 108 VW	4+4 modules
GW 16 112 VW	6+6 modules

NATURAL BEIGE



GW 16 101 VL	1 module
GW 16 102 VL	2 modules
GW 16 103 VL	3 modules
GW 16 104 VL	4 modules
GW 16 106 VL	6 modules
GW 16 108 VL	4+4 modules
GW 16 112 VL	6+6 modules

SATIN BLACK



GW 16 101 VN	1 module
GW 16 102 VN	2 modules
GW 16 103 VN	3 modules
GW 16 104 VN	4 modules
GW 16 106 VN	6 modules
GW 16 108 VN	4+4 modules
GW 16 112 VN	6+6 modules

TITANIUM ▲



GW 16 101 VT	1 module
GW 16 102 VT	2 modules
GW 16 103 VT	3 modules
GW 16 104 VT	4 modules
GW 16 106 VT	6 modules
GW 16 108 VT	4+4 modules
GW 16 112 VT	6+6 modules

TUSCAN RED



GW 16 101 VD	1 module
GW 16 102 VD	2 modules
GW 16 103 VD	3 modules
GW 16 104 VD	4 modules
GW 16 106 VD	6 modules

TEAL



GW 16 101 VZ	1 module
GW 16 102 VZ	2 modules
GW 16 103 VZ	3 modules
GW 16 104 VZ	4 modules
GW 16 106 VZ	6 modules

SOFT COPPER ▲




GW 16 101 VX	1 module
GW 16 102 VX	2 modules
GW 16 103 VX	3 modules
GW 16 104 VX	4 modules
GW 16 106 VX	6 modules

GOLD ▲



GW 16 101 VO	1 module
GW 16 102 VO	2 modules
GW 16 103 VO	3 modules
GW 16 104 VO	4 modules
GW 16 106 VO	6 modules

Modularity



▲ Metallic effect
(*) White
(**) White, Satin white, Natural beige, Satin black and Titanium

ChoruSmart

ONE plates

An informal appearance and classic shapes: the ONE line of plates in the ChoruSmart system is dedicated to all those who desire a home interior finished with a minimal simplicity. ONE's restrained and discreet design enhances any environment, bringing harmony and aesthetic coherence to all rooms. Available in a wide variety of colour tones, ONE can be fitted in any shade to leave room for the imagination.



ONE ITALIAN STANDARD PLATES

Technopolymer

ONE - White



GW 16 103 TB

Code	Description	Configuration	For support codes	Pack Carton
GW 16 101 TB	1 module	-	GW16802, GW16803, GW16803N	96
GW 16 102 TB	2 modules	-	GW16802, GW16803, GW16803N	96
GW 16 103 TB	3 modules	-	GW16803, GW16803N	96
GW 16 104 TB	4 modules	-	GW16804, GW16804N	12
GW 16 106 TB	6 modules	-	GW16806	12
GW 16 109 TB	6 modules	Large	GW16806	6
GW 16 108 TB	4+4 modules	Overlapping	GW16808	6
GW 16 112 TB	6+6 modules	Overlapping	GW16812	6

CHARACTERISTICS: glossy finish. GW16109TB total width 202 mm.

ONE - Toner black



GW 16 103 TN

Code	Description	For support codes	Pack Carton
GW 16 101 TN	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 TN	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 TN	3 modules	GW16803, GW16803N	24
GW 16 104 TN	4 modules	GW16804, GW16804N	12
GW 16 106 TN	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

ONE - Ivory



GW 16 103 TI

Code	Description	For support codes	Pack Carton
GW 16 101 TI	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 TI	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 TI	3 modules	GW16803, GW16803N	24
GW 16 104 TI	4 modules	GW16804, GW16804N	12
GW 16 106 TI	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

ONE - Hemp



GW 16 103 TC

Code	Description	For support codes	Pack Carton
GW 16 101 TC	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 TC	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 TC	3 modules	GW16803, GW16803N	24
GW 16 104 TC	4 modules	GW16804, GW16804N	12
GW 16 106 TC	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

ChoruSmart - Plates

Painted technopolymer

ONE - Satin white



GW 16 103 VW

Code	Description	Configuration	For support codes	Pack Carton
GW 16 101 VW	1 module	-	GW16802, GW16803, GW16803N	96
GW 16 102 VW	2 modules	-	GW16802, GW16803, GW16803N	96
GW 16 103 VW	3 modules	-	GW16803, GW16803N	96
GW 16 104 VW	4 modules	-	GW16804, GW16804N	12
GW 16 106 VW	6 modules	-	GW16806	12
GW 16 108 VW	4+4 modules	Overlapping	GW16808	6
GW 16 112 VW	6+6 modules	Overlapping	GW16812	6

CHARACTERISTICS: matt finish.

ONE - Natural beige




GW 16 103 VL

Code	Description	Configuration	For support codes	Pack Carton
GW 16 101 VL	1 module	-	GW16802, GW16803, GW16803N	12
GW 16 102 VL	2 modules	-	GW16802, GW16803, GW16803N	12
GW 16 103 VL	3 modules	-	GW16803, GW16803N	24
GW 16 104 VL	4 modules	-	GW16804, GW16804N	12
GW 16 106 VL	6 modules	-	GW16806	6
GW 16 108 VL	4+4 modules	Overlapping	GW16808	6
GW 16 112 VL	6+6 modules	Overlapping	GW16812	6

CHARACTERISTICS: matt finish.

ONE - Satin black



GW 16 103 VN

Code	Description	Configuration	For support codes	Pack Carton
GW 16 101 VN	1 module	-	GW16802, GW16803, GW16803N	12
GW 16 102 VN	2 modules	-	GW16802, GW16803, GW16803N	12
GW 16 103 VN	3 modules	-	GW16803, GW16803N	24
GW 16 104 VN	4 modules	-	GW16804, GW16804N	12
GW 16 106 VN	6 modules	-	GW16806	6
GW 16 108 VN	4+4 modules	Overlapping	GW16808	6
GW 16 112 VN	6+6 modules	Overlapping	GW16812	6

CHARACTERISTICS: matt finish.

ONE - Titanium



GW 16 103 VT

Code	Description	Configuration	For support codes	Pack Carton
GW 16 101 VT	1 module	-	GW16802, GW16803, GW16803N	12
GW 16 102 VT	2 modules	-	GW16802, GW16803, GW16803N	12
GW 16 103 VT	3 modules	-	GW16803, GW16803N	24
GW 16 104 VT	4 modules	-	GW16804, GW16804N	12
GW 16 106 VT	6 modules	-	GW16806	6
GW 16 108 VT	4+4 modules	Overlapping	GW16808	6
GW 16 112 VT	6+6 modules	Overlapping	GW16812	6

CHARACTERISTICS: glossy finish, metallic effect.

ONE - Tuscan red



GW 16 103 VD

Code	Description	For support codes	Pack Carton
GW 16 101 VD	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 VD	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 VD	3 modules	GW16803, GW16803N	24
GW 16 104 VD	4 modules	GW16804, GW16804N	12
GW 16 106 VD	6 modules	GW16806	6

CHARACTERISTICS: matt finish.

ONE - Teal



GW 16 103 VZ

Code	Description	For support codes	Pack Carton
GW 16 101 VZ	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 VZ	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 VZ	3 modules	GW16803, GW16803N	24
GW 16 104 VZ	4 modules	GW16804, GW16804N	12
GW 16 106 VZ	6 modules	GW16806	6

CHARACTERISTICS: matt finish.

ChoruSmart - Plates



GW 16 103 VX

ONE - Soft copper

Code	Description	For support codes	Pack Carton
GW 16 101 VX	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 VX	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 VX	3 modules	GW16803, GW16803N	12
GW 16 104 VX	4 modules	GW16804, GW16804N	12
GW 16 106 VX	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.



GW 16 103 VO

ONE - Gold

Code	Description	For support codes	Pack Carton
GW 16 101 VO	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 VO	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 VO	3 modules	GW16803, GW16803N	12
GW 16 104 VO	4 modules	GW16804, GW16804N	12
GW 16 106 VO	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.



ChoruSmart



Scan the QR Code and find out all the technical informations.

REFINED DESIGN



Minimal in shape, classic in style: ONE plates enhance any room, bringing harmony and beauty to every corner of the house.

FINISHES



The ONE plate, with its minimal appearance, is available in various colours and in 2 finishes: glossy and satin, for every need.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

GEO plates

Technopolymer

WHITE

GW 16 401 TB	1 module
GW 16 402 TB	2 modules
GW 16 403 TB	3 modules
GW 16 404 TB	4 modules
GW 16 406 TB	6 modules

TONER BLACK



GW 16 401 TN	1 module
GW 16 402 TN	2 modules
GW 16 403 TN	3 modules
GW 16 404 TN	4 modules
GW 16 406 TN	6 modules

IVORY

GW 16 401 TI	1 module
GW 16 402 TI	2 modules
GW 16 403 TI	3 modules
GW 16 404 TI	4 modules
GW 16 406 TI	6 modules

HEMP



GW 16 401 TC	1 module
GW 16 402 TC	2 modules
GW 16 403 TC	3 modules
GW 16 404 TC	4 modules
GW 16 406 TC	6 modules

Painted technopolymer

SATIN WHITE

GW 16 401 VW	1 module
GW 16 402 VW	2 modules
GW 16 403 VW	3 modules
GW 16 404 VW	4 modules
GW 16 406 VW	6 modules

NATURAL BEIGE



GW 16 401 VL	1 module
GW 16 402 VL	2 modules
GW 16 403 VL	3 modules
GW 16 404 VL	4 modules
GW 16 406 VL	6 modules

SATIN BLACK



GW 16 401 VN	1 module
GW 16 402 VN	2 modules
GW 16 403 VN	3 modules
GW 16 404 VN	4 modules
GW 16 406 VN	6 modules

TITANIUM ▲



GW 16 401 VT	1 module
GW 16 402 VT	2 modules
GW 16 403 VT	3 modules
GW 16 404 VT	4 modules
GW 16 406 VT	6 modules

TUSCAN RED



GW 16 401 VD	1 module
GW 16 402 VD	2 modules
GW 16 403 VD	3 modules
GW 16 404 VD	4 modules
GW 16 406 VD	6 modules

TEAL



GW 16 401 VZ	1 module
GW 16 402 VZ	2 modules
GW 16 403 VZ	3 modules
GW 16 404 VZ	4 modules
GW 16 406 VZ	6 modules

SOFT COPPER ▲




GW 16 401 VX	1 module
GW 16 402 VX	2 modules
GW 16 403 VX	3 modules
GW 16 404 VX	4 modules
GW 16 406 VX	6 modules

GOLD ▲



GW 16 401 VO	1 module
GW 16 402 VO	2 modules
GW 16 403 VO	3 modules
GW 16 404 VO	4 modules
GW 16 406 VO	6 modules

Modularity



1 module | 2 modules | 3 modules | 4 modules | 6 modules

▲ Metallic effect

ChoruSmart

GEO plates

The GEO plate with clean, regular lines fits perfectly into any environment with its simplicity and style. The materials and colours contribute to creating the right harmony that stands the test of time. Made from technopolymer, GEO resists the impact and stresses of everyday use. The different colours and the simple and light shapes make GEO a young and informal furnishing element that conveys a minimalist style in any space.



GEO ITALIAN STANDARD PLATES

Technopolymer

GEO - White

GW 16 403 TB

Code	Description	For support codes	Pack Carton
GW 16 401 TB	1 module	GW16802, GW16803, GW16803N	96
GW 16 402 TB	2 modules	GW16802, GW16803, GW16803N	96
GW 16 403 TB	3 modules	GW16803, GW16803N	96
GW 16 404 TB	4 modules	GW16804, GW16804N	12
GW 16 406 TB	6 modules	GW16806	12

CHARACTERISTICS: glossy finish.

GEO - Toner black



GW 16 403 TN

Code	Description	For support codes	Pack Carton
GW 16 401 TN	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 TN	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 TN	3 modules	GW16803, GW16803N	24
GW 16 404 TN	4 modules	GW16804, GW16804N	12
GW 16 406 TN	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

GEO - Ivory

GW 16 403 TI

Code	Description	For support codes	Pack Carton
GW 16 401 TI	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 TI	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 TI	3 modules	GW16803, GW16803N	24
GW 16 404 TI	4 modules	GW16804, GW16804N	12
GW 16 406 TI	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

GEO - Hemp



GW 16 403 TC

Code	Description	For support codes	Pack Carton
GW 16 401 TC	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 TC	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 TC	3 modules	GW16803, GW16803N	24
GW 16 404 TC	4 modules	GW16804, GW16804N	12
GW 16 406 TC	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.

ChoruSmart - Plates

Painted technopolymer

GW 16 403 VW

GEO - Satin white

Code	Description	For support codes	Pack Carton
GW 16 401 VW	1 module	GW16802, GW16803, GW16803N	96
GW 16 402 VW	2 modules	GW16802, GW16803, GW16803N	96
GW 16 403 VW	3 modules	GW16803, GW16803N	96
GW 16 404 VW	4 modules	GW16804, GW16804N	12
GW 16 406 VW	6 modules	GW16806	12

CHARACTERISTICS: matt finish.



GW 16 403 VL

GEO - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 401 VL	1 module	GW16802, GW16803, GW16803N	12
GW 16 402 VL	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VL	3 modules	GW16803, GW16803N	12
GW 16 404 VL	4 modules	GW16804, GW16804N	12
GW 16 406 VL	6 modules	GW16806	6

CHARACTERISTICS: matt finish.



GW 16 403 VN

GEO - Satin black

Code	Description	For support codes	Pack Carton
GW 16 401 VN	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 VN	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VN	3 modules	GW16803, GW16803N	24
GW 16 404 VN	4 modules	GW16804, GW16804N	12
GW 16 406 VN	6 modules	GW16806	6

CHARACTERISTICS: matt finish.

GEO - Titanium



GW 16 403 VT

Code	Description	For support codes	Pack Carton
GW 16 401 VT	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 VT	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VT	3 modules	GW16803, GW16803N	24
GW 16 404 VT	4 modules	GW16804, GW16804N	12
GW 16 406 VT	6 modules	GW16806	6

CHARACTERISTICS: glossy finish, metallic effect.

GEO - Tuscan red



GW 16 403 VD

Code	Description	For support codes	Pack Carton
GW 16 401 VD	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 VD	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VD	3 modules	GW16803, GW16803N	24
GW 16 404 VD	4 modules	GW16804, GW16804N	12
GW 16 406 VD	6 modules	GW16806	6

CHARACTERISTICS: matt finish.

GEO - Teal



GW 16 403 VZ

Code	Description	For support codes	Pack Carton
GW 16 401 VZ	1 module	GW16802, GW16803, GW16803N	24
GW 16 402 VZ	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VZ	3 modules	GW16803, GW16803N	24
GW 16 404 VZ	4 modules	GW16804, GW16804N	12
GW 16 406 VZ	6 modules	GW16806	6

CHARACTERISTICS: matt finish.

ChoruSmart - Plates



GW 16 403 VX

GEO - Soft copper

Code	Description	For support codes	Pack Carton
GW 16 401 VX	1 module	GW16802, GW16803, GW16803N	12
GW 16 402 VX	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VX	3 modules	GW16803, GW16803N	12
GW 16 404 VX	4 modules	GW16804, GW16804N	12
GW 16 406 VX	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.



GW 16 403 VO

GEO - Gold

Code	Description	For support codes	Pack Carton
GW 16 401 VO	1 module	GW16802, GW16803, GW16803N	12
GW 16 402 VO	2 modules	GW16802, GW16803, GW16803N	12
GW 16 403 VO	3 modules	GW16803, GW16803N	12
GW 16 404 VO	4 modules	GW16804, GW16804N	12
GW 16 406 VO	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.



ChoruSmart



Scan the QR Code and find out all the technical informations.

MINIMAL DESIGN



The colours and simple, light shapes make GEO a youthful and informal furnishing item that expresses a minimalist style wherever it is placed.

FINISHES



The GEO Plate, simple and youthful, is available in various colours and in 2 finishes: glossy and satin, for every need.

HIGHLY CUSTOMISABLE



The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

EGO plates

Painted technopolymer

SATIN WHITE

GW 16 001 PW	1 module
GW 16 002 PW	2 modules
GW 16 003 PW	3 modules
GW 16 004 PW	4 modules
GW 16 007 PW	7 modules

CLAY



GW 16 001 CY	1 module
GW 16 002 CY	2 modules
GW 16 003 CY	3 modules
GW 16 004 CY	4 modules
GW 16 007 CY	7 modules

NATURAL BEIGE



GW 16 001 NB	1 module
GW 16 002 NB	2 modules
GW 16 003 NB	3 modules
GW 16 004 NB	4 modules
GW 16 007 NB	7 modules

DARK SAND




GW 16 001 DS	1 module
GW 16 002 DS	2 modules
GW 16 003 DS	3 modules
GW 16 004 DS	4 modules
GW 16 007 DS	7 modules

SATIN BLACK



GW 16 001 DB	1 module
GW 16 002 DB	2 modules
GW 16 003 DB	3 modules
GW 16 004 DB	4 modules
GW 16 007 DB	7 modules

MAGNETIC GRAY ▲



GW 16 001 GR	1 module
GW 16 002 GR	2 modules
GW 16 003 GR	3 modules
GW 16 004 GR	4 modules
GW 16 007 GR	7 modules

LIGHT BRONZE ▲



GW 16 001 BR	1 module
GW 16 002 BR	2 modules
GW 16 003 BR	3 modules
GW 16 004 BR	4 modules
GW 16 007 BR	7 modules

STEEL ▲



GW 16 001 ST	1 module
GW 16 002 ST	2 modules
GW 16 003 ST	3 modules
GW 16 004 ST	4 modules
GW 16 007 ST	7 modules

SOFT COPPER ▲



GW 16 001 CS	1 module
GW 16 002 CS	2 modules
GW 16 003 CS	3 modules
GW 16 004 CS	4 modules
GW 16 007 CS	7 modules

GOLD ▲



GW 16 001 SG	1 module
GW 16 002 SG	2 modules
GW 16 003 SG	3 modules
GW 16 004 SG	4 modules
GW 16 007 SG	7 modules

COPPER ▲




GW 16 001 CP	1 module
GW 16 002 CP	2 modules
GW 16 003 CP	3 modules
GW 16 004 CP	4 modules
GW 16 007 CP	7 modules

BROWN SHADE ▲



GW 16 001 BS	1 module
GW 16 002 BS	2 modules
GW 16 003 BS	3 modules
GW 16 004 BS	4 modules
GW 16 007 BS	7 modules

Modularity




1 module | 2 modules | 3 modules | 4 modules | 7 modules

▲ Metallic effect

ChoruSmart

EGO plates

With their clean, compact lines, EGO plates make the right impression. Modern shapes with slightly curved surfaces that taper towards the edges convey balance and simplicity. The opalescent profiles inside the plate, in aesthetic continuity with the EGO SMART versions, add a subtle element of unique identity. Every detail is designed to ensure appeal and personality.



EGO PLATES

Painted technopolymer

EGO - Satin white

GW 16 003 PW

Code	Description	For support codes	Pack Carton
GW 16 001 PW	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 PW	2 modules	GW16802, GW16803, GW16803N	96
GW 16 003 PW	3 modules	GW16803, GW16803N	96
GW 16 004 PW	4 modules	GW16804, GW16804N	12
GW 16 007 PW	7 modules	GW16807N	6

CHARACTERISTICS: matt finish.

EGO - Clay



GW 16 003 CY

Code	Description	For support codes	Pack Carton
GW 16 001 CY	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 CY	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 CY	3 modules	GW16803, GW16803N	24
GW 16 004 CY	4 modules	GW16804, GW16804N	12
GW 16 007 CY	7 modules	GW16807N	6

CHARACTERISTICS: matt finish.

EGO - Natural beige



GW 16 003 NB

Code	Description	For support codes	Pack Carton
GW 16 001 NB	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 NB	2 modules	GW16802, GW16803, GW16803N	96
GW 16 003 NB	3 modules	GW16803, GW16803N	96
GW 16 004 NB	4 modules	GW16804, GW16804N	12
GW 16 007 NB	7 modules	GW16807N	6

CHARACTERISTICS: matt finish.

EGO - Dark sand



GW 16 003 DS

Code	Description	For support codes	Pack Carton
GW 16 001 DS	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 DS	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 DS	3 modules	GW16803, GW16803N	24
GW 16 004 DS	4 modules	GW16804, GW16804N	12
GW 16 007 DS	7 modules	GW16807N	6

CHARACTERISTICS: matt finish.

ChoruSmart - Plates




GW 16 003 DB

EGO - Satin Black

Code	Description	For support codes	Pack Carton
GW 16 001 DB	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 DB	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 DB	3 modules	GW16803, GW16803N	24
GW 16 004 DB	4 modules	GW16804, GW16804N	12
GW 16 007 DB	7 modules	GW16807N	6

CHARACTERISTICS: matt finish.



GW 16 003 GR

EGO - Magnetic gray

Code	Description	For support codes	Pack Carton
GW 16 001 GR	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 GR	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 GR	3 modules	GW16803, GW16803N	24
GW 16 004 GR	4 modules	GW16804, GW16804N	12
GW 16 007 GR	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.



GW 16 003 BR

EGO - Light bronze

Code	Description	For support codes	Pack Carton
GW 16 001 BR	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 BR	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 BR	3 modules	GW16803, GW16803N	12
GW 16 004 BR	4 modules	GW16804, GW16804N	12
GW 16 007 BR	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.

EGO - Steel




GW 16 003 ST

Code	Description	For support codes	Pack Carton
GW 16 001 ST	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 ST	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 ST	3 modules	GW16803, GW16803N	12
GW 16 004 ST	4 modules	GW16804, GW16804N	12
GW 16 007 ST	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.

EGO - Soft copper



GW 16 003 CS

Code	Description	For support codes	Pack Carton
GW 16 001 CS	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 CS	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 CS	3 modules	GW16803, GW16803N	12
GW 16 004 CS	4 modules	GW16804, GW16804N	12
GW 16 007 CS	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.

EGO - Gold




GW 16 003 SG

Code	Description	For support codes	Pack Carton
GW 16 001 SG	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 SG	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 SG	3 modules	GW16803, GW16803N	12
GW 16 004 SG	4 modules	GW16804, GW16804N	12
GW 16 007 SG	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.

ChoruSmart - Plates



GW 16 003 CP

EGO - Copper

Code	Description	For support codes	Pack Carton
GW 16 001 CP	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 CP	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 CP	3 modules	GW16803, GW16803N	12
GW 16 004 CP	4 modules	GW16804, GW16804N	12
GW 16 007 CP	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.



GW 16 003 BS


EGO - Brown shade

Code	Description	For support codes	Pack Carton
GW 16 001 BS	1 module	GW16802, GW16803, GW16803N	12
GW 16 002 BS	2 modules	GW16802, GW16803, GW16803N	12
GW 16 003 BS	3 modules	GW16803, GW16803N	12
GW 16 004 BS	4 modules	GW16804, GW16804N	12
GW 16 007 BS	7 modules	GW16807N	6

CHARACTERISTICS: matt finish, metallic effect.



ChoruSmart



Scan the QR Code and find out all the technical informations.

PRECIOUS FINISHES



Three thematic lines of plates for a perfect match with ChoruSmart devices. A total of 12 colors, all with a satin finish.

INNOVATION



EGO was designed as a modern plate and has evolved in the EGO SMART version, an innovative concept of SMART HOME.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

EGO SMART plates

Painted technopolymer

SATIN WHITE

GW 16 003 S PW 3 modules
GW 16 004 S PW 4 modules

CLAY



GW 16 003 S CY 3 modules
GW 16 004 S CY 4 modules

NATURAL BEIGE



GW 16 003 S NB 3 modules
GW 16 004 S NB 4 modules

DARK SAND



GW 16 003 S DS 3 modules
GW 16 004 S DS 4 modules

SATIN BLACK



GW 16 003 S DB 3 modules
GW 16 004 S DB 4 modules

MAGNETIC GRAY ▲



GW 16 003 S GR 3 modules
GW 16 004 S GR 4 modules

LIGHT BRONZE ▲



GW 16 003 S BR 3 modules
GW 16 004 S BR 4 modules

STEEL ▲



GW 16 003 S ST 3 modules
GW 16 004 S ST 4 modules

SOFT COPPER ▲



GW 16 003 S CS 3 modules
GW 16 004 S CS 4 modules

GOLD ▲



GW 16 003 S SG 3 modules
GW 16 004 S SG 4 modules

COPPER ▲




GW 16 003 S CP 3 modules
GW 16 004 S CP 4 modules

BROWN SHADE ▲




GW 16 003 S BS 3 modules
GW 16 004 S BS 4 modules

Modularity



3 modules



4 modules

▲ Metallic effect

ChoruSmart

EGO SMART plates

The EGO SMART plates go beyond pure aesthetics to become an element of interaction with the user and with other ChoruSmart system connected devices. Through RGB LED edge strips and a graphic display, the plates communicate operating statuses and alarms detected by other smart functions controlling your home. The EGO SMART and EGO plates, with their harmonious aesthetics, can be installed within the same system for a seamlessly designed look throughout the interior environment.



EGO SMART PLATES

Painted technopolymer

EGO SMART - Satin white



GW 16 003 SPW

Code	Description	For support codes	Pack Carton
GW 16 003 SPW	3 modules	GW16803N	1
GW 16 004 SPW	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Clay



GW 16 003 SCY

Code	Description	For support codes	Pack Carton
GW 16 003 SCY	3 modules	GW16803N	1
GW 16 004 SCY	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same plate box: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART - Natural beige



GW 16 003 SNB

Code	Description	For support codes	Pack Carton
GW 16 003 SNB	3 modules	GW16803N	1
GW 16 004 SNB	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

ChoruSmart - Plates



GW 16 003 SDS

EGO SMART - Dark sand

Code	Description	For support codes	Pack Carton
GW 16 003 SDS	3 modules	GW16803N	1
GW 16 004 SDS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SDB

EGO SMART - Satin black

Code	Description	For support codes	Pack Carton
GW 16 003 SDB	3 modules	GW16803N	1
GW 16 004 SDB	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 003 SGR

EGO SMART - Magnetic gray

Code	Description	For support codes	Pack Carton
GW 16 003 SGR	3 modules	GW16803N	1
GW 16 004 SGR	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Light bronze



GW 16 003 SBR

Code	Description	For support codes	Pack Carton
GW 16 003 SBR	3 modules	GW16803N	1
GW 16 004 SBR	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Steel



GW 16 003 SST

Code	Description	For support codes	Pack Carton
GW 16 003 SST	3 modules	GW16803N	1
GW 16 004 SST	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply. The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART - Soft copper



GW 16 003 SCS

Code	Description	For support codes	Pack Carton
GW 16 003 SCS	3 modules	GW16803N	1
GW 16 004 SCS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

ChoruSmart - Plates



GW 16 003 SSG

EGO SMART - Gold

Code	Description	For support codes	Pack Carton
GW 16 003 SSG	3 modules	GW16803N	1
GW 16 004 SSG	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SCP

EGO SMART - Copper

Code	Description	For support codes	Pack Carton
GW 16 003 SCP	3 modules	GW16803N	1
GW 16 004 SCP	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SBS

EGO SMART - Brown shade

Code	Description	For support codes	Pack Carton
GW 16 003 SBS	3 modules	GW16803N	1
GW 16 004 SBS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



ChoruSmart




Scan the QR Code and find out all the technical informations.

INNOVATION



The plate communicates with the user through simple and immediate visual feedback. The display is dynamic: text messages scroll and icons change shape to indicate the activation and operation of the commanded loads. The edges are illuminated with a coloured beam of light: each colour corresponds to a different signal.

SIMPLICITY



To recognise the associated function, each command can be linked to a different graphic. Lighting icons, messages and colours can be selected from the Home Gateway App with a wide variety of choices.

DOUBLED FUNCTIONS



The EGO SMART plate expands the functions managed from the control point. The manually activated proximity sensor enables the Shift mode on the plate, doubling the functions of the control units installed, without taking up additional space.

ChoruSmart

LUX plates

Technopolymer

WHITE



GW 16 202 TB	2 modules
GW 16 203 TB	3 modules
GW 16 204 TB	4 modules
GW 16 206 TB	6 modules

WHITE MONOCHROME



GW 16 202 YB	2 modules
GW 16 203 YB	3 modules
GW 16 204 YB	4 modules
GW 16 206 YB	6 modules

TONER BLACK



GW 16 202 TN	2 modules
GW 16 203 TN	3 modules
GW 16 204 TN	4 modules
GW 16 206 TN	6 modules

TONER BLACK LAVY



GW 16 202 YN	2 modules
GW 16 203 YN	3 modules
GW 16 204 YN	4 modules
GW 16 206 YN	6 modules

Painted technopolymer

TITANIUM ▲



GW 16 202 VT	2 modules
GW 16 203 VT	3 modules
GW 16 204 VT	4 modules
GW 16 206 VT	6 modules

TITANIUM MONOCHROME



GW 16 202 YT	2 modules
GW 16 203 YT	3 modules
GW 16 204 YT	4 modules
GW 16 206 YT	6 modules

SLATE ▲



GW 16 202 VA	2 modules
GW 16 203 VA	3 modules
GW 16 204 VA	4 modules
GW 16 206 VA	6 modules

ABSOLUTE SLATE ▲



GW 16 202 YA	2 modules
GW 16 203 YA	3 modules
GW 16 204 YA	4 modules
GW 16 206 YA	6 modules

Metal

SATIN WHITE MONOCHROME



GW 16 202 XW	2 modules
GW 16 203 XW	3 modules
GW 16 204 XW	4 modules
GW 16 206 XW	6 modules

NATURAL BEIGE MONOCHROME



GW 16 202 XL	2 modules
GW 16 203 XL	3 modules
GW 16 204 XL	4 modules
GW 16 206 XL	6 modules

SATIN BLACK MONOCHROME



GW 16 202 XM	2 modules
GW 16 203 XM	3 modules
GW 16 204 XM	4 modules
GW 16 206 XM	6 modules

PEARLY BRONZE



GW 16 202 XP	2 modules
GW 16 203 XP	3 modules
GW 16 204 XP	4 modules
GW 16 206 XP	6 modules

ANODIC BROWN



GW 16 202 XV	2 modules
GW 16 203 XV	3 modules
GW 16 204 XV	4 modules
GW 16 206 XV	6 modules

ANODIC BROWN



GW 16 202 XF	2 modules
GW 16 203 XF	3 modules
GW 16 204 XF	4 modules
GW 16 206 XF	6 modules

MONOCHROME ALUMINIUM




GW 16 202 XA	2 modules
GW 16 203 XA	3 modules
GW 16 204 XA	4 modules
GW 16 206 XA	6 modules

SOFT COPPER



GW 16 202 XE	2 modules
GW 16 203 XE	3 modules
GW 16 204 XE	4 modules
GW 16 206 XE	6 modules

MAGNETIC GRAY



GW 16 202 XR	2 modules
GW 16 203 XR	3 modules
GW 16 204 XR	4 modules
GW 16 206 XR	6 modules

▲ Metallic effect

Metal

BRUSHED ALUMINIUM



GW 16 202 XS	2 modules
GW 16 203 XS	3 modules
GW 16 204 XS	4 modules
GW 16 206 XS	6 modules

BRUSHED ALUMINIUM LAVY



GW 16 202 WS	2 modules
GW 16 203 WS	3 modules
GW 16 204 WS	4 modules
GW 16 206 WS	6 modules

GOLD



GW 16 202 XG	2 modules
GW 16 203 XG	3 modules
GW 16 204 XG	4 modules
GW 16 206 XG	6 modules

ANTIQUE BRASS



GW 16 202 XQ	2 modules
GW 16 203 XQ	3 modules
GW 16 204 XQ	4 modules
GW 16 206 XQ	6 modules

Wood

LIGHT OAK



GW 16 202 WK	2 modules
GW 16 203 WK	3 modules
GW 16 204 WK	4 modules
GW 16 206 WK	6 modules

WALNUT



GW 16 202 WU	2 modules
GW 16 203 WU	3 modules
GW 16 204 WU	4 modules
GW 16 206 WU	6 modules

Glass

NATURAL REFLECTION




GW 16 202 GT	2 modules
GW 16 203 GT	3 modules
GW 16 204 GT	4 modules
GW 16 206 GT	6 modules

PEARLY GRAY



GW 16 202 GP	2 modules
GW 16 203 GP	3 modules
GW 16 204 GP	4 modules
GW 16 206 GP	6 modules

Modularity



2 modules | 3 modules | 4 modules | 6 modules

ChoruSmart

LUX plates

LUX plates, with their modern, refined lines, marry the high-tech spirit of modernity with the refined and elegant taste of tradition. Wood, glass and metal versions are added to the classic technopolymer plates. With monochrome variants of the LUX plates, uniformity of colour becomes the distinctive character of each ChoruSmart lighting device.



LUX ITALIAN STANDARD PLATES

Technopolymer




GW 16 203 TB

LUX - White

Code	Description	For support codes	Pack Carton
GW 16 202 TB	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 TB	3 modules	GW16803, GW16803N	12
GW 16 204 TB	4 modules	GW16804, GW16804N	12
GW 16 206 TB	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.
NOTES: inner frame chromed.



GW 16 203 YB

LUX - Monochrome white

Code	Description	For support codes	Pack Carton
GW 16 202 YB	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 YB	3 modules	GW16803, GW16803N	12
GW 16 204 YB	4 modules	GW16804, GW16804N	12
GW 16 206 YB	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.
NOTES: inner frame in the same white colour as the plate, glossy finish.



GW 16 203 TN

LUX - Toner black

Code	Description	For support codes	Pack Carton
GW 16 202 TN	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 TN	3 modules	GW16803, GW16803N	12
GW 16 204 TN	4 modules	GW16804, GW16804N	12
GW 16 206 TN	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.
NOTES: inner frame chromed.



GW 16 203 YN

LUX - Toner black lavy

Code	Description	For support codes	Pack Carton
GW 16 202 YN	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 YN	3 modules	GW16803, GW16803N	12
GW 16 204 YN	4 modules	GW16804, GW16804N	12
GW 16 206 YN	6 modules	GW16806	6

CHARACTERISTICS: glossy finish.
NOTES: inner frame in the same black colour of the plate, matt finish.

Painted technopolymer

LUX - Titanium



GW 16 203 VT

Code	Description	For support codes	Pack Carton
GW 16 202 VT	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 VT	3 modules	GW16803, GW16803N	12
GW 16 204 VT	4 modules	GW16804, GW16804N	12
GW 16 206 VT	6 modules	GW16806	6

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame chromed.

LUX - Monochrome titanium



GW 16 203 YT

Code	Description	For support codes	Pack Carton
GW 16 202 YT	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 YT	3 modules	GW16803, GW16803N	12
GW 16 204 YT	4 modules	GW16804, GW16804N	12
GW 16 206 YT	6 modules	GW16806	6

CHARACTERISTICS: gglossy finish, metallic effect.
NOTES: inner frame in the same titanium colour of the plate, glossy finish.

LUX - Slate



GW 16 203 VA

Code	Description	For support codes	Pack Carton
GW 16 202 VA	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 VA	3 modules	GW16803, GW16803N	6
GW 16 204 VA	4 modules	GW16804, GW16804N	6
GW 16 206 VA	6 modules	GW16806	6

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame chromed.

LUX - Absolute slate



GW 16 203 YA

Code	Description	For support codes	Pack Carton
GW 16 202 YA	2 modules	GW16802, GW16803, GW16803N	12
GW 16 203 YA	3 modules	GW16803, GW16803N	12
GW 16 204 YA	4 modules	GW16804, GW16804N	12
GW 16 206 YA	6 modules	GW16806	6

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame in the same slate colour of the plate, glossy finish.

ChoruSmart - Plates

Metal

LUX - Monochrome satin white



GW 16 203 XW

Code	Description	For support codes	Pack Carton
GW 16 202 XW	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XW	3 modules	GW16803, GW16803N	6
GW 16 204 XW	4 modules	GW16804, GW16804N	6
GW 16 206 XW	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in same white colour, matt finish.

LUX - Monochrome natural beige



GW 16 203 XL

Code	Description	For support codes	Pack Carton
GW 16 202 XL	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XL	3 modules	GW16803, GW16803N	6
GW 16 204 XL	4 modules	GW16804, GW16804N	6
GW 16 206 XL	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in same natural beige colour, matt finish.

LUX - Monochrome satin black



GW 16 203 XM

Code	Description	For support codes	Pack Carton
GW 16 202 XM	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XM	3 modules	GW16803, GW16803N	6
GW 16 204 XM	4 modules	GW16804, GW16804N	6
GW 16 206 XM	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in same black colour as the plate, matt finish.

LUX - Pearly bronze



GW 16 203 XP

Code	Description	For support codes	Pack Carton
GW 16 202 XP	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XP	3 modules	GW16803, GW16803N	6
GW 16 204 XP	4 modules	GW16804, GW16804N	6
GW 16 206 XP	6 modules	GW16806	6

CHARACTERISTICS: glossy finish, metallic effect.
NOTES: inner frame in light bronze colour, matt finish.

LUX - Anodic brown



GW 16 203 XV

Code	Description	For support codes	Pack Carton
GW 16 202 XV	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XV	3 modules	GW16803, GW16803N	6
GW 16 204 XV	4 modules	GW16804, GW16804N	6
GW 16 206 XV	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in dark bronze colour, matt finish.

LUX - Gunbarrel grey



GW 16 203 XF

Code	Description	For support codes	Pack Carton
GW 16 202 XF	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XF	3 modules	GW16803, GW16803N	6
GW 16 204 XF	4 modules	GW16804, GW16804N	6
GW 16 206 XF	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in the same gunbarrel grey colour as the plate, matt finish.

LUX - Monochrome aluminium



GW 16 203 XA

Code	Description	For support codes	Pack Carton
GW 16 202 XA	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XA	3 modules	GW16803, GW16803N	6
GW 16 204 XA	4 modules	GW16804, GW16804N	6
GW 16 206 XA	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in the same aluminium colour as the plate, matt finish.

LUX - Soft copper




GW 16 203 XE

Code	Description	For support codes	Pack Carton
GW 16 202 XE	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XE	3 modules	GW16803, GW16803N	6
GW 16 204 XE	4 modules	GW16804, GW16804N	6
GW 16 206 XE	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in the same soft copper colour as the plate, matt finish.

LUX - Magnetic gray



GW 16 203 XR

Code	Description	For support codes	Pack Carton
GW 16 202 XR	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XR	3 modules	GW16803, GW16803N	6
GW 16 204 XR	4 modules	GW16804, GW16804N	6
GW 16 206 XR	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in the same magnetic gray colour as the plate, matt finish.

LUX - Brushed aluminium



GW 16 203 XS

Code	Description	For support codes	Pack Carton
GW 16 202 XS	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XS	3 modules	GW16803, GW16803N	6
GW 16 204 XS	4 modules	GW16804, GW16804N	6
GW 16 206 XS	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in light bronze colour, matt finish.

ChoruSmart - Plates



GW 16 203 WS

LUX - Brushed aluminium lavy

Code	Description	For support codes	Pack Carton
GW 16 202 WS	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 WS	3 modules	GW16803, GW16803N	6
GW 16 204 WS	4 modules	GW16804, GW16804N	6
GW 16 206 WS	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in black colour, matt finish.



GW 16 203 XG

LUX - Gold

Code	Description	For support codes	Pack Carton
GW 16 202 XG	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XG	3 modules	GW16803, GW16803N	6
GW 16 204 XG	4 modules	GW16804, GW16804N	6
GW 16 206 XG	6 modules	GW16806	6

CHARACTERISTICS: matt finish, metallic effect.
NOTES: inner frame in the same gold colour as the plate, matt finish.



GW 16 203 XQ

LUX - Antique brass

Code	Description	For support codes	Pack Carton
GW 16 202 XQ	2 modules	GW16802, GW16803, GW16803N	6
GW 16 203 XQ	3 modules	GW16803, GW16803N	6
GW 16 204 XQ	4 modules	GW16804, GW16804N	6
GW 16 206 XQ	6 modules	GW16806	6

CHARACTERISTICS: matt finish.
NOTES: inner frame in dark bronze colour, matt finish.

Wood

LUX - Light oak



GW 16 203 WK

Code	Description	For support codes	Pack Carton
GW 16 202 WK	2 modules	GW16802, GW16803, GW16803N	1
GW 16 203 WK	3 modules	GW16803, GW16803N	1
GW 16 204 WK	4 modules	GW16804, GW16804N	1
GW 16 206 WK	6 modules	GW16806	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in light bronze colour, matt finish. Design variations in the wooden plates are a sign of the quality and authenticity of the materials used.

LUX - Walnut



GW 16 203 WU

Code	Description	For support codes	Pack Carton
GW 16 202 WU	2 modules	GW16802, GW16803, GW16803N	1
GW 16 203 WU	3 modules	GW16803, GW16803N	1
GW 16 204 WU	4 modules	GW16804, GW16804N	1
GW 16 206 WU	6 modules	GW16806	1

CHARACTERISTICS: matt finish.

NOTES: inner frame in dark bronze colour, matt finish. Design variations in the wooden plates are a sign of the quality and authenticity of the materials used.

ChoruSmart - Plates

Glass



GW 16 203 GT

LUX - Natural reflection

Code	Description	For support codes	Pack Carton
GW 16 202 GT	2 modules	GW16802, GW16803, GW16803N	1
GW 16 203 GT	3 modules	GW16803, GW16803N	1
GW 16 204 GT	4 modules	GW16804, GW16804N	1
GW 16 206 GT	6 modules	GW16806	1

CHARACTERISTICS: matt finish.
NOTES: inner frame in light bronze colour, matt finish.
Design variations in the glass plates are a sign of quality and indicate the genuineness of the materials used.



GW 16 203 GP

LUX - Pearly gray

Code	Description	For support codes	Pack Carton
GW 16 202 GP	2 modules	GW16802, GW16803, GW16803N	1
GW 16 203 GP	3 modules	GW16803, GW16803N	1
GW 16 204 GP	4 modules	GW16804, GW16804N	1
GW 16 206 GP	6 modules	GW16806	1

CHARACTERISTICS: matt finish.
NOTES: inner frame in light bronze colour, matt finish. Design variations in the glass plates are a sign of quality and indicate the genuineness of the materials used.




ChoruSmart



Scan the QR Code and find out all the technical informations.

CONTEMPORARY STYLE



The LUX plate, with its modern shapes, is the perfect blend of modernity and the elegant aesthetics of tradition.

MATERIALS



Classic and elegantly designed, LUX plates meet all your needs with their wide variety of materials, from technopolymer to metal, from wood to glass.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

ICE plates

Glass

WHITE		BLACK		NATURAL BEIGE		TITANIUM	
							
GW 16 902 CB	2 modules	GW 16 902 CN	2 modules	GW 16 902 CL	2 modules	GW 16 902 CT	2 modules
GW 16 903 CB	3 modules	GW 16 903 CN	3 modules	GW 16 903 CL	3 modules	GW 16 903 CT	3 modules
GW 16 904 CB	4 modules	GW 16 904 CN	4 modules	GW 16 904 CL	4 modules	GW 16 904 CT	4 modules
GW 16 906 CB	6 modules	GW 16 906 CN	6 modules	GW 16 906 CL	6 modules	GW 16 906 CT	6 modules

ICE TOUCH plates

Glass


WHITE	BLACK	NATURAL BEIGE	TITANIUM
			
GW 16 955 CB	GW 16 955 CN	GW 16 955 CL	GW 16 955 CT

ICE TOUCH KNX plates


Glass

WHITE	BLACK	NATURAL BEIGE	TITANIUM
			
GW 16 946 CB	GW 16 946 CN	GW 16 946 CL	GW 16 946 CT

Modularity



2 modules | 3 modules | 4 modules | 6 modules



6 TOUCH AREAS WITH INTERCHANGEABLE SYMBOLS

ChoruSmart

ICE plates

ICE glass plates meet the most sophisticated technological and aesthetic needs and represent a new frontier for lighting devices. Available in four different colours (white, natural beige, black and titanium), ICE can accommodate all modular devices in the ChoruSmart range. Commands, systems for energy off-take, protection and signalling, comfort, climate control and technical alarms: ICE can meet the needs of any environment.



ICE ITALIAN STANDARD PLATES

Glass

GW 16 903 CB

ICE - White

Code	Description	For support codes	Pack Carton
GW 16 902 CB	2 modules	GW16802, GW16803, GW16803N	1
GW 16 903 CB	3 modules	GW16803, GW16803N	1
GW 16 904 CB	4 modules	GW16804, GW16804N	1
GW 16 906 CB	6 modules	GW16806	1

CHARACTERISTICS: glossy finish.



GW 16 903 CL

ICE - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 902 CL	2 modules	GW16802, GW16803, GW16803N	1
GW 16 903 CL	3 modules	GW16803, GW16803N	1
GW 16 904 CL	4 modules	GW16804, GW16804N	1
GW 16 906 CL	6 modules	GW16806	1

CHARACTERISTICS: glossy finish.

ChoruSmart - Plates



GW 16 903 CN

ICE - Black

Code	Description	For support codes	Pack Carton
GW 16 902 CN	2 modules	GW16802, GW16803, GW16803N	1
GW 16 903 CN	3 modules	GW16803, GW16803N	1
GW 16 904 CN	4 modules	GW16804, GW16804N	1
GW 16 906 CN	6 modules	GW16806	1

CHARACTERISTICS: glossy finish.



GW 16 903 CT

ICE - Titanium

Code	Description	For support codes	Pack Carton
GW 16 902 CT	2 modules	GW16802, GW16803, GW16803N	1
GW 16 903 CT	3 modules	GW16803, GW16803N	1
GW 16 904 CT	4 modules	GW16804, GW16804N	1
GW 16 906 CT	6 modules	GW16806	1

CHARACTERISTICS: glossy finish.

ICE TOUCH ITALIAN STANDARD PLATES

Glass




GW 16 955 CB

ICE TOUCH - White

Code	Description	For support codes	Pack Carton
GW 16 955 CB	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).
NOTES: the symbols displayed in the image are purely indicative and may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).



GW 16 955 CL

ICE TOUCH - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 955 CL	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).
NOTES: the symbols displayed in the image are purely indicative and may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).



GW 16 955 CN

ICE TOUCH - Black

Code	Description	For support codes	Pack Carton
GW 16 955 CN	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).
NOTES: the symbols displayed in the image are purely indicative: they may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).



GW 16 955 CT

ICE TOUCH - Titanium

Code	Description	For support codes	Pack Carton
GW 16 955 CT	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).
NOTES: the symbols displayed in the image are purely indicative: they may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

ChoruSmart - Plates

ICE TOUCH KNX ITALIAN STANDARD PLATES

Glass



GW 16 946 CB

ICE TOUCH KNX - White

Code	Description	For support codes	Pack Carton
GW 16 946 CB	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CL

ICE TOUCH KNX - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 946 CL	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CN

ICE TOUCH KNX - Black

Code	Description	For support codes	Pack Carton
GW 16 946 CN	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CT

ICE TOUCH KNX - Titanium


Code	Description	For support codes	Pack Carton
GW 16 946 CT	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).





ChoruSmart




Scan the QR Code and find out all the technical informations.

REFINED FINISHES



With the ICE Touch and ICE Touch KNX plates, your home responds to every gesture with just a touch of your fingertip. The purity of white, the elegance of natural beige, the rationality of titanium and the allure of black are complemented by the refined luminous symbols that identify the keys selected, enhancing the plate in its purest expression.

ELEGANT AND MODERN



Glass, the material of elegance, encapsulates a heart of pure technology, with touch controls or traditional keys that enhance every simple gesture.

HIGHLY CUSTOMISABLE

The plates can be customised through a choice of colours and finishes. This allows the installation to be adapted to the style of the interiors and enhance all applications. Thanks to tampography and lasering, the plates can be customised with lettering, trademarks and logos. Please contact the GEWISS Commercial department to discuss the feasibility of any customisation.

Special plates and free-standing enclosures

Watertight plates



2 modules - IP55
International standard

GW 16 702 TBN
Glossy white
GW 16 702 TNN
Glossy black
GW 16 702 VTN
Glossy titanium



3 modules - IP55
Italian standard

GW 16 703 TBN
Glossy white
GW 16 703 TNN
Glossy black
GW 16 703 VTN
Glossy titanium



4 modules - IP55
Italian standard

GW 16 704 TBN
Glossy white
GW 16 704 TNN
Glossy black
GW 16 704 VTN
Glossy titanium

Plates for profiles



Self-supporting plates

1 module

GW 16 711 TB
Glossy white
GW 16 711 TN
Glossy black
GW 16 711 VT
Glossy titanium

2 modules

GW 16 712 TB
Glossy white
GW 16 712 TN
Glossy black
GW 16 712 VT
Glossy titanium

Blank plates



Blank plates

3 modules

GW 16 723 TB
Glossy white
GW 16 723 TN
Glossy black

4 modules

GW 16 724 TB
Glossy white
GW 16 724 TN
Glossy black

Free-standing and wall-mounting enclosures



Enclosures
for ONE plates

4 modules

GW 16 854
Satin white
GW 16 864
Satin black

6 modules

GW 16 856
Satin white
GW 16 866
Satin black

Wall-mounting boxes

For mini-trunking and trunking used as skirting



3 modules boxes for
ONE plates

GW 16 743
Satin white
GW 16 773
Satin black



4 modules boxes for
ONE plates

GW 16 744
Satin white
GW 16 774
Satin black



2 modules boxes for
ONE International plates

GW 16 752
Satin white
GW 16 782
Satin black



2+2 modules boxes for
ONE International plates

Horizontal

GW 16 753
Satin white
GW 16 783
Satin black

Vertical

GW 16 754
Satin white
GW 16 784
Satin black

Enclosures for outdoors

Empty enclosures



Grey RAL 7035

GW 16 502
2 modules
GW 16 503
3 modules
GW 16 504
4 modules



Grey RAL 7035
IP55

GW 16 512
2 modules
GW 16 513
3 modules
GW 16 514
4 modules

Accessories

Protective covers for painting



For rectangular
supports

GW 16 873
3 modules
GW 16 874
4 modules
GW 16 876
6 modules
GW 16 877 N
7 modules



GW 16 871
For square supports

Supports for DIN rail



DIN rail

GW 16 841
1 module - 1.5 DIN module
GW 16 842
2 modules - 3 DIN modules
GW 16 843
3 modules - 4 DIN modules

Supports for ONE, GEO, EGO, LUX, ICE plates

Supports for round/square boxes




GW 16 821
With clutches - 2 modules
GW 16 823
With long clutches - 2 modules



GW 16 822
For screws (not included)
2 modules

Supports for round/square and rectangular boxes




GW 16 802
For screws - 2 modules

Supports for rectangular boxes



GW 16 803
With screws - 3 modules



GW 16 804
With screws - 4 modules
GW 16 824
For screws (not included) for French boxes



GW 16 806
With screws - 6 modules
GW 16 825
For screws (not included) for French boxes



GW 16 807 N
With screws - 7 modules



GW 16 808
With screws - 4+4 modules



GW 16 812
With screws - 6+6 modules

Supports for EGO SMART plates

Supports for round/square boxes



GW 16 821 N (**)
With clutches - 2 modules



GW 16 822 N (**)
For screws (not included) - 2 modules

Supports for rectangular boxes



GW 16 803 N (*)
With screws - 3 modules



GW 16 804 N (*)
With screws - 4 modules

(*) compatible with the whole range of ONE, GEO, EGO, LUX and ICE plates for rectangular boxes.
(**) compatible with the whole range of ONE International, GEO International, EGO International and LUX International plates for round/square boxes.

ChoruSmart

Installation accessories

Wide variety of installation accessories for all modular devices and plates from the ChoruSmart range. Watertight plates with ergonomic membrane and 2 to 4 modules. Self-supporting plates for profiles and panels. Free-standing and surface-mounted panels. Surface-mounted boxes and self-supporting protected watertight enclosures. Supports for rectangular, round and square boxes available in standard and smart versions. Covers for flush-mounted boxes from 2 to 7 modules for painting and finishing.



SPECIAL PLATES AND PANELS

Watertight plates



GW 16 703 TBN

Watertight plates - Italian standard - IP55

Code	Description	Colour	Included support	Pack Carton
GW 16 703 TBN	3 modules	Glossy white	GW16803	1/24
GW 16 704 TBN	4 modules	Glossy white	GW16804	1/24
GW 16 703 TNN	3 modules	Glossy black	GW16803	1/12
GW 16 704 TNN	4 modules	Glossy black	GW16804	1/12
GW 16 703 VTN	3 modules	Glossy titanium	GW16803	1/12
GW 16 704 VTN	4 modules	Glossy titanium	GW16804	1/12

CHARACTERISTICS: support included, equipped with 2 screws (length 30 mm). Ergonomic membrane made of UV-resistant material. Maximum opening angle lid 160° facilitated by a comfortable handle.
APPLICATIONS: for installation on rectangular (3 and 4 modules) flush mounting boxes.
NOTES: IP55 degree guaranteed with closed lid and watertight plate mounted on smooth and waterproof walls, without grooves.



GW 16 702 TBN

Watertight plates - International standard - IP55

Code	Description	Colour	Included support	Pack Carton
GW 16 702 TBN	2 modules	Glossy white	GW16822	1/24
GW 16 702 TNN	2 modules	Glossy black	GW16822	1/12
GW 16 702 VTN	2 modules	Glossy titanium	GW16822	1/12

CHARACTERISTICS: support included, equipped with 2 self-tapping screws (length 22 mm). Ergonomic membrane made of UV-resistant material. Maximum opening angle lid 160° facilitated by a comfortable handle.
APPLICATIONS: for installations on round/square flush mounting boxes equipped with screw columns (axles distance 60mm).
NOTES: IP55 degree guaranteed with closed lid and watertight plate mounted on smooth and waterproof walls, without grooves.

Plates for profiles



GW 16 711 TB

Self-supporting plates for profiles and panels

HF HALOGEN FREE

Code	Description	Colour Plate	Characteristics	Pack Carton
GW 16 711 TB	1 module	Glossy white	Halogen free	1/48
GW 16 712 TB	2 modules	Glossy white	Halogen free	1/24
GW 16 711 TN	1 module	Glossy black	Halogen free	1/24
GW 16 712 TN	2 modules	Glossy black	Halogen free	1/24
GW 16 711 VT	1 module	Glossy titanium	Halogen free	1/12
GW 16 712 VT	2 modules	Glossy titanium	Halogen free	1/12

CHARACTERISTICS: complete with insulating box and supports. Diameter for cable input max. 10mm.
NOTES: the insulating box is equipped with a tug-proof cable fastener device and a corrugated conduit fastener device.

NEWS

ChoruSmart - Installation accessories

Blank plates



GW 16 723 TB

Blank plates

Code	Description	Colour	For support codes	Characteristics	Pack Carton
GW 16 723 TB	3 modules	Glossy white	GW16802, GW16803, GW16803N	Halogen free	1/24
GW 16 724 TB	4 modules	Glossy white	GW16804, GW16804N	Halogen free	1/24
GW 16 723 TN	3 modules	Glossy black	GW16802, GW16803, GW16803N	Halogen free	1/12
GW 16 724 TN	4 modules	Glossy black	GW16804, GW16804N	Halogen free	1/12

CHARACTERISTICS: support not included for installation on rectangular boxes.

Free-standing and wall-mounting enclosures



GW 16 854

Free-standing and wall-mounting enclosures for ONE plates

Code	Description	Colour	Support	Outer dim. LxHxD (mm)	Pack Carton
GW 16 854	4 modules	Satin white	GW16804	140x90x69	1/30
GW 16 856	6 modules	Satin white	GW16806	181x90x69	1/15
GW 16 864	4 modules	Satin black	GW16804	140x90x69	1/30
GW 16 866	6 modules	Satin black	GW16806	181x90x69	1/15

CHARACTERISTICS: support and plate not included. Use ONE plates (interchangeability with the entire colour range of plates).
Diameter for cable input max. 10mm.
NOTES: cable gland and safety cable fastener included. For wall-mounting, use wall plugs with a countersunk head, max Ø 3.5mm.

BOXES, ENCLOSURES AND SUPPORTS

Wall-mounting boxes



GW 16 743

Wall-mounting boxes for mini-trunking and trunking used as skirting for ONE plates

Code	Description	Support	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
Colour: Satin White					
GW 16 743	3 modules	GW16803	118x90x46	Halogen free	3/60
GW 16 744	4 modules	GW16804	140x90x46	Halogen free	1/30
Colour: Satin black					
GW 16 773	3 modules	GW16803	118x90x46	Halogen free	3/30
GW 16 774	4 modules	GW16804	140x90x46	Halogen free	1/30

CHARACTERISTICS: support and plate not included. Use ONE plates (interchangeability with the entire colour range of plates). Pre-arranged for mini-trunking with dimensions BxH (mm): 15x8, 15x10, 22x10, 30x15.
NOTES: fitted for fixing the earth terminal GW26407.



GW 16 752

Wall-mounting boxes for mini-trunking and trunking used as skirting for ONE International plates

Code	Description	Type	Support	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
Colour: Satin White						
GW 16 752	2 modules	-	GW16822	90x90x46	Halogen free	1/30
GW 16 753	2+2 modules	Horizontal	GW16822	161x90x46	Halogen free	1/15
GW 16 754	2+2 modules	Vertical	GW16822	90x161x46	Halogen free	1/15
Colour: Satin black						
GW 16 782	2 modules	-	GW16822	90x90x46	Halogen free	1/30
GW 16 783	2+2 modules	Horizontal	GW16822	161x90x46	Halogen free	1/15
GW 16 784	2+2 modules	Vertical	GW16822	90x161x46	Halogen free	1/15

CHARACTERISTICS: support and plate not included. Use ONE International plates (interchangeability with the entire colour range of the plates).
Pre-arranged for mini-trunking with dimensions BxH (mm): 15x15, 20x20, 22x10, 30x10, 30x15, 35x15, 45x15.
GW16754 and GW16784 to be used together with plates with a centre distance of 71mm.
GW16752 - GW16782 supplied with 2 fixing screws. GW16753 - GW16754 - GW16783 - GW16784 supplied with 6 fixing screws.
NOTES: fitted for fixing the earth terminal GW26407.

Enclosures for outdoors



GW 16 503

Self-supporting, empty, protected enclosures - IP40

Code	Description	Colour	Outer dim. LxHxD (mm)	Pack Carton
GW 16 502	2 modules	Grey RAL 7035	66x82x56	5/80
GW 16 503	3 modules	Grey RAL 7035	99x82x56	3/60
GW 16 504	4 modules	Grey RAL 7035	132x82x56	1/40

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.
NOTES: not suitable for the installation of 1/2 module devices.



GW 16 513

Self-supporting, empty, watertight enclosures - IP55

Code	Description	Colour	Outer dim. LxHxD (mm)	Pack Carton
GW 16 512	2 modules	Grey RAL 7035	66x82x69	5/60
GW 16 513	3 modules	Grey RAL 7035	99x82x69	2/40
GW 16 514	4 modules	Grey RAL 7035	132x82x69	1/30

CHARACTERISTICS: fitted for fixing the earth terminal GW26407. Ergonomic membrane, in UV-resistant material, Snap closing system.
NOTES: not suitable for the installation of 1/2 module devices.

Complementary items



GW 26 407

Brass terminal for through-line earth conductor

Code	Section (mm²)	Fixing	Pack Carton
GW 26 407	4	Pressure-operated	200/1600



GW 24 224

Special self-tapping screws for fixing the devices

Code	Dimensions (mm)	Suitable for	Pack Carton
GW 24 224	TC 3.5x17	Wood, plastic, aluminium	500/7000
GW 24 225	TC 3.5x30	Deep-mounted boxes	300/4200
GW 24 229	TC 3.5x50	Deep-mounted boxes	300/4200

ChoruSmart - Installation accessories

Supports

Italian standard supports for EGO SMART plates



GW 16 803 N

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 803 N	3 modules	2 screws (included)	Halogen free	6/240
GW 16 804 N	4 modules	2 screws (included)	Halogen free	6/120

CHARACTERISTICS: specific supports for 3 and 4 module Italian standard EGO SMART plates; supports are also compatible with the other Italian standard ChoruSmart 3 and 4 module plates ONE, GEO, LUX, ICE and EGO.

International standard supports for EGO SMART plates



GW 16 822 N

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 821 N	2 modules	With fixing clutches (included)	Halogen free	20/120
GW 16 822 N	2 modules	For screws (not included)	Halogen free	20/120

CHARACTERISTICS: GW16821N equipped with fixing clutches for installation on round boxes. Supports specifically for international standard EGO SMART plates; the supports are also compatible with the other ChoruSmart international standard plates, including ONE, GEO, LUX and EGO.
NOTES: GW16822N support can be installed on single round and square boxes or in a horizontal composition; the GW16821N support can be installed on single stand-alone round boxes.

International standard supports for ONE, GEO, EGO, LUX plates




GW 16 822

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 821	2 modules	With fixing clutches	Halogen free	12/120
GW 16 822	2 modules	For screws (not included)	Halogen free	20/120
GW 16 823	2 modules	With long fixing clutches	Halogen free	12/120

CHARACTERISTICS: GW16821 and GW16823 equipped with fixing clutches for installation on round boxes.
NOTES: GW16821 and GW16823 supports can be installed on single round boxes or in vertical composition.

French standard supports



GW 16 824

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 824	4 modules	For screws (not incl.) horiz. centre dist. 57mm	Halogen free	12/60
GW 16 825	6 modules	For screws (not incl.) horiz. centre dist. 2x57mm	Halogen free	12/48

CHARACTERISTICS: supports pre-arranged for fixing on French Standard rectangular boxes.
NOTES: GW16824 fit the ChoruSmart 4 modules plates. GW16825 fit the ChoruSmart 6 modules plates.

Protective covers for painting, for CHORUSMART range, International Standard




GW 16 871

Code	Description	Suitable for support	Colour	Pack Carton
GW 16 871	2 modules	GW16821, GW16822, GW16823, GW16831, GW16821N, GW16822N	Transparent	60/480

CHARACTERISTICS: total protection during painting and finishing operations.
NOTES: snap-in mounting to facilitate assembly and removal operations.

Italian standard supports for ONE, GEO, EGO, LUX and ICE plates



GW 16 802

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 802	2 modules	2 screws (included)	Halogen free	12/120
GW 16 803	3 modules	2 screws (included)	Halogen free	12/240
GW 16 804	4 modules	2 screws (included)	Halogen free	12/120
GW 16 806	6 modules	4 screws (included)	Halogen free	12/72
GW 16 807 N	7 modules	2 screws (included)	Halogen free	12/72
GW 16 808	4+4 modules	4 screws (included)	Halogen free	12/48
GW 16 812	6+6 modules	4 screws (included)	Halogen free	12/48

CHARACTERISTICS: GW16802 predisposed for fixing on both rectangular 3-module boxes (centre distance 83.5mm) and round/square boxes (centre distance 60mm) equipped with fixing columns. To be completed with 2-module standard plates.
NOTES: GW16808 and GW16812 to be used with white or titanium colour ONE plates. GW16807N to be used with EGO plates.

Protective covers for painting, for CHORUSMART range, Italian Standard



GW 16 873

Code	Description	Suitable for support	Colour	Pack Carton
GW 16 873	3 modules	GW16802, GW16803, GW16803N	Transparent	120/480
GW 16 874	4 modules	GW16804, GW16804N	Transparent	60/240
GW 16 876	6 modules	GW16806	Transparent	60/240
GW 16 877 N	7 modules	GW16807N	Transparent	60/240

CHARACTERISTICS: total protection during painting and finishing operations.
NOTES: snap-in mounting to facilitate assembly and removal operations.

ChoruSmart - Installation accessories



GW 16 841

Supports for assembling CHORUSMART devices on DIN EN 50022 rail

Code	Description	No. DIN modules	Pack Carton
GW 16 841	1 module	1.5	5/300
GW 16 842	2 modules	3	5/150
GW 16 843	3 modules	4	5/50

CHARACTERISTICS: tool-free manual release system for flush-mounting devices.

NOTES: pay attention when using particularly deep devices (two-pole, three-way switches, movement detectors and IR receivers, relays, German standard socket-outlets with front tightening, quick wiring terminals, British standard socket-outlets, interlocked switched sockets-outlets, shaver sockets-outlets, USB power supplies, MCCB and RCCB, anti-black-out and emergency lamps, ringers and buzzers, thermostats and timed thermostats, programmers, water and gas detectors, timers, dimmers, touch commands, electronic soft-click push buttons with interlock, KNX flush-mounting timed thermostats, etc.) as they may interfere with the DIN rail, preventing the correct passage of the wires.



ChoruSmart



Scan the QR Code and find out all the technical informations.

MODERN DESIGN



The watertight plates, available in three elegant colors and equipped with a large transparent ergonomic membrane, feature a simple and discreet design, making them ideal for housing and protecting the ChoruSmart domestic range devices.

SIMPLIFIED INSTALLATION



The door opening up to 160° ensures easy access to the devices. Additionally, the possibility of mounting on deeply positioned flush-mounted boxes makes the plate installation simple and quick.

DURABILITY OVER TIME



The new handle and spring design makes it easier to release and open the door. The new gasket offers greater resistance to weather conditions, giving the plate robustness and durability over time.

Command devices - rockers

One-way switches



1M-1P-16 AX

GW 10 001 Glossy white
GW 15 001 Satin white
GW 13 001 Sat. natural beige
GW 12 001 Satin black
GW 14 001 Glossy titanium
GW 11 001 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 002 Glossy white
GW 15 002 Satin white
GW 13 002 Sat. natural beige
GW 12 002 Satin black
GW 14 002 Glossy titanium
GW 11 002 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 003 Glossy white
GW 15 003 Satin white
GW 13 003 Sat. natural beige
GW 12 003 Satin black
GW 14 003 Glossy titanium
GW 11 003 Glossy ivory



1/2M-1P-10 AX

GW 10 021 Glossy white
GW 15 021 Satin white
GW 13 021 Sat. natural beige
GW 12 021 Satin black
GW 14 021 Glossy titanium



1/2M-1P-10 AX Illuminable (*)

GW 10 022 Glossy white
GW 15 022 Satin white
GW 13 022 Sat. natural beige
GW 12 022 Satin black
GW 14 022 Glossy titanium



2M-1P-16 AX

GW 10 031 Glossy white
GW 15 031 Satin white
GW 13 031 Sat. natural beige
GW 12 031 Satin black
GW 14 031 Glossy titanium
GW 11 031 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 032 Glossy white
GW 15 032 Satin white
GW 13 032 Sat. natural beige
GW 12 032 Satin black
GW 14 032 Glossy titanium
GW 11 032 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 033 Glossy white
GW 15 033 Satin white
GW 13 033 Sat. natural beige
GW 12 033 Satin black
GW 14 033 Glossy titanium
GW 11 033 Glossy ivory



1M-2P-16 AX

GW 10 004 Glossy white
GW 15 004 Satin white
GW 13 004 Sat. natural beige
GW 12 004 Satin black
GW 14 004 Glossy titanium
GW 11 004 Glossy ivory



1M-2P-16 AX Illuminable (*)

GW 10 005 Glossy white
GW 15 005 Satin white
GW 13 005 Sat. natural beige
GW 12 005 Satin black
GW 14 005 Glossy titanium



1M-2P-10 AX With key

GW 10 006 Glossy white
GW 15 006 Satin white
GW 13 006 Sat. natural beige
GW 12 006 Satin black
GW 14 006 Glossy titanium



1M-2P-25 AX Heavy-duty loads

GW 10 007 Glossy white
GW 15 007 Satin white
GW 13 007 Sat. natural beige
GW 12 007 Satin black
GW 14 007 Glossy titanium



2M-2P-16 AX

GW 10 034 Glossy white
GW 15 034 Satin white
GW 13 034 Sat. natural beige
GW 12 034 Satin black
GW 14 034 Glossy titanium



2M-2P-16 AX Illuminable (*)

GW 10 035 Glossy white
GW 15 035 Satin white
GW 13 035 Sat. natural beige
GW 12 035 Satin black
GW 14 035 Glossy titanium

Two-way switches



1M-1P-16 AX

GW 10 051 Glossy white
GW 15 051 Satin white
GW 13 051 Sat. natural beige
GW 12 051 Satin black
GW 14 051 Glossy titanium
GW 11 051 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 052 Glossy white
GW 15 052 Satin white
GW 13 052 Sat. natural beige
GW 12 052 Satin black
GW 14 052 Glossy titanium
GW 11 052 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 053 Glossy white
GW 15 053 Satin white
GW 13 053 Sat. natural beige
GW 12 053 Satin black
GW 14 053 Glossy titanium
GW 11 053 Glossy ivory



1M-1P-10 AX With key

GW 10 054 Glossy white
GW 15 054 Satin white
GW 13 054 Sat. natural beige
GW 12 054 Satin black
GW 14 054 Glossy titanium



1/2M-1P-10 AX

GW 10 061 Glossy white
GW 15 061 Satin white
GW 13 061 Sat. natural beige
GW 12 061 Satin black
GW 14 061 Glossy titanium



2M-1P-16 AX

GW 10 071 Glossy white
GW 15 071 Satin white
GW 13 071 Sat. natural beige
GW 12 071 Satin black
GW 14 071 Glossy titanium
GW 11 071 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 072 Glossy white
GW 15 072 Satin white
GW 13 072 Sat. natural beige
GW 12 072 Satin black
GW 14 072 Glossy titanium
GW 11 072 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 073 Glossy white
GW 15 073 Satin white
GW 13 073 Sat. natural beige
GW 12 073 Satin black
GW 14 073 Glossy titanium
GW 11 073 Glossy ivory

Three-way switches



1M-1P-10 AX Positions 1-0-2

GW 10 121 Glossy white
GW 15 121 Satin white
GW 13 121 Sat. natural beige
GW 12 121 Satin black
GW 14 121 Glossy titanium
GW 11 121 Glossy ivory



1M-2P-10 AX Positions 1-0-2

GW 10 122 Glossy white
GW 15 122 Satin white
GW 13 122 Sat. natural beige
GW 12 122 Satin black
GW 14 122 Glossy titanium



2M-1P-10 AX Positions 1-0-2

GW 10 123 Glossy white
GW 15 123 Satin white
GW 13 123 Sat. natural beige
GW 12 123 Satin black
GW 14 123 Glossy titanium
GW 11 123 Glossy ivory

Intermediate switches



1M-1P-16 AX

GW 10 091 Glossy white
GW 15 091 Satin white
GW 13 091 Sat. natural beige
GW 12 091 Satin black
GW 14 091 Glossy titanium
GW 11 091 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 092 Glossy white
GW 15 092 Satin white
GW 13 092 Sat. natural beige
GW 12 092 Satin black
GW 14 092 Glossy titanium
GW 11 092 Glossy ivory



1M-1P-16 AX Illuminable (*)

GW 10 093 Glossy white
GW 15 093 Satin white
GW 13 093 Sat. natural beige
GW 12 093 Satin black
GW 14 093 Glossy titanium



2M-1P-16 AX

GW 10 101 Glossy white
GW 15 101 Satin white
GW 13 101 Sat. natural beige
GW 12 101 Satin black
GW 14 101 Glossy titanium
GW 11 101 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 102 Glossy white
GW 15 102 Satin white
GW 13 102 Sat. natural beige
GW 12 102 Satin black
GW 14 102 Glossy titanium
GW 11 102 Glossy ivory



2M-1P-16 AX Illuminable (*)

GW 10 103 Glossy white
GW 15 103 Satin white
GW 13 103 Sat. natural beige
GW 12 103 Satin black
GW 14 103 Glossy titanium

(*) supplied without LED signalling unit

Command devices - rockers



1M-1P-NO-16 A

GW 10 131 Glossy white
GW 15 131 Satin white
GW 13 131 Sat. natural beige
GW 12 131 Satin black
GW 14 131 Glossy titanium
GW 11 131 Glossy ivory



1M-1P-NO-16 A
Illuminable (*)

GW 10 132 Glossy white
GW 15 132 Satin white
GW 13 132 Sat. natural beige
GW 12 132 Satin black
GW 14 132 Glossy titanium
GW 11 132 Glossy ivory



1M-1P-NO-16 A
Illuminable (*)

GW 10 133 Glossy white
GW 15 133 Satin white
GW 13 133 Sat. natural beige
GW 12 133 Satin black
GW 14 133 Glossy titanium
GW 11 133 Glossy ivory



1M-1P-NO-16 A
With pull-cord

GW 10 136 Glossy white
GW 15 136 Satin white
GW 13 136 Sat. natural beige
GW 12 136 Satin black
GW 14 136 Glossy titanium
GW 11 136 Glossy ivory



1M-1P-NC-16 A

GW 10 137 Glossy white
GW 15 137 Satin white
GW 13 137 Sat. natural beige
GW 12 137 Satin black
GW 14 137 Glossy titanium



1M-1P-NC+NO-16 A
Stop

GW 10 138 Glossy white
GW 15 138 Satin white
GW 13 138 Sat. natural beige
GW 12 138 Satin black
GW 14 138 Glossy titanium



1M-1P-NO+NC-16 A
Start

GW 10 139 Glossy white
GW 15 139 Satin white
GW 13 139 Sat. natural beige
GW 12 139 Satin black
GW 14 139 Glossy titanium



1M-1P-NO+NO-10 A
With interlock

GW 10 140 Glossy white
GW 15 140 Satin white
GW 13 140 Sat. natural beige
GW 12 140 Satin black
GW 14 140 Glossy titanium
GW 11 140 Glossy ivory



1M-1P-NO+NO-16 A
Double

GW 10 141 Glossy white
GW 15 141 Satin white
GW 13 141 Sat. natural beige
GW 12 141 Satin black
GW 14 141 Glossy titanium



1M-1P-NO-16 A
Green - Illuminable (*)

GW 10 142 Glossy white
GW 15 142 Satin white
GW 13 142 Sat. natural beige
GW 12 142 Satin black
GW 14 142 Glossy titanium



1M-1P-NO-16 A
Red - Illuminable (*)

GW 10 143 Glossy white
GW 15 143 Satin white
GW 13 143 Sat. natural beige
GW 12 143 Satin black
GW 14 143 Glossy titanium



1M-1P-NO-16 A
Opal - Illuminable (*)

GW 10 144 Glossy white
GW 15 144 Satin white
GW 13 144 Sat. natural beige
GW 12 144 Satin black
GW 14 144 Glossy titanium

Push-buttons



1M-1P-NO-16 A
Light - Illuminable (*)

GW 10 151 Glossy white
GW 15 151 Satin white
GW 13 151 Sat. natural beige
GW 12 151 Satin black
GW 14 151 Glossy titanium



1M-1P-NO-16 A
Key - Illuminable (*)

GW 10 152 Glossy white
GW 15 152 Satin white
GW 13 152 Sat. natural beige
GW 12 152 Satin black
GW 14 152 Glossy titanium



1M-1P-NO-16 A
Bell - Illuminable (*)

GW 10 153 Glossy white
GW 15 153 Satin white
GW 13 153 Sat. natural beige
GW 12 153 Satin black
GW 14 153 Glossy titanium
GW 11 153 Glossy ivory



1/2M-1P-NO-10 A

GW 10 161 Glossy white
GW 15 161 Satin white
GW 13 161 Sat. natural beige
GW 12 161 Satin black
GW 14 161 Glossy titanium



1/2M-1P-NO-10 A
Illuminable (*)

GW 10 162 Glossy white
GW 15 162 Satin white
GW 13 162 Sat. natural beige
GW 12 162 Satin black
GW 14 162 Glossy titanium



2M-1P-NO-16 A

GW 10 171 Glossy white
GW 15 171 Satin white
GW 13 171 Sat. natural beige
GW 12 171 Satin black
GW 14 171 Glossy titanium
GW 11 171 Glossy ivory



2M-1P-NO-16 A
Illuminable (*)

GW 10 172 Glossy white
GW 15 172 Satin white
GW 13 172 Sat. natural beige
GW 12 172 Satin black
GW 14 172 Glossy titanium
GW 11 172 Glossy ivory



2M-1P-NO-16 A
Illuminable (*)

GW 10 173 Glossy white
GW 15 173 Satin white
GW 13 173 Sat. natural beige
GW 12 173 Satin black
GW 14 173 Glossy titanium
GW 11 173 Glossy ivory



1M-2P-NO-10 A
With key

GW 10 145 Glossy white
GW 15 145 Satin white
GW 13 145 Sat. natural beige
GW 12 145 Satin black
GW 14 145 Glossy titanium



1M-2P-NO-16 A

GW 10 134 Glossy white
GW 15 134 Satin white
GW 13 134 Sat. natural beige
GW 12 134 Satin black
GW 14 134 Glossy titanium



1M-2P-NO-16 A
Illuminable (*)

GW 10 135 Glossy white
GW 15 135 Satin white
GW 13 135 Sat. natural beige
GW 12 135 Satin black
GW 14 135 Glossy titanium



2M-1P-NO-10 A
With illuminated name plate (*)

GW 10 191 Glossy white
GW 15 191 Satin white
GW 13 191 Sat. natural beige
GW 12 191 Satin black
GW 14 191 Glossy titanium



3M-1P-NO-10 A
With illuminated name plate (*)

GW 10 192 Glossy white
GW 15 192 Satin white
GW 13 192 Sat. natural beige
GW 12 192 Satin black
GW 14 192 Glossy titanium

(*) supplied without LED signalling unit

Command devices - rockers

One-way switches (quick wiring)



2M-1P-16 AX

GW 10 031 F Glossy white
GW 15 031 F Satin white
GW 13 031 F Sat. natural beige
GW 12 031 F Satin black
GW 14 031 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 032 F Glossy white
GW 15 032 F Satin white
GW 13 032 F Sat. natural beige
GW 12 032 F Satin black
GW 14 032 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 033 F Glossy white
GW 15 033 F Satin white
GW 13 033 F Sat. natural beige
GW 12 033 F Satin black
GW 14 033 F Glossy titanium



2M-2P-16 AX

GW 10 034 F Glossy white
GW 15 034 F Satin white
GW 13 034 F Sat. natural beige
GW 12 034 F Satin black
GW 14 034 F Glossy titanium



2M-2P-16 AX Illuminable (*)

GW 10 035 F Glossy white
GW 15 035 F Satin white
GW 13 035 F Sat. natural beige
GW 12 035 F Satin black
GW 14 035 F Glossy titanium

Two-way switches (quick wiring)



2M-1P-16 AX

GW 10 071 F Glossy white
GW 15 071 F Satin white
GW 13 071 F Sat. natural beige
GW 12 071 F Satin black
GW 14 071 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 072 F Glossy white
GW 15 072 F Satin white
GW 13 072 F Sat. natural beige
GW 12 072 F Satin black
GW 14 072 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 073 F Glossy white
GW 15 073 F Satin white
GW 13 073 F Sat. natural beige
GW 12 073 F Satin black
GW 14 073 F Glossy titanium

Intermediate switches (quick wiring)



2M-1P-16 AX

GW 10 101 F Glossy white
GW 15 101 F Satin white
GW 13 101 F Sat. natural beige
GW 12 101 F Satin black
GW 14 101 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 102 F Glossy white
GW 15 102 F Satin white
GW 13 102 F Sat. natural beige
GW 12 102 F Satin black
GW 14 102 F Glossy titanium



2M-1P-16 AX Illuminable (*)

GW 10 103 F Glossy white
GW 15 103 F Satin white
GW 13 103 F Sat. natural beige
GW 12 103 F Satin black
GW 14 103 F Glossy titanium

Push-buttons (quick wiring)



2M-1P-NO-16 A

GW 10 171 F Glossy white
GW 15 171 F Satin white
GW 13 171 F Sat. natural beige
GW 12 171 F Satin black
GW 14 171 F Glossy titanium



2M-1P-NO-16 A Illuminable (*)

GW 10 172 F Glossy white
GW 15 172 F Satin white
GW 13 172 F Sat. natural beige
GW 12 172 F Satin black
GW 14 172 F Glossy titanium



2M-1P-NO-16 A Illuminable (*)

GW 10 173 F Glossy white
GW 15 173 F Satin white
GW 13 173 F Sat. natural beige
GW 12 173 F Satin black
GW 14 173 F Glossy titanium

Combined devices (quick wiring)



Two-way switch 1P-16 AX+ Two-way switch 1P-16 AX

GW 10 078 F Glossy white
GW 15 078 F Satin white
GW 13 078 F Sat. natural beige
GW 12 078 F Satin black
GW 14 078 F Glossy titanium



Two-way switch 1P-16 AX+ Push-button 1P-NO-16 A

GW 10 159 F Glossy white
GW 15 159 F Satin white
GW 13 159 F Sat. natural beige
GW 12 159 F Satin black
GW 14 159 F Glossy titanium



Push-button 1P-NO-16 A+ Push-button 1P-NO-16 A

GW 10 160 F Glossy white
GW 15 160 F Satin white
GW 13 160 F Sat. natural beige
GW 12 160 F Satin black
GW 14 160 F Glossy titanium

Push-buttons elettronici soft-click



Universal 1M-1P-NO

GW 10 915 Glossy white
GW 15 915 Satin white
GW 13 915 Sat. natural beige
GW 12 915 Satin black
GW 14 915 Glossy titanium



1M-NO-230 V ac Backlit

GW 10 912 Glossy white
GW 15 912 Satin white
GW 13 912 Sat. natural beige
GW 12 912 Satin black
GW 14 912 Glossy titanium



For BUS inputs 1M-1P-NO Backlit

GW 10 913 Glossy white
GW 15 913 Satin white
GW 13 913 Sat. natural beige
GW 12 913 Satin black
GW 14 913 Glossy titanium



For BUS inputs 1M-1P-NO Backlit

GW 10 916 Glossy white
GW 15 916 Satin white
GW 13 916 Sat. natural beige
GW 12 916 Satin black
GW 14 916 Glossy titanium



For BUS inputs 2M-1P-NO Backlit

GW 10 917 Glossy white
GW 15 917 Satin white
GW 13 917 Sat. natural beige
GW 12 917 Satin black
GW 14 917 Glossy titanium



For BUS inputs 2M-1P-NO Backlit

GW 10 918 Glossy white
GW 15 918 Satin white
GW 13 918 Sat. natural beige
GW 12 918 Satin black
GW 14 918 Glossy titanium



With interlock 1M-1P-NO+NO

GW 10 914 Glossy white
GW 15 914 Satin white
GW 13 914 Sat. natural beige
GW 12 914 Satin black
GW 14 914 Glossy titanium

(*) supplied without LED signalling unit

Command devices - rockers

Lenses with illuminating symbols for rocker button keys



GW 10 501 Neutral
GW 10 502 Light
GW 10 503 Stair light
GW 10 504 Table light
GW 10 505 Bell
GW 10 506 Fan
GW 10 507 Key
GW 10 508 Alarm
GW 10 509 ON
GW 10 510 OFF
GW 10 511 Nurse
GW 10 512 Waitress
GW 10 513 Dimmer increase
GW 10 514 Dimmer decrease
GW 10 515 UP arrow
GW 10 516 DOWN arrow
GW 10 517 UP-DOWN arrow
GW 10 518 RIGHT-LEFT arrow
GW 10 531 One
GW 10 532 Two
GW 10 533 Three
GW 10 534 Four
GW 10 535 Five
GW 10 536 Six
GW 10 537 Seven
GW 10 538 Eight
GW 10 539 Nine
GW 10 540 Zero

Interchangeable button keys



General
GW 10 541 Glossy white
GW 15 541 Satin white
GW 13 541 Sat. natural beige
GW 12 541 Satin black
GW 14 541 Glossy titanium

Key
GW 10 543 Glossy white
GW 15 543 Satin white
GW 13 543 Sat. natural beige
GW 12 543 Satin black
GW 14 543 Glossy titanium

Bell
GW 10 544 Glossy white
GW 15 544 Satin white
GW 13 544 Sat. natural beige
GW 12 544 Satin black
GW 14 544 Glossy titanium

Vertical arrow
GW 10 545 Glossy white
GW 15 545 Satin white
GW 13 545 Sat. natural beige
GW 12 545 Satin black
GW 14 545 Glossy titanium


Horizontal arrow
GW 10 546 Glossy white
GW 15 546 Satin white
GW 13 546 Sat. natural beige
GW 12 546 Satin black
GW 14 546 Glossy titanium

Interchangeable diffusers



GW 10 547 Red
GW 10 548 Green
GW 10 549 Opal

Blanking modules




1/2M
GW 10 197 Glossy white
GW 15 197 Satin white
GW 13 197 Sat. natural beige
GW 12 197 Satin black
GW 14 197 Glossy titanium
GW 11 197 Glossy ivory

1M
GW 10 195 Glossy white
GW 15 195 Satin white
GW 13 195 Sat. natural beige
GW 12 195 Satin black
GW 14 195 Glossy titanium
GW 11 195 Glossy ivory

2M
GW 10 198 Glossy white
GW 15 198 Satin white
GW 13 198 Sat. natural beige
GW 12 198 Satin black
GW 14 198 Glossy titanium
GW 11 198 Glossy ivory

3M
GW 10 199 Glossy white
GW 15 199 Satin white
GW 13 199 Sat. natural beige
GW 12 199 Satin black
GW 14 199 Glossy titanium

Cable outlets




1M
GW 10 196 Glossy white
GW 15 196 Satin white
GW 13 196 Sat. natural beige
GW 12 196 Satin black
GW 14 196 Glossy titanium
GW 11 196 Glossy ivory



2M
GW 10 194 Glossy white
GW 15 194 Satin white
GW 13 194 Sat. natural beige
GW 12 194 Satin black
GW 14 194 Glossy titanium

Motion/presence




Motion detector 1M
230V ac - 50/60 Hz
GW 10 594 Glossy white
GW 15 594 Satin white
GW 13 594 Sat. natural beige
GW 12 594 Satin black
GW 14 594 Glossy titanium



GW 10 595
Ceiling-mounted presence detector
220-240 V ac 50/60 Hz

Relays



Latching
1M-1P-10 AX-250 V ac
GW 10 721 Glossy white
GW 15 721 Satin white
GW 13 721 Sat. natural beige
GW 12 721 Satin black
GW 14 721 Glossy titanium

Monostable
1M-1P-10 A-250 V ac-1NO/NC
GW 10 724 Glossy white
GW 15 724 Satin white
GW 13 724 Sat. natural beige
GW 12 724 Satin black
GW 14 724 Glossy titanium

Call
1M-1P-NO/NC-12 V ac/dc
GW 10 726 Glossy white
GW 15 726 Satin white
GW 13 726 Sat. natural beige
GW 12 726 Satin black
GW 14 726 Glossy titanium

ChoruSmart

Adjustment

Dimmer



▲ Resistive 100-900 W
Inductive 40-300 VA
230 V ac-50/60 Hz

GW 10 564 Glossy white
GW 15 564 Satin white
GW 13 564 Sat. natural beige
GW 12 564 Satin black
GW 14 564 Glossy titanium
GW 11 564 Glossy ivory



Resistive 100-500 W
Inductive 100-500 VA
With two-way switch
230 V ac-50/60 Hz

GW 10 567 Glossy white
GW 15 567 Satin white
GW 13 567 Sat. natural beige
GW 12 567 Satin black
GW 14 567 Glossy titanium
GW 11 567 Glossy ivory



Universal
Resist. 10-160 W - LED 4-160 W
Electr. transf. 10-160 W
With two-way switch 230 V ac-50/60 Hz

GW 10 575 Glossy white
GW 15 575 Satin white
GW 13 575 Sat. natural beige
GW 12 575 Satin black
GW 14 575 Glossy titanium



Resistive 60-500 W
Inductive 60-500 VA
230 V ac-50 Hz

GW 10 568 Glossy white
GW 15 568 Satin white
GW 13 568 Sat. natural beige
GW 12 568 Satin black
GW 14 568 Glossy titanium



Res./Ind. 40-300 W
Electr. transf. 40-300 W
LED 5-150 W
230 V ac-50/60 Hz

GW 10 572 A Glossy white
GW 15 572 A Satin white
GW 13 572 A Sat. natural beige
GW 12 572 A Satin black
GW 14 572 A Glossy titanium



Res./Ind. 40-300 W
Electr. transf. 40-300 W
LED 5-150 W
230 V ac-50/60 Hz

GW 10 573 A Glossy white
GW 15 573 A Satin white
GW 13 573 A Sat. natural beige
GW 12 573 A Satin black
GW 14 573 A Glossy titanium
GW 11 573 A Glossy ivory

Hotel components

Badge switches



2M-1P-NO-16 AX
Illuminable (*)

GW 10 039 Glossy white
GW 15 039 Satin white
GW 13 039 Sat. natural beige
GW 12 039 Satin black
GW 14 039 Glossy titanium
GW 11 039 Glossy ivory

Interchangeable button keys for rockers



DND

GW 10 731 Glossy white
GW 15 731 Satin white
GW 13 731 Sat. natural beige
GW 12 731 Satin black
GW 14 731 Glossy titanium



MUR

GW 10 732 Glossy white
GW 15 732 Satin white
GW 13 732 Sat. natural beige
GW 12 732 Satin black
GW 14 732 Glossy titanium



DND + MUR

GW 10 733 Glossy white
GW 15 733 Satin white
GW 13 733 Sat. natural beige
GW 12 733 Satin black
GW 14 733 Glossy titanium

Double indicator lamps



1M - Opal
DND + MUR
Illuminable (*)

GW 10 736 Glossy white
GW 15 736 Satin white
GW 13 736 Sat. natural beige
GW 12 736 Satin black
GW 14 736 Glossy titanium

▲ Articles designed exclusively for export to a limited number of Countries not belonging to the EU (or candidates for membership) or the European Free Trade Association. Check with Gewiss Customer Service to make sure the product meets the regulation of the Country in question before importing it.

(*) supplied without LED signalling unit

Command devices - axial

Switch modules EVO



GW 10 671
1M
100-240 V ac - 50/60 Hz



GW 10 672
2M
100-240 V ac - 50/60 Hz

Dimmer modules EVO



GW 10 673
1M
100-240 V ac - 50/60 Hz



GW 10 674
2M
100-240 V ac - 50/60 Hz

Roller-shutter modules EVO



GW 10 675
1M
100-240 V ac - 50/60 Hz



GW 10 676
2M
100-240 V ac - 50/60 Hz

Auxiliary modules



GW 10 677
1 command
1M
100-240 V ac - 50/60 Hz



GW 10 678
1 command
2M
100-240 V ac - 50/60 Hz



GW 10 679
2 commands
1M
100-240 V ac - 50/60 Hz



GW 10 680
2 commands
2M
100-240 V ac - 50/60 Hz

Interchangeable button keys for axial modules

Button key - 1M
To be completed with lens

GW 10 551 S Glossy white
GW 15 551 S Satin white
GW 13 551 S Sat. natural beige
GW 12 551 S Satin black
GW 14 551 S Glossy titanium

Button key - 2M
To be completed with lens

GW 10 552 S Glossy white
GW 15 552 S Satin white
GW 13 552 S Sat. natural beige
GW 12 552 S Satin black
GW 14 552 S Glossy titanium

Button key - 1M
To be completed with 2 lenses

GW 10 553 S Glossy white
GW 15 553 S Satin white
GW 13 553 S Sat. natural beige
GW 12 553 S Satin black
GW 14 553 S Glossy titanium

Button key - 2M
To be completed with 2 lenses

GW 10 554 S Glossy white
GW 15 554 S Satin white
GW 13 554 S Sat. natural beige
GW 12 554 S Satin black
GW 14 554 S Glossy titanium

Button key - 1M
With diffuser

GW 10 555 S Glossy white
GW 15 555 S Satin white
GW 13 555 S Sat. natural beige
GW 12 555 S Satin black
GW 14 555 S Glossy titanium

Button key - 2M
With diffuser

GW 10 556 S Glossy white
GW 15 556 S Satin white
GW 13 556 S Sat. natural beige
GW 12 556 S Satin black
GW 14 556 S Glossy titanium

Button key - 1M
With 2 diffusers

GW 10 557 S Glossy white
GW 15 557 S Satin white
GW 13 557 S Sat. natural beige
GW 12 557 S Satin black
GW 14 557 S Glossy titanium

Button key - 2M
With 2 diffusers

GW 10 558 S Glossy white
GW 15 558 S Satin white
GW 13 558 S Sat. natural beige
GW 12 558 S Satin black
GW 14 558 S Glossy titanium

Lenses with illuminating symbols for axial button keys

GW 10 501 A
Neutral



GW 10 502 A
Light



GW 10 503 A
Stair light



GW 10 504 A
Table light



GW 10 505 A
Bell



GW 10 506 A
Burglar alarm

GW 10 507 A
Key



GW 10 508 A
ON OFF

GW 10 509 A
ON

GW 10 510 A
OFF



GW 10 511 A
Socket-outlet

GW 10 512 A
Dimmer



GW 10 513 A
Dimmer increase



GW 10 514 A
Dimmer decrease

GW 10 515 A
Arrow

GW 10 516 A
Open

GW 10 517 A
Close



GW 10 518 A
Roller shutter



GW 10 519 A
Roller shutter up



GW 10 520 A
Roller shutter down



GW 10 521 A
Curtain open



GW 10 522 A
Curtain close



GW 10 523 A
Piantana



GW 10 524 A
Lampadario



GW 10 525 A
Applique

GW 10 526 A
Luce corridoio



GW 10 527 A
Scenario



GW 10 528 A
Party



GW 10 529 A
In



GW 10 530 A
Out



GW 10 531 A
Good morning



GW 10 532 A
Good night



GW 10 533 A
TV



GW 10 534 A
Riscaldamento



GW 10 535 A
Raffrescamento



GW 10 536 A
Riscaldamento/
Raffrescamento



GW 10 537 A
Comfort



GW 10 538 A
Precomfort



GW 10 539 A
Economy



GW 10 540 A
Auto




GW 10 541 A
Do not disturb
(DND)



GW 10 542 A
Make up the room
(MUR)

Command devices - touch

Switch module interchangeable symbols



GW 10 922
1M
100-240 V ac
50/60 Hz

Dimmer module interchangeable symbols



GW 10 923
1M
100-240 V ac
50/60 Hz

Roller-shutter module interchangeable symbols



GW 10 921
1M
100-240 V ac
50/60 Hz

Auxiliary modules interchangeable symbols



GW 10 924
1 command - 1M
100-240 V ac
50/60 Hz



GW 10 925
2 commands - 1M
100-240 V ac
50/60 Hz

ICE TOUCH plates in glass



GW 16 955 CB Glossy white
GW 16 955 CL Glossy natural beige
GW 16 955 CN Glossy black
GW 16 955 CT Glossy titanium

Power

Italian



GW 10 201
Glossy white
GW 15 201
Satin white
GW 13 201
Sat. natural beige
GW 12 201
Satin black
GW 14 201
Glossy titanium

2P+E-10 A-250 V ac



GW 10 203
Glossy white
GW 15 203
Satin white
GW 13 203
Sat. natural beige
GW 12 203
Satin black
GW 14 203
Glossy titanium
GW 11 203
Glossy ivory

2P+E-16 A-250 V ac
Dual amperage



GW 10 213
2P+E-16 A-250 V ac
Dual amperage



GW 10 223
2P+E-16 A-250 V ac
Dual amperage



GW 10 233
2P+E-16 A-250 V ac
Dual amperage



GW 10 208
Glossy white
GW 15 208
Satin white
GW 13 208
Sat. natural beige
GW 12 208
Satin black
GW 14 208
Glossy titanium

2x2P+E-16 A-250 V ac
Dual amperage



GW 10 209
Glossy white
GW 15 209
Satin white
GW 13 209
Sat. natural beige
GW 12 209
Satin black
GW 14 209
Glossy titanium

3x2P+E-16 A-250 V ac
Dual amperage

Italian/German



GW 10 204
Glossy white
GW 15 204
Satin white
GW 13 204
Sat. natural beige
GW 12 204
Satin black
GW 14 204
Glossy titanium

2P+E-16 A-250 V ac
Dual amperage



GW 10 205
Glossy white
GW 15 205
Satin white
GW 13 205
Sat. natural beige
GW 12 205
Satin black
GW 14 205
Glossy titanium

2P+E-16 A-250 V ac



GW 10 214
2P+E-16 A-250 V ac
Dual amperage - Illuminable (*)



GW 10 224
2P+E-16 A-250 V ac
Dual amperage - Illuminable (*)



GW 10 234
2P+E-16 A-250 V ac
Dual amperage - Illuminable (*)

German



GW 10 241
Glossy white
GW 15 241
Satin white
GW 13 241
Sat. natural beige
GW 12 241
Satin black
GW 14 241
Glossy titanium
GW 11 241
Glossy ivory

2P+E-16 A-250 V ac



GW 10 242
Glossy white
GW 15 242
Satin white
GW 13 242
Sat. natural beige
GW 12 242
Satin black
GW 14 242
Glossy titanium
GW 11 242
Glossy ivory

2P+E-16 A-250 V ac
With lid - IP40



GW 10 341
Glossy white
GW 15 341
Satin white
GW 13 341
Sat. natural beige
GW 12 341
Satin black
GW 14 341
Glossy titanium

2P+E-16 A-250 V ac
Front-tightening terminals



GW 10 241 F
Glossy white
GW 15 241 F
Satin white
GW 13 241 F
Sat. natural beige
GW 12 241 F
Satin black
GW 14 241 F
Glossy titanium

2P+E-16 A-250 V ac
Quick wiring



GW 10 251
2P+E-16 A-250 V ac



GW 10 351
2P+E-16 A-250 V ac
Front-tightening terminals



GW 10 251 F
2P+E-16 A-250 V ac
Quick wiring

French



GW 10 246
Glossy white
GW 15 246
Satin white
GW 13 246
Sat. natural beige
GW 12 246
Satin black
GW 14 246
Glossy titanium
GW 11 246
Glossy ivory

2P-16 A-250 V ac



GW 10 247
Glossy white
GW 15 247
Satin white
GW 13 247
Sat. natural beige
GW 12 247
Satin black
GW 14 247
Glossy titanium
GW 11 247
Glossy ivory

2P+E-16 A-250 V ac



GW 10 248
Glossy white
GW 15 248
Satin white
GW 13 248
Sat. natural beige
GW 12 248
Satin black
GW 14 248
Glossy titanium

2P+E-16 A-250 V ac
Front-tightening terminals



GW 10 247 F
Glossy white
GW 15 247 F
Satin white
GW 13 247 F
Sat. natural beige
GW 12 247 F
Satin black
GW 14 247 F
Glossy titanium

2P+E-16 A-250 V ac
Quick wiring



GW 10 258
2P+E-16 A-250 V ac
Front-tightening terminals



GW 10 257 F
2P+E-16 A-250 V ac
Quick wiring



GW 10 260
Accessory for dedicated lines

USA



GW 10 286
Glossy white
GW 15 286
Satin white
GW 13 286
Sat. natural beige
GW 12 286
Satin black
GW 14 286
Glossy titanium

2P+E-15 A-250/125 V ac

Euro-American



GW 10 287
Glossy white
GW 15 287
Satin white
GW 13 287
Sat. natural beige
GW 12 287
Satin black
GW 14 287
Glossy titanium
GW 11 287
Glossy ivory

2P-15 A-250/125 V ac



GW 10 288
Glossy white
GW 15 288
Satin white
GW 13 288
Sat. natural beige
GW 12 288
Satin black
GW 14 288
Glossy titanium
GW 11 288
Glossy ivory

2P+E-15 A-250/125 V ac

Multistandard



GW 10 310
Glossy white
GW 15 310
Satin white
GW 13 310
Sat. natural beige
GW 12 310
Satin black
GW 14 310
Glossy titanium

2P+E-13 A-250 V ac
15 A-127 V ac

(*) supplied without LED signalling unit

Power

Swiss



2P+E-10 A-250 V ac
Type 13

GW 10 346
Glossy white

Israeli



2P+E-16 A-250 V ac
Illuminable (*)

GW 10 281
Glossy white
GW 15 281
Satin white
GW 13 281
Sat. natural beige
GW 12 281
Satin black
GW 14 281
Glossy titanium
GW 11 281
Glossy ivory



GW 10 291
2P+E-16 A-250 V ac
Illuminable (*)



2P+E-10 A-250 V ac

GW 10 282
Glossy white
GW 15 282
Satin white
GW 13 282
Sat. natural beige
GW 12 282
Satin black
GW 14 282
Glossy titanium

British



2P+E-13 A-250 V ac

GW 10 296
Glossy white
GW 15 296
Satin white
GW 13 296
Sat. natural beige
GW 12 296
Satin black
GW 14 296
Glossy titanium



2P+E-15 A-250 V ac

GW 10 297
Glossy white
GW 15 297
Satin white
GW 13 297
Sat. natural beige
GW 12 297
Satin black
GW 14 297
Glossy titanium

Indian/South African



2P+E-16 A-250 V ac

GW 10 298
Glossy white
GW 15 298
Satin white
GW 13 298
Sat. natural beige
GW 12 298
Satin black
GW 14 298
Glossy titanium



2P+E-16 A-250 V ac

GW 10 299
Glossy white
GW 15 299
Satin white
GW 13 299
Sat. natural beige
GW 12 299
Satin black
GW 14 299
Glossy titanium

Australian



2P+E-10 A-250 V ac

GW 10 306
Glossy white
GW 15 306
Satin white
GW 13 306
Sat. natural beige
GW 12 306
Satin black
GW 14 306
Glossy titanium



2P+E-15 A-250 V ac

GW 10 307
Glossy white
GW 15 307
Satin white
GW 13 307
Sat. natural beige
GW 12 307
Satin black
GW 14 307
Glossy titanium

Argentinian



2P+E-10 A-250 V ac

GW 10 301
Glossy white
GW 15 301
Satin white
GW 13 301
Sat. natural beige
GW 12 301
Satin black
GW 14 301
Glossy titanium

Chinese



2P+E-10 A-250 V ac

GW 10 391
Glossy white
GW 15 391
Satin white
GW 13 391
Sat. natural beige
GW 12 391
Satin black
GW 14 391
Glossy titanium



2P+E-16 A-250 V ac

GW 10 392
Glossy white
GW 15 392
Satin white
GW 13 392
Sat. natural beige
GW 12 392
Satin black
GW 14 392
Glossy titanium

Interlocked switched socket-outlets



2P+E-16 A-230 V ac

GW 10 311
Glossy white
GW 15 311
Satin white
GW 13 311
Sat. natural beige
GW 12 311
Satin black
GW 14 311
Glossy titanium



2P+E-16 A-230 V ac

GW 10 312
Glossy white
GW 15 312
Satin white
GW 13 312
Sat. natural beige
GW 12 312
Satin black
GW 14 312
Glossy titanium



2P+E-16 A-230 V ac

GW 10 321
Glossy white
GW 15 321
Satin white
GW 13 321
Sat. natural beige
GW 12 321
Satin black
GW 14 321
Glossy titanium



2P+E-16 A-230 V ac

GW 10 322
Glossy white
GW 15 322
Satin white
GW 13 322
Sat. natural beige
GW 12 322
Satin black
GW 14 322
Glossy titanium

Shaver socket-outlet



230 V ac-50/60 Hz

GW 10 331
Glossy white
GW 15 331
Satin white
GW 13 331
Sat. natural beige
GW 12 331
Satin black
GW 14 331
Glossy titanium
GW 11 331
Glossy ivory

(*) supplied without LED signalling unit

Data

TV (IEC male)



0 dB

GW 10 361 Glossy white
GW 15 361 Satin white
GW 13 361 Sat. natural beige
GW 12 361 Satin black
GW 14 361 Glossy titanium
GW 11 361 Glossy ivory



5 dB

GW 10 362 Glossy white
GW 15 362 Satin white
GW 13 362 Sat. natural beige
GW 12 362 Satin black
GW 14 362 Glossy titanium



10 dB

GW 10 363 Glossy white
GW 15 363 Satin white
GW 13 363 Sat. natural beige
GW 12 363 Satin black
GW 14 363 Glossy titanium

TV-SAT (F female)



0 dB

GW 10 371 Glossy white
GW 15 371 Satin white
GW 13 371 Sat. natural beige
GW 12 371 Satin black
GW 14 371 Glossy titanium
GW 11 371 Glossy ivory



5 dB

GW 10 372 Glossy white
GW 15 372 Satin white
GW 13 372 Sat. natural beige
GW 12 372 Satin black
GW 14 372 Glossy titanium



10 dB

GW 10 373 Glossy white
GW 15 373 Satin white
GW 13 373 Sat. natural beige
GW 12 373 Satin black
GW 14 373 Glossy titanium

TV and TV-SAT accessories



GW 20 277
Terminal resistance
75 ohm

TV-FM-SAT



TV-FM
0 dB

GW 10 381 Glossy white
GW 15 381 Satin white
GW 13 381 Sat. natural beige
GW 12 381 Satin black
GW 14 381 Glossy titanium
GW 11 381 Glossy ivory



TV-FM-SAT
0 dB

GW 10 382 Glossy white
GW 15 382 Satin white
GW 13 382 Sat. natural beige
GW 12 382 Satin black
GW 14 382 Glossy titanium



TV-SAT
0 dB

GW 10 383 Glossy white
GW 15 383 Satin white
GW 13 383 Sat. natural beige
GW 12 383 Satin black
GW 14 383 Glossy titanium
GW 11 383 Glossy ivory

TV-SAT



IEC male
0dB

GW 10 367 Glossy white
GW 15 367 Satin white
GW 13 367 Sat. natural beige
GW 12 367 Satin black
GW 14 367 Glossy titanium



F female
0dB

GW 10 377 Glossy white
GW 15 377 Satin white
GW 13 377 Sat. natural beige
GW 12 377 Satin black
GW 14 377 Glossy titanium

Covers for antenna sockets



For combined
TV-R sockets

GW 10 386 Glossy white
GW 15 386 Satin white
GW 13 386 Sat. natural beige
GW 12 386 Satin black
GW 14 386 Glossy titanium



For combined
TV-R-SAT sockets

GW 10 387 Glossy white
GW 15 387 Satin white
GW 13 387 Sat. natural beige
GW 12 387 Satin black
GW 14 387 Glossy titanium

Telephone sockets



RJ11

GW 10 401 Glossy white
GW 15 401 Satin white
GW 13 401 Sat. natural beige
GW 12 401 Satin black
GW 14 401 Glossy titanium
GW 11 401 Glossy ivory



British 6
contacts

GW 10 406 Glossy white
GW 15 406 Satin white
GW 13 406 Sat. natural beige
GW 12 406 Satin black
GW 14 406 Glossy titanium



RJ11

GW 10 409 Glossy white
GW 15 409 Satin white
GW 13 409 Sat. natural beige
GW 12 409 Satin black
GW 14 409 Glossy titanium

Adapters for optical fiber



GW 38 335
Angled SC/APC

Data sockets



RJ45 cat. 5e
UTP

GW 10 421 Glossy white
GW 15 421 Satin white
GW 13 421 Sat. natural beige
GW 12 421 Satin black
GW 14 421 Glossy titanium
GW 11 421 Glossy ivory



RJ45 cat. 5e
FTP

GW 10 422 Glossy white
GW 15 422 Satin white
GW 13 422 Sat. natural beige
GW 12 422 Satin black
GW 14 422 Glossy titanium
GW 11 422 Glossy ivory



RJ45 cat. 6
UTP

GW 10 423 Glossy white
GW 15 423 Satin white
GW 13 423 Sat. natural beige
GW 12 423 Satin black
GW 14 423 Glossy titanium
GW 11 423 Glossy ivory



RJ45 cat. 6
FTP

GW 10 424 Glossy white
GW 15 424 Satin white
GW 13 424 Sat. natural beige
GW 12 424 Satin black
GW 14 424 Glossy titanium
GW 11 424 Glossy ivory



AMP/Keystone
Jack adapters

GW 10 431 Glossy white
GW 15 431 Satin white
GW 13 431 Sat. natural beige
GW 12 431 Satin black
GW 14 431 Glossy titanium
GW 11 431 Glossy ivory



SYSTIMAX
Commscope
adapters

GW 10 438 Glossy white
GW 15 438 Satin white
GW 13 438 Sat. natural beige
GW 12 438 Satin black
GW 14 438 Glossy titanium

AMP/Keystone Jack
adapters

GW 10 433 Glossy white
GW 15 433 Satin white
GW 13 433 Sat. natural beige
GW 12 433 Satin black
GW 14 433 Glossy titanium

SELV sockets



2P-6 A-24 V

GW 10 451 Glossy white
GW 15 451 Satin white
GW 13 451 Sat. natural beige
GW 12 451 Satin black
GW 14 451 Glossy titanium



2P-6 A-24 V
Polarised

GW 10 452 Glossy white
GW 15 452 Satin white
GW 13 452 Sat. natural beige
GW 12 452 Satin black
GW 14 452 Glossy titanium

Audio and video sockets



Dual RCA

GW 10 453 Glossy white
GW 15 453 Satin white
GW 13 453 Sat. natural beige
GW 12 453 Satin black
GW 14 453 Glossy titanium



For loudspeaker

GW 10 454 Glossy white
GW 15 454 Satin white
GW 13 454 Sat. natural beige
GW 12 454 Satin black
GW 14 454 Glossy titanium



Speaker connector

GW 10 458 Glossy white
GW 15 458 Satin white
GW 13 458 Sat. natural beige
GW 12 458 Satin black
GW 14 458 Glossy titanium

USB and HDMI couplers and sockets



USB socket

GW 10 459 Glossy white
GW 15 459 Satin white
GW 13 459 Sat. natural beige
GW 12 459 Satin black
GW 14 459 Glossy titanium



GW 38 056
HDMI coupler



GW 38 057
USB coupler

USB chargers - 5V



Dual USB charger
Type A+C - 1M-3 A
100-240 V ac - 50/60 Hz

GW 10 449 Glossy white
GW 15 449 Satin white
GW 13 449 Sat. natural beige
GW 12 449 Satin black
GW 14 449 Glossy titanium

USB chargers Power Delivery



USB charger Type C 30W
Power Delivery
100-240 V ac - 50/60 Hz

GW 10 415 Glossy white
GW 15 415 Satin white
GW 13 415 Sat. natural beige
GW 12 415 Satin black
GW 14 415 Glossy titanium



USB charger Type C 63W
Power Delivery
100-240 V ac - 50/60 Hz

GW 10 417 Glossy white
GW 15 417 Satin white
GW 13 417 Sat. natural beige
GW 12 417 Satin black
GW 14 417 Glossy titanium

Protection

One-way switches Miniature circuit breakers



1P-6 A-3 kA
C-characteristic

GW 10 461 Glossy white
GW 15 461 Satin white
GW 13 461 Sat. natural beige
GW 12 461 Satin black
GW 14 461 Glossy titanium



1P-10 A-3 kA
C-characteristic

GW 10 462 Glossy white
GW 15 462 Satin white
GW 13 462 Sat. natural beige
GW 12 462 Satin black
GW 14 462 Glossy titanium



1P-16 A-3 kA
C-characteristic

GW 10 463 Glossy white
GW 15 463 Satin white
GW 13 463 Sat. natural beige
GW 12 463 Satin black
GW 14 463 Glossy titanium



1P+N-6 A-3 kA
C-characteristic

GW 10 466 Glossy white
GW 15 466 Satin white
GW 13 466 Sat. natural beige
GW 12 466 Satin black
GW 14 466 Glossy titanium



1P+N-10
A-3 kA
C-characteristic

GW 10 467 Glossy white
GW 15 467 Satin white
GW 13 467 Sat. natural beige
GW 12 467 Satin black
GW 14 467 Glossy titanium



1P+N-16
A-3 kA
C-characteristic

GW 10 468 Glossy white
GW 15 468 Satin white
GW 13 468 Sat. natural beige
GW 12 468 Satin black
GW 14 468 Glossy titanium

Protection devices



Fuse holder
In MAX=16 A

GW 10 491 Glossy white
GW 15 491 Satin white
GW 13 491 Sat. natural beige
GW 12 491 Satin black
GW 14 491 Glossy titanium



Surge
protection

GW 10 492 Glossy white
GW 15 492 Satin white
GW 13 492 Sat. natural beige
GW 12 492 Satin black
GW 14 492 Glossy titanium

Residual miniature circuit breakers



1P+N-6 A-3 kA-10 mA
C-characteristic-A type

GW 10 482 Glossy white
GW 15 482 Satin white
GW 13 482 Sat. natural beige
GW 12 482 Satin black
GW 14 482 Glossy titanium



1P+N-10 A-3 kA-10 mA
C-characteristic-A type

GW 10 485 Glossy white
GW 15 485 Satin white
GW 13 485 Sat. natural beige
GW 12 485 Satin black
GW 14 485 Glossy titanium



1P+N-16 A-3 kA-10 mA
C-characteristic-A type

GW 10 488 Glossy white
GW 15 488 Satin white
GW 13 488 Sat. natural beige
GW 12 488 Satin black
GW 14 488 Glossy titanium



1P+N-6 A-3 kA-30 mA
C-characteristic-A type

GW 10 483 Glossy white
GW 15 483 Satin white
GW 13 483 Sat. natural beige
GW 12 483 Satin black
GW 14 483 Glossy titanium



1P+N-10 A-3 kA-30 mA
C-characteristic-A type

GW 10 486 Glossy white
GW 15 486 Satin white
GW 13 486 Sat. natural beige
GW 12 486 Satin black
GW 14 486 Glossy titanium



1P+N-16 A-3 kA-30 mA
C-characteristic-A type

GW 10 489 Glossy white
GW 15 489 Satin white
GW 13 489 Sat. natural beige
GW 12 489 Satin black
GW 14 489 Glossy titanium

Signalling

Anti black-out lamps



230 V ac-50/60 Hz
Extractable

GW 10 661 Glossy white
GW 13 661 Sat. natural beige
GW 12 661 Satin black
GW 14 661 Glossy titanium



230 V ac-50/60 Hz

GW 10 662 Glossy white
GW 15 662 Satin white
GW 13 662 Sat. natural beige
GW 12 662 Satin black
GW 14 662 Glossy titanium
GW 11 662 Glossy ivory

Emergency lamps



230 V ac-50/60 Hz

GW 10 663 Glossy white
GW 15 663 Satin white
GW 13 663 Sat. natural beige
GW 12 663 Satin black
GW 14 663 Glossy titanium



230 V ac-50/60 Hz

GW 10 666 Glossy white
GW 15 666 Satin white
GW 13 666 Sat. natural beige
GW 12 666 Satin black
GW 14 666 Glossy titanium

Ringers



12 V ac-50 Hz

GW 10 601 Glossy white
GW 15 601 Satin white
GW 13 601 Sat. natural beige
GW 12 601 Satin black
GW 14 601 Glossy titanium



230 V ac-50 Hz

GW 10 602 Glossy white
GW 15 602 Satin white
GW 13 602 Sat. natural beige
GW 12 602 Satin black
GW 14 602 Glossy titanium
GW 11 602 Glossy ivory

Buzzers



12 V ac-50 Hz

GW 10 606 Glossy white
GW 15 606 Satin white
GW 13 606 Sat. natural beige
GW 12 606 Satin black
GW 14 606 Glossy titanium



230 V ac-50 Hz

GW 10 607 Glossy white
GW 15 607 Satin white
GW 13 607 Sat. natural beige
GW 12 607 Satin black
GW 14 607 Glossy titanium

Single indicator lamps



1/2M - Opal
Illuminable (*)

GW 10 641 Glossy white
GW 15 641 Satin white
GW 13 641 Sat. natural beige
GW 12 641 Satin black
GW 14 641 Glossy titanium



1/2M - Green
Illuminable (*)

GW 10 642 Glossy white
GW 15 642 Satin white
GW 13 642 Sat. natural beige
GW 12 642 Satin black
GW 14 642 Glossy titanium



1/2M - Red
Illuminable (*)

GW 10 643 Glossy white
GW 15 643 Satin white
GW 13 643 Sat. natural beige
GW 12 643 Satin black
GW 14 643 Glossy titanium



1/2M - Amber
Illuminable (*)

GW 10 644 Glossy white
GW 15 644 Satin white
GW 13 644 Sat. natural beige
GW 12 644 Satin black
GW 14 644 Glossy titanium



1M - Opal
Illuminable (*)

GW 10 621 Glossy white
GW 15 621 Satin white
GW 13 621 Sat. natural beige
GW 12 621 Satin black
GW 14 621 Glossy titanium



1M - Green
Illuminable (*)

GW 10 622 Glossy white
GW 15 622 Satin white
GW 13 622 Sat. natural beige
GW 12 622 Satin black
GW 14 622 Glossy titanium



1M - Red
Illuminable (*)

GW 10 623 Glossy white
GW 15 623 Satin white
GW 13 623 Sat. natural beige
GW 12 623 Satin black
GW 14 623 Glossy titanium
GW 11 623 Glossy ivory



1M - Amber
Illuminable (*)

GW 10 624 Glossy white
GW 15 624 Satin white
GW 13 624 Sat. natural beige
GW 12 624 Satin black
GW 14 624 Glossy titanium

Double indicator lamps



1M - Opal
Illuminable (*)

GW 10 628 Glossy white
GW 15 628 Satin white
GW 13 628 Sat. natural beige
GW 12 628 Satin black
GW 14 628 Glossy titanium



1M - Red/Green
Illuminable (*)

GW 10 629 Glossy white
GW 15 629 Satin white
GW 13 629 Sat. natural beige
GW 12 629 Satin black
GW 14 629 Glossy titanium

Protruding indicator lamps



2M-12 V ac/dc-230 V ac-50/60 Hz
Opal

GW 10 631 Glossy white
GW 15 631 Satin white
GW 13 631 Sat. natural beige
GW 12 631 Satin black
GW 14 631 Glossy titanium



2M-12 V ac/dc-230 V ac-50/60 Hz
Green

GW 10 632 Glossy white
GW 15 632 Satin white
GW 13 632 Sat. natural beige
GW 12 632 Satin black
GW 14 632 Glossy titanium



2M-12 V ac/dc-230 V ac-50/60 Hz
Red

GW 10 633 Glossy white
GW 15 633 Satin white
GW 13 633 Sat. natural beige
GW 12 633 Satin black
GW 14 633 Glossy titanium



2M-12 V ac/dc-230 V ac-50/60 Hz
Amber

GW 10 634 Glossy white
GW 15 634 Satin white
GW 13 634 Sat. natural beige
GW 12 634 Satin black
GW 14 634 Glossy titanium

Stair riser lamps



2M
Opal

GW 10 651 Glossy white
GW 15 651 Satin white
GW 13 651 Sat. natural beige
GW 12 651 Satin black
GW 14 651 Glossy titanium



4M
Opal

GW 10 656 Glossy white
GW 15 656 Satin white
GW 13 656 Sat. natural beige
GW 12 656 Satin black
GW 14 656 Glossy titanium

(*) supplied without LED signalling unit

Energy, climate and comfort management

Thermoregulation



Thermostat/Chronothermostat
Thermo ICE WiFi
110-230 V ac-50/60 Hz
Wall-mounting

GW 16 970 CB
Glossy white
GW 16 970 CL
Glossy natural beige
GW 16 970 CN
Glossy black
GW 16 970 CT
Glossy titanium



Thermostat
230 V ac-50/60 Hz

GW 10 705
Glossy white
GW 15 705
Satin white
GW 13 705
Sat. natural beige
GW 12 705
Satin black
GW 14 705
Glossy titanium
GW 11 705
Glossy ivory



Thermostat
100-240 V ac - 50/60 Hz

GW 10 709
Glossy white
GW 15 709
Satin white
GW 13 709
Sat. natural beige
GW 12 709
Satin black
GW 14 709
Glossy titanium

Electronic timers



230 V ac-50/60 Hz
Daily/Weekly

GW 10 581
Glossy white
GW 12 581
Satin black
GW 14 581
Glossy titanium

Technical alarms

Detectors



GPL
12 V ac/dc

GW 10 711
Glossy white
GW 12 711
Satin black
GW 14 711
Glossy titanium



Methane gas
12 V ac/dc

GW 10 712
Glossy white
GW 15 712
Satin white
GW 13 712
Sat. natural beige
GW 12 712
Satin black
GW 14 712
Glossy titanium



GW A1 514
Water sensor Zigbee
Battery powered



GW A1 521
1-channel actuator Zigbee
230 V ac-50 Hz

Accessories

GW A1 541
Wall-mounting support for
water sensor



GW 10 720
Power supply
100/240 V ac-50/60 Hz
12 V dc



GW 30 522
Gas solenoid valve
3/4"-230 V ac-12 VA

Accessories

LED signalling units



230 V ac-50/60 Hz

GW 10 881
Blu
GW 10 882
White
GW 10 883
Red
GW 10 884
Green
GW 10 885
Amber



GW 10 894
White
12/24 V ac/dc

Cartridge lamps



GW 20 902
White
12 V-S6x36



GW 20 903
White
24 V-S6x36

Keys



GW 20 901
For one-way/two-
way switches



GW 30 912
For push-buttons

Standard supports for ONE, GEO, EGO, LUX and ICE plates

Supports for round/square boxes




GW 16 821
With clutches - 2 modules

GW 16 823
With long clutches - 2 modules



GW 16 822
For screws (not included) - 2
modules

Support for round/square and rectangular boxes



GW 16 802
For screws - 2 modules

Protective covers for painting



For rectangular
supports

GW 16 873
3 modules
GW 16 874
4 modules
GW 16 877 N
7 modules



GW 16 871
For square supports

Supports for rectangular boxes



GW 16 803
For screws - 3 modules



GW 16 804
For screws - 4 modules

GW 16 824
For screws (not included) for French boxes



GW 16 806
For screws - 6 modules

GW 16 825
For screws (not included) for French boxes



GW 16 807 N
For screws - 7 modules



GW 16 808
For screws - 4+4 modules



GW 16 812
For screws - 6+6 modules

ChoruSmart

Glossy white modular devices





The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in glossy white, bright and versatile, they include rocker button keys with ½, 1 and 2 modules to optimise space, and axial keys in EVO or SMART version for advanced functions. The front attachment system facilitates assembly and release without removing the support.

COMMAND - GLOSSY WHITE VERSION

Command devices - rockers - screw terminals



GW 10 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 10 001	1P - 16AX	Neutral	200 W	12/96
GW 10 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 10 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 1/2				
GW 10 021	1P - 10AX	Neutral	100 W	12/24
GW 10 022	1P - 10AX illuminable	With diffuser	100 W	6/24
No. modules: 2				
GW 10 031	1P - 16AX	Neutral	200 W	6/24
GW 10 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 10 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 10 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 10 004	2P - 16 AX	Neutral	0/1	200 W	12/48
GW 10 005	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	12/24
GW 10 006	2P - 10AX	With key	0/1	100 W	1/12
No. modules: 2					
GW 10 034	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 10 035	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW10006 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 10 007

One-way switch 2P - 250V ac - heavy duty loads

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 10 007	2P - 25 AX	Neutral	0/1	250 W	12/24

APPLICATIONS: suitable for particular heavy-duty loads (e.g. fluorescent lamp batteries) or high-consumption devices (e.g. ovens, air-conditioners, boilers, etc.).



GW 10 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 10 051	1P - 16AX	Neutral	200 W	12/96
GW 10 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 10 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
GW 10 054	1P - 10AX	With key	100 W	1/12
No. modules: 1/2				
GW 10 061	1P - 10AX	Neutral	100 W	6/24
No. modules: 2				
GW 10 071	1P - 16AX	Neutral	200 W	6/24
GW 10 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 10 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW10054 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 10 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 10 091	1P - 16AX	Neutral	200 W	12/48
GW 10 092	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 10 093	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 10 101	1P - 16AX	Neutral	200 W	6/12
GW 10 102	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 10 103	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 10 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 10 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 10 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 10 122

Three-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 10 122	2P - 10AX	Neutral	UP - DOWN	100 W	12/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

ChoruSmart - Modular devices



GW 10 131

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 10 131	1P NO - 16A	Neutral	-	12/96
GW 10 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 10 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 10 136	1P NO - 16A	Pull-cord	-	1/12
GW 10 137	1P NC - 16A	Neutral	O red	12/24
GW 10 138	1P NC+NO - 16 A	Stop	Red	12/24
GW 10 139	1P NO+NC - 16 A	Start	Green	12/24
GW 10 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 10 141	1P NO+NO - 16 A	Double	-	12/24
GW 10 142	1P NO - 16A illuminable	Green diffuser	-	12/24
GW 10 143	1P NO - 16A illuminable	Red diffuser	-	12/24
GW 10 144	1P NO - 16A illuminable	Opal diffuser	-	12/24
GW 10 151	1P NO - 16A illuminable	With replaceable neutral lens	Light	12/24
GW 10 152	1P NO - 16A illuminable	With replaceable neutral lens	Key	12/24
GW 10 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 1/2				
GW 10 161	1P NO - 10A	Neutral	-	6/24
GW 10 162	1P NO - 10A illuminable	With diffuser	-	6/24
No. modules: 2				
GW 10 171	1P NO - 16A	Neutral	-	6/24
GW 10 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 10 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW10136 Cord in insulating material, 140cm long, with red knob.

GW10140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW10141 independent push-buttons that can also be activated simultaneously.



GW 10 134

Push-buttons 2P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 10 134	2P NO - 16A	Neutral	O	12/24
GW 10 135	2P NO - 10A illuminable	With replaceable neutral lens	-	12/24
GW 10 145	2P NO - 10A	With key	-	1/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

NOTES: GW10145 equipped with 2 keys. Spare keys: GW30912.



GW 10 191

Push-buttons 1P with illuminated name plate - 250V ac

Code	Description	Lamp voltage	Lamp	Lamp power	Pack Carton
No. modules: 2					
GW 10 191	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm (not included)	2 W	6/24
No. modules: 3					
GW 10 192	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	4/16

CHARACTERISTICS: lamp not included.

Command devices - rockers - quick wiring terminals



GW 10 031 F

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 10 031 F	1P - 16AX	Neutral	200 W	6/24
GW 10 032 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 10 033 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 10 034 F

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 10 034 F	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 10 035 F	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 10 071 F

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 10 071 F	1P - 16AX	Neutral	200 W	6/24
GW 10 072 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 10 073 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 10 101 F

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 10 101 F	1P - 16AX	Neutral	200 W	6/12
GW 10 102 F	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 10 103 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 10 171 F

Push-buttons 1P - 250V ac

Code	Description	Button key	Pack Carton
No. modules: 2			
GW 10 171 F	1P NO - 16A	Neutral	6/24
GW 10 172 F	1P NO - 16A illuminable	With diffuser	6/24
GW 10 173 F	1P NO - 16A illuminable	With replaceable neutral lens	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.

ChoruSmart - Modular devices



GW 10 160 F

Combined command devices - rockers - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 10 078 F	Twin two-way switch 1P - 16 AX	Neutral	-	200 W	6/24
GW 10 159 F	Two-way switch 1P - 16 AX / Push-button 1P NO - 16A	Neutral	-	200 W	6/24
GW 10 160 F	Twin push-button 1P NO - 16 A	Neutral	UP - DOWN - STOP	-	6/24

NOTES: spring quick wiring, no tools necessary.

Command devices - axial - screw terminals



GW 10 671

Axial switch module - EVO

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 671	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12
GW 10 672	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 On/Off lighting device through a live output contact. Suitable for the control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Local push button with axial activation for control of the lamps connected to the device.
Equipped with 1 input to replicate the local control of the load via auxiliary module GW10677, GW10678 or NO-type and 1 input buttons for the centralisation OFF function.
APPLICATIONS: Bistable, monostable and timed load. Centralisation function (OFF) by means of a dedicated input, the possibility of being able to switch the load on by means of auxiliary axial modules or NO-type buttons. The devices are equipped with a configurable blue LED that can be set to OFF, location mode or for signalling the connected load status.
NOTES: the devices must be completed with a front button key: GW10671 must be completed with the GW10551S or GW10555S button keys. The GW10672 must be completed with the GW10552S or GW10556S button keys.



GW 10 673

Axial dimmer module - EVO

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 673	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12
GW 10 674	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	2	1/6

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two local axial-operated buttons for dimming the connected load.
Equipped with 2 inputs for replicating local control of the load via the auxiliary modules GW10679, GW10680 or NO-type buttons, or for creating the centralisation function.
APPLICATIONS: control of the dimmable load connected to the devices. Using dedicated inputs, load switches can be added via auxiliary axial modules, or NO-type buttons, or the inputs can be set, via programming, for centralised OFF function. The devices are equipped with configurable blue LEDs that can be set to OFF mode, location or signalling of the connected load.
NOTES: To avoid overheating, multiple dimmers cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. If two dimmers are installed in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. The devices must be completed with a front button: GW10673 must be completed with the GW10553S or GW10557S button keys; GW10674 must be completed with the GW10554S or GW10558S button keys.



GW 10 675

Axial roller shutter module - EVO

Code	Supply voltage	Max current supplied	No. modules	Pack Carton
GW 10 675	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW 10 676	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., through 2 live interlocked output contacts. Two axial-operated local buttons control the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the auxiliary module GW10679, GW10680 or NO-type up/down buttons, or for creating the centralisation function.
APPLICATIONS: control of the motor connected to the devices. The dedicated inputs can be used to operate roller-shutters/venetian blinds via the auxiliary axial modules or NO-type up/down buttons, or they can be set, through programming, for centralisation functions (Up/Down). The devices are equipped with blue LEDs which can be configured to facilitate location and to signal the movement of the roller-shutter/Venetian blind.
NOTES: the devices must be completed with a front button key: GW10675 must be completed with the GW10553S or GW10557S button keys; the GW10676 must be completed with the GW10554S or GW10558S button keys.



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO switch modules.
The devices are equipped with configurable blue LEDs that can be set to OFF, location or display of the load status.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10677 must be completed with the GW10551S or GW10555S button keys. GW10678 must be completed with the GW10552S or GW10556S button keys.



GW 10 679

2-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO dimmer and roller-shutter modules.
The devices are equipped with configurable blue LEDs that can be set for location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10679 must be completed with the GW10553S or GW10557S button keys. GW10680 must be completed with the GW10554S or GW10558S button keys.


GW 10 551 S

Interchangeable button keys for axial devices

Code	Colour	Button key	No. modules	Pack Carton
GW 10 551 S	Glossy white	To be completed with lens	1	1/48
GW 10 552 S	Glossy white	To be completed with lens	2	1/48
GW 10 553 S	Glossy white	To be completed with 2 lenses	1	1/48
GW 10 554 S	Glossy white	To be completed with 2 lenses	2	1/48
GW 10 555 S	Glossy white	With 1 diffuser	1	1/48
GW 10 556 S	Glossy white	With 1 diffuser	2	1/48
GW 10 557 S	Glossy white	With 2 diffusers	1	1/48
GW 10 558 S	Glossy white	With 2 diffusers	2	1/48

NOTES: for use to complete the EVO axial modules and auxiliary axial controls.

Lenses with illuminated symbol



Symbols for illuminable rocker command devices

Code	Symbol	Pack Carton
Suitable for: General services		
GW 10 501	Neutral	20/240
GW 10 502	Light	20/240
GW 10 503	Stair light	20/240
GW 10 504	Table light	20/240
GW 10 505	Bell	20/240
GW 10 506	Fan	20/240
GW 10 507	Key	20/240
GW 10 508	Alarm	20/240
GW 10 509	ON	20/240
GW 10 510	OFF	20/240
GW 10 511	Nurse	20/240
GW 10 512	Waitress	20/240
GW 10 513	Dimmer increase	20/240
GW 10 514	Dimmer decrease	20/240
GW 10 515	UP arrow	20/240
GW 10 516	DOWN arrow	20/240
GW 10 517	UP - DOWN arrow	20/240
GW 10 518	RIGHT - LEFT arrow	20/240
Suitable for: Numerical services		
GW 10 531	One	20/240
GW 10 532	Two	20/240
GW 10 533	Three	20/240
GW 10 534	Four	20/240
GW 10 535	Five	20/240
GW 10 536	Six	20/240
GW 10 537	Seven	20/240
GW 10 538	Eight	20/240
GW 10 539	Nine	20/240
GW 10 540	Zero	20/240

NOTES: to be used in place of the neutral lens in the illuminable rocker command devices.

ChoruSmart - Modular devices



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

Interchangeable button keys and diffusers for rocker devices



Button keys for rocker controls and interchangeable diffusers for indicator lights

Code	Symbol	Pack Carton
Description: Keys 22x22 mm		
GW 10 541	General	4/48
GW 10 543	Key	4/48
GW 10 544	Bell	4/48
GW 10 545	Vertical arrow	4/48
GW 10 546	Horizontal arrow	4/48
Description: Diffusers		
GW 10 547	Red	4/48
GW 10 548	Green	4/48
GW 10 549	Opal diffuser	4/48

APPLICATIONS: replacement diffusers for indicators GW10142, GW10143 and GW10144.

NOTES: the ChoruSmart modular system allows the use of 22 x 22 mm interchangeable buttons in place of the standard buttons fitted on the control devices GW10141, GW10142, GW10143 and GW10144. Symbols/diffusers not suitable for the EVO axial keys.

Soft-click, rocker electronic push buttons



GW 10 915

Universal soft-click electronic push-button

Code	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 10 915	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contacts interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 10 912

Backlit soft-click electronic push-button

Code	Supply voltage	Type of contact	Button key	Type of use	Pack Carton
GW 10 912	230 V ac - 50/60 Hz	1NO 4A (AC1) 230 V ac	With diffuser	Relay, dimmer	1/12

CHARACTERISTICS: push-button for controlling latching relays, electronic switches for heavy duty loads, or dimmers with a remote control input.
Equipped with amber localisation LED.



GW 10 913

Backlit soft-click electronic push-buttons for BUS inputs

Code	Type of contact	Button key	Type of use	Pack Carton
No. modules: 1				
GW 10 913	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/12
GW 10 916	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/12
No. modules: 2				
GW 10 917	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/6
GW 10 918	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 10 914

Double soft-click electronic push-button

Code	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 10 914	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connecting KNX BUS contact interfaces or electronic control panels for moving roller shutters.

ChoruSmart - Modular devices

Touch command modules



GW 10 922

Touch one-way switch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 922	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: device for the On/Off control of 1 lighting device through a live output contact. Suitable for control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Equipped with 1 input for replicating local control of the load via the GW10924 auxiliary touch control modules, NO-type buttons and 1 input for the centralisation of the OFF function. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: bistable, monostable and timed load control. Centralisation function (OFF) through the dedicated input.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 923

Touch dimmer module

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 923	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two touch areas for dimming the connected load. Equipped with 2 inputs for replicating local control of the load via the auxiliary touch 2-command modules GW10925, NO-type buttons, or for creating the centralisation function OFF. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the dimmable load connected to the devices. Centralised OFF function, via dedicated inputs.
NOTES: to avoid overheating, multiple products cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. When installing two dimmers in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. To be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 921

Touch roller shutter module

Code	Supply voltage	Maximum output power	No. modules	Pack Carton
GW 10 921	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., by means of 2 interlocked live output contacts. Two touch areas for controlling the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the touch auxiliary 2-command modules GW10925, NO-type up/down buttons, or for creating a centralisation function (up/down). The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the motor connected to the devices. Centralisation function (Up/Down) by means of a dedicated inputs.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 924

1-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 924	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10922 module. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
NOTES: to be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 925

2-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 925	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10921 and GW10923 modules. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable, built-in buzzer and functions identifiable by the icons on the ICE touch plates.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).

ICE TOUCH plates



GW 16 955 CB

ICE TOUCH - white

Code	Description	For support codes	Pack Carton
GW 16 955 CB	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).

NOTES: the symbols displayed in the image are purely indicative and may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

Blanking modules and cable outlet



GW 10 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 10 195	1 module	1	10/200
GW 10 197	1/2 module	1/2	4/48
GW 10 198	2 modules	2	1/48
GW 10 199	3 modules	3	1/48



GW 10 194

Cable outlet

Code	Description	No. modules	Pack Carton
GW 10 194	2 modules	2	6/48
GW 10 196	1 module	1	1/48

NOTES: GW10196 with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.
GW10194 with anti-traction cable fastener device, cables min 4mm ø, max 10mm ø. To be installed with the cable output downwards.

ChoruSmart - Modular devices

Movement detectors



GW 10 594

Movement detector

Code	Supply voltage	Output contacts	Pack Carton
GW 10 594	230V ac - 50/60 Hz	1NO 3 A (AC1) 230 V ac	1/4

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited. Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA, LED loads: 60 W (max. 10 lamps). Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through. Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly. Detection beam angle 120°, depth of detection max 8 metres.



GW 10 595

Ceiling-mounted presence detector

Code	Supply voltage	Installation height (m)	Light sensor	Dimensions HxØ (mm)	Pack Carton
GW 10 595	220/240 V ac - 50/60 Hz	From 2,2 to 6	< 3 ÷ 2000 Lux	44x111,5	1

CHARACTERISTICS: presence sensor, sensing range: 360° circle (max. diameter 18 metres); installable with fixing springs on a surface-mounted or recessed box. Suitable for the control of incandescent/halogen lamps: 1000W, LED lamps : 200W (4 / 23 W - max. 8 lamps).
NOTES: equipped with a surface-mount box capable of holding sensors from IP20 to IP44.

Relay



GW 10 724

Relay - 230V ac 50/60Hz

Code	Type	No. of poles	Output contacts	Coil	Pack Carton
No. modules: 1					
GW 10 721	Latching relay	1P	10 AX 250V ac	230V ac - 50/60 Hz	1/12
GW 10 724	Monostable relay	1P	1NO/NC 10A(AC1)/2A(AC15)250V ac	230V ac - 50/60 Hz	1/12

CHARACTERISTICS: GW10721 suitable for commanding incandescent/halogen lamps: 1000 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: GW10721 command of lighting devices from more than one point, by means of remote NO push-buttons.
GW10721 motor function/stop commands (extractors, air agitators, etc.).
GW10724 as an auxiliary element for commanding special loads, for distance signalling, for electrical separation between the command and use circuits.



GW 10 726

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 10 726	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: inlets for remote NO push-buttons for alarms (e.g. GW10136) and alarm reset (e.g. GW10145). green LED for alarm status signalling.

HOTEL COMPONENTS - GLOSSY WHITE VERSION

Badge switch



GW 10 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted)
NOTES: badges not included. The article uses LED signalling units, not included.

Interchangeable button keys



GW 10 733

Interchangeable button keys

Code	Button key	Symbol	No. modules	Pack Carton
GW 10 731	With diffuser	DND	1	4/48
GW 10 732	With diffuser	MUR	1	4/48
GW 10 733	Neutral	DND+MUR	1	4/48

CHARACTERISTICS: with "Do not disturb" (DND) and "Make up the room" (MUR) pad printings. To be used for the customization of the Chorus command devices. GW10731 and GW10732 suitable for one-way switches, two-way switches, intermediate switches and push-buttons. GW10733 suitable for three-way switches and push-buttons with central OFF position.

Indicator light device



GW 10 736

Double indicator lamp

Code	Diffuser colour	Symbol	No. modules	Pack Carton
GW 10 736	Opal diffuser	DND+MUR	1	1/24

CHARACTERISTICS: LED signalling units not included.

POWER - GLOSSY WHITE VERSION

Socket-outlets - Italian/German standard



GW 10 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 201	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 10 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.



GW 10 204

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48
GW 10 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.




GW 10 208

Italian standard double socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 208	2x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	2	6/24

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.



GW 10 209

Italian standard triple socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 209	3x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	3	4/12

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213

Italian standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 233	2P+E - 16 A Dual amperage	Orange	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with safety shields.



GW 10 214

Italian/German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 234	2P+E - 16 A Dual amperage illuminable	Orange	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary network.

Socket-outlets - German Standard



GW 10 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 10 242

German standard socket-outlet with lid IP40 - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

ChoruSmart - Modular devices



GW 10 251

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields.



GW 10 341

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 341	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 351

German Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 241 F

German Standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 241 F	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 251 F

German standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 F	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.

Socket-outlets - French Standard



GW 10 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 10 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 10 248

French Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 248	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 258

French Standard socket-outlet for dedicated lines, with front tightening terminals - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 258	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.
To be used in combination with plugs equipped with accessory GW10260



GW 10 247 F

French standard socket-outlet with quick wiring terminals - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 247 F	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 257 F

French standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 257 F	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.
To be used in combination with plugs equipped with accessory GW10260.



GW 10 260

French standard socket-outlet accessory, for dedicated lines

Code	Colour	For sockets	Pack Carton
GW 10 260	Red	GW10257F - GW10258	10/100

CHARACTERISTICS: to be fixed directly on the 2P+E French standard plug, to avoid the incorrect insertion in dedicated line circuits.

Socket-outlets - Israeli Standard



GW 10 281

Israeli Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 281	2P+E - 16 A illuminable	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 10 291

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 10 282

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 282	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 10 346

Swiss standard socket-outlet - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 346	2P+E - 10A - type 13	Ø 4 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 10 286

USA standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 286	2P+E - 15A	Flat parallel horizontal	1	12/48



GW 10 288

Euro-American standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 10 288	2P+E - 15A	Ø 4 mm Flat	1	12/48



GW 10 296

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 296	2P+E - 13 A	Flat	2	6/48
GW 10 297	2P+E - 15A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 10 298

Indian-South African Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 298	2P+E - 16A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

ChoruSmart - Modular devices



GW 10 299

South african standard socket-outlet - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 299	2P+E - 16A	Round Ø 4,5 mm	1	12/240

CHARACTERISTICS: with safety shields.



GW 10 301

Argentinian Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 301	2P+E - 10A	Flat	2	6/48



GW 10 306

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 306	2P+E - 10A	Flat	2	6/48
GW 10 307	2P+E - 15A	Flat	2	6/48



GW 10 310

Multistandard socket-outlet - 250/127V ac

Code	Description	No. modules	Pack Carton
GW 10 310	2P+E - 13A/250 V ac - 15A/127 V ac	2	10/40

CHARACTERISTICS: with safety shields.

APPLICATIONS: suitable for plugs compliant with the following standards: Europlug 2P 2.5A - 250V, British 2P+E 13A - 250V, Italian 2P 10A - 250V, Danish 2P 10A - 250V, Chinese 2P+E 10A - 250V, Argentinean/ Australian 2P+E 10A - 250V, Indian 2P+E 6A - 250V, USA 2P+E 15A - 127V. Not suitable for 2P+E German and French sockets because they don't offer earth continuity.

NOTES: the multistandard energy sockets GW1x310 are in compliance with the safety requirements defined by the International Standard IEC 60884-1. These sockets may not be in compliance with the standard sheets used in the country where they are sold, hence their usage could be prohibited or however, restricted only for specific applications. The plugs allowed are listed in the technical datasheet. Please contact directly Gewiss technical service for further information.



GW 10 392

Chinese standard socket-outlets - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 391	2P+E - 10A	Flat	2	6/48
GW 10 392	2P+E - 16A	Flat	2	6/48

CHARACTERISTICS: with safety shields.

Interlocked switched socket-outlets




GW 10 311

Interlocked switched socket-outlets with miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	No. modules	Pack Carton
GW 10 311	2P+E - 16A	P17-P11	1P+N 16A	3 kA	2	1/6
GW 10 312	2P+E - 16A	P40	1P+N 16A	3 kA	3	1/4

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.



GW 10 321

Interlocked switched socket-outlets with residual miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	Idn	No. modules	Pack Carton
GW 10 321	2P+E - 16A	P17-P11	1P+N 16A	3 kA	10 mA	3	1/4
GW 10 322	2P+E - 16A	P40	1P+N 16A	3 kA	10 mA	4	1/2

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic) and residual current circuit breaker (type A). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.

Shaver socket-outlet



GW 10 331

Euro-American standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 10 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - GLOSSY WHITE VERSION

TV-SAT sockets



GW 10 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 10 361	Direct	0 dB	1	1/48
GW 10 362	Through wiring	5 dB	1	1/24
GW 10 363	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW10361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5dB GW10362 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load. (TV, VCR, SAT receiver or 75-Ohm termination)

ChoruSmart - Modular devices



GW 10 371

Coaxial TV-SAT sockets (5-2400 MHz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 10 371	Direct	0 dB	1	1/48
GW 10 372	Through wiring	5 dB	1	1/24
GW 10 373	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW10371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5dB GW10372 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 10 382

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 10 381	TV-FM	Direct	0 dB	2	1/24
GW 10 382	TV-FM-SAT	Direct	0 dB	2	1/24
GW 10 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW10381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW10382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW10383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.



GW 10 367

Coaxial TV sockets (5-2400 Mhz), class A shielding - male IEC connector Ø 9.5mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 10 367	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 10 377

Coaxial TV-SAT sockets (5-2400 Mhz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 10 377	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 10 386

Covers for TV-SAT-R antenna sockets

Code	Description	No. holes	Pack Carton
GW 10 386	For TV-R base	2	1/24
GW 10 387	For TV/R-SAT base	2	1/24

APPLICATIONS: suitable for integration on the Chorus range of TV-SAT-R standard bases available on the market.
ACCESSORIES SUPPLIED: fixing screws.

Telephone sockets



GW 10 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 10 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.



GW 10 409

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 10 409	RJ11	Screw-on terminals	2	1/24

APPLICATIONS: telephone, telefax, modem.



GW 10 406

British standard telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 10 406	6 contacts	Screw-on terminals	1	1/24

Data sockets



GW 10 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 10 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 10 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 10 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 10 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.

ChoruSmart - Modular devices



GW 10 431

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 10 431	AMP / Keystone Jack	1	1/48
GW 10 438	SYSTIMAX COMMSCOPE	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the GEWISS adapter.

GW 10 433

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 10 433	AMP / Keystone Jack	2	4/100

NOTES: due to technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the data socket and the GEWISS empty enclosure.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

Socket-outlets for auxiliary circuits



GW 10 451

SELV sockets

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 451	2P - 6A - 24V	Ø 3 mm	1	12/24
GW 10 452	2P - 6A - 24V polarised	Flat	1	12/24

CHARACTERISTICS: Centre distance 12,4mm.

Audio and video sockets



GW 10 453

Audio and video sockets

Code	Description	No. modules	Pack Carton
GW 10 453	Double RCA	1	1/24
GW 10 454	For loudspeaker	1	1/24
GW 10 458	Speaker socket	1	1/24

CHARACTERISTICS: GW10453 double RCA stud connector, red and white, weld-in connection.
GW10454 welding connection. GW10458 front access terminals for inserting 1.5 mm² rigid wires, insulator punching rear connection suitable for cables AWG24 or max 0.25mm².

USB and HDMI couplers and sockets



GW 10 459

USB sockets

Code	Description	No. modules	Pack Carton
GW 10 459	USB socket-outlet	1	1/24

CHARACTERISTICS: A-type USB 2.0 female connector, with screw terminals on the back.



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB chargers



GW 10 415

USB power supply for electronic devices

Code		Supply voltage	Output voltage	Max. total power output	PD	USB-IF	Outputs/N° and type	No. modules	Pack Carton
GW 10 449		100 ÷ 240 V ac - 50/60 Hz	5V dc	15 W	-	-	2 / A+C	1	1/10
GW 10 415	①	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	30 W	Yes	Yes	1 / C	1	1/12
GW 10 417	②	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	63 W	Yes	Yes	2 / C	2	1/6

CHARACTERISTICS: GW10449 USB charger suitable for charging a single electronic device (e.g., tablet) or two devices simultaneously (e.g., tablet and smartphone). The distribution of power output across the two ports depends on the charging status of the connected devices.
GW10415 USB charger for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones, and smartwatches. Charging compatibility with market devices is guaranteed by USB-IF certification.
GW10417 USB charger for fast charging up to 63W with Power Delivery technology. Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools. Charging compatibility with market devices is guaranteed by USB-IF certification.

NEWS
Availability: ① July 2025 ② November 2025

ChoruSmart - Modular devices

PROTECTION - GLOSSY WHITE VERSION

Miniature circuit breakers



GW 10 463

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. modules	Pack Carton
GW 10 461	Single pole (1P)	6	3 kA	1	1/12
GW 10 462	Single pole (1P)	10	3 kA	1	1/12
GW 10 463	Single pole (1P)	16	3 kA	1	1/12
GW 10 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 10 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 10 468	Two-pole (1P+N)	16	3 kA	1	1/12



GW 10 488

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Rated current (A)	Breaking capacity	Idn	No. modules	Pack Carton
GW 10 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 10 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 10 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 10 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 10 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 10 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

Protection devices



GW 10 491

Fuse holder - 250V ac

Code	Rated current (A)	Fuse type	No. modules	Pack Carton
GW 10 491	16	Ø 6.3x32 mm	1	1/12

CHARACTERISTICS: fuse not included.



GW 10 492

Surge protection device - 230V ac

Code	Uc	Up	No. modules	Pack Carton
GW 10 492	275 V ac 50/60Hz	1 kV	1	1/12

CHARACTERISTICS: green LED for status signalling.
APPLICATIONS: protection of electronic devices (TV, HI-FI, computer, etc.) from overvoltage (resulting from atmospheric conditions or manoeuvres) that could be channelled from the power supply lines.

INDICATOR - GLOSSY WHITE VERSION

Indicator light devices



GW 10 642

Single indicator lamps - 1/2 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 10 641	Opal diffuser	Neutral	1/2	2/48
GW 10 642	Green	Safety	1/2	2/48
GW 10 643	Red	Danger	1/2	2/48
GW 10 644	Amber	Attention	1/2	2/48

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 10 622

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 10 621	Opal diffuser	Neutral	1	1/24
GW 10 622	Green	Safety	1	1/24
GW 10 623	Red	Danger	1	1/24
GW 10 624	Amber	Attention	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 10 629

Double indicator lamps - 1 module

Code	Diffuser colour	No. modules	Pack Carton
GW 10 628	Opal diffuser	1	1/24
GW 10 629	Red/green	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 10 633

Protruding indicator lamps - 2 modules

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 10 631	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 10 632	12V ac/dc - 230V ac 50/60 Hz	Green	White LED	2	1/24
GW 10 633	12V ac/dc - 230V ac 50/60 Hz	Red	White LED	2	1/24
GW 10 634	12V ac/dc - 230V ac 50/60 Hz	Amber	White LED	2	1/24

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.



GW 10 656

Stair riser lamp

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 10 651	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 10 656	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	4	1/2

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.

Anti black-out and emergency lamps



GW 10 661

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	Pack Carton
GW 10 661	230 V ac - 50/60 Hz	Ni - Mh	2 h	White LED	1/6

CHARACTERISTICS: equipped with a 3-position selector on the front panel, for anti black-out inhibition and night functioning.
To be inserted in any socket-outlet of the Italian, German or French type. Highly efficient, white LED lamp.



GW 10 662

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 10 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/12

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.



GW 10 663

Autonomous emergency lamps

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 10 663	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	2	1/6
GW 10 666	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	4	1/2

CHARACTERISTICS: green mains presence signal LED. Highly efficient, white LED lamps.
APPLICATIONS: compliant with standards EN60598-2-22.

Acoustic signalling devices

Ringers



GW 10 601

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 10 601	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24
GW 10 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 10 606

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 10 606	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24
GW 10 607	230V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ChoruSmart - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - GLOSSY WHITE VERSION

Timer devices



GW 10 581

Electronic daily/weekly timer, 1-channel

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 581	230 V ac - 50/60 Hz	1NO/NC 8A(AC1)/4A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.

Temperature control devices



GW 10 709

Connected thermostat - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 709	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 10 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 10 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.



GW 16 970 CB

Thermo ICE Wi-Fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CB	White	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch commands (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or by remote via specific apps (smartphone and tablet).

APPLICATIONS:
The THERMO ICE Wi-Fi can be used:
- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Dimmer

Universal rotating electronic regulator



GW 10 575

Code	Supply voltage	No. modules	Pack Carton
GW 10 575	230V ac - 50 Hz	1	1/12

CHARACTERISTICS: suitable for dimming incandescent and halogen lamps 230 V ac (10-160 W); low-voltage halogen lamps (12 V ac) with electronic transformers (10-160 W) and LED lamps 230 V ac (4-160W), rotary control with 2-way switch. Equipped with amber-colour-red signalling LED. Can be operated without neutral connection.
NOTES: the installation of more than one dimmer side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two dimmers. If installing two dimmers in the same box, the maximum loads that can be controlled by each dimmer must be reduced by 50%.

Rotating electronic regulators for resistive/inductive loads



GW 10 564

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 10 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 10 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW10567 rotary command with two-way switch.
GW10564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact GEWISS Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Universal electronic regulators with push-button



GW 10 572 A

Code	Supply voltage	No. modules	Pack Carton
GW 10 572 A	230V ac - 50/60 Hz	1	1/12
GW 10 573 A	230V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Electronic regulator with button for resistive/inductive loads



GW 10 568

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 10 568	230V ac - 50 Hz	60 - 500 W	60 - 500 VA	1	1/12

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

TECHNICAL ALARMS - GLOSSY WHITE VERSION

Gas detectors



GW 10 711

LPG detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 10 711	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 712

Methane gas detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 10 712	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 720

Power supply unit 12Vdc

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

Anti-flood system with Zigbee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0...50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.



GW 10 750

Blanking module for housing RF Zigbee actuators

Code	Colour	No. modules	Pack Carton
GW 10 750	Glossy white	1	1/12

CHARACTERISTICS: 1-module blanking module with pad printing. Allows the housing and fast identification of the flush-mounting RF Zigbee actuator.
NOTES: snap-in assembly.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps - 2W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Dimensions (mm)	Pack Carton
GW 20 902	12V ac/dc	2 W	Incandescence	White	S6x36	50
GW 20 903	24V ac/dc	2 W	Incandescence	White	S6x36	50

Accessories



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




ChoruSmart






Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

Satin white modular devices

The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in satin white, distinctive and elegant, they include rocker button keys with ½, 1 and 2 modules to optimise space, and axial keys in EVO or SMART version for advanced functions. The front attachment system facilitates assembly and release without removing the support.





COMMAND - SATIN WHITE VERSION

Command devices - rockers - screw terminals



GW 15 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 15 001	1P - 16AX	Neutral	200 W	12/96
GW 15 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 15 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 1/2				
GW 15 021	1P - 10AX	Neutral	100 W	12/24
GW 15 022	1P - 10AX illuminable	With diffuser	100 W	6/24
No. modules: 2				
GW 15 031	1P - 16AX	Neutral	200 W	6/24
GW 15 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 15 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 15 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 15 004	2P - 16 AX	Neutral	0/1	200 W	12/48
GW 15 005	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	12/24
GW 15 006	2P - 10AX	With key	0/1	100 W	1/12
No. modules: 2					
GW 15 034	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 15 035	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW15006 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 15 007

One-way switch 2P - 250V ac - heavy duty loads

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 15 007	2P - 25 AX	Neutral	0/1	250 W	12/24

APPLICATIONS: suitable for particular heavy-duty loads (e.g. LED or fluorescent lamp batteries) or high-consumption devices (e.g. ovens, air-conditioners, boilers, etc.).



GW 15 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 15 051	1P - 16AX	Neutral	200 W	12/96
GW 15 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 15 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
GW 15 054	1P - 10AX	With key	100 W	1/12
No. modules: 1/2				
GW 15 061	1P - 10AX	Neutral	100 W	6/24
No. modules: 2				
GW 15 071	1P - 16AX	Neutral	200 W	6/24
GW 15 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 15 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW15054 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 15 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 15 091	1P - 16AX	Neutral	200 W	12/48
GW 15 092	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 15 093	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 15 101	1P - 16AX	Neutral	200 W	6/12
GW 15 102	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 15 103	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 15 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 15 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 15 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 15 122

Three-way switch 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 15 122	2P - 10AX	Neutral	UP - DOWN	100 W	12/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

ChoruSmart - Modular devices



GW 15 131

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 15 131	1P NO - 16A	Neutral	-	12/96
GW 15 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 15 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 15 136	1P NO - 16A	Pull-cord	-	1/12
GW 15 137	1P NC - 16A	Neutral	O red	12/24
GW 15 138	1P NC+NO - 16 A	Stop	Red	12/24
GW 15 139	1P NO+NC - 16 A	Start	Green	12/24
GW 15 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 15 141	1P NO+NO - 16 A	Double	-	12/24
GW 15 142	1P NO - 16A illuminable	Green diffuser	-	12/24
GW 15 143	1P NO - 16A illuminable	Red diffuser	-	12/24
GW 15 144	1P NO - 16A illuminable	Opal diffuser	-	12/24
GW 15 151	1P NO - 16A illuminable	With replaceable neutral lens	Light	12/24
GW 15 152	1P NO - 16A illuminable	With replaceable neutral lens	Key	12/24
GW 15 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 1/2				
GW 15 161	1P NO - 10A	Neutral	-	6/24
GW 15 162	1P NO - 10A illuminable	With diffuser	-	6/24
No. modules: 2				
GW 15 171	1P NO - 16A	Neutral	-	6/24
GW 15 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 15 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW15136 Cord in insulating material, 140cm long, with red knob.

GW15140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW15141 independent push-buttons that can also be activated simultaneously.



GW 15 134

Push-buttons 2P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 15 134	2P NO - 16A	Neutral	O	12/24
GW 15 135	2P NO - 10A illuminable	With replaceable neutral lens	-	12/24
GW 15 145	2P NO - 10A	With key	-	1/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

NOTES: GW15145 equipped with 2 keys. Spare keys: GW30912.



GW 15 191

Push-buttons 1P with illuminated name plate - 250V ac

Code	Description	Lamp voltage	Lamp	Lamp power	Pack Carton
No. modules: 2					
GW 15 191	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm (not included)	2 W	6/24
No. modules: 3					
GW 15 192	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	4/16

CHARACTERISTICS: lamp not included.

Command devices - rockers - quick wiring terminals



GW 15 031 F

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 15 031 F	1P - 16AX	Neutral	200 W	6/24
GW 15 032 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 15 033 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 15 034 F

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 15 034 F	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 15 035 F	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 15 071 F

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 15 071 F	1P - 16AX	Neutral	200 W	6/24
GW 15 072 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 15 073 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 15 101 F

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 15 101 F	1P - 16AX	Neutral	200 W	6/12
GW 15 102 F	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 15 103 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 15 171 F

Push-buttons 1P - 250V ac

Code	Description	Button key	Pack Carton
No. modules: 2			
GW 15 171 F	1P NO - 16A	Neutral	6/24
GW 15 172 F	1P NO - 16A illuminable	With diffuser	6/24
GW 15 173 F	1P NO - 16A illuminable	With replaceable neutral lens	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.

ChoruSmart - Modular devices



GW 15 160 F

Combined command devices - rockers - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 15 078 F	Twin two-way switch 1P - 16 AX	Neutral	-	200 W	6/24
GW 15 159 F	Two-way switch 1P - 16 AX / Push-button 1P NO - 16A	Neutral	-	200 W	6/24
GW 15 160 F	Twin push-button 1P NO - 16 A	Neutral	-	-	6/24

NOTES: spring quick wiring, no tools necessary.

Command devices - axial - screw terminals



GW 10 671

Axial switch module - EVO

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 671	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12
GW 10 672	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 On/Off lighting device through a live output contact. Suitable for the control of incandescent and halogen (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Local push button with axial activation for control of the lamps connected to the device. Equipped with 1 input to replicate the local control of the load via auxiliary module GW10677, GW10678 or NO-type and 1-input buttons for the centralisation OFF function.
APPLICATIONS: Bistable, monostable and timed load command. Centralisation function (OFF) by means of a dedicated input, the possibility of being able to switch the load on by means of auxiliary axial modules or NO-type buttons. The devices are equipped with a configurable blue LED that can be set to OFF, easy location mode or for signalling the connected load status.
NOTES: the devices must be completed with a front button key: GW10671 must be completed with the GW15551S or GW15555S button keys. The GW10672 must be completed with the GW15552S or GW15556S button keys.



GW 10 673

Axial dimmer module - EVO

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 673	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12
GW 10 674	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	2	1/6

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two local axial operated buttons for dimming the connected load.
Equipped with 2 inputs for replicating local control of the load via the auxiliary module GW10679, GW10680 or NO-type buttons or for creating the centralisation function.
APPLICATIONS: control of the dimmable load connected to the devices. The dedicated inputs can be used to add a load switching-on function through auxiliary axial modules or NO-type buttons, or inputs can be set, via programming, for the centralised OFF function. The devices are equipped with blue LEDs that can be set to OFF, location mode or for signalling the connected load.
NOTES: To avoid overheating, multiple dimmers cannot be installed side-by-side inside in the same enclosure. Insert a blanking module between two electronic devices. If two dimmers are installed in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. The devices must be completed with a front button key: GW10673 must be completed with the GW15553S or GW15557S button keys; GW10674 must be completed with the GW15554S or GW15558S button keys.



GW 10 675

Axial roller shutter module - EVO

Code	Supply voltage	Max current supplied	No. modules	Pack Carton
GW 10 675	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW 10 676	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., through 2 live interlocked output contacts. Two axial-operated local buttons control the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the auxiliary module GW10679, GW10680 or NO-type up/down buttons, or for creating the centralisation function.
APPLICATIONS: control of the motor connected to the devices. The dedicated inputs can be used to operate roller-shutters/venetian blinds via the auxiliary axial modules or NO-type up/down buttons, or they can be set, through programming, for centralisation functions (Up/Down). The devices are equipped with blue LEDs which can be configured to facilitate location at night and to signal the movement of the roller-shutter/Venetian blind.
NOTES: the devices must be completed with a front button key: GW10675 must be completed with the GW15553S or GW15557S button keys.GW10676 must be completed with the GW15554S or GW15558S button keys.



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO switch modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10677 must be completed with the GW15551S or GW15555S button keys. GW10678 must be completed with the GW15552S or GW15556S button keys.

2-command auxiliary axial modules



GW 10 679

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO dimmer and roller-shutter modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10679 must be completed with the GW15553S or GW15557S button keys. GW10680 must be completed with the GW15554S or GW15558S button keys.


Interchangeable keys for axial devices

GW 15 551 S

Code	Colour	Button key	No. modules	Pack Carton
GW 15 551 S	Satin White	To be completed with lens	1	1/48
GW 15 552 S	Satin White	To be completed with lens	2	1/48
GW 15 553 S	Satin White	To be completed with 2 lenses	1	1/48
GW 15 554 S	Satin White	To be completed with 2 lenses	2	1/48
GW 15 555 S	Satin White	With 1 diffuser	1	1/48
GW 15 556 S	Satin White	With 1 diffuser	2	1/48
GW 15 557 S	Satin White	With 2 diffusers	1	1/48
GW 15 558 S	Satin White	With 2 diffusers	2	1/48

NOTES: for use to complete the EVO axial modules and auxiliary axial controls.

Lenses with illuminated symbol



Symbols for backlit rocker command devices

Code	Symbol	Pack Carton
Suitable for: General services		
GW 10 501	Neutral	20/240
GW 10 502	Light	20/240
GW 10 503	Stair light	20/240
GW 10 504	Table light	20/240
GW 10 505	Bell	20/240
GW 10 506	Fan	20/240
GW 10 507	Key	20/240
GW 10 508	Alarm	20/240
GW 10 509	ON	20/240
GW 10 510	OFF	20/240
GW 10 511	Nurse	20/240
GW 10 512	Waitress	20/240
GW 10 513	Dimmer increase	20/240
GW 10 514	Dimmer decrease	20/240
GW 10 515	UP arrow	20/240
GW 10 516	DOWN arrow	20/240
GW 10 517	UP - DOWN arrow	20/240
GW 10 518	RIGHT - LEFT arrow	20/240
Suitable for: Numerical services		
GW 10 531	One	20/240
GW 10 532	Two	20/240
GW 10 533	Three	20/240
GW 10 534	Four	20/240
GW 10 535	Five	20/240
GW 10 536	Six	20/240
GW 10 537	Seven	20/240
GW 10 538	Eight	20/240
GW 10 539	Nine	20/240
GW 10 540	Zero	20/240

NOTES: to be used in place of the neutral lens in the illuminable rocker command devices.

ChoruSmart - Modular devices



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

Interchangeable button keys and diffusers for rocker devices



Button keys for rocker controls and interchangeable diffusers for indicator lights

Code	Symbol	Pack Carton
Description: Keys 22x22 mm		
GW 15 541	General	4/48
GW 15 543	Key	4/48
GW 15 544	Bell	4/48
GW 15 545	Vertical arrow	4/48
GW 15 546	Horizontal arrow	4/48
Description: Diffusers		
GW 10 547	Red	4/48
GW 10 548	Green	4/48
GW 10 549	Opal diffuser	4/48

APPLICATIONS: replacement diffusers for indicators GW15142, GW15143 and GW15144.

NOTES: the ChoruSmart modular system allows the use of 22 x 22 mm interchangeable buttons in place of the standard buttons fitted on the control devices GW15141, GW15142, GW15143 and GW15144. Symbols/diffusers not suitable for the EVO axial keys.

Soft-click, rocker electronic push buttons



GW 15 915

Universal soft-click electronic push-button

Code	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 15 915	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contacts interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 15 912

Backlit soft-click electronic push-button

Code	Supply voltage	Type of contact	Button key	Type of use	Pack Carton
GW 15 912	230 V ac - 50/60 Hz	1NO 4A (AC1) 230 V ac	With diffuser	Relay, dimmer	1/12

CHARACTERISTICS: push-button for controlling latching relays, electronic switches for heavy duty loads, or dimmers with a remote control input.
Equipped with amber localisation LED.



GW 15 913

Backlit electronic push-buttons for BUS inputs

Code	Type of contact	Button key	Type of use	Pack Carton
No. modules: 1				
GW 15 913	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/12
GW 15 916	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/12
No. modules: 2				
GW 15 917	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/6
GW 15 918	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 15 914

Double soft-click electronic push-button

Code	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 15 914	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connecting KNX BUS contact interfaces or electronic control panels for moving roller shutters.

ChoruSmart - Modular devices

Touch command modules



GW 10 922

Touch one-way switch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 922	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: device for the On/Off control of 1 lighting device through a live output contact. Suitable for control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Equipped with 1 input for replicating local control of the load via the GW10924 auxiliary touch control modules, NO-type buttons and 1 input for the centralisation of the OFF function. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: bistable, monostable and timed load control. Centralisation function (OFF) through the dedicated input.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 923

Touch dimmer module

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 923	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two touch areas for dimming the connected load. Equipped with 2 inputs for replicating local control of the load via the auxiliary touch 2-command modules GW10925, NO-type buttons, or for creating the centralisation function OFF. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the dimmable load connected to the devices. Centralised OFF function, via dedicated inputs.
NOTES: to avoid overheating, multiple products cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. When installing two dimmers in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. To be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 921

Touch roller shutter module

Code	Supply voltage	Maximum output power	No. modules	Pack Carton
GW 10 921	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., by means of 2 interlocked live output contacts. Two touch areas for controlling the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the touch auxiliary 2-command modules GW10925, NO-type up/down buttons, or for creating a centralisation function (up/down). The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the motor connected to the devices. Centralisation function (Up/Down) by means of a dedicated inputs.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 924

1-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 924	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10922 module. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
NOTES: to be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 925

2-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 925	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10921 and GW10923 modules. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable, built-in buzzer and functions identifiable by the icons on the ICE touch plates.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).

ICE TOUCH plates



GW 16 955 CB

ICE TOUCH - white

Code	Description	For support codes	Pack Carton
GW 16 955 CB	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).

NOTES: the symbols displayed in the image are purely indicative and may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

Blanking modules and cable outlet



GW 15 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 15 195	1 module	1	10/200
GW 15 197	1/2 module	1/2	4/48
GW 15 198	2 modules	2	1/48
GW 15 199	3 modules	3	1/48



GW 15 194

Cable outlets

Code	Description	No. modules	Pack Carton
GW 15 194	2 modules	2	6/48
GW 15 196	1 module	1	1/48

NOTES: GW15196 with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.
GW15194 with anti-traction cable fastener device, cables min 4mm ø, max 10mm ø. To be installed with the cable output downwards.

ChoruSmart - Modular devices

Movement detectors



GW 15 594

Movement detector

Code	Supply voltage	Output contacts	Pack Carton
GW 15 594	230V ac - 50/60 Hz	1NO 3 A (AC1) 230 V ac	1/4

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited.
Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA, LED loads: 60 W (max. 10 lamps).
Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.
Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly. Detection beam angle 120°, depth of detection max 8 metres.



GW 10 595

Ceiling-mounted presence detector

Code	Supply voltage	Installation height (m)	Light sensor	Dimensions HxØ (mm)	Pack Carton
GW 10 595	220/240 V ac - 50/60 Hz	From 2,2 to 6	< 3 ÷ 2000 Lux	44x111,5	1

CHARACTERISTICS: presence sensor, sensing range: 360° circle (max. diameter 18 metres); installable with fixing springs on a surface-mounted or recessed box. Suitable for the control of incandescent/halogen lamps: 1000W, LED lamps : 200W (4 / 23 W - max. 8 lamps).
NOTES: equipped with a surface-mount box capable of holding sensors from IP20 to IP44.

Relay



GW 15 724

Relay - 230V ac 50/60Hz

Code	Type	No. of poles	Output contacts	Coil	Pack Carton
No. modules: 1					
GW 15 721	Latching relay	1P	10 AX 250V ac	230V ac - 50/60 Hz	1/12
GW 15 724	Monostable relay	1P	1NO/NC 10A(AC1)/2A(AC15)250V ac	230V ac - 50/60 Hz	1/12

CHARACTERISTICS: GW15721 suitable for commanding incandescent/halogen lamps: 1000 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: GW15721 command of lighting devices from more than one point, by means of remote NO push-buttons.
GW15721 motor function/stop commands (extractors, air agitators, etc.).
GW15724 as an auxiliary element for commanding special loads, for distance signalling, for electrical separation between the command and use circuits.



GW 15 726

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 15 726	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: inlets for remote NO push-buttons for alarms (e.g. GW15136) and alarm reset (e.g. GW15145). green LED for alarm status signalling.

HOTEL COMPONENTS - SATIN WHITE VERSION

Badge switch




GW 15 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 15 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted)
NOTES: badges not included. The article uses LED signalling units, not included.

Interchangeable button keys



GW 15 733

Interchangeable button keys

Code	Button key	Symbol	No. modules	Pack Carton
GW 15 731	With diffuser	DND	1	4/48
GW 15 732	With diffuser	MUR	1	4/48
GW 15 733	Neutral	DND+MUR	1	4/48

CHARACTERISTICS: with "Do not disturb" (DND) and "Make up the room" (MUR) pad printings. To be used for the customization of the Chorus command devices. GW15731 and GW15732 suitable for one-way switches, two-way switches, intermediate switches and push-buttons. GW15733 suitable for three-way switches and push-buttons with central OFF position.

Indicator light device



GW 15 736

Double indicator lamp

Code	Diffuser colour	Symbol	No. modules	Pack Carton
GW 15 736	Opal diffuser	DND+MUR	1	1/24

CHARACTERISTICS: LED signalling units not included.

POWER - SATIN WHITE VERSION

Socket-outlets - Italian/German standard



GW 15 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 15 201	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 15 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.



GW 15 204

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 15 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48
GW 15 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.




GW 15 208

Italian standard double socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 15 208	2x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	2	6/24

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.



GW 15 209

Italian standard triple socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 15 209	3x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	3	4/12

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213

Italian standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 233	2P+E - 16 A Dual amperage	Orange	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with safety shields.



GW 10 214

Italian/German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 234	2P+E - 16 A Dual amperage illuminable	Orange	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary network.

Socket-outlets - German Standard



GW 15 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 15 242

German standard socket-outlet with lid IP40 - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

ChoruSmart - Modular devices



GW 10 251

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields.



GW 15 341

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 341	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 351

German Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 15 241 F

German Standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 241 F	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 251 F

German standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 F	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.

Socket-outlets - French Standard



GW 15 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 15 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 15 248

French Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 248	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 258

French Standard socket-outlet for dedicated lines, with front tightening terminals - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 258	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.
To be used in combination with plugs equipped with accessory GW10260



GW 15 247 F

French standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 247 F	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 257 F

French standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 257 F	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.
To be used in combination with plugs equipped with accessory GW10260.

ChoruSmart - Modular devices



GW 10 260

French standard socket-outlet accessory, for dedicated lines

Code	Colour	For sockets	Pack Carton
GW 10 260	Red	GW10257F - GW10258	10/100

CHARACTERISTICS: to be fixed directly on the 2P+E French standard plug, to avoid the incorrect insertion in dedicated line circuits.

Socket-outlets - Israeli Standard



GW 15 281

Israeli Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 281	2P+E - 16 A illuminable	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 10 291

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 15 282

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 282	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 15 286

USA standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 286	2P+E - 15A	Flat parallel horizontal	1	12/48



GW 15 288

Euro-American standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 15 288	2P+E - 15A	Ø 4 mm Flat	1	12/48



GW 15 296

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 296	2P+E - 13 A	Flat	2	6/48
GW 15 297	2P+E - 15A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 15 298

Indian-South African Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 298	2P+E - 16A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

ChoruSmart - Modular devices



GW 15 299

South african standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 299	2P+E - 16A	Round Ø 4,5 mm	1	12/240

CHARACTERISTICS: with safety shields.



GW 15 301

Argentinian Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 301	2P+E - 10A	Flat	2	6/48



GW 15 306

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 306	2P+E - 10A	Flat	2	6/48
GW 15 307	2P+E - 15A	Flat	2	6/48



GW 15 310

Multistandard socket-outlet - 250/127V ac

Code	Description	No. modules	Pack Carton
GW 15 310	2P+E - 13A/250 V ac - 15A/127 V ac	2	10/40

CHARACTERISTICS: with safety shields.

APPLICATIONS: suitable for plugs compliant with the following standards: Europlug 2P 2.5A - 250V, British 2P+E 13A - 250V, Italian 2P 10A - 250V, Danish 2P 10A - 250V, Chinese 2P+E 10A - 250V, Argentinean/ Australian 2P+E 10A - 250V, Indian 2P+E 6A - 250V, USA 2P+E 15A - 127V. Not suitable for 2P+E German and French sockets because they don't offer earth continuity.

NOTES: the multistandard energy sockets GW1x310 are in compliance with the safety requirements defined by the International Standard IEC 60884-1. These sockets may not be in compliance with the standard sheets used in the country where they are sold, hence their usage could be prohibited or however, restricted only for specific applications. The plugs allowed are listed in the technical datasheet. Please contact directly Gewiss technical service for further information.



GW 15 392

Chinese standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 391	2P+E - 10A	Flat	2	6/48
GW 15 392	2P+E - 16A	Flat	2	6/48

CHARACTERISTICS: with safety shields.

Interlocked switched socket-outlets




GW 15 311

Interlocked switched socket-outlets with miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	No. modules	Pack Carton
GW 15 311	2P+E - 16A	P17-P11	1P+N 16A	3 kA	2	1/6
GW 15 312	2P+E - 16A	P40	1P+N 16A	3 kA	3	1/4

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.



GW 15 321

Interlocked switched socket-outlets with residual miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	Idn	No. modules	Pack Carton
GW 15 321	2P+E - 16A	P17-P11	1P+N 16A	3 kA	10 mA	3	1/4
GW 15 322	2P+E - 16A	P40	1P+N 16A	3 kA	10 mA	4	1/2

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic) and residual current circuit breaker (type A). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.

Shaver socket-outlet



GW 15 331

Euro-American standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 15 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - SATIN WHITE VERSION

TV-SAT sockets



GW 15 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 15 361	Direct	0 dB	1	1/48
GW 15 362	Through wiring	5 dB	1	1/24
GW 15 363	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW15361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5dB GW15362 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load. (TV, VCR, SAT receiver or 75-Ohm termination)

ChoruSmart - Modular devices



GW 15 371

Coaxial TV-SAT sockets (5-2400 MHz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 15 371	Direct	0 dB	1	1/48
GW 15 372	Through wiring	5 dB	1	1/24
GW 15 373	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW15371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5dB GW15372 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 15 382

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 15 381	TV-FM	Direct	0 dB	2	1/24
GW 15 382	TV-FM-SAT	Direct	0 dB	2	1/24
GW 15 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW15381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW15382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW15383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.



GW 15 367

Coaxial TV sockets (5-2400 Mhz), class A shielding - male IEC connector Ø 9.5mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 15 367	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 15 377

Coaxial TV-SAT sockets (5-2400 Mhz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 15 377	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 15 386

Covers for TV-SAT-R antenna sockets

Code	Description	No. holes	Pack Carton
GW 15 386	For TV-R base	2	1/24
GW 15 387	For TV/R-SAT base	2	1/24

APPLICATIONS: suitable for integration on the Chorus range of TV-SAT-R standard bases available on the market.
ACCESSORIES SUPPLIED: fixing screws.

Telephone sockets



GW 15 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 15 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.



GW 15 409

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 15 409	RJ11	Screw-on terminals	2	1/24

APPLICATIONS: telephone, telefax, modem.



GW 15 406

British standard telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 15 406	6 contacts	Screw-on terminals	1	1/24

Data sockets



GW 15 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 15 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 15 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 15 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 15 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.

ChoruSmart - Modular devices



GW 15 431

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 15 431	AMP / Keystone Jack	1	1/48
GW 15 438	SYSTIMAX COMMSCOPE	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the GEWISS adapter.

GW 15 433

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 15 433	AMP / Keystone Jack	2	4/100

NOTES: due to technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the data socket and the GEWISS empty enclosure.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.

NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

Socket-outlets for auxiliary circuits



GW 15 451

SELV sockets

Code	Description	For plug pins	No. modules	Pack Carton
GW 15 451	2P - 6A - 24V	Ø 3 mm	1	12/24
GW 15 452	2P - 6A - 24V polarised	Flat	1	12/24

CHARACTERISTICS: Centre distance 12.4mm.

Audio and video sockets



GW 15 453

Audio and video sockets

Code	Description	No. modules	Pack Carton
GW 15 453	Double RCA	1	1/24
GW 15 454	For loudspeaker	1	1/24
GW 15 458	Speaker socket	1	1/24

CHARACTERISTICS: GW15453 double RCA stud connector, red and white, weld-in connection.
GW15454 welding connection. GW15458 front access terminals for inserting 1.5 mm² rigid wires, insulator punching rear connection suitable for cables AWG24 or max 0.25mm².

USB and HDMI couplers and sockets



GW 15 459

USB sockets

Code	Description	No. modules	Pack Carton
GW 15 459	USB socket-outlet	1	1/24

CHARACTERISTICS: A-type USB 2.0 female connector, with screw terminals on the back.



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB chargers



GW 15 415

USB power supply for electronic devices

Code		Supply voltage	Output voltage	Max. total power output	PD	USB-IF	Outputs/N° and type	No. modules	Pack Carton
GW 15 449		100 ÷ 240 V ac - 50/60 Hz	5V dc	15 W	-	-	2 / A+C	1	1/10
GW 15 415	①	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	30 W	Yes	Yes	1 / C	1	1/12
GW 15 417	②	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	63 W	Yes	Yes	2 / C	2	1/6

CHARACTERISTICS: GW15449 USB charger suitable for charging a single electronic device (e.g., tablet) or two devices simultaneously (e.g., tablet and smartphone). The distribution of power output across the two ports depends on the charging status of the connected devices.
GW15415 USB charger for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones, and smartwatches. Charging compatibility with market devices is guaranteed by USB-IF certification.
GW15417 USB charger for fast charging up to 63W with Power Delivery technology. Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools. Charging compatibility with market devices is guaranteed by USB-IF certification.

NEWS
Availability: ① July 2025 ② November 2025

ChoruSmart - Modular devices

PROTECTION - SATIN WHITE VERSION

Miniature circuit breakers



GW 15 463

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. modules	Pack Carton
GW 15 461	Single pole (1P)	6	3 kA	1	1/12
GW 15 462	Single pole (1P)	10	3 kA	1	1/12
GW 15 463	Single pole (1P)	16	3 kA	1	1/12
GW 15 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 15 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 15 468	Two-pole (1P+N)	16	3 kA	1	1/12



GW 15 488

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Rated current (A)	Breaking capacity	Idn	No. modules	Pack Carton
GW 15 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 15 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 15 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 15 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 15 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 15 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

Protection devices



GW 15 491

Fuse holder - 250V ac

Code	Rated current (A)	Fuse type	No. modules	Pack Carton
GW 15 491	16	Ø 6.3x32 mm	1	1/12

CHARACTERISTICS: fuse not included.



GW 15 492

Surge protection device - 230V ac

Code	Uc	Up	No. modules	Pack Carton
GW 15 492	275 V ac 50/60Hz	1 kV	1	1/12

CHARACTERISTICS: green LED for status signalling.

APPLICATIONS: protection of electronic devices (TV, HI-FI, computer, etc.) from overvoltage (resulting from atmospheric conditions or manoeuvres) that could be channelled from the power supply lines.

INDICATOR - SATIN WHITE VERSION

Indicator light devices



GW 15 642

Single indicator lamps - 1/2 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 15 641	Opal diffuser	Neutral	1/2	2/48
GW 15 642	Green	Safety	1/2	2/48
GW 15 643	Red	Danger	1/2	2/48
GW 15 644	Amber	Attention	1/2	2/48

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 15 622

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 15 621	Opal diffuser	Neutral	1	1/24
GW 15 622	Green	Safety	1	1/24
GW 15 623	Red	Danger	1	1/24
GW 15 624	Amber	Attention	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 15 629

Double indicator lamps - 1 module

Code	Diffuser colour	No. modules	Pack Carton
GW 15 628	Opal diffuser	1	1/24
GW 15 629	Red/green	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 15 633

Protruding indicator lamps - 2 modules

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 15 631	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 15 632	12V ac/dc - 230V ac 50/60 Hz	Green	White LED	2	1/24
GW 15 633	12V ac/dc - 230V ac 50/60 Hz	Red	White LED	2	1/24
GW 15 634	12V ac/dc - 230V ac 50/60 Hz	Amber	White LED	2	1/24

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.

ChoruSmart - Modular devices



GW 15 656

Stair riser lamp

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 15 651	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 15 656	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	4	1/2

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.

Anti black-out and emergency lamps



GW 15 662

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 15 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/12

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.



GW 15 663

Autonomous emergency lamps

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 15 663	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	2	1/6
GW 15 666	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	4	1/2

CHARACTERISTICS: green mains presence signal LED. Highly efficient, white LED lamps.
APPLICATIONS: compliant with standards EN60598-2-22.

Acoustic signalling devices

Ringers



GW 15 601

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 15 601	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24
GW 15 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 15 606

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 15 606	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24
GW 15 607	230V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ChoruSmart - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - SATIN WHITE VERSION

Temperature control devices



GW 15 709

Connected thermostat - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 15 709	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 15 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 15 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.



GW 16 970 CB

Thermo ICE Wi-Fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CB	White	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch commands (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or by remote via specific apps (smartphone and tablet).

APPLICATIONS: The THERMO ICE Wi-Fi can be used:
- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Dimmer



GW 15 575

Universal rotating electronic regulator

Code	Supply voltage	No. modules	Pack Carton
GW 15 575	230V ac - 50 Hz	1	1/12

CHARACTERISTICS: suitable for dimming incandescent and halogen lamps 230 V ac (10-160 W); low-voltage halogen lamps (12 V ac) with electronic transformers (10-160 W) and LED lamps 230 V ac (4-160W), rotary control with 2-way switch. Equipped with amber-colour-red signalling LED. Can be operated without neutral connection.
NOTES: the installation of more than one dimmer side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two dimmers. If installing two dimmers in the same box, the maximum loads that can be controlled by each dimmer must be reduced by 50%.



GW 15 564

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 15 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 15 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW15567 rotary command with two-way switch.
GW15564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact GEWISS Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 15 572 A

Universal electronic regulators with push-button

Code	Supply voltage	No. modules	Pack Carton
GW 15 572 A	230V ac - 50/60 Hz	1	1/12
GW 15 573 A	230V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 15 568

Electronic regulator with button for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 15 568	230V ac - 50 Hz	60 - 500 W	60 - 500 VA	1	1/12

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

TECHNICAL ALARMS - SATIN WHITE VERSION

Gas detectors



GW 15 712

Methane gas detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 15 712	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 720

Power supply unit 12Vdc

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

Anti-flood system with Zigbee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0...50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.



GW 15 750

Blanking module for housing RF Zigbee actuators

Code	Colour	No. modules	Pack Carton
GW 15 750	Satin White	1	1/12

CHARACTERISTICS: 1-modules blanking module with pad printing. Allows the housing and fast identification of the flush-mounting RF Zigbee actuator.
NOTES: snap-in assembly.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps - 2W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Dimensions (mm)	Pack Carton
GW 20 902	12V ac/dc	2 W	Incandescence	White	S6x36	50
GW 20 903	24V ac/dc	2 W	Incandescence	White	S6x36	50

Accessories



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




ChoruSmart






Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

Satin natural beige modular devices

The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in satin natural beige, warm and enveloping, they include rocker button keys with ½, 1 and 2 modules to optimise space, and axial keys in EVO or SMART version for advanced functions. The front attachment system facilitates assembly and release without removing the support.





COMMAND - NATURAL SATIN BEIGE VERSION

Command devices - rockers - screw terminals



GW 13 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 13 001	1P - 16AX	Neutral	200 W	12/96
GW 13 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 13 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 1/2				
GW 13 021	1P - 10AX	Neutral	100 W	12/24
GW 13 022	1P - 10AX illuminable	With diffuser	100 W	6/24
No. modules: 2				
GW 13 031	1P - 16AX	Neutral	200 W	6/24
GW 13 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 13 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 13 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 13 004	2P - 16 AX	Neutral	0/1	200 W	12/48
GW 13 005	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	12/24
GW 13 006	2P - 10AX	With key	0/1	100 W	1/12
No. modules: 2					
GW 13 034	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 13 035	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW13006 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 13 007

One-way switch 2P - 250V ac - heavy duty loads

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 13 007	2P - 25 AX	Neutral	0/1	250 W	12/24

APPLICATIONS: suitable for particular heavy-duty loads (e.g. LED or fluorescent lamp batteries) or high-consumption devices (e.g. ovens, air-conditioners, boilers, etc.).



GW 13 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 13 051	1P - 16AX	Neutral	200 W	12/96
GW 13 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 13 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
GW 13 054	1P - 10AX	With key	100 W	1/12
No. modules: 1/2				
GW 13 061	1P - 10AX	Neutral	100 W	6/24
No. modules: 2				
GW 13 071	1P - 16AX	Neutral	200 W	6/24
GW 13 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 13 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW13054 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 13 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 13 091	1P - 16AX	Neutral	200 W	12/48
GW 13 092	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 13 093	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 13 101	1P - 16AX	Neutral	200 W	6/12
GW 13 102	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 13 103	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 13 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 13 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 13 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 13 122

Three-way switch 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 13 122	2P - 10AX	Neutral	UP - DOWN	100 W	12/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

ChoruSmart - Modular devices



GW 13 131

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 13 131	1P NO - 16A	Neutral	-	12/96
GW 13 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 13 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 13 136	1P NO - 16A	Pull-cord	-	1/12
GW 13 137	1P NC - 16A	Neutral	O red	12/24
GW 13 138	1P NC+NO - 16 A	Stop	Red	12/24
GW 13 139	1P NO+NC - 16 A	Start	Green	12/24
GW 13 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 13 141	1P NO+NO - 16 A	Double	-	12/24
GW 13 142	1P NO - 16A illuminable	Green diffuser	-	12/24
GW 13 143	1P NO - 16A illuminable	Red diffuser	-	12/24
GW 13 144	1P NO - 16A illuminable	Opal diffuser	-	12/24
GW 13 151	1P NO - 16A illuminable	With replaceable neutral lens	Light	12/24
GW 13 152	1P NO - 16A illuminable	With replaceable neutral lens	Key	12/24
GW 13 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 1/2				
GW 13 161	1P NO - 10A	Neutral	-	6/24
GW 13 162	1P NO - 10A illuminable	With diffuser	-	6/24
No. modules: 2				
GW 13 171	1P NO - 16A	Neutral	-	6/24
GW 13 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 13 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW13136 Cord in insulating material, 140cm long, with red knob.

GW13140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW13141 independent push-buttons that can also be activated simultaneously.



GW 13 134

Push-buttons 2P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 13 134	2P NO - 16A	Neutral	O	12/24
GW 13 135	2P NO - 10A illuminable	With replaceable neutral lens	-	12/24
GW 13 145	2P NO - 10A	With key	-	1/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW13136 Cord in insulating material, 140cm long, with red knob.

GW13140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW13141 independent push-buttons that can also be activated simultaneously.



GW 13 191

Push-buttons 1P with illuminated name plate - 250V ac

Code	Description	Lamp voltage	Lamp	Lamp power	Pack Carton
No. modules: 2					
GW 13 191	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm (not included)	2 W	6/24
No. modules: 3					
GW 13 192	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	4/16

CHARACTERISTICS: lamp not included.

Command devices - rockers - quick wiring terminals



GW 13 031 F

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 13 031 F	1P - 16AX	Neutral	200 W	6/24
GW 13 032 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 13 033 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 13 034 F

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 13 034 F	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 13 035 F	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 13 071 F

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 13 071 F	1P - 16AX	Neutral	200 W	6/24
GW 13 072 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 13 073 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 13 101 F

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 13 101 F	1P - 16AX	Neutral	200 W	6/12
GW 13 102 F	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 13 103 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 13 171 F

Push-buttons 1P - 250V ac

Code	Description	Button key	Pack Carton
No. modules: 2			
GW 13 171 F	1P NO - 16A	Neutral	6/24
GW 13 172 F	1P NO - 16A illuminable	With diffuser	6/24
GW 13 173 F	1P NO - 16A illuminable	With replaceable neutral lens	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.

ChoruSmart - Modular devices



GW 13 160 F

Combined command devices - rockers - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 13 078 F	Twin two-way switch 1P - 16 AX	Neutral	-	200 W	6/24
GW 13 159 F	Two-way switch 1P - 16 AX / Push-button 1P NO - 16A	Neutral	-	200 W	6/24
GW 13 160 F	Twin push-button 1P NO - 16 A	Neutral	UP - DOWN - STOP	-	6/24

NOTES: spring quick wiring, no tools necessary.

Command devices - axial - screw terminals



GW 10 671

Axial switch module - EVO

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 671	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12
GW 10 672	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 On/Off lighting device through a live output contact. Suitable for the control of incandescent and halogen (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Local push button with axial activation for control of the lamps connected to the device.
Equipped with 1 input to replicate the local control of the load via auxiliary module GW10677, GW10678 or NO-type and 1 input buttons for the centralisation OFF function.
APPLICATIONS: Bistable, monostable and timed load. Centralisation function (OFF) by means of a dedicated input, the possibility of being able to switch the load on by means of auxiliary axial modules or NO-type buttons. The devices are equipped with a configurable blue LED that can be set to OFF, easy location mode or for signalling the connected load status.
NOTES: the devices must be completed with a front button key: GW10671 must be completed with the GW13551S or GW13555S button keys. The GW10672 must be completed with the GW13552S or GW13556S button keys.



GW 10 673

Axial dimmer module - EVO

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 673	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12
GW 10 674	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	2	1/6

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two local axial operated buttons for dimming the connected load.
Equipped with 2 inputs for replicating local control of the load via the auxiliary module GW10679, GW10680 or NO-type buttons or for creating the centralisation function.
APPLICATIONS: control of the dimmable load connected to the devices. The dedicated inputs can be used to add a load switching-on function through auxiliary axial modules or NO-type buttons, or inputs can be set, via programming, for the centralised OFF function. The devices are equipped with configurable blue LEDs that can be set to OFF, location mode or for signalling the connected load.
NOTES: To avoid overheating, multiple dimmers cannot be installed side-by-side inside in the same enclosure. Insert a blanking module between two electronic devices. If two dimmers are installed in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. The devices must be completed with a front button key: GW10673 must be completed with the GW13553S or GW13557S button keys; GW10674 must be completed with the GW13554S or GW13558S button keys.



GW 10 675

Axial roller shutter module - EVO

Code	Supply voltage	Max current supplied	No. modules	Pack Carton
GW 10 675	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW 10 676	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., through 2 live interlocked output contacts. Two axial-operated local buttons control the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the auxiliary module GW10679, GW10680 or NO-type up/down buttons, or for creating the centralisation function.
APPLICATIONS: control of the motor connected to the devices. The dedicated inputs can be used to operate roller-shutters/venetian blinds via the auxiliary axial modules or NO-type up/down buttons, or they can be set, through programming, for centralisation functions (Up/Down). The devices are equipped with blue LEDs which can be configured to facilitate location at night and to signal the movement of the roller-shutter/Venetian blind.
NOTES: the devices must be completed with a front button key: GW10675 must be completed with the GW13553S or GW13557S button keys.GW10676 must be completed with the GW13554S or GW13558S button keys.



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO switch modules.
The devices are equipped with blue LEDs for easy location or to display the load status.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10677 must be completed with the GW13551S or GW13555S button keys. The GW10678 must be completed with the GW13552S or GW13556S button keys.

2-command auxiliary axial modules



GW 10 679

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO dimmer and roller-shutter modules.
The devices are equipped with blue LEDs for easy location or to display the load status.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10679 must be completed with the GW13553S or GW13557S button keys. The GW10680 must be completed with the GW13554S or GW13558S button keys.

Interchangeable keys for axial devices




GW 13 551 S

Code	Colour	Button key	No. modules	Pack Carton
GW 13 551 S	Natural satin beige	To be completed with lens	1	1/48
GW 13 552 S	Natural satin beige	To be completed with lens	2	1/48
GW 13 553 S	Natural satin beige	To be completed with 2 lenses	1	1/48
GW 13 554 S	Natural satin beige	To be completed with 2 lenses	2	1/48
GW 13 555 S	Natural satin beige	With 1 diffuser	1	1/48
GW 13 556 S	Natural satin beige	With 1 diffuser	2	1/48
GW 13 557 S	Natural satin beige	With 2 diffusers	1	1/48
GW 13 558 S	Natural satin beige	With 2 diffusers	2	1/48

NOTES: for use for completing EVO axial modules and auxiliary axial controls.

Lenses with illuminated symbol



Symbols for illuminable rocker command devices

Code	Symbol	Pack Carton
Suitable for: General services		
GW 10 501	Neutral	20/240
GW 10 502	Light	20/240
GW 10 503	Stair light	20/240
GW 10 504	Table light	20/240
GW 10 505	Bell	20/240
GW 10 506	Fan	20/240
GW 10 507	Key	20/240
GW 10 508	Alarm	20/240
GW 10 509	ON	20/240
GW 10 510	OFF	20/240
GW 10 511	Nurse	20/240
GW 10 512	Waitress	20/240
GW 10 513	Dimmer increase	20/240
GW 10 514	Dimmer decrease	20/240
GW 10 515	UP arrow	20/240
GW 10 516	DOWN arrow	20/240
GW 10 517	UP - DOWN arrow	20/240
GW 10 518	RIGHT - LEFT arrow	20/240
Suitable for: Numerical services		
GW 10 531	One	20/240
GW 10 532	Two	20/240
GW 10 533	Three	20/240
GW 10 534	Four	20/240
GW 10 535	Five	20/240
GW 10 536	Six	20/240
GW 10 537	Seven	20/240
GW 10 538	Eight	20/240
GW 10 539	Nine	20/240
GW 10 540	Zero	20/240

NOTES: for use in place of the neutral lens in the illuminated tilting control devices.

ChoruSmart - Modular devices



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

Interchangeable button keys and diffusers for rocker devices



Button keys for rocker controls and interchangeable diffusers for indicator lights

Code	Symbol	Pack Carton
Description: Keys 22x22 mm		
GW 13 541	General	4/48
GW 13 543	Key	4/48
GW 13 544	Bell	4/48
GW 13 545	Vertical arrow	4/48
GW 13 546	Horizontal arrow	4/48
Description: Diffusers		
GW 10 547	Red	4/48
GW 10 548	Green	4/48
GW 10 549	Opal diffuser	4/48

APPLICATIONS: replacement diffusers for indicators GW13142, GW13143 and GW13144.

NOTES: the ChoruSmart modular system allows the use of 22 x 22 mm interchangeable buttons in place of the standard buttons fitted on the control devices GW13141, GW13142, GW13143 and GW13144. Symbols/diffusers not suitable for the EVO axial keys.

Soft-click, rocker electronic push buttons



GW 13 915

Universal soft-click electronic push-button

Code	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 13 915	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contacts interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 13 912

Backlit soft-click electronic push-button

Code	Supply voltage	Type of contact	Button key	Type of use	Pack Carton
GW 13 912	230 V ac - 50/60 Hz	1NO 4A (AC1) 230 V ac	With diffuser	Relay, dimmer	1/12

CHARACTERISTICS: push-button for controlling latching relays, electronic switches for heavy duty loads, or dimmers with a remote control input.
Equipped with amber localisation LED.



GW 13 913

Backlit soft-click electronic push-buttons for BUS inputs

Code	Type of contact	Button key	Type of use	Pack Carton
No. modules: 1				
GW 13 913	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/12
GW 13 916	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/12
No. modules: 2				
GW 13 917	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/6
GW 13 918	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 13 914

Double soft-click electronic push-button

Code	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 13 914	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connecting KNX BUS contact interfaces or electronic control panels for moving roller shutters.

ChoruSmart - Modular devices

Touch command modules



GW 10 922

Touch one-way switch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 922	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: device for the On/Off control of 1 lighting device through a live output contact. Suitable for control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Equipped with 1 input for replicating local control of the load via the GW10924 auxiliary touch control modules, NO-type buttons and 1 input for the centralisation of the OFF function. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: bistable, monostable and timed load control. Centralisation function (OFF) through the dedicated input.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 923

Touch dimmer module

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 923	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two touch areas for dimming the connected load. Equipped with 2 inputs for replicating local control of the load via the auxiliary touch 2-command modules GW10925, NO-type buttons, or for creating the centralisation function OFF. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the dimmable load connected to the devices. Centralised OFF function, via dedicated inputs.
NOTES: to avoid overheating, multiple products cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. When installing two dimmers in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. To be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 921

Touch roller shutter module

Code	Supply voltage	Maximum output power	No. modules	Pack Carton
GW 10 921	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., by means of 2 interlocked live output contacts. Two touch areas for controlling the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the touch auxiliary 2-command modules GW10925, NO-type up/down buttons, or for creating a centralisation function (up/down). The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the motor connected to the devices. Centralisation function (Up/Down) by means of a dedicated inputs.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 924

1-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 924	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10922 module. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
NOTES: to be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 925

2-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 925	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10921 and GW10923 modules. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable, built-in buzzer and functions identifiable by the icons on the ICE touch plates.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).

ICE TOUCH plates



GW 16 955 CL

ICE TOUCH - natural beige

Code	Description	For support codes	Pack Carton
GW 16 955 CL	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).

NOTES: the symbols displayed in the image are purely indicative and may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

Blanking modules and cable outlet



GW 13 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 13 195	1 module	1	10/200
GW 13 197	1/2 module	1/2	4/48
GW 13 198	2 modules	2	1/48
GW 13 199	3 modules	3	1/48



GW 13 194

Cable outlets

Code	Description	No. modules	Pack Carton
GW 13 194	2 modules	2	6/48
GW 13 196	1 module	1	1/48

NOTES: GW13196 with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.
GW13194 with anti-traction cable fastener device, cables min 4mm ø, max 10mm ø. To be installed with the cable output downwards.

ChoruSmart - Modular devices

Movement detectors



GW 13 594

Movement detector

Code	Supply voltage	Output contacts	Pack Carton
GW 13 594	230V ac - 50/60 Hz	1NO 3 A (AC1) 230 V ac	1/4

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited.
Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA, LED loads: 60 W (max. 10 lamps).
Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.
Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly. Detection beam angle 120°, depth of detection max 8 metres.



GW 10 595

Ceiling-mounted presence detector

Code	Supply voltage	Installation height (m)	Light sensor	Dimensions HxØ (mm)	Pack Carton
GW 10 595	220/240 V ac - 50/60 Hz	From 2,2 to 6	< 3 ÷ 2000 Lux	44x111,5	1

CHARACTERISTICS: presence sensor, sensing range: 360° circle (max. diameter 18 metres); installable with fixing springs on a surface-mounted or recessed box. Suitable for the control of incandescent/halogen lamps: 1000W, LED lamps : 200W (4 / 23 W - max. 8 lamps).
NOTES: equipped with a surface-mount box capable of holding sensors from IP20 to IP44.

Relay



GW 13 724

Relay - 230V ac 50/60Hz

Code	Type	No. of poles	Output contacts	Coil	Pack Carton
No. modules: 1					
GW 13 721	Latching relay	1P	10 AX 250V ac	230V ac - 50/60 Hz	1/12
GW 13 724	Monostable relay	1P	1NO/NC 10A(AC1)/2A(AC15)250V ac	230V ac - 50/60 Hz	1/12

CHARACTERISTICS: GW13721 suitable for commanding incandescent/halogen lamps: 1000 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: GW13721,GW13723 command of lighting devices from more than one point, by means of remote NO push-buttons.
GW13721 motor function/stop commands (extractors, air agitators, etc.).
GW13724 as an auxiliary element for commanding special loads, for distance signalling, for electrical separation between the command and use circuits.



GW 13 726

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 13 726	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: inlets for remote NO push-buttons for alarms (e.g. GW13136) and alarm reset (e.g. GW13145). green LED for alarm status signalling.

HOTEL COMPONENTS - NATURAL SATIN BEIGE VERSION

Badge switch



GW 13 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 13 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted)
NOTES: badges not included. The article uses LED signalling units, not included.

Interchangeable button keys



GW 13 733

Interchangeable button keys

Code	Button key	Symbol	No. modules	Pack Carton
GW 13 731	With diffuser	DND	1	4/48
GW 13 732	With diffuser	MUR	1	4/48
GW 13 733	Neutral	DND+MUR	1	4/48

CHARACTERISTICS: with "Do not disturb" (DND) and "Make up the room" (MUR) pad printings. To be used for the customization of the Chorus command devices. GW13731 and GW13732 suitable for one-way switches, two-way switches, intermediate switches and push-buttons. GW13733 suitable for three-way switches and push-buttons with central OFF position.

Indicator light device



GW 13 736

Double indicator lamp

Code	Diffuser colour	Symbol	No. modules	Pack Carton
GW 13 736	Opal diffuser	DND+MUR	1	1/24

CHARACTERISTICS: LED signalling units not included.

POWER - NATURAL SATIN BEIGE VERSION

Socket-outlets - Italian/German standard



GW 13 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 13 201	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 13 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.



GW 13 204

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 13 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48
GW 13 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 13 208

Italian standard double socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 13 208	2x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	2	6/24

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.



GW 13 209

Italian standard triple socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 13 209	3x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	3	4/12

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213

Italian standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 233	2P+E - 16 A Dual amperage	Orange	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with safety shields.



GW 10 214

Italian/German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 234	2P+E - 16 A Dual amperage illuminable	Orange	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary network.

Socket-outlets - German Standard



GW 13 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 13 242

German standard socket-outlet with lid IP40 - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

ChoruSmart - Modular devices



GW 10 251

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields.



GW 13 341

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 341	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 351

German Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 13 241 F

German Standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 241 F	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 251 F

German standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 F	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.

Socket-outlets - French Standard



GW 13 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 13 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 13 248

French Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 248	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 258

French Standard socket-outlet for dedicated lines, with front tightening terminals - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 258	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.
To be used in combination with plugs equipped with accessory GW10260



GW 13 247 F

French standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 247 F	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 257 F

French standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 257 F	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.
To be used in combination with plugs equipped with accessory GW10260.



GW 10 260

French standard socket-outlet accessory, for dedicated lines

Code	Colour	For sockets	Pack Carton
GW 10 260	Red	GW10257F - GW10258	10/100

CHARACTERISTICS: to be fixed directly on the 2P+E French standard plug, to avoid the incorrect insertion in dedicated line circuits.

Socket-outlets - Israeli Standard



GW 13 281

Israeli Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 281	2P+E - 16 A illuminable	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 10 291

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 13 282

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 282	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 13 286

USA standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 286	2P+E - 15A	Flat parallel horizontal	1	12/48



GW 13 288

Euro-American standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 13 288	2P+E - 15A	Ø 4 mm Flat	1	12/48



GW 13 296

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 296	2P+E - 13 A	Flat	2	6/48
GW 13 297	2P+E - 15A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 13 298

Indian-South African Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 298	2P+E - 16A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

ChoruSmart - Modular devices



GW 13 299

South african standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 299	2P+E - 16A	Round Ø 4,5 mm	1	12/240

CHARACTERISTICS: with safety shields.



GW 13 301

Argentinian Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 301	2P+E - 10A	Flat	2	6/48



GW 13 306

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 306	2P+E - 10A	Flat	2	6/48
GW 13 307	2P+E - 15A	Flat	2	6/48



GW 13 310

Multistandard socket-outlet - 250/127V ac

Code	Description	No. modules	Pack Carton
GW 13 310	2P+E - 13A/250 V ac - 15A/127 V ac	2	10/40

CHARACTERISTICS: with safety shields.

APPLICATIONS: suitable for plugs compliant with the following standards: Europlug 2P 2.5A - 250V, British 2P+E 13A - 250V, Italian 2P 10A - 250V, Danish 2P 10A - 250V, Chinese 2P+E 10A - 250V, Argentinean/ Australian 2P+E 10A - 250V, Indian 2P+E 6A - 250V, USA 2P+E 15A - 127V. Not suitable for 2P+E German and French sockets because they don't offer earth continuity.

NOTES: the multistandard energy sockets GW1x310 are in compliance with the safety requirements defined by the International Standard IEC 60884-1. These sockets may not be in compliance with the standard sheets used in the country where they are sold, hence their usage could be prohibited or however, restricted only for specific applications. The plugs allowed are listed in the technical datasheet. Please contact directly Gewiss technical service for further information.



GW 13 392

Chinese standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 391	2P+E - 10A	Flat	2	6/48
GW 13 392	2P+E - 16A	Flat	2	6/48

CHARACTERISTICS: with safety shields.

Interlocked switched socket-outlets



GW 13 311

Interlocked switched socket-outlets with miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	No. modules	Pack Carton
GW 13 311	2P+E - 16A	P17-P11	1P+N 16A	3 kA	2	1/6
GW 13 312	2P+E - 16A	P40	1P+N 16A	3 kA	3	1/4

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.



GW 13 321

Interlocked switched socket-outlets with residual miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	Idn	No. modules	Pack Carton
GW 13 321	2P+E - 16A	P17-P11	1P+N 16A	3 kA	10 mA	3	1/4
GW 13 322	2P+E - 16A	P40	1P+N 16A	3 kA	10 mA	4	1/2

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic) and residual current circuit breaker (type A). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.

Shaver socket-outlet



GW 13 331

Euro-American standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 13 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - NATURAL SATIN BEIGE VERSION

TV-SAT sockets



GW 13 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 13 361	Direct	0 dB	1	1/48
GW 13 362	Through wiring	5 dB	1	1/24
GW 13 363	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW13361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5dB GW13362 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load. (TV, VCR, SAT receiver or 75-Ohm termination)

ChoruSmart - Modular devices



GW 13 371

Coaxial TV-SAT sockets (5-2400 MHz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 13 371	Direct	0 dB	1	1/48
GW 13 372	Through wiring	5 dB	1	1/24
GW 13 373	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW13371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5dB GW13372 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 13 382

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 13 381	TV-FM	Direct	0 dB	2	1/24
GW 13 382	TV-FM-SAT	Direct	0 dB	2	1/24
GW 13 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW13381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW13382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW13383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.



GW 13 367

Coaxial TV sockets (5-2400 Mhz), class A shielding - male IEC connector Ø 9.5mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 13 367	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 13 377

Coaxial TV-SAT sockets (5-2400 Mhz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 13 377	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 13 386

Covers for TV-SAT-R antenna sockets

Code	Description	No. holes	Pack Carton
GW 13 386	For TV-R base	2	1/24
GW 13 387	For TV/R-SAT base	2	1/24

APPLICATIONS: suitable for integration on the Chorus range of TV-SAT-R standard bases available on the market.
ACCESSORIES SUPPLIED: fixing screws.

Telephone sockets



GW 13 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 13 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.



GW 13 409

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 13 409	RJ11	Screw-on terminals	2	1/24

APPLICATIONS: telephone, telefax, modem.



GW 13 406

British standard telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 13 406	6 contacts	Screw-on terminals	1	1/24

Data sockets



GW 13 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 13 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 13 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 13 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 13 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.

ChoruSmart - Modular devices




GW 13 431

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 13 431	AMP / Keystone Jack	1	1/48
GW 13 438	SYSTIMAX COMMSCOPE	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the GEWISS adapter.



GW 13 433

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 13 433	AMP / Keystone Jack	2	4/100

NOTES: due to technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the data socket and the GEWISS empty enclosure.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.

NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

Socket-outlets for auxiliary circuits



GW 13 451

SELV sockets

Code	Description	For plug pins	No. modules	Pack Carton
GW 13 451	2P - 6A - 24V	Ø 3 mm	1	12/24
GW 13 452	2P - 6A - 24V polarised	Flat	1	12/24

CHARACTERISTICS: Centre distance 12.4mm.

Audio and video sockets



GW 13 453

Audio and video sockets

Code	Description	No. modules	Pack Carton
GW 13 453	Double RCA	1	1/24
GW 13 454	For loudspeaker	1	1/24
GW 13 458	Speaker socket	1	1/24

CHARACTERISTICS: GW13453 double RCA stud connector, red and white, weld-in connection.
GW13454 welding connection. GW13458 front access terminals for inserting 1.5 mm² rigid wires, insulator punching rear connection suitable for cables AWG24 or max 0.25mm².

USB and HDMI couplers and sockets



GW 13 459

USB sockets

Code	Description	No. modules	Pack Carton
GW 13 459	USB socket-outlet	1	1/24

CHARACTERISTICS: A-type USB 2.0 female connector, with screw terminals on the back.



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB charger



GW 13 415

USB power supply for electronic devices

Code		Supply voltage	Output voltage	Max. total power output	PD	USB-IF	Outputs/N° and type	No. modules	Pack Carton
GW 13 449		100 ÷ 240 V ac - 50/60 Hz	5V dc	15 W	-	-	2 / A+C	1	1/10
GW 13 415	①	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	30 W	Yes	Yes	1 / C	1	1/12
GW 13 417	②	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	63 W	Yes	Yes	2 / C	2	1/6

CHARACTERISTICS: GW13449 USB charger suitable for charging a single electronic device (e.g., tablet) or two devices simultaneously (e.g., tablet and smartphone). The distribution of power output across the two ports depends on the charging status of the connected devices.
GW13415 USB charger for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones, and smartwatches. Charging compatibility with market devices is guaranteed by USB-IF certification.
GW13417 USB charger for fast charging up to 63W with Power Delivery technology. Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools. Charging compatibility with market devices is guaranteed by USB-IF certification.

NEWS
Availability: ① July 2025 ② November 2025

ChoruSmart - Modular devices

PROTECTION - NATURAL SATIN BEIGE VERSION

Miniature circuit breakers



GW 13 463

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. modules	Pack Carton
GW 13 461	Single pole (1P)	6	3 kA	1	1/12
GW 13 462	Single pole (1P)	10	3 kA	1	1/12
GW 13 463	Single pole (1P)	16	3 kA	1	1/12
GW 13 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 13 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 13 468	Two-pole (1P+N)	16	3 kA	1	1/12



GW 13 488

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Rated current (A)	Breaking capacity	Idn	No. modules	Pack Carton
GW 13 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 13 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 13 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 13 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 13 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 13 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

Protection devices



GW 13 491

Fuse holder - 250V ac

Code	Rated current (A)	Fuse type	No. modules	Pack Carton
GW 13 491	16	Ø 6.3x32 mm	1	1/12

CHARACTERISTICS: fuse not included.



GW 13 492

Surge protection device - 230V ac

Code	Uc	Up	No. modules	Pack Carton
GW 13 492	275 V ac 50/60Hz	1 kV	1	1/12

CHARACTERISTICS: green LED for status signalling.
APPLICATIONS: protection of electronic devices (TV, HI-FI, computer, etc.) from overvoltage (resulting from atmospheric conditions or manoeuvres) that could be channelled from the power supply lines.

INDICATOR - NATURAL SATIN BEIGE VERSION

Indicator light devices



GW 13 642

Single indicator lamps - 1/2 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 13 641	Opal diffuser	Neutral	1/2	2/48
GW 13 642	Green	Safety	1/2	2/48
GW 13 643	Red	Danger	1/2	2/48
GW 13 644	Amber	Attention	1/2	2/48

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 13 622

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 13 621	Opal diffuser	Neutral	1	1/24
GW 13 622	Green	Safety	1	1/24
GW 13 623	Red	Danger	1	1/24
GW 13 624	Amber	Attention	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 13 629

Double indicator lamps - 1 module

Code	Diffuser colour	No. modules	Pack Carton
GW 13 628	Opal diffuser	1	1/24
GW 13 629	Red/green	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 13 633

Protruding indicator lamps - 2 modules

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 13 631	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 13 632	12V ac/dc - 230V ac 50/60 Hz	Green	White LED	2	1/24
GW 13 633	12V ac/dc - 230V ac 50/60 Hz	Red	White LED	2	1/24
GW 13 634	12V ac/dc - 230V ac 50/60 Hz	Amber	White LED	2	1/24

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.

ChoruSmart - Modular devices



GW 13 656

Stair riser lamp

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 13 651	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 13 656	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	4	1/2

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.

Anti black-out and emergency lamps



GW 13 661

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	Pack Carton
GW 13 661	230 V ac - 50/60 Hz	Ni - Mh	2 h	LED	1/6

CHARACTERISTICS: equipped with a 3-position selector on the front panel, for anti black-out inhibition and night functioning.
To be inserted in any socket-outlet of the Italian, German or French type. Highly efficient, white LED lamp.



GW 13 662

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 13 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/12

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.



GW 13 663

Autonomous emergency lamps

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 13 663	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	2	1/6
GW 13 666	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	4	1/2

CHARACTERISTICS: green mains presence signal LED. Highly efficient, white LED lamps.
APPLICATIONS: compliant with standards EN60598-2-22.

Acoustic signalling devices

Ringers



GW 13 601

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 13 601	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24
GW 13 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 13 606

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 13 606	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24
GW 13 607	230V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ChoruSmart - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - NATURAL SATIN BEIGE VERSION

Temperature control devices



GW 13 709

Connected thermostat - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 13 709	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 13 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 13 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.



GW 16 970 CL

Thermo ICE Wi-Fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CL	Natural beige	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1/16

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch commands (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or by remote via specific apps (smartphone and tablet).

APPLICATIONS: the THERMO ICE Wi-Fi can be used:
- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Dimmer

Universal rotating electronic regulator



GW 13 575

Code	Supply voltage	No. modules	Pack Carton
GW 13 575	230V ac - 50 Hz	1	1/12

CHARACTERISTICS: suitable for dimming incandescent and halogen lamps 230 V ac (10-160 W); low-voltage halogen lamps (12 V ac) with electronic transformers (10-160 W) and LED lamps 230 V ac (4-160W), rotary control with 2-way switch. Equipped with amber-colour-red signalling LED. Can be operated without neutral connection.

NOTES: the installation of more than one dimmer side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two dimmers. If installing two dimmers in the same box, the maximum loads that can be controlled by each dimmer must be reduced by 50%.

Rotating electronic regulators for resistive/inductive loads



GW 13 564

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 13 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 13 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW13567 rotary command with two-way switch.

GW13564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact GEWISS Customer Service to check the product meets the regulations of the country concerned before importing it.

NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Universal electronic regulators with push-button



GW 13 572 A

Code	Supply voltage	No. modules	Pack Carton
GW 13 572 A	230V ac - 50/60 Hz	1	1/12
GW 13 573 A	230V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.

NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Electronic regulator with button for resistive/inductive loads



GW 13 568

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 13 568	230V ac - 50 Hz	60 - 500 W	60 - 500 VA	1	1/12

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.

NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

TECHNICAL ALARMS - NATURAL SATIN BEIGE VERSION

Gas detectors



GW 13 712

Methane gas detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 13 712	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 720

Power supply unit 12Vdc

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

Anti-flood system with Zigbee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.



GW 13 750

Blanking module for housing RF Zigbee actuators

Code	Colour	No. modules	Pack Carton
GW 13 750	Natural satin beige	1	1/12

CHARACTERISTICS: 1-module blanking module with pad printing. Allows the housing and fast identification of the flush-mounting RF Zigbee actuator.
NOTES: snap-in assembly.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps - 2W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Dimensions (mm)	Pack Carton
GW 20 902	12V ac/dc	2 W	Incandescence	White	S6x36	50
GW 20 903	24V ac/dc	2 W	Incandescence	White	S6x36	50

Accessories



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




ChoruSmart




Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

Satin black modular devices





The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in satin black, elegant and classy, they include rocker button keys with ½, 1 and 2 modules to optimise space, and axial keys in EVO or SMART version for advanced functions. The front attachment system facilitates assembly and release without removing the support.

COMMAND - SATIN BLACK VERSION

Command devices - rockers - screw terminals



GW 12 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 12 001	1P - 16AX	Neutral	200 W	12/96
GW 12 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 12 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 1/2				
GW 12 021	1P - 10AX	Neutral	100 W	12/24
GW 12 022	1P - 10AX illuminable	With diffuser	100 W	6/24
No. modules: 2				
GW 12 031	1P - 16AX	Neutral	200 W	6/24
GW 12 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 12 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 12 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 12 004	2P - 16 AX	Neutral	0/1	200 W	12/48
GW 12 005	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	12/24
GW 12 006	2P - 10AX	With key	0/1	100 W	1/12
No. modules: 2					
GW 12 034	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 12 035	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW12006 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 12 007

One-way switch 2P - 250V ac - heavy duty loads

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 12 007	2P - 25 AX	Neutral	0/1	250 W	12/24

APPLICATIONS: suitable for particular heavy-duty loads (e.g. fluorescent lamp batteries) or high-consumption devices. (e.g. ovens, air-conditioners, boilers, etc.)



GW 12 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 12 051	1P - 16AX	Neutral	200 W	12/96
GW 12 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 12 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
GW 12 054	1P - 10AX	With key	100 W	1/12
No. modules: 1/2				
GW 12 061	1P - 10AX	Neutral	100 W	6/24
No. modules: 2				
GW 12 071	1P - 16AX	Neutral	200 W	6/24
GW 12 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 12 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW12054 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 12 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 12 091	1P - 16AX	Neutral	200 W	12/48
GW 12 092	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 12 093	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 12 101	1P - 16AX	Neutral	200 W	6/12
GW 12 102	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 12 103	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 12 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 12 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 12 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 12 122

Three-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 12 122	2P - 10AX	Neutral	UP - DOWN	100 W	12/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

ChoruSmart - Modular devices



GW 12 131

Push-buttons 1P - 250V ac


Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 12 131	1P NO - 16A	Neutral	-	12/96
GW 12 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 12 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 12 136	1P NO - 16A	Pull-cord	-	1/12
GW 12 137	1P NC - 16A	Neutral	O red	12/24
GW 12 138	1P NC+NO - 16 A	Stop	Red	12/24
GW 12 139	1P NO+NC - 16 A	Start	Green	12/24
GW 12 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 12 141	1P NO+NO - 16 A	Double	-	12/24
GW 12 142	1P NO - 16A illuminable	Green diffuser	-	12/24
GW 12 143	1P NO - 16A illuminable	Red diffuser	-	12/24
GW 12 144	1P NO - 16A illuminable	Opal diffuser	-	12/24
GW 12 151	1P NO - 16A illuminable	With replaceable neutral lens	Light	12/24
GW 12 152	1P NO - 16A illuminable	With replaceable neutral lens	Key	12/24
GW 12 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 1/2				
GW 12 161	1P NO - 10A	Neutral	-	6/24
GW 12 162	1P NO - 10A illuminable	With diffuser	-	6/24
No. modules: 2				
GW 12 171	1P NO - 16A	Neutral	-	6/24
GW 12 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 12 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW12136 Cord in insulating material, 140cm long, with red knob.

GW12140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW12141 independent push-buttons that can also be activated simultaneously.



GW 12 134

Push-buttons 2P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 12 134	2P NO - 16A	Neutral	O	12/24
GW 12 135	2P NO - 10A illuminable	With replaceable neutral lens	-	12/24
GW 12 145	2P NO - 10A	With key	-	1/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

NOTES: GW12145 equipped with 2 keys. Spare keys: GW30912.



GW 12 191

Push-buttons 1P with illuminated name plate - 250V ac

Code	Description	Lamp voltage	Lamp	Lamp power	Pack Carton
No. modules: 2					
GW 12 191	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm (not included)	2 W	6/24
No. modules: 3					
GW 12 192	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	4/16

CHARACTERISTICS: lamp not included.

Command devices - rockers - quick wiring terminals



GW 12 031 F

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 12 031 F	1P - 16AX	Neutral	200 W	6/24
GW 12 032 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 12 033 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 12 034 F

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 12 034 F	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 12 035 F	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 12 071 F

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 12 071 F	1P - 16AX	Neutral	200 W	6/24
GW 12 072 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 12 073 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 12 101 F

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 12 101 F	1P - 16AX	Neutral	200 W	6/12
GW 12 102 F	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 12 103 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 12 171 F

Push-buttons 1P - 250V ac

Code	Description	Button key	Pack Carton
No. modules: 2			
GW 12 171 F	1P NO - 16A	Neutral	6/24
GW 12 172 F	1P NO - 16A illuminable	With diffuser	6/24
GW 12 173 F	1P NO - 16A illuminable	With replaceable neutral lens	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.

ChoruSmart - Modular devices



GW 12 160 F

Combined command devices - rockers - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 12 078 F	Twin two-way switch 1P - 16 AX	Neutral	-	200 W	6/24
GW 12 159 F	Two-way switch 1P - 16 AX / Push-button 1P NO - 16A	Neutral	-	200 W	6/24
GW 12 160 F	Twin push-button 1P NO - 16 A	Neutral	UP - DOWN - STOP	-	6/24

NOTES: spring quick wiring, no tools necessary.

Command devices - axial - screw terminals



GW 10 671

Axial switch module - EVO

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 671	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12
GW 10 672	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 On/Off lighting device through a live output contact. Suitable for the control of incandescent and halogen (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Local push button with axial activation for control of the lamps connected to the device.
Equipped with 1 input to replicate the local control of the load via auxiliary module GW10677, GW10678 or NO-type and 1 input buttons for the centralisation OFF function.
APPLICATIONS: Bistable, monostable and timed load command. Centralisation function (OFF) by means of a dedicated input, the possibility of being able to switch the load on by means of auxiliary axial modules or NO-type buttons. The devices are equipped with a configurable blue LED that can be set to OFF, easy location mode or for signalling the connected load status.
NOTES: the devices must be completed with a front button key: GW10671 must be completed with the GW12551S or GW12555S button keys. The GW10672 must be completed with the GW12552S or GW12556S button keys.



GW 10 673

Axial dimmer module - EVO

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 673	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12
GW 10 674	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	2	1/6

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two local axial operated buttons for dimming the connected load.
Equipped with 2 inputs for replicating local control of the load via the auxiliary module GW10679, GW10680 or NO-type buttons or for creating the centralisation function.
APPLICATIONS: control of the dimmable load connected to the devices. The dedicated inputs can be used to add a load switching-on function through auxiliary axial modules or NO-type buttons, or inputs can be set, via programming, for the centralised OFF function. The devices are equipped with configurable blue LEDs that can be set to OFF, location mode or for signalling the connected load.
NOTES: To avoid overheating, multiple dimmers cannot be installed side-by-side inside in the same enclosure. Insert a blanking module between two electronic devices. If two dimmers are installed in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. The devices must be completed with a front button key: GW10673 must be completed with the GW12553S or GW12557S button keys; GW10674 must be completed with the GW12554S or GW12558S button keys.



GW 10 675

Axial roller shutter module - EVO

Code	Supply voltage	Max current supplied	No. modules	Pack Carton
GW 10 675	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW 10 676	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., through 2 live interlocked output contacts. Two axial-operated local buttons control the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the auxiliary module GW10679, GW10680 or NO-type up/down buttons, or for creating the centralisation function.
APPLICATIONS: control of the motor connected to the devices. The dedicated inputs can be used to operate roller-shutters/venetian blinds via the auxiliary axial modules or NO-type up/down buttons, or they can be set, through programming, for centralisation functions (Up/Down). The devices are equipped with blue LEDs which can be configured to facilitate location at night and to signal the movement of the roller-shutter/Venetian blind.
NOTES: the devices must be completed with a front button key: GW10675 must be completed with the GW12553S or GW12557S button keys.GW10676 must be completed with the GW12554S or GW12558S button keys.



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO switch modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10677 must be completed with the GW12551S or GW12555S button keys. GW10678 must be completed with the GW12552S or GW12556S button keys.

2-command auxiliary axial modules



GW 10 679

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO dimmer and roller-shutter modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10679 must be completed with the GW12553S or GW12557S button keys. GW10680 must be completed with the GW12554S or GW12558S button keys.

Interchangeable keys for axial devices




GW 12 551 S

Code	Colour	Button key	No. modules	Pack Carton
GW 12 551 S	Satin black	To be completed with lens	1	1/48
GW 12 552 S	Satin black	To be completed with lens	2	1/48
GW 12 553 S	Satin black	To be completed with 2 lenses	1	1/48
GW 12 554 S	Satin black	To be completed with 2 lenses	2	1/48
GW 12 555 S	Satin black	With 1 diffuser	1	1/48
GW 12 556 S	Satin black	With 1 diffuser	2	1/48
GW 12 557 S	Satin black	With 2 diffusers	1	1/48
GW 12 558 S	Satin black	With 2 diffusers	2	1/48

NOTES: for use to complete the EVO axial modules and auxiliary axial controls.

Lens with illuminated symbol



Symbols for illuminable rocker command devices

Code	Symbol	Pack Carton
Suitable for: General services		
GW 10 501	Neutral	20/240
GW 10 502	Light	20/240
GW 10 503	Stair light	20/240
GW 10 504	Table light	20/240
GW 10 505	Bell	20/240
GW 10 506	Fan	20/240
GW 10 507	Key	20/240
GW 10 508	Alarm	20/240
GW 10 509	ON	20/240
GW 10 510	OFF	20/240
GW 10 511	Nurse	20/240
GW 10 512	Waitress	20/240
GW 10 513	Dimmer increase	20/240
GW 10 514	Dimmer decrease	20/240
GW 10 515	UP arrow	20/240
GW 10 516	DOWN arrow	20/240
GW 10 517	UP - DOWN arrow	20/240
GW 10 518	RIGHT - LEFT arrow	20/240
Suitable for: Numerical services		
GW 10 531	One	20/240
GW 10 532	Two	20/240
GW 10 533	Three	20/240
GW 10 534	Four	20/240
GW 10 535	Five	20/240
GW 10 536	Six	20/240
GW 10 537	Seven	20/240
GW 10 538	Eight	20/240
GW 10 539	Nine	20/240
GW 10 540	Zero	20/240

NOTES: for use in place of the neutral lens in the illuminated tilting control devices.

ChoruSmart - Modular devices



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

Interchangeable button keys and diffusers



Button keys for rocker controls and interchangeable diffusers for indicator lights

Code	Symbol	Pack Carton
Description: Keys 22x22 mm		
GW 12 541	General	4/48
GW 12 543	Key	4/48
GW 12 544	Bell	4/48
GW 12 545	Vertical arrow	4/48
GW 12 546	Horizontal arrow	4/48
Description: Diffusers		
GW 10 547	Red	4/48
GW 10 548	Green	4/48
GW 10 549	Opal diffuser	4/48

APPLICATIONS: replacement diffusers for indicators GW12142, GW12143 and GW12144.

NOTES: The ChoruSmart modular system allows the use of interchangeable buttons 22 x 22 mm to replace the standard buttons supplied on command devices GW12141, GW12142, GW12143 and GW12144.

Soft-click, rocker electronic push buttons



GW 12 915

Universal soft-click electronic push-button

Code	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 12 915	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contact interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 12 912

Backlit soft-click electronic push-button

Code	Supply voltage	Type of contact	Button key	Type of use	Pack Carton
GW 12 912	230 V ac - 50/60 Hz	1NO 4A (AC1) 230 V ac	With diffuser	Relay, dimmer	1/12

CHARACTERISTICS: push-button for controlling latching relays, electronic switches for heavy duty loads, or dimmers with a remote control input.
Equipped with amber localisation LED.



GW 12 913

Backlit soft-click electronic push-buttons for BUS inputs

Code	Type of contact	Button key	Type of use	Pack Carton
No. modules: 1				
GW 12 913	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/12
GW 12 916	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/12
No. modules: 2				
GW 12 917	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/6
GW 12 918	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 12 914

Double soft-click electronic push-button

Code	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 12 914	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connecting KNX BUS contact interfaces or electronic control panels for moving roller shutters.

ChoruSmart - Modular devices

Touch command modules



GW 10 922

Touch one-way switch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 922	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: device for the On/Off control of 1 lighting device through a live output contact. Suitable for control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Equipped with 1 input for replicating local control of the load via the GW10924 auxiliary touch control modules, NO-type buttons and 1 input for the centralisation of the OFF function. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: bistable, monostable and timed load control. Centralisation function (OFF) through the dedicated input.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 923

Touch dimmer module

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 923	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two touch areas for dimming the connected load. Equipped with 2 inputs for replicating local control of the load via the auxiliary touch 2-command modules GW10925, NO-type buttons, or for creating the centralisation function OFF. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the dimmable load connected to the devices. Centralised OFF function, via dedicated inputs.
NOTES: to avoid overheating, multiple products cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. When installing two dimmers in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. To be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 921

Touch roller shutter module

Code	Supply voltage	Maximum output power	No. modules	Pack Carton
GW 10 921	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., by means of 2 interlocked live output contacts. Two touch areas for controlling the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the touch auxiliary 2-command modules GW10925, NO-type up/down buttons, or for creating a centralisation function (up/down). The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the motor connected to the devices. Centralisation function (Up/Down) by means of a dedicated inputs.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 924

1-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 924	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10922 module. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
NOTES: to be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 925

2-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 925	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10921 and GW10923 modules. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable, built-in buzzer and functions identifiable by the icons on the ICE touch plates.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).

ICE TOUCH plates



GW 16 955 CN

ICE TOUCH - black

Code	Description	For support codes	Pack Carton
GW 16 955 CN	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).

NOTES: the symbols displayed in the image are purely indicative: they may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

Blanking modules and cable outlet



GW 12 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 12 195	1 module	1	10/200
GW 12 197	1/2 module	1/2	4/48
GW 12 198	2 modules	2	1/48
GW 12 199	3 modules	3	1/48



GW 12 194

Cable outlet

Code	Description	No. modules	Pack Carton
GW 12 194	2 modules	2	6/48
GW 12 196	1 module	1	1/48

NOTES: GW12196 with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.
GW12194 with anti-traction cable fastener device, cables min 4mm ø, max 10mm ø. To be installed with the cable output downwards.

ChoruSmart - Modular devices

Movement detectors



GW 12 594

Movement detector

Code	Supply voltage	Output contacts	Pack Carton
GW 12 594	230V ac - 50/60 Hz	1NO 3 A (AC1) 230 V ac	1/4

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited.
Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA, LED loads: 60 W (max. 10 lamps).
Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.
Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly. Detection beam angle 120°, depth of detection max 8 metres.



GW 10 595

Ceiling-mounted presence detector

Code	Supply voltage	Installation height (m)	Light sensor	Dimensions HxØ (mm)	Pack Carton
GW 10 595	220/240 V ac - 50/60 Hz	From 2,2 to 6	< 3 ÷ 2000 Lux	44x111,5	1

CHARACTERISTICS: presence sensor, sensing range: 360° circle (max. diameter 18 metres); installable with fixing springs on a surface-mounted or recessed box. Suitable for the control of incandescent/halogen lamps: 1000W, LED lamps : 200W (4 / 23 W - max. 8 lamps).
NOTES: equipped with a surface-mount box capable of holding sensors from IP20 to IP44.

Relay



GW 12 721

Relay - 230V ac 50/60Hz

Code	Type	No. of poles	Output contacts	Coil	Pack Carton
No. modules: 1					
GW 12 721	Latching relay	1P	10 AX 250V ac	230V ac - 50/60 Hz	1/12
GW 12 724	Monostable relay	1P	1NO/NC 10A(AC1)/2A(AC15)250V ac	230V ac - 50/60 Hz	1/12

CHARACTERISTICS: GW12721 suitable for commanding incandescent/halogen lamps: 1000 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: GW12721 command of lighting devices from more than one point, by means of remote NO push-buttons.
GW12721, motor function/stop commands (extractors, air agitators, etc.).
GW12724 as an auxiliary element for commanding special loads, for distance signalling, for electrical separation between the command and use circuits.



GW 12 726

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 12 726	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: inlets for remote NO push-buttons for alarms (e.g. GW12136) and alarm reset (e.g. GW12145). green LED for alarm status signalling.

HOTEL COMPONENTS - SATIN BLACK VERSION

Badge switch



GW 12 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 12 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted)
NOTES: badges not included. The article uses LED signalling units, not included.

Interchangeable button keys



GW 12 733

Interchangeable button keys

Code	Button key	Symbol	No. modules	Pack Carton
GW 12 731	With diffuser	DND	1	4/48
GW 12 732	With diffuser	MUR	1	4/48
GW 12 733	Neutral	DND+MUR	1	4/48

CHARACTERISTICS: with "Do not disturb" (DND) and "Make up the room" (MUR) pad printings. To be used for the customization of the Chorus command devices. GW12731 and GW12732 suitable for one-way switches, two-way switches, intermediate switches and push-buttons. GW12733 suitable for three-way switches and push-buttons with central OFF position.

Indicator light device



GW 12 736

Double indicator lamp

Code	Diffuser colour	Symbol	No. modules	Pack Carton
GW 12 736	Opal diffuser	DND+MUR	1	1/24

CHARACTERISTICS: LED signalling units not included.

POWER - SATIN BLACK VERSION

Socket-outlets - Italian/German standard



GW 12 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 12 201	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 12 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.



GW 12 204

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 12 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48
GW 12 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 12 208

Italian standard double socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 12 208	2x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	2	6/24

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.



GW 12 209

Italian standard triple socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 12 209	3x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	3	4/12

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213

Italian standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 233	2P+E - 16 A Dual amperage	Orange	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with safety shields.



GW 10 214

Italian/German Standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 234	2P+E - 16 A Dual amperage illuminable	Orange	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary network.

Socket-outlets - German Standard



GW 12 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 12 242

German standard socket-outlet with lid IP40 - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

ChoruSmart - Modular devices



GW 10 251

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields.



GW 12 341

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 341	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 351

German Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 12 241 F

German Standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 241 F	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 251 F

German standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 F	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.

Socket-outlets - French Standard



GW 12 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 12 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 12 248

French Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 248	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 258

French Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 258	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.
To be used in combination with plugs equipped with accessory GW10260.



GW 12 247 F

French standard socket-outlet with quick wiring terminals - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 247 F	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 257 F

French standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 257 F	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.
To be used in combination with plugs equipped with accessory GW10260.



GW 10 260

French standard socket-outlet accessory, for dedicated lines

Code	Colour	For sockets	Pack Carton
GW 10 260	Red	GW10257F - GW10258	10/100

CHARACTERISTICS: to be fixed directly on the 2P+E French standard plug, to avoid the incorrect insertion in dedicated line circuits.

Socket-outlets - Israeli Standard



GW 12 281

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 281	2P+E - 16A	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields.



GW 10 291

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 12 282

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 282	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 12 286

USA standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 286	2P+E - 15A	Flat parallel horizontal	1	12/48



GW 12 288

Euro-American standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 12 288	2P+E - 15A	Ø 4 mm Flat	1	12/48



GW 12 296

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 296	2P+E - 13 A	Flat	2	6/48
GW 12 297	2P+E - 15A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 12 298

Indian/South African Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 298	2P+E - 16A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

ChoruSmart - Modular devices



GW 12 299

South african standard socket-outlet - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 299	2P+E - 16A	Round Ø 4,5 mm	1	12/240

CHARACTERISTICS: with safety shields.



GW 12 301

Argentinian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 301	2P+E - 10A	Flat	2	6/48



GW 12 306

Australian standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 306	2P+E - 10A	Flat	2	6/48
GW 12 307	2P+E - 15A	Flat	2	6/48



GW 12 310

Multistandard socket-outlet - 250/127V ac

Code	Description	No. modules	Pack Carton
GW 12 310	2P+E - 13A/250 V ac - 15A/127 V ac	2	10/40

CHARACTERISTICS: with safety shields.

APPLICATIONS: suitable for plugs compliant with the following standards: Europlug 2P 2.5A - 250V, British 2P+E 13A - 250V, Italian 2P 10A - 250V, Danish 2P 10A - 250V, Chinese 2P+E 10A - 250V, Argentinean/ Australian 2P+E 10A - 250V, Indian 2P+E 6A - 250V, USA 2P+E 15A - 127V. Not suitable for 2P+E German and French sockets because they don't offer earth continuity.

NOTES: the multistandard energy sockets GW1x310 are in compliance with the safety requirements defined by the International Standard IEC 60884-1. These sockets may not be in compliance with the standard sheets used in the country where they are sold, hence their usage could be prohibited or however, restricted only for specific applications. The plugs allowed are listed in the technical datasheet. Please contact directly Gewiss technical service for further information.



GW 12 392

Chinese standard socket-outlets - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 391	2P+E - 10A	Flat	2	6/48
GW 12 392	2P+E - 16A	Flat	2	6/48

CHARACTERISTICS: with safety shields.

Interlocked switched socket-outlets



GW 12 311

Interlocked switched socket-outlets with miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	No. modules	Pack Carton
GW 12 311	2P+E - 16A	P17-P11	1P+N 16A	3 kA	2	1/6
GW 12 312	2P+E - 16A	P40	1P+N 16A	3 kA	3	1/4

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.



GW 12 321

Interlocked switched socket-outlets with residual miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	Idn	No. modules	Pack Carton
GW 12 321	2P+E - 16A	P17-P11	1P+N 16A	3 kA	10 mA	3	1/4
GW 12 322	2P+E - 16A	P40	1P+N 16A	3 kA	10 mA	4	1/2

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic) and residual current circuit breaker (type A). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.

Shaver socket-outlet



GW 12 331

Euro-American standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 12 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - SATIN BLACK VERSION

TV-SAT sockets



GW 12 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 12 361	Direct	0 dB	1	1/48
GW 12 362	Through wiring	5 dB	1	1/24
GW 12 363	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW12361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24 V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5dB GW12362 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).

ChoruSmart - Modular devices



GW 12 371

Coaxial TV-SAT sockets (5-2400 MHz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 12 371	Direct	0 dB	1	1/48
GW 12 372	Through wiring	5 dB	1	1/24
GW 12 373	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW12371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24 V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5dB GW12372 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 12 382

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 12 381	TV-FM	Direct	0 dB	2	1/24
GW 12 382	TV-FM-SAT	Direct	0 dB	2	1/24
GW 12 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW12381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW12382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW12383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.



GW 12 367

Coaxial TV sockets (5-2400 Mhz), class A shielding - male IEC connector Ø 9.5mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 12 367	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.




GW 12 377

Coaxial TV-SAT sockets (5-2400 Mhz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 12 377	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 12 386

Covers for TV-SAT-R antenna sockets

Code	Description	No. holes	Pack Carton
GW 12 386	For TV-R base	2	1/24
GW 12 387	For TV/R-SAT base	2	1/24

APPLICATIONS: suitable for integration on the Chorus range of TV-SAT-R standard bases available on the market.
ACCESSORIES SUPPLIED: fixing screws.

Telephone sockets



GW 12 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 12 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.



GW 12 409

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 12 409	RJ11	Screw-on terminals	2	1/24

APPLICATIONS: telephone, telefax, modem.



GW 12 406

British standard telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 12 406	6 contacts	Screw-on terminals	1	1/24

Data sockets



GW 12 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 12 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 12 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 12 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 12 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.

ChoruSmart - Modular devices



GW 12 431

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 12 431	AMP / Keystone Jack	1	1/48
GW 12 438	SYSTIMAX COMMSCOPE	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the GEWISS adapter.



GW 12 433

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 12 433	AMP / Keystone Jack	2	4/100

NOTES: due to technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the data socket and the GEWISS empty enclosure.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

Socket-outlets for auxiliary circuits



GW 12 451

SELV sockets

Code	Description	For plug pins	No. modules	Pack Carton
GW 12 451	2P - 6A - 24V	Ø 3 mm	1	12/24
GW 12 452	2P - 6A - 24V polarised	Flat	1	12/24

CHARACTERISTICS: Centre distance 12,4mm.

Audio and video sockets



GW 12 453

Audio and video sockets

Code	Description	No. modules	Pack Carton
GW 12 453	Double RCA	1	1/24
GW 12 454	For loudspeaker	1	1/24
GW 12 458	Speaker socket	1	1/24

CHARACTERISTICS: GW12453 double RCA stud connector, red and white, weld-in connection.
GW12454 welding connection. GW12458 front access terminals for inserting 1.5 mm² rigid wires, insulator punching rear connection suitable for cables AWG24 or max 0.25mm².

USB and HDMI couplers and sockets



GW 12 459

USB sockets

Code	Description	No. modules	Pack Carton
GW 12 459	USB socket-outlet	1	1/24

CHARACTERISTICS: A-type USB 2.0 female connector, with screw terminals on the back.



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB chargers



GW 12 415

USB power supply for electronic devices

Code		Supply voltage	Output voltage	Max. total power output	PD	USB-IF	Outputs/N° and type	No. modules	Pack Carton
GW 12 449		100 ÷ 240 V ac - 50/60 Hz	5V dc	15 W	-	-	2 / A+C	1	1/10
GW 12 415	①	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	30 W	Yes	Yes	1 / C	1	1/12
GW 12 417	②	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	63 W	Yes	Yes	2 / C	2	1/6

CHARACTERISTICS: GW12449 USB charger suitable for charging a single electronic device (e.g., tablet) or two devices simultaneously (e.g., tablet and smartphone). The distribution of power output across the two ports depends on the charging status of the connected devices.
GW12415 USB charger for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones, and smartwatches. Charging compatibility with market devices is guaranteed by USB-IF certification.
GW12417 USB charger for fast charging up to 63W with Power Delivery technology. Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools. Charging compatibility with market devices is guaranteed by USB-IF certification.

NEWS
Availability: ① July 2025 ② November 2025

ChoruSmart - Modular devices

PROTECTION - SATIN BLACK VERSION

Miniature circuit breakers



GW 12 463

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. modules	Pack Carton
GW 12 461	Single pole (1P)	6	3 kA	1	1/12
GW 12 462	Single pole (1P)	10	3 kA	1	1/12
GW 12 463	Single pole (1P)	16	3 kA	1	1/12
GW 12 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 12 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 12 468	Two-pole (1P+N)	16	3 kA	1	1/12



GW 12 488

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Rated current (A)	Breaking capacity	Idn	No. modules	Pack Carton
GW 12 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 12 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 12 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 12 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 12 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 12 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

Protection devices



GW 12 491

Fuse holder - 250V ac

Code	Rated current (A)	Fuse type	No. modules	Pack Carton
GW 12 491	16	Ø 6.3x32 mm	1	1/12

CHARACTERISTICS: fuse not included.



GW 12 492


Surge protection device - 230V ac

Code	Uc	Up	No. modules	Pack Carton
GW 12 492	275 V ac 50/60Hz	1 kV	1	1/12

CHARACTERISTICS: green LED for status signalling.
APPLICATIONS: protection of electronic devices (TV, HI-FI, computer, etc.) from overvoltage (resulting from atmospheric conditions or manoeuvres) that could be channelled from the power supply lines.

INDICATOR - SATIN BLACK VERSION

Indicator light devices



GW 12 642

Single indicator lamps - 1/2 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 12 641	Opal diffuser	Neutral	1/2	2/48
GW 12 642	Green	Safety	1/2	2/48
GW 12 643	Red	Danger	1/2	2/48
GW 12 644	Amber	Attention	1/2	2/48

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.




GW 12 622

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 12 621	Opal diffuser	Neutral	1	1/24
GW 12 622	Green	Safety	1	1/24
GW 12 623	Red	Danger	1	1/24
GW 12 624	Amber	Attention	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATION: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 12 629

Double indicator lamps - 1 module

Code	Diffuser colour	No. modules	Pack Carton
GW 12 628	Opal diffuser	1	1/24
GW 12 629	Red/green	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 12 633

Protruding indicator lamps - 2 modules

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 12 631	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 12 632	12V ac/dc - 230V ac 50/60 Hz	Green	White LED	2	1/24
GW 12 633	12V ac/dc - 230V ac 50/60 Hz	Red	White LED	2	1/24
GW 12 634	12V ac/dc - 230V ac 50/60 Hz	Amber	White LED	2	1/24

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.

ChoruSmart - Modular devices



GW 12 656

Stair riser lamp

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 12 651	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 12 656	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	4	1/2

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.

Anti black-out and emergency lamps



GW 12 661

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	Pack Carton
GW 12 661	230 V ac - 50/60 Hz	Ni - Mh	2 h	White LED	1/6

CHARACTERISTICS: equipped with a 3-position selector on the front panel, for anti black-out, inhibition and night functioning.
To be inserted in any socket-outlet of the Italian, German or French type. Highly efficient, white LED lamp.



GW 12 662

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 12 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/12

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.



GW 12 663

Autonomous emergency lamps

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 12 663	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	2	1/6
GW 12 666	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	4	1/2

CHARACTERISTICS: green mains presence signal LED. Highly efficient, white LED lamps.
APPLICATIONS: compliant with standards EN60598-2-22.

Acoustic signalling devices

Ringers



GW 12 601

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 12 601	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24
GW 12 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 12 606

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 12 606	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24
GW 12 607	230V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ChoruSmart - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - SATIN BLACK VERSION

Timer devices



GW 12 581

Electronic daily/weekly timer, 1-channel

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 12 581	230 V ac - 50/60 Hz	1NO/NC 8A(AC1)/4A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.

Temperature control devices



GW 12 709

Connected thermostat - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 12 709	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 12 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 12 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.



GW 16 970 CN

Thermo ICE wi-fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CN	Black	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet).

APPLICATIONS: The THERMO ICE Wi-Fi can be used:
- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Dimmer



GW 12 575

Universal rotating electronic regulator

Code	Supply voltage	No. modules	Pack Carton
GW 12 575	230V ac - 50 Hz	1	1/12

CHARACTERISTICS: suitable for dimming incandescent and halogen lamps 230 V ac (10-160 W); low-voltage halogen lamps (12 V ac) with electronic transformers (10-160 W) and LED lamps 230 V ac (4-160W), rotary control with 2-way switch. Equipped with amber-colour-red signalling LED. Can be operated without neutral connection.

NOTES: the installation of more than one dimmer side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two dimmers. If installing two dimmers in the same box, the maximum loads that can be controlled by each dimmer must be reduced by 50%.



GW 12 564

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 12 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 12 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW12567 rotary command with two-way switch.

GW12564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact GEWISS Customer Service to check the product meets the regulations of the country concerned before importing it.

NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 12 572 A

Universal electronic regulators with push-button

Code	Supply voltage	No. modules	Pack Carton
GW 12 572 A	230V ac - 50/60 Hz	1	1/12
GW 12 573 A	230V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.

NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 12 568

Electronic regulator with button for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 12 568	230V ac - 50 Hz	60 - 500 W	60 - 500 VA	1	1/12

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.

NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

TECHNICAL ALARMS - SATIN BLACK VERSION

GAS detectors



GW 12 711

LPG detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 12 711	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 12 712

Methane gas detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 12 712	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 720

Power supply unit 12Vdc

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

Anti-flood system with Zigbee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.



GW 12 750

Blanking module for housing RF Zigbee actuators

Code	Colour	No. modules	Pack Carton
GW 12 750	Satin black	1	1/12

CHARACTERISTICS: 1-module blanking module with pad printing. Allows the housing and fast identification of the flush-mounting RF Zigbee actuator.
NOTES: snap-in assembly.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps - 2W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Dimensions (mm)	Pack Carton
GW 20 902	12V ac/dc	2 W	Incandescence	White	S6x36	50
GW 20 903	24V ac/dc	2 W	Incandescence	White	S6x36	50

Accessories



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




ChoruSmart




Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

Glossy titanium modular devices





The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in glossy painted titanium, innovative and trendy, they include rocker button keys with ½, 1 and 2 modules to optimise space, and axial keys in EVO or SMART version for advanced functions. The front attachment system facilitates assembly and release without removing the support.

COMMAND - GLOSSY TITANIUM VERSION

Command devices - rockers - screw terminals



GW 14 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 14 001	1P - 16AX	Neutral	200 W	12/96
GW 14 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 14 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 1/2				
GW 14 021	1P - 10AX	Neutral	100 W	12/24
GW 14 022	1P - 10AX illuminable	With diffuser	100 W	6/24
No. modules: 2				
GW 14 031	1P - 16AX	Neutral	200 W	6/24
GW 14 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 14 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 14 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 14 004	2P - 16 AX	Neutral	0/1	200 W	12/48
GW 14 005	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	12/24
GW 14 006	2P - 10AX	With key	0/1	100 W	1/12
No. modules: 2					
GW 14 034	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 14 035	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW14006 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 14 007

One-way switch 2P - 250V ac - heavy duty loads

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 14 007	2P - 25 AX	Neutral	0/1	250 W	12/24

APPLICATIONS: suitable for particular heavy-duty loads (e.g. fluorescent lamp batteries) or high-consumption devices (e.g. ovens, air-conditioners, boilers, etc.).



GW 14 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 14 051	1P - 16AX	Neutral	200 W	12/96
GW 14 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 14 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
GW 14 054	1P - 10AX	With key	100 W	1/12
No. modules: 1/2				
GW 14 061	1P - 10AX	Neutral	100 W	6/24
No. modules: 2				
GW 14 071	1P - 16AX	Neutral	200 W	6/24
GW 14 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 14 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: GW14054 equipped with 2 keys. Key extractable in both positions. Spare keys: GW20901.



GW 14 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 14 091	1P - 16AX	Neutral	200 W	12/48
GW 14 092	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 14 093	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 14 101	1P - 16AX	Neutral	200 W	6/12
GW 14 102	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 14 103	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 14 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 14 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 14 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 14 122

Three-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 14 122	2P - 10AX	Neutral	UP - DOWN	100 W	12/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

ChoruSmart - Modular devices



GW 14 131

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 14 131	1P NO - 16A	Neutral	-	12/96
GW 14 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 14 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 14 136	1P NO - 16A	Pull-cord	-	1/12
GW 14 137	1P NC - 16A	Neutral	O red	12/24
GW 14 138	1P NC+NO - 16 A	Stop	Red	12/24
GW 14 139	1P NO+NC - 16 A	Start	Green	12/24
GW 14 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 14 141	1P NO+NO - 16 A	Double	-	12/24
GW 14 142	1P NO - 16A illuminable	Green diffuser	-	12/24
GW 14 143	1P NO - 16A illuminable	Red diffuser	-	12/24
GW 14 144	1P NO - 16A illuminable	Opal diffuser	-	12/24
GW 14 151	1P NO - 16A illuminable	With replaceable neutral lens	Light	12/24
GW 14 152	1P NO - 16A illuminable	With replaceable neutral lens	Key	12/24
GW 14 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 1/2				
GW 14 161	1P NO - 10A	Neutral	-	6/24
GW 14 162	1P NO - 10A illuminable	With diffuser	-	6/24
No. modules: 2				
GW 14 171	1P NO - 16A	Neutral	-	6/24
GW 14 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 14 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW14136 Cord in insulating material, 140cm long, with red knob.

GW14140 Button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

GW14141 independent push-buttons that can also be activated simultaneously.



GW 14 134

Push-buttons 2P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 14 134	2P NO - 16A	Neutral	O	12/24
GW 14 135	2P NO - 10A illuminable	With replaceable neutral lens	-	12/24
GW 14 145	2P NO - 10A	With key	-	1/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

NOTES: GW14145 equipped with 2 keys. Spare keys: GW30912.



GW 14 191

Push-buttons 1P with illuminated name plate - 250V ac

Code	Description	Lamp voltage	Lamp	Lamp power	Pack Carton
No. modules: 2					
GW 14 191	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm (not included)	2 W	6/24
No. modules: 3					
GW 14 192	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	4/16

CHARACTERISTICS: lamp not included.

Command devices - rockers - quick wiring terminals



GW 14 031 F

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 14 031 F	1P - 16AX	Neutral	200 W	6/24
GW 14 032 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 14 033 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 14 034 F

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 14 034 F	2P - 16 AX	Neutral	0/1	200 W	6/24
GW 14 035 F	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 14 071 F

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 14 071 F	1P - 16AX	Neutral	200 W	6/24
GW 14 072 F	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 14 073 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 14 101 F

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 2				
GW 14 101 F	1P - 16AX	Neutral	200 W	6/12
GW 14 102 F	1P - 16AX illuminable	With diffuser	200 W	6/12
GW 14 103 F	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.



GW 14 171 F

Push-buttons 1P - 250V ac

Code	Description	Button key	Pack Carton
No. modules: 2			
GW 14 171 F	1P NO - 16A	Neutral	6/24
GW 14 172 F	1P NO - 16A illuminable	With diffuser	6/24
GW 14 173 F	1P NO - 16A illuminable	With replaceable neutral lens	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.
NOTES: spring quick wiring, no tools necessary.

ChoruSmart - Modular devices



GW 14 160 F

Combined command devices - rockers - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 2					
GW 14 078 F	Twin two-way switch 1P - 16 AX	Neutral	-	200 W	6/24
GW 14 159 F	Two-way switch 1P - 16 AX / Push-button 1P NO - 16A	Neutral	-	200 W	6/24
GW 14 160 F	Twin push-button 1P NO - 16 A	Neutral	UP - DOWN - STOP	-	6/24

NOTES: spring quick wiring, no tools necessary.

Command devices - axial - screw terminals



GW 10 671

Axial switch module - EVO

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 671	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12
GW 10 672	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 On/Off lighting device through a live output contact. Suitable for the control of incandescent and halogen (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Local push button with axial activation for control of the lamps connected to the device.
Equipped with 1 input to replicate the local control of the load via auxiliary module GW10677-GW10678 or NO-type and 1 input buttons for the centralisation OFF function.
APPLICATIONS: Bistable, monostable and timed load command. Centralisation function (OFF) by means of a dedicated input, the possibility of being able to switch the load on by means of auxiliary axial modules or NO-type buttons. The devices are equipped with a configurable blue LED that can be set to OFF, easy location mode or for signalling the connected load status.
NOTES: the devices must be completed with a front button key: GW10671 must be completed with the GW14553S or GW14557S button keys. The GW10674 must be completed with the GW14554S or GW14558S button keys.



GW 10 673

Axial dimmer module - EVO

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 673	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12
GW 10 674	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	2	1/6

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two local axial operated buttons for dimming the connected load.
Equipped with 2 inputs for replicating local control of the load via the auxiliary module GW10679, GW10680 or NO-type buttons or for creating the centralisation function.
APPLICATIONS: control of the dimmable load connected to the devices. The dedicated inputs can be used to add a load switching-on function through auxiliary axial modules or NO-type buttons, or inputs can be set, via programming, for the centralised OFF function. The devices are equipped with configurable blue LEDs that can be set to OFF, location mode or for signalling the connected load.
NOTES: To avoid overheating, multiple dimmers cannot be installed side-by-side inside in the same enclosure. Insert a blanking module between two electronic devices. If two dimmers are installed in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. The devices must be completed with a front button key: GW10673 must be completed with the GW14553S or GW14557S button keys; GW10674 must be completed with the GW14554S or GW14558S button keys.



GW 10 675

Axial roller shutter module - EVO

Code	Supply voltage	Max current supplied	No. modules	Pack Carton
GW 10 675	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW 10 676	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., through 2 live interlocked output contacts. Two axial-operated local buttons control the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the auxiliary module GW10679, GW10680 or NO-type up/down buttons, or for creating the centralisation function.
APPLICATIONS: control of the motor connected to the devices. The dedicated inputs can be used to operate roller-shutters/venetian blinds via the auxiliary axial modules or NO-type up/down buttons, or they can be set, through programming, for centralisation functions (Up/Down). The devices are equipped with blue LEDs which can be configured to facilitate location at night and to signal the movement of the roller-shutter/Venetian blind.
NOTES: the devices must be completed with a front button key: GW10675 must be completed with the GW14553S or GW14557S button keys.GW10676 must be completed with the GW14554S or GW14558S button keys.



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO switch modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10677 must be completed with the GW14551S or GW14555S button keys. GW10678 must be completed with the GW14552S or GW14556S button keys.



GW 10 679

2-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary controls to be used in conjunction with the EVO dimmer and roller-shutter modules.
The devices are equipped with blue LEDs for easy location or for displaying the status of the load.
APPLICATIONS: when connected to the local inputs of the EVO axial controls, they allow replication of the local load control or the management of centralised controls.
NOTES: the devices must be completed with a front button key: GW10679 must be completed with the GW14553S or GW14557S button keys. GW10680 must be completed with the GW14554S or GW14558S button keys.




GW 14 551 S

Interchangeable keys and diffusers for axial devices

Code	Colour	Button key	No. modules	Pack Carton
GW 14 551 S	Glossy Titanium	To be completed with lens	1	1/48
GW 14 552 S	Glossy Titanium	To be completed with lens	2	1/48
GW 14 553 S	Glossy Titanium	To be completed with 2 lenses	1	1/48
GW 14 554 S	Glossy Titanium	To be completed with 2 lenses	2	1/48
GW 14 555 S	Glossy Titanium	With 1 diffuser	1	1/48
GW 14 556 S	Glossy Titanium	With 1 diffuser	2	1/48
GW 14 557 S	Glossy Titanium	With 2 diffusers	1	1/48
GW 14 558 S	Glossy Titanium	With 2 diffusers	2	1/48

NOTES: for use to complete the EVO axial modules and auxiliary axial controls.

Lens with illuminated symbol



Symbols for illuminable rocker command devices

Code	Symbol	Pack Carton
Suitable for: General services		
GW 10 501	Neutral	20/240
GW 10 502	Light	20/240
GW 10 503	Stair light	20/240
GW 10 504	Table light	20/240
GW 10 505	Bell	20/240
GW 10 506	Fan	20/240
GW 10 507	Key	20/240
GW 10 508	Alarm	20/240
GW 10 509	ON	20/240
GW 10 510	OFF	20/240
GW 10 511	Nurse	20/240
GW 10 512	Waitress	20/240
GW 10 513	Dimmer increase	20/240
GW 10 514	Dimmer decrease	20/240
GW 10 515	UP arrow	20/240
GW 10 516	DOWN arrow	20/240
GW 10 517	UP - DOWN arrow	20/240
GW 10 518	RIGHT - LEFT arrow	20/240
Suitable for: Numerical services		
GW 10 531	One	20/240
GW 10 532	Two	20/240
GW 10 533	Three	20/240
GW 10 534	Four	20/240
GW 10 535	Five	20/240
GW 10 536	Six	20/240
GW 10 537	Seven	20/240
GW 10 538	Eight	20/240
GW 10 539	Nine	20/240
GW 10 540	Zero	20/240

NOTES: for use in place of the neutral lens in the illuminated tilting control devices.

ChoruSmart - Modular devices



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

Interchangeable button keys and diffusers for rocker devices



Button keys for rocker controls and interchangeable diffusers for indicator lights

Code	Symbol	Pack Carton
Description: Keys 22x22 mm		
GW 14 541	General	4/48
GW 14 543	Key	4/48
GW 14 544	Bell	4/48
GW 14 545	Vertical arrow	4/48
GW 14 546	Horizontal arrow	4/48
Description: Diffusers		
GW 10 547	Red	4/48
GW 10 548	Green	4/48
GW 10 549	Opal diffuser	4/48

APPLICATIONS: diffusers to be used in place of those on the indicator lamps GW14142,GW14143,GW14144.

NOTES: the Chorusmart modular system allows the use of 22 x 22mm interchangeable button keys in place of the standard button keys fitted on the command devices GW14141, GW14142, GW14143, GW14144.

Soft-click, rocker electronic push buttons



GW 14 915

Universal soft-click electronic push-button

Code	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 14 915	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contact interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 14 912

Backlit soft-click electronic push-button

Code	Supply voltage	Type of contact	Button key	Type of use	Pack Carton
GW 14 912	230 V ac - 50/60 Hz	1NO 4A (AC1) 230 V ac	With diffuser	Relay, dimmer	1/12

CHARACTERISTICS: push-button for controlling latching relays, electronic switches for heavy duty loads, or dimmers with a remote control input.
Equipped with amber backlit LED.



GW 14 913

Backlit soft-click electronic push-buttons for BUS inputs

Code	Type of contact	Button key	Type of use	Pack Carton
No. modules: 1				
GW 14 913	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/12
GW 14 916	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/12
No. modules: 2				
GW 14 917	1NO - Potential-free	With diffuser	Bus contacts interfaces	1/6
GW 14 918	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 14 914

Double soft-click electronic push-button

Code	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 14 914	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connecting KNX BUS contact interfaces or electronic control panels for moving roller shutters.

ChoruSmart - Modular devices

Touch command modules



GW 10 922

Touch one-way switch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 922	100 ÷ 240 V ac - 50/60 Hz	1 NO 5A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: device for the On/Off control of 1 lighting device through a live output contact. Suitable for control of incandescent and halogen lamps (240Vac): 1000W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA. Equipped with 1 input for replicating local control of the load via the GW10924 auxiliary touch control modules, NO-type buttons and 1 input for the centralisation of the OFF function. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: bistable, monostable and timed load control. Centralisation function (OFF) through the dedicated input.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 923

Touch dimmer module

Code	Supply voltage	Halogen load	Inductive load	LED load	No. modules	Pack Carton
GW 10 923	100 ÷ 240 V ac - 50/60 Hz	4 ÷ 150 W	4 - 150 VA	4 ÷ 150 W	1	1/12

CHARACTERISTICS: trailing edge load drive mode (max. 5 lamps). Two touch areas for dimming the connected load. Equipped with 2 inputs for replicating local control of the load via the auxiliary touch 2-command modules GW10925, NO-type buttons, or for creating the centralisation function OFF. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the dimmable load connected to the devices. Centralised OFF function, via dedicated inputs.
NOTES: to avoid overheating, multiple products cannot be installed side-by-side inside in the same enclosure; insert a blanking module between two electronic devices. When installing two dimmers in the same box, the maximum loads controlled by each dimmer must be reduced by 50%. To be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 921

Touch roller shutter module

Code	Supply voltage	Maximum output power	No. modules	Pack Carton
GW 10 921	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12

CHARACTERISTICS: Devices for the control of a motor to operate roller-shutters, curtains, venetian blinds, awnings, etc., by means of 2 interlocked live output contacts. Two touch areas for controlling the motor connected to the device. Equipped with 2 inputs for replicating local control of the motor via the touch auxiliary 2-command modules GW10925, NO-type up/down buttons, or for creating a centralisation function (up/down). The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
APPLICATIONS: control of the motor connected to the devices. Centralisation function (Up/Down) by means of a dedicated inputs.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 924

1-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 924	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10922 module. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable built-in buzzer, function identification by means of icons on the ICE touch plates.
NOTES: to be completed using ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).



GW 10 925

2-command auxiliary touch module

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 925	100 ÷ 240 V ac - 50/60 Hz	-	1	1/12

CHARACTERISTICS: suitable for controlling the GW10921 and GW10923 modules. The device is equipped with blue LEDs for easy location that can be set to two different light intensity levels. Excludable, built-in buzzer and functions identifiable by the icons on the ICE touch plates.
NOTES: to be completed with ICE touch plates (codes: GW16955CB, GW16955CL, GW16955CN, GW16955CT).

ICE TOUCH plates



GW 16 955 CT

ICE TOUCH - titanium

Code	Description	For support codes	Pack Carton
GW 16 955 CT	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: glossy finish. The plate is to be used in combination with the touch modules (switch module GW10922, roller shutter module GW10921, dimmer module GW10923, 1-control auxiliary module GW10924, 2-control auxiliary module GW10925).
NOTES: the symbols displayed in the image are purely indicative: they may be customised using the icons supplied with the touch plate. The code of the plate is unique and independent of the number of icons used (from 2 to 6).

Blanking modules and cable outlet



GW 14 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 14 195	1 module	1	10/200
GW 14 197	1/2 module	1/2	4/48
GW 14 198	2 modules	2	1/48
GW 14 199	3 modules	3	1/48



GW 14 194

Cable outlet

Code	Description	No. modules	Pack Carton
GW 14 194	2 modules	2	6/48
GW 14 196	1 module	1	1/48

NOTES: GW14196 with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.
GW14194 with anti-traction cable fastener device, cables min 4mm ø, max 10mm ø. To be installed with the cable output downwards.

ChoruSmart - Modular devices

Movement detectors



GW 14 594

Movement detector

Code	Supply voltage	Output contacts	Pack Carton
GW 14 594	230V ac - 50/60 Hz	1NO 3 A (AC1) 230 V ac	1/4

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited.
Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA, LED loads: 60 W (max. 10 lamps).
Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.
Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly. Detection beam angle 120°, depth of detection max 8 metres.



GW 10 595

Ceiling-mounted presence detector

Code	Supply voltage	Installation height (m)	Light sensor	Dimensions HxØ (mm)	Pack Carton
GW 10 595	220/240 V ac - 50/60 Hz	From 2,2 to 6	< 3 ÷ 2000 Lux	44x111,5	1

CHARACTERISTICS: presence sensor, sensing range: 360° circle (max. diameter 18 metres); installable with fixing springs on a surface-mounted or recessed box. Suitable for the control of incandescent/halogen lamps: 1000W, LED lamps : 200W (4 / 23 W - max. 8 lamps).
NOTES: equipped with a surface-mount box capable of holding sensors from IP20 to IP44.

Relay



GW 14 721

Relay - 230V ac 50/60Hz

Code	Type	No. of poles	Output contacts	Coil	Pack Carton
No. modules: 1					
GW 14 721	Latching relay	1P	10 AX 250V ac	230V ac - 50/60 Hz	1/12
GW 14 724	Monostable relay	1P	1NO/NC 10A(AC1)/2A(AC15)250V ac	230V ac - 50/60 Hz	1/12

CHARACTERISTICS: GW14721 suitable for commanding incandescent/halogen lamps: 1000 W: fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: GW14721 command of lighting devices from more than one point, by means of remote NO push-buttons.
GW14721, motor function/stop commands (extractors, air agitators, etc.).
GW14724 as an auxiliary element for commanding special loads, for distance signalling, for electrical separation between the command and use circuits.



GW 14 726

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 14 726	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: inlets for remote NO push-buttons for alarms (e.g. GW14136) and alarm reset (e.g. GW14145). green LED for alarm status signalling.

HOTEL COMPONENTS - GLOSSY TITANIUM VERSION

Badge switch



GW 14 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 14 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted)
NOTES: badges not included. The article uses LED signalling units, not included.

Interchangeable button keys



GW 14 733

Interchangeable button keys

Code	Button key	Symbol	No. modules	Pack Carton
GW 14 731	With diffuser	DND	1	4/48
GW 14 732	With diffuser	MUR	1	4/48
GW 14 733	Neutral	DND+MUR	1	4/48

CHARACTERISTICS: with "Do not disturb" (DND) and "Make up the room" (MUR) pad printings. To be used for the customization of the Chorus command devices. GW14731 and GW14732 suitable for one-way switches, two-way switches, intermediate switches and push-buttons. GW14733 suitable for three-way switches and push-buttons with central OFF position.

Indicator light device



GW 14 736

Double indicator lamp

Code	Diffuser colour	Symbol	No. modules	Pack Carton
GW 14 736	Opal diffuser	DND+MUR	1	1/24

CHARACTERISTICS: LED signalling units not included.

POWER - GLOSSY TITANIUM VERSION

Socket-outlets - Italian/German standard



GW 14 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 14 201	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 14 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.



GW 14 204

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 14 204	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48
GW 14 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 14 208

Italian standard double socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 14 208	2x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	2	6/24

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.



GW 14 209

Italian standard triple socket-outlet - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 14 209	3x2P+E - 16A Dual amperage	P11-P17	Ø 4 / 5 mm	3	4/12

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213

Italian standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 233	2P+E - 16 A Dual amperage	Orange	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with safety shields.



GW 10 214

Italian/German Standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 234	2P+E - 16 A Dual amperage illuminable	Orange	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary network.

Socket-outlets - German Standard



GW 14 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 14 242

German standard socket-outlet with lid IP40 - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

ChoruSmart - Modular devices



GW 10 251

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields.



GW 14 341

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 341	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 351

German Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 14 241 F

German Standard socket-outlet with quick wiring terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 241 F	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 251 F

German standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 F	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.

Socket-outlets - French Standard



GW 14 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 14 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 14 248

French Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 248	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.



GW 10 258

French Standard socket-outlet with front tightening terminals for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 258	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Front access terminals with screw fixing, side input of the conductors.
To be used in combination with plugs equipped with accessory GW10260.



GW 14 247 F

French standard socket-outlet with quick wiring terminals - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 247 F	2P+E - 16A	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.



GW 10 257 F

French standard socket-outlet for dedicated lines with quick wiring terminals - 250 V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 257 F	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	6/12

CHARACTERISTICS: with safety shields. Spring quick wiring, no tools necessary.
To be used in combination with plugs equipped with accessory GW10260.

ChoruSmart - Modular devices



GW 10 260

French standard socket-outlet accessory, for dedicated lines

Code	Colour	For sockets	Pack Carton
GW 10 260	Red	GW10257F - GW10258	10/100

CHARACTERISTICS: to be fixed directly on the 2P+E French standard plug, to avoid the incorrect insertion in dedicated line circuits.

Socket-outlets - Israeli Standard



GW 14 281

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 281	2P+E - 16A	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields.



GW 10 291

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: with safety shields. Pre-arranged for housing LED signalling units, not included.



GW 14 282

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 282	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 14 286

USA standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 286	2P+E - 15A	Flat parallel horizontal	1	12/48



GW 14 288

Euro-American Standard socket-outlets - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 14 288	2P+E - 15A	Ø 4 mm Flat	1	12/48



GW 14 296

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 296	2P+E - 13 A	Flat	2	6/48
GW 14 297	2P+E - 15A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 14 298

Indian/South African Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 298	2P+E - 16A	Ø 7 mm	2	6/48

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

ChoruSmart - Modular devices



GW 14 299

South african standard socket-outlet - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 299	2P+E - 16A	Round Ø 4,5 mm	1	12/240

CHARACTERISTICS: with safety shields.



GW 14 301

Argentinean standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 301	2P+E - 10A	Flat	2	6/48



GW 14 306

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 306	2P+E - 10A	Flat	2	6/48
GW 14 307	2P+E - 15A	Flat	2	6/48



GW 14 310

Multistandard socket-outlet - 250/127 V ac

Code	Description	No. modules	Pack Carton
GW 14 310	2P+E - 13A/250 V ac - 15A/127 V ac	2	10/40

CHARACTERISTICS: with safety shields.

APPLICATIONS: suitable for plugs compliant with the following standards: Europlug 2P 2.5A - 250V, British 2P+E 13A - 250V, Italian 2P 10A - 250V, Danish 2P 10A - 250V, Chinese 2P+E 10A - 250V, Argentinean/ Australian 2P+E 10A - 250V, Indian 2P+E 6A - 250V, USA 2P+E 15A - 127V. Not suitable for 2P+E German and French sockets because they don't offer earth continuity.

NOTES: the multistandard energy sockets GW1x310 are in compliance with the safety requirements defined by the International Standard IEC 60884-1. These sockets may not be in compliance with the standard sheets used in the country where they are sold, hence their usage could be prohibited or however, restricted only for specific applications. The plugs allowed are listed in the technical datasheet. Please contact directly Gewiss technical service for further information.



GW 14 392

Chinese standard socket-outlets - 250 V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 391	2P+E - 10A	Flat	2	6/48
GW 14 392	2P+E - 16A	Flat	2	6/48

CHARACTERISTICS: with safety shields.

Interlocked switched socket-outlets




GW 14 311

Interlocked switched socket-outlets with miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	No. modules	Pack Carton
GW 14 311	2P+E - 16A	P17-P11	1P+N 16A	3 kA	2	1/6
GW 14 312	2P+E - 16A	P40	1P+N 16A	3 kA	3	1/4

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.



GW 14 321

Interlocked switched socket-outlets with residual miniature circuit breaker - 230V ac

Code	Description	Socket-out type	Miniature circuit breakers	Breaking capacity	Idn	No. modules	Pack Carton
GW 14 321	2P+E - 16A	P17-P11	1P+N 16A	3 kA	10 mA	3	1/4
GW 14 322	2P+E - 16A	P40	1P+N 16A	3 kA	10 mA	4	1/2

CHARACTERISTICS: Interlocked switched socket-outlets with automatic miniature circuit breaker (C characteristic) and residual current circuit breaker (type A). Pits under tension only with plug inserted.
APPLICATIONS: suitable for installation in the system terminations to protect the load.

Shaver socket-outlet



GW 14 331

Euro-American Standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 14 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - GLOSSY TITANIUM VERSION

TV-SAT sockets



GW 14 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 14 361	Direct	0 dB	1	1/48
GW 14 362	Through wiring	5 dB	1	1/24
GW 14 363	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW14361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5dB GW14362 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load. (TV, VCR, SAT receiver or 75-Ohm termination)

ChoruSmart - Modular devices



GW 14 371

Coaxial TV-SAT sockets (5-2400 MHz) class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 14 371	Direct	0 dB	1	1/48
GW 14 372	Through wiring	5 dB	1	1/24
GW 14 373	Through wiring	10 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	50/200

CHARACTERISTICS: GW14371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500mA).
GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5dB GW14372 coaxial socket-outlet is defined with conditional use: it is a special feedthrough socket-outlet, and must be used as such, with the only difference that the user port (socket-outlet towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 14 382

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 14 381	TV-FM	Direct	0 dB	2	1/24
GW 14 382	TV-FM-SAT	Direct	0 dB	2	1/24
GW 14 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW14381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW14382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW14383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.



GW 14 367

Coaxial TV sockets (5-2400 Mhz), class A shielding - male IEC connector Ø 9.5mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 14 367	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 14 377

Coaxial TV-SAT sockets (5-2400 Mhz), class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 14 377	Direct	0 dB	2	1/24

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 14 386

Covers for TV-SAT-R antenna sockets

Code	Description	No. holes	Pack Carton
GW 14 386	For TV-R base	2	1/24
GW 14 387	For TV/R-SAT base	2	1/24

APPLICATIONS: suitable for integration on the Chorus range of TV-SAT-R standard bases available on the market.
ACCESSORIES SUPPLIED: fixing screws.

Telephone sockets



GW 14 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 14 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.



GW 14 409

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 14 409	RJ11	Screw-on terminals	2	1/24

APPLICATIONS: telephone, telefax, modem.



GW 14 406

British standard telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 14 406	6 contacts	Screw-on terminals	1	1/24

Data sockets



GW 14 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 14 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 14 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 14 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 14 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.



GW 14 431

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 14 431	AMP / Keystone Jack	1	1/48
GW 14 438	SYSTIMAX COMMSCOPE	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.



GW 14 433

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 14 433	AMP / Keystone Jack	2	4/100

NOTES: due to technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the data socket and the Gewiss empty enclosure.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

Socket-outlets for auxiliary circuits



GW 14 451

SELV sockets

Code	Description	For plug pins	No. modules	Pack Carton
GW 14 451	2P - 6A - 24V	Ø 3 mm	1	12/24
GW 14 452	2P - 6A - 24V polarised	Flat	1	12/24

CHARACTERISTICS: Centre distance 12,4mm.

Audio and video sockets



GW 14 453

Audio and video sockets

Code	Description	No. modules	Pack Carton
GW 14 453	Double RCA	1	1/24
GW 14 454	For loudspeaker	1	1/24
GW 14 458	Speaker socket	1	1/24

CHARACTERISTICS: GW14453 double RCA stud connector, red and white, weld-in connection.
GW14454, welding connection. GW14458 front access terminals for inserting 1.5mm² rigid wires, insulator punching rear connection suitable for cables AWG24 or max 0.25mm².

USB and HDMI couplers and sockets



GW 14 459

USB sockets

Code	Description	No. modules	Pack Carton
GW 14 459	USB socket-outlet	1	1/24

CHARACTERISTICS: A-type USB 2.0 female connector, with screw terminals on the back.



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB chargers



GW 14 415

USB power supply for electronic devices

Code		Supply voltage	Output voltage	Max. total power output	PD	USB-IF	Outputs/N° and type	No. modules	Pack Carton
GW 14 449		100 ÷ 240 V ac - 50/60 Hz	5V dc	15 W	-	-	2 / A+C	1	1/10
GW 14 415	①	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	30 W	Yes	Yes	1 / C	1	1/12
GW 14 417	②	100 ÷ 240 V ac - 50/60 Hz	5-9-15-20 V dc	63 W	Yes	Yes	2 / C	2	1/6

CHARACTERISTICS: GW14449 USB charger suitable for charging a single electronic device (e.g., tablet) or two devices simultaneously (e.g., tablet and smartphone). The distribution of power output across the two ports depends on the charging status of the connected devices.
GW14415 USB charger for fast charging up to 30W with Power Delivery technology. Suitable for charging electronic devices such as notebooks, tablets, smartphones, and smartwatches. Charging compatibility with market devices is guaranteed by USB-IF certification.
GW14417 USB charger for fast charging up to 63W with Power Delivery technology. Suitable for charging one or two electronic devices simultaneously, such as PCs, tablets, smartphones, smartwatches, and small power tools. Charging compatibility with market devices is guaranteed by USB-IF certification.

NEWS
Availability: ① July 2025 ② November 2025

ChoruSmart - Modular devices

PROTECTION - GLOSSY TITANIUM VERSION

Miniature circuit breakers



GW 14 463

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. modules	Pack Carton
GW 14 461	Single pole (1P)	6	3 kA	1	1/12
GW 14 462	Single pole (1P)	10	3 kA	1	1/12
GW 14 463	Single pole (1P)	16	3 kA	1	1/12
GW 14 466	Two-pole (1P+N)	6	3 kA	1	1/12
GW 14 467	Two-pole (1P+N)	10	3 kA	1	1/12
GW 14 468	Two-pole (1P+N)	16	3 kA	1	1/12



GW 14 488

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Rated current (A)	Breaking capacity	Idn	No. modules	Pack Carton
GW 14 482	Two-pole (1P+N)	6	3 kA	10 mA	2	1/6
GW 14 483	Two-pole (1P+N)	6	3 kA	30 mA	2	1/6
GW 14 485	Two-pole (1P+N)	10	3 kA	10 mA	2	1/6
GW 14 486	Two-pole (1P+N)	10	3 kA	30 mA	2	1/6
GW 14 488	Two-pole (1P+N)	16	3 kA	10 mA	2	1/6
GW 14 489	Two-pole (1P+N)	16	3 kA	30 mA	2	1/6

Protection devices



GW 14 491

Fuse holder - 250V ac

Code	Rated current (A)	Fuse type	No. modules	Pack Carton
GW 14 491	16	Ø 6.3x32 mm	1	1/12

CHARACTERISTICS: fuse not included.



GW 14 492

Surge protection device - 230V ac

Code	Uc	Up	No. modules	Pack Carton
GW 14 492	275 V ac 50/60Hz	1 kV	1	1/12

CHARACTERISTICS: green LED for status signalling.
APPLICATIONS: protection for electronic devices (TV, HI-FI, computer, etc.) from overvoltage of atmospheric origin, or manoeuvres, that could be channelled by the power supply lines.

INDICATOR - GLOSSY TITANIUM VERSION

Indicator light devices



GW 14 642

Single indicator lamps - 1/2 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 14 641	Opal diffuser	Neutral	1/2	2/48
GW 14 642	Green	Safety	1/2	2/48
GW 14 643	Red	Danger	1/2	2/48
GW 14 644	Amber	Attention	1/2	2/48

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 14 622

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 14 621	Opal diffuser	Neutral	1	1/24
GW 14 622	Green	Safety	1	1/24
GW 14 623	Red	Danger	1	1/24
GW 14 624	Amber	Attention	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 14 629

Double indicator lamps - 1 module

Code	Diffuser colour	No. modules	Pack Carton
GW 14 628	Opal diffuser	1	1/24
GW 14 629	Red/green	1	1/24

CHARACTERISTICS: LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.



GW 14 633

Protruding indicator lamps - 2 modules

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 14 631	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 14 632	12V ac/dc - 230V ac 50/60 Hz	Green	White LED	2	1/24
GW 14 633	12V ac/dc - 230V ac 50/60 Hz	Red	White LED	2	1/24
GW 14 634	12V ac/dc - 230V ac 50/60 Hz	Amber	White LED	2	1/24

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.

Stair riser lamp



GW 14 656

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 14 651	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	2	1/24
GW 14 656	12V ac/dc - 230V ac 50/60 Hz	Opal diffuser	White LED	4	1/2

CHARACTERISTICS: highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.

Anti black-out and emergency lamps

Extractable anti black-out lamp



GW 14 661

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	Pack Carton
GW 14 661	230 V ac - 50/60 Hz	Ni - Mh	2 h	White LED	1/6

CHARACTERISTICS: equipped with a 3-position selector on the front panel, for anti black-out, inhibition and night functioning.
To be inserted in any socket-outlet of the Italian, German or French type. Highly efficient, white LED lamp.

Anti black-out lamp



GW 14 662

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 14 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/12

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.

Autonomous emergency lamps



GW 14 663

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 14 663	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	2	1/6
GW 14 666	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	4	1/2

CHARACTERISTICS: green mains presence signal LED. Highly efficient, white LED lamps.
APPLICATIONS: compliant with standard EN60598-2-22.

Acoustic signalling devices

Ringers



GW 14 601

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 14 601	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24
GW 14 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 14 606

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 14 606	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24
GW 14 607	230V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ChoruSmart - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - GLOSSY TITANIUM VERSION

Timer devices



GW 14 581

Electronic daily/weekly timer, 1-channel

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 14 581	230 V ac - 50/60 Hz	1NO/NC 8A(AC1)/4A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.

Temperature control devices



GW 14 709

Connected thermostat - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 14 709	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 14 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 14 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.



GW 16 970 CT

Thermo ICE wi-fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CT	Titanium	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet).

APPLICATIONS: The THERMO ICE Wi-Fi can be used:
- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Dimmer



GW 14 575

Universal rotating electronic regulator

Code	Supply voltage	No. modules	Pack Carton
GW 14 575	230V ac - 50 Hz	1	1/12

CHARACTERISTICS: suitable for dimming incandescent and halogen lamps 230 V ac (10-160 W); low-voltage halogen lamps (12 V ac) with electronic transformers (10-160 W) and LED lamps 230 V ac (4-160W), rotary control with 2-way switch. Equipped with amber-colour-red signalling LED. Can be operated without neutral connection.
NOTES: the installation of more than one dimmer side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two dimmers. If installing two dimmers in the same box, the maximum loads that can be controlled by each dimmer must be reduced by 50%.



GW 14 564

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 14 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 14 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW14567 rotary command with two-way switch.
GW14564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 14 572 A

Universal electronic regulators with push-button

Code	Supply voltage	No. modules	Pack Carton
GW 14 572 A	230V ac - 50/60 Hz	1	1/12
GW 14 573 A	230V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 14 568

Electronic regulator with button for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 14 568	230V ac - 50 Hz	60 - 500 W	60 - 500 VA	1	1/12

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

TECHNICAL ALARMS - GLOSSY TITANIUM VERSION

Gas detectors



GW 14 711

LPG detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 14 711	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 14 712

Methane gas detector

Code	Supply voltage	Tripping threshold	Output contacts	No. modules	Pack Carton
GW 14 712	12V ac/dc	9% LIE	1NO/NC 10A(NO)/3A(NC)250V ac	2	1/2

CHARACTERISTICS: relay output for the automatic command of the gas interception solenoid valve (manual reset) GW30522. Sound intensity: 85dB at 1m.



GW 10 720

Power supply unit 12Vdc

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

Anti-flood system with Zigbee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.



GW 14 750

Blanking module for housing RF Zigbee actuators

Code	Colour	No. modules	Pack Carton
GW 14 750	Glossy Titanium	1	1/12

CHARACTERISTICS: 1-module blanking module with pad printing. Allows the housing and fast identification of the flush-mounting RF Zigbee actuator.
NOTES: snap-in assembly.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps - 2W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Dimensions (mm)	Pack Carton
GW 20 902	12V ac/dc	2 W	Incandescence	White	S6x36	50
GW 20 903	24V ac/dc	2 W	Incandescence	White	S6x36	50

Accessories



GW 20 901

Set of keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




ChoruSmart




Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

Glossy ivory modular devices

The ChoruSmart modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Available in glossy ivory, bright and versatile, they include rocker button keys with 1 and 2 modules to optimise space. The front attachment system facilitates assembly and release without removing the support.





COMMAND - IVORY VERSION

Command devices - screw terminals



GW 11 001

One-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 11 001	1P - 16AX	Neutral	200 W	12/96
GW 11 002	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 11 003	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 11 031	1P - 16AX	Neutral	200 W	6/24
GW 11 032	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 11 033	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 11 004

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 11 004	2P - 16 AX	Neutral	0/1	200 W	12/48



GW 11 051

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 11 051	1P - 16AX	Neutral	200 W	12/96
GW 11 052	1P - 16AX illuminable	With diffuser	200 W	12/24
GW 11 053	1P - 16AX illuminable	With replaceable neutral lens	200 W	12/24
No. modules: 2				
GW 11 071	1P - 16AX	Neutral	200 W	6/24
GW 11 072	1P - 16AX illuminable	With diffuser	200 W	6/24
GW 11 073	1P - 16AX illuminable	With replaceable neutral lens	200 W	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 11 091

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
No. modules: 1				
GW 11 091	1P - 16AX	Neutral	200 W	12/48
GW 11 092	1P - 16AX illuminable	With diffuser	200 W	12/24
No. modules: 2				
GW 11 101	1P - 16AX	Neutral	200 W	6/12
GW 11 102	1P - 16AX illuminable	With diffuser	200 W	6/12

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.



GW 11 121

Three-way switches 1P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
No. modules: 1					
GW 11 121	1P - 10AX	Neutral	UP - DOWN	100 W	12/24
No. modules: 2					
GW 11 123	1P - 10AX	Neutral	UP - DOWN	100 W	6/24

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).

APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 11 131

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	Pack Carton
No. modules: 1				
GW 11 131	1P NO - 16A	Neutral	-	12/96
GW 11 132	1P NO - 16A illuminable	With diffuser	-	12/24
GW 11 133	1P NO - 16A illuminable	With replaceable neutral lens	-	12/24
GW 11 136	1P NO - 16A	Pull-cord	-	1/12
GW 11 140	1P NO+NO - 10A	With interlock	UP - DOWN	12/24
GW 11 153	1P NO - 16A illuminable	With replaceable neutral lens	Bell	12/24
No. modules: 2				
GW 11 171	1P NO - 16A	Neutral	-	6/24
GW 11 172	1P NO - 16A illuminable	With diffuser	-	6/24
GW 11 173	1P NO - 16A illuminable	With replaceable neutral lens	-	6/24

CHARACTERISTICS: the illuminable articles use LED signalling units, not included.

GW11136 Cord in insulating material, 140cm long, with red knob.

GW11140 button with mechanical interlock.

Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

Badge switch



GW 11 039

Badge switch

Code	Description	For badge card max. width	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 11 039	1P NO - 16 AX illuminable	54 mm	200 W	2	1/6

CHARACTERISTICS: the product can be fitted directly in 2-module plates; with plates of a greater modularity, you are advised to use 2 blanking modules for a 1/2 module (one on the right and one on the left).

APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted).

NOTES: badges not included. The article uses LED signalling units, not included.

Blanking modules and cable outlet



GW 11 195

Blanking modules

Code	Description	No. modules	Pack Carton
GW 11 195	1 module	1	10/200
GW 11 197	1/2 module	1/2	4/48
GW 11 198	2 modules	2	1/48

ChoruSmart - Modular devices



GW 11 196

Cable outlet

Code	Description	No. modules	Pack Carton
GW 11 196	1 module	1	1/48

NOTES: with anti-traction cable fastener device, cables min 6mm ø, max 10mm ø.

POWER - IVORY VERSION

Socket-outlets - Italian/German standard



GW 11 203

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 11 203	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with safety shields.

Socket-outlets - German Standard



GW 11 241

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 11 241	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.



GW 11 242

German Standard socket-outlet with lid IP40 - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 11 242	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields. Equipped with a transparent rigid cover with a glossy finish. IP40 degree of protection with the cover closed.

Socket-outlets - French Standard



GW 11 246

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 11 246	2P - 16A	Ø 4 / 4.8 mm	2	1/24
GW 11 247	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 11 288

Euro-American Standard socket-outlets - 250/125V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 11 287	2P - 15A	Ø 4 mm Flat	1	12/48
GW 11 288	2P+E - 15A	Ø 4 mm Flat	1	12/48

Shaver socket-outlet



GW 11 331

Euro-American Standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 11 331	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - IVORY VERSION

TV-SAT sockets



GW 11 361

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 11 361	Direct	0 dB	1	1/48

CHARACTERISTICS: GW11361 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 11 371

Coaxial TV-SAT sockets (5-2400 MHz) class A shielding - female F connector

Code	Description	Attenuation	No. modules	Pack Carton
GW 11 371	Direct	0 dB	1	1/48

CHARACTERISTICS: GW11371 allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 11 383

TV-FM-SAT sockets

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 11 381	TV-FM	Direct	0 dB	2	1/24
GW 11 383	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: TV-FM direct co-axial socket-outlet GW11381: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm.
TV-FM-SAT direct co-axial socket-outlet GW11382: male IEC-type TV connector ø 9.5mm, female IEC-type FM connector ø 9.5mm, female F-type SAT connector.
TV-SAT direct co-axial socket-outlet GW11383: male IEC-type TV connector ø 9.5mm, female F-type SAT connector.
NOTES: demixed socket-outlets with input for co-axial cable Ø 5mm or 7mm.

Telephone sockets



GW 11 401

RJ11 telephone sockets

Code	Description	Connection	No. modules	Pack Carton
GW 11 401	RJ11	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.

Data sockets



GW 11 421

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 11 421	RJ45	4	5e	UTP	Toolless	1	1/24
GW 11 422	RJ45	4	5e	FTP	Toolless	1	1/24
GW 11 423	RJ45	4	6	UTP	Toolless	1	1/24
GW 11 424	RJ45	4	6	FTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e; LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
NOTES: circuit identification label included.



GW 11 431

Adapter for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 11 431	AMP / Keystone Jack	1	1/48

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (Chorus, System and Dahlia) with Keystone Jack coupling.

USB and HDMI couplers



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System and Playbus) with Keystone Jack type coupling and permutation panels.

INDICATOR - IVORY VERSION

Indicator light devices



GW 11 623

Single indicator lamps - 1 module

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 11 623	Red	Danger	1	1/24

CHARACTERISTICS: LED signalling units, not included.

APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.

Anti black-out and emergency lamps



GW 11 662

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. modules	Pack Carton
GW 11 662	230 V ac - 50/60 Hz	Ni - Mh	1 h	LED	1	1/12

CHARACTERISTICS: green LED to indicate mains presence. Highly efficient, white LED lamp.

Acoustic signalling devices



GW 11 602

Ringers

Code	Supply voltage	Max power consumption	Sound intensity	No. modules	Pack Carton
GW 11 602	230V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	1/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ENERGY MANAGEMENT, CLIMATE AND COMFORT - IVORY VERSION

Temperature control devices



GW 11 705

Thermostat

Code	Supply voltage	Temperature adjustment	Output contacts	No. modules	Pack Carton
GW 11 705	230 V ac - 50/60 Hz	From +5°C to +35°C	1NO / NC 8A(AC1) 250V ac	2	1/2

CHARACTERISTICS: choice of working mode by means of selector located on the front: summer (air-conditioner), OFF, winter (boiler).
Two-colour front LED to signal the output status (open/closed contact). The lighting up of the LED also indicates mains presence.

Dimmer



GW 11 564

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. modules	Pack Carton
GW 11 564	230 V ac - 50/60 Hz	100 - 900 W	40 - 300 VA	1	1/12
GW 11 567	230 V ac - 50/60 Hz	100 - 500 W	100 - 500 VA	1	1/12

CHARACTERISTICS: with signalling led orange. GW11567 rotary command with two-way switch.
GW11564 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side by side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 11 573 A

Universal electronic regulator with push-button

Code	Supply voltage	No. modules	Pack Carton
GW 11 573 A	230 V ac - 50/60 Hz	2	1/6

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (40-300W), low voltage halogen lamps with electronic and winding transformers (40-300W), LED lamps 230V AC with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

ACCESSORIES

Signalling unit



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).




ChoruSmart






Scan the QR Code and find out all the technical informations.

INNOVATIVE



ChoruSmart offers the best technologies for an aesthetic and functional experience suitable for every person. In particular, the new EVO axial and touch controls offer the ability to centralize the management of lights and shutters with an extremely simplified installation.

AESTHETIC VARIABILITY



The wide range of options for customising the devices, in terms of colour and modularity, ensures a vast choice of solutions. Six colourways are available: three with a satin finish and three with a glossy finish, for a perfect match between the devices and the plate.

SCALABLE



ChoruSmart began as a traditional domestic series, but with the addition of a few Connected Smart Home or Home&Building Pro elements, it can become smart and suitable for both renovations and new buildings. The combination of colours, materials, finishes and shapes offers something for every taste and need.

ChoruSmart

ONE plates - Antibacterial white

Technopolymer



GW 16 101 AB
1 module



GW 16 102 AB
2 modules



GW 16 103 AB
3 modules



GW 16 104 AB
4 modules



GW 16 106 AB
6 modules

ONE International plates - Antibacterial white

Technopolymer



GW 16 122 AB
2 modules



GW 16 123 AB
2+2 modules - horizontal



GW 16 126 AB
2+2+2 modules - horizontal



GW 16 124 AB
2+2 modules - vertical



GW 16 127 AB
2+2+2 modules - vertical

Supports

Supports for round/square boxes (*)




GW 16 821 With clutches - 2 modules
GW 16 823 With long clutches - 2 modules



GW 16 822
With screws (not included) - 2 modules

Supports for round/square and rectangular boxes (*)



GW 16 802
With screws - 2 modules

Supports for rectangular boxes (*)



GW 16 803
With screws - 3 modules



GW 16 804
With screws - 4 modules



GW 16 806
With screws - 6 modules

(*) Without antibacterial treatment

Command - Antibacterial white

One-way switches



GW 10 001 AB
1M-1P-16 AX



GW 10 004 AB
1M-2P-16 AX



GW 10 007 AB
1M-2P-25 AX
Heavy-duty loads

Two-way switches



GW 10 051 AB
1M-1P-16 AX

Intermediate switches



GW 10 091 AB
1M-1P-16 AX

Three-way switches



GW 10 122 AB
1M-2P-10 AX
Positions 1-0-2

Push-buttons



GW 10 131 AB
1M-1P-NO-16 A



GW 10 136 AB
1M-1P-NO-16 A
With pull-cord



GW 10 137 AB
1M-1P-NC-16 A



GW 10 140 AB
1M-1P-NO+NO-10 A
With interlock

Interchangeable button keys



GW 10 738 AB
With diffuser



GW 10 739 AB
With neutral lens

Lenses with illuminated symbols



GW 10 505 AB
Bell



GW 10 507 AB
Key



GW 10 511 AB
Nurse

Blanking modules



GW 10 195 AB
1M

Relay



GW 10 726 AB
Call
1M-1P-NO/NC-12 V ac/dc

Power - Antibacterial white

Italian



GW 10 201 AB
2P+E-10 A-250 V ac



GW 10 203 AB
2P+E-16 A-250 V ac
Dual amperage



GW 10 213 AB
2P+E-16 A-250 V ac
Dual amperage



GW 10 223 AB
2P+E-16 A-250 V ac
Dual amperage

Italian/German



GW 10 204 AB
2P+E-16 A-250 V ac
Dual amperage



GW 10 214 AB
2P+E-16 A-250 V ac
Dual amperage - Illuminable (**)



GW 10 224 AB
2P+E-16 A-250 V ac
Dual amperage - Illuminable (**)

German



GW 10 241 AB
2P+E-16 A-250 V ac



GW 10 251 AB
2P+E-16 A-250 V ac



GW 10 341 AB
2P+E-16 A-250 V ac
Front tightening terminals



GW 10 351 AB
2P+E-16 A-250 V ac
Front tightening terminals

French



GW 10 247 AB
2P+E-16 A-250 V ac

Israeli



GW 10 281 AB
2P+E-16 A-250 V ac
Illuminable (**)



GW 10 291 AB
2P+E-16 A-250 V ac
Illuminable (**)



GW 10 282 AB 2P-
10 A-250 V ac

Shaver socket-outlet



GW 10 331 AB
230 V ac-50/60 Hz

(**) supplied without signalling units

Data - Antibacterial white

TV male IEC



GW 10 361 AB
0 dB

TV-SAT



GW 10 383 AB
0 dB

Telephone sockets



GW 10 401 AB
RJ11

Data sockets



GW 10 423 AB
RJ45 cat. 6
UTP



GW 10 424 AB
RJ45 cat. 6
FTP



GW 10 431 AB
AMP/Keystone
Jack adapter

SELV sockets



GW 10 451 AB
2P-6 A-24 V

Signalling and adjustment - Antibacterial white

Single indicator lamps



GW 10 622 AB
1M - Green
Illuminable (**)



GW 10 623 AB
1M - Red
Illuminable (**)

Protruding indicator lamps



GW 10 633 AB
2M-12 V ac/dc-230 V ac-50/60 Hz
Red

Dimmer



GW 10 572A AB
Res./Ind. 40-300 W
Electr. transf. 40-300 W
LED 5-150 W

Accessories

LED Signalling units (*)



GW 10 881
Blue
230 V ac-50/60 Hz



GW 10 882
White
230 V ac-50/60 Hz



GW 10 883
Red
230 V ac-50/60 Hz



GW 10 884
Green
230 V ac-50/60 Hz



GW 10 885
Amber
230 V ac-50/60 Hz



GW 10 894
White
12/24 V ac/dc

(**) supplied without signalling units

ChoruSmart

Antibacterial range



A range of ChoruSmart modular devices and plates made in antibacterial technopolymer, white colour and glossy finish, suitable for hospitals, structures for aged people, schools and wherever cleanness and hygiene are an essential component. The effectiveness of the antibacterial treatment, based on the addition of silver ions, is able to reduce the bacterial growth by 99% within 24 hours and has been tested according to the ISO 22196 (MRSA and Escherichia coli strains) through certified laboratories.

ONE PLATES - ANTIBACTERIAL

Technopolymer



GW 16 103 AB


ONE - White - Antibacterial

Code	Description	For support codes	Pack Carton
GW 16 101 AB	1 module	GW16802, GW16803, GW16803N	12
GW 16 102 AB	2 modules	GW16802, GW16803, GW16803N	12
GW 16 103 AB	3 modules	GW16803, GW16803N	12
GW 16 104 AB	4 modules	GW16804, GW16804N	12
GW 16 106 AB	6 modules	GW16806	6

CHARACTERISTICS: with antibacterial treatment. Glossy finish.

ONE INTERNATIONAL PLATES - ANTIBACTERIAL

Technopolymer



GW 16 124 AB

ONE International - White - Antibacterial

Code	Description	Type	Centre distance	Pack Carton
GW 16 122 AB	2 modules	-	-	12
GW 16 123 AB	2+2 modules	Horizontal	71 mm	12
GW 16 124 AB	2+2 modules	Vertical	71 mm	12
GW 16 126 AB	2+2+2 modules	Horizontal	71 mm	6
GW 16 127 AB	2+2+2 modules	Vertical	71 mm	6

CHARACTERISTICS: with antibacterial treatment. Glossy finish.

COMMAND - GLOSSY WHITE VERSION - ANTIBACTERIAL

Command devices - screw terminals



GW 10 001 AB

One-way switch 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 001 AB	1P - 16AX	Neutral	200 W	1	12/96

CHARACTERISTICS: with antibacterial treatment.

ChoruSmart - Antibacterial



GW 10 004 AB

One-way switches 2P - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 004 AB	2P - 16 AX	Neutral	0/1	200 W	1	12/48
GW 10 007 AB	2P - 25 AX	Neutral	0/1	250 W	1	12/24

CHARACTERISTICS: with antibacterial treatment.
APPLICATIONS: GW10007AB suitable for particular heavy-duty loads (e.g. LED or fluorescent lamp batteries) or high-consumption devices (e.g. ovens, air-conditioners, boilers, etc.).



GW 10 051 AB

Two-way switch 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 051 AB	1P - 16AX	Neutral	200 W	1	12/96

CHARACTERISTICS: with antibacterial treatment.



GW 10 091 AB

Intermediate switch 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 091 AB	1P - 16AX	Neutral	200 W	1	12/48

CHARACTERISTICS: with antibacterial treatment.



GW 10 122 AB

Three-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. modules	Pack Carton
GW 10 122 AB	2P - 10AX	Neutral	UP - DOWN	100 W	1	12/24

CHARACTERISTICS: anti-bacterial treatment. Three stable positions. In the central (OFF) position both contacts are open. Equipped with 6 terminals.
APPLICATIONS: circuit commands that require an interlock (e.g. activation of motorised devices with direction inversion). Selective control of 2 circuits.



GW 10 131 AB

Push-buttons 1P - 250V ac

Code	Description	Button key	Symbol	No. modules	Pack Carton
GW 10 131 AB	1P NO - 16A	Neutral	-	1	12/96
GW 10 136 AB	1P NO - 16A	Pull-cord	-	1	1/12
GW 10 137 AB	1P NC - 16A	Neutral	O red	1	12/24
GW 10 140 AB	1P NO+NO - 10A	With interlock	UP - DOWN	1	12/24

CHARACTERISTICS: with antibacterial treatment. GW10136AB cord in insulating material, 140cm long, with red knob.
GW10140AB button with mechanical interlock. Both contacts are open in the central position (OFF); advisable for activating motorised devices with direction reversal (e.g. roller-shutters, curtains, etc.).

Interchangeable button keys



GW 10 738 AB

Interchangeable button keys

Code	Button key	No. modules	Pack Carton
GW 10 738 AB	With diffuser	1	4/48
GW 10 739 AB	With replaceable neutral lens	1	4/48

CHARACTERISTICS: with antibacterial treatment. Suitable for one-way switches, two-way switches, intermediate switches and push-buttons.

Lenses with illuminated symbol



GW 10 505 AB

Lenses with illuminated symbols

Code	Symbol	Pack Carton
GW 10 505 AB	Bell	20
GW 10 507 AB	Key	20
GW 10 511 AB	Nurse	20

CHARACTERISTICS: with antibacterial treatment.
NOTES: to be used in place of the neutral lens in the illuminable command devices.

Blanking module



GW 10 195 AB

Blanking module

Code	Description	No. modules	Pack Carton
GW 10 195 AB	1 module	1	10/200

CHARACTERISTICS: with antibacterial treatment.

Relay



GW 10 726 AB

Call relay - 12V ac/dc

Code	Supply voltage	No. of poles	Output contacts	No. modules	Pack Carton
GW 10 726 AB	12V ac/dc	1P	1NO/NC 12 V (max. 1A)	1	1/12

CHARACTERISTICS: with antibacterial treatment. Inlets for remote NO push-buttons for alarms and alarm reset. Green LED for alarm status signalling.

ChoruSmart - Antibacterial

POWER - GLOSSY WHITE VERSION - ANTIBACTERIAL

Socket-outlets - Italian/German standard



GW 10 203 AB

Italian standard socket-outlets - 250V ac

Code	Description	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 201 AB	2P+E - 10A	P11	Ø 4 mm	1	12/96
GW 10 203 AB	2P+E - 16 A Dual amperage	P11-P17	Ø 4 / 5 mm	1	12/96

CHARACTERISTICS: with antibacterial treatment. With safety shields.



GW 10 204 AB

Italian/German Standard socket-outlet - 250V ac

Code	Description	Earth pit	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 204 AB	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	6/48

CHARACTERISTICS: with antibacterial treatment. With safety shields.

Socket-outlets for dedicated lines - Italian/German Standard



GW 10 213 AB

Italian standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 213 AB	2P+E - 16 A Dual amperage	Red	P11-P17	Ø 4 / 5 mm	1	12/24
GW 10 223 AB	2P+E - 16 A Dual amperage	Green	P11-P17	Ø 4 / 5 mm	1	12/24

CHARACTERISTICS: with antibacterial treatment, satin finish. With safety shields.



GW 10 214 AB

Italian/German Standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Socket-out type	For plug pins	No. modules	Pack Carton
GW 10 214 AB	2P+E - 16 A Dual amperage illuminable	Red	P40	Ø 4 / 4.8 / 5 mm	2	6/12
GW 10 224 AB	2P+E - 16 A Dual amperage illuminable	Green	P40	Ø 4 / 4.8 / 5 mm	2	6/12

CHARACTERISTICS: with antibacterial treatment, satin finish. With safety shields. Pit of side and central earth contacts. Pre-arranged for housing LED signalling units, not included.
APPLICATIONS: possibility to indicate presence of auxiliary supply.

Socket-outlets - German Standard



GW 10 241 AB

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 241 AB	2P+E - 16A	Ø 4.8 mm	2	6/48

CHARACTERISTICS: with antibacterial treatment, glossy finish. With safety shields.



GW 10 251 AB

German Standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 251 AB	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with antibacterial treatment, satin finish. With safety shields.



GW 10 341 AB

German Standard socket-outlet with front tightening terminals - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 341 AB	2P+E - 16A	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with antibacterial treatment, glossy finish. With safety shields.
Front access terminals with screw fixing, cables side entry.



GW 10 351 AB

German standard socket-outlet for dedicated lines with front tightening terminals - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 351 AB	2P+E - 16A	Red	Ø 4.8 mm	2	6/12

CHARACTERISTICS: with antibacterial treatment, satin finish. With safety shields.
Front access terminals with screw fixing, cables side entry.

ChoruSmart - Antibacterial

Socket-outlet - French standard



GW 10 247 AB

French standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 247 AB	2P+E - 16A	Ø 4 / 4.8 mm	2	6/48

CHARACTERISTICS: with antibacterial treatment. With safety shields.

Socket-outlets - israeli standard



GW 10 281 AB

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 281 AB	2P+E - 16 A illuminable	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: anti-bacterial treatment, safety shields.
Predisposed to house the LED indicator unit - not included.



GW 10 291 AB

Israeli standard socket-outlet for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. modules	Pack Carton
GW 10 291 AB	2P+E - 16 A illuminable	Red	Round Ø 4 / 4.4 mm	2	1/24

CHARACTERISTICS: anti-bacterial treatment, safety shields.
Predisposed to house the LED indicator unit - not included. Satin finish



GW 10 282 AB

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 282 AB	2P - 10 A	Round Ø 4 mm	1	1/48

CHARACTERISTICS: with antibacterial treatment. With safety shields.

Shaver socket-outlet



GW 10 331 AB

Euro-American standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. modules	Pack Carton
GW 10 331 AB	230 V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120-230V ac	20 VA	3	1/2

CHARACTERISTICS: with antibacterial treatment. The socket-outlet is equipped with a self-protection device against overloading.
The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.
The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting boxes or free-standing containers.

DATA - GLOSSY WHITE VERSION - ANTIBACTERIAL

TV-SAT sockets



GW 10 361 AB

Coaxial TV sockets (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	No. modules	Pack Carton
GW 10 361 AB	Direct	0 dB	1	1/48

CHARACTERISTICS: with antibacterial treatment. Allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlets suitable for return channel.



GW 10 383 AB

TV-SAT socket

Code	Connectors	Description	Attenuation	No. modules	Pack Carton
GW 10 383 AB	TV-SAT	Direct	0 dB	2	1/24

CHARACTERISTICS: with antibacterial treatment.Male IEC-type TV connector ø 9.5mm; female F-type SAT connector.
NOTES: demixed socket-outlet with input for co-axial cable Ø 5mm or 7mm.

Telephone socket



GW 10 401 AB

RJ11 telephone socket

Code	Description	Connection	No. modules	Pack Carton
GW 10 401 AB	RJ11	Screw-on terminals	1	1/24

CHARACTERISTICS: with antibacterial treatment.
APPLICATIONS: telephone, telefax, modem.

ChoruSmart - Antibacterial

Data sockets



GW 10 423 AB

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	No. modules	Pack Carton
GW 10 423 AB	RJ45	4	6	UTP	Toolless	1	1/24
GW 10 424 AB	RJ45	4	6	FTP	Toolless	1	1/24

CHARACTERISTICS: with antibacterial treatment.
APPLICATIONS: LANs up to 250MHz (e.g. Videoconference systems, CCTV).
NOTES: circuit identification label included.



GW 10 431 AB

Adapters for housing data connectors

Code	Compatibility	No. modules	Pack Carton
GW 10 431 AB	AMP / Keystone Jack	1	1/48

CHARACTERISTICS: with antibacterial treatment.
NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Socket-outlet for auxiliary circuits



GW 10 451 AB

SELV socket

Code	Description	For plug pins	No. modules	Pack Carton
GW 10 451 AB	2P - 6A - 24V	Ø 3 mm	1	12/24

CHARACTERISTICS: with antibacterial treatment. Centre distance 12.4 mm.

INDICATOR - GLOSSY WHITE VERSION - ANTIBACTERIAL

Indicator light devices

Single indicator lamps - 1 module



GW 10 622 AB

Code	Diffuser colour	Colour meaning	No. modules	Pack Carton
GW 10 622 AB	Green	Safety	1	1/24
GW 10 623 AB	Red	Danger	1	1/24

CHARACTERISTICS: with antibacterial treatment. LED signalling units, not included.
APPLICATIONS: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.

Protruding indicator lamp - 2 modules



GW 10 633 AB

Code	Supply voltage	Diffuser colour	Lamp	No. modules	Pack Carton
GW 10 633 AB	12V ac/dc - 230V ac 50/60 Hz	Red	LED	2	1/24

CHARACTERISTICS: with antibacterial treatment. Highly efficient white LED, powered at 12V ac/dc - 230V ac with double power supply inlet.
APPLICATIONS: suitable for special applications such as the signalling of calls from hospital wards.
NOTES: complete with lamp.

REGULATION - GLOSSY WHITE VERSION - ANTIBACTERIAL

Dimmer

Universal electronic regulator with push-button



GW 10 572 AAB

Code	Supply voltage	No. modules	Pack Carton
GW 10 572 AAB	230V ac - 50/60 Hz	1	1/12

CHARACTERISTICS: with antibacterial treatment. For the regulation and switching of incandescent and halogen lamps 230V ac (40-300W), low voltage halogen and LED lamps with electronic and winding transformers (40-300W), LED lamps 230V ac with dimmer function (5-150W). Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection. Possibility to command and regulate from remote control push-buttons with NO contacts. Equipped with orange signalling LED.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If two regulators are installed in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

ACCESSORIES

Signalling units



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



ChoruSmart



Scan the QR Code and find out all the technical informations.

ANTIBACTERIAL EFFECT

The antibacterial effect is achieved by a special silver ion additive (Biomaster technology) mixed with the technopolymer, which reduces bacterial load growth by 99% over 24 hours.

SAFE ENVIRONMENT

The antibacterial protection remains effective for the lifetime of the treated product. The active ingredient is incorporated into the material, so it does not diminish or migrate, ensuring the highest efficiency over time.

EXTENSIVE RANGE



The ChoruSmart antibacterial range, already complete with Italian and international standard solutions, is increased with addition of flush-mounted enclosures and junction boxes in antibacterial versions, offering a unique solution for the most diverse needs.

System



Domestic range

Plates

p. 988

Domestic range

Modular devices

p. 1004

System

TOP SYSTEM plates

Technopolymer

CLOUD WHITE



GW 22 501	1 module
GW 22 502	2 modules
GW 22 503	3 modules
GW 22 504	4 modules
GW 22 506	6 modules
GW 22 507	4+4 modules
GW 22 508	6+6 modules

TONER BLACK



GW 22 511	1 module
GW 22 512	2 modules
GW 22 513	3 modules
GW 22 514	4 modules
GW 22 516	6 modules
GW 22 517	4+4 modules

Painted technopolymer

TITANIUM



GW 22 601	1 module
GW 22 602	2 modules
GW 22 603	3 modules
GW 22 604	4 modules
GW 22 606	6 modules
GW 22 607	4+4 modules
GW 22 608	6+6 modules

SLATE



GW 22 611	1 module
GW 22 612	2 modules
GW 22 613	3 modules
GW 22 614	4 modules
GW 22 616	6 modules
GW 22 617	4+4 modules
GW 22 618	6+6 modules

Metallised technopolymer

SOFT CHROME



GW 22 651	1 module
GW 22 652	2 modules
GW 22 653	3 modules
GW 22 654	4 modules
GW 22 656	6 modules
GW 22 657	4+4 modules

ANTIQUE GOLD



GW 22 661	1 module
GW 22 662	2 modules
GW 22 663	3 modules
GW 22 664	4 modules
GW 22 666	6 modules
GW 22 667	4+4 modules

Technopolymer - classic colour


ENGLISH WALNUT



GW 22 671	1 module
GW 22 672	2 modules
GW 22 673	3 modules
GW 22 674	4 modules
GW 22 676	6 modules
GW 22 677	4+4 modules

Technopolymer - pastel colours

GERANIUM RED



GW 22 521	1 module
GW 22 522	2 modules
GW 22 523	3 modules
GW 22 524	4 modules
GW 22 526	6 modules
GW 22 527	4+4 modules

VENETIAN GREEN



GW 22 541	1 module
GW 22 542	2 modules
GW 22 543	3 modules
GW 22 544	4 modules
GW 22 546	6 modules
GW 22 547	4+4 modules

SKY BLUE



GW 22 561	1 module
GW 22 562	2 modules
GW 22 563	3 modules
GW 22 564	4 modules
GW 22 566	6 modules
GW 22 567	4+4 modules

CLASSIC BURGUNDY




GW 22 531	1 module
GW 22 532	2 modules
GW 22 533	3 modules
GW 22 534	4 modules
GW 22 536	6 modules
GW 22 537	4+4 modules

RACING GREEN



GW 22 551	1 module
GW 22 552	2 modules
GW 22 553	3 modules
GW 22 554	4 modules
GW 22 556	6 modules
GW 22 557	4+4 modules

JAZZ BLUE




GW 22 571	1 module
GW 22 572	2 modules
GW 22 573	3 modules
GW 22 574	4 modules
GW 22 576	6 modules
GW 22 577	4+4 modules

CORN YELLOW



GW 22 581	1 module
GW 22 582	2 modules
GW 22 583	3 modules
GW 22 584	4 modules
GW 22 586	6 modules
GW 22 587	4+4 modules

Modularity



1 module | 2 modules | 3 modules | 4 modules | 6 modules | 4+4 modules | 6+6 modules (*)

(*) Cloud white, slate and titanium

System


VIRNA plates

Technopolymer

CLOUD WHITE

GW 22 101	1 module
GW 22 102	2 modules
GW 22 103	3 modules
GW 22 104	4 modules
GW 22 106	6 modules
GW 22 107	4+4 modules
GW 22 108	6+6 modules

TONER BLACK



GW 22 111	1 module
GW 22 112	2 modules
GW 22 113	3 modules
GW 22 114	4 modules
GW 22 116	6 modules
GW 22 117	4+4 modules

Painted technopolymer

TITANIUM



GW 22 281	1 module
GW 22 282	2 modules
GW 22 283	3 modules
GW 22 284	4 modules
GW 22 286	6 modules
GW 22 287	4+4 modules
GW 22 288	6+6 modules

SLATE



GW 22 291	1 module
GW 22 292	2 modules
GW 22 293	3 modules
GW 22 294	4 modules
GW 22 296	6 modules
GW 22 297	4+4 modules
GW 22 298	6+6 modules

Metallised technopolymer

SOFT CHROME



GW 22 251	1 module
GW 22 252	2 modules
GW 22 253	3 modules
GW 22 254	4 modules
GW 22 256	6 modules
GW 22 257	4+4 modules


ANTIQUE GOLD



GW 22 261	1 module
GW 22 262	2 modules
GW 22 263	3 modules
GW 22 264	4 modules
GW 22 266	6 modules
GW 22 267	4+4 modules

Technopolymer - classic colour


ENGLISH WALNUT



GW 22 271	1 module
GW 22 272	2 modules
GW 22 273	3 modules
GW 22 274	4 modules
GW 22 276	6 modules
GW 22 277	4+4 modules

Technopolymer - pastel colours

GERANIUM RED



GW 22 121	1 module
GW 22 122	2 modules
GW 22 123	3 modules
GW 22 124	4 modules
GW 22 126	6 modules
GW 22 127	4+4 modules

VENETIAN GREEN



GW 22 141	1 module
GW 22 142	2 modules
GW 22 143	3 modules
GW 22 144	4 modules
GW 22 146	6 modules
GW 22 147	4+4 modules

SKY BLUE




GW 22 161	1 module
GW 22 162	2 modules
GW 22 163	3 modules
GW 22 164	4 modules
GW 22 166	6 modules
GW 22 167	4+4 modules

CLASSIC BURGUNDY




GW 22 131	1 module
GW 22 132	2 modules
GW 22 133	3 modules
GW 22 134	4 modules
GW 22 136	6 modules
GW 22 137	4+4 modules

RACING GREEN



GW 22 151	1 module
GW 22 152	2 modules
GW 22 153	3 modules
GW 22 154	4 modules
GW 22 156	6 modules
GW 22 157	4+4 modules

JAZZ BLUE




GW 22 171	1 module
GW 22 172	2 modules
GW 22 173	3 modules
GW 22 174	4 modules
GW 22 176	6 modules
GW 22 177	4+4 modules

CORN YELLOW



GW 22 181	1 module
GW 22 182	2 modules
GW 22 183	3 modules
GW 22 184	4 modules
GW 22 186	6 modules
GW 22 187	4+4 modules

Modularity



1 module | 2 modules | 3 modules | 4 modules | 6 modules | 4+4 modules | 6+6 modules (*)

(*) Cloud white, slate and titanium

System

Plates



The technopolymer plates, available in two different shapes, Top System and Virna, and in 14 colour shades are the ideal solution for every installation.Top System: classic forms, resistant materials. A line of simple, functional plates that can enhance every environment, bringing harmony and beauty to the entire home.Virna: plates with unmistakable modern style, created to meet the needs of contemporary design. The elegance of the rectangular form is enhanced by the lightness and simplicity of the lines which surround the command buttons.

TOP SYSTEM PLATES

Technopolymer



GW 22 503

TOP SYSTEM - Cloud white

Code	Description	Configuration	For support codes	Pack Carton
GW 22 501	1 module	-	GW24201	96
GW 22 502	2 modules	-	GW24262	96
GW 22 503	3 modules	-	GW24201	96
GW 22 504	4 modules	-	GW24202	96
GW 22 506	6 modules	-	GW24230	48
GW 22 507	4+4 modules	Overlapping	GW24240	6
GW 22 508	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.




GW 22 513

TOP SYSTEM - Toner black

Code	Description	Configuration	For support codes	Pack Carton
GW 22 511	1 module	-	GW24201	96
GW 22 512	2 modules	-	GW24262	12
GW 22 513	3 modules	-	GW24201	96
GW 22 514	4 modules	-	GW24202	12
GW 22 516	6 modules	-	GW24230	8
GW 22 517	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

Technopolymer, in pastel colours



GW 22 523

TOP SYSTEM - Geranium red

Code	Description	Configuration	For support codes	Pack Carton
GW 22 521	1 module	-	GW24201	24
GW 22 522	2 modules	-	GW24262	12
GW 22 523	3 modules	-	GW24201	24
GW 22 524	4 modules	-	GW24202	12
GW 22 526	6 modules	-	GW24230	8
GW 22 527	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

TOP SYSTEM - Classic burgundy



Code	Description	Configuration	For support codes	Pack Carton
GW 22 531	1 module	-	GW24201	24
GW 22 532	2 modules	-	GW24262	12
GW 22 533	3 modules	-	GW24201	24
GW 22 534	4 modules	-	GW24202	12
GW 22 536	6 modules	-	GW24230	8
GW 22 537	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 533

TOP SYSTEM - Venetian green



Code	Description	Configuration	For support codes	Pack Carton
GW 22 541	1 module	-	GW24201	24
GW 22 542	2 modules	-	GW24262	12
GW 22 543	3 modules	-	GW24201	24
GW 22 544	4 modules	-	GW24202	12
GW 22 546	6 modules	-	GW24230	8
GW 22 547	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 543

TOP SYSTEM - Racing green



Code	Description	Configuration	For support codes	Pack Carton
GW 22 551	1 module	-	GW24201	24
GW 22 552	2 modules	-	GW24262	12
GW 22 553	3 modules	-	GW24201	24
GW 22 554	4 modules	-	GW24202	12
GW 22 556	6 modules	-	GW24230	8
GW 22 557	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 553

TOP SYSTEM - Sky blue




Code	Description	Configuration	For support codes	Pack Carton
GW 22 561	1 module	-	GW24201	24
GW 22 562	2 modules	-	GW24262	12
GW 22 563	3 modules	-	GW24201	24
GW 22 564	4 modules	-	GW24202	12
GW 22 566	6 modules	-	GW24230	8
GW 22 567	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 563

TOP SYSTEM - Jazz blue



Code	Description	Configuration	For support codes	Pack Carton
GW 22 571	1 module	-	GW24201	24
GW 22 572	2 modules	-	GW24262	12
GW 22 573	3 modules	-	GW24201	24
GW 22 574	4 modules	-	GW24202	12
GW 22 576	6 modules	-	GW24230	8
GW 22 577	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 573

System - Plates



GW 22 583

TOP SYSTEM - Corn yellow

Code	Description	Configuration	For support codes	Pack Carton
GW 22 581	1 module	-	GW24201	24
GW 22 582	2 modules	-	GW24262	12
GW 22 583	3 modules	-	GW24201	24
GW 22 584	4 modules	-	GW24202	12
GW 22 586	6 modules	-	GW24230	8
GW 22 587	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

Painted technopolymer



GW 22 603

TOP SYSTEM - Titanium

Code	Description	Configuration	For support codes	Pack Carton
GW 22 601	1 module	-	GW24201	12
GW 22 602	2 modules	-	GW24262	12
GW 22 603	3 modules	-	GW24201	12
GW 22 604	4 modules	-	GW24202	12
GW 22 606	6 modules	-	GW24230	8
GW 22 607	4+4 modules	Overlapping	GW24240	6
GW 22 608	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.



GW 22 613

TOP SYSTEM - Slate

Code	Description	Configuration	For support codes	Pack Carton
GW 22 611	1 module	-	GW24201	12
GW 22 612	2 modules	-	GW24262	12
GW 22 613	3 modules	-	GW24201	12
GW 22 614	4 modules	-	GW24202	12
GW 22 616	6 modules	-	GW24230	8
GW 22 617	4+4 modules	Overlapping	GW24240	6
GW 22 618	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.

Technopolymer, classic colour



GW 22 673

TOP SYSTEM - English walnut

Code	Description	Configuration	For support codes	Pack Carton
GW 22 671	1 module	-	GW24201	12
GW 22 672	2 modules	-	GW24262	12
GW 22 673	3 modules	-	GW24201	12
GW 22 674	4 modules	-	GW24202	12
GW 22 676	6 modules	-	GW24230	8
GW 22 677	4+4 modules	Overlapping	GW24240	6

Metallised technopolymer

TOP SYSTEM - Soft chrome



Code	Description	Configuration	For support codes	Pack Carton
GW 22 651	1 module	-	GW24201	12
GW 22 652	2 modules	-	GW24262	12
GW 22 653	3 modules	-	GW24201	12
GW 22 654	4 modules	-	GW24202	12
GW 22 656	6 modules	-	GW24230	8
GW 22 657	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 653

TOP SYSTEM - Antique gold



Code	Description	Configuration	For support codes	Pack Carton
GW 22 661	1 module	-	GW24201	12
GW 22 662	2 modules	-	GW24262	12
GW 22 663	3 modules	-	GW24201	12
GW 22 664	4 modules	-	GW24202	12
GW 22 666	6 modules	-	GW24230	8
GW 22 667	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 663

VIRNA PLATES

Technopolymer


VIRNA - Cloud white

Code	Description	Configuration	For support codes	Pack Carton
GW 22 101	1 module	-	GW24201	96
GW 22 102	2 modules	-	GW24262	96
GW 22 103	3 modules	-	GW24201	96
GW 22 104	4 modules	-	GW24202	96
GW 22 106	6 modules	-	GW24230	48
GW 22 107	4+4 modules	Overlapping	GW24240	6
GW 22 108	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.

GW 22 103

VIRNA - Toner black




Code	Description	Configuration	For support codes	Pack Carton
GW 22 111	1 module	-	GW24201	96
GW 22 112	2 modules	-	GW24262	12
GW 22 113	3 modules	-	GW24201	96
GW 22 114	4 modules	-	GW24202	12
GW 22 116	6 modules	-	GW24230	8
GW 22 117	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 113

System - Plates

Technopolymer, in pastel colours




VIRNA - Geranium red

Code	Description	Configuration	For support codes	Pack Carton
GW 22 121	1 module	-	GW24201	24
GW 22 122	2 modules	-	GW24262	12
GW 22 123	3 modules	-	GW24201	24
GW 22 124	4 modules	-	GW24202	12
GW 22 126	6 modules	-	GW24230	8
GW 22 127	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 123



VIRNA - Classic burgundy

Code	Description	Configuration	For support codes	Pack Carton
GW 22 131	1 module	-	GW24201	24
GW 22 132	2 modules	-	GW24262	12
GW 22 133	3 modules	-	GW24201	24
GW 22 134	4 modules	-	GW24202	12
GW 22 136	6 modules	-	GW24230	8
GW 22 137	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 133




VIRNA - Venetian green

Code	Description	Configuration	For support codes	Pack Carton
GW 22 141	1 module	-	GW24201	24
GW 22 142	2 modules	-	GW24262	12
GW 22 143	3 modules	-	GW24201	24
GW 22 144	4 modules	-	GW24202	12
GW 22 146	6 modules	-	GW24230	8
GW 22 147	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 143



VIRNA - Racing green

Code	Description	Configuration	For support codes	Pack Carton
GW 22 151	1 module	-	GW24201	24
GW 22 152	2 modules	-	GW24262	12
GW 22 153	3 modules	-	GW24201	24
GW 22 154	4 modules	-	GW24202	12
GW 22 156	6 modules	-	GW24230	8
GW 22 157	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 153




VIRNA - Sky blue

Code	Description	Configuration	For support codes	Pack Carton
GW 22 161	1 module	-	GW24201	24
GW 22 162	2 modules	-	GW24262	12
GW 22 163	3 modules	-	GW24201	24
GW 22 164	4 modules	-	GW24202	12
GW 22 166	6 modules	-	GW24230	8
GW 22 167	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 163

VIRNA - Jazz blue



Code	Description	Configuration	For support codes	Pack Carton
GW 22 171	1 module	-	GW24201	24
GW 22 172	2 modules	-	GW24262	12
GW 22 173	3 modules	-	GW24201	24
GW 22 174	4 modules	-	GW24202	12
GW 22 176	6 modules	-	GW24230	8
GW 22 177	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 173

VIRNA - Corn yellow



Code	Description	Configuration	For support codes	Pack Carton
GW 22 181	1 module	-	GW24201	24
GW 22 182	2 modules	-	GW24262	12
GW 22 183	3 modules	-	GW24201	24
GW 22 184	4 modules	-	GW24202	12
GW 22 186	6 modules	-	GW24230	8
GW 22 187	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

GW 22 183

Painted technopolymer

VIRNA - Titanium




Code	Description	Configuration	For support codes	Pack Carton
GW 22 281	1 module	-	GW24201	12
GW 22 282	2 modules	-	GW24262	12
GW 22 283	3 modules	-	GW24201	24
GW 22 284	4 modules	-	GW24202	12
GW 22 286	6 modules	-	GW24230	8
GW 22 287	4+4 modules	Overlapping	GW24240	6
GW 22 288	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.

GW 22 283

VIRNA - Slate




Code	Description	Configuration	For support codes	Pack Carton
GW 22 291	1 module	-	GW24201	12
GW 22 292	2 modules	-	GW24262	12
GW 22 293	3 modules	-	GW24201	24
GW 22 294	4 modules	-	GW24202	12
GW 22 296	6 modules	-	GW24230	8
GW 22 297	4+4 modules	Overlapping	GW24240	6
GW 22 298	6+6 modules	Overlapping	GW24241	6

CHARACTERISTICS: glossy finish.

GW 22 293

System - Plates

Technopolymer, classic colour



GW 22 273

VIRNA - English walnut

Code	Description	Configuration	For support codes	Pack Carton
GW 22 271	1 module	-	GW24201	12
GW 22 272	2 modules	-	GW24262	12
GW 22 273	3 modules	-	GW24201	24
GW 22 274	4 modules	-	GW24202	12
GW 22 276	6 modules	-	GW24230	8
GW 22 277	4+4 modules	Overlapping	GW24240	6

Metallised technopolymer



GW 22 253

VIRNA - Soft chrome

Code	Description	Configuration	For support codes	Pack Carton
GW 22 251	1 module	-	GW24201	12
GW 22 252	2 modules	-	GW24262	12
GW 22 253	3 modules	-	GW24201	24
GW 22 254	4 modules	-	GW24202	12
GW 22 256	6 modules	-	GW24230	8
GW 22 257	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.



GW 22 263

VIRNA - Antique gold

Code	Description	Configuration	For support codes	Pack Carton
GW 22 261	1 module	-	GW24201	12
GW 22 262	2 modules	-	GW24262	12
GW 22 263	3 modules	-	GW24201	24
GW 22 264	4 modules	-	GW24202	12
GW 22 266	6 modules	-	GW24230	8
GW 22 267	4+4 modules	Overlapping	GW24240	6

CHARACTERISTICS: glossy finish.

SPECIAL PLATES, ENCLOSURES AND SUPPORTS

COMPACT self-supporting plates

Self-supporting plates - Cloud white



GW 24 001

Code	Description	Configuration	For flush mounting box	For wall mounting boxes	Characteristics	Pack Carton
GW 24 001	1 module	-	GW24403, GW24403PM	GW24006	Halogen free	1/120
GW 24 002	2 modules	-	GW24403, GW24403PM	GW24006	Halogen free	1/120
GW 24 003	3 modules	-	GW24403, GW24403PM	GW24006	Halogen free	1/120
GW 24 004	4 modules	-	GW24404, GW24404PM	-	Halogen free	1/60
GW 24 005	3+3 modules	Overlapping	GW24206	GW24007	Halogen free	1/60

Blank plates for rectangular flush-mounting boxes



GW 24 211

Code	Description	Configuration	Fixing	Colour	Characteristics	Pack Carton
GW 24 211	3 modules	-	With screw	Cloud white	Halogen free	1/120
GW 24 212	3 modules	-	With screw	Toner black	Halogen free	1/120
GW 24 213	4 modules	-	With screw	Cloud white	Halogen free	1/60
GW 24 214	4 modules	-	With screw	Toner black	Halogen free	1/60
GW 24 215	3+3 modules	Overlapping	With screw	Cloud white	Halogen free	1/60
GW 24 216	3+3 modules	Overlapping	With screw	Toner black	Halogen free	1/60

Watertight plates

Self-supporting watertight plates for installation on flush-mounting rectangular boxes - IP55



GW 22 451

Code	Description	Colour Plate	For flush mounting box	Pack Carton
GW 22 451	3 modules	Cloud white	Rectangular 3 modules	30
GW 22 452	3 modules	Black	Rectangular 3 modules	30
GW 22 453	3 modules	Grey RAL 7035	Rectangular 3 modules	30
GW 22 461	4 modules	Cloud white	Rectangular 4 modules	30
GW 22 462	4 modules	Black	Rectangular 4 modules	30
GW 22 463	4 modules	Grey RAL 7035	Rectangular 4 modules	30

CHARACTERISTICS: ergonomic membrane with notches in UV-resistant material. Snap closing system. Opening made easy by wide key.

System - Plates

Plates for profiles



GW 24 008

Self-supporting plates for profiles and panels complete with insulating box

Code	Description	Configuration	Colour Plate	Pack Carton
GW 24 008	1 module	-	Cloud white	1/60
GW 24 009	1 module	-	Toner black	1/60
GW 24 010	2 modules	-	Cloud white	1/60
GW 24 011	2 modules	-	Toner black	1/60
GW 24 022	2+2 modules	Overlapping	Cloud white	1/30
GW 24 023	2+2 modules	Overlapping	Toner black	1/30

CHARACTERISTICS: box colour, Grey RAL7035.

Wall-mounting boxes



GW 22 471

Wall-mounting boxes for TOP SYSTEM plates

Code	Suitable for	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Characteristics	Pack Carton
GW 22 471	1/2/3 modules TOP SYSTEM	Cloud white	14x8.5 30x13 20x10	16 - 20	Halogen free	3/60
GW 22 472	4 modules TOP SYSTEM	Cloud white	14x8.5 30x13 20x10	16 - 20	Halogen free	3/30

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.



GW 24 006

Wall-mounting boxes for COMPACT self-supporting plates

Code	Suitable for	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Characteristics	Pack Carton
GW 24 006	1/2/3 modules COMPACT	Cloud white	14x8.5 30x13 20x10	16 - 20 - 25	Halogen free	3/60
GW 24 007	3+3 modules COMPACT	Cloud white	14x8.5 30x13 20x10	16 - 20 - 25	Halogen free	3/30

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.



GW 32 431

Wall-mounting boxes for VIRNA plates

Code	Suitable for plates	Colour	For trunking dim. (mm)	For conduits max Ø (mm)	Characteristics	Pack Carton
GW 32 431	1/2/3 modules	Cloud white	15x17 / 22x10 / 25x17	16 - 20	Halogen free	3/60
GW 32 432	1/2/3 modules	Toner black	15x17 / 22x10 / 25x17	16 - 20	Halogen free	3/60

CHARACTERISTICS: fitted for fixing the earth terminal GW26407.



GW 24 018

Free-standing and wall-mounting enclosures

Code	Description	Colour	Outer dim. LxHxD (mm)	Pack Carton
GW 24 018	4 modules	Cloud white	126x91x60	1/30
GW 24 019	4 modules	Toner black	126x91x60	1/30
GW 24 020	6 modules	Cloud white	181x91x60	1/20
GW 24 021	6 modules	Toner black	181x91x60	1/20

ACCESSORIES SUPPLIED: cable gland (for max Ø 10 mm cable), cable clamp.

System - Plates

Supports



GW 24 201

Insulating supports to install TOP SYSTEM / VIRNA plates on rectangular boxes


Code	Description	Configuration	Fixing	Characteristics	Pack Carton
GW 24 201	3 modules	-	2 screws (included)	Halogen free	10/300
GW 24 202	4 modules	-	2 screws (included)	Halogen free	10/150
GW 24 230	6 modules	-	4 screws (included)	Halogen free	10/100
GW 24 240	4+4 modules	Overlapping	4 screws (included)	Halogen free	10/60
GW 24 241	6+6 modules	Overlapping	4 screws (included)	Halogen free	10/40



GW 24 262

Insulating supports to install TOP SYSTEM / VIRNA plates on square/rectangular boxes

Code	Description	Fixing	Characteristics	Pack Carton
GW 24 262	2 modules	2 screws (included)	Halogen free	10/120



GW 26 409

Supports for assembling SYSTEM devices on DIN rail

Code	Description	No. DIN modules	Pack Carton
GW 26 409	1 module	1.5	5/300
GW 26 410	2 modules	3	5/150



System



Scan the QR Code and find out all the technical informations.

TWO LINES, ONE SINGLE OFFER



The System range includes two lines of plates, one more rounded and the other with a squarer design, in a domestic series recognised for its reliability and robustness.

A COMPLETE SOLUTION



The System devices are compatible with a wide range of accessories and can be installed in any electrical installation: flush- and surface-mounted rectangular boxes, flush-mounted square boxes, profiles and DIN rails, floor turrets and 27 Combi enclosures.

INSTALLATION FLEXIBILITY



The domestic System series offers maximum application flexibility. It is highly versatile, with two attachment options, from the front or back of the support, making the mounting and release of devices quick and easy.

System

Command - white

One-way switches


GW 20 571
1M-1P-16 AX


GW 20 572
1M-1P-16 AX
Backlit 230 V ac


GW 20 583
1M-1P-16 AX
Illuminable (*)


GW 20 503
1M-2P-16 AX


GW 20 504
1M-2P-16 AX
Backlit 230 V ac


GW 20 584
1M-2P-16 AX
Illuminable (*)


GW 20 005
1M-2P-10 AX
With key


GW 20 585
1M-2P-25 AX
For heavy duty loads

Two-way switches


GW 20 576
1M-1P-16 AX


GW 20 577
1M-1P-16 AX
Backlit 230 V ac


GW 20 588
1M-1P-16 AX
Illuminable (*)


GW 20 008
1M-1P-10 AX
With key


GW 20 589
2M-1P-16 AX
Illuminable (*)

Intermediate switches


GW 20 579
1M-1P-16 AX


GW 20 580
2M-1P-16 AX
Illuminable (*)

Push-buttons


GW 20 510
1M-1P-NO-10 A


GW 20 515
Backlit 230 V ac
GW 20 516
Backlit 12/24 V


GW 20 529
1M-1P-NO-10 A
Illuminable (*)


GW 20 531
1M-1P-NC-10 A
Illuminable (*)


GW 20 511
1M-1P-NO-10 A
Key


GW 20 512
1M-1P-NO-10 A
Bell


GW 20 513
1M-1P-NO-10 A
Light


GW 20 514
1M-1P-NO-10 A
Stair light


GW 20 530
1M-2P-NO-10 A
With key


GW 20 522
1M-1P-NO+NC-10 A
Start


GW 20 523
1M-1P-NC+NO-10 A
Stop


GW 20 520
1M-1P-NO+NO-10 A
With interlock


GW 20 521
1M-1P-NO+NO-10 A
With interlock


GW 20 519
1M-1P-NC-10 A


GW 20 517
1M-2P-NO-10 A


GW 20 591
2M-1P-NO-10 A
Illuminable name plate (*)


GW 20 024
3M-1P-NO-10 A
Illuminable name plate (*)


GW 20 527
2M-1P-NO-10 A
Illuminable (*)


GW 20 518
1M-2P-NO-10 A
With pull-cord

Three-way switches


GW 20 559
1M-1P-10 AX
Positions 1-0-2


GW 20 528
1M-1P-10 AX
Positions 1-0-2


GW 20 560
1M-2P-10 AX
Positions 1-0-2

Miniature lamp



GW 10 893	12/24 V ac/dc	White
GW 30 943	230 V ac	Red
GW 30 944	230 V ac	Green
GW 30 946	110/230 V ac	Light blue
GW 30 947	110/230 V ac	White

Cartridge lamp



GW 20 902 S6x36	12 V ac/dc	White
GW 20 903 S6x36	24 V ac/dc	White
GW 20 904 S6x31	12 V ac/dc	White
GW 20 905 S6x31	24 V ac/dc	White
GW 20 906 S6,3x28	110/230 V ac	Red

Lenses with illuminated symbol

GW 20 533
Neutral


GW 20 537


GW 20 538


GW 20 539


GW 20 549


GW 20 550


GW 20 551



GW 20 595



GW 20 561



GW 20 562



GW 20 563



GW 20 564



GW 20 565


GW 20 540


GW 20 542

General services



GW 20 592



GW 20 593

GW 20 596



GW 20 597

Technical services



GW 20 594



GW 20 566



GW 20 567



GW 20 568



GW 20 569



GW 20 570

Numerical services

Infrared


GW 20 821
Movement detector
1M-1NO-3 A

Relay


GW 20 071
Latching
1M-1P-10 A-250 V ac


GW 20 072
Latching
1M-2P-10 A-250 V ac


GW 20 074
Monostable
1M-1P-10 A-250 V ac-
1NO/NC


GW 20 076
Call
1M-1P-NO/NC-12 V ac/dc

Blanking modules and cable output


GW 20 056
1M


GW 20 073
2M


GW 20 058
1M
Cable output

(*) supplied without signalling unit

Power - white

Italian


GW 20 201
2P+E-10 A-250 V ac


GW 20 203
2P+E-16 A-250 V ac
Dual amperage


GW 20 295
2P+E-16 A-250 V ac
Dual amperage


GW 20 281
2P+E-16 A-250 V ac
Dual amperage


GW 20 286
2P+E-16 A-250 V ac
Dual amperage


GW 20 291
2x2P+E-16 A-250 V ac
Dual amperage

Italian/German


GW 20 205
2P+E-16 A-250 V ac


GW 20 246
2P+E-16 A-250 V ac
Dual amperage


GW 20 296
2P+E-16 A-250 V ac
Dual amperage


GW 20 282
2P+E-16 A-250 V ac
Dual amperage


GW 20 287
2P+E-16 A-250 V ac
Dual amperage


Swiss



GW 20 351
2P+E-10 A-250 V ac
Type 12

German


GW 20 265
2P+E-16 A-250 V ac


GW 20 297
2P+E-16 A-250 V ac


GW 20 283
2P+E-16 A-250 V ac


GW 20 288
2P+E-16 A-250 V ac

French


GW 20 206
2P-16 A-250 V ac


GW 20 207
2P+E-16 A-250 V ac


GW 20 312
2P+E-16 A-250 V ac

British


GW 20 208
2P+E-13 A-250 V ac


GW 20 209
2P+E-16 A-250 V ac

Australian



GW 20 357
2P+E-10 A-250 V ac



GW 20 356
2P+E-15 A-250 V ac

Euro-american/USA


GW 20 212
2P+E-10/15 A-250/125 V ac


GW 20 214
2P+E-15 A-125 V ac


GW 20 216
2P+E-15 A-250 V ac

Argentinian


GW 20 248
2P+E-10 A-250 V ac

Israeli


GW 20 220
2P+E-16 A-250 V ac
Illuminable (*)


GW 20 298
2P+E-16 A-250 V ac
Illuminable (*)


GW 20 299
2P+E-16 A-250 V ac
Illuminable (*)


GW 20 320
2P-10 A-250 V ac

Special sockets


GW 20 239
SELV
2P-6 A-24 V


GW 20 234
SELV
2P-6 A-24 V
Polarised


GW 20 241
For loudspeaker

(*) supplied without signalling unit

System

Data - white

TV-SAT



F female
GW 20 391 - 0 dB
GW 20 396 - 5 dB
GW 20 392 - 10 dB



IEC male
GW 20 381 - 0 dB
GW 20 386 - 5 dB
GW 20 382 - 10 dB



IEC female
GW 20 228 - 0 dB
GW 20 229 - 20 dB ▲
GW 20 230 - Term. 20 dB ▲



GW 20 277
Terminal
resistance 75
ohm

Telephone sockets



GW 20 251
RJ11



GW 20 235
French 8 contacts



GW 20 272
British 6 contacts

Data sockets



GW 20 685 Cat. 6
GW 20 684 Cat. 6
GW 20 271 Cat. 5e
RJ45 - UTP



GW 20 686 Cat. 6
GW 20 243 Cat. 5e
RJ45 - FTP



GW 20 266 IBM
GW 20 267 SYSTIMAX Commscope
GW 20 270 AMP/Keystone Jack
Adapters



GW 20 238
Unwired enclosure for SUB-D 9/15/25 PIN

USB and HDMI couplers



GW 38 056
HDMI coupler



GW 38 057
USB coupler

USB power supply



GW 20 363
Dual USB charger
Type A+C - 1M-3 A
100-240 V ac - 50/60 Hz

Power, comfort and climate management - white

Dimmer



GW 20 802
Resistive 100-500 W
230 V ac-50/60 Hz



GW 20 811
Resistive 100-500 W
Inductive 100-500 VA
With two-way switch
230 V ac-50/60 Hz



▲
GW 20 803
Resistive 100-900 W
Inductive 40-300 VA
230 V ac-50/60 Hz



GW 20 828
Resistive 60-500 W
Inductive 60-500 VA
230 V ac-50/60 Hz



GW 20 829
For electronic transformers
230 V ac-50/60 Hz

Electronic timer



GW 20 825
230 V ac-50/60 Hz
Daily/Weekly

Timer



GW 20 810
2M

Thermoregulation



GW 20 852
Thermostat
230 V ac-50/60 Hz



GW 16 970 CB
Thermostat/Chronothermostat
Thermo ICE WiFi
110-230 V ac-50/60 Hz
Wall-mounting

Automatic circuit breakers



Miniature circuit breakers
3 kA
C characteristic

GW 20 431 - 6 A
GW 20 432 - 10 A
GW 20 433 - 16 A
1P

GW 20 434 - 6 A
GW 20 435 - 10 A
GW 20 436 - 16 A
1P+N

GW 20 454 - 6 A
GW 20 455 - 10 A
GW 20 456 - 16 A
1P+N colour red



Residual miniature circuit
breakers
3 kA
C characteristic

GW 20 437 - 6 A
GW 20 438 - 10 A
GW 20 439 - 16 A
1P+N-10 mA

GW 20 448 - 6 A
GW 20 449 - 10 A
GW 20 450 - 16 A
1P+N-30 mA

Protection devices



GW 20 423
Surge protection device



GW 20 401
Fuse-holder
In MAX=16 A

▲ Articles designed exclusively for export to a limited number of Countries not belonging to the EU (or candidates for membership) or the European Free Trade Association. Check with Gewiss Customer Service to make sure the product meets the regulation of the Country in question before importing it.

(*) supplied without signalling unit

Hotel components - white

Badge switch



GW 20 820
1P-NO-10 A
Backlit 230 V ac

Shaver socket-outlet



GW 20 841
230 V ac-50/60 Hz

Climate control



GW 20 853
Thermostat for fan-coil
230 V ac-50/60 Hz

Three-way switch



GW 20 651
1M-1P-10 AX
DND + MUR

Double indicator lamp



GW 20 656
1M - Opal
DND + MUR Illuminable (*)

Indicator and technical alarms - white

Anti black-out lamps



GW 20 833
230 V ac-50/60 Hz
Removable



GW 20 835
230 V ac-50/60 Hz

Ringers and buzzers



GW 20 613- 12 V ac
GW 20 616- 230 V ac
Ringers



GW 20 617- 12 V ac
GW 20 620- 230 V ac
Buzzers

Indicator lamps



- GW 20 603
- GW 20 604
- GW 20 605
- GW 20 606
- GW 20 631

Flat diffuser
Illuminable (*)



GW 20 607- 230 V ac
GW 20 608- 12/24 V ac/dc

Flat diffuser complete
with lamp



GW 20 634
Stair riser lamp
2M



- ○ GW 20 601
- ● GW 20 623
- ○ GW 20 625
- ● GW 20 626

Flat diffuser 12/24 V ac/dc



- ○ GW 20 602
- ● GW 20 627
- ○ GW 20 629
- ● GW 20 628

Protruding diffuser 12/24 V ac/dc



GW 20 622
Lamp-holder E27

Detectors



GW A1 514
Flood alarm ZigBee



GW A1 521
1-channel actuator ZigBee
230 V ac-50 Hz

Accessories


GW A1 541
Wall-mounting support
for flood alarm



GW 30 522
GAS solenoid valve
3/4"-230 V ac-12 VA

Supports

Supports for square and rectangular boxes



GW 24 262
With screws - 2 modules

Supports for rectangular boxes



GW 24 201 With screws - 3 modules



GW 24 202 With screws - 4 modules



GW 24 230 With screws - 6 modules



GW 24 240 With screws - 4+4 modules



GW 24 241 With screws - 6+6 modules

(*) supplied without signalling unit

System

White modular devices

The System modular devices make it possible to create infinite combination between devices and plates, thanks to a complete range that is able to satisfy all design, functional and installation requirements. Colour and finiture: glossy white, bright and versatile. Ideal for flush-mounting solutions (for rectangular or square boxes), surface-mounting solutions, and for special applications. The range includes commands, socket- outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.





COMMAND - WHITE VERSION

Command devices



GW 20 571

One-way switches - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 571	1P - 16AX	Neutral	-	200 W	1	80/320
GW 20 572	1P - 16 AX backlit	With replaceable neutral lens	-	200 W	1	30/60
GW 20 583	1P - 16AX illuminable	With replaceable neutral lens	-	200 W	1	30/60
GW 20 503	2P - 16 AX	Neutral	0/1	200 W	1	30/60
GW 20 504	2P - 16 AX backlit	With replaceable neutral lens	-	200 W	1	30/60
GW 20 584	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	1	30/60
GW 20 005	2P - 10AX	With key	0/1	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.
ACCESSORIES SUPPLIED: GW20572, GW20504 - red fluorescent 230Vac (0.4W) signalling unit. GW20005 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 20 585

One-way switch 2P for heavy-duty installations - 25A - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 585	25 AX	Neutral	0/1	250 W	1	15/30

CHARACTERISTICS: suitable for particular heavy-duty loads (e.g. set of fluorescent lamp) or high consumption devices (ovens, air-conditioners, boilers, etc.).



GW 20 576

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 576	1P - 16AX	Neutral	200 W	1	80/320
GW 20 577	1P - 16 AX backlit	With replaceable neutral lens	200 W	1	30/60
GW 20 588	1P - 16AX illuminable	With replaceable neutral lens	200 W	1	30/60
GW 20 008	1P - 10AX	With key	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.
ACCESSORIES SUPPLIED: GW20577 - red fluorescent 230Vac (0.4W) signalling unit. GW20008 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 20 579

Intermediate switch 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 579	1P - 16AX	Neutral	200 W	1	30/60

Three-way switch 1P - 250V ac



GW 20 559

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 559	1P - 10AX	Neutral	UP - DOWN	100 W	1	30/60
GW 20 528	1P - 10AX	With replaceable neutral lens	-	100 W	1	30/60

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
GW20528 - not-illuminated product; equipped with neutral lens.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

Three-way switch 2P - 250 V ac



GW 20 560

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 560	2P - 10AX	Neutral	UP - DOWN	100 W	1	30/60

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With 6 terminal blocks.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

Push-buttons - 250V ac



GW 20 510

Code	Description	Button key	Symbol	No. SYSTEM modules	Pack Carton
GW 20 510	1P NO - 10A	Neutral	-	1	80/160
GW 20 511	1P NO - 10A	With symbol	Key	1	15/30
GW 20 512	1P NO - 10A	With symbol	Bell	1	30/60
GW 20 513	1P NO - 10A	With symbol	Light	1	15/30
GW 20 514	1P NO - 10A	With symbol	Stair light	1	15/30
GW 20 515	1P NO - 10 A backlit	With replaceable neutral lens	-	1	30/60
GW 20 516	1P NO - 10 A backlit	With replaceable neutral lens	-	1	30/60
GW 20 529	1P NO - 10A illuminable	With replaceable neutral lens	-	1	30/60
GW 20 531	1P NC - 10 A illuminable	With replaceable neutral lens	-	1	15/30
GW 20 519	1P NC - 10A	Neutral	Circle	1	15/30
GW 20 520	1P NO+NO - 10A	With interlock	Double circles	1	15/30
GW 20 521	1P NO+NO - 10A	With interlock	UP - DOWN	1	30/60
GW 20 522	1P NO - 10A - Aux. NC	Start	Green	1	30/60
GW 20 523	1P NC - 10A - Aux. NO	Stop	Red	1	30/60
GW 20 517	2P NO - 10A	Neutral	Double circle	1	30/60
GW 20 518	2P NO - 10A	With pull-cord	-	1	20/40
GW 20 530	2P NO - 10A	With key	0/1	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included. GW20520, GW20521, both contacts are open in the central position (OFF).
ACCESSORIES SUPPLIED: GW20515 - red fluorescent 230Vac (0.4W) signalling unit. GW20516 - white LED 12/24Vac/dc (0.4W) signalling unit. GW20518, cord in insulating material, 140cm long, with a knob. GW20530 supplied with 2 keys. Spare keys: GW30912.

Push-buttons with illuminable name-plate - 250V ac



GW 20 024

Code	Description	Lamp voltage	Lamp	Lamp power	No. SYSTEM modules	Pack Carton
GW 20 591	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	2	15/30
GW 20 024	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	3	20/40

CHARACTERISTICS: supplied without lamp.

System - Modular devices



GW 20 589

Wide-button illuminable control devices - 2M - 250V ac

Code	Description	Button key	Type	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 589	1P - 16 AX - illuminable	With diffuser	Switch	200 W	2	15/30
GW 20 580	1P - 16 AX - illuminable	With diffuser	Intermediate switch	200 W	2	1/15
GW 20 527	1P NO - 10 A - illuminable	With diffuser	Push-button	-	2	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.

Blanking modules and outlet



GW 20 056

Blanking modules and cable outlet

Code	Description	No. SYSTEM modules	Pack Carton
GW 20 056	1 module	1	10/480
GW 20 073	2 modules	2	30/60
GW 20 058	1 module with outlet for cable Ø 4 and Ø 8mm	1	60/120

APPLICATIONS: in addition to their normal use, they permit installing signal socket-outlets, microswitches and LEDs after appropriate drilling/preparation.

Lenses with illuminated symbol



Symbols for illuminable switches and push-buttons

Code	Description	Symbol	Pack Carton
Suitable for: General services			
GW 20 533	Neutral	-	20
GW 20 537	Open door	Key	20
GW 20 538	Bell	Bell	20
GW 20 539	Light	Light	20
GW 20 540	Stair light	Stairs	20
GW 20 542	Service	-	20
Suitable for: Technical services			
GW 20 549	Dimmer	-	20
GW 20 550	Ventilation/Extraction	-	20
GW 20 551	Monitor/TV	-	20
GW 20 592	Opening arrows	Opening arrows	20
GW 20 593	Closing arrows	Closing arrows	20
GW 20 594	Off	OFF	20
GW 20 595	On	ON	20
GW 20 596	Up arrow	-	20
GW 20 597	Down arrow	-	20
Suitable for: Numerical services			
GW 20 561	One	1	20
GW 20 562	Two	2	20
GW 20 563	Three	3	20
GW 20 564	Four	4	20
GW 20 565	Five	5	20
GW 20 566	Six	6	20
GW 20 567	Seven	7	20
GW 20 568	Eight	8	20
GW 20 569	Nine	9	20
GW 20 570	Zero	0	20

NOTES: to be used in place of the neutral lens supplied with the illuminable command devices.

Movement detector



GW 20 821

IR movement detector

Code	Supply voltage	Output contacts	No. SYSTEM modules	Pack Carton
GW 20 821	230V ac - 50/60Hz	1NO 3A(AC1) 250V ac	1	1/6

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited. Sensor with fixed lens. Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA. Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through. Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly.

Relay



GW 20 071

Latching relay

Code	No. of poles	Output contacts	Coil	No. SYSTEM modules	Pack Carton
GW 20 071	1	10 AX 250V ac	230V ac - 50 Hz	1	1/5
GW 20 072	2	10 AX 250V ac	230V ac - 50 Hz	1	1/5

CHARACTERISTICS: suitable for commanding incandescent/halogen lamps: 800 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: command of lighting devices from several points, via push-buttons. Start/stop control of motors (extractors, air agitators, etc.).



GW 20 074

Monostable relay

Code	No. of poles	Output contacts	Coil	No. SYSTEM modules	Pack Carton
GW 20 074	1	1 NO/NC 10A(AC1) / 4A(AC15) 250V ac	230V ac - 50 Hz	1	1/5

APPLICATIONS: As an auxiliary element to control special loads, for remote signalling, and for electrical separation between control and user circuits.



GW 20 076

Call relay - 12V

Code	Supply voltage	No. of poles	Output contacts	No. SYSTEM modules	Pack Carton
GW 20 076	12V ac/dc	1	1NO/NC 12 V (max. 1A)	1	1/5

CHARACTERISTICS: reset button integrated on the front and green mains presence indicator lamp.

System - Modular devices

POWER - WHITE VERSION

Socket-outlets - Italian/German standard



GW 20 203

Italian Standard socket-outlets - 250V ac

Code	Description	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 201	2P+E - 10A	P11	Ø 4 mm	1	80/160
GW 20 203	2P+E - 16 A Dual amperage	P17-11	Ø 4 / 5 mm	1	80/320

CHARACTERISTICS: with safety shields.



GW 20 205

Italian/German Standard socket-outlets - 250V ac

Code	Description	Earth pit	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	30/60
GW 20 246	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	30/120

CHARACTERISTICS: with safety shields.



GW 20 291

Italian Standard dual socket-outlet - 250V ac

Code	Description	Type	For plug pins	Input	No. SYSTEM modules	Pack Carton
GW 20 291	2x2P+E 16A Dual amp.	P17-11	Ø 4 / 5 mm	1x16 A	2	30/60

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets - international standard



GW 20 265

German Standard socket-outlet - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 265	2P+E - 16A	Ø 4.8 mm	2	30/120

CHARACTERISTICS: with safety shields.

French standard socket-outlets - 250V ac



GW 20 206

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 206	2P - 16A	Ø 4 / 4.8 mm	2	30/60
GW 20 207	2P+E - 16A	Ø 4 / 4.8 mm	2	30/60

CHARACTERISTICS: with safety shields.

British standard socket-outlets - 250V ac



GW 20 208

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 208	2P+E - 13 A	Flat	2	30/60
GW 20 209	2P+E - 16A	Ø 7 mm	2	30/60

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.

Swiss socket-outlet - 250V ac



GW 20 351

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 351	2P+E - 10A - type 12	Ø 4 mm	1	30/60

NOTES: contact Gewiss customer service to check if the product meets the regulations of the country concerned before purchasing it. The socket is no longer compliant with Swiss standard SEV1011 of 2009.

Euro American standard socket-outlet - 250/125V ac



GW 20 212

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 212	2P+E - 15A	Ø 4 mm/ flat	1	30/60

USA standard socket-outlets - 250/125V ac



GW 20 214

Code	Description	For plug pins	Shape	No. SYSTEM modules	Pack Carton
GW 20 214	2P+E - 15A - 125V ac	Flat parallel horizontal	Parallel horizontal	1	30/60
GW 20 216	2P+E - 15A - 250V ac	Flat	Flat, aligned vertical	1	30/60

System - Modular devices



GW 20 248

Argentinian Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 248	2P+E - 10A	Flat	2	30/60



GW 20 356

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 357	2P+E - 10A	Flat	2	30/60
GW 20 356	2P+E - 15A	Flat	2	30/60



GW 20 220

Israeli Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 220	2P+E - 16A	Round Ø 4 / 4.4 mm	2	40/80

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature lamps, not included.



GW 20 320

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 320	2P - 10 A	Round Ø 4 mm	1	30/60

CHARACTERISTICS: with safety shields.

Socket-outlets for dedicated lines



GW 20 281

Italian standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 295	2P+E - 16 A Dual amperage	Red	P17-11	Ø 4 / 5 mm	1	80/320
GW 20 281	2P+E - 16 A Dual amperage	Green	P17-11	Ø 4 / 5 mm	1	30/60
GW 20 286	2P+E - 16 A Dual amperage	Orange	P17-11	Ø 4 / 5 mm	1	30/60

CHARACTERISTICS: with safety shields.

Italian/German Standard socket-outlets for dedicated lines - 250V AC




GW 20 282

Code	Description	Earth pit	Colour	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 296	2P+E - 16 A Dual amperage	Side and central	Red	P40	Ø 4 / 4.8 / 5 mm	2	30/60
GW 20 282	2P+E - 16 A Dual amperage	Side and central	Green	P40	Ø 4 / 4.8 / 5 mm	2	15/30
GW 20 287	2P+E - 16 A Dual amperage	Side and central	Orange	P40	Ø 4 / 4.8 / 5 mm	2	15/30

CHARACTERISTICS: with safety shields.

German standard socket-outlets for dedicated lines - 250V ac



GW 20 283

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 297	2P+E - 16A	Red	Ø 4.8 mm	2	15/30
GW 20 283	2P+E - 16A	Green	Ø 4.8 mm	2	15/30
GW 20 288	2P+E - 16A	Orange	Ø 4.8 mm	2	15/30

CHARACTERISTICS: with safety shields.

French Standard socket-outlet for dedicated lines - 250V ac



GW 20 312

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 312	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	15/30

CHARACTERISTICS: with safety shields.

Israeli Standard socket-outlet for dedicated lines - 250V ac



GW 20 298

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 298	2P+E - 16A	Red	Round Ø 4 / 4.4 mm	2	40/80

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature lamps, not included.

Israeli standard socket-outlet for special requirements - 250V ac



GW 20 299

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 299	2P+E - 16A	Blue	Round Ø 4 / 4.4 mm	2	40/80

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature lamps, not included.

DATA - WHITE VERSION

TV-SAT sockets



GW 20 396

Coaxial TV-SAT sockets (5-2400 MHz) class A shielding - F female connector

Code	Description	Type	Attenuation	No. SYSTEM modules	Pack Carton
GW 20 391	Direct	With passage of current	0 dB	1	15/30
GW 20 396	Through wiring	-	5 dB	1	15/30
GW 20 392	Through wiring	-	10 dB	1	15/30
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW20391 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV-SAT 5 dB GW20396 coaxial socket-outlet is defined with conditioned use, it is a special through socket-outlet and as such must be used, with the only difference that the user door (socket-outlet towards the user device) must always be closed with a load of 75 Ohm (TV, VCR, SAT receiver or 75-Ohm termination).



GW 20 386

Coaxial TV sockets (5-2400 MHz) class A shielding - IEC male connector Ø 9.5 mm

Code	Description	Type	Attenuation	No. SYSTEM modules	Pack Carton
GW 20 381	Direct	With passage of current	0 dB	1	15/30
GW 20 386	Through wiring	-	5 dB	1	15/30
GW 20 382	Through wiring	-	10 dB	1	15/30
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW20381 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5 dB GW20386 coaxial socket-outlet is defined with conditioned use, it is a special through socket-outlet and as such must be used, with the only difference that the user door (socket-outlet towards the user device) must always be closed with a load of 75 Ohm (TV, VCR, SAT receiver or 75-Ohm termination).



GW 20 229

Resistive coaxial TV sockets (40-860 MHz) - IEC female connector Ø 9.5mm

Code	Description	Attenuation	No. SYSTEM modules	Pack Carton
GW 20 228	Direct	0 dB	1	30/60
GW 20 229	Branched	20 dB	1	30/60
GW 20 230	Terminated - 75 ohm	20 dB	1	30/60

Items designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area.
Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.

Socket-outlets for auxiliary and signal circuits



GW 20 234

Socket-outlets for SELV auxiliary circuit

Code	Description	For plug pins	Centre distance	No. SYSTEM modules	Pack Carton
GW 20 239	2P - 6A - 24V	Ø 3 mm	12.4 mm	1	15/30
GW 20 234	2P - 6A - 24V polarized	Flat	12.4 mm	1	15/30



GW 20 241

Signal socket-outlet for phonic circuits

Code	Description	No. SYSTEM modules	Pack Carton
GW 20 241	For loudspeaker	1	15/30

Telephone sockets



GW 20 251

RJ11 telephone sockets

Code	Description	Cables type	Connection	No. SYSTEM modules	Pack Carton
GW 20 251	RJ11	Twisted pair	Screw-on terminals	1	15/30

APPLICATIONS: telephone, telefax, modem.



GW 20 235

French Standard telephone socket

Code	Description	Connection	No. SYSTEM modules	Pack Carton
GW 20 235	French 8 contacts	Screw-on terminals	1	15/30



GW 20 272

British Standard telephone socket

Code	Description	Connection	No. SYSTEM modules	Pack Carton
GW 20 272	British 6 contacts	Screw-on terminals	1	15/30

System - Modular devices

Data sockets



GW 20 686

RJ45 sockets

Code	Description	No. pairs	Use category	Cables	Connection	No. SYSTEM modules	Pack Carton
GW 20 271	RJ45	4	5e	UTP	Toolless	1	15/30
GW 20 243	RJ45	4	5e	FTP	Toolless	1	15/30
GW 20 685	RJ45	4	6	UTP	Toolless	1	15/30
GW 20 684	RJ45	4	6	UTP	Toolless	1	1/15
GW 20 686	RJ45	4	6	FTP	Toolless	1	15/30

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e. LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.



GW 20 266

Adapters for housing data connectors

Code	Compatibility	No. SYSTEM modules	Pack Carton
GW 20 266	IBM	1	1/120
GW 20 267	SYSTIMAX COMMSCOPE	1	1/120
GW 20 270	AMP / Keystone Jack	1	1/120

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (ChoruSmart, System and Dahlia) with Keystone Jack coupling.

USB and HDMI couplers



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

USB power supply



GW 20 363

Dual USB chargers for electronic devices

Code	Supply voltage	Output voltage	Max current supplied	Type of port	No. modules	Pack Carton
GW 20 363	100-240 V ac - 50-60 Hz	5V dc	3 A	A+C	1	1/10

CHARACTERISTICS: suitable for recharging a single electronic device (e.g. tablet) or two devices simultaneously (e.g. a tablet and smartphone). The division of the current delivered to the two outputs depends on the state of charge of the connected devices.

Enclosures for conventional networks



GW 20 238

Empty enclosure for housing SUB-D connectors

Code	Description	No. SYSTEM modules	Pack Carton
GW 20 238	SUB-D 9 / 15 / 25 PIN	3	20/40

System - Modular devices

PROTECTION - WHITE VERSION

Miniature circuit breakers



GW 20 431

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA				
GW 20 431	Single pole (1P)	6	1	15/30
GW 20 432	Single pole (1P)	10	1	15/30
GW 20 433	Single pole (1P)	16	1	15/30
GW 20 434	Two-pole (1P+N)	6	1	15/30
GW 20 435	Two-pole (1P+N)	10	1	15/30
GW 20 436	Two-pole (1P+N)	16	1	15/30



GW 20 437

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Idn	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA					
GW 20 437	Two-pole (1P+N)	10 mA	6	2	1/15
GW 20 438	Two-pole (1P+N)	10 mA	10	2	1/15
GW 20 439	Two-pole (1P+N)	10 mA	16	2	1/15
GW 20 448	Two-pole (1P+N)	30 mA	6	2	1/15
GW 20 449	Two-pole (1P+N)	30 mA	10	2	1/15
GW 20 450	Two-pole (1P+N)	30 mA	16	2	1/15



GW 20 454

MCB - Red miniature circuit breakers for dedicated circuits - C characteristic - 230V ac

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA				
GW 20 454	Two-pole (1P+N)	6	1	15/30
GW 20 455	Two-pole (1P+N)	10	1	15/30
GW 20 456	Two-pole (1P+N)	16	1	15/30

Protection devices



GW 20 401

Fuse-holder - 250V ac

Code	Rated current (A)	Fuse type	No. SYSTEM modules	Pack Carton
GW 20 401	16	Ø 6.3 x 32 mm	1	30/60



GW 20 423

Surge protection device - 250V ac

Code	Max.dischargeable energy	Maximum discharge current	No. SYSTEM modules	Pack Carton
GW 20 423	75 J	8 kA (8/20 µs)	1	1/14

APPLICATIONS: protection of electronic equipment (TV - HI-FI - computers, etc.) from overvoltage of atmospheric or manoeuvring origin that may be conveyed by the supply lines.

System - Modular devices

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - WHITE VERSION

Dimmer



GW 20 802

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. SYSTEM modules	Pack Carton
GW 20 802	230V - 50 / 60 Hz	100-500 W	-	1	1/14
GW 20 803	230V - 50 / 60 Hz	100-900 W	40-300 VA	1	1/14
GW 20 811	230V - 50 / 60 Hz	100-500 W	100-500 VA	1	1/14

CHARACTERISTICS: with signalling led orange. GW20811 rotary command with two-way switch.
GW20803 compliance with the EMC requirements is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 20 828

Electronic regulator with button for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. SYSTEM modules	Pack Carton
GW 20 828	230V - 50 / 60 Hz	60-500 W	60-500 VA	1	1/14

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Electronic timers



GW 20 825

Electronic daily/weekly timer, 1-channel

Code	Supply voltage	Output contacts	No. SYSTEM modules	Pack Carton
GW 20 825	230 V ac - 50/60 Hz	1NO/NC 8A(AC1)/4A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.



GW 20 810

Electronic timed button with input for remote control 230V - 50/60Hz

Code	Regulation field	Relay output	No. SYSTEM modules	Pack Carton
GW 20 810	30 s - 15 min	1NO 10A(AC1)/5A(AC15) 250V ac	2	1/4

Temperature control devices

Thermo ICE Wi-Fi thermostat - wall-mounting



GW 16 970 CB

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CB	White	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch commands (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or by remote via specific apps (smartphone and tablet).

APPLICATIONS:

The THERMO ICE Wi-Fi can be used:

- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Electronic summer/winter thermostat with knob adjustment and indicator led - 230V - 50/60Hz



GW 20 852

Code	Temperature adjustment	Output contacts	No. SYSTEM modules	Pack Carton
GW 20 852	From +5°C to +30°C	1 NO / NC 8A(AC1) / 2A(AC15) 250V ac	3	1/2

CHARACTERISTICS: option of controlling night-time reduction via remote control (fixed 4°C).

Electronic summer/winter thermostat with knob adjustment for fan-coil, 3-speed selector and solenoid valve command 230V - 50/60HZ



GW 20 853

Code	Regulation field	Output solenoid	Output fan	Output contacts	No. SYSTEM modules	Pack Carton
GW 20 853	+5° C / +30° C	Relay NO/NC	Three way switch 1P	5A (AC1) / 2A (AC15)	3	1/2

CHARACTERISTICS: temperature adjustment range: from +5°C to +30°C.

Operating modes: solenoid valve thermostat and fixed ventilation, solenoid valve and thermostat-controlled ventilation, only thermostat-controlled ventilation and unconnected solenoid valve.

System - Modular devices

SIGNALLING - WHITE VERSION

Anti black-out lamps



GW 20 833

Extractable anti black-out lamp

Code	Supply voltage	Power supply batteries	Autonomy	Type of lamp	No. SYSTEM modules	Pack Carton
GW 20 833	230 V ac - 50/60 Hz	Ni-Mh	2 h	White LED	2	1/4

CHARACTERISTICS: equipped with inhibition selector on the front. Replaceable batteries (battery pack 4.8 V 40 mAh).

APPLICATION: according to CEI 64-8 (chapter 37).



GW 20 835

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. SYSTEM modules	Pack Carton
GW 20 835	230 V ac - 50/60 Hz	Ni-Mh	1 h	White LED	1	1/14

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.

Acoustic signalling devices

Bells



GW 20 613

Code	Supply voltage	Power input	Sound intensity	No. SYSTEM modules	Pack Carton
GW 20 613	12 V - 50 Hz	8 VA	80 dB (at 1 m)	1	15/30
GW 20 616	230V ac - 50Hz	8 VA	80 dB (at 1 m)	1	15/30

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Buzzers



GW 20 617

Code	Supply voltage	Power input	Sound intensity	No. SYSTEM modules	Pack Carton
GW 20 617	12V ac - 50 Hz	8 VA	75 dB (at 1 m)	1	15/30
GW 20 620	230V ac - 50Hz	8 VA	75 dB (at 1 m)	1	15/30

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Indicator light devices

Single indicator lamps - 12/24/250V ac



GW 20 603

Code	Diffuser colour	Diffuser meaning	Fixing for lamp	No. SYSTEM modules	Pack Carton
Diffusor type: Flat					
GW 20 603	Red	Danger	Cartridge	1	30/60
GW 20 604	Green	Safety	Cartridge	1	30/60
GW 20 605	Yellow	Attention	Cartridge	1	30/60
GW 20 606	Transparent	Neutral	Cartridge	1	30/60
GW 20 631	Light blue	Specific	Cartridge	1	30/60

CHARACTERISTICS: supplied without lamp. They use S6x31 mm and S6.3x28 mm cartridge lamps (max 2 W).
NOTES: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.

Double indicator lamps



GW 20 608

Code	Diffuser colour	Lamp voltage	No. SYSTEM modules	Pack Carton
Diffusor type: Flat				
GW 20 607	Red/green	230V ac	1	15/30
GW 20 608	Light blue	12-24V ac/dc	1	15/30

ACCESSORIES SUPPLIED: supplied with LED lamps.

System - Modular devices



GW 20 634

Stair riser lamp with white LED light - 12/230V ac

Code	Diffuser colour	Lamp	Lamp voltage	No. SYSTEM modules	Pack Carton
GW 20 634	White	Integrated LED	12V ac/dc - 230V ac	2	1/15

CHARACTERISTICS: very bright LED, light adjustment eyelid, 12v ac/dc - 230V ac supply with double supply input.




GW 20 601

Stair riser or special uses lamps with flat diffuser - 12/24V

Code	Diffuser colour	Fixing for lamp	No. SYSTEM modules	Pack Carton
GW 20 601	Opal diffuser	Cartridge lamp S6x36 mm	3	15/30
GW 20 623	Red	Cartridge lamp S6x36 mm	3	15/30
GW 20 626	Light blue	Cartridge lamp S6x36 mm	3	15/30

CHARACTERISTICS: Supplied without lamp. Use cartridge lamps of the S6x36mm type (max 2W).
APPLICATIONS: identification of steps, obstacles etc.



GW 20 602

Stair riser or special uses lamps with protruding diffuser - 12/24V

Code	Diffuser colour	Fixing for lamp	No. SYSTEM modules	Pack Carton
GW 20 602	Opal diffuser	Cartridge lamp S6x36 mm	3	1/12
GW 20 627	Red	Cartridge lamp S6x36 mm	3	1/12
GW 20 628	Green	Cartridge lamp S6x36 mm	3	1/12

CHARACTERISTICS: Supplied without lamp. Use cartridge lamps of the S6x36mm type (max 2W).
APPLICATIONS: signalling.



GW 20 622

Lamp holder

Code	Lampholder type	Power	Colour	No. SYSTEM modules	Pack Carton
GW 20 622	E27	40 W	Black	2	15/30

APPLICATIONS: the product must be installed in compliance with the International CE regulation64-8.

TECHNICAL ALARMS - WHITE VERSION

Anti-flood system with ZigBee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

SPECIAL APPLICATIONS - WHITE VERSION

Components for hotel systems



GW 20 651

Three-way switch 1P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 651	1P - 10AX	Neutral	DND+MUR	100 W	1	30/60

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF). With "Do not disturb" (DND) and "Make up the room" (MUR) pad printings.



GW 20 656

Double indicator lamp

Code	Diffuser colour	Symbol	Lamp voltage	No. SYSTEM modules	Pack Carton
GW 20 656	Opal diffuser	DND+MUR	230 V ac	1	15/30

CHARACTERISTICS: supplied with LED lamps (red for DND signalling, green for MUR signalling).



GW 20 820

Universal badge switch with backlit light - 250V ac

Code	Description	For badge card max. width	Type	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 20 820	1P NO - 10A	54 mm	Backlit 230V ac	100 W	3	1/2

CHARACTERISTICS: supplied without badge.
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted).



GW 20 841

European/American standard shaver socket with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. SYSTEM modules	Pack Carton
GW 20 841	230V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120 - 230V ac	20 VA	3	1/4

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading. The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug. The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting containers of the 27 COMBI range.

Spare parts and accessories



Miniature lamps with quick coupling terminals

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 30 943	230 V ac	0.4 W	Fluorescent	Red	50
GW 30 944	230V ac	0.4 W	Fluorescent	Green	50
GW 30 946	110 / 230V ac	0.6 W	LED	Light blue	50
GW 30 947	110 / 230V ac	0.6 W	LED	White	50
GW 10 893	12-24V ac/dc	0.4 W	LED	White	50

APPLICATIONS: miniature lamps are mounted on all control devices fitted for luminous signalling.



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps

Code	Dimensions (mm)	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 20 902	S6x36	12V ac/dc	2 W	Incandescence	White	50
GW 20 903	S6x36	24V ac/dc	2 W	Incandescence	White	50
GW 20 904	S6x31	12V ac/dc	2 W	Incandescence	White	50
GW 20 905	S6x31	24V ac/dc	2 W	Incandescence	White	50
GW 20 906	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Red	50
GW 20 908	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Green	50

NOTES: the cartridge lamps are mounted on the stair riser, on the single indicator lamps and on the push-buttons with a name plate.

System - Modular devices



GW 20 911

Miniature fuses - 250V ac

Code	Dimensions (mm)	Rated current (A)	Rated voltage	Pack Carton
GW 20 911	Ø 5 x 20	2.5	250V ac	20/200
GW 20 921	Ø 6.3 x 32	2	250V ac	10/200
GW 20 922	Ø 6.3 x 32	4	250V ac	10/200
GW 20 923	Ø 6.3 x 32	6	250V ac	10/200
GW 20 924	Ø 6.3 x 32	10	250V ac	10/200
GW 20 925	Ø 6.3 x 32	16	250V ac	10/200



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




System



Scan the QR Code and find out all the technical informations.

TWO LINES, ONE SINGLE OFFER



The System range includes two lines of plates, one more rounded and the other with a squarer design, in a domestic series recognised for its reliability and robustness.

INSTALLATION FLEXIBILITY



The domestic System series offers maximum application flexibility. It is highly versatile, with two attachment options, from the front or back of the support, making the mounting and release of devices quick and easy.

A COMPLETE SOLUTION



The System devices are compatible with a wide range of accessories and can be installed in any electrical installation: flush- and surface-mounted rectangular boxes, flush-mounted square boxes, profiles and DIN rails, floor turrets and 27 Combi enclosures.

System

Command - black

One-way switches


GW 21 571
1M-1P-16 AX


GW 21 572
1M-1P-16 AX
Backlit 230 V ac


GW 21 583
1M-1P-16 AX
Illuminable (*)


GW 21 503
1M-2P-16 AX


GW 21 504
1M-2P-16 AX
Backlit 230 V ac


GW 21 584
1M-2P-16 AX
Illuminable (*)


GW 21 005
1M-2P-10 AX
With key


GW 21 585
1M-2P-25 AX
Heavy-duty loads

Two-way switches


GW 21 576
1M-1P-16 AX


GW 21 577
1M-1P-16 AX
Backlit 230 V ac


GW 21 588
1M-1P-16 AX
Illuminable (*)


GW 21 008
1M-1P-10 AX
With key


GW 21 589
2M-1P-16 AX
Illuminable (*)

Intermediate switches


GW 21 579
1M-1P-16 AX


GW 21 580
2M-1P-16 AX
Illuminable (*)

Push-buttons


GW 21 510
1M-1P-NO-10 A


GW 21 515
Backlit 230 V ac
GW 21 516
Backlit 12/24 V


GW 21 529
1M-1P-NO-10 A
Illuminable (*)


GW 21 531
1M-1P-NC-10 A
Illuminable (*)


GW 21 511
1M-1P-NO-10 A
Key


GW 21 512
1M-1P-NO-10 A
Bell


GW 21 513
1M-1P-NO-10 A
Light


GW 21 514
1M-1P-NO-10 A
Light scale


GW 21 530
1M-2P-NO-10 A
With key


GW 21 522
1M-1P-NO+NC-10 A
Start


GW 21 523
1M-1P-NC+NO-10 A
Stop


GW 21 520
1M-1P-NO+NO-10 A
With interlock


GW 21 521
1M-1P-NO+NO-10 A
With interlock


GW 21 519
1M-1P-NC-10 A


GW 21 517
1M-2P-NO-10 A


GW 21 591
2M-1P-NO-10 A
With illuminated name plate (*)


GW 21 024
3M-1P-NO-10 A
With illuminated name plate (*)


GW 21 527
2M-1P-NO-10 A
Illuminable (*)


GW 21 518
1M-2P-NO-10 A
With pull-cord

Three-way switches


GW 21 559
1M-1P-10 AX
Positions 1-0-2


GW 21 528
1M-1P-10 AX
Positions 1-0-2

Miniature lamp



GW 10 893	12/24 V ac/dc	White
GW 30 943	230 V ac	Red
GW 30 944	230 V ac	Green
GW 30 946	110/230 V ac	Light blue
GW 30 947	110/230 V ac	White

Cartridge lamp



GW 20 902 S6x36	12 V ac/dc	White
GW 20 903 S6x36	24 V ac/dc	White
GW 20 904 S6x31	12 V ac/dc	White
GW 20 905 S6x31	24 V ac/dc	White
GW 20 906 S6,3x28	110/230 V ac	Red
GW 20 908 S6,3x28	110/230 V ac	Green

Lenses with illuminated symbol

GW 20 533
Neutral


GW 20 537


GW 20 538


GW 20 539


GW 20 549


GW 20 550


GW 20 551


GW 20 595


GW 20 561


GW 20 562


GW 20 563


GW 20 564


GW 20 565


GW 20 540


GW 20 542

General services


GW 20 592


GW 20 593


GW 20 596


GW 20 597

Technical services


GW 20 594


GW 20 566


GW 20 567


GW 20 568


GW 20 569


GW 20 570

Numerical services

Infrarossi


GW 21 821
Movement sensor
1M-1NO-3 A

Relè


GW 21 071
Latching
1M-1P-10 A-250 V ac


GW 21 072
Latching
1M-2P-10 A-250 V ac


GW 21 074
Monostable
1M-1P-10 A-250 V ac-1NO/NC


GW 21 076
Call
1M-1P-NO/NC-12 V ac/dc

Blanking modules and cable output


GW 21 056
1M


GW 21 073
2M


GW 21 058
1M
Cable output

(*) supplied without LED signalling unit

Power - black

Italian


GW 21 201
2P+E-10 A-250 V ac


GW 21 203
2P+E-16 A-250 V ac
Dual amperage


GW 20 295
2P+E-16 A-250 V ac
Dual amperage


GW 20 281
2P+E-16 A-250 V ac
Dual amperage


GW 20 286
2P+E-16 A-250 V ac
Dual amperage


GW 21 291
2x2P+E-16 A-250 V ac
Dual amperage

Italian/German


GW 21 205
2P+E-16 A-250 V ac


GW 21 246
2P+E-16 A-250 V ac
Dual amperage


GW 20 296
2P+E-16 A-250 V ac
Dual amperage


GW 20 282
2P+E-16 A-250 V ac
Dual amperage



GW 20 287
2P+E-16 A-250 V ac
Dual amperage


Swiss


GW 21 351
2P+E-10 A-250 V ac
Type 12

German


GW 21 265
2P+E-16 A-250 V ac


GW 20 297
2P+E-16 A-250 V ac


GW 20 283
2P+E-16 A-250 V ac


GW 20 288
2P+E-16 A-250 V ac

French


GW 21 206
2P-16 A-250 V ac


GW 21 207
2P+E-16 A-250 V ac


GW 20 312
2P+E-16 A-250 V ac

British


GW 21 208
2P+E-13 A-250 V ac


GW 21 209
2P+E-16 A-250 V ac

Australian



GW 21 357
2P+E-10 A-250 V ac



GW 21 356
2P+E-15 A-250 V ac

Euro-american/USA


GW 21 212
2P+E-10/15 A-250/125 V ac


GW 21 214
2P+E-15 A-125 V ac


GW 21 216
2P+E-15 A-250 V ac

Argentinian


GW 21 248
2P+E-10 A-250 V ac

Israeli


GW 21 220
2P+E-16 A-250 V ac


GW 20 298
2P+E-16 A-250 V ac
Illuminable (*)


GW 20 299
2P+E-16 A-250 V ac
Illuminable (*)

Special sockets


GW 21 239
SELV
2P-6 A-24 V


GW 21 234
SELV
2P-6 A-24 V
Polarised


GW 21 241
For loudspeaker

(*) supplied without LED signalling unit

System

Data - black

TV-SAT



F female
GW 21 391 - 0 dB
GW 21 396 - 5 dB
GW 21 392 - 10 dB



IEC male
GW 21 381 - 0 dB
GW 21 386 - 5 dB
GW 21 382 - 10 dB



IEC female
GW 21 228 - 0 dB ▲
GW 21 229 - 20 dB ▲
GW 21 230 - Term. 20 dB ▲



GW 20 277
Terminal resistance 75 ohm

Telephone sockets



GW 21 251
RJ11



GW 21 235
French 8 contacts



GW 21 272
British 6 contacts

Data sockets



GW 21 685 Cat. 6
GW 21 684 Cat. 6
GW 21 271 Cat. 5e
RJ45 - UTP



GW 21 686 Cat. 6
GW 21 243 Cat. 5e
RJ45 - FTP



GW 21 266 IBM
GW 21 267 SYSTIMAX Commscope
GW 21 270 AMP/Keystone Jack
Adapters



GW 21 238
Unwired enclosure for SUB-D 9/15/25 PIN

USB and HDMI couplers



GW 38 056
HDMI coupler



GW 38 057
USB coupler

Power, comfort and climate management - black

Dimmer



GW 21 802
Resistive 100-500 W
230 V ac-50/60 Hz



GW 21 811
Resistive 100-500 W
Inductive 100-500 VA
With two-way switch
230 V ac-50/60 Hz



▲ GW 21 803
Resistive 100-900 W
Inductive 40-300 VA
230 V ac-50/60 Hz



GW 21 828
Resistive 60-500 W
Inductive 60-500 VA
230 V ac-50/60 Hz



GW 21 829
For electronic transformers
230 V ac-50/60 Hz

Electronic timer



GW 21 825
230 V ac-50/60 Hz
Daily/Weekly

Timer



GW 21 810
2M

Thermoregulation



GW 21 852
Thermostat
230 V ac-50/60 Hz



GW 16 970 CN
Thermostat/Chronothermostat
Thermo ICE WiFi
110-230 V ac-50/60 Hz
Wall-mounting

Automatic circuit breakers



Miniature circuit breakers
3 kA
C characteristic

GW 21 431 - 6 A
GW 21 432 - 10 A
GW 21 433 - 16 A
1P

GW 21 434 - 6 A
GW 21 435 - 10 A
GW 21 436 - 16 A
1P+N

GW 20 454 - 6 A
GW 20 455 - 10 A
GW 20 456 - 16 A
1P+N colour red



Residual miniature circuit breakers
3 kA
C characteristic

GW 21 437 - 6 A
GW 21 438 - 10 A
GW 21 439 - 16 A
1P+N-10 mA

GW 21 448 - 6 A
GW 21 449 - 10 A
GW 21 450 - 16 A
1P+N-30 mA

Protection devices



GW 21 423
Surge protection device



GW 21 401
Fuse-holder
In MAX=16 A

▲ Articles designed exclusively for export to a limited number of Countries not belonging to the EU (or candidates for membership) or the European Free Trade Association. Check with Gewiss Customer Service to make sure the product meets the regulation of the Country in question before importing it.

(*) supplied without signalling unit

Hotel components - black

Badge switch



GW 21 820
1P-NO-10 A
Backlit 230 V ac

Shaver socket-outlet



GW 21 841
230 V ac-50/60 Hz

Climate control



GW 21 853
Thermostat for fan-coil
230 V ac-50/60 Hz

Indicator and technical alarms - black

Anti black-out lamps



GW 21 833
230 V ac-50/60 Hz
Removable



GW 21 835
230 V ac-50/60 Hz

Ringers and buzzers



GW 21 613- 12 V ac
GW 21 616- 230 V ac
Ringers



GW 21 617- 12 V ac
GW 21 620- 230 V ac
Buzzers

Indicator lamps



- GW 21 603
- GW 21 604
- GW 21 605
- GW 21 606
- GW 21 631

Flat diffuser
Illuminable (*)



GW 21 607- 230 V ac
GW 21 608- 12/24 V ac/dc

Flat diffuser complete
with lamp



GW 21 634
Stair riser lamp
2M



- GW 20 601
- GW 20 623
- GW 20 625
- GW 20 626

Flat diffuser 12/24 V ac/dc



- GW 20 602
- GW 20 627
- GW 20 629
- GW 20 628

Protruding diffuser 12/24 V ac/dc



GW 20 622
Lamp-holder E27

Detectors



GW A1 514
Flood alarm ZigBee



GW A1 521
1-channel actuator ZigBee
230 V ac-50 Hz


GW A1 541
Wall-mounting support for
flood alarm



GW 30 522
GAS solenoid valve
3/4"-230 V ac-12 VA

Supports

Supports for square and rectangular boxes



GW 24 262 With screws - 2 modules


Supports for rectangular boxes



GW 24 201
With screws - 3 modules



GW 24 202
With screws - 4 modules



GW 24 230
With screws - 6 modules



GW 24 240
With screws - 4+4 modules



GW 24 241
With screws - 6+6 modules

(*) supplied without signalling unit

System

Black modular devices



The System modular devices allow the creation of infinite combinations of devices and plates, through a complete range that covers all design, functional and installation needs. Colours and finishes: satin black, elegant and classy. Ideal for flush-mounted solutions (for rectangular or square boxes), surface-mounted solutions and special applications. The range includes control units, socket-outlets, breakers, indicators, connectors and devices for the control, safety and comfort of your home.

COMMAND - BLACK VERSION

Command devices



GW 21 571

One-way switches - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 571	1P - 16AX	Neutral	-	200 W	1	80/320
GW 21 572	1P - 16 AX backlit	With replaceable neutral lens	-	200 W	1	30/60
GW 21 583	1P - 16AX illuminable	With replaceable neutral lens	-	200 W	1	30/60
GW 21 503	2P - 16 AX	Neutral	0/1	200 W	1	30/60
GW 21 504	2P - 16 AX backlit	With replaceable neutral lens	-	200 W	1	30/60
GW 21 584	2P - 16AX illuminable	With replaceable neutral lens	-	200 W	1	30/60
GW 21 005	2P - 10AX	With key	0/1	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.
ACCESSORIES SUPPLIED: GW21572, GW21504 - red fluorescent 230Vac (0.4W) signalling unit. GW21005 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 21 585

One-way switch 2P for heavy-duty installations - 25A - 250V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 585	25 AX	Neutral	0/1	250 W	1	15/30

CHARACTERISTICS: suitable for particular heavy-duty loads (e.g. set of fluorescent lamp) or high consumption devices (ovens, air-conditioners, boilers, etc.).



GW 21 576

Two-way switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 576	1P - 16AX	Neutral	200 W	1	80/320
GW 21 577	1P - 16 AX backlit	With replaceable neutral lens	200 W	1	30/60
GW 21 588	1P - 16AX illuminable	With replaceable neutral lens	200 W	1	30/60
GW 21 008	1P - 10AX	With key	100 W	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.
ACCESSORIES SUPPLIED: GW21577 - red fluorescent 230Vac (0.4W) signalling unit. GW21008 supplied with 2 keys. The key can be extracted in both positions. Spare keys: GW20901.



GW 21 579

Intermediate switches 1P - 250V ac

Code	Description	Button key	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 579	1P - 16AX	Neutral	200 W	1	30/60

Three-way switch 1P - 250V ac



GW 21 559

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 559	1P - 10AX	Neutral	UP - DOWN	100 W	1	30/60
GW 21 528	1P - 10AX	With replaceable neutral lens	-	100 W	1	30/60

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).
GW21528 - not-illuminated product; equipped with neutral lens.
APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.

Push-buttons - 250V ac



GW 21 510

Code	Description	Button key	Symbol	No. SYSTEM modules	Pack Carton
GW 21 510	1P NO - 10A	Neutral	-	1	80/160
GW 21 511	1P NO - 10A	With symbol	Key	1	15/30
GW 21 512	1P NO - 10A	With symbol	Bell	1	15/30
GW 21 513	1P NO - 10A	With symbol	Light	1	15/30
GW 21 514	1P NO - 10A	With symbol	Stair light	1	15/30
GW 21 515	1P NO - 10 A backlit	With replaceable neutral lens	-	1	30/60
GW 21 516	1P NO - 10 A backlit	With replaceable neutral lens	-	1	30/60
GW 21 529	1P NO - 10A illuminable	With replaceable neutral lens	-	1	30/60
GW 21 531	1P NC - 10 A illuminable	With replaceable neutral lens	-	1	15/30
GW 21 519	1P NC - 10A	Neutral	Circle	1	15/30
GW 21 520	1P NO+NO - 10A	With interlock	Double circles	1	15/30
GW 21 521	1P NO+NO - 10A	With interlock	UP - DOWN	1	30/60
GW 21 522	1P NO - 10A - Aux. NC	Start	Green	1	30/60
GW 21 523	1P NC - 10A - Aux. NO	Stop	Red	1	30/60
GW 21 517	2P NO - 10A	Neutral	Double circle	1	30/60
GW 21 518	2P NO - 10A	With pull-cord	-	1	20/40
GW 21 530	2P NO - 10A	With key	0/1	1	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included; GW21520, GW21521, both contacts are open in the central position (OFF).
ACCESSORIES SUPPLIED: GW21515 - red fluorescent 230Vac (0.4W) signalling unit. GW21516 - white LED 12/24Vac/dc (0.4W) signalling unit. GW21518, cord in insulating material, 140cm long, with a knob. GW21530 supplied with 2 keys. Spare keys: GW30912.

Push-button with illuminable name plate - 250V ac



GW 21 024

Code	Description	Lamp voltage	Lamp	Lamp power	No. SYSTEM modules	Pack Carton
GW 21 591	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	2	15/30
GW 21 024	1P NO - 10A	12-24V ac/dc	Cartridge lamp S6x36 mm	2 W	3	20/40

CHARACTERISTICS: supplied without lamp.

Wide-button illuminable control devices - 2M - 250V ac



GW 21 589

Code	Description	Button key	Type	Rated power of 230V LED lamps	No. SYSTEM modules	Pack Carton
GW 21 589	1P - 16 AX - illuminable	With diffuser	Switch	200 W	2	15/30
GW 21 580	1P - 16 AX - illuminable	With diffuser	Intermediate switch	200 W	2	1/15
GW 21 527	1P NO - 10 A - illuminable	With diffuser	Push-button	-	2	15/30

CHARACTERISTICS: the illuminable articles use miniature lamp units, not included.

System - Modular devices

Blanking modules and cable outlet



GW 21 056

Blanking modules and cable outlet

Code	Description	No. SYSTEM modules	Pack Carton
GW 21 056	1 module	1	10/480
GW 21 073	2 modules	2	30/60
GW 21 058	1 module with outlet for cable Ø 4 and Ø 8mm	1	60/120

APPLICATIONS: in addition to their normal use, they permit installing signal socket-outlets, microswitches and LEDs after appropriate drilling/preparation.

Lenses with illuminated symbol



Symbols for illuminable switches and push-buttons

Code	Description	Symbol	Pack Carton
Suitable for: General services			
GW 20 533	Neutral	-	20
GW 20 537	Open door	Key	20
GW 20 538	Bell	Bell	20
GW 20 539	Light	Light	20
GW 20 540	Stair light	Stairs	20
GW 20 542	Service	-	20
Suitable for: Technical services			
GW 20 549	Dimmer	-	20
GW 20 550	Ventilation/Extraction	-	20
GW 20 551	Monitor/TV	-	20
GW 20 592	Opening arrows	Opening arrows	20
GW 20 593	Closing arrows	Closing arrows	20
GW 20 594	Off	OFF	20
GW 20 595	On	ON	20
GW 20 596	Up arrow	-	20
GW 20 597	Down arrow	-	20
Suitable for: Numerical services			
GW 20 561	One	1	20
GW 20 562	Two	2	20
GW 20 563	Three	3	20
GW 20 564	Four	4	20
GW 20 565	Five	5	20
GW 20 566	Six	6	20
GW 20 567	Seven	7	20
GW 20 568	Eight	8	20
GW 20 569	Nine	9	20
GW 20 570	Zero	0	20

NOTES: to be used in place of the neutral lens supplied with the illuminable command devices.

Movement sensor



GW 21 821

IR movement detector

Code	Supply voltage	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 821	230V ac - 50/60Hz	1NO 3A(AC1) 250V ac	1	1/6

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited. Sensor with fixed lens. Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA. Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.

APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.

Comfort and safety: automatic command of circuits without needing to activate one-way switches.

NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly.

Relay

Latching relay



GW 21 071

Code	No. of poles	Output contacts	Coil	No. SYSTEM modules	Pack Carton
GW 21 071	1	10 AX 250V ac	230V ac - 50 Hz	1	1/5
GW 21 072	2	10 AX 250V ac	230V ac - 50 Hz	1	1/5

CHARACTERISTICS: suitable for commanding incandescent/halogen lamps: 800 W, fluorescent tubes with electronic ballast: 400 W, fluorescent tubes with electromechanical ballast: 360 W, compact fluorescent lamps (CFL): 200 W, LED lamps (230V ac): 200 W, low voltage halogen or LED lamps with electronic ballast: 200 W, low voltage halogen or LED lamps with electromechanical ballast: 400 W.
APPLICATIONS: command of lighting devices from several points, via push-buttons. Start/stop control of motors (extractors, air agitators, etc.).

Monostable relay 230 V ac



GW 21 074

Code	No. of poles	Output contacts	Coil	No. SYSTEM modules	Pack Carton
GW 21 074	1	1 NO/NC 10A(AC1) / 4A(AC15) 250V ac	230V ac - 50 Hz	1	1/5

APPLICATIONS: As an auxiliary element to control special loads, for remote signalling, and for electrical separation between control and user circuits.

Call relay - 12V



GW 21 076

Code	Supply voltage	No. of poles	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 076	12V ac/dc	1	1NO/NC 12 V (max. 1A)	1	1/5

CHARACTERISTICS: reset button integrated on the front and green mains presence indicator lamp.

System - Modular devices

POWER - BLACK VERSION

Socket-outlets - Italian/German standard



GW 21 203

Italian standard socket-outlets - 250V ac

Code	Description	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 201	2P+E - 10A	P11	Ø 4 mm	1	80/160
GW 21 203	2P+E - 16 A Dual amperage	P17-11	Ø 4 / 5 mm	1	80/320

CHARACTERISTICS: with safety shields.



GW 21 205

Italian/German standard socket-outlets - 250V ac

Code	Description	Earth pit	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 205	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	30/60
GW 21 246	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	30/120

CHARACTERISTICS: with safety shields.



GW 21 291

Italian standard quick wiring double socket-outlet - 250V ac

Code	Description	Type	For plug pins	Input	No. SYSTEM modules	Pack Carton
GW 21 291	2x2P+E 16A Dual amp.	P17-11	Ø 4 / 5 mm	1x16 A	2	30/60

CHARACTERISTICS: with safety shields. The wiring is carried out via 3 terminals that power the socket-outlets, without using U-bolts.

Socket-outlets - international standard



GW 21 265

German standard socket-outlet - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 265	2P+E - 16A	Ø 4.8 mm	2	30/60

CHARACTERISTICS: with safety shields.



GW 21 206

French standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 206	2P - 16A	Ø 4 / 4.8 mm	2	30/60
GW 21 207	2P+E - 16A	Ø 4 / 4.8 mm	2	30/60

CHARACTERISTICS: with safety shields.



GW 21 208

British standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 208	2P+E - 13 A	Flat	2	30/60
GW 21 209	2P+E - 16A	Ø 7 mm	2	30/60

CHARACTERISTICS: with safety shields.

NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 21 351

Swiss socket-outlet - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 351	2P+E - 10A - type 12	Ø 4 mm	1	30/60

NOTES: contact Gewiss customer service to check if the product meets the regulations of the country concerned before purchasing it. The socket is no longer compliant with Swiss standard SEV1011 of 2009.



GW 21 212

Euro American standard socket-outlet - 250/125V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 212	2P+E - 15A	Ø 4 mm/ flat	1	30/60

System - Modular devices



GW 21 214

USA standard socket-outlets - 250/125V ac

Code	Description	For plug pins	Shape	No. SYSTEM modules	Pack Carton
GW 21 214	2P+E - 15A 125V ac	Flat parallel horizontal	Parallel horizontal	1	30/60
GW 21 216	2P+E - 15A 250V ac	Flat, aligned vertical	Flat, aligned vertical	1	30/60



GW 21 248

Argentinian Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 248	2P+E - 10A	Flat	2	30/60



GW 21 356

Australian standard socket-outlets - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 357	2P+E - 10A	Flat	2	30/60
GW 21 356	2P+E - 15A	Flat	2	30/60



GW 21 220

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. SYSTEM modules	Pack Carton
GW 21 220	2P+E - 16A	Round Ø 4 / 4.4 mm	2	30/60

CHARACTERISTICS: with safety shields.

Socket-outlets for dedicated lines



GW 20 281

Italian standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 295	2P+E - 16 A Dual amperage	Red	P17-11	Ø 4 / 5 mm	1	80/320
GW 20 281	2P+E - 16 A Dual amperage	Green	P17-11	Ø 4 / 5 mm	1	30/60
GW 20 286	2P+E - 16 A Dual amperage	Orange	P17-11	Ø 4 / 5 mm	1	30/60

CHARACTERISTICS: with safety shields.




GW 20 282

Italian/German standard socket-outlets for dedicated lines - 250V ac

Code	Description	Earth pit	Colour	Type	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 296	2P+E - 16 A Dual amperage	Side and central	Red	P40	Ø 4 / 4.8 / 5 mm	2	30/60
GW 20 282	2P+E - 16 A Dual amperage	Side and central	Green	P40	Ø 4 / 4.8 / 5 mm	2	15/30
GW 20 287	2P+E - 16 A Dual amperage	Side and central	Orange	P40	Ø 4 / 4.8 / 5 mm	2	15/30

CHARACTERISTICS: with safety shields.



GW 20 283

German standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 297	2P+E - 16A	Red	Ø 4.8 mm	2	15/30
GW 20 283	2P+E - 16A	Green	Ø 4.8 mm	2	15/30
GW 20 288	2P+E - 16A	Orange	Ø 4.8 mm	2	15/30

CHARACTERISTICS: with safety shields.



GW 20 312

French standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 312	2P+E - 16A	Red	Ø 4 / 4.8 mm	2	15/30

CHARACTERISTICS: with safety shields.

System - Modular devices



GW 20 298

Israeli standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 298	2P+E - 16A	Red	Round Ø 4 / 4.4 mm	2	40/80

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature lamps, not included.



GW 20 299

Israeli standard socket-outlet for special requirements - 250V ac

Code	Description	Colour	For plug pins	No. SYSTEM modules	Pack Carton
GW 20 299	2P+E - 16A	Blue	Round Ø 4 / 4.4 mm	2	40/80

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature lamps, not included.

DATA - BLACK VERSION

TV-SAT sockets



GW 21 391

Coaxial TV-SAT sockets (5-2400 MHz) class A shielding - F female connector

Code	Description	Type	Attenuation	No. SYSTEM modules	Pack Carton
GW 21 391	Direct	With passage of current	0 dB	1	15/30
GW 21 396	Through wiring	-	5 dB	1	15/30
GW 21 392	Through wiring	-	10 dB	1	15/30
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW21391 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.

APPLICATIONS: socket-outlets suitable for return channel.

NOTES: the TV-SAT 5dB GW21396 coaxial socket is defined with conditioned use. It is a special feedthrough socket and must be used as such, with the only difference being that the user port (socket towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 21 381

Coaxial TV sockets (5-2400 MHz) class A shielding - IEC male connector Ø 9.5 mm

Code	Description	Type	Attenuation	No. SYSTEM modules	Pack Carton
GW 21 381	Direct	With passage of current	0 dB	1	15/30
GW 21 386	Through wiring	-	5 dB	1	15/30
GW 21 382	Through wiring	-	10 dB	1	15/30
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW21381 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.

APPLICATIONS: socket-outlets suitable for return channel.

NOTES: the TV 5dB GW21386 coaxial socket is defined with conditioned use. It is a special feedthrough socket and must be used as such, with the only difference being that the user port (socket towards the user device) must always be closed with a 75-Ohm load (TV, VCR, SAT receiver or 75-Ohm termination).



GW 21 228

Coaxial TV resistive sockets (40-860 MHz) IEC female connector Ø 9.5 mm

Code	Description	Attenuation	No. SYSTEM modules	Pack Carton
GW 21 228	Direct	0 dB	1	30/60
GW 21 229	Branched	20 dB	1	30/60
GW 21 230	Terminated - 75 ohm	20 dB	1	30/60

Items designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area.
Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.

Socket-outlets for auxiliary and signal circuits



GW 21 234

Socket-outlets for SELV auxiliary circuits

Code	Description	For plug pins	Centre distance	No. SYSTEM modules	Pack Carton
GW 21 239	2P - 6A - 24V	Ø 3 mm	12.4 mm	1	15/30
GW 21 234	2P - 6A - 24V polarized	Flat	12.4 mm	1	15/30



GW 21 241

Signal socket-outlet for phonic circuits

Code	Description	No. SYSTEM modules	Pack Carton
GW 21 241	For loudspeaker	1	15/30

Telephone sockets



GW 21 251

RJ11 telephone sockets

Code	Description	Cables type	Connection	No. SYSTEM modules	Pack Carton
GW 21 251	RJ11	Twisted pair	Screw-on terminals	1	15/30

APPLICATIONS: telephone, telefax, modem.

System - Modular devices



GW 21 235

French standard telephone socket

Code	Description	Connection	No. SYSTEM modules	Pack Carton
GW 21 235	French 8 contacts	Screw-on terminals	1	15/30



GW 21 272

British standard telephone socket

Code	Description	Connection	No. SYSTEM modules	Pack Carton
GW 21 272	British 6 contacts	Screw-on terminals	1	15/30

Data sockets



GW 21 686

RJ45 sockets

Code	Description	No. pairs	Use category	Cables	Connection	No. SYSTEM modules	Pack Carton
GW 21 271	RJ45	4	5e	UTP	Toolless	1	15/30
GW 21 243	RJ45	4	5e	FTP	Toolless	1	15/30
GW 21 685	RJ45	4	6	UTP	Toolless	1	15/30
GW 21 684	RJ45	4	6	UTP	Toolless	1	1/15
GW 21 686	RJ45	4	6	FTP	Toolless	1	15/30

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e. LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.



GW 21 266

Adapters for housing data connectors

Code	Compatibility	No. SYSTEM modules	Pack Carton
GW 21 266	IBM	1	1/120
GW 21 267	SYSTIMAX COMMSCOPE	1	1/120
GW 21 270	AMP / Keystone Jack	1	1/120

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.

NOTES: for adapters (ChoruSmart, System and Dahlia) with Keystone Jack coupling.

USB and HDMI couplers



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

Enclosures for conventional networks



GW 21 238

Empty enclosure for housing SUB-D connectors

Code	Description	No. SYSTEM modules	Pack Carton
GW 21 238	SUB-D 9 / 15 / 25 PIN	3	20/40

PROTECTION - BLACK VERSION

Miniature circuit breakers



GW 21 431

MCB - Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA				
GW 21 431	Single pole (1P)	6	1	15/30
GW 21 432	Single pole (1P)	10	1	15/30
GW 21 433	Single pole (1P)	16	1	15/30
GW 21 434	Two-pole (1P+N)	6	1	15/30
GW 21 435	Two-pole (1P+N)	10	1	15/30
GW 21 436	Two-pole (1P+N)	16	1	15/30

System - Modular devices



GW 21 437

RCBO - Residual current breakers with overcurrent protection - C characteristic - class A - 230V ac - 50/60 Hz

Code	Description	Idn	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA					
GW 21 437	Two-pole (1P+N)	10 mA	6	2	1/15
GW 21 438	Two-pole (1P+N)	10 mA	10	2	1/15
GW 21 439	Two-pole (1P+N)	10 mA	16	2	1/15
GW 21 448	Two-pole (1P+N)	30 mA	6	2	1/15
GW 21 449	Two-pole (1P+N)	30 mA	10	2	1/15
GW 21 450	Two-pole (1P+N)	30 mA	16	2	1/15



GW 20 454

MCB - Red miniature circuit breakers for dedicated circuits - C characteristic - 230V ac

Code	Description	Rated current (A)	No. SYSTEM modules	Pack Carton
Breaking capacity: 3 kA				
GW 20 454	Two-pole (1P+N)	6	1	15/30
GW 20 455	Two-pole (1P+N)	10	1	15/30
GW 20 456	Two-pole (1P+N)	16	1	15/30

Protection devices



GW 21 401

Fuse-holder - 250V ac

Code	Rated current (A)	Fuse type	No. SYSTEM modules	Pack Carton
GW 21 401	16	Ø 6.3 x 32 mm	1	30/60



GW 21 423

Surge protection device - 250V ac

Code	Max.dischargeable energy	Maximum discharge current	No. SYSTEM modules	Pack Carton
GW 21 423	75 J	8 kA (8/20 µs)	1	1/14

APPLICATIONS: protection of electronic equipment (TV - HI-FI - computers, etc.) from overvoltage of atmospheric or manoeuvring origin that may be conveyed by the supply lines.

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT - BLACK VERSION

Dimmer



GW 21 802

Rotating electronic regulators for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. SYSTEM modules	Pack Carton
GW 21 802	230V - 50 / 60 Hz	100-500 W	-	1	1/14
GW 21 803	230V - 50 / 60 Hz	100-900 W	40-300 VA	1	1/14
GW 21 811	230V - 50 / 60 Hz	100-500 W	100-500 VA	1	1/14

CHARACTERISTICS: with signalling led orange. GW21811 rotary command with two-way switch.
GW21803 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside of the European Union or countries applying to become part of the European Free Trade Area. Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 21 828

Electronic regulator with button for resistive/inductive loads

Code	Supply voltage	Resistive load 230V ac	Inductive load 230V ac	No. SYSTEM modules	Pack Carton
GW 21 828	230V - 50 / 60 Hz	60-500 W	60-500 VA	1	1/14

CHARACTERISTICS: possibility to command and regulate from remote control push-buttons with NO contact. With signalling led orange.
NOTES: to avoid overheating, the side-by-side installation of several products in a single container is not permitted; insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Electronic timers



GW 21 825

Electronic daily/weekly timer, 1-channel

Code	Supply voltage	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 825	230 V ac - 50/60 Hz	1NO/NC 8A(AC1)/4A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.



GW 21 810

Electronic push-button timer with remote control input - 230V - 50/60Hz

Code	Regulation field	Relay output	No. SYSTEM modules	Pack Carton
GW 21 810	30 s - 15 min	1NO 10A(AC1)/5A(AC15) 250V ac	2	1/4

System - Modular devices

Temperature control devices

Thermo ICE wi-fi thermostat - wall-mounting



GW 16 970 CN

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CN	Black	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet).

APPLICATIONS: The THERMO ICE Wi-Fi can be used:

- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm). Plate material: technopolymer.

Summer/winter electronic thermostat with knob adjustment and indicator led - 230V - 50/60Hz



GW 21 852

Code	Temperature adjustment	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 852	From +5°C to +30°C	1 NO / NC 8A(AC1) / 2A(AC15) 250V ac	3	1/2

CHARACTERISTICS: option of controlling night-time reduction via remote control (fixed 4°C).

Summer/winter electronic thermostat for fan-coil, with knob adjustment 3-speed selector and solenoid valve control - 230V - 50/60Hz



GW 21 853

Code	Regulation field	Output solenoid	Output fan	Output contacts	No. SYSTEM modules	Pack Carton
GW 21 853	+5° C / +30° C	Relay NO/NC	Three way switch 1P	5A (AC1) / 2A (AC15)	3	1/2

CHARACTERISTICS: temperature adjustment range: from +5°C to +30°C.
operating modes: solenoid valve thermostat and fixed ventilation, solenoid valve and thermostat-controlled ventilation, only thermostat-controlled ventilation and unconnected solenoid valve.

SIGNALLING - BLACK VERSION

Anti black-out lamps

Extractable anti black-out lamp



GW 21 833

Code	Supply voltage	Power supply batteries	Autonomy	Type of lamp	No. SYSTEM modules	Pack Carton
GW 21 833	230V - 50/60 Hz	Ni-Mh	2 h	White LED	2	1/4

CHARACTERISTICS: equipped with inhibition selector on the front. Replaceable batteries (battery pack 4.8 V 40 mAh).



GW 21 835

Anti black-out lamp

Code	Supply voltage	Power supply batteries	Minimum autonomy	Lamp	No. SYSTEM modules	Pack Carton
GW 21 835	230 V ac - 50/60 Hz	Ni - Mh	1 h	White LED	1	1/14

CHARACTERISTICS: green LED for the presence of mains voltage signalling. Highly efficient, white LED lamp.

Acoustic signalling devices



GW 21 613

Bells

Code	Supply voltage	Power input	Sound intensity	No. SYSTEM modules	Pack Carton
GW 21 613	12 V - 50 Hz	8 VA	80 dB (at 1 m)	1	15/30
GW 21 616	230V ac - 50Hz	8 VA	80 dB (at 1 m)	1	15/30

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).



GW 21 617

Buzzers

Code	Supply voltage	Power input	Sound intensity	No. SYSTEM modules	Pack Carton
GW 21 617	12 V - 50 Hz	8 VA	75 dB (at 1 m)	1	15/30
GW 21 620	230 V - 50 Hz	8 VA	75 dB (at 1 m)	1	15/30

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

Indicator light devices



GW 21 603

Single indicator lamps - 12/24/250V ac

Code	Diffuser colour	Diffuser meaning	Fixing for lamp	No. SYSTEM modules	Pack Carton
Diffusor type: Flat					
GW 21 603	Red	Danger	Cartridge	1	30/60
GW 21 604	Green	Safety	Cartridge	1	30/60
GW 21 605	Yellow	Attention	Cartridge	1	30/60
GW 21 606	Transparent	Neutral	Cartridge	1	30/60
GW 21 631	Light blue	Specific	Cartridge	1	30/60

CHARACTERISTICS: Supplied without lamp. They use S6x31 mm and S6.3x28 mm cartridge lamps (max 2 W).

NOTES: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.

System - Modular devices



GW 21 607

Double indicator lamps

Code	Diffuser colour	Lamp voltage	No. SYSTEM modules	Pack Carton
Diffusor type: Flat				
GW 21 607	Red/green	230V ac	1	15/30
GW 21 608	Light blue	12-24V ac/dc	1	15/30

ACCESSORIES SUPPLIED: supplied with LED lamps.



GW 21 634

Stair riser lamp with white LED light - 12/230V ac

Code	Diffuser colour	Lamp	Lamp voltage	No. SYSTEM modules	Pack Carton
GW 21 634	White	Integrated LED	12V ac/dc - 230V ac	2	1/15

CHARACTERISTICS: very bright LED, light adjustment eyelid, 12v ac/dc - 230V ac supply with double supply input.




GW 20 601

Stair riser or special uses lamps with flat diffuser - 12/24V

Code	Diffuser colour	Fixing for lamp	No. SYSTEM modules	Pack Carton
GW 20 601	Opal diffuser	Cartridge lamp S6x36 mm	3	15/30
GW 20 623	Red	Cartridge lamp S6x36 mm	3	15/30
GW 20 626	Light blue	Cartridge lamp S6x36 mm	3	15/30

CHARACTERISTICS: supplied without lamp. Use cartridge lamps of the S6x36mm type (max 2W).
APPLICATIONS: identification of steps, obstacles etc.



GW 20 602

Stair riser or special uses lamps with protruding diffuser - 12/24V

Code	Diffuser colour	Fixing for lamp	No. SYSTEM modules	Pack Carton
GW 20 602	Opal diffuser	Cartridge lamp S6x36 mm	3	1/12
GW 20 627	Red	Cartridge lamp S6x36 mm	3	1/12
GW 20 628	Green	Cartridge lamp S6x36 mm	3	1/12

CHARACTERISTICS: Supplied without lamp Use cartridge lamps of the S6x36mm type (max 2W).
APPLICATIONS: signalling.



GW 20 622

Lamp holder

Code	Lampholder type	Power	Colour	No. SYSTEM modules	Pack Carton
GW 20 622	E27	40 W	Black	2	15/30

APPLICATIONS: the product must be installed in compliance with IEC 64-8.

TECHNICAL ALARMS - BLACK VERSION

Anti-flood system with ZigBee wireless transmission



GW A1 514

Zigbee flood alarm - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the alarm detects the presence of water and includes a temperature sensor. Powered by CR123-type battery (replaceable).
NOTES: floor-mounting or alternatively wall-mounting possibility through the GWA1541 accessory. To be used in combination with the Zigbee actuator GWA1521 when controlling an electrovalve or a load.



GW A1 521

1-channel actuator Zigbee

Code	Supply voltage	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for activating loads via the potential-free output contact (NO). Suitable for commanding incandescent lamps (230 V ac): 2300W, loads controlled from toroidal transfomers: 450W, loads controlled from electronic transformers: 600W, energy saving lamps (compact fluorescent): 150W, LED lamps (230 V ac): 150W, motors: 500W.
APPLICATIONS: when used with the water sensor, provide the installation of a NO push-button to open the electrovalve manually.
NOTES: installation in flush-mounting boxes, junction boxes, etc.

Accessories



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.



GW 30 522

Solenoid valve, with manual reset, normally open - 230V - 50Hz

Code	Delivery Ø	Material	Power input	Pack Carton
GW 30 522	3/4"	Brass	12 VA	1/2

SPECIAL APPLICATIONS - BLACK VERSION

Components for hotel systems



GW 21 820

Universal badge switch with backlit light - 250V ac

Code	Description	For badge card max. width	Type	Rated power of LED lamps	No. 230V SYSTEM modules	Pack Carton
GW 21 820	1P NO - 10A	54 mm	Backlit 230V ac	100 W	3	1/2

CHARACTERISTICS: supplied without a badge.
APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted).



GW 21 841

Euro-American Standard shaver socket-outlet with insulation transformer

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. SYSTEM modules	Pack Carton
GW 21 841	230V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120 - 230V ac	20 VA	3	1/4

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading. The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug. The relevant indicator LED allows the chosen voltage to be clearly seen.
NOTES: not suitable for installation in wall-mounting containers of the 27 COMBI range.

Spare parts and accessories



Miniature lamps with quick coupling terminals

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 30 943	230 V ac	0.4 W	Fluorescent	Red	50
GW 30 944	230V ac	0.4 W	Fluorescent	Green	50
GW 30 946	110 / 230V ac	0.6 W	LED	Light blue	50
GW 30 947	110 / 230V ac	0.6 W	LED	White	50
GW 10 893	12-24V ac/dc	0.4 W	LED	White	50

APPLICATIONS: miniature lamps are mounted on all control devices fitted for luminous signalling.



GW 10 881

LED signalling units - 230 V ac - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 881	230 V ac - 50/60 Hz	0.6 W	LED	Blue	Blue	50
GW 10 882	230 V ac - 50/60 Hz	0.6 W	LED	White	White	50
GW 10 883	230 V ac - 50/60 Hz	0.6 W	LED	Red	Red	50
GW 10 884	230 V ac - 50/60 Hz	0.6 W	LED	Green	Green	50
GW 10 885	230 V ac - 50/60 Hz	0.6 W	LED	Amber	Orange	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).

System - Modular devices



GW 10 894

LED signalling units - 12-24 V ac/dc - 0.6 W

Code	Lamp voltage	Lamp power	Lamp	Light emitted	Cable Colour	Pack Carton
GW 10 894	12-24V ac/dc	0.6 W	LED	White	White	50

NOTES: the LED signalling units are supplied with power supply cables (length 10 cm).



GW 20 902

Cartridge lamps

Code	Dimensions (mm)	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 20 902	S6x36	12V ac/dc	2 W	Incandescence	White	50
GW 20 903	S6x36	24V ac/dc	2 W	Incandescence	White	50
GW 20 904	S6x31	12V ac/dc	2 W	Incandescence	White	50
GW 20 905	S6x31	24V ac/dc	2 W	Incandescence	White	50
GW 20 906	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Red	50
GW 20 908	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Green	50

NOTES: the cartridge lamps are mounted on the stair riser, on the single indicator lamps and on the push-buttons with a name plate.



GW 20 911

Miniature fuses - 250V ac

Code	Dimensions (mm)	Rated current (A)	Rated voltage	Pack Carton
GW 20 911	Ø 5 x 20	2.5	250V ac	20/200
GW 20 921	Ø 6.3 x 32	2	250V ac	10/200
GW 20 922	Ø 6.3 x 32	4	250V ac	10/200
GW 20 923	Ø 6.3 x 32	6	250V ac	10/200
GW 20 924	Ø 6.3 x 32	10	250V ac	10/200
GW 20 925	Ø 6.3 x 32	16	250V ac	10/200



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100




System



Scan the QR Code and find out all the technical informations.

TWO LINES, ONE SINGLE OFFER



The System range includes two lines of plates, one more rounded and the other with a squarer design, in a domestic series recognised for its reliability and robustness.

INSTALLATION FLEXIBILITY



The domestic System series offers maximum application flexibility. It is highly versatile, with two attachment options, from the front or back of the support, making the mounting and release of devices quick and easy.

A COMPLETE SOLUTION



The System devices are compatible with a wide range of accessories and can be installed in any electrical installation: flush- and surface-mounted rectangular boxes, flush-mounted square boxes, profiles and DIN rails, floor turrets and 27 Combi enclosures.

27 Combi







27 Combi

Wall-mounting
enclosures
and modular
components

p. 1058

27 Combi

COMBI SYSTEM 40 enclosures

IP40



GW 27 001
1 module

GW 27 002
2 modules

GW 27 003
3 modules

GW 27 004
4 modules

GW 27 005
3+3 modules

GW 27 006
4+4 modules

GW 27 007
4+4+4 modules

GW 27 008
4+4+4+4 modules



GW 27 021
2+2 modules

GW 27 022
2+2+2
modules

GW 27 023
4+4 modules

GW 27 024
4+4+4 modules

COMBI-DIN enclosures

IP40



GW 27 071
2+2 modules
2 DIN modules

GW 27 072
2+2+2+2 modules
4 DIN modules

GW 27 073
4+4+4+4 modules
8 DIN modules

Enclosures for mini-trunking used as skirting and framing

IP40



GW 27 603
1 module
White RAL 9010

GW 27 609
2 modules
White RAL 9010

GW 27 615
3 modules
White RAL 9010

GW 27 621
4 modules
White RAL 9010

GW 27 627
4+4 modules
White RAL 9010

GW 27 616
3 modules
Anthracite RAL 7021

GW 27 622
4 modules
Anthracite RAL 7021

GW 27 628
4+4 modules
Anthracite RAL 7021

Enclosures complete with SYSTEM devices

IP40



GW 27 801 One-way switch 1P-16 AX
GW 27 802 One-way switch 2P-16 AX
GW 27 803 Two way-switch 1P-16 AX
GW 27 804 Two way-switch+Two way-switch 1P-16 AX
GW 27 805 Push-button 1P-NO-10 A

GW 27 811 Italian standard socket-outlet 2P+E-16 A
GW 27 812 Italian/German standard socket-outlet 2P+E-16 A
GW 27 813 British standard socket-outlet 2P+E-13 A
GW 27 814 German standard socket-outlet 2P+E-16 A
GW 27 815 French standard socket-outlet 2P+E-16 A

Complete devices

IP40



Buzzers for signalling

GW 26 417 - 24 V ac
GW 26 427 - 230 V ac

IP44



Wall-mounting

GW 26 222 - 2P+E-230 V ac
GW 26 223 - 3P+E-400 V ac



Flush-mounting

GW 26 420 - 2P+E-230 V ac
GW 26 421 - 3P+E-400 V ac

Combi 22 enclosures for Ø 22mm operators

IP66



GW 27 101 - 1 operator
GW 27 111 - 1 operator - yellow lid
GW 27 102 - 2 operators
GW 27 103 - 3 operators
GW 27 104 - 6 operators
GW 27 105 - 12 operators

Empty enclosures



GW 27 201 - 1 operator
GW 27 202 - 1 operator - yellow lid
GW 27 203 - 2 operators
GW 27 204 - 3 operators

Enclosures complete

COMBI SYSTEM 55/65 enclosures

IP55



GW 27 041
1 module



GW 27 042
2 modules



GW 27 043
3 modules



GW 27 044
4 modules



GW 27 051
4+4 modules



GW 27 052
4+4+4 modules

IP55



GW 27 056
3 modules
Pole head



GW 27 057
3 modules
Pole arm

IP65



GW 27 062
2 modules

Watertight covers (for Q-DIN, Q-BOX)

IP55



For application on Q-DIN, junction boxes, PTC, IB range flanged lids, Q-BOX and panels

GW 27 401
2 modules
75x85 mm-IP55
Gray RAL 7035

IP65



For application on Q-DIN, junction boxes, PTC, IB range flanged lids, Q-BOX and panels

GW 27 403
2 modules
75x85 mm-IP65
Grey RAL 7035

Watertight plates (for rectangular flush-rettangolari)

IP55



GW 22 451 - 3 modules
GW 22 461 - 4 modules
Cloud white



GW 22 452 - 3 modules
GW 22 462 - 4 modules
Toner black



GW 22 453 - 3 modules
GW 22 463 - 4 modules
Grey RAL 7035

Enclosures complete with SYSTEM devices

IP55



GW 27 831 One-way switch 1P-16 AX
GW 27 832 One-way switch 2P-16 AX
GW 27 833 Two way switch 1P-16 AX
GW 27 834 Two way switch+Two way switch 1P-16 AX
GW 27 835 Push-button 1P-NO-10 A



GW 27 841 Italian standard socket-outlet 2P+E-16 A
GW 27 842 Italian/German standard socket-outlet 2P+E-16 A
GW 27 843 British standard socket-outlet 2P+E-13 A
GW 27 844 German standard socket-outlet 2P+E-16 A
GW 27 845 French standard socket-outlet 2P+E-16 A



GW 27 836
Push-button
1P-NO-10 A
With illuminated name plate (*)

Complete devices

IP55



- GW 27 415
- GW 27 416
- GW 27 417
- GW 27 418
- GW 27 419

Indicator lamps
230 V ac (*)



- GW 27 421 — 24 V ac
- GW 27 422 — 230 V ac
- GW 27 423 — 24 V ac
- GW 27 424 — 230 V ac

Electronic flashlights (*)



GW 27 431 B
IR motion detector
230 V ac

IP65



GW 27 432
Light sensitive detector
230 V ac

Complementary items

Complementary items



GW 27 402



GW 26 406



GW 44 622



GW 26 407



GW 27 441 Vertical division
GW 27 442 Horizontal division

(*) supplied without LED signalling unit

27 Combi

Wall-mounting enclosures and modular components

A complete, versatile system of modular enclosures, perfectly integrated in the SYSTEM domestic range capable to meet the high protection installation requirements of domestic, commercial and industrial sectors. The 27 COMBI range is available both in the IP40 version and in watertight versions with IP55 and IP65 degree of protection, recommended for all outdoor applications which are subjected to extreme atmospheric conditions.



COMBI SYSTEM 40

Protected enclosures for SYSTEM devices



GW 27 001

Protected empty enclosures for fixed or mobile applications - Grey RAL 7035 - IP40

HF HALOGEN FREE

IP 40

Code	Description	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 001	1 module	1	3 on sides / 1 on the bottom	66x82x55	Halogen free	5/80
GW 27 002	2 modules	1	3 on sides / 1 on the bottom	66x82x55	Halogen free	5/80
GW 27 003	3 modules	1	3 on sides / 1 on the bottom	99x82x55	Halogen free	3/60
GW 27 004	4 modules	-	8 on sides / 1 on the bottom	132x82x55	Halogen free	2/40

CHARACTERISTICS: Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 005

Protected empty enclosures for fixed or mobile applications - Grey RAL 7035 - IP40 Horizontal multiple configurations

HF HALOGEN FREE

IP 40

Code	Description	Configuration	Compartment pre-arrangement	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 005	6 modules	Module 3 x 2	2	8 on sides / 2 on the bottom	198x82x55	Halogen free	1/30
GW 27 006	8 modules	Module 4 x 2	2	10 on sides / 2 on the bottom	231x82x55	Halogen free	1/20
GW 27 007	12 modules	Module 4 x 3	3	16 on sides / 3 on the bottom	330x82x55	Halogen free	1/20
GW 27 008	16 modules	Module 4 x 4	2	18 on sides / 4 on the bottom	429x82x55	Halogen free	1/20

CHARACTERISTICS: customized to be divided into compartments using the special functional dividers. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 021

Protected empty enclosures for fixed or mobile applications - Grey RAL 7035 - IP40 Vertical multiple configurations

HF HALOGEN FREE

IP 40

Code	Description	Configuration	Compartment pre-arrangement	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 021	4 modules	Module 2 x 2	1	8 on sides / 1 on the bottom	82x132x55	Halogen free	2/40
GW 27 022	6 modules	Module 2 x 3	3	8 on sides / 2 on the bottom	82x198x55	Halogen free	1/30
GW 27 023	8 modules	Module 4 x 2	2	10 on sides / 2 on the bottom	132x132x55	Halogen free	1/20
GW 27 024	12 modules	Module 4 x 3	3	12 on sides / 3 on the bottom	132x198x55	Halogen free	1/20

CHARACTERISTICS: customized to be divided into compartments (except for GW27021) using the special functional dividers. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.

Self-supporting boxes for SYSTEM devices

Self-supporting device-holder boxes for mini-trunking for cables single and twin-trunking



GW 27 603

HF HALOGEN FREE

IP 40

Code	Description	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
Colour: White RAL 9010					
GW 27 603	1 module	1 on the bottom	120x82x54	Halogen free	10
GW 27 609	2 modules	1 on the bottom	120x82x54	Halogen free	10

CHARACTERISTICS: fitted for mini-trunking with sizes LxH (mm): 15x15, 20x20, 22x10, 30x10, 30x15, 35x15. Knockout holes removable with tool. Complete insulation can be obtained by using the screwcaps GW44622.

Self-supporting device-holder boxes for mini-trunking and trunking used as skirting and framing



GW 27 615

HF HALOGEN FREE

IP 40

Code	Description	Compartment pre-arrangement	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
Colour: White RAL 9010						
GW 27 615	3 modules	1	1 on the bottom	99x82x54	Halogen free	10
GW 27 621	4 modules	1	1 on the bottom	132x82x54	Halogen free	10
GW 27 627	8 modules	2	2 on the bottom	132x132x54	Halogen free	5
Colour: Anthracite RAL 7021						
GW 27 616	3 modules	1	1 on the bottom	99x82x54	Halogen free	10
GW 27 622	4 modules	1	1 on the bottom	132x82x54	Halogen free	10
GW 27 628	8 modules	2	2 on the bottom	132x132x54	Halogen free	5

CHARACTERISTICS: fitted for mini-trunking with sizes LxH (mm): 15x15, 20x20, 22x10, 30x10, 30x15, 35x15. Knockout holes removable with tool. Complete insulation can be obtained by using the screwcaps GW44622. GW27627 and GW27628 fitted for division into compartments using the special functional dividers.

COMBI SYSTEM 55

Watertight enclosures for SYSTEM devices



GW 27 041

Watertight empty enclosures for fixed or mobile applications - Grey RAL 7035 - IP55

IP 55

Code	Description	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 27 041	1 module	1	3 on sides / 1 on the bottom	66x82x65	5/60
GW 27 042	2 modules	1	3 on sides / 1 on the bottom	66x82x65	5/60
GW 27 043	3 modules	1	3 on sides / 1 on the bottom	99x82x65	2/40
GW 27 044	4 modules	-	8 on sides / 1 on the bottom	132x82x65	3/30

CHARACTERISTICS: Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 051

Watertight empty enclosures for fixed or mobile applications - Grey RAL 7035 - IP55 Vertical multiple configurations

IP 55

Code	Description	Configuration	Compartment pre-arrangement	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 27 051	8 modules	Module 4 x 2	2	10 on sides / 2 on the bottom	132x171x65	1/20
GW 27 052	12 modules	Module 4 x 3	3	12 on sides / 3 on the bottom	132x258x65	1/15

CHARACTERISTICS: customized to be divided into compartments using the special functional dividers. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 056

Watertight garden enclosures for application on pole - Grey RAL 7035 - IP55

IP 55

Code	Description	Fixing	For pole Ø	No. open holes	No. knockouts holes Ø20	Outer dim. LxHxD (mm)	Pack Carton
GW 27 056	3 modules	Pole head	54 - 60 mm	1	-	122x149x85	1/12
GW 27 057	3 modules	Pole arm	54 - 76 mm	1	1	122x164x85	1/12

CHARACTERISTICS: GW27057, complete with 2 holes for screw fixing and 2 slots for fixing with thermoplastic or metal cable ties up to 13mm in height. Knockout holes removable with tool. Enclosures are fit for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: cable gland PG13.5.

COMBI SYSTEM 65

Watertight enclosures for SYSTEM devices



GW 27 062

Empty watertight enclosures for fixed or mobile applications - Solid smoked transparent door - Grey RAL 7035 - IP65

IP 65

Code	Description	No. knockout holes Ø23	Door type	Outer dim. LxHxD (mm)	Pack Carton
GW 27 062	2 modules	4 on sides / 1 on the bottom	Rigid	66x82x65	5/60

CHARACTERISTICS: equipped with a transparent rigid door. Knockout holes removable with tool. Enclosures are fit for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.

COMPLETE COMBI SYSTEM ENCLOSURES AND DEVICES

Protected enclosures complete with SYSTEM devices



GW 27 801

Protected enclosures complete with SYSTEM devices colour Grey RAL 7035 - IP40 - 250V ac

IP 40

Code	Description	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 801	One-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x55	-	5/60
GW 27 802	One-way switch 2P - 16AX	1	3 on sides / 1 on the bottom	66x82x55	-	5/60
GW 27 803	Two-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x55	-	5/60
GW 27 804	2 x Two-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x55	-	5/60
GW 27 805	Push-button 1P NO 10A	1	3 on sides / 1 on the bottom	66x82x55	-	5/60
GW 27 811	S.-outlet 2P+E - 16A Dual amp	1	3 on sides / 1 on the bottom	66x82x55	Italian standard	5/80
GW 27 812	S.-outlet 2P+E - 16A Dual amp	1	3 on sides / 1 on the bottom	66x82x55	Italian/German standard	5/80
GW 27 813	Socket-outlet 2P+E - 13A	1	3 on sides / 1 on the bottom	66x82x55	British Standard	5/80
GW 27 814	Socket-outlet 2P+E - 16A	1	3 on sides / 1 on the bottom	66x82x55	German standard	5/80
GW 27 815	Socket-outlet 2P+E - 16A	1	3 on sides / 1 on the bottom	66x82x55	French standard	5/80

CHARACTERISTICS: Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622. GW27801, GW27802, GW27803, GW27804, rated power of 230V LED lamps: 200W.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.

Watertight enclosures complete with SYSTEM devices



GW 27 832

Watertight enclosures complete with SYSTEM devices Grey RAL 7035 - IP55- 250V ac

IP 55

Code	Description	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 831	One-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x65	-	5/60
GW 27 832	One-way switch 2P - 16AX	1	3 on sides / 1 on the bottom	66x82x65	-	5/60
GW 27 833	Two-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x65	-	5/60
GW 27 834	2 x Two-way switch 1P - 16AX	1	3 on sides / 1 on the bottom	66x82x65	-	5/60
GW 27 835	Push-button 1P NO 10A	1	3 on sides / 1 on the bottom	66x82x65	-	5/60
GW 27 836	Push-button 1P NO 10A	1	3 on sides / 1 on the bottom	99x82x65	Illuminable name plate	2/40
GW 27 841	S.-outlet 2P+E - 16A Dual amp	1	3 on sides / 1 on the bottom	66x82x65	Italian standard	5/60
GW 27 842	S.-outlet 2P+E - 16A Dual amp	1	3 on sides / 1 on the bottom	66x82x65	Italian/German standard	5/60
GW 27 843	Socket-outlet 2P+E - 13A	1	3 on sides / 1 on the bottom	66x82x65	British Standard	5/60
GW 27 844	Socket-outlet 2P+E - 16A	1	3 on sides / 1 on the bottom	66x82x65	German standard	5/60
GW 27 845	Socket-outlet 2P+E - 16A	1	3 on sides / 1 on the bottom	66x82x65	French standard	5/60

CHARACTERISTICS: IP55 with door closed. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622. GW27836 supplied without lamp: S6x36 - 12/24V cartridge lamp required. GW27831, GW27832, GW27833, GW27834, rated power of 230V LED lamps: 200W.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.

Complete devices



GW 26 222

Wall-mounting industrial socket-outlets to IEC 309 standard - colour Grey RAL 7035 - IP44

IP 44

Code	Rated current (A)	No. of poles	Rated voltage	Reference h	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 26 222	16	2P+E	230 V ac	6	1	1 on sides / 1 on the bottom	64x80x97	5/40
GW 26 223	16	3P+E	400V ac	6	1	1 on sides / 1 on the bottom	64x80x97	5/40

rated voltage with alternated current.

CHARACTERISTICS: Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 415

Indicator lamps- max 15W - Grey RAL 7035 - IP55

IP 55

Code	Diffuser colour	Rated voltage	Lampholder type	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 27 415	Red	230 V ac	E14	1	3 on sides / 1 on the bottom	66x82x95	5/40
GW 27 416	Green	230 V ac	E14	1	3 on sides / 1 on the bottom	66x82x95	5/40
GW 27 417	Yellow	230 V ac	E14	1	3 on sides / 1 on the bottom	66x82x95	5/40
GW 27 418	Transparent	230 V ac	E14	1	3 on sides / 1 on the bottom	66x82x95	5/40
GW 27 419	Light blue	230 V ac	E14	1	3 on sides / 1 on the bottom	66x82x95	5/40

Rated voltage with alternated current. Supplied without lamp.

CHARACTERISTICS: Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 27 424

Electronic flashlights- max 25W - Grey RAL 7035 - IP55

IP 55

Code	Diffuser colour	Rated voltage	Flash frequency	Lampholder type	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 27 421	Red	24V ac	1 Hz	E14	1	3 on sides / 1 on the bottom	66x82x95	1/12
GW 27 422	Red	230 V ac	1 Hz	E14	1	3 on sides / 1 on the bottom	66x82x95	1/12
GW 27 423	Yellow	24V ac	1 Hz	E14	1	3 on sides / 1 on the bottom	66x82x95	1/12
GW 27 424	Yellow	230 V ac	1 Hz	E14	1	3 on sides / 1 on the bottom	66x82x95	1/12

Supplied without lamp.

CHARACTERISTICS: knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.



GW 26 417

Buzzers for signalling - Grey RAL 7035 - IP40

IP 40

Code	Rated voltage	Sound intensity	Frequency impulses of sound	N. holes Ø 23 with cable gland	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Pack Carton
GW 26 417	24V ac	70 dB (at 1 m)	1 Hz	1	1 on sides / 1 on the bottom	64x80x59	1/12
GW 26 427	230 V ac	70 dB (at 1 m)	1 Hz	1	1 on sides / 1 on the bottom	64x80x59	1/12

CHARACTERISTICS: knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. GW26417 consumption 60mA.

ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.

Infrared adjustable motion detector 230V - 50 Hz - IP55



GW 27 431 B

IP 55

Code	Range of action	Duration adjustment	Treshold adjustment	Outer dim. LxHxD (mm)	Pack Carton
GW 27 431 B	12 m	10 sec. - 12 min.	3 - 100 lux	72x88x106	1/10

CHARACTERISTICS: horizontal cover range: 240°; rotating angle of the horizontal detection head: ±90°; sensitivity regulation: 3-12m. Incandescent and halogen lamps: max. 2000W, uncompensated fluorescent lamps: max. 480W, compensated fluorescent lamps: max. 200W, dimmable LED lamps 230V ac and dimmable CFL lamps: max. 8 (7÷23W).
ACCESSORIES SUPPLIED: support for installation in corners; cover kit for limiting the detection field.

Light-sensitive detector with relay output 230V - 50/60 Hz - IP65



GW 27 432

IP 65

Code	Treshold adjustment	Output contacts	Outer dim. LxHxD (mm)	Pack Carton
GW 27 432	0 - 200 lux	1NO 16 A (AC1) 250 V ac	55x106x45	1/24

CHARACTERISTICS: halogen and incandescent lamps: 23x100W (2300W); uncompensated fluorescent lamps: 12x58W (700W); compensated fluorescent lamps: 5x58W 35uF (290W); LED and energy saving lamps: max. 7 (7÷15W).
APPLICATIONS: wall or pole mounting.

SPECIAL ENCLOSURES

COMBI-DIN - Protected DIN-SYSTEM combined enclosures

Protected enclosures for combined installation of DIN modular devices and SYSTEM Smoked transparent door - Grey RAL 7035 - IP40



GW 27 071

HF HALOGEN FREE

IP 40

Code	No. DIN modules	No. SYSTEM modules	Configuration	Dispersible power (W)	No. knockout holes Ø23	Outer dim. LxHxD (mm)	Characteristics	Pack Carton
GW 27 071	2	4	Module 2 x 2	13	10 on sides / 2 on the bottom	132x132x95	Halogen free	1/8
GW 27 072	4	8	Module 2 x 4	15	12 on sides / 2 on the bottom	231x132x95	Halogen free	1/6
GW 27 073	8	16	Module 4 x 4	18	18 on sides / 2 on the bottom	429x132x95	Halogen free	1/4

CHARACTERISTICS: customized to be divided into 2 vertical compartments (except for GW27071) using the special functional dividers. Knockout holes removable with tool. Enclosures are customized for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.
ACCESSORIES SUPPLIED: quick entry cable gland for cables with Ø from 4 to 14 mm and conduits Ø 16 and 20 mm.
NOTES: dispersible power calculated according to IEC 60670-24.

COMBI-IN - Flush-mounting flanged components

SYSTEM 2-modules watertight cap - Grey RAL 7035 - IP55




GW 27 401

IP 55

Code	No. SYSTEM modules	Door type	Dimensions LxH (mm)	Pack Carton
GW 27 401	2	With membrane	75x85	3/60

ACCESSORIES SUPPLIED: 4 self-tapping screws. IP55 with door closed.
APPLICATIONS: for Q-DIN boards, junction boxes PTC, flanged lids 66 range, Q-BOX and panels



GW 27 403

SYSTEM 2-modules watertight cap - Solid smoked transparent door - Grey RAL 7035 - IP65

IP 65

Code	No. SYSTEM modules	Door type	Dimensions LxH (mm)	Pack Carton
GW 27 403	2	Rigid IK09	75x85	3/60

ACCESSORIES SUPPLIED: 4 self-tapping screws. IP65 with door closed.
APPLICATIONS: for Q-DIN boards, junction boxes, PTC, flanged lids 66 range, Q-BOX and panels.



GW 22 451

Self-supporting watertight plates for installation on flush-mounting rectangular boxes - IP55

IP 55

Code	Description	Colour Plate	For flush mounting box	Pack Carton
GW 22 451	3 modules	Cloud white	Rectangular 3 modules	30
GW 22 452	3 modules	Black	Rectangular 3 modules	30
GW 22 453	3 modules	Grey RAL 7035	Rectangular 3 modules	30
GW 22 461	4 modules	Cloud white	Rectangular 4 modules	30
GW 22 462	4 modules	Black	Rectangular 4 modules	30
GW 22 463	4 modules	Grey RAL 7035	Rectangular 4 modules	30

CHARACTERISTICS: ergonomic membrane with notches in UV-resistant material. Snap closing system. Opening made easy by wide key.



GW 26 420

Industrial socket-outlets in compliance with IEC 309 - Grey RAL 7035 - IP44

IP 44

Code	Rated current (A)	No. of poles	Rated voltage	Reference h	Outer dim. LxHxD (mm)	Pack Carton
GW 26 420	16	2P+E	230 V ac	6	116x90x45	1/20
GW 26 421	16	3P+E	400V ac	6	116x90x45	1/20

CHARACTERISTICS: for installation on rectangular flush-mounting box GW24403.

COMBI 22 - Enclosures for push buttons, controls and indicators Ø 22 mm



GW 27 101

Empty enclosures for push-buttons, controls and indicators Ø 22 mm - Grey RAL 7035 - IP66

IP 66

Code	No. gangs	Side entries	Top entries	Bottom entries	Outer dim. LxHxD (mm)	Pack Carton
GW 27 101	1	2xØ 23	1xØ 23	1xØ 23	66x82x65	5/60
GW 27 111	1	2xØ 23	1xØ 23	1xØ 23	66x82x65	5/60
GW 27 102	2	6xØ 23	1xØ 23	1xØ 23	132x82x65	2/30
GW 27 103	3	4xØ 23	1xØ 23	1xØ 23	66x171x65	1/20
GW 27 104	6	4xØ 23	3xØ 23	3xØ 23	132x171x65	1/10
GW 27 105	12	4xØ 23	3xØ 23	3xØ 23	264x171x65	1/10

CHARACTERISTICS: degree of protection guaranteed with IP66 operators correctly installed. The hole seat has knockouts for installing operators with any reference. GW27111 with specific yellow lid for assembling emergency push-buttons GW74361, GW74362 and GW74365.
NOTES: the empty containers can be supplied with push-buttons, commands and indicators Ø 22mm and single contacts, type GW74501 and GW74502.



GW 27 202

Enclosures complete with operator - Grey RAL 7035 - IP66

IP 66

Code	No. gangs	Contacts	Operators Ø 22	Outer dim. LxHxD (mm)	Pack Carton
GW 27 201	1	1 NO	General (black)	66x82x65	1/30
GW 27 202	1	1 NO - 1 NC	Emergency (red)	66x82x65	1/30
GW 27 203	2	1 NO - 1 NC	Start (green) Stop (red)	132x82x65	1/10
GW 27 204	3	1 NO - 1 NC	Start, stop, indicator	66x171x65	1/10

CHARACTERISTICS: 3-seat flange. Maximum protrusion of the operator from the container: GW27201, GW27203, GW27204 - 20mm; GW27202 - 25mm. GW27202, yellow lid, mushroom-head push-button with retainer. GW27204, direct supply, BA9S coupling included, max 380V-2 W, lamp not included, operators Ø 22 for run (green), stop (red) and signalling (white). Complete insulation, in accordance with Standard IEC 536.

COMPLEMENTARY ITEMS

Complementary items



GW 27 402

Junction box for combined assembly of modular containers - Grey RAL 7035 - IP55

IP 55

Code	No. knockout holes Ø23	Lid screws	Outer dim. LxHxD (mm)	Pack Carton
GW 27 402	8 on sides / 1 on the bottom	Stainless steel	132x82x55	2/60

CHARACTERISTICS: knockout holes removable with tool. Enclosures are fit for fixing the earth terminal GW26407. Complete insulation can be obtained by using the screwcaps GW44622.



GW 26 406

Waterproof coupler for enclosures, devices and boxes - IP55

IP 55

Code	Mounting hole Ø (mm)	Type of pitch	Pack Carton
GW 26 406	23	PG16	25/250

APPLICATIONS: for the combined assembly of enclosures, junction boxes, etc.



GW 27 441

Functional divider in insulating material for wall-mounting modular enclosures

Code	Suitable for	Pack Carton
GW 27 441	GW27005, GW27006, GW27007, GW27008, GW27022	10/100
GW 27 442	GW27023, GW27024, GW27051, GW27052, GW27072, GW27073, GW27627, GW27628	10/100

APPLICATIONS: circuits with different voltages / Energy-signal division / Division of special circuits.

Functional dividers in metal for modular enclosures for wall-mounting

Code	Suitable for	Pack Carton
GW 27 443	GW27024, GW27627, GW27628	10/100



GW 27 443

Insulating screw cap

Code	Description	Pack Carton
GW 44 622	Screwcap Ø16mm	10/100

APPLICATIONS: used to maintain the double insulation and the original IP degree of protection of the boxes, containers and other GEWISS products.



GW 44 622

Brass terminal for through-line earth conductor

Code	Section (mm²)	Fixing	Pack Carton
GW 26 407	4	Pressure-operated	200/1600



GW 26 407



27 Combi



Scan the QR Code and find out all the technical informations.

RELIABILITY OVER TIME



The 27 Combi Series provides customised protection for every installation. This complete and versatile system of modular enclosures can be perfectly integrated into the domestic series, with IP40, IP55 and IP65 protection ratings ensuring reliability over the years.

COMBI IP 40: SAFETY AND VERSATILITY



The installation of the modular enclosures is extremely easy, thanks to the possibility to combine different enclosures to make custom configurations and the large internal space for wiring, which can be divided for greater safety with special functional separators.

COMBI IP55: ERGONOMICS AND PROTECTION



The special recessed transparent membrane makes it easy to locate the button keys by touch, while simple upward pressure opens the door. A perfect watertight seal is ensured by the closure system and coupling of the seals.

Playbus



Domestic range

Plates

p. 1072

Domestic range

Modular devices

p. 1082

Playbus

PLAYBUS YOUNG plates

Technopolymer

CLOUD WHITE



GW 32 242	2 modules
GW 32 243	3 modules
GW 32 244	4 modules
GW 32 246	6 modules

TONER BLACK



GW 32 302	2 modules
GW 32 303	3 modules
GW 32 304	4 modules
GW 32 306	6 modules


Metallised technopolymer

SOFT CHROME



GW 32 752	2 modules
GW 32 753	3 modules
GW 32 754	4 modules
GW 32 756	6 modules

Modularity



2 modules 3 modules 4 modules 6 modules

Design: architect Paolo Villa

PLAYBUS plates

Technopolymer

CLOUD WHITE



GW 32 022	2 modules
GW 32 023	3 modules
GW 32 024	4 modules
GW 32 026	6 modules
GW 32 027	4+4 modules
GW 32 028	6+6 modules
GW 32 029	6+6+6 modules

TONER BLACK



GW 32 052	2 modules
GW 32 053	3 modules
GW 32 054	4 modules
GW 32 056	6 modules
GW 32 057	4+4 modules

Metallised technopolymer

SOFT CHROME



GW 32 072	2 modules
GW 32 073	3 modules
GW 32 074	4 modules
GW 32 076	6 modules
GW 32 077	4+4 modules

Painted technopolymer

TITANIUM




GW 32 012	2 modules
GW 32 013	3 modules
GW 32 014	4 modules
GW 32 016	6 modules
GW 32 017	4+4 modules
GW 32 018	6+6 modules
GW 32 019	6+6+6 modules

SLATE



GW 32 002	2 modules
GW 32 003	3 modules
GW 32 004	4 modules
GW 32 006	6 modules
GW 32 007	4+4 modules
GW 32 008	6+6 modules
GW 32 009	6+6+6 modules

Modularity



2 modules | 3 modules | 4 modules | 6 modules | 4+4 modules | 6+6 modules (*) | 6+6+6 modules (*)

(*) Cloud white, slate and titanium
Design: architect Paolo Villa

Playbus

Plates



The technopolymer plates, available in two different shapes, Playbus and Playbus Young, available in different colour shades are the ideal solution for every installation. Playbus Young: classic forms, resistant materials. A line of simple, functional plates that can enhance every environment, bringing harmony and beauty to the entire home. Playbus: plates with unmistakable modern style, created to meet the needs of contemporary design. The elegance of the rectangular form is enhanced by the lightness and simplicity of the lines which surround the command buttons.

PLAYBUS YOUNG PLATES

Technopolymer, pastel colour, satin finish



GW 32 243

PLAYBUS YOUNG - Cloud white

Code	Description	For support codes	Pack Carton
GW 32 242	2 modules	GW32402	12
GW 32 243	3 modules	GW32403	96
GW 32 244	4 modules	GW32404	12
GW 32 246	6 modules	GW32406	8



GW 32 303

PLAYBUS YOUNG - Toner black

Code	Description	For support codes	Pack Carton
GW 32 302	2 modules	GW32402	12
GW 32 303	3 modules	GW32403	96
GW 32 304	4 modules	GW32404	12
GW 32 306	6 modules	GW32406	8

Metallised technopolymer



GW 32 753

PLAYBUS YOUNG - Soft chrome, satin finish

Code	Description	For support codes	Pack Carton
GW 32 752	2 modules	GW32402	12
GW 32 753	3 modules	GW32403	12
GW 32 754	4 modules	GW32404	12
GW 32 756	6 modules	GW32406	8

PLAYBUS PLATES

Technopolymer, pastel colour, glossy finish



GW 32 023

PLAYBUS - Cloud white

Code	Description	Configuration	For support codes	Pack Carton
GW 32 022	2 modules	-	GW32402	48
GW 32 023	3 modules	-	GW32403	48
GW 32 024	4 modules	-	GW32404	24
GW 32 026	6 modules	-	GW32406	24
GW 32 027	4+4 modules	Overlapping	GW32407	12
GW 32 028	6+6 modules	Overlapping	GW32408	12
GW 32 029	6+6+6 modules	Overlapping	GW32409	6



GW 32 053

PLAYBUS - Toner black

Code	Description	Configuration	For support codes	Pack Carton
GW 32 052	2 modules	-	GW32402	48
GW 32 053	3 modules	-	GW32403	48
GW 32 054	4 modules	-	GW32404	24
GW 32 056	6 modules	-	GW32406	24
GW 32 057	4+4 modules	Overlapping	GW32407	12

Painted technopolymer with scratchproof vitrified enamelling



GW 32 013

PLAYBUS - Titanium

Code	Description	Configuration	For support codes	Pack Carton
GW 32 012	2 modules	-	GW32402	48
GW 32 013	3 modules	-	GW32403	48
GW 32 014	4 modules	-	GW32404	24
GW 32 016	6 modules	-	GW32406	24
GW 32 017	4+4 modules	Overlapping	GW32407	12
GW 32 018	6+6 modules	Overlapping	GW32408	12
GW 32 019	6+6+6 modules	Overlapping	GW32409	6



GW 32 003

PLAYBUS - Slate

Code	Description	Configuration	For support codes	Pack Carton
GW 32 002	2 modules	-	GW32402	48
GW 32 003	3 modules	-	GW32403	48
GW 32 004	4 modules	-	GW32404	24
GW 32 006	6 modules	-	GW32406	24
GW 32 007	4+4 modules	Overlapping	GW32407	12
GW 32 008	6+6 modules	Overlapping	GW32408	12
GW 32 009	6+6+6 modules	Overlapping	GW32409	6

Playbus - Plates

Metallised technopolymer



GW 32 073

PLAYBUS - Soft chrome, glossy finish

Code	Description	Configuration	For support codes	Pack Carton
GW 32 072	2 modules	-	GW32402	48
GW 32 073	3 modules	-	GW32403	48
GW 32 074	4 modules	-	GW32404	24
GW 32 076	6 modules	-	GW32406	24
GW 32 077	4+4 modules	Overlapping	GW32407	12

SPECIAL PLATES, ENCLOSURES AND SUPPORTS

Watertight plates



GW 32 461

Self-supporting watertight plates for installation on flush-mounting rectangular boxes - IP55

Code	Description	Colour Plate	For flush mounting box	Pack Carton
GW 32 461	3 modules	Cloud white	GW24403, GW24403PM	1/60
GW 32 462	3 modules	Toner black	GW24403, GW24403PM	1/60
GW 32 466	4 modules	Cloud white	GW24404, GW24404PM	1/30
GW 32 467	4 modules	Toner black	GW24404, GW24404PM	1/30

Plates for profiles



GW 32 121

Plates for profiles and panels complete with insulating box and supports

Code	Description	Colour Plate	Pack Carton
GW 32 123	1 module	Cloud white	1/30
GW 32 121	1 module	Slate	1/30
GW 32 133	2 modules horizontal	Cloud white	1/30
GW 32 131	2 modules horizontal	Slate	1/30

ACCESSORIES SUPPLIED: the insulating box is equipped with a tug-proof cable fastener device and a corrugated conduit fastener device.

Tabletop and wall-mounting consoles



GW 32 411

Self-supporting tabletop and wall-mounting consoles

Code	Description	Colour	Outer dim. LxHxD (mm)	Pack Carton
GW 32 411	4 modules	Black	140x110x80	2/24
GW 32 412	8 modules	Black	240x110x80	2/12

CHARACTERISTICS: the feet are made of soft, slip-proof rubber.
ACCESSORIES SUPPLIED: cable gland, safety cable clamp and housing for command identification labels.

Wall-mounting boxes



GW 32 431

Wall-mounting boxes

Code	Suitable for	Colour	Characteristics	Pack Carton
GW 32 431	1/2/3 modules PLAYBUS	Cloud white	Halogen free	3/60
GW 32 432	1/2/3 modules PLAYBUS	Toner black	Halogen free	3/60

CHARACTERISTICS: fitted for fixing the earth terminal GW26407. Suitable for conduit Ø 16 - 20 mm.

Plates for lift/emergency



GW 32 450

Self-supporting wired plates for lift/emergency with illuminable button switch, triangle key and breakable glass - IP40

Code	Colour	Suitable for	For flush mounting box	Pack Carton
GW 32 450	White	Lift	GW24403	1/10
GW 32 451	Red	Emergency	GW24403	1/10

The articles are supplied with an 11mm button key already assembled, without a lamp. They use miniature lamp units.
CHARACTERISTICS: contacts supplied 1 NO + 1 NC - 10A (AC1) / 6A (AC15) - 380V AC.
APPLICATIONS: the plates are suitable for the GW40422 security lock, available as an accessory.
ACCESSORIES SUPPLIED: accessory button key, 17mm high, to operate the contacts when glass is broken.



GW 42 216

Glass breaker with universal fixing support

Code	Colour	Support dimension (mm)	Pack Carton
GW 42 216	Toner black	70x60	1/10




GW 40 422

Cylindrical security lock

Code	Description	Pack Carton
GW 40 422	Security lock	1/10

Playbus - Plates



GW 32 457

Spare breakable glass for lift/emergency plates

Code	Suitable for	Pack Carton
GW 32 457	GW32450, GW32451, GW32452, GW32453	1/10


Supports



GW 32 403

Insulating supports for installation of PLAYBUS / PLAYBUS YOUNG plates on rectangular boxes

Code	Description	Configuration	Fixing	Characteristics	Pack Carton
GW 32 403	3 modules	-	2 screws (included)	Halogen free	10/150
GW 32 404	4 modules	-	2 screws (included)	Halogen free	10/100
GW 32 406	6 modules	-	4 screws (included)	Halogen free	10/100
GW 32 407	4+4 modules	Overlapping	4 screws (included)	Halogen free	5/50
GW 32 408	6+6 modules	Overlapping	4 screws (included)	Halogen free	5/50
GW 32 409	6+6+6 modules	Overlapping	4 screws (included)	Halogen free	5/25



GW 32 402

Insulating supports for installation of PLAYBUS / PLAYBUS YOUNG plates on square/rectangular boxes

Code	Description	Fixing	Characteristics	Pack Carton
GW 32 402	2 modules	2 screws (included)	Halogen free	10/150



GW 32 421

Supports for mounting PLAYBUS devices on DIN rail

Code	Description	No. DIN modules	Pack Carton
GW 32 421	1 module	1.5	5/200





Playbus



Scan the QR Code and find out all the technical informations.

DESIGN AND SAFETY



The Playbus series includes two plate shapes, modern or classic, with a glossy or satin finish. The use of technopolymer ensures complete and safe electrical insulation together with greater durability of colours and finishes.

INSTALLATION FLEXIBILITY



The Playbus series lets you manage multiple sockets and lines from a single point, thanks to the high-capacity plates, with up to 18 modules and internal circuit separation. The exceptional flexibility of the installations is also ensured by the wide range of accessories available.

CONTROL DEVICES



The control units have three types of backlighting: functional (also visible during the day), night location (discrete luminosity) and iconographic.

Playbus

Command

One-way switches



GW 30 001
1M-1P-16 AX
General

GW 30 002
1M-1P-16 AX
Backlit (*)

GW 30 003
1M-1P-16 AX
Indicator (*)

GW 30 004
1M-2P-16 AX
General

GW 30 007
1M-2P-10 AX
With key

Two-way switches



GW 30 011
1M-1P-16 AX
General

GW 30 012
1M-1P-16 AX
Backlit (*)

GW 30 013
1M-1P-16 AX
Indicator (*)

Intermediate switch



GW 30 015
1M-1P-16 AX
General

Three-way switch



GW 30 016
1M-1P-10 AX
Positions 1-0-2

Push-buttons



GW 30 021
1M-1P-NO-16 A
General

GW 30 022
1M-1P-NO-16 A
Backlit (*)

GW 30 023
1M-1P-NO-16 A
Indicator (*)

GW 30 024
1M-1P-NO-16 A
Key (*)

GW 30 025
1M-1P-NO-16 A
Bell (*)

GW 30 026
1M-1P-NO-16 A
Light (*)

GW 30 027
1M-1P-NO-16 A
Light scale (*)

GW 30 030
1M-2P-NO-16 A
General

GW 30 031
1M-2P-NO-16 A
With pull-cord



GW 30 033
1M-1P-NO+NO-16 A
Double

GW 30 032
1M-2P-NO-10 A
With key

GW 30 034
1M-1P-NO+NO-10 A
With interlock

GW 30 035
1M-1P-NC-16 A
General

GW 30 036
1M-1P-NO+NC-10 A
Start

GW 30 037
1M-1P-NC+NO-10 A
Stop

GW 30 038
2M-1P-NO-10 A
With illuminated name plate (*)

Miniature lamp



GW 10 893	12/24 V ac/dc	White
GW 30 943	230 V ac	Red
GW 30 944	230 V ac	Green
GW 30 946	110/230 V ac	Light blue
GW 30 947	110/230 V ac	White

Cartridge lamp



GW 20 902 S6x36	12 V ac/dc	White
GW 20 903 S6x36	24 V ac/dc	White
GW 20 904 S6x31	12 V ac/dc	White
GW 20 905 S6x31	24 V ac/dc	White
GW 20 906 S6,3x28	110/230 V ac	Red
GW 20 908 S6,3x28	110/230 V ac	Green

Infrared



GW 30 121
Movement sensor
230 V ac-50/60 Hz

Blanking modules and cable output



GW 30 901 - 1M
GW 30 902 - 2M
GW 30 903 - 3M

GW 30 905
1M

(*) supplied without LED signalling unit

Power and data

Italian



GW 30 201
2P+E-10 A-250 V ac



GW 30 203
2P+E-16 A-250 V ac
Dual amperage



GW 30 321
2P+E-16 A-250 V ac
Dual amperage



GW 30 331
2P+E-16 A-250 V ac
Dual amperage

Israeli



GW 30 237
2P+E-16 A-250 V ac

Italian/German



GW 30 210
2P+E-16 A-250 V ac



GW 30 212
2P+E-16 A-250 V ac
Dual amperage



GW 30 214
2P+E-16 A-250 V ac
Dual amperage

Swiss



GW 30 234
2P+E-10 A-250 V ac

German



GW 30 211
2P+E-16 A-250 V ac



GW 30 322
2P+E-16 A-250 V ac

French



GW 30 215
2P-16 A-250 V ac



GW 30 216
2P+E-16 A-250 V ac

British



GW 30 219
2P+E-13 A-250 V ac



GW 30 220
2P+E-16 A-250 V ac

Euro-American/USA



GW 30 227
2P+E-10/15
A-250/125 V ac



GW 30 232
2P+E-15 A-125 V ac

TV-SAT



F female
GW 30 311 - 0 dB
GW 30 316 - 5 dB



IEC male
GW 30 301 - 0 dB
GW 30 306 - 5 dB



GW 20 277
Terminal
resistance 75
ohm

Telephone sockets



GW 30 261
RJ11

Data sockets



GW 30 685 Cat. 6
GW 30 267 Cat. 5e
RJ45 - UTP



GW 30 686 Cat. 6
GW 30 266 Cat. 5e
RJ45 - FTP



GW 30 286 SYSTIMAX Commscope
GW 30 287 AMP/Keystone Jack
Adapters

Power, comfort and climate management

Dimmer



GW 30 402
Resistive 230 V ac 100-500 W
Resistive 110 V ac 50-250 W



GW 30 403▲
Resistive 230 V ac 100-900 W
Resistive 110 V ac 100-500 W
Inductive 230 V ac 40-300 VA
Inductive 110 V ac 20-150 VA

GW 30 404
Resistive 230V ac 40-300W
Resistive 110V ac 20-150W
Inductive 230V ac 40-300VA
Inductive 110V ac 20-150VA
With two-way switch



GW 30 401
Resistive 60-500 W
Inductive 60-500 VA
230 V ac-50/60 Hz

Climate control



GW 30 702
Thermostat
230 V ac-50/60 Hz



GW 30 703
Probe to measure temperature



GW 30 706
Timed thermostat
230 V ac-50/60 Hz

Hotel components



GW 30 430
Universal badge switch
1P-NO-10 A



GW 30 711
Shaver socket-outlet
230 V ac-50/60 Hz

▲ Articles designed exclusively for export to a limited number of Countries not belonging to the EU (or candidates for membership) or the European Free Trade Association. Check with Gewiss Customer Service to make sure the product meets the regulation of the Country in question before importing it.

Protection, safety and signalling

Automatic circuit breakers



GW 30 371 - 6 A
GW 30 372 - 10 A
GW 30 373 - 16 A
1P

GW 30 374 - 6 A
GW 30 375 - 10 A
GW 30 376 - 16 A
1P+N

Miniature circuit breakers
3 kA
Curve C



GW 30 377 - 6 A
GW 30 378 - 10 A
GW 30 379 - 16 A
1P+N-10 mA

Miniature circuit breakers
3 kA
Curve C

Protection devices



GW 30 360
Fuse-holder
In MAX=16 A

Accessories



GW 30 522
GAS solenoid valve
3/4"-230 V ac-12 VA

Ringers and buzzers



GW 30 633 - 12 V ac
GW 30 634 - 230 V ac
Ringers



GW 30 635 - 12 V ac
GW 30 636 - 230 V ac
Buzzers

Anti black-out lamp



GW 30 501
230 V ac-50/60 Hz
Removable

Indicator lamps



GW 30 611
Red
Illuminable (*)




GW 30 612
Green
Illuminable (*)



GW 30 614
Transparent
Illuminable (*)

Supports

Supports for square and rectangular boxes



GW 32 402
With screws - 2 modules

Supports for rectangular boxes



GW 32 403
With screws - 3 modules



GW 32 404
With screws - 4 modules



GW 32 406
With screws - 6 modules



GW 32 407
With screws - 4+4 modules



GW 32 408
With screws - 6+6 modules



GW 32 409
With screws - 6+6+6 modules

(*) supplied without LED signalling unit

Playbus

Modular devices

A range of modular devices for domestic and similar uses; can be composed on frames for rectangular flush-mounting boxes of up to 18 modules, or on square versions. Colours and finishes: satin black, elegant and classy. The range includes commands, socket-outlets, protection, indicators, connectors and devices for the control, safety and comfort of your home.





COMMAND

Command devices



GW 30 001

One-way switches - 250V ac

Code	Description	Type	Symbol	Rated power of 230V LED lamps	No. Playbus modules	Pack Carton
GW 30 001	1P - 16AX	General	-	200 W	1	24/96
GW 30 002	1P - 16AX illuminable	Night-time backlit	-	200 W	1	24/48
GW 30 003	1P - 16AX illuminable	Functional indicator	-	200 W	1	24/48
GW 30 004	2P - 16 AX	General	0/1	200 W	1	24/48
GW 30 007	2P - 10AX	With key	0/1	100 W	1	1/12

ACCESSORIES SUPPLIED: GW30007: 2 keys. The key can be extracted in both positions. Spare keys: GW20901. Backlit items are supplied without lamp. They use miniature lamp units.



GW 30 011

Two-way switches - 250V ac

Code	Description	Type	Rated power of 230V LED lamps	No. Playbus modules	Pack Carton
GW 30 011	1P - 16AX	General	200 W	1	24/96
GW 30 012	1P - 16AX illuminable	Night-time backlit	200 W	1	24/48
GW 30 013	1P - 16AX illuminable	Functional indicator	200 W	1	24/48

ACCESSORIES SUPPLIED: backlit items are supplied without lamp. They use miniature lamp units.



GW 30 015

Intermediate switch - 250V ac

Code	Description	Type	Rated power of 230V LED lamps	No. Playbus modules	Pack Carton
GW 30 015	1P - 16AX	General	200 W	1	24/48



GW 30 016

Three-way switch - 250V ac

Code	Description	Symbol	Rated power of 230V LED lamps	No. Playbus modules	Pack Carton
GW 30 016	1P - 10AX	UP - DOWN	100 W	1	24/48

CHARACTERISTICS: three standing positions. Both contacts are open in the central position (OFF).

APPLICATIONS: command of circuits requiring an interlock (e.g. operating motorised devices with direction reversal). 2-user selective control.



GW 30 021

Push-buttons - 250V ac

Code	Description	Type	Symbol	No. Playbus modules	Pack Carton
GW 30 021	1P NO - 16A	General	-	1	24/96
GW 30 022	1P NO - 16A illuminable	Night-time backlit	-	1	12/24
GW 30 023	1P NO - 16A illuminable	Functional indicator	-	1	12/24
GW 30 024	1P NO - 16A illuminable	With symbol	Key	1	12/24
GW 30 025	1P NO - 16A illuminable	With symbol	Bell	1	12/24
GW 30 026	1P NO - 16A illuminable	With symbol	Light	1	12/24
GW 30 027	1P NO - 16A illuminable	With symbol	Stairs	1	12/24
GW 30 030	2P NO - 16A	General	0	1	24/48
GW 30 031	2P NO - 16A	With pull-cord	-	1	4/32
GW 30 032	2P NO - 10A	With key	0/1	1	1/24
GW 30 033	1P NO - 16A double button	Double button 25 x 22.5 mm	-	1	12/24
GW 30 034	1P NO+NO - 10A	With interlock	UP - DOWN	1	12/24
GW 30 035	1P NC - 16A	General	0	1	12/24
GW 30 036	1P NO - 10A - Aux. NC	Start	Green	1	12/24
GW 30 037	1P NC - 10A - Aux. NO	Stop	Red	1	12/24

CHARACTERISTICS: GW30033: independent push-buttons that can also be activated simultaneously. GW30034: three-way push-button with interlock. Both contacts are open in the central position (OFF).
APPLICATIONS: GW30034: impulse activation of motorised devices with direction reversal (e.g. roller shutters, curtains, etc.).
ACCESSORIES SUPPLIED: GW30031 cord in insulating material, 150cm long, with knob. GW30032 supplied with 2 keys. Spare keys: GW30912.
Backlit items are supplied without lamp. They use miniature lamp units.



GW 30 038

Push-button with backlit name-plate - 250V ac

Code	Description	Lamp	Lamp voltage	Lamp power	No. Playbus modules	Pack Carton
GW 30 038	1P NO - 10A illuminable	Cartridge lamp S6x36 mm	12 - 24 V	2 W	2	12/36

APPLICATIONS: in installations on 3 modules plates, the dimensions of the device (only 2 modules) allow another 1 module device to be inserted.
ACCESSORIES SUPPLIED: supplied without lamp.

Blanking modules and cable outlet



GW 30 901

Blanking modules and cable outlet

Code	Description	No. Playbus modules	Pack Carton
GW 30 901	1 module	1	5/200
GW 30 902	2 modules	2	12/48
GW 30 903	3 modules	3	8/32
GW 30 905	1 module with outlet for cable Ø 4 and Ø 8mm	1	24/48

APPLICATIONS: in addition to their normal use, they permit installing signal socket-outlets, microswitches and LEDs after appropriate drilling/preparation.
In addition, it is possible to apply the temperature sensor GW30703 using the special double-sided adhesive.
ACCESSORIES SUPPLIED: GW30905, fastner cable fastener device.

Infrared movement sensor



GW 30 121

Infrared movement detectors

Code	Supply voltage	Output contacts	No. Playbus modules	Pack Carton
GW 30 121	230V ac - 50/60Hz	1NO 3A(AC1) 250V ac	1	1/6

CHARACTERISTICS: adjustment of the intervention duration 15 sec - 10 min. Light sensitive threshold adjustment - min. 10 lux - max. inhibited. Sensor with fixed lens. Suitable for commanding halogen lamps/resistive loads: 700 W, incandescent lamps: 450 W, low voltage halogen lamps (12 V) controlled by toroidal or electronic transformers: 450 W, uncompensated fluorescent lamps: 2x58 W, motors and gear motors: 400 VA. Not suitable for compensated fluorescent lamps, for discharge lamps and for all loads not indicated that must be commanded using a support relay.
APPLICATIONS: Energy-saving: command of the lighting of rooms and areas only when people pass through.
Comfort and safety: automatic command of circuits without needing to activate one-way switches.
NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to work correctly.

Playbus - Modular devices

POWER

Socket-outlets - Italian standard



GW 30 203

Italian standard socket-outlets - 250V ac

Code	Description	Type	For plug pins	No. Playbus modules	Pack Carton
GW 30 201	2P+E - 10A	P11	Ø 4 mm	1	24/96
GW 30 203	2P+E - 16 A Dual amperage	P17-11	Ø 4 / 5 mm	1	24/96

CHARACTERISTICS: with safety shields.



GW 30 210

Italian/German standard socket-outlets - 250V ac

Code	Description	Earth pit	Type	For plug pins	No. Playbus modules	Pack Carton
GW 30 210	2P+E - 16A	Side and central	P30	Ø 4 / 4.8 mm	2	12/48
GW 30 212	2P+E - 16 A Dual amperage	Side and central	P40	Ø 4 / 4.8 / 5 mm	2	12/48

CHARACTERISTICS: with safety shields.

Socket-outlets for dedicated lines



GW 30 321

Italian Standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	Type	For plug pins	No. Playbus modules	Pack Carton
GW 30 321	2P+E - 16 A Dual amperage	Red	P17-11	Ø 4 / 5 mm	1	24/48
GW 30 331	2P+E - 16 A Dual amperage	Green	P17-11	Ø 4 / 5 mm	1	24/48

CHARACTERISTICS: with safety shields.



GW 30 214

Italian/German standard socket-outlets for dedicated lines - 250V ac

Code	Description	Earth pit	Colour	Type	For plug pins	No. Playbus modules	Pack Carton
GW 30 214	2P+E - 16 A Dual amperage	Side and central	Red	P40	Ø 4 / 4.8 / 5 mm	2	12/24

CHARACTERISTICS: with safety shields.



GW 30 322

German Standard socket-outlets for dedicated lines - 250V ac

Code	Description	Colour	For plug pins	No. Playbus modules	Pack Carton
GW 30 322	2P+E - 16A	Red	Ø 4.8 mm	2	12/24

CHARACTERISTICS: with safety shields.

Socket-outlets - international standard



GW 30 211

German standard socket-outlet - 250V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 211	2P+E - 16A	Ø 4.8 mm	2	12/48

CHARACTERISTICS: with safety shields.



GW 30 215

French Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 215	2P - 16A	Ø 4 / 4.8 mm	2	12/48
GW 30 216	2P+E - 16A	Ø 4 / 4.8 mm	2	12/48

CHARACTERISTICS: with safety shields.



GW 30 219

British Standard socket-outlets - 250V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 219	2P+E - 13 A	Flat	2	12/48
GW 30 220	2P+E - 16A	Ø 7 mm	2	12/48

CHARACTERISTICS: with safety shields.
NOTES: given the size of the plugs, it is not possible to install two or more socket-outlets side-by-side.



GW 30 234

Swiss standard socket-outlets - 250V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 234	2P+E - 10A - type 13	Ø 4 mm	1	24/48

CHARACTERISTICS: with safety shields.

Playbus - Modular devices



GW 30 227

Euro American standard socket-outlets - 250/125V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 227	2P+E - 10/15A	Ø 4.8 mm/ flat	1	24/48



GW 30 232

USA standard socket-outlets - 125V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 232	2P+E - 15A	Flat parallel horizontal	1	24/48



GW 30 237

Israeli standard socket-outlet - 250V ac

Code	Description	For plug pins	No. Playbus modules	Pack Carton
GW 30 237	2P+E - 16A	Round Ø 4 / 4.4 mm	2	12/48

CHARACTERISTICS: with safety shields.

DATA

TV-SAT sockets



GW 30 316

Coaxial TV-SAT sockets (5-2400 MHz) class A shielding F female connector

Code	Description	Type	Attenuation	No. Playbus modules	Pack Carton
GW 30 311	Direct	With passage of current	0 dB	1	24/48
GW 30 316	Through wiring	-	5 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW30311 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.

APPLICATIONS: Socket-outlets suitable for return channel.

NOTES: the TV-SAT 5 dB GW30316 coaxial socket-outlet is defined with conditioned use, it is a special through socket-outlet and as such must be used, with the only difference that the user door (socket-outlet towards the user device) must always be closed with a load of 75 Ohm (TV, VCR, SAT receiver or 75-Ohm termination).



GW 30 306

Coaxial TV sockets (5-2400 MHz) class A shielding IEC male connector Ø 9.5 mm

Code	Description	Type	Attenuation	No. Playbus modules	Pack Carton
GW 30 301	Direct	With passage of current	0 dB	1	24/48
GW 30 306	Through wiring	-	5 dB	1	1/24
GW 20 277	Terminal resistance 75 ohm	-	-	-	50/200

CHARACTERISTICS: GW30301 permits carrying a remote power supply voltage/current and/or control signals towards the user port (max 24 V - 500 mA). GW20277 in combination with feedthrough socket-outlets allows you to make terminal socket-outlets.
APPLICATIONS: Socket-outlets suitable for return channel.
NOTES: the TV 5 dB GW30306 coaxial socket-outlet is defined with conditioned use, it is a special through socket-outlet and as such must be used, with the only difference that the user door (socket-outlet towards the user device) must always be closed with a load of 75 Ohm (TV, VCR, SAT receiver or 75-Ohm termination).

Telephone sockets



GW 30 261

RJ11 telephone sockets

Code	Description	No. pairs	Cables type	Connection	No. Playbus modules	Pack Carton
GW 30 261	RJ11	2	Twisted pair	Screw-on terminals	1	1/24

APPLICATIONS: telephone, telefax, modem.

Data sockets



GW 30 685

RJ45 sockets

Code	Description	No. pairs	Use category	Cables type	Connection	No. Playbus modules	Pack Carton
GW 30 686	RJ45	4	6	FTP	Toolless	1	1/12
GW 30 685	RJ45	4	6	UTP	Toolless	1	1/12
GW 30 266	RJ45	4	5e	FTP	Toolless	1	1/24
GW 30 267	RJ45	4	5e	UTP	Toolless	1	1/24

APPLICATIONS: LANs up to 100MHz (e.g. Ethernet, Token Ring networks) for cat. 5e.
LANs up to 250MHz (e.g. Videoconference systems, CCTV) for cat. 6.
ACCESSORIES SUPPLIED: circuit identification label.



GW 30 287

Adapters for housing data socketsS

Code	Compatibility	No. Playbus modules	Pack Carton
GW 30 286	SYSTIMAX COMMSCOPE	1	1/96
GW 30 287	AMP / Keystone Jack	1	1/96

ACCESSORIES SUPPLIED: circuit identification labels.
NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the empty Gewiss container.

Playbus - Modular devices

PROTECTION

Miniature circuit breakers



GW 30 371

Miniature circuit breakers - C characteristic - 230V ac

Code	Description	Rated current (A)	Breaking capacity	No. Playbus modules	Pack Carton
GW 30 371	Single pole (1P)	6	3 kA	1	1/12
GW 30 372	Single pole (1P)	10	3 kA	1	1/12
GW 30 373	Single pole (1P)	16	3 kA	1	1/12
GW 30 374	Two-pole (1P+N)	6	3 kA	1	1/12
GW 30 375	Two-pole (1P+N)	10	3 kA	1	1/12
GW 30 376	Two-pole (1P+N)	16	3 kA	1	1/12



GW 30 377

Residual current miniature circuit breakers - characteristic C - class A - 230V ac - 50/60 Hz

Code	Description	Idn	Rated current (A)	Breaking capacity	No. Playbus modules	Pack Carton
GW 30 377	Two-pole (1P+N)	10 mA	6	3 kA	2	1/6
GW 30 378	Two-pole (1P+N)	10 mA	10	3 kA	2	1/6
GW 30 379	Two-pole (1P+N)	10 mA	16	3 kA	2	1/6

Protection devices



GW 30 360

Fuse-holder - 250V ac

Code	Rated current (A)	Fuse type	No. Playbus modules	Pack Carton
GW 30 360	16	Ø 6.3 x 32 mm	1	24/48

SIGNALLING

Anti black-out lamp



GW 30 501

Extractable anti black-out lamp - 230V - 50/60Hz

Code	Supply voltage	Power supply batteries	Autonomy	Type of lamp	No. Playbus modules	Pack Carton
GW 30 501	230V - 50/60 Hz	Ni-Mh	2 h	White LED	2	1/6

CHARACTERISTICS: equipped with inhibition selector on the front. Use battery pack 4.8 V 40 mAh.

Indicator light devices



GW 30 611

Indicator lamps - 12/24/250V ac

Code	Diffuser colour	Diffuser meaning	Diffusor type	Fixing for lamp	No. Playbus modules	Pack Carton
Type: Single lamps						
GW 30 611	Red	Danger	Flat	Cartridge	1	24/48
GW 30 612	Green	Safety	Flat	Cartridge	1	24/48
GW 30 614	Transparent	Neutral	Flat	Cartridge	1	24/48

CHARACTERISTICS: supplied without lamp. They use S6x31 mm and S6.3x28 mm cartridge lamps (max 2 W).
NOTES: the meaning of the diffusers refers to the recommendations of standard EN60073 with regard to the use of the colours in indicator lights.

Acoustic signalling devices



GW 30 634

Bells

Code	Supply voltage	Max power consumption	Sound intensity	No. Playbus modules	Pack Carton
GW 30 633	12V ac - 50 Hz	8 VA	80 dB (at 1 m)	1	12/24
GW 30 634	230V ac - 50Hz	8 VA	80 dB (at 1 m)	1	12/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).



GW 30 636

Buzzers

Code	Supply voltage	Max power consumption	Sound intensity	No. Playbus modules	Pack Carton
GW 30 635	12V ac - 50 Hz	8 VA	70 dB (at 1 m)	1	12/24
GW 30 636	230V ac - 50Hz	8 VA	70 dB (at 1 m)	1	12/24

CHARACTERISTICS: for intermittent use (5 sec. ON / 15 sec. OFF).

ENERGY, TEMPERATURE AND COMFORT MANAGEMENT

Dimmer



GW 30 402

Rotating electronic regulator for resistive loads

Code	Resistive load 230V ac	Resistive load 110V ac	Control	No. Playbus modules	Pack Carton
GW 30 402	100-500 W	50-250 W	Rotary	1	1/12

CHARACTERISTICS: frequency 50/60 Hz. Equipped with orange signalling LED.
NOTES: the installation of more than one product side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Playbus - Modular devices



GW 30 403

Rotating electronic regulators for resistive and inductive loads

Code	Resistive load 230V ac	Inductive load 230V ac	Control	No. Playbus modules	Pack Carton
GW 30 403	100-900 W	40-300 VA	Rotary	1	1/12

CHARACTERISTICS: frequency 50/60 Hz. Equipped with orange signalling LED. GW30403: resistive load 110V AC 100-500 W; inductive load 110V AC 20-150 VA.
GW30403 compliance with the EMC directive is only guaranteed by connecting the regulator to an LC filter with the following characteristics: L=1mH - 5A, C=0.15uF - 275V X2, according to the documentation provided with the product. Item designated solely for export to a limited number of countries outside the European Union or countries applying to become part of the European Free Trade Area. Contact Gewiss Customer Service to check the product meets the regulations of the country concerned before importing it.
NOTES: the installation of more than one product side-by-side in a single container is not permitted. To avoid overheating, insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.



GW 30 401

Electronic regulator with button - for resistive and inductive loads

Code	Resistive load 230V ac	Inductive load 230V ac	Control	No. Playbus modules	Pack Carton
GW 30 401	60-500 W	60-500 VA	Push-button	2	1/6

CHARACTERISTICS: frequency 50/60 Hz. Equipped with orange signalling LED.
ACCESSORIES SUPPLIED: quick fuse Ø 5x20 mm - 2.5 A.
NOTES: the installation of more than one product side-by-side in a single container is not permitted.
To avoid overheating, insert a blanking module between two electronic devices. If installing two regulators in the same box, the maximum loads that can be commanded by each regulator must be reduced by 50%.

Temperature control devices



GW 30 706

Timed thermostat - Daily/weekly programming

Code	Supply voltage	Temperature adjustment	Output contacts	No. Playbus modules	Pack Carton
GW 30 706	230 V ac - 50/60 Hz	From +5°C to +40°C	1NO/NC 5A(AC1)/2A(AC15) 250V ac	2	1/2

CHARACTERISTICS: with rechargeable buffer battery to guarantee the updating of the calendar (date, day, time) in the event of a blackout.
Serial input for connecting the GW90821 GSM remote control.



GW 30 702

Electronic summer/winter thermostat with input for remote control of night-time reduction 230V - 50/60Hz

Code	Temperature adjustment	Output contacts	No. Playbus modules	Pack Carton
GW 30 702	From +5°C to +40°C	1NO 5A(AC1)/2A (AC15) 250V ac	3	2/4

CHARACTERISTICS: with buffer battery (30 days reserve charge). Input for 1 external probe GW30703 available as accessory, to display the temperature of another environment.
NOTES: customizable temperature setpoints: frost, comfort and night.



GW 30 703

Probe to measure internal/external temperature

Code	Suitable for	Outer dim. LxHxD (mm)	Cable length	Pack Carton
GW 30 703	GW30702	39x23x14	10 m	2/12

CHARACTERISTICS: cable extendable up to max 50m (min section 2x0.35mm²).
APPLICATIONS: can be used in bedrooms, bathrooms, kitchens, as a supplementary indoor probe, or outside the home.
ACCESSORIES SUPPLIED: expandable wall plug with screws and double-sided adhesive for wall or smooth surfaces mounting (or on a blanking module).

SPECIAL APPLICATIONS

Components for hotel systems

Universal badge switch with backlit light - 250V ac



GW 30 430

Code	Description	For badge card max. width	Type	Rated power of LED lamps	230V No. Playbus modules	Pack Carton
GW 30 430	1P NO - 10A	54 mm	Backlit 230V ac	100 W	3	1/2

CHARACTERISTICS: supplied without a badge.

APPLICATIONS: activation of circuits and services in hotel rooms (e.g. lights, air-conditioner, fridge-bar), indication of room occupied (with badge inserted).

European/American standard shaver socket with insulation transformer



GW 30 711

Code	Supply voltage	For plug pins	Selectable output voltage	Maximum power	No. Playbus modules	Pack Carton
GW 30 711	230V ac - 50/60 Hz	Ø 4 / 5 - 6.3x1.5 mm	120 - 230V ac	20 VA	3	2/4

CHARACTERISTICS: the socket-outlet is equipped with a self-protection device against overloading.

The output voltage should be selected correctly, consulting the rating of the user device before inserting the plug.

The relevant indicator LED allows the chosen voltage to be clearly seen.

ACCESSORIES

Spare parts and accessories

Miniature lamps with quick coupling terminals



Code	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 30 943	230 V ac	0.4 W	Fluorescent	Red	50
GW 30 944	230V ac	0.4 W	Fluorescent	Green	50
GW 30 946	110 / 230V ac	0.6 W	LED	Light blue	50
GW 30 947	110 / 230V ac	0.6 W	LED	White	50
GW 10 893	12-24V ac/dc	0.4 W	LED	White	50

APPLICATIONS: miniature lamps are mounted on all control devices fitted for luminous signalling.

Cartridge lamps



GW 20 902

Code	Dimensions (mm)	Lamp voltage	Lamp power	Lamp	Light emitted	Pack Carton
GW 20 902	S6x36	12V ac/dc	2 W	Incandescence	White	50
GW 20 903	S6x36	24V ac/dc	2 W	Incandescence	White	50
GW 20 904	S6x31	12V ac/dc	2 W	Incandescence	White	50
GW 20 905	S6x31	24V ac/dc	2 W	Incandescence	White	50
GW 20 906	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Red	50
GW 20 908	S6.3x28	110 / 230V ac	0.4 W	Fluorescent	Green	50

NOTES: the cartridge lamps are mounted on the stair riser, on the single indicator lamps and on the push-buttons with a name plate.

Playbus - Modular devices



GW 20 911

Miniature fuses - 250V ac

Code	Dimensions (mm)	Rated current (A)	Rated voltage	Pack Carton
GW 20 911	Ø 5 x 20	2.5	250V ac	20/200
GW 20 921	Ø 6.3 x 32	2	250V ac	10/200
GW 20 922	Ø 6.3 x 32	4	250V ac	10/200
GW 20 923	Ø 6.3 x 32	6	250V ac	10/200
GW 20 924	Ø 6.3 x 32	10	250V ac	10/200
GW 20 925	Ø 6.3 x 32	16	250V ac	10/200



GW 20 901

Set of 2 keys for command devices

Code	Suitable for	Pack Carton
GW 20 901	One-way switches - two-way switches	1/100
GW 30 912	Push-buttons	1/100





Playbus



Scan the QR Code and find out all the technical informations.

DESIGN AND SAFETY



The Playbus series includes two plate shapes, modern or classic, with a glossy or satin finish. The use of technopolymer ensures complete and safe electrical insulation together with greater durability of colours and finishes.

INSTALLATION FLEXIBILITY




The Playbus series lets you manage multiple sockets and lines from a single point, thanks to the high-capacity plates, with up to 18 modules and internal circuit separation. The exceptional flexibility of the installations is also ensured by the wide range of accessories available.


CONTROL DEVICES



The control units have three types of backlighting: functional (also visible during the day), night location (discrete luminosity) and iconographic.

Dahlia





Domestic range

Plates

p. 1097

Domestic range

Monobloc devices

p. 1102

Dahlia plates

Technopolymer

WHITE

GW 35 901 AW	1 gang
GW 35 902 AW	2 gang
GW 35 903 AW	3 gang
GW 35 904 AW	4 gang
GW 35 905 AW	5 gang
GW 35 909 AW	Double

IVORY



GW 35 901 AY	1 gang
GW 35 902 AY	2 gang
GW 35 903 AY	3 gang
GW 35 904 AY	4 gang
GW 35 905 AY	5 gang
GW 35 909 AY	Double

HEMP



GW 35 901 AH	1 gang
GW 35 902 AH	2 gang
GW 35 903 AH	3 gang
GW 35 904 AH	4 gang
GW 35 905 AH	5 gang
GW 35 909 AH	Double

CREAM



GW 35 901 AM	1 gang
GW 35 902 AM	2 gang
GW 35 903 AM	3 gang
GW 35 904 AM	4 gang
GW 35 905 AM	5 gang
GW 35 909 AM	Double

LIGHT GREY



GW 35 901 AG	1 gang
GW 35 902 AG	2 gang
GW 35 903 AG	3 gang
GW 35 904 AG	4 gang
GW 35 905 AG	5 gang
GW 35 909 AG	Double

DARK GREY



GW 35 901 AD	1 gang
GW 35 902 AD	2 gang
GW 35 903 AD	3 gang
GW 35 904 AD	4 gang
GW 35 905 AD	5 gang
GW 35 909 AD	Double


ANTHRACITE GREY



GW 35 901 AN	1 gang
GW 35 902 AN	2 gang
GW 35 903 AN	3 gang
GW 35 904 AN	4 gang
GW 35 905 AN	5 gang
GW 35 909 AN	Double

Modularity

Centre distance 71 mm



Dahlia

Plates

A wide choice of plates, realized in technopolymer in seven colors with glossy finish: white, ivory, hemp, cream, light grey, dark grey, anthracite grey. Plates available in different modularities, from 1 to 5 gang, installable indifferently in horizontal or in vertical position.



DAHLIA PLATES

Technopolymer

GW 35 901 AW

DAHLIA - White

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AW	1 gang	-	-	240
GW 35 902 AW	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AW	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AW	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AW	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AW	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AW suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.



GW 35 901 AY

DAHLIA - Ivory

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AY	1 gang	-	-	240
GW 35 902 AY	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AY	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AY	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AY	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AY	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AY suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.




GW 35 901 AH

DAHLIA - Hemp

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AH	1 gang	-	-	240
GW 35 902 AH	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AH	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AH	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AH	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AH	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AH suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.



GW 35 901 AM

DAHLIA - Cream

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AM	1 gang	-	-	240
GW 35 902 AM	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AM	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AM	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AM	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AM	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AM suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.

Dahlia



GW 35 901 AG

DAHLIA - Light grey

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AG	1 gang	-	-	240
GW 35 902 AG	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AG	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AG	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AG	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AG	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AG suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.



GW 35 901 AD

DAHLIA - Dark grey

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AD	1 gang	-	-	240
GW 35 902 AD	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AD	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AD	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AD	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AD	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AD suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.



GW 35 901 AN

DAHLIA - Anthracite grey

Code	Description	Type	Centre distance	Pack Carton
GW 35 901 AN	1 gang	-	-	240
GW 35 902 AN	2 gang	Horizontal/Vertical	71 mm	120
GW 35 903 AN	3 gang	Horizontal/Vertical	71 mm	100
GW 35 904 AN	4 gang	Horizontal/Vertical	71 mm	80
GW 35 905 AN	5 gang	Horizontal/Vertical	71 mm	60
GW 35 909 AN	Double	-	-	120

CHARACTERISTICS: glossy finish. GW35909AN suitable for double socket-outlets GW35204W, GW35204Y,GW35214W and GW35214Y.



Dahlia




Scan the QR Code and find out all the technical informations.

DAHLIA RANGE



A wide choice of plates, realized in technopolymer in 7 colors with glossy finish and in many modularities, from 1 to 5 gang.

EASIER INSTALLATION



Dahlia plates can be installed either horizontally or vertically, minimising the number of product codes and simplifying installation.

EXPANDABLE WITH CHORUSMART



The special frame support allows the integration of the Dahlia range with the ChoruSmart modular devices, picking up whatever ChoruSmart device you should need. The support has to be completed with Dahlia plates.

Dahlia

Switches - white

One-way switches quick wiring



GW 35 031 W
1P-10 AX
Illuminable (*)



GW 35 002 W
1P-10 AX
Backlit



GW 35 006 W
1P-10 AX
Backlit



GW 35 003 W
2P-10 AX
Illuminable (*)



GW 35 051 W
1P-10 AX
Double one-way switch

Two-way switches quick wiring



GW 35 071 W
1P-10 AX
Illuminable (*)



GW 35 012 W
1P-10 AX
Backlit



GW 35 016 W
1P-10 AX
Backlit



GW 35 052 W
1P-10 AX
Double two-way switch

Intermediate switch quick wiring



GW 35 015 W
1P-10 AX

Push-buttons quick wiring



GW 35 021 W
1P-10 A
Illuminable (*)



GW 35 022 W
1P-10 A
Backlit



GW 35 026 W
1P-10 A
Backlit

Energy sockets - white

German socket-outlet quick wiring



GW 35 206 W
2P+E-16 A-250 V ac
Illuminable (*)

German socket-outlets screw wiring



GW 35 207 W
2P+E-16 A-250 V ac
Illuminable (*)



GW 35 203 W
2P+E-16 A-250 V ac
IP40 - With lid
Illuminable (*)



GW 35 204 W
2P+E-16 A-250 V ac
Double

French socket-outlet quick wiring



GW 35 216 W
2P+E-16 A-250 V ac
Illuminable (*)

French socket-outlets screw wiring



GW 35 212 W
2P+E-16 A-250 V ac
Illuminable (*)



GW 35 213 W
2P+E-16 A-250 V ac
IP40 - With lid
Illuminable (*)



GW 35 214 W
2P+E-16 A-250 V ac
Double

Dimmers - white

Universal dimmer




GW 35 301 W
4-160 W
With two-way switch
230 V ac-50 Hz

(*) supplied without LED signalling unit

Data sockets - white

TV socket




GW 35 261 W
Direct - 0 db

Telephone socket




GW 35 251 W
RJ11


Data sockets




GW 35 271 W
RJ45 cat.5e
UTP



GW 35 272 W
RJ45 cat.5e
FTP



GW 35 273 W
RJ45 cat.6
UTP



GW 35 274 W
RJ45 cat.6
FTP



GW 35 280 W
AMP/Keystone
Jack adapter

USB and HDMI couplers



GW 38 056
HDMI coupler



GW 38 057
USB coupler

Accessories

LED signalling unit



GW 35 981
230 V ac-50/60 Hz

Lenses with illuminated symbol



GW 35 986
Lens kit

Protective cover

GW 35 996
For painting

Wall-mounting boxes - IP40




GW 35 911
1 gang



GW 35 912
2 gang


Supports for modular devices

Support



GW 35 991

All ChoruSmart modular devices (max. 2 modules) can be fitted with GW35991 supports and completed with DAHLIA plates.




Dahlia devices are suitable for Ø 60 mm round boxes. They can be used with all the Gewiss round boxes. They can be mounted on the Gewiss GW24231 square boxes only with screws (not with claws).

Dahlia


White monobloc devices

With an elegant appearance and classic shapes, the wiring device system Dahlia complements the decor of the home with minimal and essential forms. Colours and finishes: glossy white, bright and versatile. Ideal for flush-mounting solutions (for square and round boxes) and surface-mounting solutions.



COMMAND - WHITE VERSION

Command devices - quick wiring terminals




GW 35 001 W

One-way switches 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 031 W	1P - 10AX illuminable	Neutral	100 W	10/100
GW 35 002 W	1P - 10 AX backlit	Neutral	100 W	10/100
GW 35 006 W	1P - 10 AX backlit	With replaceable neutral lens	100 W	10/100

CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 003 W

One-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
GW 35 003 W	2P - 10 AX illuminable	Neutral	0/1	100 W	10/100

CHARACTERISTICS: the illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 051 W

Double one-way switch 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 051 W	Double 1P - 10 AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 011 W

Two-way switches 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 071 W	1P - 10AX illuminable	Neutral	100 W	10/100
GW 35 012 W	1P - 10 AX backlit	Neutral	100 W	10/100
GW 35 016 W	1P - 10 AX backlit	With replaceable neutral lens	100 W	10/100

CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

Double two-way switch 1P - 250 V ac




GW 35 052 W

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 052 W	Double 1P - 10 AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Intermediate switch 1P - 250 V ac




GW 35 015 W

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 015 W	1P - 10AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Push-buttons 1P - 250 V ac



GW 35 021 W

Code	Description	Button key	Pack Carton
GW 35 021 W	1P - 10A illuminable	Neutral	10/100
GW 35 022 W	1P - 10 A backlit	Neutral	10/100
GW 35 026 W	1P - 10 A backlit	With replaceable neutral lens	10/100


CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Dahlia - Monobloc devices

POWER - WHITE VERSION

German standard socket-outlets - quick wiring terminals




GW 35 206 W

German standard socket-outlet - 250 V ac

Code	Description	For plug pins	Pack Carton
GW 35 206 W	2P+E - 16A	Ø 4.8 mm	10/100

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

German standard socket-outlets - screw terminals




GW 35 207 W

German standard socket-outlets with front tightening terminals - 250 V ac

Code	Description	Type	For plug pins	Pack Carton
GW 35 207 W	2P+E - 16A	-	Ø 4.8 mm	10/100
GW 35 203 W	2P+E - 16A	With lid	Ø 4.8 mm	10/100
GW 35 204 W	2P+E - 16A	Double	Ø 4.8 mm	6/60

CHARACTERISTICS: with safety shields. GW35203W equipped with rigid transparent lid with glossy finish and degree of protection IP40 with closed lid. GW35207W and GW35203W pre-arranged for housing miniature led lamp units (not included).
NOTES: front access terminals with screw wiring.

French standard socket-outlets - quick wiring terminals




GW 35 216 W

French standard socket-outlet - 250 V ac

Code	Description	For plug pins	Pack Carton
GW 35 216 W	2P+E - 16A	Ø 4 / 4.8 mm	10/100

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

French standard socket-outlets - screw terminals



GW 35 212 W


French standard socket-outlets with front tightening terminals - 250 V ac

Code	Description	Type	For plug pins	Pack Carton
GW 35 212 W	2P+E - 16A	-	Ø 4 / 4.8 mm	10/100
GW 35 213 W	2P+E - 16A	With lid	Ø 4 / 4.8 mm	10/100
GW 35 214 W	2P+E - 16A	Double	Ø 4 / 4.8 mm	6/60

CHARACTERISTICS: with safety shields. GW35213W equipped with rigid transparent lid with glossy finish and degree of protection IP40 with closed lid. GW35212W and GW35213W pre-arranged for housing miniature led lamp units (not included).
NOTES: front access terminals with screw wiring.

DIMMERS - WHITE VERSION

Dimmers - Screw terminals



GW 35 301 W


Universal rotating electronic regulator

Code	Supply voltage	Pack Carton
GW 35 301 W	230V ac - 50Hz	6/60

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (20-160W), low voltage halogen lamps (12Vac) with electronic transformers (40-160W), LED lamps 230V AC with dimmer functions (4-160W), low voltage LED lamps (12Vac) with electronic transformers (4-110W). Rotary command with two-way switch.

DATA - WHITE VERSION

TV sockets




GW 35 261 W

Coaxial TV socket (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	Pack Carton
GW 35 261 W	Direct	0 dB	10/100

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlet suitable for return channel.

Telephone sockets



GW 35 251 W


International standard telephone sockets

Code	Description	Connection	Pack Carton
GW 35 251 W	RJ11	Screw-on terminals	10/100

APPLICATIONS: telephone, telefax, modem.

Dahlia - Monobloc devices

Data sockets




GW 35 271 W

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	Pack Carton
GW 35 271 W	RJ45	4	5e	UTP	Toolless	10/100
GW 35 272 W	RJ45	4	5e	FTP	Toolless	10/100
GW 35 273 W	RJ45	4	6	UTP	Toolless	10/100
GW 35 274 W	RJ45	4	6	FTP	Toolless	10/100

APPLICATIONS: LAN networks up to 100 MHz (e.g. Ethernet or Token Ring networks) for cat. 5e; LAN networks up to 250 MHz (e.g. video conference or video control systems) for cat. 6.



GW 35 280 W

Adapter for housing data connectors

Code	Compatibility	Pack Carton
GW 35 280 W	AMP / Keystone Jack	10/100

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (ChoruSmart, System and Dahlia) with Keystone Jack coupling.

USB and HDMI couplers




GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

Support for ChoruSmart modular devices



GW 35 991

Support

Code	Description	Fixing	Pack Carton
GW 35 991	For Dahlia plates	With clutches/Screws	20/200

CHARACTERISTICS: support equipped with fixing clutches, also pre-arranged for screw fixing.
APPLICATIONS: suitable for ChoruSmart modular devices.

Dahlia - Monobloc devices

Accessories



GW 35 981

Miniature led lamp unit

Code	Lamp voltage	Colour	Power	Pack Carton
GW 35 981	230V ac - 50/60 Hz	Amber	0.6 W	50/500

NOTES: the miniature led lamps are supplied with power supply cables (length 10 cm).
APPLICATIONS: suitable for housing into backlit and illuminable switches and single socket-outlets.



GW 35 986

Lenses with illuminated symbols

Code	Description	Pack Carton
GW 35 986	Lens kit	1/50

NOTES: to be used in place of the neutral lens in the command devices.
The kit includes: 10 pieces of lens with the "Light" symbol, 10 pieces with the "Stair light" symbol, 10 pieces with the "Key" symbol and 10 pieces with the "Bell" symbol.



GW 35 996

Protective cover for painting

Code	Description	Colour	Pack Carton
GW 35 996	1 gang	Transparent	50/800

CHARACTERISTICS. total protection during painting and finishing operations. Snap-in mounting to facilitate assembly and removal operation.
NOTES: available in 5-piece strip.



GW 35 911

Wall-mounting boxes for Dahlia plates

Code	Description	Colour	Pack Carton
GW 35 911	1 gang	White	10/80
GW 35 912	2 gang	White	5/40

CHARACTERISTICS: plate not included. GW35911 requires a Dahlia 1 gang plate (GW35901xx); GW35912 requires a Dahlia 2 gang plate (GW35902xx).




Dahlia




Scan the QR Code and find out all the technical informations.

DAHLIA RANGE



The socket-outlets are all provided with integral child protection safety shields.

SCREW-FREE



Quick wiring terminals with colour-coded cable entries for switches and screwless sockets.

EXPANDABLE WITH CHORUSMART



The special frame support allows the integration of the Dahlia range with the ChoruSmart modular devices, picking up whatever ChoruSmart device you should need. The support has to be completed with Dahlia plates.

Dahlia

Switches - ivory

One-way switches quick wiring



GW 35 001 Y
1P-10 AX
Illuminable (*)



GW 35 002 Y
1P-10 AX
Backlit



GW 35 006 Y
1P-10 AX
Backlit



GW 35 003 Y
2P-10 AX
Illuminable (*)



GW 35 051 Y
1P-10 AX
Double one-way switch

Two-way switches quick wiring



GW 35 011 Y
1P-10 AX
Illuminable (*)



GW 35 012 Y
1P-10 AX
Backlit



GW 35 016 Y
1P-10 AX
Backlit



GW 35 052 Y
1P-10 AX
Double two-way switch

Intermediate switch quick wiring



GW 35 015 Y
1P-10 AX

Push-buttons quick wiring



GW 35 021 Y
1P-10 A
Illuminable (*)




GW 35 022 Y
1P-10 A
Backlit



GW 35 026 Y
1P-10 A
Backlit


Energy sockets - ivory

German socket-outlet quick wiring



GW 35 201 Y
2P+E-16 A-250 V ac
Illuminable (*)

German socket-outlets screw wiring



GW 35 202 Y
2P+E-16 A-250 V ac
Illuminable (*)



GW 35 203 Y
2P+E-16 A-250 V ac
IP40 - With lid
Illuminable (*)



GW 35 204 Y
2P+E-16 A-250 V ac
Double

French socket-outlet quick wiring



GW 35 211 Y
2P+E-16 A-250 V ac
Illuminable (*)

French socket-outlets screw wiring



GW 35 212 Y
2P+E-16 A-250 V ac
Illuminable (*)



GW 35 213 Y
2P+E-16 A-250 V ac
IP40 - With lid
Illuminable (*)



GW 35 214 Y
2P+E-16 A-250 V ac
Double

Dimmers - ivory

Universal dimmer




GW 35 301 Y
4-160 W
With two-way switch
230 V ac-50 Hz

(*) supplied without LED signalling unit


Data sockets - ivory

TV socket




GW 35 261 Y
Direct - 0 db

Telephone socket




GW 35 251 Y
RJ11


Data sockets




GW 35 271 Y
RJ45 cat.5e
UTP




GW 35 272 Y
RJ45 cat.5e
FTP



GW 35 273 Y
RJ45 cat.6
UTP



GW 35 274 Y
RJ45 cat.6
FTP



GW 35 280 Y
AMP/Keystone
Jack adapter

USB and HDMI couplers



GW 38 056
HDMI coupler



GW 38 057
USB coupler

Accessories

LED signalling unit



GW 35 981
230 V ac-50/60 Hz

Lenses with illuminated symbol



GW 35 986
Lens kit

Protective cover

GW 35 996
For painting

Wall-mounting boxes - IP40




GW 35 911
1 gang



GW 35 912
2 gang


Supports for modular devices

Support



GW 35 991

All ChoruSmart modular devices (max. 2 modules) can be fitted with GW35991 supports and completed with DAHLIA plates.




Dahlia devices are suitable for Ø 60 mm round boxes. They can be used with all the Gewiss round boxes. They can be mounted on the Gewiss GW24231 square boxes only with screws (not with claws).

Dahlia


Ivory monobloc devices

With an elegant appearance and classic shapes, the wiring device system Dahlia complements the decor of the home with minimal and essential forms. Colours and finishes: glossy ivory, bright and versatile. Ideal for flush-mounting solutions (for square and round boxes) and surface-mounting solutions.



COMMAND - IVORY VERSION

Command devices - quick wiring terminals




GW 35 001 Y

One-way switches 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 001 Y	1P - 10AX illuminable	Neutral	100 W	10/100
GW 35 002 Y	1P - 10 AX backlit	Neutral	100 W	10/100
GW 35 006 Y	1P - 10 AX backlit	With replaceable neutral lens	100 W	10/100

CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 003 Y

One-way switch 2P - 250 V ac

Code	Description	Button key	Symbol	Rated power of 230V LED lamps	Pack Carton
GW 35 003 Y	2P - 10AX illuminable	Neutral	0/1	100 W	10/100

CHARACTERISTICS: the illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 051 Y

Double one-way switch 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 051 Y	Double 1P - 10 AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.




GW 35 011 Y

Two-way switches 1P - 250 V ac

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 011 Y	1P - 10AX illuminable	Neutral	100 W	10/100
GW 35 012 Y	1P - 10 AX backlit	Neutral	100 W	10/100
GW 35 016 Y	1P - 10 AX backlit	With replaceable neutral lens	100 W	10/100

CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

Double two-way switch 1P - 250 V ac




GW 35 052 Y

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 052 Y	Double 1P - 10 AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Intermediate switch 1P - 250 V ac




GW 35 015 Y

Code	Description	Button key	Rated power of 230V LED lamps	Pack Carton
GW 35 015 Y	1P - 10AX	Neutral	100 W	10/100

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Push-buttons 1P - 250 V ac



GW 35 021 Y

Code	Description	Button key	Pack Carton
GW 35 021 Y	1P - 10A illuminable	Neutral	10/100
GW 35 022 Y	1P - 10 A backlit	Neutral	10/100
GW 35 026 Y	1P - 10 A backlit	With replaceable neutral lens	10/100


CHARACTERISTICS: the backlit articles include miniature lamp units with amber led lamp. The illuminable articles are pre-arranged for housing miniature led lamp units (not included).

NOTES: rear access terminals with spring quick wiring, no tools necessary.

Dahlia - Monobloc devices

POWER - IVORY VERSION

German standard socket-outlets - quick wiring terminals




GW 35 201 Y

German standard socket-outlet - 250 V ac

Code	Description	For plug pins	Pack Carton
GW 35 201 Y	2P+E - 16A	Ø 4.8 mm	10/100

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

German standard socket-outlets - screw terminals



GW 35 202 Y

German standard socket-outlets with front tightening terminals - 250 V ac

Code	Description	Type	For plug pins	Pack Carton
GW 35 202 Y	2P+E - 16A	-	Ø 4.8 mm	10/100
GW 35 203 Y	2P+E - 16A	With lid	Ø 4.8 mm	10/100
GW 35 204 Y	2P+E - 16A	Double	Ø 4.8 mm	6/60

CHARACTERISTICS: with safety shields. GW35203Y equipped with rigid transparent lid with glossy finish and degree of protection IP40 with closed lid. GW35202Y and GW35203Y pre-arranged for housing miniature led lamp units (not included).
NOTES: front access terminals with screw wiring.

French standard socket-outlets - quick wiring terminals



GW 35 211 Y

French standard socket-outlet - 250 V ac

Code	Description	For plug pins	Pack Carton
GW 35 211 Y	2P+E - 16A	Ø 4 / 4.8 mm	10/100

CHARACTERISTICS: with safety shields. Pre-arranged for housing miniature led lamp units (not included).
NOTES: rear access terminals with spring quick wiring, no tools necessary.

French standard socket-outlets - screw terminals



GW 35 212 Y


French standard socket-outlets with front tightening terminals - 250 V ac

Code	Description	Type	For plug pins	Pack Carton
GW 35 212 Y	2P+E - 16A	-	Ø 4 / 4.8 mm	10/100
GW 35 213 Y	2P+E - 16A	With lid	Ø 4 / 4.8 mm	10/100
GW 35 214 Y	2P+E - 16A	Double	Ø 4 / 4.8 mm	6/60

CHARACTERISTICS: with safety shields. GW35213Y equipped with rigid transparent lid with glossy finish and degree of protection IP40 with closed lid. GW35212Y and GW35213Y pre-arranged for housing miniature led lamp units (not included).
NOTES: front access terminals with screw wiring.

DIMMERS - IVORY VERSION

Dimmers - Screw terminals



GW 35 301 Y


Universal rotating electronic regulator

Code	Supply voltage	Pack Carton
GW 35 301 Y	230V ac - 50Hz	6/60

CHARACTERISTICS: for the regulation and switching of incandescent and halogen lamps 230V AC (20-160W), low voltage halogen lamps (12Vac) with electronic transformers (40-160W), LED lamps 230V AC with dimmer functions (4-160W), low voltage LED lamps (12Vac) with electronic transformers (4-110W). Rotary command with two-way switch.

DATA - IVORY VERSION

TV sockets




GW 35 261 Y

Coaxial TV socket (5-2400 MHz), class A shielding - male IEC connector Ø 9.5 mm

Code	Description	Attenuation	Pack Carton
GW 35 261 Y	Direct	0 dB	10/100

CHARACTERISTICS: allows the passage of voltage/current of remote power supply and/or control signals towards the user port (max 24V - 500 mA).
APPLICATIONS: socket-outlet suitable for return channel.

Telephone sockets



GW 35 251 Y


International standard telephone sockets

Code	Description	Connection	Pack Carton
GW 35 251 Y	RJ11	Screw-on terminals	10/100

APPLICATIONS: telephone, telefax, modem.

Dahlia - Monobloc devices

Data sockets




GW 35 271 Y

RJ45 sockets

Code	Description	Number pairs	Use category	Cables	Connection	Pack Carton
GW 35 271 Y	RJ45	4	5e	UTP	Toolless	10/100
GW 35 272 Y	RJ45	4	5e	FTP	Toolless	10/100
GW 35 273 Y	RJ45	4	6	UTP	Toolless	10/100
GW 35 274 Y	RJ45	4	6	FTP	Toolless	10/100

APPLICATIONS: LAN networks up to 100 MHz (e.g. Ethernet or Token Ring networks) for cat. 5e; LAN networks up to 250 MHz (e.g. video conference or video control systems) for cat. 6.



GW 35 280 Y

Adapter for housing data connectors

Code	Compatibility	Pack Carton
GW 35 280 Y	AMP / Keystone Jack	10/100

NOTES: with regard to the technological developments and dimensional variants introduced by connector manufacturers, you are advised to check in advance the full compatibility between the connector and the Gewiss adapter.

Adapters for optical fiber



GW 38 335

Angled SC/APC adapter

Code	Type	Tilt	For connectors	Compatibility	Colour	Pack Carton
GW 38 335	Female/Female	40°	SC/APC	Keystone Jack	Green RAL 6018	1/25

CHARACTERISTICS: cable outlet inclined of 40° to the wall line. With ceramic fiber optic sleeve and dust caps. The front output is protected with safety cap and unmissable cord. Suitable to join two single-mode SC/APC fiber optic patch cables.
NOTES: for adapters (ChoruSmart, System and Dahlia) with Keystone Jack coupling.

USB and HDMI couplers




GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System, Playbus and Dahlia) with Keystone Jack type coupling and permutation panels.

Support for ChoruSmart modular devices



GW 35 991

Support

Code	Description	Fixing	Pack Carton
GW 35 991	For Dahlia plates	With clutches/Screws	20/200

CHARACTERISTICS: support equipped with fixing clutches, also pre-arranged for screw fixing.
APPLICATIONS: suitable for ChoruSmart modular devices.

Dahlia - Monobloc devices

Accessories



GW 35 981

Miniature led lamp unit

Code	Lamp voltage	Colour	Power	Pack Carton
GW 35 981	230V ac - 50/60 Hz	Amber	0.6 W	50/500

NOTES: the miniature led lamps are supplied with power supply cables (length 10 cm).
APPLICATIONS: suitable for housing into backlit and illuminable switches and single socket-outlets.



GW 35 986

Lenses with illuminated symbols

Code	Description	Pack Carton
GW 35 986	Lens kit	1/50

NOTES: to be used in place of the neutral lens in the command devices.
The kit includes: 10 pieces of lens with the "Light" symbol, 10 pieces with the "Stair light" symbol, 10 pieces with the "Key" symbol and 10 pieces with the "Bell" symbol.



GW 35 996

Protective cover for painting

Code	Description	Colour	Pack Carton
GW 35 996	1 gang	Transparent	50/800

CHARACTERISTICS. total protection during painting and finishing operations. Snap-in mounting to facilitate assembly and removal operation.
NOTES: available in 5-piece strip.



GW 35 911

Wall-mounting boxes for Dahlia plates

Code	Description	Colour	Pack Carton
GW 35 911	1 gang	White	10/80
GW 35 912	2 gang	White	5/40

CHARACTERISTICS: plate not included. GW35911 requires a Dahlia 1 gang plate (GW35901xx); GW35912 requires a Dahlia 2 gang plate (GW35902xx).



Dahlia




Scan the QR Code and find out all the technical informations.

PROTECTION



The socket-outlets are all provided with integral child protection safety shields.

SCREW-FREE




Quick wiring terminals with colour-coded cable entries for switches and screwless sockets.

EXPANDABLE WITH CHORUSMART



The special frame support allows the integration of the Dahlia range with the ChoruSmart modular devices, picking up whatever ChoruSmart device you should need. The support has to be completed with Dahlia plates.

Smart home & building





Connected Smart Home

Connected Smart Home range

p. 1126

Home & Building Pro

Home & Building Pro range

p. 1150

Connected Smart Home

Supervision

Gateway



Home Gateway 2M
100-240 V ac - 50/60 Hz

GW 10 840 Glossy white
GW 15 840 Satin white
GW 13 840 Sat. natural beige
GW 12 840 Satin black
GW 14 840 Glossy titanium


ECO command devices

Conected ECO push-button panel module



GW A1 291
4 commands

Interchangeable button keys for ECO push-button panel



Button key - 1M

GW 10 819 Glossy white
GW 15 819 Satin white
GW 13 819 Sat. natural beige
GW 12 819 Satin black
GW 14 819 Glossy titanium



Button key - 1M

GW 10 820 Glossy white
GW 15 820 Satin white
GW 13 820 Sat. natural beige
GW 12 820 Satin black
GW 14 820 Glossy titanium

Command devices - AXIAL

Connected 2-way switch modules



GW A1 201
1M
100-240 V ac - 50/60 Hz

GW A1 202
2M
100-240 V ac - 50/60 Hz

Connected dimmer modules



GW A1 221
1M
100-240 V ac - 50/60 Hz

GW A1 222
2M
100-240 V ac - 50/60 Hz

Connected roller shutter modules



GW A1 231
1M
100-240 V ac - 50/60 Hz

GW A1 232
2M
100-240 V ac - 50/60 Hz


Connected 2 commands modules



GW A1 241
1M
100-240 V ac - 50/60 Hz

GW A1 242
2M
100-240 V ac - 50/60 Hz

Auxiliary modules



GW 10 677
1 command - 1M
100-240 V ac - 50/60 Hz

GW 10 678
1 command - 2M
100-240 V ac - 50/60 Hz

GW 10 679
2 commands - 1M
100-240 V ac - 50/60 Hz

GW 10 680
2 commands - 2M
100-240 V ac - 50/60 Hz

Interchangeable button keys for axial modules

Button key - 1M
To be completed with lens

GW 10 551 S Glossy white
GW 15 551 S Satin white
GW 13 551 S Sat. natural beige
GW 12 551 S Satin black
GW 14 551 S Glossy titanium

Button key - 2M
To be completed with lens

GW 10 552 S Glossy white
GW 15 552 S Satin white
GW 13 552 S Sat. natural beige
GW 12 552 S Satin black
GW 14 552 S Glossy titanium

Button key - 1M
To be completed with 2 lenses

GW 10 553 S Glossy white
GW 15 553 S Satin white
GW 13 553 S Sat. natural beige
GW 12 553 S Satin black
GW 14 553 S Glossy titanium

Button key - 2M
To be completed with 2 lenses

GW 10 554 S Glossy white
GW 15 554 S Satin white
GW 13 554 S Sat. natural beige
GW 12 554 S Satin black
GW 14 554 S Glossy titanium

Button key - 1M
With diffuser

GW 10 555 S Glossy white
GW 15 555 S Satin white
GW 13 555 S Sat. natural beige
GW 12 555 S Satin black
GW 14 555 S Glossy titanium

Button key - 2M
With diffuser

GW 10 556 S Glossy white
GW 15 556 S Satin white
GW 13 556 S Sat. natural beige
GW 12 556 S Satin black
GW 14 556 S Glossy titanium


Button key - 1M
With 2 diffusers

GW 10 557 S Glossy white
GW 15 557 S Satin white
GW 13 557 S Sat. natural beige
GW 12 557 S Satin black
GW 14 557 S Glossy titanium

Button key - 2M
With 2 diffusers

GW 10 558 S Glossy white
GW 15 558 S Satin white
GW 13 558 S Sat. natural beige
GW 12 558 S Satin black
GW 14 558 S Glossy titanium

Lenses with illuminating symbols for axial button keys



GW 10 501 A Neutral
GW 10 502 A Light
GW 10 503 A Stair light
GW 10 504 A Table light
GW 10 505 A Bell
GW 10 506 A Burglar alarm
GW 10 507 A Key
GW 10 508 A ON OFF
GW 10 509 A ON
GW 10 510 A OFF
GW 10 511 A Socket-outlet
GW 10 512 A Dimmer
GW 10 513 A Dimmer increase
GW 10 514 A Dimmer decrease
GW 10 515 A Arrow
GW 10 516 A Open
GW 10 517 A Close
GW 10 518 A Roller shutter
GW 10 519 A Roller shutter up
GW 10 520 A Roller shutter down
GW 10 521 A Curtain open
GW 10 522 A Curtain close
GW 10 523 A Floor light
GW 10 524 A Ceiling light
GW 10 525 A Wall light
GW 10 526 A Aisle light
GW 10 527 A Scenario
GW 10 528 A Party
GW 10 529 A In
GW 10 530 A Out
GW 10 531 A Good morning
GW 10 532 A Good night
GW 10 533 A TV
GW 10 534 A Heating
GW 10 535 A Cooling
GW 10 536 A Heating/Cooling
GW 10 537 A Comfort
GW 10 538 A Precomfort
GW 10 539 A Economy
GW 10 540 A Auto
GW 10 541 A Do not disturb (DND)
GW 10 542 A Make up the room (MUR)

Recessed command devices

Connected contact interfaces



GW A1 501
2-channel potential-free
Battery powered



GW A1 502
2-channel
230Vac - 50Hz

Climate management

Connected thermostats



Thermo ICE WiFi
110-230 V ac-50/60 Hz
Wall-mounting

GW 16 970 CB Glossy white
GW 16 970 CL Glossy natural beige
GW 16 970 CN Glossy black
GW 16 970 CT Glossy titanium



Thermostat
2M
100-240 V ac - 50/60 Hz

GW 10 709 Glossy white
GW 15 709 Satin white
GW 13 709 Sat. natural beige
GW 12 709 Satin black
GW 14 709 Glossy titanium

Sensors

Connected sensors



GW 10 856 Glossy white
GW 15 856 Satin white
GW 13 856 Sat. natural beige
GW 12 856 Satin black
GW 14 856 Glossy titanium

Motion sensor
1M
100-240 V ac - 50/60 Hz



GW A1 511 [3]
Range 6m
GW A1 511 A [4]
Range 9m

Motion sensors
Battery powered

GW A1 513
Window sensor
Battery powered



GW A1 512
Smoke sensor
Battery powered



GW A1 514
Water sensor
Battery powered

GW A1 541
Wall-mounting support for water sensor

Actuators

Connected actuators for generic loads



GW 10 826 Glossy white
GW 15 826 Satin white
GW 13 826 Sat. natural beige
GW 12 826 Satin black
GW 14 826 Glossy titanium

1-channel 16 A
with energy meter
1M
100-240 V ac - 50/60 Hz

Recessed actuators

Connected actuators for generic loads



GW A1 521
1-channel 10A
potential-free
230Vac - 50Hz



GW A1 522
2-channel 6A
230Vac - 50Hz



GW A1 523
1-channel 10A
with power meter
230Vac - 50Hz

Connected actuators for roller shutters



GW A1 531
1-channel 6A
230Vac - 50Hz

Smart plug

Connected smart plug



GW A1 526
10A Schuko adapter
with power meter
230Vac

Load management

Connected energy meter



GW A1 918
With load management
100-240 V ac - 50/60 Hz

Load management relay



GW A1 916
P-Comfort
230Vac - 50Hz

Accessories

Power supply and connection



GW A1 700
For EGO SMART plates
100-240 V ac - 50/60 Hz

Blanking modules



GW 10 750 Glossy white
GW 15 750 Satin white
GW 13 750 Sat. natural beige
GW 12 750 Satin black
GW 14 750 Glossy titanium

For housing Zigbee contact interfaces and actuators

Protective covers for painting



GW 16 873
3 modules
GW 16 874
4 modules

For rectangular supports



GW 16 871
For square supports

Supports for DIN rail



DIN rail


GW 16 841
1 module - 1.5 DIN module
GW 16 842
2 modules - 3 DIN modules
GW 16 843
3 modules - 4 DIN modules

Smart supports for EGO SMART plates

Supports for round/square boxes



GW 16 821 N [2]
With clutches - 2 modules



GW 16 822 N [2]
For screws (not included)
2 modules

Supports for rectangular boxes



GW 16 803 N [1]
With screws - 3 modules



GW 16 804 N [1]
With screws - 4 modules

[1] Compatible with the whole range of ONE, GEO, EGO, LUX and ICE plates for rectangular boxes.
[2] Compatible with the whole range of ONE International, GEO International, EGO International and LUX International plates for round/square boxes.
[3] Available until stocks last.
[4] For the date of availability, please contact the GEWISS Sales Organization.

EGO SMART International plates

Painted technopolymer

SATIN WHITE



GW 16 022 S PW 2 modules

CLAY



GW 16 022 S CY 2 modules

NATURAL BEIGE



GW 16 022 S NB 2 modules

DARK SAND



GW 16 022 S DS 2 modules

SATIN BLACK



GW 16 022 S DB 2 modules

MAGNETIC GRAY ▲



GW 16 022 S GR 2 modules

LIGHT BRONZE ▲



GW 16 022 S BR 2 modules

STEEL ▲



GW 16 022 S ST 2 modules

SOFT COPPER ▲



GW 16 022 S CS 2 modules

GOLD ▲



GW 16 022 S SG 2 modules

COPPER ▲




GW 16 022 S CP 2 modules

BROWN SHADE ▲



GW 16 022 S BS 2 modules

Modularity



2 modules

▲ Metallic effect

EGO SMART plates

Painted technopolymer

SATIN WHITE

GW 16 003 S PW 3 modules
GW 16 004 S PW 4 modules

CLAY



GW 16 003 S CY 3 modules
GW 16 004 S CY 4 modules

NATURAL BEIGE



GW 16 003 S NB 3 modules
GW 16 004 S NB 4 modules

DARK SAND



GW 16 003 S DS 3 modules
GW 16 004 S DS 4 modules

SATIN BLACK



GW 16 003 S DB 3 modules
GW 16 004 S DB 4 modules

MAGNETIC GRAY ▲



GW 16 003 S GR 3 modules
GW 16 004 S GR 4 modules

LIGHT BRONZE ▲



GW 16 003 S BR 3 modules
GW 16 004 S BR 4 modules

STEEL ▲



GW 16 003 S ST 3 modules
GW 16 004 S ST 4 modules

SOFT COPPER ▲



GW 16 003 S CS 3 modules
GW 16 004 S CS 4 modules

GOLD ▲



GW 16 003 S SG 3 modules
GW 16 004 S SG 4 modules

COPPER ▲




GW 16 003 S CP 3 modules
GW 16 004 S CP 4 modules

BROWN SHADE ▲




GW 16 003 S BS 3 modules
GW 16 004 S BS 4 modules

Modularity



3 modules



4 modules

▲ Metallic effect

Connected Smart Home

Connected Smart Home range

The connected system, based on the Zigbee wireless protocol, offers a full range of solutions for smart homes and small offices that are suitable for both new buildings and renovations. It enables you to control safety, comfort and consumption, through a unique user experience, using the Home Gateway APP and EGO Smart plates. The system integrates with the Google Home IoT platforms, Amazon Alexa and IFTTT, and all functions can be controlled with Google and Alexa voice assistants.





SYSTEM SUPERVISION

Gateway



GW 14 840

Home gateway

Code	Colour	Supply voltage	No. modules	Pack Carton
GW 10 840	Glossy white	100 ÷ 240 V ac - 50/60 Hz	2	1/2
GW 15 840	Satin white	100 ÷ 240 V ac - 50/60 Hz	2	1/2
GW 13 840	Natural satin beige	100 ÷ 240 V ac - 50/60 Hz	2	1/2
GW 12 840	Satin black	100 ÷ 240 V ac - 50/60 Hz	2	1/2
GW 14 840	Glossy titanium	100 ÷ 240 V ac - 50/60 Hz	2	1/2

CHARACTERISTICS: multiprotocol gateway provided with ZigBee, Wi-Fi and Bluetooth (BLE) interfaces.
APPLICATIONS: the device enables the configuration, supervision, command and control of the smart home installation via the cloud. Management of functions and access to the system's data is done through a cloud platform, via a dedicated app (smartphone and tablet). System configuration is carried out through this device using the same app.
NOTES: an Internet connection is required in the system. The Bluetooth connection is only used when configuring devices.

AXIAL COMMAND DEVICES

Connected 2-way switch modules



GW A1 201

Connected axial 2-way switch modules - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW A1 201	100 ÷ 240 V ac - 50/60 Hz	1 NO / NC 2 A (AC1) 240 V ac	1	1/12
GW A1 202	100 ÷ 240 V ac - 50/60 Hz	1 NO / NC 2 A (AC1) 240 V ac	2	1/6

CHARACTERISTICS: devices for controlling 1 On/Off load through a live output contact, with indicative measurement of the power and energy consumed (measurements also transmitted on Zigbee). Suitable for control of incandescent and halogen lamps (240Vac): 4-500W, LED lamps (240Vac): 4-100W, fluorescent lamps (240Vac): 4-120W, halogen lamps powered by electronic transformers (240Vac): 4-250VA. Local push button with axial activation for control of the lamps connected to the device.
Equipped with 2 inputs (auxiliary axial controls, traditional push-buttons and switches, sensors, etc.) to replicate the local control of the lamp or send Zigbee commands and statuses.
The devices are equipped with a blue LED that can be configured to facilitate localisation at night or to signal the local load status and are designed to power the EGO SMART plate within which they are housed.
APPLICATIONS: On/off and timed control of the lamp connected to the devices using the local push-button. The lamp can also be controlled via Zigbee from other devices connected to the network (control unit, scenarios). The inputs can be used to add control points for the local lamp connected to the device, Zigbee commands to other actuators (on/off control and lamp dimming, roller-shutter and Venetian blind control, generic load command, scenarios) or to send sensor statuses over the ZigBee network.
When these devices are used in conjunction with the EGO SMART Plate, an additional Zigbee command can be sent, activated by the push-button on the device when "SHIFT" is enabled from the SMART Plate.
NOTES: The devices must be completed with a front button key: GWA1201 with the GW1x551S or GW1x555S button keys; GWA1202 with the GW1x552S or GW1x556S button keys.

Connected dimmer modules



GW A1 221

Connected axial dimmer modules - ZigBee

Code	Supply voltage	Power	No. modules	Pack Carton
GW A1 221	100 ÷ 240 V ac - 50/60 Hz	4-150 W 240 V ac	1	1/12
GW A1 222	100 ÷ 240 V ac - 50/60 Hz	4-150 W 240 V ac	2	1/6

CHARACTERISTICS: devices for the control of 1 dimmable lighting device. Suitable for incandescent, halogen, LED and fluorescent lamps (240Vac): 4-150W, halogen lamps powered by electronic transformers (240Vac): 4-150VA. Trailing edge load driver mode.
Two axial-operated local buttons for dimming the lamp connected to the device.
Equipped with 2 inputs (auxiliary axial controls, traditional push-buttons and switches, sensors, etc.) to replicate the local control of the lamp or to send Zigbee commands and statuses.
The devices are equipped with two blue LEDs that can be configured to facilitate localisation at night or to display the local load status.
APPLICATIONS: Control of the dimmable lamp connected to the devices via local push-buttons. The lamp can also be controlled via Zigbee by other devices connected to the network (control unit, scenarios). The inputs can be used to add control points for the local lamp connected to the device, Zigbee commands to other actuators (on/off control and lamp dimming, roller-shutter and Venetian blind control, generic load command, scenarios) or to send sensor statuses over the Zigbee network.
Use of these devices in conjunction with the EGO SMART plate enables 2 additional Zigbee commands to be sent. These can be activated with the push-buttons on the device when the "SHIFT" feature is enabled from the SMART plate.
NOTES: The devices must be completed with a front button key: GWA1221 must be completed with the GW1x553S or GW1x557S button keys; GWA1222 must be completed with the GW1x554S or GW1x558S button keys.

Connected roller shutter modules



GW A1 231

Connected axial roller shutter modules - ZigBee

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW A1 231	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	1	1/12
GW A1 232	100 ÷ 240 V ac - 50/60 Hz	2,3 A 240 V ac (according to IEC 60669-2-1)	2	1/6

CHARACTERISTICS: devices for controlling a motor for roller shutters, curtains, venetian blinds, roller blinds, etc., via 2 interlocked output contacts. Two local push buttons with axial activation enable operation of the motor connected to the device.

Equipped with 2 inputs (auxiliary axial commands, traditional switches and push buttons, sensors etc.) to replicate local control of the motor or for sending ZigBee commands and status.

The devices are equipped with two blue LEDs that can be configured to facilitate localisation at night or to indicate the motor operation in progress and are designed to supply power to the EGO SMART plate within which they are housed.

APPLICATIONS: control of 1 motor connected to the device via local push buttons. The motor can also be controlled via ZigBee by other devices connected to the network (up/down commands, scenarios). Using the inputs, it is possible to add local motor-control points connected to the device, ZigBee commands to other actuators (on/off and lamp dimming control, roller shutter and venetian blind control, generic load control, scenarios) or send sensor status over the ZigBee network.

Using this device in combination with the EGO SMART plate, 2 further ZigBee commands can be sent, activated via the push buttons on the device when the SMART plate has the "SHIFT" function enabled.

NOTES: the devices must be completed with a front push button: GWA1231 must be completed with push buttons GW1x553S or GW1x557S; GWA1232 must be completed with push buttons GW1x554S or GW1x558S.

Connected command modules



GW A1 241

Connected axial 2 commands modules - ZigBee

Code	Supply voltage	No. of channels	No. modules	Pack Carton
GW A1 241	100 ÷ 240 V ac - 50/60 Hz	2	1	1/12
GW A1 242	100 ÷ 240 V ac - 50/60 Hz	2	2	1/6

CHARACTERISTICS: devices for the sending of 2 independent ZigBee commands via the operation of 2 local push buttons with axial activation.

Equipped with 2 inputs (auxiliary axial commads, traditional switches and push buttons, sensors etc.) for sending ZigBee commands and status.

The devices are equipped with two blue LEDs that can be configured to facilitate localisation at night or to display the status of the loads with on/off type controls and are designed to supply power to the EGO SMART plate within which they are housed.

APPLICATIONS: sending of 2 ZigBee commands (On/off and lamp dimming commands, roller shutter command, generic load command, scenarios). Using the inputs, it is possible to add ZigBee commands to other actuators (lamp on/off and dimming control, roller shutter and Venetian blind control, generic load control, scenarios) or send sensor status over the ZigBee network.

Using this device in combination with the EGO SMART plate, 2 further ZigBee commands can be sent, activated via the push buttons on the device when the SMART plate has the "SHIFT" function enabled.

NOTES: the devices must be completed with a front push button: GWA1241 must be completed with push buttons GW1x553S or GW1x557S; GWA1242 must be completed with push buttons GW1x554S or GW1x558S.

Auxiliary modules



GW 10 677

1-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 677	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	1	1/12
GW 10 678	100 ÷ 240 V ac - 50/60 Hz	1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary commands to use in combination with ZigBee connected axial commands or to EVO axial commands.

The devices are equipped with a blue LED that can be configured to facilitate localisation at night or to display the status of the load.

APPLICATIONS: connected to the local inputs of the connected axial commands, they enable the replication of local load control or the sending of ZigBee commands; connected to the local inputs of the EVO axial commands, they enable the replication of local load control or the management of centralised controls.

NOTES: the devices must be completed with a front push button: GW10677 must be completed with push buttons GW1x551S or GW1x555S; GW10678 must be completed with push buttons GW1x552S or GW1x556S.



GW 10 679

2-command auxiliary axial modules

Code	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 679	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	1	1/12
GW 10 680	100 ÷ 240 V ac - 50/60 Hz	n. 2 x 1A (AC1)	2	1/6

CHARACTERISTICS: auxiliary commands to be used in combination with ZigBee connected axial commands or to EVO axial commands.

The devices are equipped with two blue LEDs that can be configured to facilitate localisation at night or to display the status of the load.

APPLICATIONS: connected to the local inputs of the connected axial commands, they enable the replication of local load control or the sending of ZigBee commands; connected to the local inputs of the EVO axial commands, they enable the replication of local load control or the management of centralised controls.

NOTES: the devices must be completed with a front push button: GWA10679 must be completed with push buttons GW1x553S or GW1x557S; GWA10680 must be completed with push buttons GW1x554S or GW1x558S.

Interchangeable button keys and lenses for axial command modules



GW 14 551 S

Interchangeable button keys for axial command modules

Code	Colour	Button key	No. modules	Pack Carton
GW 10 551 S	Glossy white	To be completed with lens	1	1/48
GW 15 551 S	Satin white	To be completed with lens	1	1/48
GW 13 551 S	Natural satin beige	To be completed with lens	1	1/48
GW 12 551 S	Satin black	To be completed with lens	1	1/48
GW 14 551 S	Glossy titanium	To be completed with lens	1	1/48
GW 10 552 S	Glossy white	To be completed with lens	2	1/48
GW 15 552 S	Satin white	To be completed with lens	2	1/48
GW 13 552 S	Natural satin beige	To be completed with lens	2	1/48
GW 12 552 S	Satin black	To be completed with lens	2	1/48
GW 14 552 S	Glossy titanium	To be completed with lens	2	1/48
GW 10 553 S	Glossy white	To be completed with 2 lenses	1	1/48
GW 15 553 S	Satin white	To be completed with 2 lenses	1	1/48
GW 13 553 S	Natural satin beige	To be completed with 2 lenses	1	1/48
GW 12 553 S	Satin black	To be completed with 2 lenses	1	1/48
GW 14 553 S	Glossy titanium	To be completed with 2 lenses	1	1/48
GW 10 554 S	Glossy white	To be completed with 2 lenses	2	1/48
GW 15 554 S	Satin white	To be completed with 2 lenses	2	1/48
GW 13 554 S	Natural satin beige	To be completed with 2 lenses	2	1/48
GW 12 554 S	Satin black	To be completed with 2 lenses	2	1/48
GW 14 554 S	Glossy titanium	To be completed with 2 lenses	2	1/48
GW 10 555 S	Glossy white	With 1 diffuser	1	1/48
GW 15 555 S	Satin white	With 1 diffuser	1	1/48
GW 13 555 S	Natural satin beige	With 1 diffuser	1	1/48
GW 12 555 S	Satin black	With 1 diffuser	1	1/48
GW 14 555 S	Glossy titanium	With 1 diffuser	1	1/48
GW 10 556 S	Glossy white	With 1 diffuser	2	1/48
GW 15 556 S	Satin white	With 1 diffuser	2	1/48
GW 13 556 S	Natural satin beige	With 1 diffuser	2	1/48
GW 12 556 S	Satin black	With 1 diffuser	2	1/48
GW 14 556 S	Glossy titanium	With 1 diffuser	2	1/48
GW 10 557 S	Glossy white	With 2 diffusers	1	1/48
GW 15 557 S	Satin white	With 2 diffusers	1	1/48
GW 13 557 S	Natural satin beige	With 2 diffusers	1	1/48
GW 12 557 S	Satin black	With 2 diffusers	1	1/48
GW 14 557 S	Glossy titanium	With 2 diffusers	1	1/48
GW 10 558 S	Glossy white	With 2 diffusers	2	1/48
GW 15 558 S	Satin white	With 2 diffusers	2	1/48
GW 13 558 S	Natural satin beige	With 2 diffusers	2	1/48
GW 12 558 S	Satin black	With 2 diffusers	2	1/48
GW 14 558 S	Glossy titanium	With 2 diffusers	2	1/48

NOTES: to be used to complete the ZigBee connected axial commands, EVO axial commands and auxiliary axial commands.



Lenses with illuminating symbols for axial button keys

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTE: for use to customise the interchangeable push buttons for axial controls with 1 and 2 lenses.

ECO COMMAND DEVICES

ECO connected push-button panel module




GW A1 291

Connected 4 commands ECO push button panel - ZigBee - flush and surface mounting

Code	Supply voltage	No. of channels	No. modules	Pack Carton
GW A1 291	None	4	2	1

CHARACTERISTICS: device for sending 4 independent Zigbee commands via activation by the local 4 push buttons.
The device can be installed both flush (ChoruSmart supports) and surface mounted. For surface mounted installation, it can be completed with ONE, GEO, LUX, ICE and EGO plates in both the 2-gang rectangular version and the international 2-gang version.
The device does not require power (neither from the mains nor from batteries).
APPLICATIONS: sending 4 Zigbee commands (on/off command and lamp dimming, roller-shutter control, generic load command, scenarios) using local buttons.
NOTES: The push-button panel must be completed with front buttons: with 2 push button keys GW1x819 of 1 module or 1 push button key GW1x820 of 2 modules.
The device cannot be used to control actuators: GWA1521, GWA1522, GWA1523, GWA1526, GWA1531 and the local relay of GWA1916.
ACCESSORIES SUPPLIED: base and fitting KIT (screws, wall-plugs and bi-adhesive strips) for surface mounting, adapter for flush mounting on ChoruSmart supports.



GW 14 819

Replaceable push button keys for connected 4-channel ECO push button panel - ZigBee

Code	Colour	No. modules	Pack Carton
GW 10 819	Glossy white	1	2/48
GW 15 819	Satin white	1	2/48
GW 13 819	Natural satin beige	1	2/48
GW 12 819	Satin black	1	2/48
GW 14 819	Glossy titanium	1	2/48
GW 10 820	Glossy white	2	1/48
GW 15 820	Satin white	2	1/48
GW 13 820	Natural satin beige	2	1/48
GW 12 820	Satin black	2	1/48
GW 14 820	Glossy titanium	2	1/48

NOTES: to be used to complete the connected push-button panel module ECO ZigBee GWA1291.

RECESSED COMMAND DEVICES

Connected contact interfaces



GW A1 501

2-channel connected contact interfaces - ZigBee

Code	Supply voltage	No. input channels	Input voltage	Max cable length	Dimensions LxHxD (mm)	Pack Carton
GW A1 501	Battery powered	2	Potential-free	15 m	42x40x20	1/4
GW A1 502	230V ac - 50 Hz	2	230V ac	-	42x40x20	1/4

CHARACTERISTICS: interface for the connection of 2 independent input contacts (auxiliary axial commands, push buttons and traditional switches sensors etc.), potential-free (GWA1501) or live (GWA1502). GWA1501 powered by CR2032-type battery (replaceable).

APPLICATIONS: allows commands to be sent for ON-OFF, timed, roller shutters and Venetian blinds, dimmers, scenarios, priority commands and signalling the current state of the contact.

NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

SENSORS

Connected sensors



GW 14 856

Connected movement sensors - ZigBee

Code	Colour	Max range	Light sensor	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 856	Glossy white	8 m	1 - 1000 lux	100 ÷ 240 V ac - 50/60 Hz	1 NO 2 A (AC1) 240 Vac	1	1/12
GW 15 856	Satin white	8 m	1 - 1000 lux	100 ÷ 240 V ac - 50/60 Hz	1 NO 2 A (AC1) 240 Vac	1	1/12
GW 13 856	Natural satin beige	8 m	1 - 1000 lux	100 ÷ 240 V ac - 50/60 Hz	1 NO 2 A (AC1) 240 Vac	1	1/12
GW 12 856	Satin black	8 m	1 - 1000 lux	100 ÷ 240 V ac - 50/60 Hz	1 NO 2 A (AC1) 240 Vac	1	1/12
GW 14 856	Glossy titanium	8 m	1 - 1000 lux	100 ÷ 240 V ac - 50/60 Hz	1 NO 2 A (AC1) 240 Vac	1	1/12

CHARACTERISTICS: motion sensor with detection based on the set brightness threshold. Fixed lens. Parameters that can be set during configuration via the APP: brightness threshold value, shutdown time after presence detection.

Local live contact for direct control of the load, connectable loads: incandescent and halogen lamps (240Vac): 500W, LED lamps (240Vac): 100W, fluorescent lamps (240Vac): 120W, halogen lamps powered by electronic transformers (240Vac): 250VA.

Equipped with 2 inputs (auxiliary axial controls, traditional push-buttons and switches, sensors, etc.) to replicate the direct control of the lamp/load connected to the local relay or to send Zigbee commands and statuses. The device has a blue LED to indicate motion detection (regardless of the brightness threshold).

APPLICATIONS: the devices detect a person's movement and send the signal via Zigbee which activates lamps and/or loads. The connected lamp and/or load can be activated directly through the local contact. Energy savings: light control of the environments or areas concerned only when there is traffic/presence of people.

NOTES: do not install the product in watertight plates: the lid membrane does not allow the detector lens to function correctly.

Connected movement sensors - ZigBee - IP31



GW A1 511

Code	Max range	Light sensor	Temperature sensor	Colour	Dimensions LxHxD (mm)	Pack Carton
GW A1 511	6 m	3...70.000 lux	0...50 °C	White	82x82x28	1/2
GW A1 511 A	9 m	3...70.000 lux	0...50 °C	White	71x71x21	1

CHARACTERISTICS: motion sensors with horizontal detection angle: ±45° and vertical detection angle: ±45°. Include a brightness sensor and a temperature sensor. GWA1511A: battery power supply type AA (x2); GWA1511: battery power supply type CR123 (replaceable).

NOTES: wall or shelf installation via included accessories.

For the control of actuations, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202, GWA1221 or GWA1222 (max 5 sensors per actuator) or with the connected Zigbee actuators GWA1526, GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202, GWA1221, GWA1222 can only be controlled in combination with the "Home Gateway" GW1x840.

GWA1511A: please contact GEWISS sales team for the date of availability. GWA1511 available while stock lasts.

Connected window sensor - ZigBee - IP40



GW A1 513

Code	Sensor type	Temperature sensor	Material	Colour	Dimensions LxHxD (mm)	Pack Carton
GW A1 513	Magnetic	0...50 °C	Plastic	White	76x26x17	1/4

CHARACTERISTICS: the sensor detects the opening and closing of doors and windows and includes a temperature sensor. Powered with 2 AAA type batteries (replaceable).

NOTES: Installation on doors or windows.

Use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator) or with the ZigBee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202 can only be controlled in combination with the "Home Gateway" GW1x840.

NEWS

Connected Smart Home



GW A1 512

Connected smoke sensor - ZigBee - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 512	85 dB/3 m	0…50 °C	White	Ø 65x40	1/3

CHARACTERISTICS: the sensor detects the presence of smoke and includes a temperature sensor. Power supplied by a CR123 type (replaceable) battery.
NOTES: wall or ceiling installation.
To operate a solenoid valve, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator if the actuator is configured for automatic solenoid reset; unlimited sensors for manual reset) or with Zigbee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator if the actuator is configured for automatic solenoid reset; unlimited sensors for manual reset). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202 can only be commanded in conjunction with the "Home Gateway" GW1x840.



GW A1 514

Connected water sensor - ZigBee - IP20

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0…50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the sensor detects the presence of water and includes a temperature sensor. CR123 (replaceable) type battery power supply.
NOTES: floor installation or alternative wall mounted option using the accessory GWA1541.
To activate a solenoid valve, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator if actuator is configured for automatic solenoid reset; unlimited sensors for manual reset) or with Zigbee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator if actuator is configured for automatic solenoid reset; unlimited sensors for manual reset). Zigbee connected actuators GW1x826, GWA1201, GWA1202 can only be controlled in conjunction with the GW1x840 Home Gateway.



GW A1 541

Wall-mounting support for flood alarm

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.

ACTUATORS

Connected actuators for generic loads with energy meter



GW 14 826

Connected 1-channel on/off actuators with energy measurement - ZigBee

Code	Colour	Supply voltage	No. output channels	Output contacts	No. modules	Pack Carton
GW 10 826	Glossy white	100 ÷ 240 V ac - 50/60 Hz	1	1 NO 16 A (AC1) 240 V ac	1	1/12
GW 15 826	Satin white	100 ÷ 240 V ac - 50/60 Hz	1	1 NO 16 A (AC1) 240 V ac	1	1/12
GW 13 826	Natural satin beige	100 ÷ 240 V ac - 50/60 Hz	1	1 NO 16 A (AC1) 240 V ac	1	1/12
GW 12 826	Satin black	100 ÷ 240 V ac - 50/60 Hz	1	1 NO 16 A (AC1) 240 V ac	1	1/12
GW 14 826	Glossy titanium	100 ÷ 240 V ac - 50/60 Hz	1	1 NO 16 A (AC1) 240 V ac	1	1/12

CHARACTERISTICS: 1-channel actuator for controlling loads with a live NO output contact and measurement of the power absorbed and the energy consumed (both measurements transmitted via Zigbee). Local push-button and blue LED for control and display of load status.
Controllable Loads: incandescent and halogen lamps (240Vac): 1920W, LED lamps (240Vac): 200W, fluorescent lamps (240Vac): 200W, halogen lamps powered by electronic transformers (240Vac): 500VA.
Equipped with 1 input (auxiliary axial controls, traditional push-buttons and switches, sensors, etc.) to replicate the local control of the load or to send Zigbee commands and statuses.
The devices are designed to supply power to the EGO SMART plate within which they are housed.
APPLICATIONS: On/off and timed control of the load connected to the devices by local push-button. The load can also be controlled via Zigbee from other devices connected to the network (control unit, scenarios). The input can be used to add control points for the connected local load to the devices, send ZigBee commands to other actuators (on/off command and lamp dimming, roller-shutter and Venetian blind control, control of generic loads, scenarios) or send sensor statuses over the ZigBee network.
Automatic load disconnection: the devices can be configured to disconnect the local load when a defined (power) consumption threshold is exceeded during configuration.
Using this device in combination with the EGO SMART plate, 1 further ZigBee command can be sent, activated via the push button on the device when the SMART plate has the "SHIFT" function enabled.

RECESSED ACTUATORS

Connected actuators for generic loads



GW A1 521

1-channel connected actuator - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of loads through a potential-free output contact (NO). Suitable for controlling incandescent lamps (230 V ac): 2300 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: (230 V ac): 150 W, motors: 500 W. Equipped with 1 input for local control of the output.
APPLICATIONS: ON-OFF control, timed commands, priority commands and scenario management. If used in combination with the ZigBee GWA1514 water sensor, the installation of a push button (NO) is required for the manual opening of the solenoid valve.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.



GW A1 522

2-channel connected actuator - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 522	230V ac - 50 Hz	2	2 NO 6A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 2-channel actuator for the activation of loads through a 230 V output contact (NO). Suitable for controlling incandescent lamps (230 V ac): 1400 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: 150 W, LED lamps (230 V ac): 150 W, motors: 500 W. Equipped with 2 inputs for local control of the outputs.
APPLICATIONS: ON-OFF control, timed commands, priority commands and management of scenarios.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Connected actuators for generic loads with power measurement



GW A1 523

1-channel connected actuator with power meter - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 523	230V ac - 50 Hz	1	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of loads through a 230 V output contact (NO) and measurement of instantaneous power. Suitable for controlling incandescent lamps (230 V ac): 2300 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: (230 V ac): 150 W, motors: 500 W. Equipped with 1 input for local control of the output.
APPLICATIONS: ON-OFF control, timed commands, priority commands and management of scenarios and measurement of instantaneous power.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Connected actuators for roller shutters



GW A1 531

1-channel connected actuator for roller shutters - ZigBee

Code	Supply voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW A1 531	230V ac - 50 Hz	6A-230V ac (compl. 60669-2-1)	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of a motor to operate roller shutters, curtains, Venetian blinds, roller blinds etc. via 2 interlocked output contacts 230 V ac. Suitable for the control of motors: 500 W. Equipped with 2 inputs for local control of the outputs.
APPLICATIONS: controlling operation/adjustment/stop, priority commands, scenario management and alarm signalling.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Connected Smart Home

SMART PLUG

Connected Smart Plug



GW A1 526

Connected Smart Plug 230 V ac - German standard - ZigBee

Code	Type of plug	Socket-outlet type	Dimensions ØxH (mm)	Colour	Pack Carton
GW A1 526	2P+E - 10A	2P+E - 10A	41x45	White	1/2

CHARACTERISTICS: adaptor with socket, side earthing and safety shields. It detects power consumed by the connected loads and sends the data on the ZigBee network.

LOADS MANAGEMENT

Connected energy meter - recessed mounting



GW A1 918

Connected energy meter with load control - Zigbee

Code	Supply voltage	Measurement	Dimensions LxHxD (mm)	Pack Carton
GW A1 918	100 ÷ 240 V ac - 50/60 Hz	Via A.T.	40x40x20 mm	1/4

CHARACTERISTICS: measurement: single phase voltage 100-240Vac 50/60 Hz, maximum current 70A min 0.05A. The device measures the power absorbed and the energy consumed (transmitting the measurements), and implements the load control function (max 10 controllable loads) according to EN 61010-1, EN 61010-2-030. A.T. provided in the package.
APPLICATIONS: measurement and monitoring of electrical consumption (power and energy consumed) of a housing unit or area within a building. Load Control Function: automatically disconnects electrical loads to prevent the electrical meter from tripping when the contractual KW limit is exceeded, thus preventing disruption to the user; the load disconnection and connection sequence can be set during configuration via the APP, by priority or by absorption; The loads to be controlled must be controlled by Zigbee-connected actuators: GW1x826, GWA1201, GWA1202, GWA1221, GWA1222, GWA1523, GWA1526, GWA1521 or GWA1522.
NOTES: The module can be installed in flush-mounted boxes, junction boxes or enclosures. It can aso be installed on ChoruSmart supports using ChoruSmart blanking module GW1x750, it can be mounted on a DIN rail using DIN rail support GW16841 + ChoruSmart GW1x750 blanking module.

Load management relay



GW A1 916

Connected P-Comfort load management relay - Zigbee

Code	Rated voltage (V)	Rated current	Type relay contact	Capacity relay contact	No. of modules EN 50022	Pack Carton
GW A1 916	230V ac	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

APPLICATION: The P-Comfort relay can be installed in electrical systems limited to a maximum power load of 6 kW. In the event of overload due to the simultaneous switching-on of multiple electrical loads, P-Comfort prevents the interruption of electrical power by disconnecting non-preferred loads controlled by ZigBee-connected actuators: GW1x826, GWA1201, GWA1202, GWA1221, GWA1222, GWA1523, GWA1526, GWA1521 or GWA1522, or wired to the relay contact on the device (maximum 10 devices total). The disconnection and reconnection sequence for non-preferred loads can be set by Priority (regardless of load absorption) or by Power (depending on the power absorbed).
NOTES: The Zigbee-connected actuators GW1x826, GWA1201, GWA1202, GWA1221, GWA1222 can only be controlled in combination with the "Home Gateway" GW1x840.

TEMPERATURE ADJUSTMENT

Connected thermostats



GW 14 709

Connected thermostat - ZigBee

Code	Colour	Supply voltage	Output contacts	No. modules	Pack Carton
GW 10 709	Glossy white	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4
GW 15 709	Satin white	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4
GW 13 709	Natural satin beige	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4
GW 12 709	Satin black	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4
GW 14 709	Glossy titanium	100 - 240 V ac/dc - 50/60 Hz	1 NO / NC 5A (AC1) 240 V ac	2	1/4

CHARACTERISTICS: flush-mounted thermostat for the control of heating/cooling systems with manual temperature management and possibility of shutdown. Control algorithms for two-way systems: two points (ON/OFF), proportional-integral (PWM). The thermostat can control a solenoid valve for heating or cooling through a local contact or via Zigbee, in which case the solenoid valve must be controlled by a Zigbee actuator. GWA1521, GWA1522, GWA1523, GW1x826, GWA1201, and GWA1202 Zigbee connected actuators can be used.

The thermostat is equipped with integrated temperature and humidity sensors. The thermostat has an input for a NTC sensor (GW10800 and GW1x900 sensors can be used) for external temperature measurement (e.g., for compensation of temperatures measured locally by the thermostat or for protection in case of underfloor heating/cooling).

APPLICATIONS: climate control (heating or cooling) of a housing unit or area; option to manage a daily or weekly heating/cooling profile via the APP. The device measures humidity, if a threshold (defined during configuration) is exceeded, Zigbee can activate a dehumidification system and display/notify the measurement on the APP.

Use in traditional unconnected systems: the connected thermostat can also be used in traditional unconnected installations. In this case, configuration is not carried out via the APP and the NTC sensor input can only be used to compensate for the temperature measurement detected locally by the thermostat.



GW 16 970 CT

THERMO Ice Wi-Fi thermostat - wall-mounting

Code	Colour	Supply voltage	Temperature adjustment	Output contacts	Pack Carton
GW 16 970 CB	White	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1
GW 16 970 CL	Natural beige	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1/16
GW 16 970 CN	Black	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1
GW 16 970 CT	Titanium	110-230V ac - 50/60Hz	From +5°C to +40°C	Max switching current at 250Vac: 6A (cosΦ = 1); 1,5A (cosΦ = 0,6)	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for two-way systems: two points (ON/OFF), proportional integral (PWM). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch controls (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors and a Wi-Fi interface for setting parameters and programming temperature profiles (timed thermostat function) locally or remotely via specific apps (smartphone and tablet).

APPLICATIONS: the THERMO ICE Wi-Fi can be used:

- as an independent intelligent thermostat (in a stand-alone way), i.e. without the need for a Smart Home system, in this case the configuration and control of the device takes place via the "ThermoICE 2.0" APP; or
- integrated into the Gewiss "Connected Smart Home", in this case the device can interoperate with all the other devices of the "Connected Smart Home" system and is configured and controlled together with all the other functions of the system via the "Home Gateway" APP.

NOTES: wall-mounting with wall-plugs or on 3-modules rectangular boxes (centre distance 83.5 mm) Plate material; technopolymer.

ACCESSORIES

Blanking modules



GW 14 750

Blanking modules for housing ZigBee contacts interfaces and actuators

Code	Colour	No. modules	Pack Carton
GW 10 750	Glossy white	1	1/12
GW 15 750	Satin white	1	1/12
GW 13 750	Natural satin beige	1	1/12
GW 12 750	Satin black	1	1/12
GW 14 750	Glossy titanium	1	1/12

CHARACTERISTICS: 1-module blanking module with pad-printing. Enables the housing and rapid identification of the recessed connected control devices, of the recessed connected actuators and the connected energy meter with load control.

NOTES: snap-in assembly.

DIN rail mounting supports



GW 16 841

Supports for assembling CHORUSMART devices on DIN EN 50022 rail

Code	Description	No. DIN modules	Pack Carton
GW 16 841	1 module	1.5	5/300
GW 16 842	2 modules	3	5/150
GW 16 843	3 modules	4	5/50

CHARACTERISTICS: tool-free manual release system for flush-mounting devices.

NOTES: pay attention when using particularly deep devices (two-pole, three-way switches, movement detectors and IR receivers, relays, German standard socket-outlets with front tightening, quick wiring terminals, British standard socket-outlets, interlocked switched sockets-outlets, shaver sockets-outlets, USB power supplies, MCCB and RCCB, anti-black-out and emergency lamps, ringers and buzzers, thermostats and timed thermostats, programmers, water and gas detectors, timers, dimmers, touch commands, electronic soft-click push buttons with interlock, KNX flush-mounting timed thermostats, etc.) as they may interfere with the DIN rail, preventing the correct passage of the wires.

EGO SMART PLATES

Painted technopolymer

EGO SMART - Satin white



GW 16 003 SPW

Code	Description	For support codes	Pack Carton
GW 16 003 SPW	3 modules	GW16803N	1
GW 16 004 SPW	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Clay



GW 16 003 SCY

Code	Description	For support codes	Pack Carton
GW 16 003 SCY	3 modules	GW16803N	1
GW 16 004 SCY	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same plate box: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART - Natural beige



GW 16 003 SNB

Code	Description	For support codes	Pack Carton
GW 16 003 SNB	3 modules	GW16803N	1
GW 16 004 SNB	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Dark sand



GW 16 003 SDS

Code	Description	For support codes	Pack Carton
GW 16 003 SDS	3 modules	GW16803N	1
GW 16 004 SDS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART - Satin black



GW 16 003 SDB

Code	Description	For support codes	Pack Carton
GW 16 003 SDB	3 modules	GW16803N	1
GW 16 004 SDB	4 modules	GW16804N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Magnetic gray



GW 16 003 SGR

Code	Description	For support codes	Pack Carton
GW 16 003 SGR	3 modules	GW16803N	1
GW 16 004 SGR	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Light bronze



GW 16 003 SBR

Code	Description	For support codes	Pack Carton
GW 16 003 SBR	3 modules	GW16803N	1
GW 16 004 SBR	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.

EGO SMART - Steel



GW 16 003 SST

Code	Description	For support codes	Pack Carton
GW 16 003 SST	3 modules	GW16803N	1
GW 16 004 SST	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply. The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART - Soft copper



GW 16 003 SCS

Code	Description	For support codes	Pack Carton
GW 16 003 SCS	3 modules	GW16803N	1
GW 16 004 SCS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SSG

EGO SMART - Gold

Code	Description	For support codes	Pack Carton
GW 16 003 SSG	3 modules	GW16803N	1
GW 16 004 SSG	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SCP

EGO SMART - Copper

Code	Description	For support codes	Pack Carton
GW 16 003 SCP	3 modules	GW16803N	1
GW 16 004 SCP	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 003 SBS

EGO SMART - Brown shade

Code	Description	For support codes	Pack Carton
GW 16 003 SBS	3 modules	GW16803N	1
GW 16 004 SBS	4 modules	GW16804N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following Smart devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; the connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

EGO SMART INTERNATIONAL PLATES

Painted technopolymer



GW 16 022 SPW

EGO SMART International - Satin white

Code	Description	For support codes	Pack Carton
GW 16 022 SPW	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SCY

EGO SMART International - Clay

Code	Description	For support codes	Pack Carton
GW 16 022 SCY	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SNB

EGO SMART International - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 022 SNB	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SDS

EGO SMART International - Dark sand

Code	Description	For support codes	Pack Carton
GW 16 022 SDS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SDB

EGO SMART International - Satin black

Code	Description	For support codes	Pack Carton
GW 16 022 SDB	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed within the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SGR

EGO SMART International - Magnetic gray

Code	Description	For support codes	Pack Carton
GW 16 022 SGR	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SBR

EGO SMART International - Light bronze

Code	Description	For support codes	Pack Carton
GW 16 022 SBR	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: the plate must be powered by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.



GW 16 022 SST

EGO SMART International - Steel

Code	Description	For support codes	Pack Carton
GW 16 022 SST	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SCS

EGO SMART International - Soft copper

Code	Description	For support codes	Pack Carton
GW 16 022 SCS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SSG

EGO SMART International - Gold

Code	Description	For support codes	Pack Carton
GW 16 022 SSG	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SCP

EGO SMART International - Copper

Code	Description	For support codes	Pack Carton
GW 16 022 SCP	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.



GW 16 022 SBS

EGO SMART International - Brown shade

Code	Description	For support codes	Pack Carton
GW 16 022 SBS	2 modules	GW16821N, GW16822N	1

CHARACTERISTICS: matt finish, metallic effect. The plate has a dot-matrix display on the upper portion, RGB LED strips (along the outer and inner edges at the top and bottom) and a proximity sensor.
APPLICATIONS: visualisation of dynamic icons on the display indicating the functions associated with the devices installed in the plate; event/alarm signalling using the display (messages) and/or RGB led strips.
NOTES: The plate must be supplied with power by one of the following connected devices, which must be installed in the same box as the plate: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242 or GW1x826, or by a dedicated GWA1700 power supply; The connection cable from the plate to the device powering it is included in the plate package.
Codes not held as stock, for delivery times contact your local representative.

ACCESSORIES FOR EGO SMART AND EGO SMART INTERNATIONAL PLATES

Power supply and connection



GW A1 700

Power and communication unit for EGO SMART plate - ZigBee

Code	Supply voltage	Pack Carton
GW A1 700	100 ÷ 240 V ac - 50/60 Hz	1/4

CHARACTERISTICS: device for power supply and communication of the EGO SMART plates.
NOTES: the device must be placed in the flush-mounting box where the EGO SMART plate it powers is installed; installable in ChoruSmart supports using the blanking module GW1x750. The connection between device and the EGO SMART plate must be made using the cable supplied in the EGO SMART packaging.
This device is unnecessary if one of the following devices is already present in the Smart plate box: GWA1201, GWA1202, GWA1231, GWA1232, GWA1241, GWA1242, GW1x826 (any of these devices can power the EGO SMART plate).

Supports for rectangular boxes



GW 16 803 N

Italian standard supports for EGO SMART plates

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 803 N	3 modules	2 screws (included)	Halogen free	6/240
GW 16 804 N	4 modules	2 screws (included)	Halogen free	6/120

CHARACTERISTICS: specific supports for 3 and 4 module Italian standard EGO SMART plates; supports are also compatible with the other Italian standard ChoruSmart 3 and 4 module plates ONE, GEO, LUX, ICE and EGO.

Supports for square and round boxes




GW 16 822 N

International standard supports for EGO SMART plates

Code	Description	Fixing	Characteristics	Pack Carton
GW 16 821 N	2 modules	With fixing clutches (included)	Halogen free	20/120
GW 16 822 N	2 modules	For screws (not included)	Halogen free	20/120

CHARACTERISTICS: GW16821N equipped with fixing clutches for installation on round boxes. Supports specifically for international standard EGO SMART plates; the supports are also compatible with the other ChoruSmart international standard plates, including ONE, GEO, LUX and EGO.
NOTES: GW16822N support can be installed on single round and square boxes or in a horizontal composition; the GW16821N support can be installed on single stand-alone round boxes.

Protective covers for painting



GW 16 873

Protective covers for painting, for CHORUSMART range, Italian Standard

Code	Description	Suitable for support	Colour	Pack Carton
GW 16 873	3 modules	GW16802, GW16803, GW16803N	Transparent	120/480
GW 16 874	4 modules	GW16804, GW16804N	Transparent	60/240

CHARACTERISTICS: total protection during painting and finishing operations.
NOTES: snap in fastening to facilitate installation and removal.



GW 16 871


Protective covers for painting for international standard supports

Code	Description	Suitable for support	Colour	Pack Carton
GW 16 871	2 modules	GW16821, GW16822, GW16823, GW16831, GW16821N, GW16822N	Transparent	60/480

CHARACTERISTICS: total protection during painting and finishing operations.
NOTES: snap in fastening to facilitate installation and removal.



Connected Smart Home



Scan the QR Code and find out all the technical informations.

UNIQUE USER EXPERIENCE



The user can easily control all functions via the APP, voice assistants and the innovative EGO SMART plate, which signals abnormal or alarm situations within the home (e.g., water or gas leaks) and allows the user to increase the control possibilities of smart functions.

A COMPLETE RANGE OF FUNCTIONS



The system offers a wide range of functions to control safety, comfort and energy to meet all application needs.

INTEGRATION WITH IOT DEVICES



Thanks to integration with the Google Home IoT platforms, Amazon Alexa and IFTTT, the system can also interoperate with all IoT devices and systems compatible with these platforms.

Home&Building Pro supervision - KNX and Zigbee

Gateway



Smart Gateway
12Vdc - 1A

GW A9 000
without license

GW A9 002
with unlimited
preloaded license



GW A9 001
Unlimited license
for Smart Gateway

Touch panels



GW A9 007 CB
7" panel - White



GW 90 802 A
Power-supply 24 V dc-2.5 A
100/240 V ac-50/60 Hz

System components - KNX

Self-protected electronic power supplies



GW 90 709
320 mA
220-240 V ac - 50/60 Hz



GW 90 710
640 mA
220-240 V ac - 50/60 Hz

Complementary items



GW 90 708 A
Line/field coupler



GW 90 706 B
KNX/USB interface



GW 90 706 U
KNX/USB stick
interface



GW A9 705
KNX/IP interface



GW A9 707
KNX/IP router

Command devices - KNX

TOUCH push-button panel module with interchangeable symbols



GW A9 421
KNX 6-channel
with interchangeable symbols

ICE TOUCH KNX glass plates



GW 16 946 CB
Glossy white
GW 16 946 CL
Glossy natural beige
GW 16 946 CN
Glossy black
GW 16 946 CT
Glossy titanium

Contact interfaces



GW 90 727
KNX 2-input with
2 outlets for leds



GW 90 721 A (*)
KNX 4-input with
4 outlets for leds



GW A9 181 (**)
KNX Secure 4-input with
4 outlets for leds



GW 90 728
KNX 8-channel input module
(4 digital + 4 universal)



GW 90 729
KNX 8-channel ac/dc
voltage input module

LED signalling units



3.3 V dc

GW 10 886
Blue
GW 10 887
White
GW 10 888
Red
GW 10 889
Green
GW 10 890
Amber

Blanking modules



For housing contact
interfaces

GW 10 751
Glossy white
GW 15 751
Satin white
GW 13 751
Sat. natural beige
GW 12 751
Satin black
GW 14 751
Glossy titanium

Soft-click electronic push-buttons



Universal
1M-1P-NO

GW 10 915
Glossy white
GW 15 915
Satin white
GW 13 915
Sat. natural beige
GW 12 915
Satin black
GW 14 915
Glossy titanium



For BUS inputs
1M-1P-NO
Backlit

GW 10 913
Glossy white
GW 15 913
Satin white
GW 13 913
Sat. natural beige
GW 12 913
Satin black
GW 14 913
Glossy titanium



For BUS inputs
1M-1P-NO
Backlit

GW 10 916
Glossy white
GW 15 916
Satin white
GW 13 916
Sat. natural beige
GW 12 916
Satin black
GW 14 916
Glossy titanium



For BUS inputs
2M-1P-NO
Backlit

GW 10 917
Glossy white
GW 15 917
Satin white
GW 13 917
Sat. natural beige
GW 12 917
Satin black
GW 14 917
Glossy titanium



For BUS inputs
2M-1P-NO
Backlit

GW 10 918
Glossy white
GW 15 918
Satin white
GW 13 918
Sat. natural beige
GW 12 918
Satin black
GW 14 918
Glossy titanium



With interlock
1M-1P-NO+NO

GW 10 914
Glossy white
GW 15 914
Satin white
GW 13 914
Sat. natural beige
GW 12 914
Satin black
GW 14 914
Glossy titanium

(*) Available until stocks last.
(**) For the date of availability, please contact the GEWISS Sales Organization.

Command devices - KNX

Push-button panels



KNX 6-channel
with interchangeable symbols

GW 10 783 A Glossy white
GW 15 783 A Satin white
GW 13 783 A Sat. natural beige
GW 12 783 A Satin black
GW 14 783 A Glossy titanium



KNX 6-channel + switch actuator
with interchangeable symbols

GW 10 784 A Glossy white
GW 15 784 A Satin white
GW 13 784 A Sat. natural beige
GW 12 784 A Satin black
GW 14 784 A Glossy titanium



KNX 6-channel + roller shutter actuator
with interchangeable symbols

GW 10 785 A Glossy white
GW 15 785 A Satin white
GW 13 785 A Sat. natural beige
GW 12 785 A Satin black
GW 14 785 A Glossy titanium



KNX 4-channel
with interchangeable symbols

GW 10 787 Glossy white
GW 15 787 Satin white
GW 13 787 Sat. natural beige
GW 12 787 Satin black
GW 14 787 Glossy titanium

Interchangeable button keys for push-button panels

Button key - 1M
To be completed
with lens

GW 10 551 Glossy white
GW 15 551 Satin white
GW 13 551 Sat. natural beige
GW 12 551 Satin black
GW 14 551 Glossy titanium



Button key - 2M
To be completed with lens

GW 10 552 Glossy white
GW 15 552 Satin white
GW 13 552 Sat. natural beige
GW 12 552 Satin black
GW 14 552 Glossy titanium

Button key - 1M
To be completed
with 2 lenses

GW 10 553 Glossy white
GW 15 553 Satin white
GW 13 553 Sat. natural beige
GW 12 553 Satin black
GW 14 553 Glossy titanium



Button key - 2M
To be completed with
2 lenses

GW 10 554 Glossy white
GW 15 554 Satin white
GW 13 554 Sat. natural beige
GW 12 554 Satin black
GW 14 554 Glossy titanium



Button key - 1M
With 2 diffusers

GW 10 557 Glossy white
GW 15 557 Satin white
GW 13 557 Sat. natural beige
GW 12 557 Satin black
GW 14 557 Glossy titanium



Button key - 1M
Complete with 2 lenses
DND+MUR

GW 10 559 Glossy white
GW 15 559 Satin white
GW 13 559 Sat. natural beige
GW 12 559 Satin black
GW 14 559 Glossy titanium

Lenses with illuminating symbols

GW 10 501 A
Neutral



GW 10 502 A
Light



GW 10 503 A
Stair light



GW 10 504 A
Table light



GW 10 505 A
Bell



GW 10 506 A
Burglar alarm



GW 10 507 A
Key



GW 10 508 A
ON OFF



GW 10 509 A
ON

GW 10 510 A
OFF



GW 10 511 A
Socket-outlet

GW 10 512 A
Dimmer



GW 10 513 A
Dimmer increase



GW 10 514 A
Dimmer decrease

GW 10 515 A
Arrow

GW 10 516 A
Open

GW 10 517 A
Close



GW 10 518 A
Roller shutter



GW 10 519 A
Roller shutter up



GW 10 520 A
Rolle shutter
down



GW 10 521 A
Curtain open



GW 10 522 A
Curtain close



GW 10 523 A
Floor light



GW 10 524 A
Ceiling light



GW 10 525 A
Wall light

GW 10 526 A
Aisle light



GW 10 527 A
Scenario



GW 10 528 A
Party



GW 10 529 A
in



GW 10 530 A
Out



GW 10 531 A
Good morning



GW 10 532 A
Good night



GW 10 533 A
TV



GW 10 534 A
Heating



GW 10 535 A
Cooling



GW 10 536 A
Heating/Cooling



GW 10 537 A
Comfort



GW 10 538 A
Precomfort



GW 10 539 A
Economy



GW 10 540 A
Auto



GW 10 541 A
Do not disturb
(DND)



GW 10 542 A
Make up the room
(MUR)

Actuators - KNX

Switch actuators



KNX 1-channel 16 A
1 NO/NC 230 V ac - 50/60 Hz

GW 10 796 Glossy white
GW 15 796 Satin white
GW 13 796 Sat. natural beige
GW 12 796 Satin black
GW 14 796 Glossy titanium



GW 90 741
KNX 4-channel 10 A
4 NO 230 V ac - 50/60 Hz



GW 90 740 A (*)
KNX 4-channel 16 AX
4 NO 230 V ac - 50/60 Hz



GW A9 151 (**)
KNX Secure 4-channel 16 AX
4 NO 230 V ac - 50/60 Hz



GW 90 742
KNX 4-channel 16 AX
with manual operation
4 NO 230 V ac - 50/60 Hz



GW A9 108
KNX 8-channel 10 AX
8 NO 230 V ac - 50/60 Hz



GW A9 103
KNX 3-channel 16 AX
with energy meter
3 NO 230 V ac - 50/60 Hz

Roller shutters actuators



KNX 1-channel 6 A
230 V ac - 50/60 Hz

GW 10 797 Glossy white
GW 15 797 Satin white
GW 13 797 Sat. natural beige
GW 12 797 Satin black
GW 14 797 Glossy titanium



GW 90 856
KNX 2-channel 6 A
230 V ac - 50/60 Hz



GW 90 857
KNX 4-channel 6 A
230 V ac - 50/60 Hz

Fan-coil actuators



GW A9 140
KNX fan-coil
230 V ac - 50 Hz



GW A9 141
KNX fan-coil 0-10V
100-240 V ac - 50/60 Hz



GW A9 145
Temperature probe sensor

Combined actuators



GW 90 730
KNX 4-channel 10 A switch actuator
+ 4 universal inputs



GW A9 126
KNX 6/12-channel 8 AX
switch and roller shutter actuator
12 NO 230 V ac - 50/60 Hz

Dimmer actuators



GW A9 313
For electronic ballasts 1-10V
KNX 3-channel 16 AX
230 V ac - 50/60 Hz



GW A9 301 (*)
Universal
KNX 1-channel 500 VA
230V ac - 50/60 Hz



GW A9 321 (**)
Universal
KNX Secure 1-channel 500 VA
230 V ac - 50/60 Hz



GW A9 302 (*)
Universal
KNX 2-channel 300 VA
230V ac - 50/60 Hz



GW A9 322 (**)
Universal
KNX Secure 2-channel 300 VA
230 V ac - 50/60 Hz



GW A9 303
Universal
KNX 2-channel 400W (or 1-channel 800W)
230 V ac - 50 Hz



GW A9 350
Bleeder



GW 90 764 (*)
For CVD LED
KNX 4-channel
12-24 V dc



GW A9 326 (**)
For CVD LED
KNX Secure 4-channel
12-24 V dc



GW 90 765
For CCD LED
KNX 4-channel
12-48 V dc



GW 90 766
Booster for CVD LED
dimmer 4x10A
12-24 V dc



GW 90 768 (***)
Booster for CVD LED
dimmer 4x16A
12-24 V dc

(*) Available until stocks last.
(**) For the date of availability, please contact the GEWISS Sales Organization.
(***) Available: July 2025

Light/motion sensors - KNX

Motion/Presence



KNX IR motion detector
with twilight sensor

- GW 10 786 Glossy white
- GW 15 786 Satin white
- GW 13 786 Sat. natural beige
- GW 12 786 Satin black
- GW 14 786 Glossy titanium



GW A9 531 A
KNX presence detector



GW A9 543
Wall-mounting frame for KNX
presence detector



GW A9 545
Plasterboard-mounting box for
KNX presence detector

Weather sensors - KNX

Devices



GW 90 800
KNX weather station



GW 90 884
KNX light intensity sensor



GW 90 885
KNX temperature sensor

Temperature control - KNX



KNX timed thermostats/programmers
with humidity management (*)

- GW 10 794 H Glossy white
- GW 15 794 H Satin white
- GW 13 794 H Sat. natural beige
- GW 12 794 H Satin black
- GW 14 794 H Glossy titanium



KNX thermostats
with humidity management (*)

- GW 10 795 H Glossy white
- GW 15 795 H Satin white
- GW 13 795 H Sat. natural beige
- GW 12 795 H Satin black
- GW 14 795 H Glossy titanium

Climate control



KNX temperature
sensors

- GW 10 799 Glossy white
- GW 15 799 Satin white
- GW 13 799 Sat. natural beige
- GW 12 799 Satin black
- GW 14 799 Glossy titanium



KNX temperature/humidity
sensors

- GW 10 799 H Glossy white
- GW 15 799 H Satin white
- GW 13 799 H Sat. natural beige
- GW 12 799 H Satin black
- GW 14 799 H Glossy titanium



KNX temperature/humidity
probe sensors

- GW 10 762 H Glossy white
- GW 15 762 H Satin white
- GW 13 762 H Sat. natural beige
- GW 12 762 H Satin black
- GW 14 762 H Glossy titanium



Temperature
probe sensors

- GW 10 900 Glossy white
- GW 15 900 Satin white
- GW 13 900 Sat. natural beige
- GW 12 900 Satin black
- GW 14 900 Glossy titanium



GW 10 800
Temperature probe sensor



KNX Thermo ICE thermostats
12-24 V ac/dc

- GW 16 974 CB Glossy white
- GW 16 974 CL Glossy natural beige
- GW 16 974 CN Glossy black
- GW 16 974 CT Glossy titanium



KNX Secure Thermo ICE thermostats
110/230 V ac - 50/60 Hz
Wall-mounting

- GW 16 976 CB Glossy white
- GW 16 976 CL Glossy natural beige
- GW 16 976 CN Glossy black
- GW 16 976 CT Glossy titanium



GW 10 720
Power supply
100/240 V ac-50/60 Hz
12 V dc

(*) Not equipped with on boards humidity sensor

Home & Building Pro

Energy control - KNX

P-Comfort



GW A9 916
KNX Secure P-Comfort
230 V ac - 50 Hz

KNX energy meters



GW A9 801
KNX Secure single-phase
direct connection

Traditional energy meters



GW D6 801
Single-phase direct connection
GW D6 802
Single-phase direct connection
MID



GW D6 807
Three-phase direct connection
MID



GW D6 809
Three-phase C.T. connection
MID

Interfaces



GW 90 876
KNX interface for
traditional energy
meters

Access control and hotel management - KNX

Transponder units



GW 16 891 CB
Glossy white
GW 16 891 CL
Glossy natural beige
GW 16 891 CN
Glossy black
GW 16 891 CT
Glossy titanium

KNX transponder card reader unit
12/24 V ac/dc



GW 16 892 CB
Glossy white
GW 16 892 CL
Glossy natural beige
GW 16 892 CN
Glossy black
GW 16 892 CT
Glossy titanium

KNX transponder card holder unit
12/24 V ac/dc



GW 16 893 CN
Glossy black

Transponder programming unit
Powered via USB



GW 16 899
Transponder card

Software



GW A9 787
Up to 15 pages
GW A9 788
Up to 35 pages
GW A9 789
Up to 100 pages
GW A9 790
Over 100 pages

Hotel management software
GW HOST

Complementary Items - KNX

Interfaces



GW 90 871
Gateway KNX/DMX



GW 90 873
Gateway KNX Secure/DALI2
multimaster 64/16

Accessories



GW 90 807
Connection terminal to BUS
(red/black)



GW 90 808
Connection terminal to SELV line
(yellow/white)



GW 90 584
KNX BUS cable
2 conductors 1x2x0.8
GW 90 585
KNX BUS cable
4 conductors 2x2x0.8

Command devices - Zigbee

Contact interfaces



GW A1 501
2-channel potential-free
Battery powered



GW A1 502
2-channel
230Vac - 50Hz

Actuators - Zigbee

Switch actuators



GW A1 521
1-channel 10A potential-free
230Vac - 50Hz



GW A1 522
2-channel 6A
230Vac - 50Hz



GW A1 523
1-channel 10A with power meter
230Vac - 50Hz

Roller shutters actuator



GW A1 531
1-channel 6A
230Vac - 50Hz

Smart plug



GW A1 526
10A Schuko adapter
with power meter
230Vac

Load management - Zigbee

Load management kit



GW A1 911
P-Comfort + 1 Smart plug



GW A1 912
P-Comfort + 2 Smart plugs

Load management relay



GW A1 916
P-Comfort
230Vac - 50Hz

Sensors and alarms - Zigbee

Sensors



GW A1 511 [1]
Range 6m
GW A1 511 A [2]
Range 9m

Motion sensors
Battery powered

GW A1 513
Window sensor
Battery powered

Alarms



GW A1 512
Smoke sensor
Battery powered



GW A1 514
Water sensor
Battery powered

Accessory for water sensor

GW A1 541
Wall-mounting support for
water sensor

Accessories

ChoruSmart blanking modules



For housing Zigbee
contact interfaces and
actuators



GW 10 750
Glossy white
GW 15 750
Satin white
GW 13 750
Sat. natural beige
GW 12 750
Satin black
GW 14 750
Glossy titanium

[1] Available until stocks last.
[2] For the date of availability, please contact the GEWISS Sales Organization.

Home & Building Pro

Home & Building Pro range



Wired system based on the KNX international standard protocol, suitable for advanced automation solutions for residential solutions and small-to-medium offices. The offer is highly customisable, complete with all functions and can be integrated with third-party devices and systems (video intercom, smart locks, entertainment). It can be controlled via the APP, voice assistants or touch panels. With Home and Building PRO, you can also manage ZigBee devices and communicate with the Google Home IoT platforms, Amazon Alexa and IFTTT.

HOME AND BUILDING PRO SUPERVISION - KNX AND ZIGBEE

SMART GATEWAY



GW A9 000

Smart Gateway

Code	Supply voltage	Colour	License type	Dimensions (mm)	Pack Carton
GW A9 000	12 V dc - 1 A	White	Without license	171x110x30	1
GW A9 002	12 V dc - 1 A	White	With unlimited license	171x110x30	1

CHARACTERISTICS: multiprotocol gateway provided with KNX, ZigBee, WiFi, Bluetooth (BLE) and LAN interfaces.
APPLICATIONS: the device allows to supervise, command and control the Home and Building automation system through the cloud, ensuring full integration and functional interoperability between different communication protocols. The management of the functions and the access to the data of the system is cloud-based and takes place through a dedicated App (for PC, smartphone and tablet).
ACCESSORIES SUPPLIED: plug power supply and brackets for DIN rail-mounting.
NOTES: table- or DIN rail-mounting.
GWA9000: the access to the cloud services is free of charge for a first period after the purchase. After that period, the payment of the service can be made in a lump sum or with annual tranches. Please, refer to the www.gewiss.com website for more information or contact the Gewiss technical service.
GWA9002: smart gateway includes an unlimited preloaded license.



GW A9 001

SMART GATEWAY license

Code	Description	Pack Carton
GW A9 001	Unlimited license for Smart Gateway	1

CHARACTERISTICS: extends the license for the access to the GWA9000 Smart Gateway cloud services for an unlimited period.

TOUCH panels



GW A9 007 CB

Touch panel - with H&B automation supervision and video entryphone functions

Code	Supply voltage	Display	Colour	Dimensions LxHxD (mm)	Pack Carton
GW A9 007 CB	12-24 Vdc / PoE	7"	White	196x128x19	1/16

CHARACTERISTICS: the device combines the function of a command and supervision panel in a H&B automation system (together with Smart Gateway) and of video entryphone indoor unit with speakerphone (together with 2N IP video entryphone outdoor units). Supply voltage via Power over Ethernet - PoE (IEEE 802.3af) or, as an alternative, with external power supply (eg: GW90802). The panel is based on SIP protocol with H.264 video coding.
NOTES: wall-mounting. To fix it, use flush-mounting Ø60mm round (eg: GW24232), square (eg: GW24231) or rectangular (eg: GW24403) boxes with the aid of the supplied wall metal bracket.



GW 90 802 A

Power supply 24 V dc - 2,5 A - DIN rail mounting

Code	Input voltage	Output voltage	No. DIN modules	Pack Carton
GW 90 802 A	100 ÷ 240 V ac - 50/60 Hz	24V dc - 2.5 A	3	1

CHARACTERISTICS: protected against input overvoltages and output short-circuiting.
NOTES: to supply 7" touch panels.

SYSTEM COMPONENTS - KNX

Power supplies



GW 90 710

Self-protected electronic power supplies 220-240V - IP20 - DIN rail mounting

Code	Output voltage	Current supplied (max)	No. DIN modules	Pack Carton
GW 90 709	30V dc +/- 2V (SELV)	320 mA	4	1
GW 90 710	30V dc +/- 2V (SELV)	640 mA	4	1

CHARACTERISTICS: integrated coil to uncouple the power supply from the BUS line.
Reset push-button for restoring all the devices connected to the BUS line.
APPLICATIONS: the power supply feeds and controls the BUS voltage.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
The maximum number of devices that can be powered is calculated on the basis of their absorption.

Complementary items



GW 90 708 A

Line/field coupling - IP20 - DIN rail mounting

Code	Functions	No. DIN modules	Pack Carton
GW 90 708 A	Coupler - Repeater	2	1/4

APPLICATIONS: for the logic connection and the galvanic separation of lines and areas (fields).
NOTES: equipped with 2 coupling terminals for connection to BUS.



GW 90 706 B

KNX/USB interface - IP20 - DIN rail mounting

Code	Max USB cable length	No. DIN modules	Pack Carton
GW 90 706 B	5 m	1	1

CHARACTERISTICS: equipped with B-type USB port.
APPLICATIONS: for the connection of a PC with a USB port to the KNX BUS.
NOTES: equipped with coupling terminal for connection to bus.



GW 90 706 U

KNX/USB stick interface - IP20

Code	Description	Dimensions LxHxD (mm)	Pack Carton
GW 90 706 U	USB key	60x19x13	1

CHARACTERISTICS: equipped with A-type USB connector.
APPLICATIONS: for the connection of a PC with a USB port to the KNX BUS.
NOTES: equipped with screw terminal for connection to the bus.



GW A9 707

KNX/IP router - IP20 - DIN rail mounting

Code	Description	Max power consumption	No. DIN modules	Pack Carton
GW A9 707	KNX/IP router	<500 mW	1	1/8

CHARACTERISTICS: equipped with RJ45 port.
APPLICATIONS: for connecting the KNX lines to the IP backbones and the PC interface via LAN to the KNX BUS. Supports up to 5 simultaneous connections.
NOTES: equipped with coupling terminal for connection to bus.



GW A9 705

KNX/IP interface - IP20 - DIN rail mounting

Code	Description	Max power consumption	No. DIN modules	Pack Carton
GW A9 705	KNX/IP interface	<500 mW	1	1/8

CHARACTERISTICS: equipped with RJ45 port.
APPLICATIONS: for connecting a PC via LAN to the KNX BUS. Supports up to 5 simultaneous connections. To be used with the HAPPY HOME app for smartphones and tablets (available for Android and iOS) to manage the KNX domotic system via LAN and WiFi access points, or from a distance. The app can also be used with the codes GW90767 and GW90767AP.
NOTES: equipped with coupling terminal for connection to bus.

COMMAND DEVICES - KNX

Touch push-button panels



GW A9 421

KNX 6-channel touch push-button panel module with interchangeable symbols

Code	No. channels	No. modules	Pack Carton
GW A9 421	6	3	1

CHARACTERISTICS: KNX module with 6 independent channels. Each channel is associated with an RGB night-time backlit LED or a status display LED for the commanded load. Each channel can be personalised using a set of adhesive icons. To be completed with the glass ICE Touch KNX plate (code GW16946CB, GW16946CN, GW16946CT, GW16946CL). The device's touch commands can only be activated with the plate mounted: therefore, to configure the module the ICE Touch KNX plates or alternative the test plate (GW16950) must be used. To be configured with ETS software.
APPLICATIONS: used for sending ON-OFF commands with fronts management, switching commands and sequences, timed commands, multiple pressing, priority commands, commands for managing roller shutters (single or double push-button), dimmers (single or double push-button) and scenes (storage and activation).
NOTES: equipped with coupling terminal with protection lid, for connection to BUS, and with set of icons to personalise the functions of each channel.

ICE TOUCH KNX - White

Code	Description	For support codes	Pack Carton
GW 16 946 CB	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CB

ICE touch KNX - Black

Code	Description	For support codes	Pack Carton
GW 16 946 CN	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CN

ICE touch KNX - Titanium

Code	Description	For support codes	Pack Carton
GW 16 946 CT	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates made of glass with a glossy finish, to match the KNX touch-panel modules (GWA9421).
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).



GW 16 946 CT

ICE touch KNX - Natural beige

Code	Description	For support codes	Pack Carton
GW 16 946 CL	6 touch areas	GW16803, GW16803N	1

CHARACTERISTICS: plates in glass and with a glossy finish, used to complete the KNX touch panel modules (GWA9421). The plates are equipped with 6 capacitive touch areas.
NOTES: the symbols shown in the image are purely indicative: they can be customised using the adhesive icons supplied with the touch-panel module. The plate code is unique, regardless of the number of channels to be activated (from 1 to 6).




GW 16 946 CL

Test plate for KNX 6-channels stouch panel modules with interchangeable symbols

Code	Description	For support codes	Pack Carton
GW 16 950	Test plate	GW16803, GW16803N	12

CHARACTERISTICS: transparent plastic plate with 6 capacitive touch areas.
NOTES: tob used for configuring the KNX touch panel module (GWA9421) if the KNX ICE touch glass plates are not available in the installation.



GW 16 950

Contact interfaces



GW 90 721 A

KNX 2- and 4-channel contacts interfaces

Code	No. input channels	No. output channels	Max cable length	Dimensions LxHxD (mm)	Pack Carton
GW 90 727	2	2	10 m	38x32x14	1
GW 90 721 A	4	4	10 m	38x32x14	1
GW A9 181	4	4	10 m	38x32x14	1

CHARACTERISTICS: BUS interfaces for connecting 2 or 4 push-buttons or conventional potential-free contacts. The reading voltage (SELV) is generated inside the device. For each input, an output is available for powering a low absorption LED (lower than 1mA such as, for example, GW10886, GW10887, GW10888, GW10889, GW10890) for displaying the status of the load commanded. GWA9181 supports KNX Secure. To be configured with ETS software.
APPLICATIONS: for sending ON-OFF commands with fronts management, switching commands and sequences, brief / prolonged contact closure management, timed commands, priority commands, commands for managing roller shutters (single or double push-button), dimmers (single or double push-button), scenes (storage and activation), impulse count, output LED control, acquisition of temperature values via NTC sensor (GW90721A, GWA9181), setting threshold values with threshold exceedance notification and hysteresis management (GWA9181 only). Installation in flush-mounting box, junction boxes or embedded in the blanking modules GW1x751. The slot on the plastic casing also allows it to be fixed with screws.
NOTES: equipped with coupling terminal for connection to the BUS, and unshielded cables for connecting the inputs, of length 30 cm extendible to 10m with unshielded twisted cable.
GW90721A: product available while stock lasts. GWA9181: please contact GEWISS sales team for the date of availability.



GW 90 728

KNX 8-channel (4 digital + 4 universal) input module - IP20 - DIN rail mounting

Code	No. input channels	No. universal input channels	No. output channels	No. DIN modules	Pack Carton
GW 90 728	4	4	4	4	1

CHARACTERISTICS: the module has 4 digital inputs for push-buttons or conventional potential-free contacts and 4 universal input channels. The universal input channels can be configured as inputs for push-buttons or conventional potential-free contacts, analogue inputs (0..20mA, 4..20mA, 0..10V, 0..1V), digital inputs for measurement devices with S0 interface, inputs for NTC probe sensors that can be used for controlling the same number of thermoregulation areas. The module is provided also with 4 PWM outputs for LEDs (3.3V) for signalling the status of the loads. The device has 8 amber LEDs for signalling the status of the inputs. To be configured with ETS software.
APPLICATIONS: the input channels are used for sending ON-OFF commands with fronts management, switching commands and sequences, brief / prolonged contact closure management, timed commands, priority commands, thermoregulation commands, commands for managing roller shutters (single or double push-button), dimmers (single or double push-button), scenes (storage and activation), impulse count.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 90 729

KNX 8-channel ac/dc voltage input module - IP20 - DIN rail mounting

Code	No. input channels	Input voltage	Max cable length	No. DIN modules	Pack Carton
GW 90 729	8	24-48 V dc, 24-230 V ac	100 m	4	1

CHARACTERISTICS: BUS interface module for connecting 8 push-buttons or conventional live contacts. The device has 8 amber LEDs for signalling the status of the inputs. To be configured with ETS software.
APPLICATIONS: for sending ON-OFF commands with fronts management, switching commands and sequences, brief / prolonged contact closure management, timed commands, priority commands, commands for managing roller shutters (single or double push-button), dimmers (single or double push-button), scenes (storage and activation), impulse count.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 10 886

LED signalling units

Code	Supply voltage	Lamp	Colour	Cable Colour	Pack Carton
GW 10 886	3.3V dc	LED	Blue	Blue - Black	50
GW 10 887	3.3V dc	LED	White	White - Black	50
GW 10 888	3.3V dc	LED	Red	Red - Black	50
GW 10 889	3.3V dc	LED	Green	Green - Black	50
GW 10 890	3.3V dc	LED	Amber	Amber - Black	50

NOTES: the miniature lamps are equipped with power cables.
If connected with the interfaces GW90721, GW90834, GW90721A, GWA9181, GW90727, GW90834A, GW90833 they do not require the use of a current limiting resistance. In this case, the maximum current consumption is less than 1mA.



GW 14 751

Blanking modules for housing 2- and 4-channel contacts interface

Code	Colour	No. modules	Pack Carton
GW 10 751	Glossy white	1	5/200
GW 15 751	Satin white	1	5/200
GW 13 751	Natural satin beige	1	5/200
GW 12 751	Satin black	1	5/200
GW 14 751	Glossy titanium	1	5/200

CHARACTERISTICS: 1 module blanking module with pad printing KNX/EIB.
Allows the housing and fast identification of the 2- and 4-channel contact interface.
NOTES: embedded coupling.

Push-button panels

KNX 6-channel push-button panels with interchangeable symbols



GW 14 783 A

Code	Colour	No. channels	No. modules	Pack Carton
GW 10 783 A	Glossy white	6	3	1
GW 15 783 A	Satin white	6	3	1
GW 13 783 A	Natural satin beige	6	3	1
GW 12 783 A	Satin black	6	3	1
GW 14 783 A	Glossy titanium	6	3	1

CHARACTERISTICS: KNX module with 6 independent channels, with replaceable button keys and built-in temperature sensor. Each channel is associated with an amber/green night-time locating LED or a status display LED for the commanded load. To be configured with ETS software. The package includes 3 replaceable button keys (GW1x553) and 10 lenses with illuminated symbols (2 x GW10502A, 1 x GW10509A, 1 x GW10510A, 1 x GW10513A, 1 x GW10514A, 1 x GW10519A, 1 x GW10520A, 1 x GW10529A, 1 x GW10530A). You can still customize the module with other type of replaceable button keys (suited for 1 or 2 lenses, with 2 diffusers, 1- or 2-module) or with other lenses in the catalogue.

APPLICATIONS: allows you to send ON-OFF commands with fronts management, switching commands and sequences, brief/prolonged contact closure management, timed commands, priority commands, commands for roller shutter management (single or double push-button), dimmers (single or double push-button) and scenes (memorisation and activation).

NOTES: equipped with coupling terminal for connection to BUS (with protection lid).

KNX 6-channel push-button panels with interchangeable symbols + switch actuator



GW 14 784 A

Code	Colour	No. channels	Output contacts	No. modules	Pack Carton
GW 10 784 A	Glossy white	6+1	1NO/NC 10A(AC1) 230Vac	3	1
GW 15 784 A	Satin white	6+1	1NO/NC 10A(AC1) 230Vac	3	1
GW 13 784 A	Natural satin beige	6+1	1NO/NC 10A(AC1) 230Vac	3	1
GW 12 784 A	Satin black	6+1	1NO/NC 10A(AC1) 230Vac	3	1
GW 14 784 A	Glossy titanium	6+1	1NO/NC 10A(AC1) 230Vac	3	1

CHARACTERISTICS: KNX module with 6 independent channels, with replaceable button keys and 1-channel switch actuator. Each channel is associated with an amber/green night-time locating LED or a status display LED for the commanded load. One pair of keys can be used for local actuator command. The actuator manages the load via a potential-free output contact (NO). To be configured with ETS software. The package includes 3 replaceable button keys (GW1x553) and 10 lenses with illuminated symbols (2 x GW10502A, 1 x GW10509A, 1 x GW10510A, 1 x GW10513A, 1 x GW10514A, 1 x GW10519A, 1 x GW10520A, 1 x GW10529A, 1 x GW10530A). You can still customize the module with other type of replaceable button keys (suited for 1 or 2 lenses, with 2 diffusers, 1- or 2-module) or with other lenses in the catalogue.

APPLICATIONS: the push-button panel allows you to send ON-OFF commands with fronts management, switching commands and sequences, brief/prolonged contact closure management, timed commands, priority commands, commands for roller shutter management (single or double push-button), dimmers (single or double push-button) and scenes (memorisation and activation). The actuator allows the execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands and scene management commands.

NOTES: equipped with coupling terminal for connection to BUS (with protection lid).

KNX 6-channel push-button panels with interchangeable symbols + roller shutter actuator



GW 14 785 A

Code	Colour	No. channels	Max current supplied	No. modules	Pack Carton
GW 10 785 A	Glossy white	6+1	6A-230V ac (compl. 60669-2-1)	3	1
GW 15 785 A	Satin white	6+1	6A-230V ac (compl. 60669-2-1)	3	1
GW 13 785 A	Natural satin beige	6+1	6A-230V ac (compl. 60669-2-1)	3	1
GW 12 785 A	Satin black	6+1	6A-230V ac (compl. 60669-2-1)	3	1
GW 14 785 A	Glossy titanium	6+1	6A-230V ac (compl. 60669-2-1)	3	1

CHARACTERISTICS: KNX module with 6 independent channels, with replaceable button keys and 1-channel roller shutter actuator. Each channel is associated with an amber/green night-time locating LED or a status display LED for the commanded load. One pair of keys can be used for local actuator command. The actuator manages a motor to move roller-shutters, curtains, venetian blinds, rolling blinds, etc. via 2 potential-free interlocked output contacts (NO). To be configured with ETS software. The package includes 3 replaceable button keys (GW1x553) and 10 lenses with illuminated symbols (2 x GW10502A, 1 x GW10509A, 1 x GW10510A, 1 x GW10513A, 1 x GW10514A, 1 x GW10519A, 1 x GW10520A, 1 x GW10529A, 1 x GW10530A). You can still customize the module with other type of replaceable button keys (suited for 1 or 2 lenses, with 2 diffusers, 1- or 2-module) or with other lenses in the catalogue.

APPLICATIONS: the push-button panel allows you to send ON-OFF commands with fronts management, switching commands and sequences, brief/prolonged contact closure management, timed commands, priority commands, commands for roller shutter management (single or double push-button), dimmers (single or double push-button) and scenes (memorisation and activation). The actuator allows the execution of commands of movements/adjustment/stopping, along with priority commands, scene management and alarm signalling commands.

NOTES: equipped with coupling terminal for connection to BUS (with protection lid).

KNX 4-channel push-button panels with interchangeable symbols



GW 14 787

Code	Colour	No. channels	No. modules	Pack Carton
GW 10 787	Glossy white	4	2	1
GW 15 787	Satin white	4	2	1
GW 13 787	Natural satin beige	4	2	1
GW 12 787	Satin black	4	2	1
GW 14 787	Glossy titanium	4	2	1

CHARACTERISTICS: KNX module with 4 independent channels, with replaceable button keys. Each channel is associated with a RGB LED for night-time locating or status display for the commanded load. To be configured with ETS software. The package includes 2 replaceable button keys (GW1x553) and 10 lenses with illuminated symbols (2 x GW10502A, 1 x GW10509A, 1 x GW10510A, 1 x GW10513A, 1 x GW10514A, 1 x GW10519A, 1 x GW10520A, 1 x GW10529A, 1 x GW10530A). You can still customize the module with other type of replaceable button keys (arranged for 1 or 2 lenses, with 2 diffusers, 1 or 2 modules) or with other lenses in the catalogue.

APPLICATIONS: allows you to send ON-OFF commands with fronts management, switching commands and sequences, brief/prolonged contact closure management, timed commands, priority commands, commands for roller shutter management (single or double push-button), dimmers (single or double push-button) and scenes (memorisation and activation).

NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 14 553

Replaceable button keys for push-button panels

Code	Colour	Button key	No. modules	Pack Carton
GW 10 551	Glossy white	To be completed with lens	1	4/48
GW 15 551	Satin white	To be completed with lens	1	4/48
GW 13 551	Natural satin beige	To be completed with lens	1	4/48
GW 12 551	Satin black	To be completed with lens	1	4/48
GW 14 551	Glossy titanium	To be completed with lens	1	4/48
GW 10 552	Glossy white	To be completed with lens	2	4/48
GW 15 552	Satin white	To be completed with lens	2	4/48
GW 13 552	Natural satin beige	To be completed with lens	2	4/48
GW 12 552	Satin black	To be completed with lens	2	4/48
GW 14 552	Glossy titanium	To be completed with lens	2	4/48
GW 10 553	Glossy white	To be completed with 2 lenses	1	4/48
GW 15 553	Satin white	To be completed with 2 lenses	1	4/48
GW 13 553	Natural satin beige	To be completed with 2 lenses	1	4/48
GW 12 553	Satin black	To be completed with 2 lenses	1	4/48
GW 14 553	Glossy titanium	To be completed with 2 lenses	1	4/48
GW 10 554	Glossy white	To be completed with 2 lenses	2	4/48
GW 15 554	Satin white	To be completed with 2 lenses	2	4/48
GW 13 554	Natural satin beige	To be completed with 2 lenses	2	4/48
GW 12 554	Satin black	To be completed with 2 lenses	2	4/48
GW 14 554	Glossy titanium	To be completed with 2 lenses	2	4/48
GW 10 557	Glossy white	With 2 diffusers	1	4/48
GW 15 557	Satin white	With 2 diffusers	1	4/48
GW 13 557	Natural satin beige	With 2 diffusers	1	4/48
GW 12 557	Satin black	With 2 diffusers	1	4/48
GW 14 557	Glossy titanium	With 2 diffusers	1	4/48

NOTES: to be used to customise the 6 and 4 channels KNX push-button panels (GW1x783A, GW1x784A, GW1x785A, GW1x787).



GW 14 559

Replaceable button keys for push-button panels - hotel solutions

Code	Colour	Button key	Symbol	No. modules	Pack Carton
GW 10 559	Glossy white	Complete of 2 lenses	DND+MUR	1	1/48
GW 15 559	Satin white	Complete of 2 lenses	DND+MUR	1	1/48
GW 13 559	Natural satin beige	Complete of 2 lenses	DND+MUR	1	1/48
GW 12 559	Satin black	Complete of 2 lenses	DND+MUR	1	1/48
GW 14 559	Glossy titanium	Complete of 2 lenses	DND+MUR	1	1/48

CHARACTERISTICS: equipped with "Do not disturb" and "Make up the room" pad printing. Complete with lenses with illuminated symbols.

NOTES: to be used to customise the 6 and 4 channels KNX push-button panels (GW1x783A, GW1x784A, GW1x785A, GW1x787).



Lenses with illuminated symbols

Code	Symbol	Pack Carton
GW 10 501 A	Neutral	24
GW 10 502 A	Light	24
GW 10 503 A	Stair light	24
GW 10 504 A	Table light	24
GW 10 505 A	Bell	24
GW 10 506 A	Burglar alarm	24
GW 10 507 A	Key	24
GW 10 508 A	ON OFF	24
GW 10 509 A	ON	24
GW 10 510 A	OFF	24
GW 10 511 A	Socket-outlet	24
GW 10 512 A	Dimmers	24
GW 10 513 A	Dimmer increase	24
GW 10 514 A	Dimmer decrease	24
GW 10 515 A	Arrow	24
GW 10 516 A	Open	24
GW 10 517 A	Close	24
GW 10 518 A	Roller shutter	24
GW 10 519 A	Roller shutter up	24
GW 10 520 A	Roller shutter down	24
GW 10 521 A	Curtain open	24
GW 10 522 A	Curtain close	24
GW 10 523 A	Floor light	24
GW 10 524 A	Ceiling light	24
GW 10 525 A	Wall light	24
GW 10 526 A	Aisle light	24
GW 10 527 A	Scenario	24
GW 10 528 A	Party	24
GW 10 529 A	In	24
GW 10 530 A	Out	24
GW 10 531 A	Good morning	24
GW 10 532 A	Good night	24
GW 10 533 A	TV	24
GW 10 534 A	Heating	24
GW 10 535 A	Cooling	24
GW 10 536 A	Heating/Cooling	24
GW 10 537 A	Comfort	24
GW 10 538 A	Precomfort	24
GW 10 539 A	Economy	24
GW 10 540 A	Auto	24
GW 10 541 A	Do not disturb	24
GW 10 542 A	Make up the room	24

NOTES: to be used to customise the buttons for the 6- and 4-channel KNX push-button panel (GW1x783A, GW1x784A, GW1x785A, GW1x787).

Soft-click electronic push-buttons



GW 14 915

Universal soft-click electronic push-buttons

Code	Colour	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 10 915	Glossy white	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12
GW 15 915	Satin white	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12
GW 13 915	Natural satin beige	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12
GW 12 915	Satin black	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12
GW 14 915	Glossy titanium	1NO/NC 4A (AC1) 230 V ac - Potential-free	Neutral	Relay, dimmer, bus contacts interfaces	1	1/12

CHARACTERISTICS: push-button suitable for connection of KNX BUS contacts interfaces, or the command of bistable relays, electronic one-way switches for heavy duty loads, or dimmers with a remote control input.



GW 14 913

Backlit soft-click electronic push-buttons for BUS inputs

Code	Colour	Type of contact	Button key	Type of use	No. modules	Pack Carton
GW 10 913	Glossy white	1NO - Potential-free	With diffuser	Bus contacts interfaces	1	1/12
GW 15 913	Satin white	1NO - Potential-free	With diffuser	Bus contacts interfaces	1	1/12
GW 13 913	Natural satin beige	1NO - Potential-free	With diffuser	Bus contacts interfaces	1	1/12
GW 12 913	Satin black	1NO - Potential-free	With diffuser	Bus contacts interfaces	1	1/12
GW 14 913	Glossy titanium	1NO - Potential-free	With diffuser	Bus contacts interfaces	1	1/12
GW 10 916	Glossy white	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1	1/12
GW 15 916	Satin white	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1	1/12
GW 13 916	Natural satin beige	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1	1/12
GW 12 916	Satin black	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1	1/12
GW 14 916	Glossy titanium	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	1	1/12
GW 10 917	Glossy white	1NO - Potential-free	With diffuser	Bus contacts interfaces	2	1/6
GW 15 917	Satin white	1NO - Potential-free	With diffuser	Bus contacts interfaces	2	1/6
GW 13 917	Natural satin beige	1NO - Potential-free	With diffuser	Bus contacts interfaces	2	1/6
GW 12 917	Satin black	1NO - Potential-free	With diffuser	Bus contacts interfaces	2	1/6
GW 14 917	Glossy titanium	1NO - Potential-free	With diffuser	Bus contacts interfaces	2	1/6
GW 10 918	Glossy white	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	2	1/6
GW 15 918	Satin white	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	2	1/6
GW 13 918	Natural satin beige	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	2	1/6
GW 12 918	Satin black	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	2	1/6
GW 14 918	Glossy titanium	1NO - Potential-free	With replaceable neutral lens	Bus contacts interfaces	2	1/6

CHARACTERISTICS: push-button for BUS inputs, suitable for KNX BUS contact interface connections. Equipped with 2-colour (amber/green) LED with colour selector (can be set up to work as a night-time localisation lamp or to indicate the load status).



GW 14 914

Dual soft-click electronic push-buttons

Code	Colour	Type of contact	Button key	Symbol	No. modules	Pack Carton
GW 10 914	Glossy white	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12
GW 15 914	Satin white	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12
GW 13 914	Natural satin beige	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12
GW 12 914	Satin black	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12
GW 14 914	Glossy titanium	Dual, potential-free and with interlock	Neutral	UP - DOWN	1	1/12

CHARACTERISTICS: double push-button suitable for connection of KNX BUS contacts interfaces or electronic control panels for moving roller shutters.

MOVEMENT/LIGHT SENSORS - KNX

Movement



GW 14 786

KNX IR motion detectors with twilight sensor

Code	Colour	Recovery time	Treshold adjustment	No. modules	Pack Carton
GW 10 786	Glossy white	10s - 1min	10 - 500 lux	2	1
GW 15 786	Satin white	10s - 1min	10 - 500 lux	2	1
GW 13 786	Natural satin beige	10s - 1min	10 - 500 lux	2	1
GW 12 786	Satin black	10s - 1min	10 - 500 lux	2	1
GW 14 786	Glossy titanium	10s - 1min	10 - 500 lux	2	1

CHARACTERISTICS: movement sensor with detection conditioned by the light threshold value set. Adjustable lens. Operating range: 10m.
Vertical bearing angle: 30°. Horizontal bearing angle: 105°. Light threshold value adjustable by means of the frontal access trimmer or ETS parameter.
The cycle time can be set via ETS and modified (± 50%) via the front access trimmer.
Front green LED signals movement detection and command entry. To be configured with ETS software.
APPLICATIONS: allows you to send timed commands to the movement detector.
The device is able to manage a safety pause upon the deactivation of the controlled load. For installation indoors.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW A9 531 A

KNX presence detector with constant brightness control - ceiling mounting

Code	Max. assembly height (m)	Light sensor	Dimensions (mm)	Colour	Pack Carton
GW A9 531 A	6	5...2000 lux	Ø 105x44	White	1

CHARACTERISTICS: with 3 PIR sensors and a 360° circular shape operating range. Max. presence detection range: from 4 up to 8m, max. motion detection range: from 10 to 16m depending on the installatin height and the type of approach (tangential or radial). Ceiling installation. To be configured with ETS software.
APPLICATIONS: for environments where it is necessary to send activation commands to actuator devices via the KNX bus according to the movements detected and possibily the light intensity measured.
NOTES: equipped with coupling terminal for connection to BUS.



GW A9 543

Wall-mounting frame

Code	Suitable for	Dimensions (mm)	Colour	Pack Carton
GW A9 543	GWA9531A	Ø 105x40	White	1

APPLICATIONS: accessory for the KNX presence detector GWA9531A wall installation.



GW A9 545

Plasterboard-mounting box

Code	Suitable for	Dimensions (mm)	Pack Carton
GW A9 545	GWA9531A	Ø 78	1

APPLICATIONS: flush-mounting box with spring clip for the KNX presence detector GWA9531A plasterboard installation.

ACTUATORS - KNX

Switch actuators



GW 14 796

KNX 1-channel 16A switch actuators

Code	Colour	Output contacts	No. modules	Pack Carton
GW 10 796	Glossy white	1NO/NC 16A(AC1) 230Vac	2	1
GW 15 796	Satin white	1NO/NC 16A(AC1) 230Vac	2	1
GW 13 796	Natural satin beige	1NO/NC 16A(AC1) 230Vac	2	1
GW 12 796	Satin black	1NO/NC 16A(AC1) 230Vac	2	1
GW 14 796	Glossy titanium	1NO/NC 16A(AC1) 230Vac	2	1

CHARACTERISTICS: 1-channel switch actuator for activating loads via a potential-free output contact (NO/NC).
Equipped with a front push-button for local command, a indicator LED for output contact closure and night-time backlit LED. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions.
For discharge lamps and compensated fluorescent lamps, use a support relay.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 90 741

KNX 4-channel 10A switch actuator - IP20 - DIN rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW 90 741	4	4NO 10A(AC1) 230Vac	4	1

CHARACTERISTICS: 4-channel switch actuator for activating loads via potential-free output contacts (NO). Suitable for commanding incandescent lamps (230Vac): 1500 W, halogen lamps (230Vac): 1500 W, loads controlled from electronic transformers: 600 VA, uncompensated fluorescent lamps: 400 VA, energy saving lamps (compact fluorescent): 8x23 W. Max switchover current 10 A (cos.fi 1). Use a support relay for the compensated fluorescent lamps and for all loads that are not indicated. Equipped with front push-buttons for local implementation, and signalling LED for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 90 740 A

KNX 4-channel 16AX switch actuator - IP20 - DIN rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW 90 740 A	4	4NO 16AX 230Vac	4	1

CHARACTERISTICS: 4-channel switch actuator for activating loads via potential-free output contacts (NO). Suitable for commanding incandescent lamps (230Vac): 3000 W, halogen lamps (230Vac): 3000 W, loads controlled from toroidal transformers: 3000 W, loads controlled from electronic transformers: 2000 W, energy saving lamps (compact fluorescent): 80x23W. Max switchover current 16A (AC1), 16AX (140µF ref EN 60669-1) fluorescent loads with maximum surge current 400A (200µs). Equipped with front push-buttons for local implementation, and signalling LED for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
Product available while stock lasts.



GW A9 151

KNX Secure 4-channel 16 AX switch actuator - IP20 - DIN rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW A9 151	4	4 NO 16 AX 230 V ac	4	1

CHARACTERISTICS: 4-channel switch actuator for activating loads via potential-free output contacts (NO). Suitable for commanding incandescent lamps (230Vac): 3000 W, halogen lamps (230Vac): 3000 W, loads controlled from toroidal transformers: 3000 W, loads controlled from electronic transformers: 2000 W, LED lamps(230V): 400W. Max switchover current 16A(AC1), 16AX (140µF ref EN 60669-1) fluorescent loads with maximum surge current 400A (200µs). Equipped with front push buttons for local control that can be enabled/disabled via KNX BUS and signalling LED for closure of output contact. The device supports KNX Secure. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions, number of maneuvers, and contact closure period.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
Please contact GEWISS sales team for the date of availability.



GW 90 742

KNX 4-channel 16AX switch actuator with manual operation - IP20 - DIN rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW 90 742	4	4NO 16AX 230Vac	4	1

CHARACTERISTICS: 4-channel switch actuator for activating loads via potential-free output contacts (NO). Suitable for commanding incandescent lamps (230Vac): 3000 W, halogen lamps (230Vac): 3000 W, loads controlled from toroidal transformers: 3000 W, loads controlled from electronic transformers: 2000 W, energy saving lamps (compact fluorescent): 80x23W. Max switchover current 16A (AC1), 16AX (140µF ref. EN 60669-1) fluorescent loads with maximum surge current 400A (200µs). Equipped with front push-buttons for manual activation, and signalling LED for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid). Possibility to activate the loads manually, even without the BUS voltage (230Vac auxiliary power supply required).



GW A9 108

KNX 8-channel 10AX switch actuator - IP20 - DIN rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW A9 108	8	8NO 10AX 230Vac	4	1

CHARACTERISTICS: 8-channel switch actuator for activating loads via potential-free output contacts (NO). Suitable for commanding incandescent lamps (230Vac): 2000W, halogen lamps (230Vac): 2000W, loads controlled from toroidal transformers: 1500W, loads controlled from electronic transformers: 1200W, energy saving lamps (compact fluorescent): 40x23W, LED lamps (230Vac): 40x10W. Max switchover current 10A (AC1), 10AX (140µF rif. EN 60669-1) fluorescent loads with maximum surge current 400A (150µs). Equipped with front push-buttons for local implementation, and signalling LED for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions, counters.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW A9 103

KNX 3-channel 16AX switch actuator with energy meter - IP20 - DIN rail mounting

Code	Supply voltage	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW A9 103	230V ac - 50Hz	3	3NO 16AX 230V ac	4	1

CHARACTERISTICS: 3-channel switch actuator for activating loads via potential-free output contacts (NO), with the measure of the power and the energy consumed by each channel. Suitable for commanding incandescent lamps (230Vac): 3000W, halogen lamps (230Vac): 3000W, loads controlled from toroidal transformers: 3000W, loads controlled from electronic transformers: 2000W, energy saving lamps (compact fluorescent): 80x23W. Max switchover current 16 A (AC1), 16 AX (140 µF ref. EN 60669-1) fluorescent loads with maximum surge current 400A (200 µs). Equipped with front push-buttons for local implementation and signalling led for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, lockout commands, safety functions, logic functions. Allows the measurement and the sending on the KNX bus of the active energy (exported and imported), instantaneous active and reactive power (exported and imported), voltage, current, power factor and frequency, with the possibility to disconnect the load for each channel independently. Suitable for single-phase systems.
NOTES: equipped with coupling terminal for connection to bus (with protection lid).

Actuators for roller shutters



GW 14 797

NEWS

KNX 1-channel 6A roller shutter actuators

Code	Colour	Max current supplied	No. modules	Pack Carton
GW 10 797	Glossy white	6A-230V ac (compl. 60669-2-1)	2	1
GW 15 797	Satin white	6A-230V ac (compl. 60669-2-1)	2	1
GW 13 797	Natural satin beige	6A-230V ac (compl. 60669-2-1)	2	1
GW 12 797	Satin black	6A-230V ac (compl. 60669-2-1)	2	1
GW 14 797	Glossy titanium	6A-230V ac (compl. 60669-2-1)	2	1

CHARACTERISTICS: 1-channel actuator to activate a motor to move roller-shutters, curtains, Venetian blinds, rolling blinds, etc. via 2 potential-free interlocked output contacts (NO). Equipped with two front push-buttons for local implementation, two LEDs to signal the closure of the outputs contacts, and two LEDs for night-time localisation. To be configured with ETS software.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW 90 857

KNX 6A roller shutter actuators - 230V - IP20 - DIN rail mounting

Code	No. channels	Max current supplied	No. DIN modules	Pack Carton
GW 90 856	2	6A-230V ac (compl. 60669-2-1)	4	1
GW 90 857	4	6A-230V ac (compl. 60669-2-1)	4	1

CHARACTERISTICS: 2- and 4-channel actuators to activate motors to move roller-shutters, curtains, venetian blinds, rolling blinds, etc. via respectively 4 and 8 potential-free interlocked output contacts (NO) With 4 (8) frontal push-buttons for local activation, and 4 (8) LEDs indicating output contact closure.
APPLICATIONS: carries out commands of movement/adjustment/stopping, along with priority commands, scene management and alarm signalling commands. Permit the management of different times for up/down movements and for slat adjustment.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
GW90857: possibility to activate the loads manually, even without the BUS voltage.

Combined actuators



GW 90 730

KNX 4-channel 10A switch actuator + 4 universal inputs - IP 20 - DIN rail mounting

Code	No. universal input channels	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW 90 730	4	4	4NO 10A(AC1) 230Vac	4	1

CHARACTERISTICS: the module has 4 relay 10A output channels and 4 universal input channels that can be configured as inputs for push-buttons or conventional potential-free contacts, analogue inputs (0..20mA, 4..20mA, 0..10V, 0..1V), digital inputs for measurement devices with S0 interface (max 1), inputs for NTC probe sensors (max 2) that can be used for controlling the same number of thermoregulation areas. The 4 universal input channels can also be configured as PWM outputs for LEDs (3.3V) for signalling the status of the loads. The 4 relay output channels are suitable for commanding incandescent lamps (230Vac): 1500W, halogen lamps (230Vac): 1500W, loads controlled from electronic transformers: 600 VA, uncompensated fluorescent lamps 400VA, energy saving lamps (compact fluorescent): 8x23W. Max switchover current 10 A (cos. fi 1). Use a support relay for the compensated fluorescent lamps and for all loads that are not indicated. The device has front push-buttons for the local command of the relay outputs, 4 green LEDs for signalling output contact closure, and 4 amber LEDs for signalling the status of the inputs. To be configured with ETS software.
APPLICATIONS: the input channels are used for sending ON-OFF commands with fronts management, switching commands and sequences, brief / prolonged contact closure management, timed commands, priority commands, commands for managing roller shutters (single or double push-button), dimmers (single or double push-button), scenes (storage and activation), impulse count. The output channels are used for the execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, and scene management commands.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).



GW A9 126

KNX 12/6-channel 8AX switch and roller shutter actuator with manual operation - IP20 - Din rail mounting

Code	No. output channels	Output contacts	No. DIN modules	Pack Carton
GW A9 126	12	12NO 8AX 230Vac	8	1

CHARACTERISTICS: 12-channel switch actuator with potential-free output contacts (NO) for activating 12 loads or 6 shutters/venetian blinds with 230Vac motors. Each single pair of channels can be separately configured for switching loads or roller shutter command. Suitable for commanding incandescent lamps (230Vac): 1500W, halogen lamps (230Vac): 1500W, loads controlled from toroidal transformers: 1200W, loads controlled from electronic transformers: 1000W, energy saving lamps (compact fluorescent): 25x23W, LED lamps (230Vac): 25x10W, motors: 800W. Max switchover currents 8A (AC1), 8AX (140µF ref. EN 60669-1) fluorescent loads with maximum surge current 300A (150µs). Equipped with front push-buttons for manual activation, and signalling LED for closure of output contact. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, timed commands with pre-alarm at switch-off, priority commands, scene management commands, block commands, safety functions, logic functions, counters, output status signal, commands of movement/adjustment/stopping, alarm signalling.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid). Possibility to activate the loads manually, even without the BUS voltage (230Vac auxiliary power supply required).

Dimmer actuators



GW A9 313

KNX dimmer actuator for electronic ballast 1-10V - 3 channels - IP 20 - DIN rail mounting

Code	No. of channels	Output contacts	Max current per channel	No. DIN modules	Pack Carton
GW A9 313	3	16 AX (140µF) - 230 V ac	100 mA	4	1

CHARACTERISTICS: it has 3 output channels 1-10V for commanding ballast with 1-10 V interface and 3 relay On/Off output channels switching the ballast power off. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, relative and absolute light intensity adjustment, scene management, timed commands, priority commands, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).

KNX universal dimmer actuators - IP20 - DIN rail mounting



GW A9 302

Code	Supply voltage	No. output channels	Power max.	No. DIN modules	Pack Carton
GW A9 301	230V ac - 50/60 Hz	1	500 VA	4	1
GW A9 302	230V ac - 50/60 Hz	2	300VA per channel	4	1

CHARACTERISTICS: for the adjustment and switching of incandescent and halogen lamps 230Vac, low voltage halogen lamps with electronic and winding transformers, LED lamps 230Vac with dimmer function, and CFL lamps with dimmer function. Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection, front LEDs for signalling the status of the outputs. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, relative and absolute light intensity adjustment, scene management, timed commands, priority commands, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
Products available while stock lasts.

KNX Secure universal dimmer actuators - IP20 - DIN rail mounting



GW A9 322

Code	Supply voltage	No. output channels	Power max.	No. DIN modules	Pack Carton
GW A9 321	230 V ac - 50/60 Hz	1	500 VA	4	1
GW A9 322	230 V ac - 50/60 Hz	2	300VA per channel	4	1

CHARACTERISTICS: for the adjustment and switching of incandescent and halogen lamps 230Vac, low voltage halogen lamps with electronic and winding transformers, LED lamps 230Vac with dimmer function, and CFL lamps with dimmer function. Manual selection of the type of load (Leading Edge or Trailing Edge piloting), soft-start function for lamp protection, front LEDs for signalling the status of the outputs, the four local command push-buttons can be enabled/disabled via KNX BUS. The device supports KNX Data Secure. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, relative and absolute light intensity adjustment, scene management, timed commands, priority commands, logic functions.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
Please contact GEWISS sales team for the date of availability.

Bleeder - 230Vac - 50Hz



GW A9 350

Code	Description	Dimensions LxHxD (mm)	Pack Carton
GW A9 350	Bleeder	38x32x14	1/48

CHARACTERISTICS: load adapter for dimmable LED lamps. Equipped with 15 cm long cables.
APPLICATIONS: suitable for KNX Secure universal (GWA9321, GWA9322, GWA9301, GWA9302) or traditional (GW1x572, GW1x573) dimmers.

KNX universal dimming actuator with manual operation - IP20 - DIN rail mounting



GW A9 303

Code	Supply voltage	No. output channels	Power max.	No. DIN modules	Pack Carton
GW A9 303	230V ac - 50 Hz	2	400 W per channel	4	1

CHARACTERISTICS: for the adjustment and switching of incandescent lamps, halogen lamps (high and low voltage), compact adjustable fluorescent lamps (energy saving lamps), 230Vac adjustable LED lamps and fans (max. 100W). Automatic load recognition and light intensity regulation power: 400W per channel or 800W in parallel operation. The device has frontal buttons for manual operation and signalling leds for the operation status of each channel. To be configured via ETS software.
APPLICATIONS: light intensity regulation, regulation value limitations, soft switchover, block function, forced operation, scenarios, status return on channels, operating hour-counter and signalling for assistance, management during mains or bus failure and reset, diagnosis messages.
NOTES: equipped with coupling terminal for connection to BUS. Possibility to activate the loads manualy, even without the bus voltage.

KNX dimmer actuator for LED loads - IP20 - DIN rail mounting



GW 90 764

Code	Supply voltage	No. output channels	Type of control	No. DIN modules	Pack Carton
GW 90 764	12-24V dc	4	CVD	4	1
GW 90 765	12-48V dc	4	CCD	4	1

CHARACTERISTICS: dimmer in CVD version (control with constant voltage) for regulating RGB(W) LED strips, and in CCD version (control with constant current) for regulating "power" LEDs. 4 front button keys for testing the outputs and 4 front LEDs for signalling the load status and other operating parameters. To be configured with ETS software.
APPLICATIONS: execution of ON-OFF commands, regulation and setting of the light intensity level for each single channel (and the 4 channels simultaneously), selection of feedback on status or light intensity value, scene management, timed sequences, priority commands, logic functions. The 4 outputs can be used to control each of the 4 channels R, G, B and W of a single LED lamp, or up to 4 independent LEDs.
NOTES: equipped with coupling terminal for connection to BUS (with protection lid).
GW90764:product available while stock lasts.

NEWS



GW A9 326

KNX Secure dimmer actuator for CVD LED loads - IP20 - DIN rail mounting

Code	Supply voltage	No. output channels	Type of control	No. DIN modules	Pack Carton
GW A9 326	12-24V dc	4	CVD	4	1

CHARACTERISTICS: dimmer in CVD version (control with constant voltage) for regulating RGB(W) LED strips. 4 front push buttons for local implementation that can be enabled/disabled via KNX BUS 4 front LEDs for signalling the load status and other operating parameters. The device supports KNX Secure. To be configured with ETS software.

APPLICATIONS: execution of ON-OFF commands, regulation and setting of the light intensity level for each single channel (and the 4channels simultaneously), selection of feedback on status or light intensity value, scene management, timed sequences, prioritycommands, logic functions. The 4 outputs can be used to control each of the 4 channels R, G, B and W of a single LED lamp, or up to 4 independent LEDs. Auxiliary relay also controllable via KNX BUS.

NOTES: equipped with coupling terminal for connection to BUS (with protection lid).

Please contact GEWISS sales team for the date of availability.



GW 90 766

Booster for CVD LED dimmer actuators 4x10 A - IP20 - DIN rail mounting

Code		Supply voltage	No. output channels	Max current per channel	No. DIN modules	Pack Carton
GW 90 766		12-24V dc	4	10A	4	1/4
GW 90 768	ⓘ	12-24V dc	4	16A	4	1/4

CHARACTERISTICS: device used to extend the driving capacity of CVD LED dimmers.

APPLICATIONS: to be used with LED dimmer actuators with CVD KNX control (GWA9326, GW90764).

NOTES: equipped with a coupling terminal for connection to BUS, with protective cover.

Fan coil actuators



GW A9 140

KNX fan coil actuator - IP20 - DIN rail mounting

Code	Supply voltage	No. input channels	Valves output contacts	Fan relay contacts	Additional relay contacts	No. DIN modules	Pack Carton
GW A9 140	230V ac - 50 Hz	2	0,5A (24-230 V ac), triac	8A (AC1) 250 V ac	16A (AC1) 250 V ac	4	1

CHARACTERISTICS: actuator for the command of fan coils with 2- or 3-point heating/cooling valves and up to 3 fan levels in 2- and 4-pipe systems. Equipped with an additional programmable relay (eg: to control a heating/cooling battery or as a switching output) and two potential-free inputs for windows contact or temperature probe sensor (es: GWA9145) and condensate monitoring. The device has frontal Test buttons (for a simple check of fan levels and heating/cooling switching during the setup steps) and 9 signalling leds for the operation status. Regulation is via an external control variable or the integrated ambient thermostat (in the latter case it is necessary to add the temperature probe sensor). To be configured via ETS software.

APPLICATIONS: KNX timed thermostats and thermostats that can be used with the fan coil actuators GWA9140 and GWA9141:

- THERMO ICE KNX surface-mounting thermostat GW16976CB/CN/CT: for controlling all the functions of the fan coil actuators (that shall be configured to work with kind of used controller "remote controller") and commanding the fan in both automatic and manual mode.
- THERMO ICE KNX flush-mounting thermostat GW16974CB/CN/CT: attention - this thermostat can only be used in KNX-SYSTEM mode (configurable with ETS). For controlling the fan coil actuators (that shall be configured to work with kind of used controller "remote controller") and commanding the fan in automatic mode only - i.e. the thermostat conveys the valve opening request (0..100% byte) to the fan coil actuators, which automatically define the fan speed; the fan speed cannot therefore be controlled via the thermostat.
- Other KNX SYSTEM timed thermostats, thermostats and probes: attention - these models permit only limited use of the control functions of the fan coil actuators (that shall be configured to work with kind of used controller "remote controller"), so their validity should be evaluated for the individual situation on the basis of the application requisites.
- KNX EASY timed thermostats, thermotats and probes: attention - these models cannot be used to control the fan coil actuators.

NOTES: equipped with coupling terminal for connection to BUS.



GW A9 141

KNX fan coil actuator 0-10V - IP20 - DIN rail mounting

Code	Supply voltage	No. input channels	Valves and fan output	Fan relay contacts	Additional relay contacts	No. DIN modules	Pack Carton
GW A9 141	100-240 V ac - 50-60 Hz	2	0-10V, max 10mA	6A (AC1) 250 V ac	16A (AC1) 250 V ac	4	1

CHARACTERISTICS: actuator for the command of fan coils with 0-10V proportional heating/cooling valves and up to 3 fan levels (or with 0-10V proportional output) in 2- and 4-pipe systems. Equipped with an additional progrmmable relay (eg: to control a heating/cooling battery or as a switching output) and two potential-free inputs for windows contact or temperature probe sensor (es: GWA9145) and condensate monitoring. The device has frontal Test buttons (for a simple check of fan levels and heating/cooling switching during the setup steps) and 9 signalling leds for the operation status. Regulation is via an external control variable or the integrated ambient thermostat (in the latter case it is necessary to add the temperature probe sensor). To be configured via ETS software.

APPLICATIONS: KNX timed thermostats and thermostats that can be used with the fan coil actuators GWA9140 and GWA9141:

- THERMO ICE KNX surface-mounting thermostat GW16976CB/CN/CT: for controlling all the functions of the fan coil actuators (that shall be configured to work with kind of used controller "remote controller") and commanding the fan in both automatic and manual mode.
- THERMO ICE KNX flush-mounting thermostat GW16974CB/CN/CT: attention - this thermostat can only be used in KNX-SYSTEM mode (configurable with ETS). For controlling the fan coil actuators (that shall be configured to work with kind of used controller "remote controller") and commanding the fan in automatic mode only - i.e. the thermostat conveys the valve opening request (0..100% byte) to the fan coil actuators, which automatically define the fan speed; the fan speed cannot therefore be controlled via the thermostat.
- Other KNX SYSTEM timed thermostats, thermostats and probes: attention - these models permit only limited use of the control functions of the fan coil actuators (that shall be configured to work with kind of used controller "remote controller"), so their validity should be evaluated for the individual situation on the basis of the application requisites.
- KNX EASY timed thermostats, thermotats and probes: attention - these models cannot be used to control the fan coil actuators.

NOTES: equipped with coupling terminal for connection to BUS.

NEWS

Availability: ⓘ July 2025



GW A9 145

Temperature probe sensor

Code	Capsule diameter (mm)	Capsule length (mm)	Cable length (m)	IP degree	Pack Carton
GW A9 145	6	30	4	IP65	1

CHARACTERISTICS: NTC sensor 100K.
NOTES: to be used in combination with KNX fan coil actuators.

TEMPERATURE CONTROL - KNX

Climate control



GW 14 794 H

KNX timed thermostats/programmers with humidity management

Code	Colour	Output contacts	Humidity sensor	No. modules	Pack Carton
GW 10 794 H	Glossy white	1NO / NC 5A(AC1) 250V ac	Not included	3	1
GW 15 794 H	Satin white	1NO / NC 5A(AC1) 250V ac	Not included	3	1
GW 13 794 H	Natural satin beige	1NO / NC 5A(AC1) 250V ac	Not included	3	1
GW 12 794 H	Satin black	1NO / NC 5A(AC1) 250V ac	Not included	3	1
GW 14 794 H	Glossy titanium	1NO / NC 5A(AC1) 250V ac	Not included	3	1

CHARACTERISTICS: flush-mounting timed thermostat with humidity management, that can be programmed on a weekly basis to control heating/cooling and humidification/dehumidification systems on the BUS. 3-level temperature profile (comfort, pre-comfort, economy). Control algorithms for 2- or 4-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous), fan coil (max. 3 speeds). Includes: 1 output for commanding the area solenoid valve (or as a generic output for executing ON/OFF commands, timed commands, priority commands or scene management); 1 input for the potential-free contact (for the window contact function, or for managing fronts, dimmers, roller shutters and scenes); 1 input for the external temperature NTC probe sensor (e.g. protection for floor-mounting heating) or, alternatively, as a second input for a potential-free contact. With 10 hour profiles that can be freely used (programmer function) plus another two reserved for the timed thermostat, with 15-minute resolution. Equipped with an extractable front and LCD display with customisable RGB backlighting. To be configured with ETS software.
APPLICATIONS: can be combined with KNX flush-mounting thermostats for local temperature adjustment: In this case, the timed thermostat acts as a master, sending the temperature profile to the BUS.
NOTES: equipped with coupling terminal for connection to BUS. The device requires a back-up power supply from 2 AA alkaline batteries (not included), housed in the extractable front, to guarantee the updating of the calendar (day, time) in the event of a BUS voltage failure. **The device does not have a built-in humidity sensor, so the relative humidity value must be obtained from an external KNX sensor (es: GW1x762H).**



GW 14 795 H

KNX thermostats with humidity management

Code	Colour	Output contacts	Humidity sensor	No. modules	Pack Carton
GW 10 795 H	Glossy white	1NO / NC 5A(AC1) 250V ac	Not included	2	1
GW 15 795 H	Satin white	1NO / NC 5A(AC1) 250V ac	Not included	2	1
GW 13 795 H	Natural satin beige	1NO / NC 5A(AC1) 250V ac	Not included	2	1
GW 12 795 H	Satin black	1NO / NC 5A(AC1) 250V ac	Not included	2	1
GW 14 795 H	Glossy titanium	1NO / NC 5A(AC1) 250V ac	Not included	2	1

CHARACTERISTICS: flush-mounting thermostat with humidity management, to control heating/cooling and humidification/dehumidification systems on the BUS and to manually manage the temperature on three levels (comfort, pre-comfort, economy). Control algorithms for 2- or 4-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous), fan coil (max. 3 speeds). Includes: 1 output for commanding the area solenoid valve (or as a generic output for executing ON/OFF commands, timed commands, priority commands or scene management); 1 input for the potential-free contact (for the window contact function, or for managing fronts, dimmers, roller shutters and scenes); 1 input for the external temperature NTC probe sensor (e.g. protection for floor-mounting heating) or, alternatively, as a second input for a potential-free contact. Equipped with an LCD display with customisable RGB backlighting. To be configured with ETS software.
APPLICATIONS: can be combined with KNX flush-mounting timed thermostats for local temperature adjustment: in this case, the thermostat acts as a Slave, executing the temperature profile sent from the Master (timed thermostat), using the locally defined setpoint values. If the system contains remote elements with their own control logic (e.g. flush-mounting KNX temperature adjustment probes), the thermostat can be used to visualise and set their operating parameters (max. 4 elements).
NOTES: equipped with coupling terminal for connection to BUS. **The device does not have a built-in humidity sensor, so the relative humidity value must be obtained from an external KNX sensor (es: GW1x762H).**



GW 14 799

KNX temperature sensors

Code	Colour	No. modules	Pack Carton
GW 10 799	Glossy white	1	1
GW 15 799	Satin white	1	1
GW 13 799	Natural satin beige	1	1
GW 12 799	Satin black	1	1
GW 14 799	Glossy titanium	1	1

CHARACTERISTICS: flush-mounting temperature adjustment probe for controlling heating/cooling systems on the BUS. 3-level temperature profile (comfort, pre-comfort, economy). Control algorithms for 2- or 4-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous), fan coil (max. 3 speeds). Includes: 1 input for the potential-free contact (for the window contact function, or for managing fronts, dimmers, roller shutters and scenes); 1 input for the external temperature NTC probe sensor (e.g. protection for floor-mounting heating) or, alternatively, as a second input for a potential-free contact. Equipped with a front LED signalling the operating status and the load status (solenoid valve). To be configured with ETS software.
APPLICATIONS: can be combined with thermostats GW1x795H or timed thermostats GW1x794H to adjust the temperature in specific areas and for controlling and displaying the probe parameters (the probe does not have a display).
NOTES: it is equipped with coupling terminal for connection to bus.



GW 14 799 H

KNX humidity/temperature sensors

Code	Colour	Humidity sensor	No. modules	Pack Carton
GW 10 799 H	Glossy white	Built-in	1	1
GW 15 799 H	Satin white	Built-in	1	1
GW 13 799 H	Natural satin beige	Built-in	1	1
GW 12 799 H	Satin black	Built-in	1	1
GW 14 799 H	Glossy titanium	Built-in	1	1

CHARACTERISTICS: flush-mounting temperature adjustment probe with humidity sensor for controlling heating/cooling systems and humidification/dehumidification systems on the BUS. 3-level temperature profile (comfort, pre-comfort, economy). Control algorithms for 2- or 4-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous), fan coil (max. 3 speeds). Includes: 1 input for a potential-free contact (for the window contact function, or for managing fronts, dimmers, roller shutters and scenes); 1 input for the external temperature NTC probe sensor (e.g. protection for floor-mounting heating) or, alternatively, as a second input for a potential-free contact. Equipped with a front LED signalling the operating status and the load status (solenoid valve). To be configured with ETS software.
APPLICATIONS: can be combined with thermostats GW1x795H or timed thermostats GW1x794H to adjust the temperature in specific areas and for controlling and displaying the probe parameters (the probe does not have a display).
NOTES: it is equipped with coupling terminal for connection to bus.



GW 14 762 H

KNX temperature/humidity sensors

Code	Colour	Humidity sensor	No. modules	Pack Carton
GW 10 762 H	Glossy white	Built-in	1	1
GW 15 762 H	Satin white	Built-in	1	1
GW 13 762 H	Natural satin beige	Built-in	1	1
GW 12 762 H	Satin black	Built-in	1	1
GW 14 762 H	Glossy titanium	Built-in	1	1

CHARACTERISTICS: flush-mounting temperature/humidity sensor for sending temperature and relative humidity values on the KNX BUS. Temperature range: 0…+45°C. Relative humidity range: 10-95%. Equipped with a front signalling LED. To be configured with ETS software.
NOTES: equipped with coupling terminal for connection to BUS.



GW 10 800

Outdoor temperature probe sensor

Code	Capsule diameter (mm)	Capsule length (mm)	Cable length (m)	IP degree	Pack Carton
GW 10 800	5	20	3	IP68	1

CHARACTERISTICS: NTC sensor 10K BETA 3435 1%. Temperature range: -50...+110°C; accuracy: ±1%; capsule material: thermoplastic rubber.
NOTES: for use in combination with timed thermostats, thermostats, flush mounting KNX temperature/humidity sensors, input modules.



GW 14 900

Temperature probe sensors

Code	Colour	No. modules	Pack Carton
GW 10 900	Glossy white	1	1
GW 15 900	Satin white	1	1
GW 13 900	Natural satin beige	1	1
GW 12 900	Satin black	1	1
GW 14 900	Glossy titanium	1	1

CHARACTERISTICS: flush-mounting temperature sensor, NTC 10K±2%, BETA 3977±0,75%, temperature range: -40…+125°C. Equipped with a front signalling LED.
NOTES: for use in combination with timed thermostats, temperature sensors, flush-mounting KNX temperature/humidity sensors, input modules, etc.



GW 16 974 CN

KNX THERMO ICE thermostats

Code	Colour	Power supply	Dimensions LxHxD (mm)	Pack Carton
GW 16 974 CB	White	12-24V ac/dc	123,2x95,2x10,7	1
GW 16 974 CL	Natural beige	12-24V ac/dc	123,2x95,2x10,7	1
GW 16 974 CN	Black	12-24V ac/dc	123,2x95,2x10,7	1
GW 16 974 CT	Titanium	12-24V ac/dc	123,2x95,2x10,7	1

CHARACTERISTICS: flush-mounting thermostat for controlling heating/cooling systems via BUS, and manual or 3-level temperature management (comfort, pre-comfort, economy). Control algorithms for two- or four-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous 0%-100%), fan coil (max. 3 speeds with ON/OFF control). Allows control of humidification and dehumidification systems if connected to an external humidity sensor (e.g. GW1x762H). Has 1 input for potential-free contact (for window contact function, for managing fronts, dimmers, shutters or scenarios); 1 input for NTC external temperature sensor (e.g. protection for underfloor heating) or, alternatively, as a second input for potential-free contact. Equipped with user interface with touch-type (capacitive) controls on glass plate and rear-projection display. The thermostat has integrated proximity and temperature sensors. Configuration is via ETS software.
APPLICATIONS: option to combine with flush-mounted KNX timed thermostats or KNX control panels for zoned temperature control: in this case, the thermostat acts as a slave, implementing the temperature profile sent from the master.
NOTES: equipped with a coupling terminal for connection to BUS. The thermostats include a front plate, electronic unit and metal support and are designed for screw fastening to either rectangular 3-gang boxes (83.5 mm centre distance) or round/square boxes (60 mm centre distance) equipped with installation columns. Plate materials: glass.

Power supply unit 12Vdc



GW 10 720

Code	Supply voltage	Output voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW 10 720	100 ÷ 240 V ac - 50/60 Hz	12V dc	300 mA	52x33x17	1/10

APPLICATIONS: to be used for powering LPG detectors (GW1x711, GW2x868, GW30520), methane detectors (GW1x712, GW2x867, GW30519); Thermo ICE KNX (GW16974CB, GW16974CL, GW16974CN, GW16974CT) thermostats.

KNX Secure THERMO ICE thermostat - wall-mounting



GW 16 976 CN

Code	Colour	Power supply	Dimensions LxHxD (mm)	Pack Carton
GW 16 976 CB	White	110-230V ac - 50/60Hz	123,2x95,2x20,6	1
GW 16 976 CL	Natural beige	110-230V ac - 50/60Hz	123,2x95,2x20,6	1/16
GW 16 976 CN	Black	110-230V ac - 50/60Hz	123,2x95,2x20,6	1
GW 16 976 CT	Titanium	110-230V ac - 50/60Hz	123,2x95,2x20,6	1

CHARACTERISTICS: wall-mounting thermostat to control heating/cooling and humidification/dehumidification systems on the BUS and manage the temperature in manual mode or on 3 levels (comfort, pre-comfort, economy). Control algorithms for 2- or 4-way systems: two points (ON/OFF or 0%/100%), proportional-integral (PWM or continuous adjustment 0%-100%), fan coil (max. 3 speeds or with continuous adjustment 0%-100%). Includes 1 input for external NTC temperature sensor (e.g.: protection for flood mounting heating). Equipped with a user interface with touch commands (capacitive) on technopolymer plate and backlit display. The thermostat has built-in proximity, temperature and humidity sensors. The device supports KNX Secure. To be configured with ETS software.
APPLICATIONS: can be combined with KNX flush-mounting timed thermostats or KNX control panels for local temperature adjustment: in this case, the thermostat acts as the slave by executing the temperature sent by the master. Available a "hotel" operating mode with simplified functionalities and user interface for hotel applications.
NOTES: equipped with coupling terminal for connection to bus. Wall fixing with wall plugs or screw fixing on rectangular 3 modules boxes (centre distance 83.5 mm). Plate material: technopolymer.

ENERGY CONTROL - KNX

P-COMFORT

KNX Secure load management relay P-COMFORT - IP20 - DIN rail mounting



GW A9 916

Code	Supply voltage	Rated current	Type relay contact	Capacity relay contact	No. DIN modules	Pack Carton
GW A9 916	230V ac - 50Hz	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

CHARACTERISTICS: load management to control the activation/deactivation of electrical appliances wired to the relay inside the device or connected to KNX actuators, preventing the main line power supply disconnection and avoiding service interruptions. The device supports KNX Secure. To be configured with ETS software.
APPLICATIONS: allows the measurement, the visualisation on the display and the sending on the KNX bus of the active energy (exported and imported), instantaneous active and reactive power (exported and imported), voltage, current, power factor and frequency.
NOTES: equipped with coupling terminal for connection to bus.

KNX- energy meters

KNX Secure single-phase energy meter for direct connection - IP20 - DIN rail mounting



GW A9 801

Code	Supply voltage	Rated current	No. DIN modules	Pack Carton
GW A9 801	230V ac - 50Hz	32 A	2	1/6

CHARACTERISTICS: the device supports KNX Secure. To be configured with ETS software.
APPLICATIONS: allows the measurement, the visualisation on the display and the sending on the KNX bus of the active energy (exported and imported), instantaneous active and reactive power (exported and imported), voltage, current, power factor and frequency.
NOTES: equipped with coupling terminal for connection to bus.

Traditional energy meters



GW D6 801

Single-phase digital energy meters for direct connection - IP20 - DIN rail mounting

Code	Type MID	N. digit	Accuracy	I max (A)	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 801	No	5 unit + 2 decimals	1	40 A	230 ac	1	1/5
GW D6 802	Yes	5 unit + 2 decimals	1	40 A	230 ac	1	1/5

APPLICATION: allows the measurement and visualisation on the display of the active energy values (exported and imported), istantaneous active power (exported and imported), voltage, current, power factor and frequency.
If used with the KNX GW90876 interface, the measured values can be sent on the KNX BUS.
If used with the MODBUS GWD6820 interface, the measured values can be sent on Modbus RS485.
CHARACTERISTICS: the energy meters have an impulse output for remote energy consumption control.



GW D6 809

Three-phase digital energy meters - IP20 - DIN rail mounting

Code	Type MID	N. digit	Accuracy	Connection	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW D6 807	Yes	6 unit + 2 decimals	1 (active energy) 2 (reactive energy)	Direct (I max=80 A)	400 ac	4	1/2
GW D6 809	Yes	6 unit + 2 decimals	1 (active energy) 2 (reactive energy)	Using C.T./5 A	400 ac	4	1/2

APPLICATION: allow the measurement and the visualization on display of the active and reactive energy values (exported and imported), and instantaneous active and reactive power values (exported and imported). If used with the KNX GW90876 interface, the measured values can be sent on the KNX BUS.
If used with the MODBUS GWD6820 interface, the measured values can be sent on Modbus RS485.
CHARACTERISTICS: the meters have two impulse outputs for remote energy consumption control.

KNX interface



GW 90 876


KNX interface for traditional energy meter - IP20 - DIN rail mounting

Code	No. DIN modules	Pack Carton
GW 90 876	1	1/5

CHARACTERISTICS: to be configured with ETS software.
APPLICATIONS: it communicates the values of energy and power as measured by the GWD6801, GWD6802, GWD6807, GWD6809 energy meters on the KNX bus system. The KNX interface is optically coupled to the energy meter (the two devices have to be installed side-by-side).
NOTE: it is equipped with a coupling terminal for connection to bus.

ACCESS CONTROL AND HOTEL MANAGEMENT

Transponder units



GW 16 891 CN

KNX transponder card reader unit

Code	Colour	Power supply	Dimensions LxHxD (mm)	Pack Carton
GW 16 891 CB	White	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 891 CL	Natural beige	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 891 CN	Black	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 891 CT	Titanium	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1

CHARACTERISTICS: the transponder card reader unit allows the recognition of cards with RFID-MIFARE® transponder technology, use the cards from Gewiss catalogue. Card recognition is reported to the hotel access control and management software and can be configured to control other actions and automations. The devices are equipped with 2 inputs for potential-free contacts and 2 NO relay outputs for SELV circuits (max switching voltage 30Vdc / 24Vac, max switching current 5A(AC1) 1A (AC3)).
APPLICATIONS: the inputs can be used to detect the status of sensors or to send on/off and toggle commands, dimming commands (1 or 2 buttons), shutter commands, sequence commands, scenario commands, short/long press commands; the pulse counter function is also available. The outputs can control generic loads on, off, timed on, with flashing. The devices implement advanced logical functions and the "Virtual holder" function.
NOTES: the devices include a technopolymer front plate and a KNX bus terminal; the devices are suitable for screw fixing on 3-module rectangular (GW24403, GW24403PM), round (GW24234, GW24234PM) or square (GW24231) boxes.

NEWS

KNX transponder card holder unit



GW 16 892 CN

Code	Colour	Power supply	Dimensions LxHxD (mm)	Pack Carton
GW 16 892 CB	White	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 892 CL	Natural beige	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 892 CN	Black	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1
GW 16 892 CT	Titanium	SELV: 12-24 Vac 50/60Hz, 12-32 Vdc	110,0x78,0x12,1	1

CHARCTERISTICS: the transponder card holder unit allows the recognition of cards with RFID-MIFARE® transponder technology, use the cards from Gewiss catalogue. Card recognition is reported to the hotel access control and management software and can be configured to control other actions and automations. The devices are equipped with 2 inputs for potential-free contacts and 2 NO relay outputs for SELV circuits (max switching voltage 30Vdc / 24Vac, max switching current 5A(AC1) 1A (AC3)).

APPLICATIONS:the inputs can be used to detect the status of sensors or to send on/off and toggle commands, dimming commands (1 or 2 buttons), shutter commands, sequence commands, scenario commands, short/long press commands; the pulse counter function is also available. The outputs can control generic loads on, off, timed on, with flashing. The devices implement advanced logical functions and the "Virtual holder" function.

NOTES: the devices include a technopolymer front plate and a KNX bus terminal; the devices are suitable for screw fixing on 3-module rectangular (GW24403, GW24403PM), round (GW24234, GW24234PM) or square (GW24231) boxes.

Transponder card programming unit



GW 16 893 CN

Code	Colour	Power supply	Dimensions LxHxD (mm)	Pack Carton
GW 16 893 CN	Black	Via USB	98x98x100	1

CHARACTERISTICS: the transponder card programming unit allows the writing/reading of cards with RFID-MIFARE® transponder technology, use cards from the Gewiss catalogue. Powered directly via USB cable connected to a USB port (5V 160mA) of the card programming PC (e.g. reception).

APPLICATIONS: to program the cards, a client license must be installed on the PC (included in the GW Host software package).

NOTES: the device is supplied already installed in a table box complete with technopolymer front plate and USB cable.

MIFARE® transponder card



GW 16 899

Code	Dimensions LxH (mm)	Pack Carton
GW 16 899	86x54	10/40

CHARACTERISTICS: the card can be programmed using a transponder programming unit. The same card can be enabled for more than one transponder raeder units and transponder holder units.

NOTES: space available for customization (e.g. with hotel name and logo), for customization requests contact the Gewiss sales organization.

Software

GW HOST



GW A9 787

Code	Description	No. pages managed	Mini-PC included	No. client licenses included	Pack Carton
GW A9 787	GWHost hotel management sw	Up to 15	Yes	3	1
GW A9 788	GWHost hotel management sw	Up to 35	Yes	3	1
GW A9 789	GWHost hotel management sw	Up to 100	Yes	3	1
GW A9 790	GWHost hotel management sw	More than 100	Yes	3	1

CHARACTERISTICS: software developed to dialog with devices on KNX bus, suitable for the access management in hotel facilities and tertiary, with different sizes according to the number of required supervision pages (rooms, common areas, etc.). They include the GWHost software pre-installed in a mini-PC with USB dongle license and 3 client licenses that can be installed in as many PCs running Windows (es: reception). For additional client licenses (necessary in case more than 3 PCs are required to be connected to the mini-PC) or how to interface GWHost with the most common hotel management sw, please refer to the Gewiss technical assistance.

NOTE: the mini-PC included in GWHost is a compact hardware platform, based on Microsoft® Windows, that connects to the PC in reception via LAN network.

NEWS

WEATHER SENSORS - KNX

Devices

KNX weather station - IP44



GW 90 800

Code	Power supply	Assembly	Dimensions LxHxD (mm)	Pack Carton
GW 90 800	24V ac/dc, max. 100mA	Wall/pole-mounting	96x77x118	1

CHARACTERISTICS: includes the following sensors: rain, temperature (from -40°C to +80°C), luminosity (from 0 lux to 150000 lux), wind (from 0 m/s to 35 m/s). The weather station includes a GPS receiver for determining coordinates, data and hour.
APPLICATIONS: the weather station stores and processes the analogue signals coming from the embedded sensors.
NOTES: equipped with coupling terminal for connection to BUS.

KNX light intensity sensor - IP44



GW 90 884

Code	Power supply	Current consumption	Measurement interval	Dimensions LxHxD (mm)	Pack Carton
GW 90 884	KNX BUS voltage	10 mA	0…150000 lux	96x77x118	1

CHARACTERISTICS: the device measures the light intensity. With light-sensitive sensor function. To be configured with ETS software.
APPLICATIONS: detects and analyses the light level.
NOTES: equipped with coupling terminal for connection to BUS.

KNX temperature sensor - IP65



GW 90 885

Code	Power supply	Current consumption	Measurement interval	Dimensions LxHxD (mm)	Pack Carton
GW 90 885	KNX BUS voltage	5.5 mA	-40…+80°C	65x93x38	1

CHARACTERISTICS: the sensor measures the temperature. The sensor is also equipped with a PI (proportional integral) regulator for heating and air conditioning. To be configured with ETS software.
APPLICATIONS: measures the temperature.
NOTES: equipped with coupling terminal for connection to BUS.

COMPLEMENTARY ITEMS - KNX

Interfaces

KNX/DMX Gateway - DIN rail mounting



GW 90 871

Code	Power supply	No. DMX channels	Dimensions LxHxD (mm)	Pack Carton
GW 90 871	9-30V dc, 100mA	512	107x75x31 mm	1

APPLICATIONS: one-way interface that can receive the KNX BUS commands and re-transmit them towards the devices on the DMX BUS.
The interface manages up to 512 DMX channels.
NOTES: equipped with coupling terminal for connection to BUS.

Gateway KNX Secure/DALI2 advanced - multimaster 64/16 - DIN rail mounting



Code	Power supply	Max no. DALI units	Max no. DALI devices	No. DIN modules	Pack Carton
GW 90 873	100 - 240 V ac/dc - 50/60 Hz	16	64 lighting fixtures	4	1/4

CHARACTERISTICS: gateway capable of controlling up to 64 lamps managed with the DALI protocol via a KNX bus. In addition, up to 8 DALI motion detectors or DALI light sensors can be connected. The device supports DALI2 with multimaster operation in accordance with EN 62386-103 ed. 2. The power required for the connected DALI lamps and sensors is supplied directly by the device and no additional DALI power supplies are required.
The device supports KNX Secure and is configured via ETS software.
The device has an RJ45 LAN port for configuration and/or IP access. Category 1 equipment (in accordance with EN 62386-103).
APPLICATIONS: the device also enables the control of emergency lamps (with Data Type DT1) and lamps with colour control (with Data Type DT8).
NOTES: equipped with a coupling terminal for bus connection.
Contact the GEWISS sales department for the availability date.

GW 90 873

Accessories

Connection terminal to BUS



Code	Colour	Pack Carton
GW 90 807	Red - Black	50

APPLICATIONS: for connecting up to 4 pairs of conductors. Can also be used as a junction terminal.

GW 90 807

Connection terminal to SELV line



Code	Colour	Pack Carton
GW 90 808	Yellow - white	50

APPLICATIONS: for connecting up to 4 pairs of conductors. Can also be used as a junction terminal.

GW 90 808

KNX BUS cables



Code	Type	Description	Ø (mm)	Colour	CPR class	Pack Carton
GW 90 584	2 conductors 1 x 2 x 0.8	LSZH Cable sheath	5.2	Green	Cca-s1a,d0,a1	100
GW 90 585	4 conductors 2 x 2 x 0.8	LSZH Cable sheath	6.1	Green	Cca-s1a,d0,a1	100

CHARACTERISTICS: GW90584 made of 1 twisted pair of wires: red/black colour used for the power supply and the data transmission of the KNX devices. GW90585 made of 2 twisted pairs of wires: red/black colour used for the power supply and the data transmission of the KNX devices, yellow/white used for another SELV service power supply.
APPLICATIONS: can be installed with the 230V power supply cable, and are recommended for protruding or flush assembly, for arrangement in conduits, in dry environments, and outdoors if protected against direct solar irradiation.

GW 90 584

COMMAND DEVICES - ZIGBEE

Contact interfaces



GW A1 501

2-channel connected contact interfaces - ZigBee

Code	Supply voltage	No. input channels	Input voltage	Max cable length	Dimensions LxHxD (mm)	Pack Carton
GW A1 501	Battery powered	2	Potential-free	15 m	42x40x20	1/4
GW A1 502	230V ac - 50 Hz	2	230V ac	-	42x40x20	1/4

CHARACTERISTICS: interface for the connection of 2 independent input contacts (auxiliary axial commands, push buttons and traditional switches sensors etc.), potential-free (GWA1501) or live (GWA1502). GWA1501 powered by CR2032-type battery (replaceable).
APPLICATIONS: allows commands to be sent for ON-OFF, timed, roller shutters and Venetian blinds, dimmers, scenarios, priority commands and signalling the current state of the contact.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

ACTUATORS - ZIGBEE

Actuators for generic loads



GW A1 521

1-channel connected actuator - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 521	230V ac - 50 Hz	1	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of loads through a potential-free output contact (NO). Suitable for controlling incandescent lamps (230 V ac): 2300 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: (230 V ac): 150 W, motors: 500 W. Equipped with 1 input for local control of the output.
APPLICATIONS: ON-OFF control, timed commands, priority commands and scenario management. If used in combination with the ZigBee GWA1514 water sensor, the installation of a push button (NO) is required for the manual opening of the solenoid valve.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.



GW A1 522

2-channel connected actuator - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 522	230V ac - 50 Hz	2	2 NO 6A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 2-channel actuator for the activation of loads through a 230 V output contact (NO). Suitable for controlling incandescent lamps (230 V ac): 1400 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: 150 W, LED lamps (230 V ac): 150 W, motors: 500 W. Equipped with 2 inputs for local control of the outputs.
APPLICATIONS: ON-OFF control, timed commands, priority commands and management of scenarios.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Actuators for generic loads with power meter



GW A1 523

1-channel connected actuator with power meter - ZigBee

Code	Supply voltage	No. output channels	Output contacts	Dimensions LxHxD (mm)	Pack Carton
GW A1 523	230V ac - 50 Hz	1	1 NO 10A (AC1) 230 V ac	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of loads through a 230 V output contact (NO) and measurement of instantaneous power. Suitable for controlling incandescent lamps (230 V ac): 2300 W, loads driven by toroidal transformers: 450 W, loads driven by electronic transformers: 600 W, fluorescent lamps: (230 V ac): 150 W, motors: 500 W. Equipped with 1 input for local control of the output.
APPLICATIONS: ON-OFF control, timed commands, priority commands and management of scenarios and measurement of instantaneous power.
NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Actuators for roller shutters



GW A1 531

1-channel connected actuator for roller shutters - ZigBee

Code	Supply voltage	Max current supplied	Dimensions LxHxD (mm)	Pack Carton
GW A1 531	230V ac - 50 Hz	6A-230V ac (compl. 60669-2-1)	42x40x20	1/4

CHARACTERISTICS: 1-channel actuator for the activation of a motor to operate roller shutters, curtains, Venetian blinds, roller blinds etc. via 2 interlocked output contacts 230 V ac. Suitable for the control of motors: 500 W. Equipped with 2 inputs for local control of the outputs.

APPLICATIONS: controlling operation/adjustment/stop, priority commands, scenario management and alarm signalling.

NOTES: installation in flush-mounting boxes, junction boxes or clipped into the ChoruSmart GW1x750 blanking modules.

Smart plug



GW A1 526

Connected Smart Plug 230 V ac - German standard - ZigBee

Code	Type of plug	Socket-outlet type	Dimensions ØxH (mm)	Colour	Pack Carton
GW A1 526	2P+E - 10A	2P+E - 10A	41x45	White	1/2

CHARACTERISTICS: adaptor with socket, side earthing and safety shields. It detects power consumed by the connected loads and sends the data on the ZigBee network.

LOAD MANAGEMENT - ZIGBEE

Load management kits



GW A1 912

Pre-installed kit P-Comfort RF Zigbee and Smart plug

Code	Number of smart plugs included	Pack Carton
GW A1 911	1	1
GW A1 912	2	1

CHARACTERISTICS: P-Comfort RF ZigBee provided with the kit is pre-installed to operate in Priority mode: when the power threshold is exceeded, loads connected to the Smart plug 1 are disconnected, then the loads connected to the Smart plug 2 and after all the loads wired to the relay inside the device. The reconnection of non-preferential loads is done following reverse sequence.

P-Comfort load management relay



GW A1 916

Connected P-Comfort load management relay - Zigbee

Code	Rated voltage (V)	Rated current	Type relay contact	Capacity relay contact	No. of modules EN 50022	Pack Carton
GW A1 916	230V ac	32 A	Changeover (potential free contact)	16 A AC1 250 V ac	2	1/6

APPLICATION: The P-Comfort relay can be installed in electrical systems limited to a maximum power load of 6 kW. In the event of overload due to the simultaneous switching-on of multiple electrical loads, P-Comfort prevents the interruption of electrical power by disconnecting non-preferred loads controlled by ZigBee-connected actuators: GW1x826, GWA1201, GWA1202, GWA1221, GWA1222, GWA1523, GWA1526, GWA1521 or GWA1522, or wired to the relay contact on the device (maximum 10 devices total). The disconnection and reconnection sequence for non-preferred loads can be set by Priority (regardless of load absorption) or by Power (depending on the power absorbed).

NOTES: The Zigbee-connected actuators GW1x826, GWA1201, GWA1202, GWA1221, GWA1222 can only be controlled in combination with the "Home Gateway" GW1x840.

SENSORS AND ALARMS - ZIGBEE

Sensors



GW A1 511

Connected movement sensors - ZigBee - IP31

Code	Max range	Light sensor	Temperature sensor	Colour	Dimensions LxHxD (mm)	Pack Carton
GW A1 511	6 m	3…70.000 lux	0…50 °C	White	82x82x28	1/2
GW A1 511 A	9 m	3…70.000 lux	0…50 °C	White	71x71x21	1

CHARACTERISTICS: motion sensors with horizontal detection angle: ±45° and vertical detection angle: ±45°. Include a brightness sensor and a temperature sensor. GWA1511A: battery power supply type AA (x2); GWA1511: battery power supply type CR123 (replaceable).

NOTES: wall or shelf installation via included accessories.

For the control of actuations, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202, GWA1221 or GWA1222 (max 5 sensors per actuator) or with the connected Zigbee actuators GWA1526, GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202, GWA1221, GWA1222 can only be controlled in combination with the "Home Gateway" GW1x840.

GWA1511A: please contact GEWISS sales team for the date of availability. GWA1511 available while stock lasts.



GW A1 513

Connected window sensor - ZigBee - IP40

Code	Sensor type	Temperature sensor	Material	Colour	Dimensions LxHxD (mm)	Pack Carton
GW A1 513	Magnetic	0…50 °C	Plastic	White	76x26x17	1/4

CHARACTERISTICS: the sensor detects the opening and closing of doors and windows and includes a temperature sensor. Powered with 2 AAA type batteries (replaceable).

NOTES: Installation on doors or windows.

Use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator) or with the ZigBee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202 can only be controlled in combination with the "Home Gateway" GW1x840.

NEWS

Alarms

Connected smoke sensor - ZigBee - IP20



GW A1 512

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 512	85 dB/3 m	0...50 °C	White	Ø 65x40	1/3

CHARACTERISTICS: the sensor detects the presence of smoke and includes a temperature sensor. Power supplied by a CR123 type (replaceable) battery.

NOTES: wall or ceiling installation.

To operate a solenoid valve, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator if the actuator is configured for automatic solenoid reset; unlimited sensors for manual reset) or with Zigbee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator if the actuator is configured for automatic solenoid reset; unlimited sensors for manual reset). The Zigbee-connected actuators GW1x826, GWA1201, GWA1202 can only be commanded in conjunction with the "Home Gateway" GW1x840.

Connected water sensor - ZigBee - IP20



GW A1 514

Code	Siren output	Temperature sensor	Colour	Dimensions (mm)	Pack Carton
GW A1 514	85 dB/3 m	0...50 °C	White	Ø 60x37	1/3

CHARACTERISTICS: the sensor detects the presence of water and includes a temperature sensor. CR123 (replaceable) type battery power supply.

NOTES: floor installation or alternative wall mounted option using the accessory GWA1541.

To activate a solenoid valve, use the sensor in combination with the connected Zigbee actuators GW1x826, GWA1201 or GWA1202 (max 5 sensors per actuator if actuator is configured for automatic solenoid reset; unlimited sensors for manual reset) or with Zigbee actuators GWA1521, GWA1522, GWA1523 (max 1 sensor per actuator if actuator is configured for automatic solenoid reset; unlimited sensors for manual reset). Zigbee connected actuators GW1x826, GWA1201, GWA1202 can only be controlled in conjunction with the GW1x840 Home Gateway.

Wall-mounting support for flood alarm



GW A1 541

Code	Colour	Support dimension (mm)	Dimensions of probe (mm)	Cable max. length (cm)	Pack Carton
GW A1 541	White	Ø72x25	Ø50x8	85	1/4

APPLICATIONS: to be used for the wall-mounting of the Zigbee flood alarm GWA1514.

ACCESSORIES

Accessories



GW 14 750

Blanking modules for housing ZigBee contacts interfaces and actuators

Code	Colour	No. modules	Pack Carton
GW 10 750	Glossy white	1	1/12
GW 15 750	Satin white	1	1/12
GW 13 750	Natural satin beige	1	1/12
GW 12 750	Satin black	1	1/12
GW 14 750	Glossy titanium	1	1/12

CHARACTERISTICS: 1-module blanking module with pad-printing. Enables the housing and rapid identification of the recessed connected control devices, of the recessed connected actuators and the connected energy meter with load control.

NOTES: snap-in assembly.



Home & Building Pro



Scan the QR Code and find out all the technical informations.

ADVANCED SOLUTIONS



The system is suitable for the advanced automation of applications within a residential and small-to-medium offices. It is very flexible and allows you to control even very extensive installations with a large number of devices.

KNX INTERNATIONAL STANDARD

The system is based on the international standard protocol KNX, the world most widely used protocol for home and building automation applications, making them very robust and ensuring interoperability between devices from different manufacturers. This ensures reliable solutions free from the risk of technological obsolescence, which is a major difficulty with solutions based on proprietary protocols.

INTEGRATION WITH THIRD-PARTY SYSTEMS

In addition to offering a wide range of functions for controlling safety, comfort and consumption, the system is further complemented by the integration of third-party systems for video intercoms (2N system), access control using Smart Lock (ISEO Argo system) and for entertainment and audio (SONOS system).

Data and energy distribution





Data Center

Network cabling

p. 1182

28 Spic

Plugs, sockets and adapters
for domestic and similar uses

p. 1189

Data Center

19” Wall mount rack cabinets

19” cabinets



GW 38 406 - 6U
GW 38 407 - 9U
GW 38 408 - 12U
GW 38 409 - 15U

Cabinets D=400mm



GW 38 418 - 12U
GW 38 419 - 15U

Cabinets D=600mm

Spare parts



GW 38 590 - 6U
GW 38 591 - 9U
GW 38 592 - 12U
GW 38 593 - 15U

Replacement doors



GW 38 471
Replacement lock

Accessories



GW 38 485
Single fan

19” Floor rack cabinets

19” cabinets



GW 38 451 - 24U
GW 38 452 - 30U
GW 38 453 - 42U

Cabinets 600x600mm



GW 38 461 - 24U
GW 38 462 - 30U
GW 38 463 - 42U

Cabinets 800x800mm



GW 38 464 - 42U

Cabinet 800x1000mm

Spare parts



GW 38 594 - 24U
GW 38 596 - 30U
GW 38 598 - 42U

Replacement doors for cabinets
600x600mm



GW 38 595 - 24U
GW 38 597 - 30U
GW 38 599 - 42U

Replacement doors for cabinets
800x800mm



GW 38 599 - 42U

Replacement door for cabinet
800x1000mm



GW 38 472
Replacement lock

Accessories



GW 38 474 - 24U
GW 38 475 - 30U
GW 38 476 - 42U

Pair of posts



GW 38 480
600x600mm
GW 38 481
800x800mm
GW 38 482
800x1000mm

Plinths



GW 38 477
Kit with 8 metal rings for cabinets
800x800mm and 800x1000mm



GW 38 483
Coupling set for cabinets



GW 38 484
Set of 4 swiveling wheels



GW 38 479
Air circulation unit
complete with thermostat



GW 38 558
Earthing set

Accessories for 19” rack cabinets

Accessories




GW 38 603 - UTP/FTP
Empty patch panel for
24 RJ45 sockets - 1U



GW 38 612 - SC/LC
GW 38 613 - ST

Empty fiber optic panels for
24 ports - 1U



GW 38 607 - D=260mm
GW 38 608 - D=360mm

Fixed shelves - 2U



GW 38 609 - D=410mm

Sliding shelf - 2U



GW 38 606
Power strip with ita/ger std
sockets - 1U

GW 38 610
With brushes - 1U
GW 38 611
With 4 rings - 1U



Cable management panels

GW 38 601 - 1U
GW 38 602 - 2U



Blind panels



GW 38 557
Cage nuts and screws

Components and accessories

RJ45 connectors



GW 38 031 - Cat. 5e
GW 38 032 - Cat. 6
GW 38 033 - Cat. 6a

RJ45 - UTP



GW 38 034 - Cat. 5e
GW 38 035 - Cat. 6
GW 38 036 - Cat. 6a

RJ45 - FTP

Couplers



GW 38 056
HDMI



GW 38 057
USB

Patch cords and cables



GW 38 116
Cat. 5e - L=0,5m
GW 38 117
Cat. 5e - L=1m
GW 38 118
Cat. 5e - L=2m
GW 38 119
Cat. 5e - L=5m
GW 38 131
Cat. 6 - L=1m
GW 38 132
Cat. 6 - L=2m
GW 38 133
Cat. 6 - L=5m

Copper patch cords - UTP



GW 38 121
Cat. 5e - L=0,5m
GW 38 122
Cat. 5e - L=1m
GW 38 123
Cat. 5e - L=2m
GW 38 124
Cat. 5e - L=5m

Copper patch cords - FTP

Data Center

Network cabling

A complete system with components and accessories for LAN network cabling set-ups, for both copper wire and fibre optics. The range includes 19” surface-mounting boards and floor-standing cabinets, with a modern, innovative design, that enable extreme ease of wiring thanks to large internal volumes and lateral space. These solutions reduce installation time and allow for quick configuration at any time for new usage requirements.



COMPONENTS FOR COPPER WIRING

UTP data sockets for panel



GW 38 033

Unshielded RJ45 UTP sockets T568A/B

Code	Description	Use category	Cables type	Pack Carton
GW 38 031	RJ45	5e	UTP	10/50
GW 38 032	RJ45	6	UTP	10/50
GW 38 033	RJ45	6a	UTP	10/50

CHARACTERISTICS: terminals with tool-less etched insulation.

NOTES: for patch panels and adapters designed to house data connectors (ChoruSmart, System and Playbus) with Keystone Jack-type coupling.

UTP patch Cords



GW 38 116

RJ45 - RJ45 UTP unshielded patchcords

Code	Description	Use category	Cables type	Cable length	Colour	Pack Carton
GW 38 116	RJ45 - RJ45	5e	UTP 24 AWG	0.5 m	Grey	1/24
GW 38 117	RJ45 - RJ45	5e	UTP 24 AWG	1 m	Grey	1/24
GW 38 118	RJ45 - RJ45	5e	UTP 24 AWG	2 m	Grey	1/24
GW 38 119	RJ45 - RJ45	5e	UTP 24 AWG	5 m	Grey	1/24
GW 38 131	RJ45 - RJ45	6	UTP 24 AWG	1 m	Grey	1/24
GW 38 132	RJ45 - RJ45	6	UTP 24 AWG	2 m	Grey	1/24
GW 38 133	RJ45 - RJ45	6	UTP 24 AWG	5 m	Grey	1/24

PRODUCTION CHARACTERISTICS: 24 AWG copper conductor. Flameproof polyethylene insulation. Plug contacts in phosphorous bronze.

PERFORMANCE CHARACTERISTICS: performance is higher than what is envisaged for cat. 5e.

Compliant with the prescriptions required for applications such as 100BASE-Tx, 155Mbps ATM and Gigabit Ethernet.

ELECTRICAL CHARACTERISTICS AT 20°C: Impedance 100 Ohm +/- 15% 1-100 MHz; Capacity: 13.5 pF/ft at 1 MHz.

FTP data sockets for panel



GW 38 036

Shielded RJ45 FTP sockets T568A/B

Code	Description	Use category	Cables type	Pack Carton
GW 38 034	RJ45	5e	FTP	10/50
GW 38 035	RJ45	6	FTP	10/50
GW 38 036	RJ45	6a	FTP	10/50

CHARACTERISTICS: tool-less etching terminals.

NOTES: for permutation panels and adapters designed to house data connectors with Keystone Jack type coupling.

FTP patch Cords



GW 38 121

RJ45 - RJ45 FTP shielded patchcords

Code	Description	Use category	Cables type	Cable length	Colour	Pack Carton
GW 38 121	RJ45 - RJ45	5e	FTP 24 AWG	0.5 m	Grey	1/24
GW 38 122	RJ45 - RJ45	5e	FTP 24 AWG	1 m	Grey	1/24
GW 38 123	RJ45 - RJ45	5e	FTP 24 AWG	2 m	Grey	1/24
GW 38 124	RJ45 - RJ45	5e	FTP 24 AWG	5 m	Grey	1/24

CONSTRUCTION CHARACTERISTICS: 24 AWG copper conductor. Flameproof polyethylene insulation. Plug contacts in phosphorous bronze.
PERFORMANCE CHARACTERISTICS: performance is higher than what is envisaged for cat. 5e.
Compliant with the prescriptions required for applications such as 100BASE-Tx, 155Mbps ATM and Gigabit Ethernet.
ELECTRICAL CHARACTERISTICS AT 20°C: Impedance 100 Ohm +/- 15% 1-100 MHz. Capacity: 13.5 pF/ft at 1 MHz.

USB and HDMI couplers



GW 38 056

USB and HDMI couplers

Code	Description	Type	Compatibility	Pack Carton
GW 38 056	HDMI coupler	Female/Female	Keystone Jack	1/48
GW 38 057	USB coupler	Female/Female - A type	Keystone Jack	1/48

NOTES: for adapters designed to house data connectors (ChoruSmart, System and Playbus) with Keystone Jack type coupling and permutation panels.

RACK CABINETS

19” wall mount rack cabinets



GW 38 407

19” metal wall mount cabinets with transparent door

Code	Colour	No. uprights	Cabling unity	IP degree	Outer dim. LxHxD (mm)	Pack Carton
Depth (mm): 400 mm						
GW 38 406	Grey (RAL 7035)	2	6 U	IP20	600x335x400	1
GW 38 407	Grey (RAL 7035)	2	9U	IP20	600x470x400	1
GW 38 408	Grey (RAL 7035)	2	12 U	IP20	600x605x400	1
GW 38 409	Grey (RAL 7035)	2	15 U	IP20	600x740x400	1
Depth (mm): 600 mm						
GW 38 418	Grey (RAL 7035)	2	12 U	IP20	600x605x600	1
GW 38 419	Grey (RAL 7035)	2	15 U	IP20	600x740x600	1

CHARACTERISTICS: made from sheet steel, powder coated, texture finish, with upper, lower and rear cable entry. Movable and reversing 180° opening door with tempered glass window. Uprights adjustable in depth. Static load capacity 50Kg.
ACCESSORIES SUPPLIED: quick coupling blind side panels, rear panel, roof plate and base; lock with 2 keys; earthing set.



GW 38 591

Replacement doors for 19” wall mount cabinets

Code	Colour	For 19” wall mount cabinets	Pack Carton
GW 38 590	Grey (RAL 7035)	GW38406	1
GW 38 591	Grey (RAL 7035)	GW38407	1
GW 38 592	Grey (RAL 7035)	GW38408, GW38418	1
GW 38 593	Grey (RAL 7035)	GW38409, GW38419	1

CHARACTERISTICS: made from sheet steel, powder coated, texture finish and tempered glass window.
ACCESSORIES SUPPLIED: lock with 2 keys.

Replacement lock for 19” wall mount cabinets



GW 38 471

Code	Description	Pack Carton
GW 38 471	Security lock	1/30

CHARACTERISTICS: suitable for 19” wall mount cabinets.
ACCESSORIES SUPPLIED: lock with 2 keys.

Accessories for 19” wall mount cabinets



GW 38 485

Code	Description	Characteristics	Pack Carton
GW 38 485	Single fan	220-240 Vac - 50/60 Hz - 28 W	1

19” floor rack cabinets

19” metal floor rack cabinets with transparent door



GW 38 453

Code	Colour	No. uprights	Cabling unity	IP degree	Outer dim. LxHxD (mm)	Pack Carton
Depth (mm): 600 mm						
GW 38 451	Grey (RAL 7035)	2	24 U	IP20	600x1185x600	1
GW 38 452	Grey (RAL 7035)	2	30 U	IP20	600x1485x600	1
GW 38 453	Grey (RAL 7035)	2	42U	IP20	600x1985x600	1
Depth (mm): 800 mm						
GW 38 461	Grey (RAL 7035)	4	24 U	IP20	800x1185x800	1
GW 38 462	Grey (RAL 7035)	4	30 U	IP20	800x1485x800	1
GW 38 463	Grey (RAL 7035)	4	42U	IP20	800x1985x800	1
Depth (mm): 1000 mm						
GW 38 464	Grey (RAL 7035)	4	42U	IP20	800x1985x1000	1

CHARACTERISTICS: made from sheet steel, powder coated, texture finish, with upper and lower cable entry. Movable and reversing 135° opening door with tempered glass window. Uprights adjustable in depth. Static load capacity 1000Kg.
ACCESSORIES SUPPLIED: quick coupling blind side and rear panels, roof plate and base; adjustable levelling feet; lock with 2 keys; earthing set.

Replacement doors for 19” floor rack cabinets



GW 38 598

Code	Colour	For 19” rack cabinets	Pack Carton
GW 38 594	Grey (RAL 7035)	GW38451	1
GW 38 596	Grey (RAL 7035)	GW38452	1
GW 38 598	Grey (RAL 7035)	GW38453	1
GW 38 595	Grey (RAL 7035)	GW38461	1
GW 38 597	Grey (RAL 7035)	GW38462	1
GW 38 599	Grey (RAL 7035)	GW38463, GW38464	1

CHARACTERISTICS: made from sheet steel, powder coated, texture finish and tempered glass window.
ACCESSORIES SUPPLIED: lock with 2 keys.

Replacement lock for 19” floor rack cabinets



GW 38 472

Code	Description	Pack Carton
GW 38 472	Security lock	1/5

CHARACTERISTICS: suitable for 19” floor rack cabinets.
ACCESSORIES SUPPLIED: lock with 2 keys.

Pair of posts for 19” floor rack cabinets

Code	Cabling unity	Pack Carton
GW 38 474	24 U	1
GW 38 475	30 U	1
GW 38 476	42U	1

CHARACTERISTICS: made from zinc-plated sheet steel. Suitable for 19" floor rack cabinets.

GW 38 476

Plinths for 19” floor rack cabinets

Code	Colour	For 19” rack cabinets	Outer dim. LxHxD (mm)	Pack Carton
GW 38 480	Black RAL 9005	GW38451, GW38452, GW38453	600x100x600	1
GW 38 481	Black RAL 9005	GW38461, GW38462, GW38463	800x100x800	1
GW 38 482	Black RAL 9005	GW38464	800x100x1000	1

CHARACTERISTICS: made from painted sheet steel, wrinkle texture.



GW 38 480

Accessories for 19” floor rack cabinets

Code	Description	Characteristics	Colour	Pack Carton
GW 38 477	Kit with 8 metal rings	H 90 mm	Zinc-plated	1/8
GW 38 479	Air circulation unit	220-240 Vac - 50/60 Hz - 2x28 W	Black RAL 9005	1/8
GW 38 483	Coupling set for cabinets	-	-	1/15
GW 38 484	Set of 4 swiveling wheels	Provided with brakes. Load capacity 360 Kg	-	1
GW 38 558	Earthing set	Earth connection cables	-	1/30

CHARACTERISTICS: GW38477 suitable for fixing on the vertical cable management bars for the cabinets GW38461, GW38462, GW38463 and GW38464. GW38479 wrinkle texture, equipped with a pair of fans complete of 3m cable with german std plug and a thermostat.
NOTES: for mounting the air circulation unit GW38479 on 19" floor rack cabinets use the metal small parts kit GW38557.



GW 38 479

Accessories for 19” rack cabinets

19” empty patch panel

Code	Characteristics	Colour	Cabling unity	Pack Carton
GW 38 603	Suitable for 24 UTP/FTP RJ45 sockets	Black RAL 9005	1U	1/10

CHARACTERISTICS: made from painted sheet steel, wrinkle texture.
NOTES: to be completed with UTP and FTP RJ45 socket-outlets with Keystone Jack coupling (eg: GW38031, GW38032, GW38033, GW38034, GW38035, GW38036). For mounting on 19" rack cabinets use the metal small parts kit GW38557.



GW 38 603

19” empty fiber optic patch panel drawer

Code	Characteristics	Colour	Depth	Cabling unity	Pack Carton
GW 38 612	Suitable for 24 SC/LC couplers	Black RAL 9005	250 mm	1U	1
GW 38 613	Suitable for 24 ST couplers	Black RAL 9005	250 mm	1U	1

CHARACTERISTICS: made from painted sheet steel, wrinkle texture. Optic drawers with easy clip opening.
NOTES: suitable for SC simplex (GW38326), LC duplex or ST simplex couplers. For mounting on 19" rack cabinets use the metal small parts kit GW38557.



GW 38 612

Data Center

19” rack shelves



GW 38 609

Code	Description	Load capacity (Kg)	Colour	Depth	Cabling unity	Pack Carton
GW 38 607	19” fixed shelf	20	Black RAL 9005	260 mm	2U	1/6
GW 38 608	19” fixed shelf	20	Black RAL 9005	360 mm	2U	1/6
GW 38 609	19” sliding shelf	15	Black RAL 9005	410 mm	2U	1/6

CHARACTERISTICS: made from painted sheet steel, wrinkle texture. The load capacity values (Kg) are referred to a uniformly distributed load. GW38609 not suitable for 19" wall mount cabinets with depth of 400mm.
NOTES: for mounting on 19" rack cabinets use the metal small parts kit GW38557.

19” blind panels



GW 38 601

Code	Colour	Cabling unity	Pack Carton
GW 38 601	Black RAL 9005	1U	1/20
GW 38 602	Black RAL 9005	2U	1/10

CHARACTERISTICS: made from painted sheet steel, wrinkle texture.
NOTES: for mounting on 19" rack cabinets use the metal small parts kit GW38557.

19” cable management panels



GW 38 611

Code	Characteristics	Colour	Cabling unity	Pack Carton
GW 38 610	With brushes	Black RAL 9005	1U	1/20
GW 38 611	With 4 rings	Black RAL 9005	1U	1/15

CHARACTERISTICS: made from painted sheet steel, wrinkle texture.
NOTES: for mounting on 19" rack cabinets use the metal small parts kit GW38557.

19” power strip



GW 38 606

Code	Characteristics	Colour	Cabling unity	Pack Carton
GW 38 606	6 sockets 2P+E - 16 A dual amp. ita/ger std	Black	1U	1/10

CHARACTERISTICS: body in plastic material, with dual pole luminous switch, 3m long cable, 90° 2P+E - 16A fre/ger std plug, power max 3500W.
NOTES: for mounting on 19" rack cabinets use the metal small parts kit GW38557.

Accessories for rack cabinets



GW 38 557

Code	Description	Dimensions LxH (mm)	Pack Carton
GW 38 557	Small parts kit	-	1/30
GW 38 473	Alignment adhesive strip	-	1/30
GW 46 447	Self-adhesive document holder	230x310	1/10

ACCESSORIES SUPPLIED: GW38557 kit of cage nuts and 50 M6 screws.



Data Center



Scan the QR Code and find out all the technical informations.

A CABINET FOR ANY REQUIREMENT



The cabinets are available in a wide choice of modules and in a variety of depths (up to 1000mm) to adapt to any application. A wide range of accessories is available for copper and fiber optic cabling.

HIGH PERFORMANCE



All the components of the range are made with high quality materials and with particular attention to every detail and finish. The result offers sturdy switchboards and cabinets, with static full load capacity that can reach 1000kg.

BUDGETING SOFTWARE



GEWISS offers programmes for the estimation of enclosures and cabinets, which can be used from any web-page display device or installed on a PC.

Plugs

Italian standard



GW 28 003 - 10A
White
GW 28 004 - 10A
Slate
GW 28 005 - 16A
White
GW 28 006 - 16A
Slate

Straight plugs
2P+E - 250 Vac



GW 28 007 - 10A
White
GW 28 008 - 10A
Slate
GW 28 009 - 16A
White
GW 28 010 - 16A
Slate

90° plugs
2P+E - 250 Vac

German/french standard



GW 28 011 - 16A
White
GW 28 013 - 16A
Black

Straight plugs
2P+E - 250 Vac



GW 28 012 - 16A
White

90° plugs
2P+E - 250 Vac

Portable socket-outlets

Italian standard



GW 28 203 - 10A
White
GW 28 204 - 10A
Slate
GW 28 205 - 16A biv.
White
GW 28 206 - 16A biv.
Slate

Plugs
2P+E - 250 Vac

Single adaptors

Italian/german standard



GW 28 415
2P+E adaptor - 250 Vac
1x 16A ger. std plug
1x 16A dual amp. socket



GW 28 509
1x 10A plug
GW 28 510
1x 16A plug

2P+E - 250 Vac adaptor
1x 16A ita/ger std socket


Multiple adaptors

Italian standard



GW 28 421
1x 10A plug - 3x 10A sockets
GW 28 423
1x 16A plug - 3x 16A dual amp. sockets

3 outputs adaptors
2P+E - 250 Vac



GW 28 418
1x 10A plug - 3x 10A sockets
GW 28 419
1x 16A plug - 3x 16A dual amp. sockets

3 outputs flat adaptors
2P+E - 250 Vac

Italian/german standard



GW 28 416
1x 10A plug - 2x 10A sockets -
1x 16A ita/ger std socket
GW 28 417
1x 16A plug - 2x 16A dual amp. sockets -
1x 16A dual amp. ita/ger std socket

3 outputs adaptors
2P+E - 250 Vac

28 Spic

Plugs, sockets and adapters for domestic and similar uses

Range of plugs, socket-outlets, multiple adaptors and trailing socket-outlets for the most common power take-off needs in the domestic environment.





PLUGS AND PORTABLE SOCKET-OUTLETS

Plugs

Straight plugs - Italian standard - 250V ac



GW 28 005

Code	No. of poles	Rated current (A)	Type	Colour	Pack Carton
GW 28 003	2P+E	10	S11	White	25/250
GW 28 004	2P+E	10	S11	Slate	25/250
GW 28 005	2P+E	16	S17	White	25/150
GW 28 006	2P+E	16	S17	Slate	25/150

90° plugs - Italian Standard - 250V ac



GW 28 007

Code	No. of poles	Rated current (A)	Type	Colour	Pack Carton
GW 28 007	2P+E	10	SPA11	White	25/150
GW 28 008	2P+E	10	SPA11	Slate	25/150
GW 28 009	2P+E	16	SPA17	White	25/250
GW 28 010	2P+E	16	SPA17	Slate	25/250

GW28009 - GW28010: check extractability for side socket-outlets.

Straight plugs - German/French standard - 250V ac



GW 28 011

Code	No. of poles	Rated current (A)	Colour	Characteristics	Pack Carton
GW 28 011	2P+E	16	White	Halogen free	25/175
GW 28 013	2P+E	16	Black	Halogen free	25/175

Plug with double earthing contact (side for German standard, middle for French standard).

90° angle plug - German/French standard - 250V ac



GW 28 012

Code	No. of poles	Rated current (A)	Colour	Characteristics	Pack Carton
GW 28 012	2P+E	16	White	Halogen free	25/175

Plug with double earthing contact (side for German standard, middle for French standard).

28 Spic

Portable socket-outlets



GW 28 205

Italian Standard portable socket-outlets - 250V ac

Code	No. of poles	Rated current (A)	Type	Colour	Pack Carton
GW 28 203	2P+E	10	P11	White	25/250
GW 28 204	2P+E	10	P11	Slate	25/250
GW 28 205	2P+E	16	Dual amperage P17-11	White	25/150
GW 28 206	2P+E	16	Dual amperage P17-11	Slate	25/150

CHARACTERISTICS: with safety shields.

ADAPTORS AND MULTIPLE TRAILING SOCKET-OUTLETS

Adaptors



GW 28 423

Italian Standard multiple adaptors with 3 outputs - 250V ac - 1500W

Code	Type of plug	Socket-outlet type	Colour	Pack Carton
GW 28 421	2P+E 10A (S11)	10A (P11)	White	50/200
GW 28 423	2P+E 16A (S17)	16A dual amper (P17/11)	White	50/200

CHARACTERISTICS: with safety shields.



GW 28 419

Italian standard flat multiple adapters with 3 outputs - 250V ac - 1500W

Code	Type of plug	Socket-outlet type	Colour	Pack Carton
GW 28 418	2P+E 10A (S11)	10A (P11)	White	40/160
GW 28 419	2P+E 16A (S17)	16A dual amper (P17/11)	White	40/160

CHARACTERISTICS: with safety shields.



GW 28 417

Multiple adapters with 2 outputs (Italian standard) and 1 output (Italian/German standard) 250V ac - 1500W

Code	Type of plug	Socket-outlet type	Socket-outlet type	Colour	Pack Carton
GW 28 416	2P+E 10A (S11)	16 A (P30)	10 A (P11)	White	50/200
GW 28 417	2P+E 16A (S17)	16 A (P40)	16A dual amper (P17/11)	White	50/200

28 Spic



GW 28 510

Italian/German Standard single adaptors with 1 output - 250V ac - 1500W

Code	Type of plug	Socket-outlet type	Colour	Pack Carton
GW 28 510	2P+E 16A (S17)	16A (P30)	Satin White	50/200
GW 28 509	2P+E 10A (S11)	16A (P30)	Satin White	50/200

CHARACTERISTICS: socket-outlet with side and central earthing.



GW 28 415

Italian Standard single adaptor with 1 output - 250V ac - 150W

Code	Type of plug	Socket-outlet type	Colour	Pack Carton
GW 28 415	2P+E 16A German stand.	16A dual amper (P17/11)	White	15/150

CHARACTERISTICS: with safety shields.

NEWS



28 Spic



Scan the QR Code and find out all the technical informations.

ERGONOMIC



Anti-slip ribs allow the best ergonomics during use.

WALKABLE



Designed to withstand shock in accordance with standard 23-50.

Flush-mounting enclosures





Domo Center

Flush-mounting system columns for distribution, Home & Building automation and data

p. 1202

Green Wall

Flush-mounting system for plasterboard walls

p. 260







40 CDi

Flush-mounting distribution boards and enclosures

p. 280

48

Flush-mounting junction and modular boxes system

p. 301

24 SC

Flush-mounting, surface and underfloor boxes

p. 316

Domo Center

Range

The versatility of DOMO CENTER makes it possible to perform various functions, such as: energy distribution, networking devices housing, Home and building automation monitoring and control devices Touchscreen 7", and use as an upright column for the distribution of common services to the various floors of the building.
The Domo Center range is divided into 2 parts:



Front configuration kit

These are configurations with predefined heights and types (with and without door) that contain all the components necessary for implementing the system column, with the exception of the back-mounting box that must be purchased separately. Available in the catalogue in several configurations, these kits facilitate the product selection, transport and assembly.


Components

It is possible, however, to create personalised configurations as required by making up the system column using the Domo Center components.componendo la colonna d'impianto attraverso i Componenti Domo Center.

Installation

DOMO CENTER, comes in two standard dimensions, It is designed for installation in rooms with floor-ceiling heights (with the work completed) of 2700 mm or 2400 mm.


ROOMS WITH HEIGHT H 2700 mm



Pre-arrangement for GW N1 003 back-mounting box
(for brick or plasterboard wall)

Effect when installation is complete

ROOMS WITH HEIGHT H 2400 mm




Pre-arrangement for GW N1002 back-mounting box
(for brick or plasterboard walls)

Effect when installation is complete

Note: the buffer panels H 150 mm inserted in the upper and lower edge of the flush-mounting back-mounting box are designed to be finished like the wall (both brick and plasterboard).

AN EXAMPLE OF USE AS AN UPRIGHT COLUMN FOR THE DISTRIBUTION OF COMMON SERVICES TO THE VARIOUS FLOORS OF THE BUILDING.


e.g. KIT code GWN1261XB



Structure

The DOMO CENTER can be configured in multiple solutions, with or without a door. Once the back-mounting box (height 2700 or 2400 mm) has been selected, the following aspects must be defined on the basis of its modularity: the internal configuration, the underdoor panels (if necessary) the front configuration until the modularity of the back-mounting box itself is reached. Examples that represent the two types are given below. For each assembly level, there is a description of the components that can be installed and their relative modular dimensions (1U corresponds to overall modular dimensions of h 300 mm).


Version without door



Composition representing code GWN1601XB and flush-mounting back-mounting box GWN1002

1. FLUSH-MOUNTING BACK-MOUNTING BOX
   Back-mounting box for masonry or plasterboard, in heights of 2700 mm (8U) and 2400 mm (7U)
2. INTERNAL CONFIGURATION ELEMENTS
   Functional frames with DIN rail (1U/2U), functional frames with back-mounting plate (1U/2U), home networking kit (2U)
3. FINISH FRAME
   For heights 2400 mm (for a back-mounting box height of 2700 mm) and 2100 mm (for back-mounting box height of 2400 mm)
4. FRONT CONFIGURATION ELEMENTS
   40-module enclosure (1U), panels without windows (1U/2U/3U), panels with windows (1U/2U)

Version with door



Composition representing code GWN1401XB and flush-mounting back-mounting box GWN1003

1. FLUSH-MOUNTING BACK-MOUNTING BOX
   Back-mounting box for masonry or plasterboard, in heights of 2700 mm (8U) and 2400 mm (7U)
2. INTERNAL CONFIGURATION ELEMENTS
   Functional frames with DIN rail (1U/2U), functional frames with back-mounting plate (1U/2U), Home networking kit (2U)
3. FINISH FRAME
   For heights 2400 mm (for a back-mounting box height of 2700 mm) and 2100 mm (for back-mounting box height of 2400 mm)
4. UNDERDOOR ELEMENTS
   Underdoor panels with windows 2 DIN rail rows (1U), underdoor panels without windows (1U)
5. FRONT CONFIGURATION ELEMENTS
   Doors* (5U/6U) and panels without windows (1U/2U/3U)

* For a mirror finish, the door in 7U and 8U modularities includes panels without windows.

HOW TO REQUEST THE MOST SUITABLE CONFIGURATION (KIT)
Contact customer service (sat@gewiss.com) or the sales organisation for configuration and estimate support.
To facilitate these requests, the DOMO CENTER Gweb software is freely available on gewiss.com.

Kit preconfigured

DOMO CENTER FRONT CONFIGURATION KIT

KIT TYPE	VERSION	FOR FLUSH-MOUNTING BACK-MOUNTING BOX (not included in the KIT)		KIT CODE	FINISH (metal)	CAPACITY (unit/ modularity/ functional height)	Functional frame with back-mounting plate			
							Function frame with DIN rails		Functional frame with back-mounting plate	
										
							Dimensions (unit/modularity/height)			
							1 U 40 M (20x2) H 300 mm	2 U 80 M (20x4) H 600 mm	1 U H 300 mm	2 U H 600 mm
KIT versions without door	Enclosure	GWN1003 (H 2700 mm)		GWN1201XB	Finish panels and enclosure front white RAL 9003	8 U 320 M 2400 mm		N°4		
		GWN1002 (H 2400 mm)		GWN1601XB		7 U 280 M 2100 mm	N°1	N°3		
	Upright column	GWN1003 (H 2700 mm)		GWN1261XB	Finish panels white RAL 9003	8 U 40 M 2400 mm	N°1		N°1	N°3
		GWN1002 (H 2400 mm)		GWN1661XB		7 U 40 M 2100 mm	N°1			N°3
KIT versions with door	Enclosure with smoked transparent finish door	GWN1003 (H 2700 mm)		GWN1401XB	Finish panels white RAL 9003 and smoked transparent glass door	8 U 320 M 2400 mm		N°4		
		GWN1002 (H 2400 mm)		GWN1801XB		7 U 280 M 2100 mm	N°1	N°3		
	Enclosure with door and mirror finish panels	GWN1003 (H 2700 mm)		GWN1431CP	Door and panels with integral mirror finish on the entire surface	8 U 320 M 2400 mm		N°4		
		GWN1002 (H 2400 mm)		GWN1831CP		7 U 280 M 2100 mm	N°1	N°3		
	Enclosure with metal finish door	GWN1003 (H 2700 mm)		GWN1461XB	Door and panels with white RAL 9003 finish	8 U 320 M 2400 mm		N°4		
		GWN1002 (H 2400 mm)		GWN1861XB		7 U 280 M 2100 mm	N°1	N°3		

KIT complementary items

						
Flush-mounting back-mounting boxes* GWN1002 (for H 2400 mm) GWN1003 (for H 2700 mm)	Kit for coupling back-mounting boxes GWN1131	Safety lock GWN1132	Channel crossing the floor slab GWN1133	Separator plate GWN1141 (horizontal) GWN1142 (vertical)	Fixing brackets for Internet Gateway GWN1134	Safety lock kit for white blind metal panels with finishing design GWN1135

* Before installing the front configuration KIT, install the metal flush-mounting back-mounting box.
NOTE: (U) refers to the modular dimensions (e.g. 1U corresponds to overall modular dimensions equal to h 300 mm)

ACCESSORIES SUPPLIED IN THE KIT

FINISH FRAME	Front CONFIGURATION (external finish elements)											
	Enclosure with smoked transparent door	Enclosure function panel with windows (underdoor)	Panel without windows (underdoor)	Door in smoked transparent glass		Door and 2 panels H=300 mm with mirror finish on the entire surface		Finish door		Finish panels without windows		
	Metal white RAL 9003							Metal White RAL 9003				
												
	Dimensions (unit/modularity/height)											
	1 U 40 M (20x2) H 300 mm	**1 U 40 M (20x2) H 300 mm**	**1 U H 300 mm**	**5 U H 1500 mm**	**6 U H 1800 mm**	**7 U H 2100 mm**	**8 U H 2400 mm**	**5 U H 1500 mm**	**6 U H 1800 mm**	**1 U H 300 mm**	**2 U H 600 mm**	**3 U H 900 mm**
N°1	N°2											N°2
	N°1											N°2
											N°1	N°2
										N°1		N°2
		N°2	N°4		N°1					N°2		
		N°1	N°4	N°1						N°2		
		N°2	N°4				N°1					
		N°1	N°4			N°1						
		N°2	N°4						N°1	N°2		
		N°1	N°4					N°1		N°2		

Domo Center

Versions without door
(with enclosure and finish panels)



					INTERNAL CONFIGURATION					FINISH FRAME
					Function frame with DIN rails		Functional frame with back-mounting plate		Home networking kit	
										
					Dimensions (unit/modularity/height)					
					1 U 40 M (20x2) H 300 mm	**2 U 80 M (20x4) H 600 mm**	**1 U H 300 mm**	**2 U H 600 mm**	**2 U H 600 mm**	Element required for fixing front configuration elements
FLUSH-MOUNTING BACK-MOUNTING BOXES		**GWN1002** (dim. back-mounting box LxHxD 590x2400x85 mm) (functional dimensions LxHxD 590x2100x85 mm)	CAPACITY (unit/modularity/functional height)	7 U 280 M (20x14) H 2100 mm	GWN1012	GWN1014	GWN1022	GWN1024	GWN1031F (Note: Closing through blind finish panels) Optional: complete windowed panel under door GWN1122XB for home networking kit	GWN1042XB
		GWN1003 (dim. back-mounting box LxHxD 590x2700x85 mm) (functional dimensions LxHxD 590x2400x85 mm)		8 U 320 M (20x16) H 2400 mm						GWN1043XB

Versions with door
(with underdoor panels, door and finish panels)



					INTERNAL CONFIGURATION					FINISH FRAME
					Function frame with DIN rails		Functional frame with back-mounting plate		Home networking kit	
										
					Dimensions (unit/modularity/height)					
					1 U 40 M (20x2) H 300 mm	**2 U 80 M (20x4) H 600 mm**	**1 U H 300 mm**	**2 U H 600 mm**	**2 U H 600 mm**	Element required for fixing front configuration elements
FLUSH-MOUNTING BACK-MOUNTING BOXES		**GWN1002** (dim. back-mounting box LxHxD 590x2400x85 mm) (functional dimensions LxHxD 590x2100x85 mm)	CAPACITY (unit/modularity/functional height)	7 U 280 M (20x14) H 2100 mm	GWN1012	GWN1014	GWN1022	GWN1024	GWN1031F (Note: for an hight aesthetic performance and device protection use the underdoor windowed panel code GWN1122XB for networking kit) (Note: closure with underdoor finish panels without windows)	GWN1042XB
		GWN1003 (dim. back-mounting box LxHxD 590x2700x85 mm) (functional dimensions LxHxD 590x2400x85 mm)		8 U 320 M (20x16) H 2400 mm						GWN1043XB

NOTE: (U) refers to the modular dimensions (e.g. 1U corresponds to overall modular dimensions equal to h 300 mm)

Front CONFIGURATION (external finish elements)

Enclosure with smoked transparent door	Finish panels without windows			Finish panels with windows for specific devices
Metal White RAL 9003				
				
Dimensions (unit/modularity/height)				
1 U 40 M (20x2) H 300 mm	**1 U H 300 mm**	**2 U H 600 mm**	**3 U H 900 mm**	**1 U H 300 mm**
GWN1051XB	GWN1062XB	GWN1064XB	GWN1066XB	GWN1071XB (for Touchscreen 7" -> article to be ordered separately) 

COMPLEMENTARY ITEMS

Safety lock kit for white blind metal panels with finishing design GWN1135 

 Kit for coupling back-mounting boxes GWN1131

 Safety lock GWN1132

 Channel crossing the floor slab GWN1133

 Separator plate GWN1141 (horizontal) GWN1142 (vertical)

 Fixing brackets for Internet Gateway GWN1134

Front CONFIGURATION (external finish elements)

Enclosure function panel with windows (underdoor)	Panel without windows (underdoor)	Finish doors (glass, metal and mirror finishes*) (*) For mirrored doors: 2 mirror panels H=300 mm supplied.			Finish panels without windows
Metal White RAL 9003					Metal White RAL 9003
					
Dimensions (unit/modularity/height)					

1 U 40 M (20x2) H 300 mm	**1 U H 300 mm**	**5 U H 1500 mm**	**6 U H 1800 mm**	**5 U H 1500 mm**	**6 U H 1800 mm**	**7 U H 2100 mm**	**8 U H 2400 mm**	**1 U H 300 mm**	**2 U H 600 mm**	**3 U H 900 mm**
GWN1121XB	GWN1124XB	GWN1101CF (glass)	GWN1111CF (glass)	GWN1101XB (metal)	GWN1111XB (metal)	GWN1101CP (mirror)	/	GWN1062XB	GWN1064XB	GWN1066XB
						/	GWN1111CP (mirror)			

COMPLEMENTARY ITEMS

Safety lock kit for white blind metal panels with finishing design GWN1135 

 Kit for coupling back-mounting boxes GWN1131

 Safety lock GWN1132

 Channel crossing the floor slab GWN1133

 Separator plate GWN1141 (horizontal) GWN1142 (vertical)

 Fixing brackets for Internet Gateway GWN1134

Domo Center



Flush-mounting system columns for distribution, Home and Building automation and data

DOMO CENTER transforms the domestic systems into furnishing accessories: a modern design solution that blends with the existing context, centralising and rationalising the existing services - from the most traditional to the most advanced, in a single point with a modularity of up to 320 modules. Also available with characteristic full-mirror version.

DOMO CENTER FRONT CONFIGURATION KIT







2700 kit versions - without door



GW N1 201 XB

System column front kit with finish panels in white metal RAL 9003 and 2 enclosure - 40 modules

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 201 XB	590x2700x85	642x2400x25	320 (20x16)	1

*: 320M maximum available modular space.

ACCESSORIES SUPPLIED:

4 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 metal frame, code GWN1043XB.

2 finish panels without windows, code GWN1066XB.

2 enclosures - 40 DIN rail modules (20x2) with door in smoked transparent glass, code GWN1051XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2700 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1003.

GW N1 261 XB

System column front kit with finish panels in white metal RAL 9003 for use as an upright column

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 261 XB	590x2700x85	642x2400x25	40 (20x2)	1

*: 40M maximum modular space available (e.g. for terminal block for junction, cross-pieces etc.).

SUPPLIED:

1 functional frame for 40 DIN rail modules (20x2), code GWN1012.

3 functional frames supplied with back-mounting plate, code GWN1024.

1 functional frame supplied with back-mounting plate, code GWN1022.

1 metal frame, code GWN1043XB.

2 finish panels without windows, code GWN1066XB.

1 finish panel without windows, code GWN1064XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2700 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1003.

2700 kit versions - with door



GW N1 401 XB

System column front kit with door in smoked transparent glass, finish panels in white metal RAL 9003, 2 underdoor enclosures 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 401 XB	590x2700x85	642x2400x25	320 (20x16)	1

*: 320M maximum available modular space.

ACCESSORIES SUPPLIED:

4 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 metal frame, code GWN1043XB.

2 finish panels without windows, code GWN1062XB.

2 underdoor enclosures for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 door in transparent smoked glass, code GWN1111CF.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2700 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1003.



GW N1 431 CP

System column front kit with mirror finish panels and door, 2 underdoor enclosures 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 431 CP	590x2700x85	642x2400x25	320 (20x16)	1

*: 320M maximum available modular space.

CHARACTERISTICS: door and panels in metal with integral mirror finish on the entire surface.

ACCESSORIES SUPPLIED:

4 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 metal frame, code GWN1043XB.

2 underdoor enclosures for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 door and 2 mirror panels, code GWN1111CP.

NOTES:

installation is recommended in areas with a floor-ceiling height of h 2700 mm when the work is complete.

The door pack with mirror finish include also 2 mirror panels with h = 300 mm.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1003.



GW N1 461 XB

System column front kit with door and finish panels in white metal RAL 9003, 2 underdoor enclosures 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 461 XB	590x2700x85	642x2400x25	320 (20x16)	1

*: 320M maximum available modular space.

ACCESSORIES SUPPLIED:

4 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 metal frame, code GWN1043XB.

2 finish panels without windows, code GWN1062XB.

2 underdoor enclosures for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 metal door, code GWN1111XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2700 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1003.

2400 kit versions - without door



GW N1 601 XB

System column front kit with finish panels in metal colour RAL 9003 and 1 enclosure - 40 modules

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 601 XB	590x2400x85	642x2100x25	280 (20x14)	1

*: 280M maximum available modular space.

ACCESSORIES SUPPLIED:

3 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 functional frame supplied with DIN rails, code GWN1012.

1 metal frame, code GWN1042XB.

2 finish panels without windows, code GWN1066XB.

1 enclosure for 40 DIN rail modules (20x2) with door in smoked transparent glass, code GWN1051XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2400 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1002.

GW N1 661 XB

System column front kit with finish panels in white metal RAL 9003 for use as an upright column

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 661 XB	590x2400x85	642x2100x25	40 (20x2)	1

*: 40M maximum modular space available (e.g. for terminal block for junction, cross-pieces etc.).

ACCESSORIES SUPPLIED:

1 functional frame for 40 DIN rail modules (20x2), code GWN1012.

3 functional frames supplied with back-mounting plate, code GWN1024.

1 metal frame, code GWN1042XB.

2 finish panels without windows, code GWN1066XB.

1 finish panel without windows, code GWN1062XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2400 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1002.

2400 kit versions - with door



GW N1 801 XB

System column front kit with door in smoked transparent glass, finish panels in white metal RAL 9003, 1 underdoor enclosure 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 801 XB	590x2400x85	642x2100x25	280 (20x14)	1

*: 280M maximum available modular space.

ACCESSORIES SUPPLIED:

3 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 functional frame supplied with DIN rails, code GWN1012.

1 metal frame, code GWN1042XB.

2 finish panels without windows, code GWN1062XB.

1 underdoor enclosure for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 door in transparent smoked glass, code GWN1101CF.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2400 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1002.



GW N1 831 CP

System column front kit with mirror finish panels and door, 1 underdoor enclosure 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 831 CP	590x2400x85	642x2100x25	280 (20x14)	1

*: 280M maximum available modular space.

CHARACTERISTICS: door and panels in metal with integral mirror finish on the entire surface.

ACCESSORIES SUPPLIED:

3 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 functional frame supplied with DIN rails, code GWN1012.

1 metal frame, code GWN1042XB.

1 underdoor enclosure for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 door and 2 mirror panels, code GWN1101CP.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2400 mm when the work is complete.

The door pack with mirror finish include also 2 mirror panels with h = 300 mm.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1002.



GW N1 861 XB

System column front kit with door and finish panels in white metal RAL 9003, 1 underdoor enclosure 40 M and underdoor panels white RAL 9003

Code	For back-mounting box dim. LxHxD (mm)	Outer dim. LxHxD (mm)	No. of modules EN 50022 *	Pack Carton
GW N1 861 XB	590x2400x85	642x2100x25	280 (20x14)	1

*: 280M maximum available modular space.

ACCESSORIES SUPPLIED:

3 functional frames for 80 DIN rail modules (20x4), code GWN1014.

1 functional frame supplied with DIN rails, code GWN1012.

1 metal frame, code GWN1042XB.

2 finish panels without windows, code GWN1062XB.

1 underdoor enclosure for 40 DIN rail modules (20x2), code GWN1121XB.

4 underdoor panels, code GWN1124XB.

1 metal door, code GWN1101XB.

NOTES: installation is recommended in areas with a floor-ceiling height of h 2400 mm when the work is complete.

Maximum rated current In = 125 A.

Flush-mounting back-mounting box to be ordered separately. Reference code GWN1002.

Back-mounting boxes



GW N1 002

Metal flush-mounting back-mounting box for masonry and plasterboard walls

Code	For kit	Functional dim. LxHxD (mm)	Back plate dim. LxHxD (mm)	No. of modules EN 50022	Maximum dispersible power (W)	Pack Carton
GW N1 002	Versions 2400	590x2100x85	590x2400x85	280 (20x14)	800	1
GW N1 003	Versions 2700	590x2400x85	590x2700x85	320 (20x16)	700	1

ACCESSORIES SUPPLIED: adjustable feet, masonry template, casing union band and 2 upper and lower cover panels with h=150 mm.
CHARACTERISTICS: flush-mounting back-mounting box can be obtained with two coupled casings. Rectangular knockouts on the vertical sides and lower and upper heads open for pipe entrance. Adjustable feet from 0 to 205 mm both on the lower side as well as on the upper side for installation adjustment.
APPLICATIONS: flush-mounting back-mounting box, code GWN1002, for applications in areas with a floor-ceiling height of h 2400 mm when the work is complete. flush-mounting back-mounting box, code GWN1003, for applications in areas with a floor-ceiling height of h 2700 mm when the work is complete.

Internal configuration



GW N1 014

Functional metal frames equipped with DIN rails for modular devices

Code	Height (mm)	No. of modules EN 50022	Pack Carton
GW N1 012	300	40 (20x2)	1
GW N1 014	600	80 (20x4)	1

ACCESSORIES SUPPLIED: vertical wiring trunking 80x60 mm. Screw kit for fixing the frame on the back-mounting box.
CHARACTERISTICS: pre-arrangement for horizontal trunking 30x60 and use of horizontal dividers, code GWN1141.



GW N1 024

Functional frames with metal back-mounting plate for fixing non-modular devices

Code	Height (mm)	Max load (kg)	Pack Carton
GW N1 022	300	10	1
GW N1 024	600	20	1

ACCESSORIES SUPPLIED: vertical wiring trunking 80x60 mm. Screw kit for fixing the frame on the back-mounting box.
CHARACTERISTICS: pre-arrangement for horizontal trunking 30x60 and use of horizontal dividers, code GWN1141.



GW N1 031 F

Multimedia board for Domo Center

Code	Height (mm)	Pack Carton
GW N1 031 F	600	1

APPLICATIONS: multimedia Boards allow the distribution of the services from the DOMO CENTER through the apartment (e.g. internet, phone, satellite TV, etc.). This version is dedicated to big apartments and villas with a huge amount of services and devices that have to be connected.
CHARACTERISTICS: the product is compliant to the CEI 306-2 Guide.
ACCESSORIES SUPPLIED: 2 pcs vertical wiring trunking 80x60 mm, 1 kit fixing screws, 1 pc frame with 3 pcs perforated mounting plates (1 pc with 18 Keystone Jack slot), 3 m velcro roll h=16 mm, 6 pcs brackets, 6 pcs self-adhesive cable clips with cable ties, 6 pcs. RJ45 Cat.6 Keystone Jack, 6 pcs patch cord RJ45-RJ45 Cat.6 0,6 m, 1 pc thelephone splitter with 5 RJ11 socket and 5 pcs patch cord RJ11-RJ45, 1 pc multiple socket with 4 Italian/German socket 2P+E 16A.
INSTALLATION: the finishing panel GWN1122XB can be used for better aesthetics and protection.

Frames



GW N1 043 XB

Modular metal frames for fixing front configuration elements white RAL 9003

Code	Height (mm)	For back-mounting box	Pack Carton
GW N1 042 XB	2100	GWN1002	1
GW N1 043 XB	2400	GWN1003	1

ACCESSORIES SUPPLIED: fixing template.
CHARACTERISTICS: to fix the frame, it is necessary to first install the internal configuration elements: functional frames and kits for specific functions (network cabling).

Front configuration



GW N1 051 XB

40 module enclosure with door in smoked transparent glass Front in white metal RAL 9003

Code	Colour	No. of modules EN 50022	Pack Carton
GW N1 051 XB	RAL 9003 White	40 (20x2)	1

CHARACTERISTICS: reversible door in smoked glass; magnet closure; can be fitted with a safety lock GWN1132.
Door opening 170°.
ACCESSORIES SUPPLIED: panel for covering the modular devices, 2 module covering masks (6.5 DIN rail modules) white colour.
Panel closure by the tool for board accessibility.

GW N1 062 XB

Panels without windows with design finish in metal - white RAL 9003

Code	Description	Height (mm)	Pack Carton
GW N1 062 XB	Panel without windows 300	300	1
GW N1 064 XB	Panel without windows 600	600	1
GW N1 066 XB	Panel without windows 900	900	1

CHARACTERISTICS: magnet closure; hinged panels with reversible opening to 170°;
NOTES: Panel closure by the tool for board accessibility.

Door in smoked transparent glass



GW N1 101 CF

Code	Height (mm)	For functional dimensions (mm)	No. of locks that can be installed	Pack Carton
GW N1 101 CF	1500	2400	2	1
GW N1 111 CF	1800	2400	2	1

CHARACTERISTICS: tempered glass; hinged and reversible door with 170° opening and magnet closure; can be fitted with a safety lock code GWN1132.
NOTES: To foresee 2 blank panels for aesthetic finishing GWN1062XB.

Door and 2 panels with mirror finish



GW N1 101 CP

Code	Door height (mm)	Panel height (mm)	For functional dimensions (mm)	No. of locks that can be installed	Pack Carton
GW N1 101 CP	1500	300	2100	2	1
GW N1 111 CP	1800	300	2400	2	1

CHARACTERISTICS: hinged and reversible door with 170° opening and magnet closure; can be fitted with a safety lock code GWN1132. door and panels in metal with integral mirror finish on the entire surface.
ACCESSORIES SUPPLIED: 2 panels with mirror finish h = 300 mm.

Metal door - white RAL 9003

GW N1 101 XB

Code	Height (mm)	For functional dimensions (mm)	No. of locks that can be installed	Pack Carton
GW N1 101 XB	1500	2400	2	1
GW N1 111 XB	1800	2400	2	1

CHARACTERISTICS: hinged and reversible door with 170° opening and magnet closure; can be fitted with a safety lock code GWN1132.
NOTES: To foresee 2 blank panels for aesthetic finishing GWN1062XB.

Underdoor panel with windows in white metal RAL 9003



GW N1 121 XB

Code	Description	No. of modules EN 50022	Pack Carton
GW N1 121 XB	Panel with windows, 2 DIN rail rows	40 (20x2)	1

NOTES: panel for covering the modular devices.


Underdoor panel without windows in white metal RAL 9003

GW N1 124 XB

Code	Description	Height (mm)	Closure	Pack Carton
GW N1 124 XB	Removable blank panell	300	With screws	1

NOTES: Panel closure via the tool for board accessibility.

Windowed metal underdoor panel for kit multimedia full and burglar alarm - White RAL 9003




GW N1 122 XB

Code	Description	Height (mm)	Pack Carton
GW N1 122 XB	Removable under door windowed panel for complete QDSA kit GWN1031F	600	1

NOTE: panel closure by the tool for board accessibility. The panels can be used in both without door configuration (under the blank metal panles for aesthetic finishing) and with door configuration (as metal underdoor panels).

Complementary items

Kit for coupling metal back-mounting boxes



GW N1 131

Code	For back-mounting boxes h (mm)	Pack Carton
GW N1 131	2700	1

APPLICATIONS: for side-by-side installation and alignment of two back-mounting boxes.

Security lock



GW N1 132

Code	Material	Pack Carton
GW N1 132	Metal	1

APPLICATIONS: for closing doors height h 1500/1800 mm and for enclosure door code GWN1051XB. Lock block to be installed on the metal frame.
ACCESSORIES SUPPLIED: 2 keys.
NOTES: all the keys and relative locks with the same product code are identical.

Channel crossing the floor slab and back-mounting box coupling device



GW N1 133

Code	Material	Dimensions LxHxD (mm)	Pack Carton
GW N1 133	Plastic	500x550x75	1

NOTES: to be used to connect the flush-mounting back-mounting boxes between different floors.

Fixing bracket for coupling the Internet Gateway to the DIN rail

Code	Description	No. of modules EN 50022	Pack Carton
GW N1 134	Kit for Internet Gateway installation	11	1

NOTES: Internet Gateway code GW90816 to be purchased separately.



GW N1 134

Security lock kit

Code	Description	Pack Carton
GW N1 135	Safety lock kit for white blind metal panels with finishing design	1/10

CHARACTERISTICS: the kit is suppled with 2 safety closings for the frame with relative fixing screws.
APPLICATIONS: the kit has to be used with metal blank underdoor panels for aesthetic finishing GWN1062XB, GWN1064XB, GWN1066XB to allow the opening only to qualified personnel.



GW N1 135

Dividers

Code	Type	Fixing	Characteristics	Pack Carton
GW N1 141	Horizontal divider	On internal frames	-	1
GW N1 142	Vertical divider	On internal frames	3 overlapping modular elements	1

NOTES: the horizontal divider is used for creating internal separation between circuits of differing voltages on several rows within a single casing.
CHARACTERISTICS: vertical divider to be used for back-mounting boxes GWN1002 and GWN1003. Ideal for the segregation of circuits when using the Domo Center as an upright column. Pre-arrangement of up to 3 installable vertical dividers.



GW N1 141

Module cover profile in plastic

Code	Colour	No. of modules EN 50022	Characteristics	Pack Carton
GW 40 467 TB	White	6.5	Halogen free	50

CHARACTERISTICS: clip fixing on the windows of the front. Can be divided into 1/2 module elements, using scissors.



GW 40 467 TB

Domo Center multimedia board complementary items



GW 38 098

Telephone jack expansion kit

Code	Description	Pack Carton
GW 38 098	RJ11 telephone socket and telephone cable	1

ACCESSORIES SUPPLIED: 1 multiple telephone socket-outlet with 5 RJ11 socket-outlets.



Domo Center



Scan the QR Code and find out all the technical informations.

SOLUTIONS IN HARMONY WITH THE INTERIOR



DOMO CENTER transforms domestic systems into items of interior design: the wall-hanging effect, minimal footprints and finishes make it the ideal solution to bring a touch of personality and modernity to your surroundings. Available in versions with or without doors.

MAXIMUM DECORATIVE INTEGRATION



The version with door and mirror-finish panels ensures elegant aesthetic integration even in the most sophisticated settings, ensuring complete cover for all electrical-system equipment. A unique solution from GEWISS.

THE TECHNOLOGICAL CORE OF THE SYSTEM



With its unmatched modular capacity (320M in the largest version), DOMO CENTER is the technological core of an advanced electrical system. A conventional smart home system can be integrated inside it, together with anti-intrusion and Home Networking devices.

Mobility





JOINON
Electric vehicle charging

The complete offer of JOINON charging stations, compliant with the international standard IEC 61851, allows the connection and charging of all electric cars currently on the market, both in residential and public installations, such as rest areas, shopping centers, hotels and service stations. The stations are available in both AC and DC versions, with wall- or floor-mounting installation options. All product versions have connectivity and guarantee continuous updates via OTA technology. The offer also includes the possibility of dynamic load management (DLM), optimizing the power available in the system and improving the efficiency of the charging infrastructure.



Energy and services
distribution pedestals

The 68 Q-MC range is the innovative energy and services distribution system for environments such as tourist ports, campsites and public spaces (trade fairs, markets, gardens, etc.) that combines an attractive design with total reliability that is maintained over time thanks to its resistance to chemicals and atmospheric agents. The terminals are available both in AISI 316L stainless steel and in thermoplastic material, in blue, white or green colours. The range includes both pre-wired and empty versions, which can be configured as needed.

JOINON
Electric vehicle charging



I-CON EVO

AC charging wallboxes

p. 1218







I-ON EVO

AC charging stations

p. 1226

I-FAST

DC charging stations

p. 1233

COMPONENTS

Charging components

p. 1237

I-CON EVO

AC charging wallboxes

PRIVATE/SEMI-PUBLIC USE	**APPLICATION CONTEXT**		Individual homes		Condominiums		Companies	
	CASING TYPE		Thermoplastic 					
	DYNAMIC LOAD MANAGEMENT INCLUDING PHOTOVOLTAIC		Yes					
	USER RECOGNITION		FREE + APP				RFID + APP	
	ENERGY METER		Yes				Yes	
	CONNECTIVITY		WiFi		WiFi + LAN		WiFi + LAN	
	MASTER / SLAVE		No		Yes		Yes	
	CHARGING CONNECTOR TYPE		Type 2 Mobile with cable	Type 2 Vandal-proof with shutter	Type 2 Mobile with cable	Type 2 Vandal-proof with shutter	Type 2 Mobile with cable	Type 2 Vandal-proof with shutter
	MAXIMUM CHARGING POWER	**7.4 kW**	GW J3 412 C	GW J3 402 C	GW J3 512 G	GW J3 502 G	GW J3 612 T	GW J3 602 T
		11 kW	GW J3 413 C	-	GW J3 513 G	-	GW J3 613 T	GW J3 603 T
		22 kW	GW J3 414 C	GW J3 404 C	GW J3 514 G	GW J3 504 G	GW J3 614 T	GW J3 604 T

NOTES: optional internal 4G modem available for specific versions.

PRIVATE/SEMI-PUBLIC USE	**APPLICATION CONTEXT**		Hotel, Restaurants, Shopping centres	
	CASING TYPE		Thermoplastic 	
	DYNAMIC LOAD MANAGEMENT INCLUDING PHOTOVOLTAIC		Yes	
	USER RECOGNITION		RFID + APP	
	ENERGY METER		Yes, MID type	
	CONNECTIVITY		WiFi + LAN	
	MASTER / SLAVE		Yes	
	CHARGING CONNECTOR TYPE		Type 2 Mobile with cable	Type 2 Vandal-proof with shutter
	MAXIMUM CHARGING POWER	**7.4 kW**	GW J3 712 T	GW J3 702 T
		11 kW	-	-
		22 kW	GW J3 714 T	GW J3 704 T

NOTES: optional 4G internal modem.

AC charging wallboxes - UK - PEN compliant

PRIVATE/SEMI-PUBLIC USE

		Individual homes	Condominiums	Companies	Hotels, Restaurants, Shopping centres
APPLICATION CONTEXT					
CASING TYPE		Thermoplastic 			Thermoplastic 
DYNAMIC LOAD MANAGEMENT INCLUDING PHOTOVOLTAIC		Yes			Yes
USER RECOGNITION		FREE + APP		RFID + APP	RFID + APP
ENERGY METER		Yes			Yes, MID type
CONNECTIVITY		WiFi	WiFi + LAN		WiFi + LAN
MASTER / SLAVE		No	Yes		Yes
CHARGING CONNECTOR TYPE		Type 2 Vandal-proof with shutter			Type 2 Vandal-proof with shutter
MAXIMUM CHARGING POWER	**7.4 kW**	GW J3 402 CK	GW J3 502 GK	GW J3 602 TK	-
	11 kW	-	-	-	-
	22 kW	GW J3 404 CK	GW J3 504 GK	GW J3 604 TK	GW J3 704 TK

NOTES: optional internal 4G modem available for specific versions.

AC charging wallboxes - FR - TIC compliant

PRIVATE/SEMI-PUBLIC USE

		Individual homes	Condominiums	Companies, Hotels, Restaurants, Shopping centres
APPLICATION CONTEXT				
CASING TYPE		Thermoplastic 		Thermoplastic 
DYNAMIC LOAD MANAGEMENT INCLUDING PHOTOVOLTAIC		Yes		Yes
USER RECOGNITION		FREE + APP		RFID + APP
ENERGY METER		Yes		Yes, MID type
CONNECTIVITY		WiFi	WiFi + LAN	WiFi + LAN
MASTER / SLAVE		No	Yes	Yes
CHARGING CONNECTOR TYPE		Type 2 Vandal-proof with shutter		Type 2 Vandal-proof with shutter
MAXIMUM CHARGING POWER	**7.4 kW**	GW J3 402 CF	GW J3 502 GF	GW J3 702 TF
	11 kW	-	-	-
	22 kW	GW J3 404 CF	GW J3 504 GF	GW J3 704 TF

NOTES: optional internal 4G modem available for specific versions.

I-CON EVO

AC charging wallboxes



The I-CON EVO wallboxes by JOINON, compliant with IEC 61851-1 ed. 3, are ideal for private and semi-public environments. Featuring a compact design, 'one-hand recharge' function, vandal-proof socket, combined with IP55 and IK11 protection, they ensure safety and reliability. Equipped with full connectivity for the myJOINON App, smart load management, and integration with photovoltaic panels, they can be installed on walls, flushed, or on the floor. For condominium or business contexts, the SMALL NET management platform is also available, enabling centralized monitoring and management of an entire charging infrastructure composed of multiple stations.

I-CON EVO CHARGING SYSTEMS FOR ELECTRIC VEHICLES - AC (MODE 3)

IP 55 IK 11 WiFi OCPP DLM SOLAR

For residential scenarios



GW J3 412 C

I-CON EVO Wallbox - free access or via APP

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 402 C	1	7,4 kW	DC Leakage	Wifi	No	Yes	1
GW J3 404 C	1	22 kW	DC Leakage	Wifi	No	Yes	1
Type of Socket: Mobile with cable							
GW J3 412 C	1	7,4 kW	DC Leakage	Wifi	No	Yes	1
GW J3 413 C	1	11 kW	DC Leakage	Wifi	No	Yes	1
GW J3 414 C	1	22 kW	DC Leakage	Wifi	No	Yes	1

FEATURES: charging solutions designed to ensure easy access to charging either with free access or with authorization via the myJOINON app. The charging power can be configured through the myJOINON app, which also allows users to monitor consumption, keep the wallbox constantly updated, receive notifications related to the system and the charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Customizable front panel available upon request.
EQUIPMENT: LED indicators for user status signaling. Mobile connector versions equipped with a smooth 5-meter cable and integrated sheath.



GW J3 402 CK

I-CON EVO Wallbox - free access or via APP with integrated PEN

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 402 CK	1	7,4 kW	DC Leakage + SPD + PEN	Wifi	No	Yes	1
GW J3 404 CK	1	22 kW	DC Leakage + SPD + PEN	Wifi	No	Yes	1

FEATURES: charging solutions designed to ensure easy access to charging either with free access or with authorization via the myJOINON app. The charging power can be configured through the myJOINON app, which also allows users to monitor consumption, keep the wallbox constantly updated, receive notifications related to the system and the charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Customizable front panel available upon request.
EQUIPMENT: LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Equipped with anti-tamper.



GW J3 402 CF

I-CON EVO Wallbox - free access or via APP with TIC device

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 402 CF	1	7,4 kW	DC Leakage	Wifi	No	Yes	1
GW J3 404 CF	1	22 kW	DC Leakage	Wifi	No	Yes	1

FEATURES: charging solutions designed to ensure easy access to charging either with free access or with authorization via the myJOINON app. The charging power can be configured through the myJOINON app, which also allows users to monitor consumption, keep the wallbox constantly updated, receive notifications related to the system and the charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Customizable front panel available upon request.
EQUIPMENT: LED indicators for user status signaling. TIC device inserted inside.

For complex residential/condominium scenarios



GW J3 512 G

I-CON EVO Wallbox - free access or via APP connectable in Master/Slave

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 502 G	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1
GW J3 504 G	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1
Type of Socket: Mobile with cable							
GW J3 512 G	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1
GW J3 513 G	1	11 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1
GW J3 514 G	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1

FEATURES: charging solutions designed to ensure access to charging either with free access or with authorization via the myJOINON app when the SMALL NET management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station and reviewing logs. With the myJOINON app and the SMALL NET platform, users can monitor consumption, receive notifications related to the system and charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Mobile connector versions equipped with a smooth 5-meter cable and integrated sheath. Integrated SPDs.



GW J3 502 GK

I-CON EVO Wallbox - free access or via APP connectable in Master/Slave with integrated PEN

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 502 GK	1	7,4 kW	DC Leakage + SPD + PEN	Wifi+Ethernet	No	Yes	1
GW J3 504 GK	1	22 kW	DC Leakage + SPD + PEN	Wifi+Ethernet	No	Yes	1

FEATURES: charging solutions designed to ensure access to charging either with free access or with authorization via the myJOINON app when the SMALL NET management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station and reviewing logs. With the myJOINON app and the SMALL NET platform, users can monitor consumption, receive notifications related to the system and charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Equipped with anti-tamper.



GW J3 502 GF

I-CON EVO Wallbox - free access or via APP connectable in Master/Slave with TIC device

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 502 GF	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1
GW J3 504 GF	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	No	Yes	1

FEATURES: charging solutions designed to ensure access to charging either with free access or with authorization via the myJOINON app when the SMALL NET management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station and reviewing logs. With the myJOINON app and the SMALL NET platform, users can monitor consumption, receive notifications related to the system and charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. TIC device inserted inside. Integrated SPDs.

I-CON EVO

For corporate or semi-public scenarios



GW J3 602 T

I-CON EVO Wallbox - controlled access connectable in Master/Slave

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 602 T	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1
GW J3 603 T	1	11 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1
GW J3 604 T	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1
Type of Socket: Mobile with cable							
GW J3 612 T	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1
GW J3 613 T	1	11 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1
GW J3 614 T	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes	1

FEATURES: charging solutions designed to ensure controlled access to charging either with one or more RFID cards or with authorization via the myJOINON app when the SMALL NET management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station, reviewing logs, and configuring the RFID cards if necessary. With the myJOINON app, users can monitor consumption, receive notifications related to the system and charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Mobile connector versions equipped with a smooth 5-meter cable and integrated sheath. Integrated SPDs. Includes 2 RFID user cards.



GW J3 602 TK

I-CON EVO Wallbox - controlled access connectable in Master/Slave with integrated PEN

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 602 TK	1	7,4 kW	DC Leakage + SPD + PEN	Wifi+Ethernet	Yes	Yes	1
GW J3 604 TK	1	22 kW	DC Leakage + SPD + PEN	Wifi+Ethernet	Yes	Yes	1

FEATURES: charging solutions designed to ensure controlled access to charging either with one or more RFID cards or with authorization via the myJOINON app when the SMALL NET management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station, reviewing logs, and configuring the RFID cards if necessary. With the myJOINON app, users can monitor consumption, receive notifications related to the system and charging station status, and much more. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Equipped with anti-tamper. Includes 2 RFID user cards.



GW J3 702 T

I-CON EVO Wallbox - controlled access connectable in Master/Slave

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 702 T	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1
GW J3 704 T	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1
Type of Socket: Mobile with cable							
GW J3 712 T	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1
GW J3 714 T	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or useful for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through App when a third-party management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station, reviewing logs, and configuring the RFID cards if necessary. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Mobile connector versions equipped with a smooth 5-meter cable and integrated sheath. Integrated SPDs. Includes 2 RFID user cards.

I-CON EVO Wallbox - controlled access connectable in Master/Slave with integrated PEN



GW J3 704 TK

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 704 TK	1	22 kW	DC Leakage + SPD + PEN	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or useful for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through App when a third-party management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station, reviewing logs, and configuring the RFID cards if necessary. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Equipped with anti-tamper. Includes 2 RFID user cards.

I-CON EVO Wallbox - controlled access connectable in Master/Slave with TIC device



GW J3 702 TF

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J3 702 TF	1	7,4 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1
GW J3 704 TF	1	22 kW	DC Leakage + SPD	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or useful for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through App when a third-party management platform is activated. The charging power can be configured through the onboard portal, which also allows checking the status of the charging station, reviewing logs, and configuring the RFID cards if necessary. For dynamic load management (DLM), we recommend GWJ8037 (single-phase) or GWJ8038 (three-phase) kits for systems up to 100 A in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. For systems above 100 A, we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each wallbox. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8111).

EQUIPMENT: LED indicators for user status signaling. TIC device inserted inside. Integrated SPDs. Includes 2 RFID user cards.

COMPLEMENTS FOR INSTALLATION


I-CON EVO accessories



GW J8 002

RFID charging authorization card

Code	Description	Suitable for	Pack Carton
GW J8 002	JOINON card to enable the charging process	Wallbox I-CON EVO	1



GW J8 014

Communication system KIT

Code	Description	Suitable for	Pack Carton
GW J8 014	SIM Data JOINON	Wallbox I-CON EVO	1
GW J8 111	4G Modem Kit	Wallbox I-CON EVO	1
GW J8 113	Commissioning Kit	Wallbox I-CON EVO	1/10

NOTES: the commissioning kit GWJ8113 includes the JOINON data SIM and the QR Code sticker, which helps facilitate charging authorization through the app. For each data SIM, different tariff plans can be activated depending on the number of stations connected to the 4G modem.



GW J8 102

Complementary items for installation

Code	Description	Suitable for	Pack Carton
GW J8 101	Flush-mounting box	Wallbox I-CON EVO	1
GW J8 102	Floor-mounting support (single-sided)	Wallbox I-CON EVO	1
GW J8 103	Floor-mounting support (double-sided)	Wallbox I-CON EVO	1
GW J8 104	Protection cover	Wallbox I-CON EVO	1
GW J8 105	Charging cable holder	Wallbox I-CON EVO	1/4
GW J8 034	Metal plate for wall mounting	Wallbox I-CON EVO	1



GW J8 037

Dynamic load management KIT

Code	Description	Suitable for	Pack Carton
GW D6 809	IP Energy Meter	Wallbox I-CON EVO	1/2
GW D6 821	IP Module	Wallbox I-CON EVO	1/5
GW J8 037	CT kit for single-phase DLM	Wallbox I-CON EVO	1
GW J8 038	CT kit for three-phase DLM	Wallbox I-CON EVO	1

NOTES: for dynamic load management in systems up to 100 A, we recommend the single-phase (GWJ8037) or three-phase (GWJ8038) DLM kits. For systems above 100 A, the dynamic load management solution requires the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog.



I-CON EVO




Scan the QR Code and find out all the technical informations.

SAFE AND SMART SOLUTION




Manage your charging point via WiFi, LAN or 4G, for easy monitoring and remote control. Thanks to OTA (Over the Air) technology, the station is able to automatically update, ensuring the latest available features and the security of a better charging experience.

DYNAMIC LOAD MANAGEMENT



Dynamic load management (DLM) available on all products in the range both as single installation and in multiple configurations (Master/Slave) to guarantee the best distribution of loads, avoiding peaks or overloads and optimizing the costs of sizing the electrical system.

MYJOINON APP



The myJOINON app, developed for private contexts (single homes, condominiums, corporate fleets) allows you to configure the free access charging stations and monitor the consumption and charging status, easily, wherever you are, thanks to a simple and intuitive interface.

I-ON EVO

AC charging stations

SEMI-PUBLIC / PUBLIC USE	**APPLICATION CONTEXT**		Companies, Hotel, Restaurants, Sport and shopping centres, Public car parks, Private car parks					
	INSTALLATION TYPE		Wall-mounting		Floor-mounting			
	CASING TYPE		Metal 		Metal 			
	DYNAMIC LOAD MANAGEMENT		Yes		Yes			
	CHARGING CONNECTOR TYPE		2 x Type 2 Vandal-proof with shutter		2 x Type 2 Vandal-proof with shutter		2 x Type 2 Spiral mobile connector	
	USER RECOGNITION		RFID + APP	RFID + APP	RFID + APP		RFID + APP	
	ENERGY METER		Yes	Yes, MID type	Yes	Yes, MID type	Yes	Yes, MID type
	CONNECTIVITY		WiFi + LAN		WiFi + LAN			
	MASTER / SLAVE		Yes		Yes			
	MAXIMUM CHARGING POWER	**2x7.4 kW**	GW J2 402 T	GW J2 502 T	GW J1 402 T	GW J1 502 T	GW J1 412 T	-
		2x11 kW	-	-	GW J1 403 T	-	-	-
		2x22 kW	GW J2 404 T	GW J2 504 T	GW J1 404 T	GW J1 504 T	GW J1 414 T	GW J1 514 T

NOTES: optional 4G internal modem.

AC charging stations - UK - PEN compliant

SEMI-PUBLIC / PUBLIC USE	APPLICATION CONTEXT		Companies, Hotels, Restaurants, Shopping centres, Public car parks, Private car parks	
	INSTALLATION TYPE		Wall-mounting	Floor-mounting
	CASING TYPE		Metal 	Metal 
	DYNAMIC LOAD MANAGEMENT		Yes	Yes
	CHARGING CONNECTOR TYPE		2 x Type 2 Vandal-proof with shutter	2 x Type 2 Vandal-proof with shutter
	USER RECOGNITION		RFID + APP	
	ENERGY METER		Yes, MID type	Yes, MID type
	CONNECTIVITY		WiFi + LAN	
	MASTER / SLAVE		Yes	
	MAXIMUM CHARGING POWER	2x7.4 kW	GW J2 502 TK	GW J1 502 TK
		2x22 kW	GW J2 504 TK	GW J1 504 TK

NOTES: optional 4G internal modem.

AC charging stations - FR - TIC compliant

SEMI-PUBLIC / PUBLIC USE	APPLICATION CONTEXT		Companies, Hotels, Restaurants, Shopping centres, Public car parks, Private car parks	
	INSTALLATION TYPE		Wall-mounting	Floor-mounting
	CASING TYPE		Metal 	Metal 
	DYNAMIC LOAD MANAGEMENT		Yes	Yes
	CHARGING CONNECTOR TYPE		2 x Type 2 Vandal-proof with shutter	2 x Type 2 Vandal-proof with shutter
	USER RECOGNITION		RFID + APP	
	ENERGY METER		Yes, MID type	Yes, MID type
	CONNECTIVITY		WiFi + LAN	
	MASTER / SLAVE		Yes	
	MAXIMUM CHARGING POWER	2x7.4 kW	GW J2 502 TF	GW J1 502 TF
		2x22 kW	GW J2 504 TF	GW J1 504 TF

NOTES: optional 4G internal modem.

I-ON EVO

AC charging stations



The I-ON EVO (floor-mounted) and I-ON EVO WALL (wall-mounted) solutions by JOINON are ideal for corporate charging, thanks to integration with the myJOINON app and the SMALL NET platform. They are also perfect for public spaces, supporting third-party app and platform compatible with OCPP. Resistant to impacts, vandalism, and weather conditions, they feature an innovative hexagonal design that blends well with urban environments and parking areas. The color graphic display offers a clear interface, enhancing the user experience. Available with standard JOINON graphics or customizable upon request, they fit any style and branding requirements

I-ON EVO CHARGING SYSTEMS FOR ELECTRIC VEHICLES - AC (MODE 3)

IP 55 IK 11 WiFi OCPP DLM SOLAR

Floor-mounted - for corporate or semi-public or public scenarios



GW J1 412 T

I-ON EVO Column - controlled access connectable in Master/Slave

RFID APP

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J1 402 T	2	7,4 kW + 7,4 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes	1
GW J1 403 T	2	11 kW + 11 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes	1
GW J1 404 T	2	22 kW + 22 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes	1
Type of Socket: Mobile with spiral cable							
GW J1 412 T	2	7,4 kW + 7,4 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes	1
GW J1 414 T	2	22 kW + 22 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes	1

FEATURES: charging stations designed for ensuring controlled access to charging either with one or more RFID cards or with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).

EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated SPDs. Mobile connector versions equipped with a spiral cable with a maximum extension of 4 meters and integrated sheath. Includes 2 RFID user cards.



GW J1 502 T

I-ON EVO Column - controlled access connectable in Master/Slave

RFID APP MID

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J1 502 T	2	7,4 kW + 7,4 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes, MID type	1
GW J1 504 T	2	22 kW + 22 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes, MID type	1
Type of Socket: Mobile with spiral cable							
GW J1 514 T	2	22 kW + 22 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).

EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated SPDs. Mobile connector versions equipped with a spiral cable with a maximum extension of 4 meters and integrated sheath. Includes 2 RFID user cards.

I-ON EVO Column - controlled access connectable in Master/Slave with integrated PEN



GW J1 502 TK

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J1 502 TK	2	7,4 kW + 7,4 kW	DC Leakage + MCB + RCD + PEN	Wifi+Ethernet	Yes	Yes, MID type	1
GW J1 504 TK	2	22 kW + 22 kW	DC Leakage + MCB + RCD + PEN	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).
EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Includes 2 RFID user cards.

I-ON EVO Column - controlled access connectable in Master/Slave with TIC device



GW J1 502 TF

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J1 502 TF	2	7,4 kW + 7,4 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes, MID type	1
GW J1 504 TF	2	22 kW + 22 kW	DC Leakage + MCB + RCD	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards with authorization through a third-party app and activation of a management platform. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).
EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. TIC device inserted inside on DIN rail. Integrated SPDs. Includes 2 RFID user cards.

I-ON EVO

WALLBOX I-ON EVO CHARGING SYSTEMS FOR ELECTRIC VEHICLES - AC (MODE 3)

IP 55 **IK 10**

Wall-mounted - for corporate or semi-public or public scenarios



GW J2 402 T

I-ON EVO Wallbox - controlled access connectable in Master/Slave

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J2 402 T	2	7,4 kW + 7,4 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes	1
GW J2 404 T	2	22 kW + 22 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes	1

FEATURES: charging stations designed for ensuring controlled access to charging either with one or more RFID cards or with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).

EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated SPDs. Includes 2 RFID user cards.



GW J2 502 T

I-ON EVO Wallbox - controlled access connectable in Master/Slave

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J2 502 T	2	7,4 kW + 7,4 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes, MID type	1
GW J2 504 T	2	22 kW + 22 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).

EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated SPDs. Includes 2 RFID user cards.



GW J2 502 TK

I-ON EVO Wallbox - controlled access connectable in Master/Slave with integrated PEN

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J2 502 TK	2	7,4 kW + 7,4 kW	DC Leakage + RCBO + PEN	Wifi+Ethernet	Yes	Yes, MID type	1
GW J2 504 TK	2	22 kW + 22 kW	DC Leakage + RCBO + PEN	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).
EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. Integrated PEN to avoid having to install additional ground stakes. Integrated SPDs. Includes 2 RFID user cards.



GW J2 502 TF

I-ON EVO Wallbox - controlled access connectable in Master/Slave with TIC device

Code	N. of sockets Type 2	Power max.	Protection integrated	Connectivity	RFID Reader	Energy meter	Pack Carton
Type of Socket: Vandal-proof recessed with shutter							
GW J2 502 TF	2	7,4 kW + 7,4 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes, MID type	1
GW J2 504 TF	2	22 kW + 22 kW	DC Leakage + RCBO	Wifi+Ethernet	Yes	Yes, MID type	1

FEATURES: charging solutions designed for offering a chargeable charging service or for consumption reporting, as they are equipped with a certified MID energy meter. They ensure controlled access to charging either with one or more RFID cards or with authorization through a third-party app when a management platform is activated. For dynamic load management (DLM), we recommend the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog on each socket in order to avoid overloads (and thus blackouts) and to use the Solar Boost feature that allows electric vehicles to be charged using excess energy from installed photovoltaic panels. Using DLM, these products can be interconnected via Ethernet in Master/Slave mode to optimally balance the maximum charging power for each charging station. Customizable front panel available upon request. Can be accessorized with a 4G modem kit (GWJ8013).
EQUIPMENT: no. 2 T2 socket modules, each equipped with a 4.3" color TFT display, a language selection button, and an RFID reader. LED indicators for user status signaling. TIC device inserted inside on DIN rail. Integrated SPDs. Includes 2 RFID user cards.

COMPLEMENTS FOR INSTALLATION


I-ON EVO accessories



GW J8 002

RFID charging authorization card

Code	Description	Suitable for	Pack Carton
GW J8 002	JOINON card to enable the charging process	I-ON EVO and I-ON EVO WALL	1



GW J8 014

Communication system KIT

Code	Description	Suitable for	Pack Carton
GW J8 014	SIM Data JOINON	I-ON EVO and I-ON EVO WALL	1
GW J8 013	4G Modem Kit	I-ON EVO and I-ON EVO WALL	1
GW J8 114	Commissioning kit	I-ON EVO and I-ON EVO WALL	1/10

NOTES: the commissioning kit GWJ8114 includes the JOINON data SIM and the QR Code sticker, which helps facilitate charging authorization via the app. For each data SIM, different tariff plans can be activated depending on the number of stations connected to the 4G modem.



GW J8 021

Complementary items for installation

Code	Description	Suitable for	Pack Carton
GW J8 021	Concrete ground fixing plate	I-ON EVO	1
GW 46 551	Pole support KIT	I-ON EVO WALL	1



GW J8 038

Dynamic load management KIT

Code	Description	Suitable for	Pack Carton
GW D6 809	IP Energy Meter	I-ON EVO and I-ON EVO WALL	1/2
GW D6 821	IP Module	I-ON EVO and I-ON EVO WALL	1/5
GW J8 037	CT kit for single-phase DLM	I-ON EVO and I-ON EVO WALL	1
GW J8 038	CT kit for three-phase DLM	I-ON EVO and I-ON EVO WALL	1

NOTES: for dynamic load management in systems up to 100 A, we recommend the single-phase (GWJ8037) or three-phase (GWJ8038) DLM kits. For systems above 100 A, the dynamic load management solution requires the use of the energy meter (GWD6809) in addition to the IP module (GWD6821) and closed amperometric transformers (code GW96447 to GW96453) available in the Energy Catalog.



I-ON EVO




Scan the QR Code and find out all the technical informations.

EASY CHARGING WITH “ONE-HAND RECHARGE” SYSTEM



Charging your electric vehicle is faster and more practical. Thanks to the “one-hand recharge” feature, you can connect the charging socket with one hand, so as to facilitate other unloading operations (shopping bags, packages, suitcases and more).

DYNAMIC LOAD MANAGEMENT



Dynamic load management (DLM) available on all products in the range both as single installation and in multiple configurations (Master/Slave) to guarantee the best distribution of loads, avoiding peaks or overloads and optimizing the costs of sizing the electrical system.

DESIGN SUITABLE FOR EVERY NEED



The unique style, with an exclusive hexagonal shape, integrates perfectly into any parking configuration, including “Back To Back” (two units placed together, one behind the other) with considerable savings on installation costs.

DC charging stations

SEMI-PUBLIC / PUBLIC USE	**APPLICATION CONTEXT**		Offices, Hotel, Restaurants, Sport and shopping centres, Public / Private car parks, Service stations, Motorways	
	INSTALLATION TYPE		Wall- or Floor-mounting	Floor-mounting	Floor-mounting
	CASING TYPE		Metal 	Metal 	Metal 
	CHARGING CONNECTOR TYPE		1 x CCS2 mobile connector 80 A	2 x CCS2 mobile connectors 150 A	2 x CCS2 mobile connectors 250 A (peak 350 A)
	CONNECTIVITY		WiFi + LAN + 4G	WiFi + LAN + 4G	WiFi + LAN + 4G
	USER RECOGNITION		RFID + APP	RFID + APP	RFID + APP
	ENERGY METER		Yes, integrated DC Meter	Yes, integrated DC Meter	Yes, integrated DC Meter
	MAXIMUM CHARGING POWER	**30 kW**	GW J9 011 W	-	-
		60 kW	-	GW J9 122 Y	-
		90 kW	-	-	GW J9 232 Y
		120 kW	-	-	GW J9 242 Y
		150 kW	-	-	GW J9 252 Y
		180 kW	-	-	GW J9 262 Y

NOTES: versions with CHAdeMO or GBT connectors, 7-meter-long charging cables, payment terminal or DC certified energy meters are available upon request. For the 150 kW and 180 kW versions, CCS2 connectors with a maximum output current of 300 A (peak at 500 A) can also be requested. Possibility of floor installation for code GWJ9011W via dedicated accessory.

I-FAST

DC charging stations

The I-FAST products are JOINON solutions for fast DC charging, ideal for charging all types of electric vehicles equipped with high-power systems in private or public high-traffic parking areas, highways, expressways, and service areas. They support any OCPP-compatible third-party app and platform. The range includes wallboxes up to 30 kW and stations up to 180 kW. They are characterized by an elegant design and finishes that make them an urban and extra-urban furniture, with a graphic display for a better User Experience and service use for the EV Driver.



I-FAST CHARGING SYSTEMS FOR ELECTRIC VEHICLES - DC (MODE 4)

IP 55 **IK 10**

Wall-mounted



GW J9 011 W

I-FAST Wallbox - Wall - or floor-mounting charging station

Code	No. of sockets	Power max.	Max output current	RFID Reader	Energy meter	Payment terminal	Pack Carton
Connector type: CCS2							
GW J9 011 W	1	30 kW	CCS2: 80A	Yes	Yes, integrated DC Meter	No	1

FEATURES: products equipped with a 4 m charging cable. Possibility of connection via WiFi network, Ethernet cable, or 4G network.
EQUIPMENT: products equipped with a 7" color TFT graphic display and menu navigation buttons.
NOTES: versions with 7-meter-long charging cable or CHAdeMO connector are available upon request.

Floor-mounted



GW J9 122 Y

I-FAST Compact Station - Compact floor charging station

Code	No. of sockets	Power max.	Max output current	RFID Reader	Energy meter	Payment terminal	Pack Carton
Connector type: CCS2							
GW J9 122 Y	2	60 kW	CCS2: 150A	Yes	Yes, integrated DC Meter	No	1

FEATURES: products equipped with a 4 m charging cable. Possibility of connection via WiFi network, Ethernet cable, or 4G network. They can simultaneously charge up to 2 electric vehicles.
EQUIPMENT: products equipped with a 7" color TFT graphic display and menu navigation buttons.
NOTES: versions with CHAdeMO or GBT connectors, 7-meter-long charging cables, payment terminal or DC certfied energy meters, are available upon request.



GW J9 232 Y

I-FAST Station - Floor charging station

Code	No. of sockets	Power max.	Max output current	RFID Reader	Energy meter	Payment terminal	Pack Carton
Connector type: CCS2							
GW J9 232 Y	2	90 kW	CCS2: 250A (peak 350A)	Yes	Yes, integrated DC Meter	No	1
GW J9 242 Y	2	120 kW	CCS2: 250A (peak 350A)	Yes	Yes, integrated DC Meter	No	1
GW J9 252 Y	2	150 kW	CCS2: 250A (peak 350A)	Yes	Yes, integrated DC Meter	No	1
GW J9 262 Y	2	180 kW	CCS2: 250A (peak 350A)	Yes	Yes, integrated DC Meter	No	1

FEATURES: products equipped with a 4.5 m charging cable. Possibility of connection via WiFi network, Ethernet cable, or 4G network. They can simultaneously charge up to 2 electric vehicles. The 90 kW, 120 kW, and 150 kW stations can be upgraded in terms of maximum power by adding 30 kW power modules (GWJ9902), reaching a maximum of 180 kW.
EQUIPMENT: products equipped with a 7" color TFT graphic display and menu navigation buttons.
NOTES: versions with CHAdeMO or GBT connectors, 7-meter-long charging cables, payment terminal or DC certfied energy meters, are available upon request. For the 150 kW and 180 kW versions, CCS2 connectors with a maximum output current of 300 A (peak at 500 A) can also be requested.

COMPLEMENTS FOR INSTALLATION

I-FAST accessories



GW J8 002

RFID charging authorization card

Code	Description	Suitable for	Pack Carton
GW J8 002	JOINON card to enable the charging process	I-FAST WALLBOX, I-FAST COMPACT STATION and I-FAST STATION	1



GW J8 112

Communication system kit

Code	Description	Suitable for	Pack Carton
GW J8 112	JOINON Micro SIM Data	I-FAST WALLBOX, I-FAST COMPACT STATION and I-FAST STATION	1
GW J8 115	I-FAST Commissioning Kit	I-FAST COMPACT STATION and I-FAST STATION	1/10
GW J8 116	I-FAST Commissioning Kit 1 Connector	I-FAST WALLBOX	1/10

NOTES: the commissioning kits include the JOINON data SIM and the QR Code sticker to facilitate authorization for charging via the app. For each data SIM, different pricing plans can be activated depending on the number of stations connected to the 4G modem.



GW J9 911

Complementary items for installation

Code	Description	Suitable for	Pack Carton
GW J9 902	30 kW AC-DC additional power conversion module	I-FAST STATION	1
GW J9 911	Upper support for charging cable	I-FAST COMPACT STATION	1
GW J9 912	Upper support for charging cable	I-FAST STATION	1
GW J9 923	Floor installation support	I-FAST WALLBOX	1
GW J9 921	Concrete floor fixing plate	I-FAST COMPACT STATION	1
GW J9 922	Concrete floor fixing plate	I-FAST STATION	1



I-FAST



Scan the QR Code and find out all the technical informations.

WIDE RANGE SUITABLE FOR EVERY CONTEXT



I-FAST is the line of DC stations, available in different versions: floor-mounting (Compact Station and Station) and wall-mounting (Wallbox). Thanks to its scalable solution, I-FAST stations offer charging powers ranging from 30kW to 180kW. Furthermore, the 90kW stations can be easily upgraded up to 180kW, ensuring greater flexibility and performance.

7” GRAPHIC DISPLAY



Simple and intuitive interface, thanks to a 7” graphic monitor that improves the user experience while charging your vehicle.

STRENGTH AND PROTECTION



Highest level of protection against dust and fluid penetration available on the market today: IP55. A high level of protection from impacts, stresses and acts of vandalism, for a perfect supply of energy whatever the environmental conditions: IK10.

AC charging cables

FOR AC CHARGING UNITS

CABLE TYPE	SMOOTH							
								
MAXIMUM CURRENT	20 A		32 A		16 A		32 A	
MAXIMUM POWER	4,6 kW		7,4 kW		11 kW		22 kW	
VOLTAGE	230/250 V				380/480 V			
FREQUENCY	50-60 Hz				50-60 Hz			
CABLE LENGTH	5 m	8 m	5 m	8 m	5 m	8 m	5 m	8 m
NUMBER OF POLES	L1 - N - PE - CC - CP				L1/L2/L3 - N - PE - CC - CP			
CODE	GW J5 815 BL	GW J5 818 BL	GW J5 815 CL	GW J5 818 CL	GW J5 835 AL	GW J5 838 AL	GW J5 835 CL	GW J5 838 CL

FOR AC CHARGING UNITS

CABLE TYPE	SPIRAL	
		
MAXIMUM CURRENT	32 A	
MAXIMUM POWER	7,4 kW	22 kW
VOLTAGE	230/250 V	380/480 V
FREQUENCY	50-60 Hz	
CABLE LENGTH	4 m (maximum extension)	
NUMBER OF POLES	L1 - N - PE - CC - CP	L1/L2/L3 - N - PE - CC - CP
CODE	GW J5 814 CT	GW J5 834 CT

Components

Charging components



Range of Type 2 charging cables and connectors for electric vehicles, compliant with the international standards IEC 62196-1 and IEC 62196-2, and suitable for use with EV charging units according to IEC 61851. The range includes charging cables for electric vehicles, mobile Type 2 connectors with or without cable, and flushmounting Type 2 sockets equipped with safety shutters (IPXXD protection), dual drainage for water runoff, vandal-proof system, and a locking actuator that locks the shutters and interlocks the plug during energy delivery.

TYPE 2 CHARGING CABLES FOR ELECTRIC VEHICLES

Flat Charging cables

IP 55 **IK 10** **GWT 650°C 850°C**



GW J5 815 BL

Single Phase

Code	I max (A)	Power max.	Voltage	Frequency	Cable length	Number of poles	Pack Carton
GW J5 815 BL	20 A	4,6 kW	230/250 V	50 - 60 Hz	5 m	L1 - N - PE - CC - CP	1
GW J5 818 BL	20 A	4,6 kW	230/250 V	50 - 60 Hz	8 m	L1 - N - PE - CC - CP	1
GW J5 815 CL	32 A	7,4 kW	230/250 V	50 - 60 Hz	5 m	L1 - N - PE - CC - CP	1
GW J5 818 CL	32 A	7,4 kW	230/250 V	50 - 60 Hz	8 m	L1 - N - PE - CC - CP	1



GW J5 835 AL

Three phase

Code	I max (A)	Power max.	Voltage	Frequency	Cable length	Number of poles	Pack Carton
GW J5 835 AL	16 A	11 kW	380/480 V	50 - 60 Hz	5 m	L1/L2/L3 - N- PE - CC - CP	1
GW J5 838 AL	16 A	11 kW	380/480 V	50 - 60 Hz	8 m	L1/L2/L3 - N- PE - CC - CP	1
GW J5 835 CL	32 A	22 kW	380/480 V	50 - 60 Hz	5 m	L1/L2/L3 - N- PE - CC - CP	1
GW J5 838 CL	32 A	22 kW	380/480 V	50 - 60 Hz	8 m	L1/L2/L3 - N- PE - CC - CP	1

Components

Spiral charging cables

IP 55

IK 10

GWT 650°C 850°C



GW J5 814 CT

Spiral

Code	I max (A)	Power max.	Voltage	Frequency	Cable length	Number of poles	Pack Carton
GW J5 814 CT	32 A	7,4 kW	230/250 V	50 - 60 Hz	4 m	L1 - N - PE - CC - CP	1
GW J5 834 CT	32 A	22 kW	380/480 V	50 - 60 Hz	4 m	L1/L2/L3 - N- PE - CC - CP	1

Accessories for charging cable



GW J5 913

Accessories

Code	Description	Pack Carton
GW J5 913	Cable bag in waterproof fabric made from recycled material	10

TYPE 2 CHARGING SOCKETS FOR ELECTRIC VEHICLES

Type 2 charging sockets vandalproof



GW J5 002 B

Type 2 vandal-proof charging socket with shutter - IP55

IP	IK	GWT
55	10	960°C

Code	Sockets Type	No. of poles	Power max.	Locking system	Pack Carton
Cable entry orientation: Rear Connection					
GW J5 001 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	Yes	1/12
GW J5 002 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12
GW J5 003 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	No	1/12
GW J5 004 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	No	1/12
Cable entry orientation: Side Connection					
GW J5 011 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	Yes	1/12
GW J5 012 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12
GW J5 013 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	No	1/12
GW J5 014 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	No	1/12

FEATURES: charging sockets compliant with the international standard IEC 62196-2. Models GWJ50x3B and GWJ50x4B are provided without shutter lock, suitable for creating charging stations without access control (e.g., AUTOSTART configuration), with an IP55 protection rating both when the connector is inserted and when the socket is unengaged.
EQUIPMENT: Locking actuator to prevent interruptions during the charging process, internal water drainage system, micro-switch for monitoring the exact status and position of the charging socket.
NOTES: the actuator connector for wiring the Type 2 socket must be purchased separately (code GWJ5901).



GW J5 002 G

Type 2 vandal-proof charging socket with shutter and blinking lighting system - IP55

IP	IK	GWT
55	10	960°C

Code	Sockets Type	No. of poles	Power max.	Locking system	Pack Carton
Cable entry orientation: Rear Connection					
GW J5 001 G	Type 2	L1 - N- PE - CP - PP	7,4 kW	Yes	1/12
GW J5 002 G	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12
Cable entry orientation: Side Connection					
GW J5 011 G	Type 2	L1 - N- PE - CP - PP	7,4 kW	Yes	1/12
GW J5 012 G	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12

FEATURES: charging sockets compliant with the international standard IEC 62196-2, with an IP55 protection rating both when the connector is inserted and when the socket is unengaged.
EQUIPMENT: Locking actuator to prevent interruptions during the charging process, internal water drainage system, micro-switch to monitor the exact status and position of the charging socket. Equipped with an internal LED FLASHING light system to facilitate the insertion of the mobile connector by the EV driver.
NOTES: the actuator connector for wiring the Type 2 socket must be purchased separately (code GWJ5901).



GW J5 002 L

Type 2 vandal-proof charging socket with shutter and RGB lighting system - IP55

IP	IK	GWT
55	10	960°C

Code	Sockets Type	No. of poles	Power max.	Locking system	Pack Carton
Cable entry orientation: Rear Connection					
GW J5 002 L	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12
GW J5 004 L	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	No	1/12
Cable entry orientation: Side Connection					
GW J5 012 L	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Yes	1/12
GW J5 014 L	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	No	1/12

FEATURES: charging sockets compliant with the international standard IEC 62196-2, with an IP55 protection rating both when the connector is inserted and when the socket is unengaged.
EQUIPMENT: Locking actuator to prevent interruptions during the charging process, internal water drainage system, and micro-switches for monitoring the exact status and position of the charging socket. Equipped with an internal RGB LED lighting system to indicate the socket's status.
NOTES: the actuator connector for wiring the Type 2 socket must be purchased separately (code GWJ5901).

Components

Type 2 vandal-proof socket accessories



GW J5 901

Actuator connector

Code	Description	Suitable for	Pack Carton
GW J5 901	Actuator connector + crimp pins kit	Type 2 vandal-proof charging sockets	1/20

Type 2 mobile charging connectors



GW J5 114 B

Type 2 mobile charging connector with cable

IP **55** **IK** **10**

Code	Sockets Type	No. of poles	Power max.	Cable type/length	Pack Carton
GW J5 111 B	Type 2	L1 - N- PE - CP - PP	4,6 kW	Flat / 5 meters	1
GW J5 112 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	Flat / 5 meters	1
GW J5 113 B	Type 2	L1/L2/L3 - N- PE - CP - PP	11 kW	Flat / 5 meters	1
GW J5 114 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	Flat / 5 meters	1

FEATURES: overmoulded rubber inserts to improve grip. The product achieves IP55 degree if mated with GWJ5912 holder (sold separately).



GW J5 102 B

Type 2 mobile charging connector

IP **55** **IK** **10**

Code	Sockets Type	No. of poles	Power max.	Pack Carton
GW J5 101 B	Type 2	L1 - N- PE - CP - PP	7,4 kW	1
GW J5 102 B	Type 2	L1/L2/L3 - N- PE - CP - PP	22 kW	1

FEATURES: overmoulded rubber inserts to improve grip. The product achieves IP55 degree if mated with GWJ5912 holder (sold separately).

Type 2 mobile charging connector accessories



GW J5 912

Complementary items for Type 2 charging cable

Code	Description	Pack Carton
GW J5 912	Holder for Type 2 charging cable	1

FEATURES: the GWJ5912 protects the mobile connector from the ingress of dust and liquids, ensuring an IP55 protection rating. It features the same fastening system and housing as the Type 2 socket. It is installable in a flush-mount configuration.




Components



Scan the QR Code and find out all the technical informations.

THE FUTURE OF CHARGING IS GREEN



I-CORD socket and plug are made partially of Renycle®, a range of specialty technopolymers, obtained from recovered nylon, with much lower environmental impact than virgin material. As a result, it is ideal for projects where sustainability is a key requirement.

REMOVABLE AND REPAIRABLE COMPONENTS



The I-CORD charging cable connectors are designed to be easily disassembled and reassembled, allowing for quick replacement in the event of malfunction, without compromising the entire functionality of the system and ensuring simple and efficient maintenance over time.

EASY CHARGING WITH “ONE-HAND RECHARGE” SYSTEM



Vandal-proof socket with shutter, without lid, designed to facilitate the start of charging via a “one-hand” system. The socket is also available in versions with an INTERMITTENT LED lighting system, to facilitate cable insertion, or RGB LED, to highlight the socket status indication.

Energy and services distribution pedestals





68 Q-MC 63X

Stainless steel distribution and service pedestals

p. 1246

68 Q-MC

Pedestals for energy distribution and service in insulating material

p. 1254

68 Q-MC 63X

Wired distribution pedestals in AISI 316L stainless steel material

EXAMPLE OF APPLICATION									
Ports	Campsites	Urban areas	Gardens, parks	Block of flats	Industrial areas	TYPE		STAINLESS STEEL	IP DEGREE
●	●	●	●	●	●	PEDESTAL Q-MC 63X		GW 68 901	IP56
●		●	●		●			GW 68 902	IP56
●		●			●			GW 68 903	IP56
●								GW 68 904	IP56
	●	●			●			GW 68 905	IP56

Fire-fighting pedestals Q-MC 63 X in AISI 316 L stainless steel



CODE	CONFIGURATION
GW 68 921	SUITABLE FOR 6 KG FIRE EXTINGUISHER
GW 68 923	SUITABLE FOR VALVE, LANCE, SUPPORT AND HOSE
GW 68 779	KIT CONTAINING LANCE, 15M HOSE, SUPPORT AND ACCESSORIES

Empty distribution pedestal Q-MC 63 X in AISI 316 L stainless steel



CODE	CONFIGURATION	SIDE A	SIDE B
GW 68 931	DOUBLE-SIDED	Empty compartment that c an be equipped with 1 panel	Empty compartment that can be equipped with 1 panel

MAIN SWITCH	NO. OF MODULAR PROTECTION AND MONITORING DEVICES		TYPE AND NO. OF SOCKETS INSTALED		
SWITCH DISCONNECTOR	RESIDUAL CURRENT CIRCUIT BREAKERS 30mA AC		IEC 309 NON-INTERLOCKED	IEC 309 INTERLOCKED	
4P	2P	4P	2P+E	2P+E	3P+N+E
1 x 32A	4 x 16A			4 x 16A	
1 x 63A	2 x 16A	2 x 16A		2 x 16A	2 x 16A
1 x 80A	2 x 16A	2 x 32A		2 x 16A	2 x 32A
		2 x 63A			2 x 63A
1 x 32A	6 x 16A		6 x 16A		

Components for Q-MC 63 X in AISI 316 L stainless steel

TYPES OF PANELS





	FOR SBF INTERLOCKED SOCKET-OUTLETS			FOR IEC 309 NON-INTERLOCKED SOCKET-OUTLETS	
	CODE	TYPE	NO.	TYPE	NO.
	GW 68 745 W	67 IB range Vertical IP67 16/32A	2		
	GW 68 746 W	44 IB range Horizontal IP44 16/32A	2		
	GW 68 747 W	Combibloc range IP44/55 16/32A	2	IEC 309 range, flush-mounting 16A or 85x75mm flanged lids	1
	GW 68 748 W			IEC 309 range, flush-mounting 16/32A or 85x75mm flanged lids	4
	GW 68 749 W	67 IB range Vertical IP67 63A	1		
	GW 68 750 W	BLANK			

68 Q-MC 63X

Stainless steel distribution and service pedestals



AISI 316L Class II stainless steel terminals for electricity, water, TV signal, telephone and data distribution. The terminals are distinguished by their design and resistance to mechanical and atmospheric stress. They are suitable for installation in prestigious environments where, in addition to the aesthetic factor, top performance is also required. The range consists of pre-wired and unwired versions, which can be configured as needed.

COMPACT PEDESTALS IN STAINLESS STEEL AISI 316L

Wired



GW 68 901

QMC 63 X wired pedestals in stainless steel AISI 316L, with double-face take-off, equipped with vertical interlocked socket-outlets - Class II - IP55

Code	Socket-outlets 2P+E 16A	Socket-outlets 3P+N+E 16A	Socket-outlets 3P+N+E 32A	Socket-outlets 3P+N+E 63A	Pack Carton
GW 68 901	4	-	-	-	1
GW 68 902	2	2	-	-	1
GW 68 903	2	-	2	-	1
GW 68 904	-	-	-	2	1

PROTECTIONS:
GW68901: board In: 25 A.
Main switch disconnector 4P 32 A;
4 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V socket-outlets.
GW68902: board In: 40 A.
Main switch disconnector 4P 63 A;
2 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the two 2P+E 16 A 230 V socket-outlets;
2 RCBO - MDC Range 4P 400 V 16 A C characteristic 6 kA 0.03 A - AC Type for the two 3P+N+E 16 A 400 V socket-outlets.
GW68903: board In: 64 A.
Main switch disconnector 4P 80 A;
2 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the two 2P+E 16 A 230 V socket-outlets;
2 RCBO - MDC Range 4P 400 V 32 A C characteristic 6 kA 0.03 A - AC Type for the two 3P+N+E 32 A 400 V socket-outlets.
GW68904: board In: 90 A.
2 RCBO MT+BD 4P 400 V 63 A C characteristic 10 kA 0.03 A - AC type for the 2 3P+N+E 63 A 400 V socket-outlets.
CHARACTERISTICS: head in heat-absorbing thermoplastic material, base in stainless steel with easily removable knock-proof and anti-abrasion protective cover in insulating material.
Power supply terminal block section: GW68901 and GW68902 16 mm², GW68903 and GW68904 35 mm².
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230 V;
GW68901, GW68902 and GW68903: 4 padlockable 1/2" ball valves; GW68904: 2 padlockable 1/2" ball valves.



GW 68 905

QMC 63 X wired pedestal in stainless steel AISI 316L with double-face take-off equipped with IEC 309 socket-outlets - Class II - IP55

Code	Socket-outlets 2P+E 16A	Pack Carton
GW 68 905	6	1

PROTECTIONS: board In: 25 A.
Main switch disconnector 4P 32 A;
6 RCBO - MDC Range 2P 230 V 16 A C characteristic 6 kA 0.03 A - AC Type for the six 2P+E 16 A 230 V socket-outlets.
CHARACTERISTICS: head in heat-absorbing thermoplastic material, base in stainless steel with easily removable knock-proof and anti-abrasion protective cover in insulating material.
Power supply terminal block section: 16 mm².
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230 V.

Empty



GW 68 931

Empty pedestal in stainless steel AISI 316L with double-face take-off QMC 63X - Class II - IP55

Code	Type	Possible configuration	Possible configuration	No. of modules EN 50022	Pack Carton
GW 68 931	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1

CHARACTERISTICS: 18-module enclosure with hinged opening, that can be fitted with security lock, for access to modular devices.
Prearrangement for lighting kit 16W 230V and water kit with 2 or 4 padlockable 1/2" water taps, available as accessories.
Double-face take-off with cable fastener devices on sides A and B.
Head in heat-absorbing thermoplastic material, base in stainless steel with easily removable knock-proof and anti-abrasion protective cover in insulating material.
ACCESSORIES SUPPLIED: junction box for housing power supply terminal block.

COMPLEMENTARY ITEMS FOR COMPACT PEDESTALS

Panels



GW 68 748 W

Flanged panels prearranged for assembly of socket-outlets

Code	No. IB socket-outlets houseable	No of IEC 309 socket-outlets that can be housed	Pack Carton
Colour: White			
GW 68 745 W	2 IB Vert. 16-32A IP67	-	1/2
GW 68 746 W	2 IB Horiz. 16-32A SBF IP44	-	1/2
GW 68 747 W	2 COMBIBLOC 16-32A IP44/55	1 IEC 309 16A 2P+E IP44/67	1/2
GW 68 748 W	-	4 IEC 309 16-32A IP44/67	1/2
GW 68 749 W	1 IB Vert. 63A IP67	-	1/2

ACCESSORIES SUPPLIED: screws for fixing panel.
CHARACTERISTICS: dimensions (LxHxD): 211x276x17 mm.




GW 68 750 W

Blank panel

Code	Description	Pack Carton
Colour: White		
GW 68 750 W	Blank panel	1/2

ACCESSORIES SUPPLIED: screws for fixing panel.
CHARACTERISTICS: dimensions (LxHxD): 211x276x17 mm.

Service complementary items




GW 68 789

Power supply terminal blocks for compact pedestals

Code	Terminal blocks	For cables	Terminal type	Rail type	Pack Carton
GW 68 788	3P+N+E	Up to 16 mm²	Modular	EN 50035	1
GW 68 789	3P+N+E	Up to 35 mm²	With eyelet	EN 50035	1
GW 68 800	3P+N+E	Up to 70 mm²	With eyelet	EN 50035	1

68 Q-MC 63X

Water kit with lockable taps




GW 68 794

Code	Input	Output	Suitable for	Pack Carton
GW 68 793	N. 1 valve 1/2"	N. 2 taps 1/2"	QMC 63 B / 63 C	1
GW 68 794	N. 1 valve 1/2"	N. 4 taps 1/2"	QMC 63 B / 63 C	1

ACCESSORIES SUPPLIED: adjustment fittings and nuts for pedestals.

Lighting kit for compact pedestals



GW 68 790

Code	Lamp	Lamp power	Voltage	Lamp holder	Pack Carton
Lighting: Ordinary					
GW 68 790	FSS	16 W	230 V - 50 Hz	GR8	1
Lighting: EMERGENCY TYPE M					
GW 68 791	FSS	16 W	230 V - 50 / 60 Hz	GR10	1

ACCESSORIES SUPPLIED: lamp and supply cable.

CHARACTERISTICS: GW68791 permanent emergency lighting, equipped with double supply circuit, keeps the Ni/C storage batteries charged; autonomy 1h.

Lighting kit for compact pedestals - LED technology



GW 68 990

Code	Lamp	System power	Colour temperature	Pack Carton
Voltage: 220-240 V - 50/60 Hz				
GW 68 990	LED	8.7 W	4000 K	1

CHARACTERISTICS: the lighting KIT with LED technology enables electricity savings of up to 66%.

NOTES: due to the continuous changes with the LED technologies, the technical data can undertake variations.

Fixing plate



GW 68 796

Code	Description	Application	Material	Pack Carton
GW 68 796	Plate for fixing	On concrete	Stainless steel	1
GW 68 781	Plate for fixing	On MARTINI pontoon	Stainless steel	1
GW 68 782	Plate for fixing	On INGEMAR pontoon	Stainless steel	1

Security lock with key



GW 68 778

Code	Suitable for	For terminals	Pack Carton
GW 68 778	Enc. door and blank door	Q-MC in stainless steel material	1/5

ACCESSORIES SUPPLIED: 2 keys.

NOTES: all the keys and relative locks with the same product code are identical.



68 Q-MC 63X



Scan the QR Code and find out all the technical informations.

TOTAL INSULATION



The Class II case makes grounding and periodic maintenance unnecessary and increases the safety of the user. It prevents any possibility of coming into contact with live parts which, in the event of a loss of insulation, could be dangerous.

SAFETY FIRST



The water compartment is completely segregated and therefore separate from the electrical circuits: in this way, any water leakage or humidity will not compromise the safety and operation of the product.

ATTENTION TO DETAIL



The head is made of technopolymer to avoid the danger of slight burns after long exposures to the sun and has a scratch-resistant finish. In addition, it also has a handle for portability and two sections for winding around water pipes.

Wired distribution pedestals in insulating material

EXAMPLES OF APPLICATION												MAIN SWITCH		
												SWITCH DISCONNECTOR		
Ports	Campsites	Urban areas	Gardens, parks	Block of flats	Itinerant road shows	Industrial areas	TYPE		BLUE VERSION	WHITE VERSION	GREEN VERSION	IP DEGREE	2P	3P	4P
			●	●			Q-MC 16 B PEDESTAL		GW 68 841 A	GW 68 841 W		IP55			
									GW 68 842 A	GW 68 842 W		IP55			
					●		Q-MC 16 T PEDESTAL		GW 68 846 A	GW 68 846 W		IP55			
									GW 68 847 A	GW 68 847 W		IP55			
●		●		●		●	Q-MC 63 B PEDESTAL		GW 68 851 A	GW 68 851 W		IP55			1 x 32A
									GW 68 852 A	GW 68 852 W		IP55			1 x 32A
		●	●	●			Q-MC 63 B PEDESTAL				GW 68 855 G	IP55	1 x 40A		
●	●	●		●		●	Q-MC 63 E ELECTRONICS PEDESTAL		GW 68 876 A	GW 68 876 W		IP55			1 x 32A
									GW 68 877 A	GW 68 877 W		IP55			1 x 32A
									GW 68 878 A	GW 68 878 W		IP55			1 x 63A
●	●								GW 68 874 A	GW 68 874 W		IP55			
									GW 68 875 A	GW 68 875 W		IP55			
	●						Q-MC 63 C PEDESTAL		GW 68 856 A	GW 68 856 W		IP55	1 x 32A		
									GW 68 857 A	GW 68 857 W		IP44	1 x 40A		
									GW 68 858 A	GW 68 858 W		IP44	1 x 32A		
●		●		●		●	Q-MC 125 B PEDESTAL		GW 68 801 A	GW 68 801 W		IP55			1 x 32A
									GW 68 802 A	GW 68 802 W		IP44			1 x 63A
									GW 68 803 A	GW 68 803 W		IP44			1 x 63A
●	●					●	Q-MC 200 B PEDESTAL		GW 68 831 A	GW 68 831 W		IP44			1 x 32A
									GW 68 832 A	GW 68 832 W		IP55			1 x 32A
									GW 68 833 A	GW 68 833 W		IP55			1 x 32A
●	●						Q-MC 200 E ELECTRONICS PEDESTAL		GW 68 867 A	GW 68 867 W		IP55			
									GW 68 868 A	GW 68 868 W		IP55			

(*) Residual current device Type A.

NO. OF MODULAR PROTECTION AND MONITORING DEVICES						TYPE AND NO. SOCKETS INSTALLED					
RESIDUAL CURRENT DEVICE 30mA AC		MINIATURE CIRCUIT BREAKERS C CHARACTERISTIC 6kA		RESIDUAL CURRENT CIRCUIT BREAKERS 30mA AC		IEC 309 NON-INTERLOCKED	IEC 309 INTERLOCKED			SPECIAL SOCKETS	ITA./GER.STD. DOMESTIC SOCKETS
2P	4P	2P	3P	2P	4P	2P+E	2P+E	3P+E	3P+N+E	RJ45+ TV/SAT	2P+E 10/16A
				1 x 16A			2 x 16A				
				1 x 16A			1 x 16A				2
	1 x 40A	4 x 16A				6 x 16A					2
	1 x 40A	3 x 16A	1 x 16A				2 x 16A	1 x 16A			2
				4 x 16A			4 x 16A				
				2 x 16A 2 x 32A			2 x 16A 2 x 32A				
				4 x 10A*							4
				4 x 16A			4 x 16A				
				3 x 16A	1 x 16A		3 x 16A		1 x 16A		
				4 x 32A			4 x 32A				
					2 x 63A				2 x 63A		
Earth leakage relay with external toroid		MTHP 4P C125 16kA							1 x 125A		
				4 x 6A			4 x 16A				
				8 x 6A		8 x 16A					
				4 x 6A		4 x 16A				4+4	
				4 x 16A			4 x 16A				
				2 x 16A	2 x 16A		2 x 16A		2 x 16A		
				1 x 16A	2 x 25A		1 x 16A		2 x 32A		
				4 x 10A			4 x 16A				
				6 x 10A			6 x 16A				
				8 x 10A			8 x 16A				
Earth leakage relay with external toroid		MTX 4P 250A Type N 36kA				Direct coupling without socket					
		MTX 4P 250A Type N 36kA				1 Interlocked socket-outlet 250A with electric management					

Empty distribution pedestals

	TYPE	BLUE VERSION	WHITE VERSION	GREEN VERSION	EN 50022 MODULES	TAKE-OFF TYPE	SIDE A	SIDE B
	Q-MC 16 B PEDESTAL	GW 68 701 A	GW 68 701 W	-	18 (9x2)	Single-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 water kit
		GW 68 711 A	GW 68 711 W	-	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 16 T PEDESTAL	GW 68 712 A	GW 68 712 W	-	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 B PEDESTAL	GW 68 713 A	GW 68 713 W	GW 68 713 G	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 C PEDESTAL	GW 68 714 A	GW 68 714 W	-	18 (9x2)	Double-sided	Empty compartment that can be equipped with 1 panel	Empty compartment that can be equipped with 1 panel
	Q-MC 63 C PEDESTAL	GW 68 716 A	GW 68 716 W	-	36 (9x4)	Double-sided	Empty compartment that can be equipped with 2 panels	Empty compartment that can be equipped with 2 panels
	Q-MC 125 B PEDESTAL	GW 68 715 A	GW 68 715 W	-	14	Single-sided	Empty compartment with blank retractable door that can be equipped with 1 panel	Empty compartment with blank retractable door that can be equipped with 1 panel
	Q-MC 200 B PEDESTAL	GW 68 717 A	GW 68 717 W	-	28 (14x2)	Double-sided	Empty compartment with blank retractable door that can be equipped with 2 panels	Empty compartment with blank retractable door that can be equipped with 2 panels

Components for Q-MC 16 B, 16 T, 63 B and 63 C





TYPE OF PANELS						
FOR INTERLOCKED SOCKET-OUTLET ASSEMBLY					FOR NON-INTERLOCKED SOCKET-OUTLET ASSEMBLY	
BLUE VERSION	WHITE VERSION	GREEN VERSION	TYPE	NO.	TYPE	NO.
GW 68 745 A	GW 68 745 W	GW 68 745 G	67 IB range Vertical IP67 16/32A	2		
GW 68 746 A	GW 68 746 W		44 IB range Horizontal IP44 16/32A	2		
GW 68 747 A	GW 68 747 W		COMBIBLOC range IP44 or IP55 16/32A	2	IEC309 flush-mounting sockets 16A or 85x75mm flanged lids	1
GW 68 748 A	GW 68 748 W	GW 68 748 G			IEC309 flush-mounting sockets 16/32A or 85x75mm flanged lids	4
GW 68 749 A	GW 68 749 W		67 IB range Vertical IP67 63A	1		
GW 68 750 A	GW 68 750 W	GW 68 750 G	Blank			

Components for Q-MC 125 B and 200 B







TYPE OF PANELS					
FOR INTERLOCKED SOCKET-OUTLET ASSEMBLY				FOR NON-INTERLOCKED SOCKET-OUTLET ASSEMBLY	
BLUE VERSION	WHITE VERSION	TYPE	NO.	TYPE	NO.
	GW 68 731 W	67 IB range Vertical IP67 16/32A	3		
	GW 68 732 W	44 IB range Horizontal IP44 16/32A	4		
	GW 68 733 W	COMBIBLOC range IP44 or IP55 16/32A	3	IEC309 flush-mounting sockets 16/32A or 85x75mm flanged lids	2
	GW 68 734 W			IEC309 flush-mounting sockets 16/32A or 85x75mm flanged lids	6
	GW 68 735 W	67 IB range Vertical IP67 63A	2		
	GW 68 736 W			IEC309 flush-mounting sockets 125A	1
GW 68 737 A	GW 68 737 W	Blank			
GW 68 741 A	GW 68 741 W	14-module control unit panel EN 50022			

68 Q-MC

Pedestals for energy distribution and service in insulating material



The 68 Q-MC range is an innovative energy and services distribution system made of thermoplastic, for environments such as tourist ports, campsites and public spaces (trade fairs, markets, gardens, etc.). It combines an attractive design with complete reliability over time, thanks to its resistance to chemical and atmospheric agents. The range includes both pre-wired and unwired versions, which can be configured as needed, and is available in light blue and white.

COMPACT PEDESTAL IN INSULATED MATERIAL

Wired



GW 68 841

QMC 16 B wired pedestals with single-face take-off equipped with vertical interlocked socket-outlets and domestic socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	German Std socket-outlet 16A	Pack Carton
Colour: Light blue			
GW 68 841 A	2	-	1
GW 68 842 A	1	2	1
Colour: White			
GW 68 841 W	2	-	1
GW 68 842 W	1	2	1

PROTECTIONS:
GW68841A/W: board In: 14 A; 1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type.
GW68842A/W: board In: 14 A; 1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type.
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230V; nr.2 lockable 1/2" water taps.
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Power supply terminal block section: 16 mm². Pedestal dimensions: 445x625x300 mm (LxHxD).
Protection degree IP55.



GW 68 846

QMC 16 T transportable wired pedestals with double-face take-off equipped with vertical interlocked and non-interlocked socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Socket-out 3P+E 16A	German Std socket-outlet 16A	Pack Carton
Colour: Light blue				
GW 68 846 A	6 non-interlocked (4 side A - 2 side B)	-	2 (only side B)	1
GW 68 847 A	2 Interlocked (only side A)	1 Interlocked (only side B)	2 (only side B)	1
Colour: White				
GW 68 846 W	6 non-interlocked (4 side A - 2 side B)	-	2 (only side B)	1
GW 68 847 W	2 Interlocked (only side A)	1 Interlocked (only side B)	2 (only side B)	1

PROTECTIONS:
GW68846A/W: board In: 25 A; Main RCD 4P 40 A 0.03 A AC Type;
3 MCB - MTC Range 2P 230 V 16 A C 6 kA for the six 2P+E 16 A 230 V non-interlocked socket-outlets;
1 MCB - MTC Range 2P 230 V 16 A C 6 kA for the two 2P+E 10/16 A 230 V domestic socket-outlets.
GW68847A/W: board In: 25 A; Main RCD 4P 40 A 0.03 A AC Type;
2 MCB - MTC Range 2P 230 V 16 A C 6 kA for the two 2P+E 16 A 230 V interlocked socket-outlets;
1 MCB - MTC Range 3P 400 V 16 A C 6 kA for the 3P+E 16 A 400 V interlocked socket-outlet;
1 MCB - MTC Range 2P 230 V 16 A C 6 kA for the two 2P+E 10/16 A 230 V domestic socket-outlets.
ACCESSORIES SUPPLIED: plug IEC 309 for supply GW68846 and GW68847 3P+N+E 32A 400V; 5 mt of H 07 RN - F cable for supply;
1 LED lighting lamp 16W 230V.
CHARACTERISTICS: enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Pedestal dimensions: 445x697x346 mm (LxHxD).



GW 68 851

QMC 63 B wired pedestals with double-face take-off equipped with vertical interlocked socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Socket-out 2P+E 32A	Pack Carton
Colour: Light blue			
GW 68 851 A	4 (2 for side)	-	1
GW 68 852 A	2 (1 for side)	2 (1 for side)	1
Colour: White			
GW 68 851 W	4 (2 for side)	-	1
GW 68 852 W	2 (1 for side)	2 (1 for side)	1

PROTECTIONS:
GW68851A/W: board In: 25 A; Main switch disconnector 4P 32 A;
4 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V socket-outlets.
GW68852A/W: board In: 25 A; Main switch disconnector 4P 32 A;
2 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the two 2P+E 16 A 230 V socket-outlets;
2 RCBO - MDC Range 2P 230 V 32 A C characteristic 6 kA 0.03 A - AC Type for the two 2P+E 32 A 230 V socket-outlets.
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230 V; 4 padlockable 1/2" ball valves.
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Power supply terminal block section: 16 mm². Pedestal dimensions: 445x950x300 mm (LxHxD).



GW 68 855 G

QMC 63 B wired pedestal with double face take-off equipped with domestic sockets - IP55

Code	German Std socket-outlet 16A	Pack Carton
Colour: Green		
GW 68 855 G	4 (2 for side)	1

PROTECTIONS: board In: 32 A. Main switch disconnector 4P 40A;
4 RCBO - MDC Range 2P 230 V 10 A C 6 kA 0.03 A - A Type for the 2P+E 230 V domestic sockets.
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock for access to modular devices.
Power supply terminal section: 16mm². Pedestal dimensions: 445x950x300 mm (LxHxD).



GW 68 856

QMC 63 C Wired pedestals with double-sided take-off equipped with interlocked COMBIBLOC socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Pack Carton
Colour: Light blue		
GW 68 856 A	4 (2 for side)	1
Colour: White		
GW 68 856 W	4 (2 for side)	1

PROTECTIONS: board In: 20 A. Main switch disconnector 2P 32A;
4 RCBO - MDC Range 2P 230 V 6 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V interlocked socket-outlets.
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Power supply terminal block section: 16 mm². Pre-arrangement for LED lighting lamp 230V; pre-arrangement for nr. 2 or 4 padlockable 1/2" water taps.
Pedestal dimensions: 445x1284x300 mm (LxHxD).

68 Q-MC



GW 68 857

QMC 63 C Wired double-sided take-off pedestals equipped with non-interlocked IEC 309 socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Socket-out TV/SAT	Socket-out TEL/DATA	Pack Carton
Colour: Light blue				
GW 68 857 A	8 (4 for side)	-	-	1
GW 68 858 A	4 (2 for side)	4 (2 for side)	4 (2 for side)	1
Colour: White				
GW 68 857 W	8 (4 for side)	-	-	1
GW 68 858 W	4 (2 for side)	4 (2 for side)	4 (2 for side)	1

PROTECTIONS:

GW68857A/W: board In: 32 A; Main switch disconnector 2P 40A;

8 RCBO - MDC Range 2P 230 V 6 A C 6 kA 0.03 A - AC Type for the eight 2P+E 16 A 230 V non-interlocked socket-outlets.

GW68858A/W: board In: 25 A; Main switch disconnector 2P 32A;

4 RCBO - MDC Range 2P 230 V 6 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V non-interlocked socket-outlets.

CHARACTERISTICS: stainless steel cable fastener devices.

Enclosure with hinged opening that can be fitted with security lock, for access to modular devices.

Power supply terminal block section: 16 mm². Pre-arrangement for LED lighting lamp 230V; pre-arrangement for nr. 2 or 4 lockable spherical 1/2" water taps.

Pedestal dimensions: 445x1284x300 mm (LxHxD).

Protection degree IP55.

Wired with electronic system



GW 68 876

QMC 63 E wired pedestals with double-face take-off for prepaid, centralised electronic management system with vertical interlocked switched socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Socket-outlet 3P+N+E 16A	Socket-out 2P+E 32A	Pack Carton
Colour: Light blue				
GW 68 876 A	4 (2 for side)	-	-	1
GW 68 877 A	3	1	-	1
GW 68 878 A	-	-	4 (2 for side)	1
Colour: White				
GW 68 876 W	4 (2 for side)	-	-	1
GW 68 877 W	3	1	-	1
GW 68 878 W	-	-	4 (2 for side)	1

PROTECTIONS:
GW68876A/W: board In: 25 A; Main switch disconnector 4P 32 A;
4 MDC 2P 16 A 0.03 A one-way switches, class AC 6 kA for the 4 2P+E 16 A 230 V socket-outlets.
GW68877A/W: board In: 25 A; Main switch disconnector 4P 32 A;
3 MDC 2P 16 A 0.03 A one-way switches, class AC 6 kA for the 3 2P+E 16 A 230 V socket-outlets;
1 MDC 4P 16 A 0.03 A one-way switch, class AC 6 kA for the 3P+N+E 16 A 400 V socket-outlet.
GW68878A/W: board In: 50 A; Main switch disconnector 4P 63 A;
4 MDC 2P 32 A 0.03 A one-way switches, class AC 6 kA for the 4 2P+E 32 A 230 V socket-outlets.
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230 V; 4 padlockable 1/2" ball valves.
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Power supply terminal block section: 16 mm²; Pedestal dimensions: 445x1284x300 mm (LxHxD).
NOTES: for technical-commercial information, please contact your local sales representative or GSS (035 946 111).



GW 68 874

QMC 63 E wired pedestals with double-face take-off for prepaid centralised electronic management system, equipped with vertical interlocked socket-outlets - IP55

Code	Socket-out 3P+N+E 63A	Socket-out 3P+N+E 125A	Pack Carton
Colour: Light blue			
GW 68 874 A	2 (1 for side)	-	1
GW 68 875 A	-	1	1
Colour: White			
GW 68 874 W	2 (1 for side)	-	1
GW 68 875 W	-	1	1

PROTECTIONS:
GW68874A/W: board In: 90 A.
2 RCBO MT+BD 4P 400 V 63 A C characteristic 10 kA 0.03 A - AC type for the 2 3P+N+E 63 A 400 V socket-outlets.
GW68875A/W: board In: 90 A.
1 miniature circuit breaker with earthing residual current relay with separate toroid MTHP 4P 400 V 125 A C characteristic 16 kA for 125 A socket-outlet.
ACCESSORIES SUPPLIED: 1 LED lighting lamp 230 V;
GW68874A/W: 2 padlockable 1/2" ball valves; GW68875A/W: 2 padlockable 1/2" ball valves;
CHARACTERISTICS: stainless steel cable fastener devices; enclosure with hinged opening that can be fitted with security lock, for access to modular devices.
Power supply terminal block section: GW68874A/W 70 mm², GW68875A/W 70 mm²; Pedestal dimensions: 445x1284x300 mm (LxHxD).
NOTES: for technical-commercial information, please contact your local sales representative or GSS (035 946 111).

68 Q-MC

Access control



GW 68 998

Surface-mounting transponder reader for access control - IP56

Code	Description	Material	Colour	Pack Carton
GW 68 998	surface-mounting access control	Thermoplastic	Grey RAL 7012	1

APPLICATION: the access control can be integrated in the system with 68 Q-MC terminal boards with electronic management in order to allow the access of people in determinated areas, or to anable the use of specific services.

ACCESSORIES SUPPLIED: n. 2 M12 cable gland; screwcaps for double insulation; screws for the sealing of the frontal.

Empty



GW 68 701

Empty pedestals Q-MC 16 B - IP55

Code	Type	Possible configuration	Possible configuration	No. of modules EN 50022	Pack Carton
Colour: Light blue					
GW 68 701 A	Single-sided	Side A: 1 panel	Side B: 1 water kit	18 (9x2)	1
GW 68 711 A	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
Colour: White					
GW 68 701 W	Single-sided	Side A: 1 panel	Side B: 1 water kit	18 (9x2)	1
GW 68 711 W	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1

ACCESSORIES SUPPLIED: junction box for housing power supply terminal block.

CHARACTERISTICS: 18-module enclosure with hinged opening, that can be fitted with security lock, for access to modular devices; prearrangement for lighting kit 230V, available as an accessory.

GW68701A/W: single-face take-off with cable fastener devices only on side A;

GW68711A/W: double-face take-off with cable fastener devices on sides A and B;

Pedestal dimensions: 445x625x300 mm (LxHxD).



GW 68 712

Empty transportable pedestal Q-MC 16 T - IP55

Code	Type	Possible configuration	Possible configuration	No. of modules EN 50022	Pack Carton
Colour: Light blue					
GW 68 712 A	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
Colour: White					
GW 68 712 W	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1

CHARACTERISTICS: 18-module enclosure with hinged opening, that can be fitted with security lock, for access to modular devices; prearrangement for lighting kit 230V, available as an accessory. Pedestal dimensions: 445x697x346 mm (LxHxD).



GW 68 713

Empty pedestal Q-MC 63 B - IP55

Code	Type	Possible configuration	Possible configuration	No. of modules EN 50022	Pack Carton
Colour: Light blue					
GW 68 713 A	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
Colour: White					
GW 68 713 W	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
Colour: Green					
GW 68 713 G	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1

ACCESSORIES SUPPLIED: junction box for housing power supply terminal block.

CHARACTERISTICS: 18-module enclosure with hinged opening, that can be fitted with security lock, for access to modular devices; prearrangement for lighting kit 230V and water kit with 2 or 4 padlockable spherical taps of 1/2", available as accessories; double-face take-off with cable fastener devices on sides A and B. Pedestal dimensions: 445x950x300 mm (LxHxD).



GW 68 714

Empty pedestal Q-MC 63 C - IP55

Code	Type	Possible configuration	Possible configuration	No. of modules EN 50022	Pack Carton
Colour: Light blue					
GW 68 714 A	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
GW 68 716 A	Double-sided	Side A: 2 panels	Side B: 2 panels	36 (9x4)	1
Colour: White					
GW 68 714 W	Double-sided	Side A: 1 panel	Side B: 1 panel	18 (9x2)	1
GW 68 716 W	Double-sided	Side A: 2 panels	Side B: 2 panels	36 (9x4)	1

ACCESSORIES SUPPLIED: junction box for housing power supply terminal block.
GW68716A/W: dual 18-module enclosure with hinged opening, can be equipped with a security lock.
CHARACTERISTICS: 18-module enclosure with hinged opening, that can be fitted with security lock, for access to modular devices; prearrangement for lighting kit 16W 230V and water kit with 2 or 4 padlockable 1/2" water taps, available as accessories; double-face take-off with cable fastener devices on sides A and B. Pedestal dimensions: 445x1284x300 mm (LxHxD).

Complementary items for prepaid and centralised electronic system



GW 68 991

Transponder key programming kit (prepaid / centralised system)

Code	Description	Pack Carton
GW 68 991	Programming console and s/w for PC with USB key	1

NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or SAT (035 946 111).



GW 68 992

Transponder key (prepaid / centralised system)

Code	Description	N. Keys	Pack Carton
GW 68 992	Transponder key to encode	1	1/10

NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or SAT (035 946 111).



GW 68 994

RS485/USB insulated converter with terminal block

Code	Description	Pack Carton
GW 68 994	USB/RS485 converter	1

NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or SAT (035 946 111).
The converter RS485/USB can manage up to 250 pedestals for line. In case of more lines is necessary to use more converters GW68994.
For the use of more lines please verify that the PC has more USB doors availables. Use an Hub for have other USB.



GW 68 995

Kit for centralised system

Code	Description	Pack Carton
GW 68 995	Management software with USB key and converter	1

COMPOSITION:
1 USB key for PC;
1 USB-RS485 converter;
1 Sw for management To be used with terminal boards with electronic management system and with access control GW68998.
NOTES: for technical-commercial information, please contact your local sales representative or SAT (035 946 111).
General note for centralised system: for the wiring of the pedestals, in a centralised system, is necessary to use an RS485 Bus cable. The cable must be an armed and twisted with a couple of wires 0.22mm² and 120Ohm impedance of the cable.
Some cables suitable for centralised system: bELDEN P/N 9841, ITC/CDT 14S7Y and CEAM CPR 6003.

COMPLEMENTARY ITEMS FOR COMPACT PEDESTALS

Panels



GW 68 748 A

Flanged panels prearranged for assembly of socket-outlets

Code	No. IB socket-outlets houseable	No of IEC 309 socket-outlets that can be housed	Pack Carton
Colour: Light blue			
GW 68 745 A	2 IB Vert. 16-32A IP67	-	1/2
GW 68 746 A	2 IB Horiz. 16-32A SBF IP44	-	1/2
GW 68 747 A	2 COMBIBLOC 16-32A IP44/55	1 IEC 309 16A 2P+E IP44/67	1/2
GW 68 748 A	-	4 IEC 309 16-32A IP44/67	1/2
GW 68 749 A	1 IB Vert. 63A IP67	-	1/2
Colour: White			
GW 68 745 W	2 IB Vert. 16-32A IP67	-	1/2
GW 68 746 W	2 IB Horiz. 16-32A SBF IP44	-	1/2
GW 68 747 W	2 COMBIBLOC 16-32A IP44/55	1 IEC 309 16A 2P+E IP44/67	1/2
GW 68 748 W	-	4 IEC 309 16-32A IP44/67	1/2
GW 68 749 W	1 IB Vert. 63A IP67	-	1/2
Colour: Green			
GW 68 745 G	2 IB Vert. 16-32A IP67	-	1/2
GW 68 748 G	-	4 IEC 309 16-32A IP44/67	1/2

ACCESSORIES SUPPLIED: screws for fixing panel.
CHARACTERISTICS: dimensions (LxHxD): 211x276x17 mm.




GW 68 750 A

Blank panel

Code	Description	Pack Carton
Colour: Light blue		
GW 68 750 A	Blank panel	1/2
Colour: White		
GW 68 750 W	Blank panel	1/2
Colour: Green		
GW 68 750 G	Blank panel	1/2

ACCESSORIES SUPPLIED: screws for fixing panel.
CHARACTERISTICS: dimensions (LxHxD): 211x276x17 mm.


Service complementary items



GW 68 789

Power supply terminal blocks for compact pedestals

Code	Terminal blocks	For cables	Terminal type	Rail type	Pack Carton
GW 68 788	3P+N+E	Up to 16 mm²	Modular	EN 50035	1
GW 68 789	3P+N+E	Up to 35 mm²	With eyelet	EN 50035	1
GW 68 800	3P+N+E	Up to 70 mm²	With eyelet	EN 50035	1




GW 68 794

Water kit with lockable taps

Code	Input	Output	Suitable for	Pack Carton
GW 68 792	N. 1 valve 1/2"	N. 2 taps 1/2"	QMC 16 B	1
GW 68 793	N. 1 valve 1/2"	N. 2 taps 1/2"	QMC 63 B / 63 C	1
GW 68 794	N. 1 valve 1/2"	N. 4 taps 1/2"	QMC 63 B / 63 C	1

ACCESSORIES SUPPLIED: adjustment fittings and nuts for pedestals.

Lighting kit for compact pedestals



GW 68 790

Code	Lamp	Lamp power	Voltage	Lamp holder	Pack Carton
Lighting: Ordinary					
GW 68 790	FSS	16 W	230 V - 50 Hz	GR8	1
Lighting: EMERGENCY TYPE M					
GW 68 791	FSS	16 W	230 V - 50 / 60 Hz	GR10	1

ACCESSORIES SUPPLIED: lamp and supply cable.
CHARACTERISTICS: GW68791 permanent emergency lighting, equipped with double supply circuit, keeps the Ni/C storage batteries charged; autonomy 1h

Lighting kit for compact pedestals - LED technology



GW 68 990

Code	Lamp	System power	Colour temperature	Pack Carton
Voltage: 220-240 V - 50/60 Hz				
GW 68 990	LED	8.7 W	4000 K	1

CHARACTERISTICS: the lighting KIT with LED technology enables electricity savings of up to 66%.
NOTES: due to the continuous changes with the LED technologies, the technical data can undertake variations.

Compressed air kit



GW 68 770

Code	Maximum operating pressure	Input	Output	Pack Carton
GW 68 770	6 bar	N. 1 valve 1/2"	1 quick connection valve, female 3/8"	1

ACCESSORIES SUPPLIED: adjustment fittings and nuts for pedestals.

Fixing plate



GW 68 796

Code	Description	Application	Material	Pack Carton
GW 68 796	Plate for fixing	On concrete	Stainless steel	1
GW 68 781	Plate for fixing	On MARTINI pontoon	Stainless steel	1
GW 68 782	Plate for fixing	On INGEMAR pontoon	Stainless steel	1

Security lock with key



GW 68 776

Code	Suitable for	For terminals	Pack Carton
GW 68 776	Enc. door and blank door	Q-MC in insulating material	1/5

ACCESSORIES SUPPLIED: 2 keys.
NOTES: all the keys and relative locks with the same product code are identical.



GW 68 799

Fault signalling device

Code	Description	Pack Carton
GW 68 799	High efficiency LED with power supply unit	1

STANDARD PEDESTAL IN INSULATED MATERIAL

Wired



GW 68 801

Wired pedestals with single-sided take-off QMC 125 B equipped with horizontal interlocked socket-outlets - IP44

Code	Socket-outlet 2P+E 16A	Socket-outlet 3P+N+E 16A	Pack Carton
Colour: Light blue			
GW 68 801 A	4	-	1
GW 68 802 A	2	2	1
Colour: White			
GW 68 801 W	4	-	1
GW 68 802 W	2	2	1

PROTECTIONS:
GW68801A/W: board In: 25 A; Main switch disconnector 4P 32 A;
4 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V socket-outlets.
GW68802A/W: board In: 40 A; Main switch disconnector 4P 63 A;
2 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the two 2P+E 16 A 230 V socket-outlets;
2 RCBO - MDC Range 4P 400 V 16 A C 6 kA 0.03 A - AC Type for the two 3P+N+E 16 A 400 V socket-outlets.
ACCESSORIES SUPPLIED: 2 fluorescent lighting lamps 11W 230V;
4 padlockable 1/2" ball valves;
2 supports for flexible conduit GW68762.
CHARACTERISTICS: side A: user socket-outlets, cable guide with cable fastener devices, blank retractable door;
side B: enclosure complete with modular protection equipped with security lock.
Power supply terminal block section: GW68801A/W 16 mm², GW68802A/W 35 mm².
Pedestal dimensions: 600x840x520 mm (LxHxD).



GW 68 803

QMC 125 B wired pedestal with single-face take-off equipped with vertical interlocked socket-outlets - IP55

Code	Socket-outlet 2P+E 16A	Socket-out 3P+N+E 32A	Pack Carton
Colour: Light blue			
GW 68 803 A	1	2	1
Colour: White			
GW 68 803 W	1	2	1

Board In: 50A
PROTECTIONS: Main switch disconnector 4P 63A;
1 RCBO - MDC Range 2P 230 V 16 A C 6 kA 0.03 A - AC Type for the 2P+E 16 A 230 V socket-outlet;
2 RCBO - MDC Range 4P 400 V 25 A C 6 kA 0.03 A - AC Type for the two 3P+N+E 32 A 400 V socket-outlets.
ACCESSORIES SUPPLIED: 2 fluorescent lighting lamp 11W 230V; 4 padlockable 1/2" ball valves; 2 supports for flexible conduit GW68762.
CHARACTERISTICS: side A: user socket-outlets, cable guide with cable fastener devices, blank retractable door;
side B: enclosure complete with modular protection equipped with security lock.
Power supply terminal block section: 35 mm².
Pedestal dimensions: 600x840x520 mm (LxHxD).

Empty



GW 68 715

Empty pedestals with single-sided take-off QMC 125 B - IP55

Code	Sides with blank door	Side A standard	Side B standard	Possible configuration	Pack Carton
Colour: Light blue					
GW 68 715 A	A-B	Empty	Empty	1 enclosure	1
Colour: White					
GW 68 715 W	A-B	Empty	Empty	1 enclosure	1

ACCESSORIES SUPPLIED: 2 supports for flexible conduit GW68762; junction box for housing power supply terminal block.
CHARACTERISTICS: blank retractable doors; 14-module enclosure with transparent door (not supplied). Pre-arrangement for lighting kit 11W 230V (2 ordinary and 1 emergency) and water kit with 2 or 4 lockable 1/2" water taps, available as accessories.
Single-sided take-off with cable guide and cable fastener devices only on side A.
Pedestal dimensions: 600x840x520 mm (LxHxD).

HIGH CAPACITY PEDESTAL IN INSULATED MATERIAL

Wired



GW 68 833

Wired pedestals with double-sided take-off QMC 200 B equipped with horizontal interlocked socket-outlets - IP44

Code	Socket-outlet 2P+E 16A	Pack Carton
Colour: Light blue		
GW 68 831 A	4 (2 for side)	1
GW 68 832 A	6 (3 for side)	1
GW 68 833 A	8 (4 for side)	1
Colour: White		
GW 68 831 W	4 (2 for side)	1
GW 68 832 W	6 (3 for side)	1
GW 68 833 W	8 (4 for side)	1

PROTECTIONS:
GW68831A/W: board In: 16 A; Main switch disconnector 4P 32A;
4 RCBO - MDC Range 2P 230 V 10 A C 6 kA 0.03 A - AC Type for the four 2P+E 16 A 230 V socket-outlets.
GW68832A/W: board In: 16 A; Main switch disconnector 4P 32A;
6 RCBO - MDC Range 2P 230 V 10 A C 6 kA 0.03 A - AC Type for the six 2P+E 16 A 230 V socket-outlets.
GW68833A/W: board In: 24 A; Main switch disconnector 4P 32A;
8 RCBO - MDC Range 2P 230 V 10 A C 6 kA 0.03 A - AC Type for the eight 2P+E 16 A 230 V socket-outlets.
ACCESSORIES SUPPLIED: 2 plexiglass kits for lateral protection.
CHARACTERISTICS: sides A and B: user socket-outlets, enclosure complete with modular protections equipped with security lock, cable guide with cable fastener devices, blank retractable door. Pre-arrangement for lighting kit 11W 230V (2 ordinary and 1 emergency) and water kit with 2 or 4 padlockable 1/2" ball valves, available as accessories.
Power supply terminal block section: GW68831A/W 16mm²; GW68832A/W, and GW68833A/W 35mm².
Pedestal dimensions: 600x1540x600 mm (LxHxD).

Wired with electronic system - high-current systems



GW 68 867 A

QMC 200 E wired pedestals with single-face take-off for prepaid, centralised electronic management system with direct 250A coupling in terminal block - IP55

Code	Type of connection	Pack Carton
Colour: Light blue		
GW 68 867 A	250A direct coupling on terminal block	1
Colour: White		
GW 68 867 W	250A direct coupling on terminal block	1

PROTECTIONS: board In: 200 A; 1 miniature circuit breaker with earthing residual current relay with separate toroid MTX 4P 400 V 250 A type N 36 kA.
ACCESSORIES SUPPLIED: n. 2 lockable 1/2" water taps; 2 fluorescent lighting lamps 11 W 230 V, 2 supports for flexible conduit GW68762.
CHARACTERISTICS: stainless steel cable fastener devices; board in stainless steel, can be equipped with security lock for access to the modular devices.
Connection to the power supply network and power take-off via two terminal blocks 185 mm² 4P.
NOTES: for technical-commercial information, please contact your local sales representative or GSS (035 946 111).
Pedestal dimensions: 600x1540x600 mm (LxHxD).



GW 68 868 W

Wired terminals with single-face take-off for centralised, prepaid, electronic management system QMC200 E equipped with high-current socket-outlets 250A - IP55

Code	Type of connection	Pack Carton
Colour: Light blue		
GW 68 868 A	Interlocked socket-outlets 250A	1
Colour: White		
GW 68 868 W	Interlocked socket-outlets 250A	1

PROTECTIONS: board In: 200 A; 1 MTX 4 pole 250 A switch type N 36 kA with earthing residual current relay with separate toroid.
ACCESSORIES SUPPLIED: 2 lockable 1/2" water taps; 2 fluorescent lighting lamps 11 W 230 V; 2 supports for flexible conduit GW68762;
CHARACTERISTICS: cable clamp devices in stainless steel, can be equipped with security lock for access to the modular devices.
NOTES: for technical-commercial information, please contact your local sales representative or GSS (035 946 111). Casing dimensions (LxHxD): 600x1540x600 mm.

Empty



GW 68 717

Empty pedestal with double-face take-off QMC 200 B - IP55

Code	Sides with blank door	Side A standard	Side B standard	Possible configuration	Pack Carton
Colour: Light blue					
GW 68 717 A	A-B	Empty	Empty	2 enclosures or 2 panels	1
Colour: White					
GW 68 717 W	A-B	Empty	Empty	2 enclosures or 2 panels	1

ACCESSORIES SUPPLIED: 2 plexiglass kits for lateral protection; junction box for housing power supply terminal block.
CHARACTERISTICS: 2 blank retractable doors; 14+14 module enclosure with transparent door (not supplied).
Pre-arrangement for lighting kit 11W 230V (2 ordinary and 1 emergency) and water kit with 2 or 4 lockable spherical taps of 1/2", available as accessories.
Double-face take-off with cable guide and cable fastener devices on sides A and B.
Pedestal dimensions: 600x1540x600 mm (LxHxD).

Complementary items for prepaid and centralised electronic system



GW 68 991

Transponder key programming kit (prepaid / centralised system)

Code	Description	Pack Carton
GW 68 991	Programming console and s/w for PC with USB key	1

NOTES: to be used with terminal boards with electronic management system.
For technical-commercial information, please contact your local sales representative or GSS (035 946 111).



GW 68 992

Transponder key (prepaid / centralised system)

Code	Description	N. Keys	Pack Carton
GW 68 992	Transponder key to encode	1	1/10

NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or GSS (035 946 111).

RS485/USB insulated converter with terminal block

Code	Description	Pack Carton
GW 68 994	USB/RS485 converter	1

NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or GSS (035 946 111).
The converter RS485/USB can manage up to 250 pedestals for line. In case of more lines is necessary to use more converters GW68994.
For the use of more lines please verify that the PC has more USB doors availables. Use an Hub for have other USB.



GW 68 994

Kit for centralised system

Code	Description	Pack Carton
GW 68 995	Management software with USB key and converter	1

COMPOSITION:
1 USB key for PC;
1 USB-RS485 converter;
1 Sw for management.
NOTES: to be used with terminal boards with electronic management system and with access control GW68998.
For technical-commercial information, please contact your local sales representative or GSS.
General note for centralised system: for the wiring of the pedestals, in a centralised system, is necessary to use an RS485 Bus cable.
The cable must be an armed and twisted with a couple of wires 0.22mm² and 120Ohm impedance of the cable.
Some cables suitable for centralised system: bELDEN P/N 9841, ITC/CDT 14S7Y and CEAM CPR 6003.



GW 68 995

COMPLEMENTARY ITEMS FOR STANDARD AND HIGH CAPACITY PEDESTALS

Panels

Flanged panels prearranged for assembly of socket-outlets - Grey RAL 7035

Code	No. IB socket-outlets houseable	No of IEC 309 socket-outlets that can be housed	Pack Carton
GW 68 731 W	3 IB Vert. 16-32A IP67	-	1/2
GW 68 732 W	4 IB Horiz. 16/32 A IP44	-	1/2
GW 68 733 W	3 COMBIBLOC 16-32A IP44/55	2 IEC 309 16A 2P+E IP44/67	1/2
GW 68 734 W	-	6 IEC 309 16-32A IP44/67	1/2
GW 68 735 W	2 IB Vert. 63 A IP67	-	1/2
GW 68 736 W	-	1 IEC 309 125A IP67	1/2

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: dimensions LxHxD: 328x285x21, GW68736W: 328x285x110 mm.
NOTES: GW68736W compatible only with standard, 125B type terminals.



GW 68 731 W

Blank panel

Code	Description	Pack Carton
Colour: Light blue		
GW 68 737 A	Blank panel	1/2
Colour: White		
GW 68 737 W	Blank panel	1/2

ACCESSORIES SUPPLIED: fixing screws.
CHARACTERISTICS: dimensions LxHxD: 328x285x43mm.



GW 68 737 W



GW 68 741 W

Enclosure panels with transparent door

Code	Colour	Pack Carton
GW 68 741 A	Light blue	1/2
GW 68 741 W	White	1/2

ACCESSORIES SUPPLIED: 14-module rail EN 50022, panel fixing screws.
CHARACTERISTICS: dimensions LxHxD: 328x285x43mm; transparent door that can be equipped with security lock GW68758.

Flush-mounting socket-outlets with clean contact - 125 A - IP67



GW 68 785

Low voltage screw wiring 10° angled flush-mounting interlocked socket-outlets 125A

Code	No. of poles	Rated voltage	Colour	Frequency	Reference h	Flange dimensions (mm)	Pack Carton
GW 68 785	3P+E	380 - 415 V		50/60 Hz	6	114x114	1
GW 68 786	3P+N+E	380 - 415 V		50/60 Hz	6	114x114	1

CHARACTERISTICS: the socket-outlets are equipped with a NO contact (mechanically activated by the plug pilot) to allow the creation of the electric interlock circuit. nickel-plated contacts.

Service complementary items



GW 68 766

Terminal blocks for power supply

Code	Terminal blocks	For cables	Terminal type	Rail type	Pack Carton
GW 68 765	3P+N+E	Up to 16 mm²	Modular	EN 50022	1
GW 68 766	3P+N+E	Up to 35 mm²	With eyelet	EN 50035	1
GW 68 767	3P+N+E	Up to 70 mm²	With eyelet	EN 50035	1
GW 68 768	3P+N+E	Up to 120 mm²	With eyelet	EN 50035	1
GW 68 769	3P+N+E	Up to 185 mm²	With eyelet	EN 50035	1

CHARACTERISTICS: they permit making supply systems with terminals in series, with the enter-exit type of connection, for power cables up to 185 mm².
All codes include a 6 mm² 2P+E terminal block for the lighting circuit supply.



GW 68 753

Water kit with lockable taps

Code	Input	Output	Characteristics	Pack Carton
GW 68 753	N. 1 valve 1/2"	N. 4 taps 1/2"	-	1
GW 68 763	N. 1 valve 1/2"	N. 2 taps 1/2"	-	1
GW 68 764	N. 1 valve 1/2"	N. 2 taps 1/2"	With meter	1

ACCESSORIES SUPPLIED: adjustment fittings and nuts for pedestals.
CHARACTERISTICS: GW68764 with 2 meters of diameter 70mm, capacity 1.5m³/h.

Lighting kit for standard and high capacity pedestal

Code	Lamp	Lamp power	Voltage	Lamp holder	Dimensions LxH (mm)	Pack Carton
Lighting: Ordinary						
GW 68 751	FSD	11 W	230 V - 50 Hz	G23	371x74	1/4
Lighting: Emergency						
GW 68 752	FSD	11 W	230 V - 50 / 60 Hz	2G7	371x74	1



GW 68 751

ACCESSORIES SUPPLIED: protection grille, fixing screws, lamp and supply cable.
CHARACTERISTICS: GW68752 permanent emergency lighting kit, equipped with double supply circuit for switching the lamp on and off keeps the Ni/Cd storage batteries charged.

Compressed air kit

Code	Maximum operating pressure	Input	Output	Pack Carton
GW 68 770	6 bar	N. 1 valve 1/2"	1 quick connection valve, female 3/8"	1



GW 68 770

ACCESSORIES SUPPLIED: adjustment fittings and nuts for pedestals.

Fixing plate for standard and high capacity pedestal

Code	Description	Application	Material	Pack Carton
GW 68 761	Plate for fixing	On concrete	Stainless steel	1



GW 68 761

ACCESSORIES SUPPLIED: check nuts and non-skid washer.
CHARACTERISTICS: fastening to the terminal is achieved using the threaded pins M8 soldered to the plate.

Security lock with handle

Code	Description	N. Keys	Pack Carton
GW 68 758	Security lock with key	2	1/5



GW 68 758

CHARACTERISTICS: all keys have a standardised code; can be mounted on the blank doors of the terminals and on the door of the enclosure panels.

68 Q-MC



GW 68 762 A

Support for flexible tube / extension

Code	Description	Pack Carton
Colour: Light blue		
GW 68 762 A	No.1 supports flexible tube	1/2
Colour: White		
GW 68 762 W	No.1 supports flexible tube	1/2

ACCESSORIES SUPPLIED: fixing screws.



GW 68 795

Self-adhesive protection kit

Code	Description	Pack Carton
GW 68 795	White support with transparent protection	1/10



68 Q-MC



Scan the QR Code and find out all the technical informations.

A WORLD OF APPLICATIONS



The 68 Q-MC terminals represent the ideal solution for the distribution of energy, water, data signals and services, perfect for marine environments, campsites and urban areas. Thanks to these devices, the customer can offer users high quality and comfortable services, integrating perfectly with the elegance of the surrounding environment.

SIMPLE AND INTELLIGENT MANAGEMENT



The electronically managed terminals allow real-time recording and monitoring of consumption. The user interface display and credit management transponder key reader are housed in the head.

ACCESS CONTROL



The access control can be integrated in the system with 68 Q-MC terminal boards with electronic management in order to allow the access of people in determined areas, or to enable the use of specific services.

Items
while stocks last

ENERGY - Items while stocks last

90 RCD RANGE

IDP - AC Type instantaneous



GW 95 604

Residual current circuit breakers

Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 4P							
GW 95 604	125 A	500 mA	400 V	Yes	No	4	1

IDP - A Type istantaneous



GW 95 606

Residual current circuit breakers

Code	Rated current	Idn	Rated voltage	Auxiliaries compatibility	ReStart compatibility	No. of modules EN 50022	Pack Carton
No. of poles: 4P							
GW 95 606	125 A	30 mA	400 V	Yes	No	4	1
GW 95 609	125 A	500 mA	400 V	Yes	No	4	1

BDHP - AC type (instantaneous)



GW 95 406

Add-on residual current devices



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 406	30 mA	125 A	230 V	4	1/2

BDHP - A type (instantaneous)



GW 95 436

Add-on residual current devices



Code	Idn	Rated current	Rated voltage	No. of modules EN 50022	Pack Carton
No. of poles: 2P					
GW 95 436	30 mA	125 A	230 V	4	1/2

Time switches



GW 96 832

Analogue time switches

Code	Type	Type of contacts	Rated voltage (V)	Charge reserve	No. of modules EN 50022	Pack Carton
GW 96 832	Weekly	1 Changeover	230 ac - 110 dc	150 h	3	1/4

APPLICATIONS: command and management of circuits according to pre-established daily or weekly programming; particularly useful where it is necessary to time the functions and optimise the level of comfort (ventilation, lighting, heating).
NOTE: minimum adjustment of the time switch: 30 minutes (daily), 3 hours (weekly).

Motor protection switches



GW 96 758

Motor protection switches

Code	Operating current	Rated voltage (V)	No. of modules EN 50022	Pack Carton
No. of poles: 3P				
GW 96 751	0.1 - 0.16 A	230/400 ac	3	1/4
GW 96 752	0.16 - 0.25 A	230/400 ac	3	1/4
GW 96 753	0.25 - 0.4 A	230/400 ac	3	1/4
GW 96 754	0.4 - 0.63 A	230/400 ac	3	1/4
GW 96 755	0.63 - 1 A	230/400 ac	3	1/4
GW 96 756	1 - 1.6 A	230/400 ac	3	1/4
GW 96 757	1.6 - 2.5 A	230/400 ac	3	1/4
GW 96 758	2.5 - 4 A	230/400 ac	3	1/4
GW 96 759	4 - 6.3 A	230/400 ac	3	1/4
GW 96 760	6.3 - 10 A	230/400 ac	3	1/4
GW 96 761	10 - 16 A	230/400 ac	3	1/4
GW 96 762	16 - 25 A	230/400 ac	3	1/4
GW 96 763	25 - 40 A	230/400 ac	3	1/4

APPLICATIONS: protection of electric motors both in single-phase and 3-phase distribution. Using an adjustment screw, it is possible to set the thermal tripping threshold within an adjustable value range with a ratio of 1:1.6.



GW 96 765

Auxiliary contacts for motor protection switches

Code	Contacts Description	No. of contacts	Type of contacts	No. of modules EN 50022	Pack Carton
GW 96 764	Position	2	1 NO + 1 NC	0.5	1/12
GW 96 765	Fault/position indicator	2	CHANGE-OVER	0.5	1/12



GW 96 767

Shunt trip release for motor protection switches

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 767	110-415 ac	1	1/6

ENERGY - Items while stocks last



GW 96 769

Under voltage release for motor protection switches

Code	Rated voltage (V)	No. of modules EN 50022	Pack Carton
GW 96 769	230 ac	1	1/6
GW 96 770	400 ac	1	1/6



GW 96 771

Surface-mounting box IP54 for motor protection switches

Code	Description	Pack Carton
GW 96 771	Box with rotary manoeuvre	1

90 PV - PREWIRED STRING BOARDS

Prewired string boards



GW D9 903

Prewired string boards

Code	No. of strings	Rated current	No. of board modules	Pack Carton
String voltage: 600 V dc				
GW D9 902	3	25 A	2x12	1
GW D9 903	4	50 A	2x12	1
String voltage: 1000 V dc				
GW D9 907	3	32 A	2x12	1
GW D9 908	4	32 A	2x12	1

ACCESSORIES SUPPLIED: cable glands as spare parts and equipotential terminal blocks.
DC fuses not included. Refer to the fuse code list.

CVX 160 I / 160 E RANGE

Front panels



GW 47 177

Front panels for measuring instruments and three-way switches

Code	Dimensions LxH (mm)	3-way switch no. x hole Ø	Instruments N. x dimensions	Pack Carton
Modules: 24				
GW 47 177	600x200	1 Ø9.5 mm	4 96x96 mm	1/10

ACCESSORIES SUPPLIED: pair of hinges.
APPLICATIONS: installation of ammeters, voltmeters, voltage/current 3 way switches and distribution board RCCB relay.
CHARACTERISTICS: quick coupling front panel, in Grey RAL 7035 insulating material, with ergonomic Blue RAL 5003 socket; panels prepared for rotation hinges (included).

QDX 630 L RANGE - MODULAR DISTRIBUTION BOARDS UP TO 630A - IP43

Floor-mounting distribution boards



GW D3 041

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 041	600x200	650x230	1
GW D3 042	600x300	650x320	1
GW D3 043	850x200	850x230	1
GW D3 044	850x300	850x320	1

ACCESSORIES SUPPLIED: no. 2 wall mounting brackets. Inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height.

Doors



GW D3 021

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 021	600x1000	1
GW D3 022	600x1200	1
GW D3 023	850x1000	1
GW D3 024	850x1200	1
GW D3 068	600x1600	1
GW D3 069	600x1800	1
GW D3 070	600x2000	1
GW D3 071	850x1600	1
GW D3 072	850x1800	1
GW D3 073	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Smoked tempered glass.




GW D3 025

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 025	600x1000	1
GW D3 026	600x1200	1
GW D3 027	850x1000	1
GW D3 028	850x1200	1
GW D3 074	600x1600	1
GW D3 075	600x1800	1
GW D3 076	600x2000	1
GW D3 077	850x1600	1
GW D3 078	850x1800	1
GW D3 079	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

External compartment



GW D3 045

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 045	400x200	400x230	1
GW D3 046	400x300	400x320	1

COMPONENTS: 3 crosspieces for attaching cables. 4 wall attachment brackets for GWD3003 and GWD3006; 2 wall attachment brackets for GWD3045 and GWD3046.
Inspectable base for GWD3045 and GWD3046, supplied loose inside the package.
NOTES: Base height = 100 mm.
Associating the external compartment with the structure can be carried out using the side attachment kit, to be ordered separately.

ENERGY - Items while stocks last



GW D3 082

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 029	300x1000	1
GW D3 030	300x1200	1
GW D3 080	400x1600	1
GW D3 081	400x1800	1
GW D3 082	400x2000	1

ACCESSORIES SUPPLIED: triangular insert key for opening the external compartment door.
CHARACTERISTICS: reversible door opening (right/left).

Accessories




GW D3 316

DIN rail mounting tool

Code	Suitable for	Pack Carton
GW D3 316	Wall and floor boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.



GW D3 401

Additional plinths

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 401	400x200	1
GW D3 402	600x200	1
GW D3 403	850x200	1
GW D3 404	400x300	1
GW D3 405	600x300	1
GW D3 406	850x300	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board.

Spare parts



GW D3 432

Spare part lock

Code	Suitable for	Pack Carton
GW D3 431	External compartment door	1
GW D3 432	Glass door / blind door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 440

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 440	Triangular	Internal / external compartment	1

QDX 630 H RANGE - MONOBLOC AND MODULAR DISTRIBUTION BOARDS UP TO 630A - IP55

Wall-mounting distribution boards

Glass doors



GW D3 113

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 113	600x1000	1
GW D3 114	600x1200	1
GW D3 115	850x1000	1
GW D3 116	850x1200	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Smoked tempered glass.

Blind doors



GW D3 117

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 117	600x1000	1
GW D3 118	600x1200	1
GW D3 119	850x1000	1
GW D3 120	850x1200	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

Floor mounting distribution boards - Single board

Base and headboard



GW D3 131

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 131	600x250	650x250	1
GW D3 132	600x400	650x400	1
GW D3 139	850x250	850x250	1
GW D3 140	850x400	850x400	1

ACCESSORIES SUPPLIED: no. 2 wall mounting brackets. Inspectable plinth (supplied loose) inside the package.
NOTES:H=100 mm plinth height.

Pair of side panels



GW D3 178

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 178	1600x250	1
GW D3 179	1600x400	1
GW D3 180	1800x250	1
GW D3 181	1800x400	1
GW D3 183	2000x250	1
GW D3 184	2000x400	1

ENERGY - Items while stocks last



GW D3 218

Pair of ventilated side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 218	1600x400	1
GW D3 219	1800x400	1
GW D3 220	2000x400	1

NOTES: In the case of installation of aerated side panels, the enclosure protection rating is IP30. Each side panel has 2 surfaces with slits (one lower and one upper) each 58 cm² in size.




GW D3 187

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 187	600x1600	1
GW D3 188	600x1800	1
GW D3 189	600x2000	1
GW D3 193	850x1600	1
GW D3 194	850x1800	1
GW D3 195	850x2000	1

Floor-mounting distribution boards with side compartment



GW D3 135

Bases and headboard

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 135	(600+300)x250	945x250	1
GW D3 136	(600+300)x400	945x400	1

CHARACTERISTICS: Structures are equipped with an associated side compartment (300 mm wide) for the cables, terminal block or bar system.
COMPONENTS: 2 wall mounting brackets and 4 crosspieces for attaching cables.
Inspectable base supplied loose inside the package.
NOTES: Base height = 100 mm.



GW D3 190

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 190	(600+300)x1600	1
GW D3 191	(600+300)x1800	1
GW D3 192	(600+300)x2000	1



GW D3 214

Blind doors for side compartment

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 214	(600+300)x1600	1
GW D3 215	(600+300)x1800	1
GW D3 216	(600+300)x2000	1

ACCESSORIES SUPPLIED: triangular insert key for opening side compartment door.

Doors

Glass doors



GW D3 199

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 199	600x1600	1
GW D3 200	600x1800	1
GW D3 201	600x2000	1
GW D3 202	850x1600	1
GW D3 203	850x1800	1
GW D3 204	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Smoked tempered glass.

Blind doors




GW D3 205

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 205	600x1600	1
GW D3 206	600x1800	1
GW D3 207	600x2000	1
GW D3 208	850x1600	1
GW D3 209	850x1800	1
GW D3 210	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

External compartment

Bases and headboards



GW D3 143

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 143	400x250	400x250	1
GW D3 144	400x400	400x400	1

COMPONENTS: 2 wall mounting brackets.
Inspectable base supplied loose inside the package.
NOTES: Base height = 100 mm.
Associating the external compartment with the structure can be carried out using the side attachment kit, to be ordered separately.
To secure the cables in the outer compartment, use the pair of GWD3468 crosspieces, to be ordered separately.

Rear panels



GW D3 196

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 196	400x1600	1
GW D3 197	400x1800	1
GW D3 198	400x2000	1

ENERGY - Items while stocks last



GW D3 211

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 211	400x1600	1
GW D3 212	400x1800	1
GW D3 213	400x2000	1

Accessories




GW D3 316

DIN rail mounting tool

Code	Suitable for	Pack Carton
GW D3 316	Wall and floor boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.




GW D3 407

Additional plinths

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 407	400x250	1
GW D3 408	600x250	1
GW D3 409	850x250	1
GW D3 410	(600+300)x250	1
GW D3 411	400x400	1
GW D3 412	600x400	1
GW D3 413	850x400	1
GW D3 414	(600+300)x400	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board.

Spare parts



GW D3 434

Spare part locks for wall-mounting distribution boards

Code	Suitable to	Pack Carton
GW D3 434	Glass door / blind door	1
GW D3 435	Side compartment door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 437

Spare part locks for floor-mounting distribution boards

Code	Suitable to	Pack Carton
GW D3 437	External compartment door	1
GW D3 438	Glass door / blind door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 440

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 440	Triangular	Side / external compartment	1



GW D3 456


Inserts for screws

Code	Suitable for	Pack Carton
GW D3 456	Side panels	1

NOTES: Not suitable for wall-mounting distribution boards.

QDX 1600 H - STRUCTURES - DEGREE OF PROTECTION WITH DOOR IP55

Floor-mounting distributon boards - Single board



GW D3 133

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 133	600x600	650x625	1
GW D3 134	600x800	650x800	1
GW D3 141	850x600	850x625	1
GW D3 142	850x800	850x800	1

ACCESSORIES: inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height.

ENERGY - Items while stocks last



GW D3 182

Pair of side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 182	1800x600	1
GW D3 185	2000x600	1
GW D3 186	2000x800	1



GW D3 222

Pair of ventilated side panels

Code	Functional dim. HxD (mm)	Pack Carton
GW D3 221	1800x600	1
GW D3 222	2000x600	1
GW D3 223	2000x800	1

NOTES: In the case of installation of aerated side panels, the enclosure protection rating is IP30.
Each side panel has 2 surfaces with slits (one lower and one upper) each 58 cm² in size.



GW D3 188

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 188	600x1800	1
GW D3 189	600x2000	1
GW D3 194	850x1800	1
GW D3 195	850x2000	1

Floor-mounting distribution boards with side compartment



GW D3 137

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 137	(600+300)x600	945x625	1
GW D3 138	(600+300)x800	945x800	1



GW D3 191

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 191	(600+300)x1800	1
GW D3 192	(600+300)x2000	1



GW D3 215

Blind doors for side compartment

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 215	(600+300)x1800	1
GW D3 216	(600+300)x2000	1

Doors




GW D3 206

Glass doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 206	600x1800	1
GW D3 207	600x2000	1
GW D3 209	850x1800	1
GW D3 210	850x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).
Smoked tempered glass.

External compartment



GW D3 145

Bases and headboards

Code	Functional dim. LxD (mm)	External dim. LxD (mm)	Pack Carton
GW D3 145	400x600	400x625	1
GW D3 146	400x800	400x850	1

ACCESSORIES SUPPLIED : to fix the cables in the external compartment, use the pair of crosspieces GWD3462 to be ordered separately. Inspectable plinth (supplied loose) inside the package.
NOTES: H=100 mm plinth height. The external compartment can be put together with the structure by using the special side kit to be ordered separately.



GW D3 197

Rear panels

Code	Functional dim. LxH (mm)	Pack Carton
GW D3 197	400x1800	1
GW D3 198	400x2000	1

ENERGY - Items while stocks last



GW D3 212

Blind doors

Code	Suitable for structures LxH (mm)	Pack Carton
GW D3 212	400x1800	1
GW D3 213	400x2000	1

ACCESSORIES SUPPLIED: rod-mechanism lock door, equipped with rotary handle with security lock and Yale type key.
CHARACTERISTICS: possibility to assemble the door with reversible opening (right/left).

Accessories




GW D3 316

DIN rail mounting tool

Code	Suitable for	Pack Carton
GW D3 316	Floor-mounting distribution boards	1

CHARACTERISTICS: tool required for mounting and disassembling the double EN 50022 (DIN 35) rail on the brackets.



GW D3 415

Additional plinths

Code	Suitable for structures LxD (mm)	Pack Carton
GW D3 415	400x600	1
GW D3 416	600x600	1
GW D3 417	850x600	1
GW D3 418	(600+300)x600	1
GW D3 419	400x800	1
GW D3 420	600x800	1
GW D3 421	850x800	1
GW D3 422	(600+300)x800	1

CHARACTERISTICS: additional inspectable plinth (H=100 mm) to facilitate cable entry and/or raise the distribution board.

Spare parts



GW D3 437

Spare part lock

Code	Suitable to	Pack Carton
GW D3 437	External compartment door	1
GW D3 438	Glass door / blind door	1

ACCESSORIES SUPPLIED: spare part locks supplied with keys.



GW D3 440

Spare part door keys

Code	Type	Suitable for	Pack Carton
GW D3 440	Triangular	Side / external compartment	1



GW D3 456

Inserts for screws

Code	Suitable for	Pack Carton
GW D3 456	Side panels	1

MOBILITY - Items while stocks last

I-CON CHARGING UNITS FOR ELECTRIC VEHICLES FOR PRIVATE AND/OR PUBLIC ACCESS MODE 3

Charging activation: autostart



GW J3 011 A

I-CON WALLBOX - Stand-alone charging station - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Pack Carton
Type of Socket: type 2 vandal-proof with shutter				
GW J3 001 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 002 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 003 A	1	11 kW	DC residual current protection 6mA	1
GW J3 004 A	1	22 kW	DC residual current protection 6mA	1
Type of Socket: type 2 mobile with cable				
GW J3 011 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 012 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 013 A	1	11 kW	DC residual current protection 6mA	1
GW J3 014 A	1	22 kW	DC residual current protection 6mA	1

CHARACTERISTICS: the use of AUTOSTART charging stations is open to anyone; charging sessions start automatically as soon as the electric vehicle is connected. The charging power can be adjusted using a 3-position side selector switch. The front panel is customisable on request. Floor mounting installation can be provided via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

Charging activation: autostart DLM



GW J3 101 A

I-CON WALLBOX - Stand-alone charging station DLM + BLUETOOTH - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Pack Carton
Type of Socket: type 2 vandal-proof with shutter				
GW J3 101 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 102 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 103 A	1	11 kW	DC residual current protection 6mA	1
Type of Socket: type 2 mobile with cable				
GW J3 111 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 112 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 113 A	1	11 kW	DC residual current protection 6mA	1

CHARACTERISTICS: the use of AUTOSTART charging stations is open to anyone; charging sessions start automatically as soon as the electric vehicle is connected. Bluetooth connection and App for configuration and local control are available, including charging power limitation and management of deferred charging sessions. «Dynamic Load Management» (DLM) is possible for dedicated products by connecting an external meter (codes GWD6812 for single phase and GWD6817 for three phases, sold separately) via MODBUS RS485. Flush-mounting installation is possible using dedicated code GWJ8101; floor mounting installation can be provided via specific GWJ8102 / GWJ8103 codes.
SUPPLIED ACCESSORIES: LED status indicator. Remote enabling via a NA dry contact. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.



GW J3 211 A

I-CON PREMIUM WALL BOX - Stand-alone charging station DLM + BLUETOOTH - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Pack Carton
Type of Socket: type 2 vandal-proof with shutter				
GW J3 201 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 202 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 203 A	1	11 kW	DC residual current protection 6mA	1
Type of Socket: type 2 mobile with cable				
GW J3 211 A	1	4,6 kW	DC residual current protection 6mA	1
GW J3 212 A	1	7,4 kW	DC residual current protection 6mA	1
GW J3 213 A	1	11 kW	DC residual current protection 6mA	1

CHARACTERISTICS:the use of AUTOSTART charging stations is open to anyone; charging sessions start automatically as soon as the electric vehicle is connected. «Dynamic Load Management» (DLM) is possible for dedicated products by connecting an external meter (codes GWD6812 for single phase and GWD6817 for three phases, sold separately) via MODBUS RS485. Customizable front panel on request. Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. Remote enabling via a NA dry contact. Human interface through information display and slider touch to set up configuration paramenters. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.



GW J3 311 A

Wallbox I-CON premium - Stand-alone charging station DLM + bluetooth + BACK-LIGHT - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Back-light report	Pack Carton
Type of Socket: type 2 vandal-proof with shutter					
GW J3 301 A	1	4,6 kW	DC residual current protection 6mA	Yes	1
GW J3 302 A	1	7,4 kW	DC residual current protection 6mA	Yes	1
GW J3 303 A	1	11 kW	DC residual current protection 6mA	Yes	1
Type of Socket: type 2 mobile with cable					
GW J3 311 A	1	4,6 kW	DC residual current protection 6mA	Yes	1
GW J3 312 A	1	7,4 kW	DC residual current protection 6mA	Yes	1
GW J3 313 A	1	11 kW	DC residual current protection 6mA	Yes	1

CHARACTERISTICS:the use of AUTOSTART charging stations is open to anyone; charging sessions start automatically as soon as the electric vehicle is connected. «Dynamic Load Management» (DLM) is possible for dedicated products by connecting an external meter (codes GWD6812 for single phase and GWD6817 for three phases, sold separately) via MODBUS RS485. Back-light function: the front status LED is also replicated on the rear side, reflecting the color on the installation wall. Customizable front panel on request. Floor mounting installation can be provided via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. Remote enable/disable control with a NA voltage-free contact. Human interface through information display and slider touch to set up configuration paramenters. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

Charging activation RFID



GW J3 002 R

I-CON WALL BOX - Stand-alone charging station RFID - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 002 R	1	7,4 kW	DC residual current protection 6mA	Yes	No	1
GW J3 004 R	1	22 kW	DC residual current protection 6mA	Yes	No	1
Type of Socket: type 2 mobile with cable						
GW J3 012 R	1	7,4 kW	DC residual current protection 6mA	Yes	No	1
GW J3 014 R	1	22 kW	DC residual current protection 6mA	Yes	No	1

CHARACTERISTICS: charging stations made to allow RFID card authorization based charging sessions. Parameters settings can be modified via internal SD card, during installation.
Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicator. 1 RFID MASTER card, 2 RFID USER cards.
Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

MOBILITY - Items while stocks last



GW J3 202 R

I-CON PREMIUM WALLBOX - Stand-alone charging station RFID - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 202 R	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 204 R	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
Type of Socket: type 2 mobile with cable						
GW J3 212 R	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 214 R	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1

CHARACTERISTICS: charging stations made to allow RFID card authorization based charging sessions.
Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. 1 RFID MASTER card, 2 RFID USER cards.
Human interface through display to show charging information and slider touch to set up configuration paramenters.
Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

Charging activation: through cloud management software and apps



GW J3 002 L

I-CON WALL BOX - CLOUD OCPP 1.6 charging station - Ethernet - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 002 L	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 004 L	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
Type of Socket: type 2 mobile with cable						
GW J3 012 L	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 014 L	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1

CHARACTERISTICS: charging stations made to offer a fee-based charging service. Each charging station can be managed through a backend platform and an App that allows Drivers to localize and enable the charging point. Dynamic Load Management is available via Site Controller kit GWJ8031 (purchased separately and managed via JOINON Cloud Platform). Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. 1 RFID MASTER card, 2 RFID USER cards. Embedded Ethernet kit. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.
NOTES: for JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately.



GW J3 002 W

I-CON WALL BOX - CLOUD OCPP 1.6 charging station - Ethernet + 4G modem - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 002 W	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 004 W	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
Type of Socket: type 2 mobile with cable						
GW J3 012 W	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 014 W	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1

CHARACTERISTICS: charging stations made to offer a fee-based charging service. Each charging station can be managed through a backend platform and an App that allows Drivers to localize and enable the charging point. Dynamic Load Management (DLM) is available via Site Controller kit GWJ8031 (purchased separately and managed via JOINON Cloud Platform). Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.
SUPPLIED ACCESSORIES: LED status indicators. 1 RFID MASTER card, 2 RFID USER cards. Embedded Ethernet + Modem 4G kit.
Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.
NOTES: For JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately.

I-CON WALL PREMIUM BOX - Charging station CLOUD OCPP 1.6 charging station - Ethernet - IP55



GW J3 202 L

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 202 L	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 204 L	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
Type of Socket: type 2 mobile with cable						
GW J3 212 L	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 214 L	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1

CHARACTERISTICS: charging stations made to offer a fee-based charging service. Each charging station can be managed through a backend platform and an App that allows Drivers to localize and enable the charging point. Dynamic Load Management (DLM) is available via Site Controller kit GWJ8031 (purchased separately and managed via JOINON Cloud Platform). Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.

SUPPLIED ACCESSORIES: LED status indicators. 1 RFID MASTER card, 2 RFID USER cards. Human interface through information display and slider touch to set up configuration paramenters. Integrated Ethernet kit. Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

NOTES: For JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately.

I-CON PREMIUM WALLBOX - Charging station CLOUD OCPP 1.6 charging station - Ethernet + 4G modem - IP55



GW J3 202 W

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	RFID	Energy meter	Pack Carton
Type of Socket: type 2 vandal-proof with shutter						
GW J3 202 W	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 204 W	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
Type of Socket: type 2 mobile with cable						
GW J3 212 W	1	7,4 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1
GW J3 214 W	1	22 kW	DC residual current protection 6mA	Yes	Yes (Type MID)	1

CHARACTERISTICS: charging stations made to offer a fee-based charging service. Each charging station can be managed through a backend platform and an App that allows Drivers to localize and enable the charging point.

Dynamic Load Management is available via Site Controller kit GWJ8031 (purchased separately and managed via JOINON Cloud Platform).

Flush-mounting installation is possible using code GWJ8101; floor mounting installation available via specific codes GWJ8102 / GWJ8103.

SUPPLIED ACCESSORIES: LED status indicator. 1 RFID MASTER card, 2 RFID USER cards. Human interface through display to show charging information and slider touch to set up configuration paramenters. Integrated Ethernet + 4G Modem available.

Specific versions with mobile connector, equipped with 5 meters flat cable and integrated holder, are available.

NOTES: for JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately.

I-CON Accessories


RFID CARD



GW J8 001

Code	Description	Suitable for	Pack Carton
GW J8 001	RFID card to enable the charging process	Wallbox I-CON EVO with RFID reader	1

Communication system kit



GW J8 014

Code	Description	Suitable for	Pack Carton
GW J8 018	Configuration KIT cable	WALLBOX I-CON, WALLBOX I-ON, I-ON	1/5

NOTES: GWJ8018 kit to be used in combination with the configuration software (also available on the website: Gewiss.com) to change the setting of the OCPP parameters necessary for connecting the station with charging platforms and DLM management.

MOBILITY - Items while stocks last



GW D6 812

Load management

Code	Description	Suitable for	Pack Carton
GW D6 812	Energy meter single phase for DLM in home field	I-CON Wallbox with DLM READY FUNCTION	1/6
GW D6 817	Energy meter three-phase for DLM in Home field	I-CON Wallbox with DLM READY FUNCTION	1/6

I-ON CHARGING UNITS FOR ELECTRIC VEHICLES FOR PRIVATE AND/OR PUBLIC ACCESS MODE 3

Charging activation: aUTOSTART



GW J1 003 A

I-ON - Floor-mounting charging station stand-alone - IP55

IP 55 **IK 10**

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
GW J1 001 A	2	7,4 kW + 7,4 kW	Magnetothermic + Diff. Type B	No	No	1
GW J1 002 A	2	11 kW + 11 kW	Magnetothermic + Diff. Type B	No	No	1
GW J1 003 A	2	22 kW + 22 kW	Magnetothermic + Diff. Type B	No	No	1

CHARACTERISTICS: the use of the AUTOSTART station is free for anyone, charging starts automatically as soon as the electric vehicle is connected.
ACCESORIES SUPPLIED: N. 2 TFT Display high visibility, LED to monitor the status of the socket, frontal door completely personalized.



GW J2 103 A

I-ON WALL - Surface-mounting charging station stand-alone - IP55

IP 55 **IK 10**

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
GW J2 101 A	2	7,4 kW + 7,4 kW	No	No	No	1
GW J2 102 A	2	11 kW + 11 kW	No	No	No	1
GW J2 103 A	2	22 kW + 22 kW	No	No	No	1

CHARACTERISTICS: the use of AUTOSTART charging stations is open to anyone; charging sessions start automatically as soon as the electric vehicle is connected.
SUPPLIED ACCESSORIES: N. 2 TFT high visibility displays, LED indicators for monitoring the status of the socket, customisable front door.
NOTES: protection devices have to be ordered sepately and to be installed upstream.

Charging activation: RFID



GW J1 003 R

I-ON - Floor-mounting charging station stand-alone with authorized access - IP55

IP 55 **IK 10**

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
GW J1 001 R	2	7,4 kW + 7,4 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 002 R	2	11 kW + 11 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 003 R	2	22 kW + 22 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1

CHARACTERISTICS: charging stations that are ideal to ensure reserved access to your charging station through one or more RFID cards.
ACCESSORIES SUPPLIED: 2 x high-visibility TFT Displays, LED to monitor socket status, fully customisable front panel, 1 RFID MASTER card to programme the personal RFID cards (2 supplied).
NOTES: Each domestic type F socket is equipped with dedicated Magnetothermic protection (10A) and contactor.



GW J2 103 R

WALLBOX I-ON - Surface-mounting charging station stand-alone with authorized access - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
GW J2 101 R	2	7,4 kW + 7,4 kW	No	Yes (Type MID)	Yes	1
GW J2 102 R	2	11 kW + 11 kW	No	Yes (Type MID)	Yes	1
GW J2 103 R	2	22 kW + 22 kW	No	Yes (Type MID)	Yes	1

CHARACTERISTICS: charging stations made to allow RFID card authorization based charging sessions.
SUPPLIED ACCESSORIES: 2 x high-visibility TFT Displays, LED status indicator for each socket, customisable front panel, 1 x RFID MASTER card to set up USER RFID cards (2 supplied).
NOTES: protection devices must be ordered separately and installed upstream.

Charging activation: through cloud management software and apps



GW J1 003 W

I-ON column - Floor-mounting charging station cloud OCPP 1.6 - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
Communication: Ethernet kit						
GW J1 001 L	2	7,4 kW + 7,4 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 002 L	2	11 kW + 11 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 003 L	2	22 kW + 22 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
Communication: Ethernet Kit and 4G Modem with booster antenna						
GW J1 001 W	2	7,4 kW + 7,4 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 002 W	2	11 kW + 11 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1
GW J1 003 W	2	22 kW + 22 kW	Magnetothermic + Diff. Type B	Yes (Type MID)	Yes	1

CHARACTERISTICS: charging stations made to offer a fee-based charging service. Each charging station can be managed through a backend platform and an App that allows Drivers to localize and enable the charging point.
SUPPLIED ACCESSORIES: 2 x high-visibility TFT Displays, LED indicators for monitoring the socket status, customisable front panel, 1 x RFID MASTER Card + 2 RFID USER cards, 1 x OCPP 1.6 JSON communication kit.
NOTES: for JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately. Each domestic type F socket is equipped with dedicated Magnetothermic protection (10A) and contactor.



GW J2 103 W

I-ON WALL - Surface-mounting charging station cloud OCPP 1.6 - IP55

IP 55 IK 10

Code	N. of sockets Type 2	Charging power	Protection integrated	Power meter	RFID Reader	Pack Carton
Communication: Ethernet kit						
GW J2 101 L	2	7,4 kW + 7,4 kW	No	Yes (Type MID)	Yes	1
GW J2 102 L	2	11 kW + 11 kW	No	Yes (Type MID)	Yes	1
GW J2 103 L	2	22 kW + 22 kW	No	Yes (Type MID)	Yes	1
Communication: Ethernet Kit and 4G Modem with booster antenna						
GW J2 101 W	2	7,4 kW + 7,4 kW	No	Yes (Type MID)	Yes	1
GW J2 102 W	2	11 kW + 11 kW	No	Yes (Type MID)	Yes	1
GW J2 103 W	2	22 kW + 22 kW	No	Yes (Type MID)	Yes	1

CHARACTERISTICS: charging stations that are ideal for offering a charging service to the public for a fee. Each charging station can be managed through a backEnd Monitor and related App, allowing Drivers to simply recharge using their MobileApp.
SUPPLIED ACCESSORIES: 2 x high-visibility TFT Displays, LED indicators for monitoring the socket status, customisable front panel, 1 x RFID MASTER card + 2 RFID USER cards, 1 x OCPP 1.6 JSON communication kit.
NOTES: protection devices must be ordered separately and installed upstream. For JOINON Connected Solutions, Commissioning, Testing, and Post-Sales Service shall be quoted separately.

MOBILITY - Items while stocks last

I-ON Accessories



GW J8 001

RFID CARD

Code	Description	Suitable for	Pack Carton
GW J8 001	RFID card to enable the charging process	I-ON and I-ON WALL with RFID reader	1



GW J8 011

Communication system kit

Code	Description	Suitable for	Pack Carton
GW J8 011	Joinon ethernet kit	I-ON EVO e I-ON EVO WALL	1
GW J8 012	Joinon ethernet kit + modem 4G + antenna	I-ON EVO e I-ON EVO WALL	1
GW J8 015	I-ON Commissioning Kit	I-ON	1/5
GW J8 016	I-ON WALL Commissioning Kit	I-ON WALL	1/5
GW J8 018	Configuration KIT cable	WALLBOX I-CON, WALLBOX I-ON, I-ON	1/5

NOTES: GWJ8011 and GWJ8012 codes make the upgrade of RFID versions to CLOUD versions possible.

GWJ8015 and GWJ8016 codes include DATA SIM, QR CODE for App based charging authoorization and JoinOn instruction stickers.

GWJ8018 kit, in combination with the configuration software (available on the website: Gewiss.com), allows the modification of the OCPP settings for connecting the station with charging platforms and of DLM parameters.

I-FAST CHARGING SYSTEMS FOR ELECTRIC VEHICLES - DC (MODE 4)

Floor-mounted



GW J9 122 W

I-FAST Compact Station - compact floor charging station

Code	No. of sockets	Power max.	Max output current	RFID Reader	Energy meter	Payment terminal	Pack Carton
Connector type: cCS2							
GW J9 122 W	2	60 kW	CCS2: 120A	Yes	Yes, integrated DC Meter	No	1

FEATURES: products equipped with a 4-meter-long charging cable. Possibility of connection via WiFi network, Ethernet cable or 4G network. They are capable of charging up to 2 electric vehicles simultaneously.
EQUIPMENT: products equipped with 7" color graphic TFT display and menu navigation buttons.
NOTES: a version with a 7 meter-long charging cables is available upon request.



I-FAST Station - floor charging station

Code	No. of sockets	Power max.	Max output current	RFID Reader	Energy meter	Payment terminal	Pack Carton
Connector type: cCS2							
GW J9 232 W	2	90 kW	CCS2: 200A (peak at 250A)	Yes	Yes, integrated DC Meter	No	1
GW J9 242 W	2	120 kW	CCS2: 200A (peak at 250A)	Yes	Yes, integrated DC Meter	No	1
GW J9 252 W	2	150 kW	CCS2: 200A (peak at 250A)	Yes	Yes, integrated DC Meter	No	1
GW J9 262 W	2	180 kW	CCS2: 200A (peak at 250A)	Yes	Yes, integrated DC Meter	No	1

FEATURES: products equipped with a 4,5 m long charging cable. Possibility of connection via WiFi network, Ethernet cable or 4G network. They are capable of charging up to 2 electric vehicles simultaneously. The 90 kW, 120 kW and 150 kW stations can be increased in terms of maximum power with the addition of the 30 kW power modules (GWJ9902), to reach a maximum of 180 kW.EQUIPMENT: products equipped with 7" color graphic TFT display and menu navigation buttons.
NOTES: a 7 m long charging cable version is available upon request. CCS2 connectors with a maximum output current of 300 A (peak at 400 A) can also be requested for 150 kW and 180 kW versions.

Product icon key







INSTALLATION

 2P+E (200 - 250V) socket IEC 309 standard	 3P+E (380 - 415V) socket IEC 309 standard	 3P+N+E (380 - 415V) socket IEC 309 standard	 16A 2P+E - 16A dual amperage socket Italian/german standard	 16A 2P+E - 16A socket Italian/german standard
 Socket with safety shields	 Quick wiring spring terminals	 Screw terminals	 Mantle terminals	 Nickel-plated pins
 Nickel-plated contacts	 Distribution board intended for use by ordinary persons (DBO) EN IEC 61439-3 standard	 Distribution board for construction site (ACS) EN IEC 61439-4 standard	 Plug with phase inverter	 Installation temperature
IP 65 Degree of protection against the intrusion of solid particles and access of liquids	IK 09 Degree of protection against external mechanical impacts	GWT 650°C Resistance to glow-wire test	 Resistance to ball pressure test	 Resistance to compression
 Resistance to impact	 Double insulation equipment (Class II)	 Product equipped with solutions for fast and easy installation	 Rated insulation voltage (Ui) according to EN 62208	 UV resistance according to EN 62208
 Material with antibacterial properties	 Halogen Free according to EN 60754-2	 Halogen Free according to EN 50642	 Low Smoke according to EN 61034-2	 Classification of conduits and accessories according to EN 61386-1

MOBILITY

IP 55 Degree of protection against the intrusion of solid particles and access of liquids	IK 11 Degree of protection against external mechanical impacts	GWT 960°C Resistance to glow-wire test	 WiFi connectivity	 OCPP communication protocol
 Dynamic load management (DLM)	 Solar Boost mode	 Free access charging	 Controlled access charging via RFID	 Controlled access charging via App authorization
 Stations connectable in Master/Slave mode	 MID-type energy meter	 Compliant with IEC 61439-7	 UV resistance according to EN 62208	 2P+E (200 - 250V) socket IEC 60309 standard
 3P+E (380 - 415V) socket IEC 60309 standard	 3P+N+E (380 - 415V) socket IEC 60309 standard	 16A 2P+E - 16A socket German standard	 Screw terminals	 Nickel-plated contacts
 TV SAT TV SAT socket	 RJ 45 Telephone/data socket	 LED lighting		

IP 65 Degree of protection against the intrusion of solid particles and access of liquids	HF HALOGEN FREE Halogen Free according to EN 60754-2	CLASS I EN 61140 Product prepared for earthing collar (Class I)	INSTALLATION -25°C min +60°C max Installation temperature

 Electric arc detection device	 Residual Circuit Breaker with Overcurrent protection (RCBO)	 Type of fault residual current	 Type of residual current circuit breaker	 Add-on residual current device for circuit breakers
 Residual Current Circuit Breaker (RCCB)	 Surge protective device waveform	 Photovoltaic applications	 Data line protection	 Switch disconnector
 Isolating switch	 Isolating switch with fuse	 1P on-off switch with indicator lamp	 2P on-off switch with indicator lamp	 2-way switch 1P
 2-way switch 2P	 3-way switch 1P	 3-way switch 2P	 NO+NC switch	 Contactor
 Monostable relay	 Latching relay	 NO push-button	 NC push-button	 NO+NC push-button
 NO+NO double push-button	 NO+NC double push-button	 3-way switch (I 0 II)	 Indicator light	 Illuminated NO push-button
 Illuminated NC push-button	 Illuminated NO+NC push-button	 Bluetooth connectivity	 NFD connectivity	 Busbars installation location

Quick Reference

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
DX 10			
DX 10 016 R	100/6400	6400	344
DX 10 020 R	100/5200	5200	344
DX 10 025 R	75/3300	3300	344
DX 10 032 R	50/1800	1800	344
DX 10 040 R	25/1100	1100	344
DX 10 050 R	25/400	400	344
DX 10 116 R	100/6400	6400	344
DX 10 120 R	100/5200	5200	344
DX 10 125 R	75/3300	3300	344
DX 10 132 R	50/1800	1800	344
DX 10 140 R	25/500	500	344
DX 10 150 R	25/400	400	344
DX 15			
DX 15 016 R	100/6400	6400	345
DX 15 020 R	100/5200	5200	345
DX 15 020 X	100/5200	5200	347
DX 15 025 R	75/3300	3300	345
DX 15 025 X	75/3300	3300	347
DX 15 032 R	50/1800	1800	345
DX 15 032 X	50/1800	1800	347
DX 15 040 R	25/1100	1100	345
DX 15 040 X	25/500	500	347
DX 15 050 R	25/400	400	345
DX 15 063 R	20/240	240	345
DX 15 116 R	100/6400	6400	345
DX 15 120 R	100/5200	5200	345
DX 15 125 R	75/3300	3300	345
DX 15 132 R	50/1800	1800	345
DX 15 140 R	25/500	500	345
DX 15 150 R	25/400	400	345
DX 15 163 R	20/240	240	345
DX 15 216 R	100/2800	2800	345
DX 15 220 R	100/5200	5200	345
DX 15 220 X	100/2400	2400	347
DX 15 225 R	75/3300	3300	345
DX 15 225 X	75/1500	1500	347
DX 15 232 R	50/800	800	345
DX 15 232 X	50/800	800	347
DX 15 240 R	25/500	500	345
DX 15 240 X	25/500	500	347
DX 15 250 R	25/400	400	345
DX 15 316 R	100/2800	2800	345
DX 15 320 R	100/2400	2400	345
DX 15 325 R	75/1500	1500	345
DX 15 332 R	50/800	800	345
DX 15 416 R	100/2800	2800	345
DX 15 420 R	100/5200	5200	345
DX 15 420 X	100/2400	2400	347
DX 15 425 R	75/3300	3300	345
DX 15 425 X	75/1500	1500	347
DX 15 432 R	50/800	800	345
DX 15 432 X	50/800	800	347
DX 15 440 R	25/500	500	345
DX 15 440 X	25/500	500	347
DX 15 450 R	25/400	400	345
DX 15 516 R	100/2800	2800	345
DX 15 520 R	100/2400	2400	345
DX 15 525 R	75/1500	1500	345
DX 15 532 R	50/800	800	345
DX 15 616 R	100/2800	2800	346
DX 15 620 R	100/2400	2400	346
DX 15 620 X	100/2400	2400	348
DX 15 625 R	75/1500	1500	346
DX 15 625 X	75/1500	1500	348
DX 15 632 R	50/800	800	346
DX 15 632 X	50/800	800	348
DX 15 640 R	25/500	500	346
DX 15 640 X	25/500	500	348
DX 15 650 R	25/400	400	346
DX 15 716 R	100/2800	2800	346
DX 15 720 R	100/2400	2400	346
DX 15 725 R	75/1500	1500	346
DX 15 732 R	50/800	800	346
DX 15 816 R	100/2800	2800	346
DX 15 820 R	100/2400	2400	346
DX 15 820 X	100/5200	5200	348
DX 15 825 R	75/1500	1500	346
DX 15 825 X	75/3300	3300	348
DX 15 832 R	50/800	800	346
DX 15 832 X	50/1800	1800	348
DX 15 840 R	25/500	500	346
DX 15 840 X	25/500	500	348
DX 15 850 R	25/400	400	346
DX 15 916 R	100/2800	2800	346
DX 15 920 R	100/2400	2400	346
DX 15 925 R	75/1500	1500	346
DX 15 932 R	50/800	800	346
DX 16			
DX 16 216 R	100/2800	2800	344
DX 16 220 R	100/2400	2400	344
DX 16 220 X	100/2400	2400	347
DX 16 225 R	75/1500	1500	344
DX 16 225 X	75/1500	1500	347
DX 16 232 R	50/800	800	344
DX 16 232 X	50/800	800	347
DX 16 240 R	25/500	500	344
DX 16 240 X	25/500	500	347
DX 16 250 R	25/400	400	344
DX 16 316 R	100/2800	2800	344
DX 16 320 R	100/2400	2400	344
DX 16 325 R	75/1500	1500	344
DX 16 332 R	50/800	800	344
DX 20			
DX 20 016 R	100/6400	6400	349
DX 20 020 R	100/5200	5200	349
DX 20 025 R	75/3300	3300	349
DX 20 032 R	50/1800	1800	349
DX 20 040 R	25/500	500	349
DX 20 050 R	25/400	400	349
DX 20 063 R	20/240	240	349
DX 20 116 R	100/6400	6400	349
DX 20 120 R	100/5200	5200	349
DX 20 125 R	75/3300	3300	349
DX 20 132 R	50/1800	1800	349
DX 20 140 R	25/500	500	349
DX 20 150 R	25/400	400	349
DX 20 163 R	20/240	240	349
DX 20 416 R	100/6400	6400	350
DX 20 420 R	100/5200	5200	350
DX 20 425 R	75/3300	3300	350
DX 20 432 R	50/1800	1800	350
DX 20 440 R	25/500	500	350
DX 20 450 R	25/400	400	350
DX 20 463 R	20/240	240	350
DX 20 516 R	100/6400	6400	350
DX 20 520 R	100/5200	5200	350
DX 20 525 R	75/3300	3300	350
DX 20 532 R	50/1800	1800	350
DX 20 540 R	25/500	500	350
DX 20 550 R	25/400	400	350
DX 20 563 R	20/240	240	350
DX 22			
DX 22 016 R	100/2800	2800	274
DX 22 016 R	100/2800	2800	350
DX 22 020 R	100/2400	2400	274
DX 22 020 R	100/2400	2400	350
DX 22 025 R	75/1500	1500	274
DX 22 025 R	75/1500	1500	350
DX 22 032 R	50/800	800	274
DX 22 032 R	50/800	800	350
DX 22 040 R	25/500	500	274
DX 22 040 R	25/500	500	350
DX 22 050 R	25/400	400	274
DX 22 050 R	25/400	400	350
DX 22 116 R	100/2800	2800	274
DX 22 116 R	100/2800	2800	350
DX 22 120 R	100/2400	2400	274
DX 22 120 R	100/2400	2400	350
DX 22 125 R	75/1500	1500	274
DX 22 125 R	75/1500	1500	350
DX 22 132 R	50/800	800	274
DX 22 132 R	50/800	800	350
DX 22 140 R	25/500	500	274
DX 22 140 R	25/500	500	350
DX 22 150 R	25/400	400	274
DX 22 150 R	25/400	400	350
DX 23			
DX 23 016 R	100/2800	2800	350
DX 23 020 R	100/2400	2400	350
DX 23 025 R	75/1500	1500	350
DX 23 032 R	50/800	800	350
DX 23 040 R	25/500	500	350
DX 23 050 R	25/400	400	350
DX 23 116 R	100/2800	2800	350
DX 23 120 R	100/2400	2400	350
DX 23 125 R	75/1500	1500	350
DX 23 132 R	50/800	800	350
DX 23 140 R	25/500	500	350
DX 23 150 R	25/400	400	350
DX 23 216 R	100/2800	2800	351
DX 23 220 R	100/5200	5200	351

Code	Quantity		Page
	Pack/carton	Pallet	
DX 23 225 R	75/3300	3300	351
DX 23 232 R	50/800	800	351
DX 23 240 R	25/500	500	351
DX 23 250 R	25/400	400	351
DX 23 316 R	100/2800	2800	351
DX 23 320 R	100/5200	5200	351
DX 23 325 R	75/3300	3300	351
DX 23 332 R	50/800	800	351
DX 23 340 R	25/500	500	351
DX 23 350 R	25/400	400	351
DX 24			
DX 24 216 R	100/5600	5600	349
DX 24 220 R	100/4400	4400	349
DX 24 225 R	75/2700	2700	349
DX 24 232 R	50/1600	1600	349
DX 24 240 R	25/500	500	349
DX 24 250 R	25/400	400	349
DX 24 263 R	20/240	240	349
DX 24 816	74/2220	2220	330
DX 24 820	48/1344	1344	330
DX 24 825	48/864	864	330
DX 24 832	38/532	532	330
DX 24 840	14/350	350	330
DX 24 916	75/3150	3150	330
DX 24 920	51/2142	2142	330
DX 24 925	51/1224	1224	330
DX 24 932	30/780	780	330
DX 24 940	21/525	525	330
DX 24 950	15/360	360	330
DX 25			
DX 25 116	111/3330	3330	330
DX 25 116 W	111/3330	3330	331
DX 25 120	57/2223	2223	330
DX 25 120 W	57/2223	2223	331
DX 25 125	57/1311	1311	330
DX 25 125 W	57/1311	1311	331
DX 25 132	30/780	780	330
DX 25 132 W	30/780	780	331
DX 25 140	30/540	540	330
DX 25 140 W	30/540	540	331
DX 25 150	15/360	360	330
DX 25 216	74/2220	2220	333
DX 25 220	48/1344	1344	333
DX 25 225	48/864	864	333
DX 25 232	38/532	532	333
DX 25 316	111/3330	3330	333
DX 25 320	57/2223	2223	333
DX 25 325	57/1311	1311	333
DX 25 332	30/780	780	333
DX 25 340	30/540	540	333
DX 25 350	15/360	360	333
DX 25 363	9/180	180	333
DX 25 716	57/3192	3192	334
DX 25 720	57/2223	2223	334
DX 25 725	57/1311	1311	334
DX 25 732	30/780	780	334
DX 25 740	30/540	540	334
DX 25 750	15/360	360	334
DX 25 763	9/180	180	334
DX 26			
DX 26 216	60/4620	4620	334
DX 26 220	46/3542	3542	334
DX 26 225	48/2640	2640	334
DX 26 232	36/1980	1980	334
DX 26 240	30/1080	1080	334
DX 26 250	18/648	648	334
DX 26 263	12/420	420	334
DX 26 316	87/1827	1827	334
DX 26 320	69/1449	1449	334
DX 26 325	60/840	840	334
DX 26 332	36/504	504	334
DX 26 716 W	87/1827	1827	331
DX 26 720 W	69/1449	1449	331
DX 26 725 W	60/840	840	331
DX 26 732 W	36/504	504	331
DX 27			
DX 27 616	74/2220	2220	332
DX 27 620	48/1344	1344	332
DX 27 625	48/864	864	332
DX 27 632	38/532	532	332
DX 27 640	14/350	350	332
DX 27 650	10/240	240	332
DX 27 663	6/120	120	332
DX 27 716	75/3150	3150	332
DX 27 720	51/2142	2142	332
DX 27 725	51/1224	1224	332
DX 27 732	30/780	780	332
DX 27 740	21/525	525	332
DX 27 750	15/360	360	332
DX 27 763	9/180	180	332
DX 30			
DX 30 008	30/2070	2070	356
DX 30 010	30/1800	1800	356
DX 30 012	30/1800	1800	356
DX 30 014	30/1440	1440	356
DX 30 016	30/1080	1080	356
DX 30 020	30/1080	1080	356
DX 30 022	30/720	720	356
DX 30 025	30/600	600	356
DX 30 028	30/480	480	356
DX 30 032	30/480	480	356
DX 30 035	30/480	480	356
DX 30 040	30/360	360	356
DX 30 050	30/180	180	356
DX 30 060	30/120	120	356
DX 30 108	30/2070	2070	356
DX 30 110	30/1800	1800	356
DX 30 112	30/1800	1800	356
DX 30 114	30/1440	1440	356
DX 30 116	30/1080	1080	356
DX 30 120	30/1080	1080	356
DX 30 122	30/720	720	356
DX 30 125	30/600	600	356
DX 30 128	30/480	480	356
DX 30 132	30/480	480	356
DX 30 135	30/480	480	356
DX 30 140	30/360	360	356
DX 30 150	30/180	180	356
DX 30 160	30/120	120	356
DX 30 812	30/1800	1800	360
DX 30 816	30/1080	1080	360
DX 30 820	30/1080	1080	360
DX 30 825	30/600	600	360
DX 40			
DX 40 016	30/300	18000	335
DX 40 016	30/300	18000	392
DX 40 020	30/450	14400	335
DX 40 020	30/450	14400	392
DX 40 025	20/240	12000	335
DX 40 025	20/240	12000	392
DX 40 032	10/100	5000	335
DX 40 032	10/100	5000	392
DX 40 040	5/25	3000	335
DX 40 040	5/25	3000	392
DX 40 050	15	1800	335
DX 40 050	15	1800	392
DX 40 063	8	400	335
DX 40 063	8	400	392
DX 40 116	30/300	18000	335
DX 40 116	30/300	18000	392
DX 40 120	30/300	9600	335
DX 40 120	30/300	9600	392
DX 40 125	20/100	5400	335
DX 40 125	20/100	5400	392
DX 40 132	10/50	3000	335
DX 40 132	10/50	3000	392
DX 40 140	5/25	1250	335
DX 40 140	5/25	1250	392
DX 40 150	10	640	335
DX 40 150	10	640	392
DX 40 163	1	168	335
DX 40 163	1	168	392
DX 40 216	30/120	6000	335
DX 40 216	30/120	6000	392
DX 40 220	30/120	7200	335
DX 40 220	30/120	7200	392
DX 40 225	20/60	3840	335
DX 40 225	20/60	3840	392
DX 40 232	10/30	1200	335
DX 40 232	10/30	1200	392
DX 40 316	30/180	18000	335
DX 40 316	30/180	18000	392
DX 40 320	30/120	12000	335
DX 40 320	30/120	12000	392
DX 40 325	20/60	3000	335
DX 40 325	20/60	3000	392
DX 40 332	10/40	2000	335
DX 40 332	10/40	2000	392
DX 43			
DX 43 016	10/300	6000	336
DX 43 016	10/300	6000	393

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
DX 43 020	10/240	14400	336
DX 43 020	10/240	14400	393
DX 43 025	5/150	9600	336
DX 43 025	5/150	9600	393
DX 43 032	5/120	6000	336
DX 43 032	5/120	6000	393
DX 43 040	5/90	1800	336
DX 43 040	5/90	1800	393
DX 43 050	3/54	1080	336
DX 43 050	3/54	1080	393
DX 43 116	10/100	6400	336
DX 43 116	10/100	6400	393
DX 43 120	10/80	5120	336
DX 43 120	10/80	5120	393
DX 43 125	5/50	3200	336
DX 43 125	5/50	3200	393
DX 43 132	5/30	1920	336
DX 43 132	5/30	1920	393
DX 43 140	5/15	960	336
DX 43 140	5/15	960	393
DX 43 150	8	512	336
DX 43 150	8	512	393
DX 43 216	10/360	21600	336
DX 43 216	10/360	21600	393
DX 43 220	10/300	18000	336
DX 43 220	10/300	18000	393
DX 43 225	5/180	10800	336
DX 43 225	5/180	10800	393
DX 43 232	5/150	7500	336
DX 43 232	5/150	7500	393
DX 43 240	5/30	3600	336
DX 43 240	5/30	3600	393
DX 43 250	5/15	1800	336
DX 43 250	5/15	1800	393
DX 43 316	10/450	9000	336
DX 43 316	10/450	9000	359
DX 43 316	10/450	9000	393
DX 43 316	10/450	9000	400
DX 43 320	10/300	18000	336
DX 43 320	10/300	18000	359
DX 43 320	10/300	18000	393
DX 43 320	10/300	18000	400
DX 43 325	5/210	12600	336
DX 43 325	5/210	12600	359
DX 43 325	5/210	12600	393
DX 43 325	5/210	12600	400
DX 43 332	5/120	7200	336
DX 43 332	5/120	7200	359
DX 43 332	5/120	7200	393
DX 43 332	5/120	7200	400
DX 43 340	5/25	1250	336
DX 43 340	5/25	1250	359
DX 43 340	5/25	1250	393
DX 43 340	5/25	1250	400
DX 43 350	5/20	800	336
DX 43 350	5/20	800	359
DX 43 350	5/20	800	393
DX 43 350	5/20	800	400
DX 43 416	10/360	7200	336
DX 43 416	10/360	7200	359
DX 43 416	10/360	7200	394
DX 43 416	10/360	7200	400
DX 43 420	10/240	14400	336
DX 43 420	10/240	14400	359
DX 43 420	10/240	14400	394
DX 43 420	10/240	14400	400
DX 43 425	5/150	9000	336
DX 43 425	5/150	9000	359
DX 43 425	5/150	9000	394
DX 43 425	5/150	9000	400
DX 43 432	5/40	4800	336
DX 43 432	5/40	4800	359
DX 43 432	5/40	4800	394
DX 43 432	5/40	4800	400
DX 43 440	5/20	2400	336
DX 43 440	5/20	2400	359
DX 43 440	5/20	2400	394
DX 43 440	5/20	2400	400
DX 43 516	60	2400	337
DX 43 516	60	2400	394
DX 43 520	40	1600	337
DX 43 520	40	1600	394
DX 43 525	20	800	337
DX 43 525	20	800	394
DX 43 532	20	400	337
DX 43 532	20	400	394
DX 43 540	12	216	337
DX 43 540	12	216	394
DX 43 550	9	162	337
DX 43 550	9	162	394
DX 45			
DX 45 003	3/15	1800	339
DX 45 004	5/60	480	339
DX 45 007	5/60	480	339
DX 45 010	1/16	288	339
DX 47			
DX 47 000	50/450	18000	340
DX 47 001	20/60	6600	340
DX 47 212	10/450	4500	340
DX 47 216	10/450	4500	340
DX 47 220	10/390	3900	340
DX 47 503	10/300	6000	340
DX 47 506	10/300	6000	340
DX 47 509	10/300	6000	340
DX 47 616	10/390	7800	340
DX 47 620	10/360	7200	340
DX 47 625	10/300	6000	340
DX 51			
DX 51 120	100/1500	30000	387
DX 51 232	100/800	43200	387
DX 51 263	100/400	24000	387
DX 51 306	200/600	76800	387
DX 51 308	200/600	42000	387
DX 51 316	1/10	900	338
DX 51 316	1/10	900	395
DX 51 320	1/10	800	338
DX 51 320	1/10	800	395
DX 51 325	1/5	500	338
DX 51 325	1/5	500	395
DX 51 416	1/10	900	337
DX 51 416	1/10	900	395
DX 51 420	1/10	500	337
DX 51 420	1/10	500	395
DX 51 425	1/5	500	337
DX 51 425	1/5	500	395
DX 51 432	1/5	400	337
DX 51 432	1/5	400	395
DX 51 440	1	200	337
DX 51 440	1	200	395
DX 51 450	1	200	337
DX 51 450	1	200	395
DX 51 600	1/5	200	338
DX 51 600	1/5	200	395
DX 52			
DX 52 016	50/200	10000	351
DX 52 020	50/300	24000	351
DX 52 025	50/200	16000	351
DX 52 032	25/150	9600	351
DX 52 040	10/40	2000	351
DX 52 050	10/40	2000	351
DX 52 063	25	1250	351
DX 52 116	100/500	55000	351
DX 52 120	100/400	44000	351
DX 52 125	50/250	27500	351
DX 52 132	25/125	13750	351
DX 52 140	25/100	11000	351
DX 52 150	25/75	8250	351
DX 52 163	50	5500	351
DX 52 205	1/10	3600	352
DX 52 210	1/10	360	352
DX 52 215	1/10	360	352
DX 52 220	1/10	320	352
DX 52 225	1/10	360	352
DX 52 299	10/200	20000	352
DX 52 305	1/40	720	352
DX 52 310	1/25	400	352
DX 52 315	1/15	240	352
DX 52 320	1/15	240	352
DX 52 325	1/15	270	352
DX 52 399	10/200	20000	352
DX 54			
DX 54 008	20/180	19800	357
DX 54 008	20/180	19800	396
DX 54 010	20/160	17600	357
DX 54 010	20/160	17600	396
DX 54 012	10/100	11000	357
DX 54 012	10/100	11000	396
DX 54 016	10/150	7500	357
DX 54 016	10/150	7500	396
DX 54 020	10/100	10000	357
DX 54 020	10/100	10000	396
DX 54 022	10/100	5000	357

Code	Quantity		Page
	Pack/carton	Pallet	
DX 54 022	10/100	5000	396
DX 54 025	5/60	3000	357
DX 54 025	5/60	3000	396
DX 54 028	5/40	2000	357
DX 54 028	5/40	2000	396
DX 54 032	5/30	1500	357
DX 54 032	5/30	1500	396
DX 54 040	25	1250	357
DX 54 040	25	1250	396
DX 54 050	15	750	357
DX 54 050	15	750	396
DX 54 108	20/180	19800	357
DX 54 108	20/180	19800	396
DX 54 110	20/160	17600	357
DX 54 110	20/160	17600	396
DX 54 112	10/100	11000	357
DX 54 112	10/100	11000	396
DX 54 116	10/150	7500	357
DX 54 116	10/150	7500	396
DX 54 120	10/100	5000	357
DX 54 120	10/100	5000	396
DX 54 122	10/100	5000	357
DX 54 122	10/100	5000	396
DX 54 125	5/60	3000	357
DX 54 125	5/60	3000	396
DX 54 128	5/40	2000	357
DX 54 128	5/40	2000	396
DX 54 132	5/30	1500	357
DX 54 132	5/30	1500	396
DX 54 140	25	1250	357
DX 54 140	25	1250	396
DX 54 150	15	750	357
DX 54 150	15	750	396
DX 54 208	20/180	11880	357
DX 54 208	20/180	11880	397
DX 54 210	20/160	17600	357
DX 54 210	20/160	17600	397
DX 54 212	10/100	11000	357
DX 54 212	10/100	11000	397
DX 54 214	10/150	7500	357
DX 54 214	10/150	7500	397
DX 54 216	10/150	18000	357
DX 54 216	10/150	18000	397
DX 54 220	10/100	12000	357
DX 54 220	10/100	12000	397
DX 54 222	10/100	5000	357
DX 54 222	10/100	5000	397
DX 54 225	5/60	7200	357
DX 54 225	5/60	7200	397
DX 54 228	5/40	4800	357
DX 54 228	5/40	4800	397
DX 54 232	5/30	3600	357
DX 54 232	5/30	3600	397
DX 54 235	5/30	1500	357
DX 54 235	5/30	1500	397
DX 54 240	25	3000	357
DX 54 240	25	3000	397
DX 54 250	15	1800	357
DX 54 250	15	1800	397
DX 54 308	20/180	19800	357
DX 54 308	20/180	19800	397
DX 54 310	20/160	17600	357
DX 54 310	20/160	17600	397
DX 54 312	10/100	13200	357
DX 54 312	10/100	13200	397
DX 54 314	10/150	7500	357
DX 54 314	10/150	7500	397
DX 54 316	10/150	7500	357
DX 54 316	10/150	7500	397
DX 54 320	10/100	5000	357
DX 54 320	10/100	5000	397
DX 54 322	10/100	3000	357
DX 54 322	10/100	3000	397
DX 54 325	5/60	3000	357
DX 54 325	5/60	3000	397
DX 54 328	5/40	2000	357
DX 54 328	5/40	2000	397
DX 54 332	5/30	1500	357
DX 54 332	5/30	1500	397
DX 54 335	5/30	1500	357
DX 54 335	5/30	1500	397
DX 54 340	25	1250	357
DX 54 340	25	1250	397
DX 54 350	15	750	357
DX 54 350	15	750	397
DX 54 408	20/180	19800	358
DX 54 408	20/180	19800	398
DX 54 410	20/160	17600	358
DX 54 410	20/160	17600	398
DX 54 411	20/160	17600	358
DX 54 411	20/160	17600	398
DX 54 412	10/100	11000	358
DX 54 412	10/100	11000	398
DX 54 413	10/100	11000	358
DX 54 413	10/100	11000	398
DX 54 414	10/150	7500	358
DX 54 414	10/150	7500	398
DX 54 416	10/150	18000	358
DX 54 416	10/150	18000	398
DX 54 417	10/150	6000	358
DX 54 417	10/150	6000	398
DX 54 420	10/100	5000	358
DX 54 420	10/100	5000	398
DX 54 422	10/100	4000	358
DX 54 422	10/100	4000	398
DX 54 425	5/60	3000	358
DX 54 425	5/60	3000	398
DX 54 428	5/40	2000	358
DX 54 428	5/40	2000	398
DX 54 432	5/30	1500	358
DX 54 432	5/30	1500	398
DX 54 435	5/30	1500	358
DX 54 435	5/30	1500	398
DX 54 508	20/180	19800	358
DX 54 508	20/180	19800	398
DX 54 510	20/160	17600	358
DX 54 510	20/160	17600	398
DX 54 511	20/160	17600	358
DX 54 511	20/160	17600	398
DX 54 512	10/100	6600	358
DX 54 512	10/100	6600	398
DX 54 513	10/100	11000	358
DX 54 513	10/100	11000	398
DX 54 514	10/150	7500	358
DX 54 514	10/150	7500	398
DX 54 516	10/150	7500	358
DX 54 516	10/150	7500	398
DX 54 517	10/150	4500	358
DX 54 517	10/150	4500	398
DX 54 520	10/100	5000	358
DX 54 520	10/100	5000	398
DX 54 522	10/100	4000	358
DX 54 522	10/100	4000	398
DX 54 525	5/60	3000	358
DX 54 525	5/60	3000	398
DX 54 528	5/40	2000	358
DX 54 528	5/40	2000	398
DX 54 532	5/30	1500	358
DX 54 532	5/30	1500	398
DX 54 535	5/30	1500	358
DX 54 535	5/30	1500	398

DX 56

Code	Quantity		Page
	Pack/carton	Pallet	
DX 56 008	20/160	17600	358
DX 56 008	20/160	17600	399
DX 56 010	10/170	8500	358
DX 56 010	10/170	8500	399
DX 56 012	10/150	7500	358
DX 56 012	10/150	7500	399
DX 56 014	10/130	6500	358
DX 56 014	10/130	6500	399
DX 56 016	10/110	4400	358
DX 56 016	10/110	4400	399
DX 56 022	10/50	2500	358
DX 56 022	10/50	2500	399
DX 56 025	10/50	2500	358
DX 56 025	10/50	2500	399
DX 56 028	10/40	2000	358
DX 56 028	10/40	2000	399
DX 56 040	15	750	358
DX 56 040	15	750	399
DX 56 050	12	600	358
DX 56 050	12	600	399
DX 56 208	20/160	17600	358
DX 56 208	20/160	17600	399
DX 56 210	10/170	8500	358
DX 56 210	10/170	8500	399
DX 56 212	10/150	7500	358
DX 56 212	10/150	7500	399
DX 56 214	10/130	3900	358
DX 56 214	10/130	3900	399
DX 56 216	10/110	5500	358
DX 56 216	10/110	5500	399
DX 56 222	10/50	2500	358
DX 56 222	10/50	2500	399

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
DX 56 225	10/50	2500	358
DX 56 225	10/50	2500	399
DX 56 228	10/40	2000	358
DX 56 228	10/40	2000	399
DX 56 232	3/18	900	358
DX 56 232	3/18	900	399
DX 56 235	3/18	900	358
DX 56 235	3/18	900	399
DX 56 240	15	750	358
DX 56 240	15	750	399
DX 56 250	12	600	358
DX 56 250	12	600	399
DX 56 408	20/160	17600	359
DX 56 408	20/160	17600	399
DX 56 410	10/170	8500	359
DX 56 410	10/170	8500	399
DX 56 411	10/150	7500	359
DX 56 411	10/150	7500	399
DX 56 412	10/150	7500	359
DX 56 412	10/150	7500	399
DX 56 413	10/150	7500	359
DX 56 413	10/150	7500	399
DX 56 414	10/130	6500	359
DX 56 414	10/130	6500	399
DX 56 415	10/110	5500	359
DX 56 415	10/110	5500	399
DX 56 416	10/110	4400	359
DX 56 416	10/110	4400	399
DX 56 417	10/110	4400	359
DX 56 417	10/110	4400	399
DX 56 422	10/50	2500	359
DX 56 422	10/50	2500	399
DX 56 423	10/50	2500	359
DX 56 423	10/50	2500	399
DX 56 425	10/50	2500	359
DX 56 425	10/50	2500	399
DX 56 428	10/40	2000	359
DX 56 428	10/40	2000	399
DX 56 432	3/18	720	359
DX 56 432	3/18	720	399
DX 56 435	3/18	900	359
DX 56 435	3/18	900	399
DX 56 440	15	750	359
DX 56 440	15	750	399
DX 56 450	12	600	359
DX 56 450	12	600	399

DX 59

Code	Quantity		Page
	Pack/carton	Pallet	
DX 59 230	1/6	108	366
DX 59 231	1/6	96	366
DX 59 240	1/6	300	366
DX 59 241	1/4	48	366
DX 59 242	1/4	162	366
DX 59 401	1/60	60	363
DX 59 402	1/60	60	363
DX 59 410	1/5	240	363
DX 59 411	1/5	350	363
DX 59 430	1/5	280	363
DX 59 431	1/5	120	363
DX 59 440	1/10	1600	363
DX 59 450	1/50	5500	363
DX 59 450	1/50	5500	364
DX 59 451	1/10	1440	363
DX 59 452	1/50	8700	365
DX 59 452	1/50	8700	365
DX 59 453	1/20	2200	365
DX 59 453	1/20	2200	365
DX 59 501	1	45	366
DX 59 502	1	18	366
DX 59 511	1/6	108	366
DX 59 520	1/6	108	366
DX 59 551	1/10	1100	366
DX 59 650	1/50	5500	366
DX 59 701	1/36	36	364
DX 59 702	1/36	36	364
DX 59 710	1/5	140	364
DX 59 711	1/5	100	364
DX 59 730	1/5	140	364
DX 59 731	1/5	100	364
DX 59 740	1/10	500	364
DX 59 751	1/10	3000	364
DX 59 801	1/18	18	365
DX 59 802	1/24	24	365
DX 59 810	1/5	30	365
DX 59 811	1/5	30	365
DX 59 830	1/5	30	365
DX 59 831	1/5	30	365
DX 59 840	1/10	240	365
DX 59 851	1/10	1600	365
DX 59 901	1/8	8	365
DX 59 902	1/8	8	365
DX 59 910	1/5	100	365
DX 59 911	1/5	20	365
DX 59 930	1/5	60	365
DX 59 931	1/5	60	365
DX 59 940	1/10	80	365
DX 59 951	1/10	1600	365

GW 10

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 001	12/96	9216	788
GW 10 001 AB	12/96	9216	971
GW 10 002	12/24	6552	788
GW 10 003	12/24	6720	788
GW 10 004	12/48	7488	788
GW 10 004 AB	12/48	3744	972
GW 10 005	12/24	5904	788
GW 10 006	1/12	2340	788
GW 10 007	12/24	7728	788
GW 10 007 AB	12/24	3744	972
GW 10 021	12/24	8448	788
GW 10 022	6/24	6336	788
GW 10 031	6/24	3744	788
GW 10 031 F	6/24	1152	791
GW 10 032	6/24	1872	788
GW 10 032 F	6/24	1344	791
GW 10 033	6/24	1872	788
GW 10 033 F	6/24	2304	791
GW 10 034	6/24	1872	788
GW 10 034 F	6/24	2304	791
GW 10 035	6/24	1872	788
GW 10 035 F	6/24	1728	791
GW 10 039	1/6	2112	799
GW 10 051	12/96	9216	789
GW 10 051 AB	12/96	4608	972
GW 10 052	12/24	5760	789
GW 10 053	12/24	3744	789
GW 10 054	1/12	2340	789
GW 10 061	6/24	4800	789
GW 10 071	6/24	3744	789
GW 10 071 F	6/24	1344	791
GW 10 072	6/24	1872	789
GW 10 072 F	6/24	1344	791
GW 10 073	6/24	1872	789
GW 10 073 F	6/24	1728	791
GW 10 078 F	6/24	1152	792
GW 10 091	12/48	7488	789
GW 10 091 AB	12/48	3744	972
GW 10 092	12/24	2952	789
GW 10 093	12/24	3312	789
GW 10 101	6/12	3312	789
GW 10 101 F	6/12	1620	791
GW 10 102	6/12	2208	789
GW 10 102 F	6/12	1620	791
GW 10 103	6/12	2208	789
GW 10 103 F	6/12	1620	791
GW 10 121	12/24	5400	789
GW 10 122	12/24	5904	789
GW 10 122 AB	12/24	2952	972
GW 10 123	6/24	1536	789
GW 10 131	12/96	9216	790
GW 10 131 AB	12/96	4608	972
GW 10 132	12/24	6720	790
GW 10 133	12/24	6720	790
GW 10 134	12/24	4416	790
GW 10 135	12/24	4416	790
GW 10 136	1/12	3744	790
GW 10 136 AB	1/12	1872	972
GW 10 137	12/24	3744	790
GW 10 137 AB	12/24	2880	972
GW 10 138	12/24	3240	790
GW 10 139	12/24	3240	790
GW 10 140	12/24	4920	790
GW 10 140 AB	12/24	5904	972
GW 10 141	12/24	5400	790
GW 10 142	12/24	3240	790
GW 10 143	12/24	3240	790
GW 10 144	12/24	3240	790
GW 10 145	1/12	2340	790
GW 10 151	12/24	7728	790
GW 10 152	12/24	3744	790
GW 10 153	12/24	6720	790
GW 10 159 F	6/24	1728	792
GW 10 160 F	6/24	1152	792
GW 10 161	6/24	4800	790
GW 10 162	6/24	2880	790
GW 10 171	6/24	3744	790

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 171 F	6/24	1344	791
GW 10 172	6/24	1872	790
GW 10 172 F	6/24	1344	791
GW 10 173	6/24	3744	790
GW 10 173 F	6/24	1728	791
GW 10 191	6/24	2304	790
GW 10 192	4/16	1152	790
GW 10 194	6/48	1200	797
GW 10 195	10/200	18000	797
GW 10 195 AB	10/200	18000	973
GW 10 196	1/48	3072	797
GW 10 197	4/48	14976	797
GW 10 198	1/48	4608	797
GW 10 199	1/48	2304	797
GW 10 201	12/96	7200	800
GW 10 201 AB	12/96	2400	974
GW 10 203	12/96	7200	800
GW 10 203 AB	12/96	7200	974
GW 10 204	6/48	3600	535
GW 10 204	6/48	3600	800
GW 10 204 AB	6/48	3600	974
GW 10 205	6/48	3600	800
GW 10 208	6/24	1872	800
GW 10 209	4/12	936	800
GW 10 213	12/24	7728	801
GW 10 213	12/24	7728	903
GW 10 213	12/24	7728	937
GW 10 213 AB	12/24	2952	974
GW 10 214	6/12	3444	801
GW 10 214	6/12	3444	903
GW 10 214	6/12	3444	937
GW 10 214 AB	6/12	3444	974
GW 10 223	12/24	2952	801
GW 10 223	12/24	2952	903
GW 10 223	12/24	2952	937
GW 10 223 AB	12/24	1476	974
GW 10 224	6/12	1476	801
GW 10 224	6/12	1476	903
GW 10 224	6/12	1476	937
GW 10 224 AB	6/12	1476	974
GW 10 233	12/24	7728	801
GW 10 233	12/24	7728	835
GW 10 233	12/24	7728	869
GW 10 233	12/24	7728	903
GW 10 233	12/24	7728	937
GW 10 234	6/12	1656	801
GW 10 234	6/12	1656	835
GW 10 234	6/12	1656	869
GW 10 234	6/12	1656	903
GW 10 234	6/12	1656	937
GW 10 241	6/48	3600	801
GW 10 241 AB	6/48	3600	975
GW 10 241 F	6/12	1476	802
GW 10 242	6/48	3600	801
GW 10 246	1/24	2304	803
GW 10 247	6/48	1200	803
GW 10 247 AB	6/48	1200	976
GW 10 247 F	6/12	1476	803
GW 10 248	6/12	1476	803
GW 10 251	6/12	2460	802
GW 10 251	6/12	2460	836
GW 10 251	6/12	2460	870
GW 10 251	6/12	2460	904
GW 10 251	6/12	2460	938
GW 10 251 AB	6/12	2952	975
GW 10 251 F	6/12	1620	802
GW 10 251 F	6/12	1620	836
GW 10 251 F	6/12	1620	870
GW 10 251 F	6/12	1620	904
GW 10 251 F	6/12	1620	938
GW 10 257 F	6/12	1620	803
GW 10 257 F	6/12	1620	837
GW 10 257 F	6/12	1620	871
GW 10 257 F	6/12	1620	905
GW 10 257 F	6/12	1620	939
GW 10 258	6/12	1620	803
GW 10 258	6/12	1620	837
GW 10 258	6/12	1620	871
GW 10 258	6/12	1620	905
GW 10 258	6/12	1620	939
GW 10 260	10/100	19500	804
GW 10 260	10/100	19500	838
GW 10 260	10/100	19500	872
GW 10 260	10/100	19500	906
GW 10 260	10/100	19500	940
GW 10 281	1/24	2304	804
GW 10 281 AB	1/24	3072	976
GW 10 282	1/48	4608	804
GW 10 282 AB	1/48	3072	976
GW 10 286	12/48	3744	805
GW 10 287	12/48	7488	805
GW 10 288	12/48	7488	805
GW 10 291	1/24	2304	804
GW 10 291	1/24	2304	838
GW 10 291	1/24	2304	872
GW 10 291	1/24	2304	906
GW 10 291	1/24	2304	940
GW 10 291 AB	1/24	1536	976
GW 10 296	6/48	3600	805
GW 10 297	6/48	1200	805
GW 10 298	6/48	1200	805
GW 10 299	12/240	5760	806
GW 10 301	6/48	1200	806
GW 10 306	6/48	1200	806
GW 10 307	6/48	1200	806
GW 10 310	10/40	3000	806
GW 10 311	1/6	1170	807
GW 10 312	1/4	800	807
GW 10 321	1/4	352	807
GW 10 322	1/2	246	807
GW 10 331	1/2	312	807
GW 10 331 AB	1/2	156	977
GW 10 341	6/12	3240	802
GW 10 341 AB	6/12	1476	975
GW 10 346	6/48	1200	805
GW 10 351	6/12	1476	802
GW 10 351	6/12	1476	836
GW 10 351	6/12	1476	870
GW 10 351	6/12	1476	904
GW 10 351	6/12	1476	938
GW 10 351 AB	6/12	1476	975
GW 10 361	1/48	4608	807
GW 10 361 AB	1/48	3072	977
GW 10 362	1/24	5400	807
GW 10 363	1/24	3240	807
GW 10 367	1/24	1536	808
GW 10 371	1/48	4608	808
GW 10 372	1/24	3240	808
GW 10 373	1/24	3240	808
GW 10 377	1/24	2304	808
GW 10 381	1/24	1536	808
GW 10 382	1/24	1536	808
GW 10 383	1/24	1536	808
GW 10 383 AB	1/24	1536	977
GW 10 386	1/24	3744	808
GW 10 387	1/24	1872	808
GW 10 391	6/48	1200	806
GW 10 392	6/48	1200	806
GW 10 401	1/24	2304	809
GW 10 401 AB	1/24	1536	977
GW 10 406	1/24	2976	809
GW 10 409	1/24	1536	809
GW 10 415 ①			811
GW 10 417 ②			811
GW 10 421	1/24	2304	809
GW 10 422	1/24	1536	809
GW 10 423	1/24	2304	809
GW 10 423 AB	1/24	1536	978
GW 10 424	1/24	2880	809
GW 10 424 AB	1/24	1536	978
GW 10 431	1/48	4608	810
GW 10 431 AB	1/48	4608	978
GW 10 433	4/100	3000	810
GW 10 438	1/48	3072	810
GW 10 449	1/10	1800	811
GW 10 451	12/24	3240	810
GW 10 451 AB	12/24	2952	978
GW 10 452	12/24	3240	810
GW 10 453	1/24	2976	811
GW 10 454	1/24	3240	811
GW 10 458	1/24	1536	811
GW 10 459	1/24	1728	811
GW 10 461	1/12	3168	812
GW 10 462	1/12	3168	812
GW 10 463	1/12	3168	812
GW 10 466	1/12	3168	812
GW 10 467	1/12	2640	812
GW 10 468	1/12	2400	812
GW 10 482	1/6	1104	812
GW 10 483	1/6	1104	812
GW 10 485	1/6	1104	812
GW 10 486	1/6	1104	812
GW 10 488	1/6	1104	812
GW 10 489	1/6	1104	812

Availability: ① July 2025 ② November 2025

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 491	1/12	2400	812
GW 10 492	1/12	2340	812
GW 10 501	20/240	86400	793
GW 10 501	20/240	86400	827
GW 10 501	20/240	86400	861
GW 10 501	20/240	86400	895
GW 10 501	20/240	86400	929
GW 10 501 A	24	9600	794
GW 10 501 A	24	9600	828
GW 10 501 A	24	9600	862
GW 10 501 A	24	9600	896
GW 10 501 A	24	9600	930
GW 10 501 A	24	9600	1129
GW 10 501 A	24	9600	1157
GW 10 502	20/240	86400	793
GW 10 502	20/240	86400	827
GW 10 502	20/240	86400	861
GW 10 502	20/240	86400	895
GW 10 502	20/240	86400	929
GW 10 502 A	24	9600	794
GW 10 502 A	24	9600	828
GW 10 502 A	24	9600	862
GW 10 502 A	24	9600	896
GW 10 502 A	24	9600	930
GW 10 502 A	24	9600	1129
GW 10 502 A	24	9600	1157
GW 10 503	20/240	86400	793
GW 10 503	20/240	86400	827
GW 10 503	20/240	86400	861
GW 10 503	20/240	86400	895
GW 10 503	20/240	86400	929
GW 10 503 A	24	9600	794
GW 10 503 A	24	9600	828
GW 10 503 A	24	9600	862
GW 10 503 A	24	9600	896
GW 10 503 A	24	9600	930
GW 10 503 A	24	9600	1129
GW 10 503 A	24	9600	1157
GW 10 504	20/240	86400	793
GW 10 504	20/240	86400	827
GW 10 504	20/240	86400	861
GW 10 504	20/240	86400	895
GW 10 504	20/240	86400	929
GW 10 504 A	24	9600	794
GW 10 504 A	24	9600	828
GW 10 504 A	24	9600	862
GW 10 504 A	24	9600	896
GW 10 504 A	24	9600	930
GW 10 504 A	24	9600	1129
GW 10 504 A	24	9600	1157
GW 10 505	20/240	86400	793
GW 10 505	20/240	86400	827
GW 10 505	20/240	86400	861
GW 10 505	20/240	86400	895
GW 10 505	20/240	86400	929
GW 10 505 A	24	9600	794
GW 10 505 A	24	9600	828
GW 10 505 A	24	9600	862
GW 10 505 A	24	9600	896
GW 10 505 A	24	9600	930
GW 10 505 A	24	9600	1129
GW 10 505 A	24	9600	1157
GW 10 505 AB	20	48000	973
GW 10 506	20/240	86400	793
GW 10 506	20/240	86400	827
GW 10 506	20/240	86400	861
GW 10 506	20/240	86400	895
GW 10 506	20/240	86400	929
GW 10 506 A	24	9600	794
GW 10 506 A	24	9600	828
GW 10 506 A	24	9600	862
GW 10 506 A	24	9600	896
GW 10 506 A	24	9600	930
GW 10 506 A	24	9600	1129
GW 10 506 A	24	9600	1157
GW 10 507	20/240	86400	793
GW 10 507	20/240	86400	827
GW 10 507	20/240	86400	861
GW 10 507	20/240	86400	895
GW 10 507	20/240	86400	929
GW 10 507 A	24	9600	794
GW 10 507 A	24	9600	828
GW 10 507 A	24	9600	862
GW 10 507 A	24	9600	896
GW 10 507 A	24	9600	930
GW 10 507 A	24	9600	1129
GW 10 507 A	24	9600	1157
GW 10 507 AB	20	48000	973
GW 10 508	20/240	86400	793
GW 10 508	20/240	86400	827
GW 10 508	20/240	86400	861
GW 10 508	20/240	86400	895
GW 10 508	20/240	86400	929
GW 10 508 A	24	9600	794
GW 10 508 A	24	9600	828
GW 10 508 A	24	9600	862
GW 10 508 A	24	9600	896
GW 10 508 A	24	9600	930
GW 10 508 A	24	9600	1129
GW 10 508 A	24	9600	1157
GW 10 509	20/240	86400	793
GW 10 509	20/240	86400	827
GW 10 509	20/240	86400	861
GW 10 509	20/240	86400	895
GW 10 509	20/240	86400	929
GW 10 509 A	24	9600	794
GW 10 509 A	24	9600	828
GW 10 509 A	24	9600	862
GW 10 509 A	24	9600	896
GW 10 509 A	24	9600	930
GW 10 509 A	24	9600	1129
GW 10 509 A	24	9600	1157
GW 10 510	20/240	86400	793
GW 10 510	20/240	86400	827
GW 10 510	20/240	86400	861
GW 10 510	20/240	86400	895
GW 10 510	20/240	86400	929
GW 10 510 A	24	9600	794
GW 10 510 A	24	9600	828
GW 10 510 A	24	9600	862
GW 10 510 A	24	9600	896
GW 10 510 A	24	9600	930
GW 10 510 A	24	9600	1129
GW 10 510 A	24	9600	1157
GW 10 511	20/240	86400	793
GW 10 511	20/240	86400	827
GW 10 511	20/240	86400	861
GW 10 511	20/240	86400	895
GW 10 511	20/240	86400	929
GW 10 511 A	24	9600	794
GW 10 511 A	24	9600	828
GW 10 511 A	24	9600	862
GW 10 511 A	24	9600	896
GW 10 511 A	24	9600	930
GW 10 511 A	24	9600	1129
GW 10 511 A	24	9600	1157
GW 10 511 AB	20	48000	973
GW 10 512	20/240	86400	793
GW 10 512	20/240	86400	827
GW 10 512	20/240	86400	861
GW 10 512	20/240	86400	895
GW 10 512	20/240	86400	929
GW 10 512 A	24	9600	794
GW 10 512 A	24	9600	828
GW 10 512 A	24	9600	862
GW 10 512 A	24	9600	896
GW 10 512 A	24	9600	930
GW 10 512 A	24	9600	1129
GW 10 512 A	24	9600	1157
GW 10 513	20/240	86400	793
GW 10 513	20/240	86400	827
GW 10 513	20/240	86400	861
GW 10 513	20/240	86400	895
GW 10 513	20/240	86400	929
GW 10 513 A	24	9600	794
GW 10 513 A	24	9600	828
GW 10 513 A	24	9600	862
GW 10 513 A	24	9600	896
GW 10 513 A	24	9600	930
GW 10 513 A	24	9600	1129
GW 10 513 A	24	9600	1157
GW 10 514	20/240	86400	793
GW 10 514	20/240	86400	827
GW 10 514	20/240	86400	861
GW 10 514	20/240	86400	895
GW 10 514	20/240	86400	929
GW 10 514 A	24	9600	794
GW 10 514 A	24	9600	828
GW 10 514 A	24	9600	862
GW 10 514 A	24	9600	896
GW 10 514 A	24	9600	930
GW 10 514 A	24	9600	1129
GW 10 514 A	24	9600	1157
GW 10 515	20/240	86400	793

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 515	20/240	86400	827
GW 10 515	20/240	86400	861
GW 10 515	20/240	86400	895
GW 10 515	20/240	86400	929
GW 10 515 A	24	9600	794
GW 10 515 A	24	9600	828
GW 10 515 A	24	9600	862
GW 10 515 A	24	9600	896
GW 10 515 A	24	9600	930
GW 10 515 A	24	9600	1129
GW 10 515 A	24	9600	1157
GW 10 516	20/240	86400	793
GW 10 516	20/240	86400	827
GW 10 516	20/240	86400	861
GW 10 516	20/240	86400	895
GW 10 516	20/240	86400	929
GW 10 516 A	24	9600	794
GW 10 516 A	24	9600	828
GW 10 516 A	24	9600	862
GW 10 516 A	24	9600	896
GW 10 516 A	24	9600	930
GW 10 516 A	24	9600	1129
GW 10 516 A	24	9600	1157
GW 10 517	20/240	86400	793
GW 10 517	20/240	86400	827
GW 10 517	20/240	86400	861
GW 10 517	20/240	86400	895
GW 10 517	20/240	86400	929
GW 10 517 A	24	9600	794
GW 10 517 A	24	9600	828
GW 10 517 A	24	9600	862
GW 10 517 A	24	9600	896
GW 10 517 A	24	9600	930
GW 10 517 A	24	9600	1129
GW 10 517 A	24	9600	1157
GW 10 518	20/240	86400	793
GW 10 518	20/240	86400	827
GW 10 518	20/240	86400	861
GW 10 518	20/240	86400	895
GW 10 518	20/240	86400	929
GW 10 518 A	24	9600	794
GW 10 518 A	24	9600	828
GW 10 518 A	24	9600	862
GW 10 518 A	24	9600	896
GW 10 518 A	24	9600	930
GW 10 518 A	24	9600	1129
GW 10 518 A	24	9600	1157
GW 10 519 A	24	9600	794
GW 10 519 A	24	9600	828
GW 10 519 A	24	9600	862
GW 10 519 A	24	9600	896
GW 10 519 A	24	9600	930
GW 10 519 A	24	9600	1129
GW 10 519 A	24	9600	1157
GW 10 520 A	24	9600	794
GW 10 520 A	24	9600	828
GW 10 520 A	24	9600	862
GW 10 520 A	24	9600	896
GW 10 520 A	24	9600	930
GW 10 520 A	24	9600	1129
GW 10 520 A	24	9600	1157
GW 10 521 A	24	9600	794
GW 10 521 A	24	9600	828
GW 10 521 A	24	9600	862
GW 10 521 A	24	9600	896
GW 10 521 A	24	9600	930
GW 10 521 A	24	9600	1129
GW 10 521 A	24	9600	1157
GW 10 522 A	24	9600	794
GW 10 522 A	24	9600	828
GW 10 522 A	24	9600	862
GW 10 522 A	24	9600	896
GW 10 522 A	24	9600	930
GW 10 522 A	24	9600	1129
GW 10 522 A	24	9600	1157
GW 10 523 A	24	9600	794
GW 10 523 A	24	9600	828
GW 10 523 A	24	9600	862
GW 10 523 A	24	9600	896
GW 10 523 A	24	9600	930
GW 10 523 A	24	9600	1129
GW 10 523 A	24	9600	1157
GW 10 524 A	24	9600	794
GW 10 524 A	24	9600	828
GW 10 524 A	24	9600	862
GW 10 524 A	24	9600	896
GW 10 524 A	24	9600	930
GW 10 524 A	24	9600	1129
GW 10 524 A	24	9600	1157
GW 10 525 A	24	9600	794
GW 10 525 A	24	9600	828
GW 10 525 A	24	9600	862
GW 10 525 A	24	9600	896
GW 10 525 A	24	9600	930
GW 10 525 A	24	9600	1129
GW 10 525 A	24	9600	1157
GW 10 526 A	24	9600	794
GW 10 526 A	24	9600	828
GW 10 526 A	24	9600	862
GW 10 526 A	24	9600	896
GW 10 526 A	24	9600	930
GW 10 526 A	24	9600	1129
GW 10 526 A	24	9600	1157
GW 10 527 A	24	9600	794
GW 10 527 A	24	9600	828
GW 10 527 A	24	9600	862
GW 10 527 A	24	9600	896
GW 10 527 A	24	9600	930
GW 10 527 A	24	9600	1129
GW 10 527 A	24	9600	1157
GW 10 528 A	24	9600	794
GW 10 528 A	24	9600	828
GW 10 528 A	24	9600	862
GW 10 528 A	24	9600	896
GW 10 528 A	24	9600	930
GW 10 528 A	24	9600	1129
GW 10 528 A	24	9600	1157
GW 10 529 A	24	9600	794
GW 10 529 A	24	9600	828
GW 10 529 A	24	9600	862
GW 10 529 A	24	9600	896
GW 10 529 A	24	9600	930
GW 10 529 A	24	9600	1129
GW 10 529 A	24	9600	1157
GW 10 530 A	24	9600	794
GW 10 530 A	24	9600	828
GW 10 530 A	24	9600	862
GW 10 530 A	24	9600	896
GW 10 530 A	24	9600	930
GW 10 530 A	24	9600	1129
GW 10 530 A	24	9600	1157
GW 10 531	20/240	86400	793
GW 10 531	20/240	86400	827
GW 10 531	20/240	86400	861
GW 10 531	20/240	86400	895
GW 10 531	20/240	86400	929
GW 10 531 A	24	9600	794
GW 10 531 A	24	9600	828
GW 10 531 A	24	9600	862
GW 10 531 A	24	9600	896
GW 10 531 A	24	9600	930
GW 10 531 A	24	9600	1129
GW 10 531 A	24	9600	1157
GW 10 532	20/240	86400	793
GW 10 532	20/240	86400	827
GW 10 532	20/240	86400	861
GW 10 532	20/240	86400	895
GW 10 532	20/240	86400	929
GW 10 532 A	24	9600	794
GW 10 532 A	24	9600	828
GW 10 532 A	24	9600	862
GW 10 532 A	24	9600	896
GW 10 532 A	24	9600	930
GW 10 532 A	24	9600	1129
GW 10 532 A	24	9600	1157
GW 10 533	20/240	86400	793
GW 10 533	20/240	86400	827
GW 10 533	20/240	86400	861
GW 10 533	20/240	86400	895
GW 10 533	20/240	86400	929
GW 10 533 A	24	9600	794
GW 10 533 A	24	9600	828
GW 10 533 A	24	9600	862
GW 10 533 A	24	9600	896
GW 10 533 A	24	9600	930
GW 10 533 A	24	9600	1129
GW 10 533 A	24	9600	1157
GW 10 534	20/240	86400	793
GW 10 534	20/240	86400	827
GW 10 534	20/240	86400	861
GW 10 534	20/240	86400	895
GW 10 534	20/240	86400	929
GW 10 534 A	24	9600	794
GW 10 534 A	24	9600	828

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 534 A	24	9600	862
GW 10 534 A	24	9600	896
GW 10 534 A	24	9600	930
GW 10 534 A	24	9600	1129
GW 10 534 A	24	9600	1157
GW 10 535	20/240	86400	793
GW 10 535	20/240	86400	827
GW 10 535	20/240	86400	861
GW 10 535	20/240	86400	895
GW 10 535	20/240	86400	929
GW 10 535 A	24	9600	794
GW 10 535 A	24	9600	828
GW 10 535 A	24	9600	862
GW 10 535 A	24	9600	896
GW 10 535 A	24	9600	930
GW 10 535 A	24	9600	1129
GW 10 535 A	24	9600	1157
GW 10 536	20/240	86400	793
GW 10 536	20/240	86400	827
GW 10 536	20/240	86400	861
GW 10 536	20/240	86400	895
GW 10 536	20/240	86400	929
GW 10 536 A	24	9600	794
GW 10 536 A	24	9600	828
GW 10 536 A	24	9600	862
GW 10 536 A	24	9600	896
GW 10 536 A	24	9600	930
GW 10 536 A	24	9600	1129
GW 10 536 A	24	9600	1157
GW 10 537	20/240	86400	793
GW 10 537	20/240	86400	827
GW 10 537	20/240	86400	861
GW 10 537	20/240	86400	895
GW 10 537	20/240	86400	929
GW 10 537 A	24	9600	794
GW 10 537 A	24	9600	828
GW 10 537 A	24	9600	862
GW 10 537 A	24	9600	896
GW 10 537 A	24	9600	930
GW 10 537 A	24	9600	1129
GW 10 537 A	24	9600	1157
GW 10 538	20/240	86400	793
GW 10 538	20/240	86400	827
GW 10 538	20/240	86400	861
GW 10 538	20/240	86400	895
GW 10 538	20/240	86400	929
GW 10 538 A	24	9600	794
GW 10 538 A	24	9600	828
GW 10 538 A	24	9600	862
GW 10 538 A	24	9600	896
GW 10 538 A	24	9600	930
GW 10 538 A	24	9600	1129
GW 10 538 A	24	9600	1157
GW 10 539	20/240	86400	793
GW 10 539	20/240	86400	827
GW 10 539	20/240	86400	861
GW 10 539	20/240	86400	895
GW 10 539	20/240	86400	929
GW 10 539 A	24	9600	794
GW 10 539 A	24	9600	828
GW 10 539 A	24	9600	862
GW 10 539 A	24	9600	896
GW 10 539 A	24	9600	930
GW 10 539 A	24	9600	1129
GW 10 539 A	24	9600	1157
GW 10 540	20/240	86400	793
GW 10 540	20/240	86400	827
GW 10 540	20/240	86400	861
GW 10 540	20/240	86400	895
GW 10 540	20/240	86400	929
GW 10 540 A	24	9600	794
GW 10 540 A	24	9600	828
GW 10 540 A	24	9600	862
GW 10 540 A	24	9600	896
GW 10 540 A	24	9600	930
GW 10 540 A	24	9600	1129
GW 10 540 A	24	9600	1157
GW 10 541	4/48	17280	794
GW 10 541 A	24	28800	794
GW 10 541 A	24	28800	828
GW 10 541 A	24	28800	862
GW 10 541 A	24	28800	896
GW 10 541 A	24	28800	930
GW 10 541 A	24	28800	1129
GW 10 541 A	24	28800	1157
GW 10 542 A	24	28800	794
GW 10 542 A	24	28800	828
GW 10 542 A	24	28800	862
GW 10 542 A	24	28800	896
GW 10 542 A	24	28800	930
GW 10 542 A	24	28800	1129
GW 10 542 A	24	28800	1157
GW 10 543	4/48	17280	794
GW 10 544	4/48	17280	794
GW 10 545	4/48	17280	794
GW 10 546	4/48	17280	794
GW 10 547	4/48	17280	794
GW 10 547	4/48	17280	828
GW 10 547	4/48	17280	862
GW 10 547	4/48	17280	896
GW 10 547	4/48	17280	930
GW 10 548	4/48	17280	794
GW 10 548	4/48	17280	828
GW 10 548	4/48	17280	862
GW 10 548	4/48	17280	896
GW 10 548	4/48	17280	930
GW 10 549	4/48	17280	794
GW 10 549	4/48	17280	828
GW 10 549	4/48	17280	862
GW 10 549	4/48	17280	896
GW 10 549	4/48	17280	930
GW 10 551	4/48	7488	1156
GW 10 551 S	1/48	3744	793
GW 10 551 S	1/48	3744	1128
GW 10 552	4/48	7488	1156
GW 10 552 S	1/48	3744	793
GW 10 552 S	1/48	3744	1128
GW 10 553	4/48	7488	1156
GW 10 553 S	1/48	3744	793
GW 10 553 S	1/48	3744	1128
GW 10 554	4/48	7488	1156
GW 10 554 S	1/48	3744	793
GW 10 554 S	1/48	3744	1128
GW 10 555 S	1/48	7488	793
GW 10 555 S	1/48	7488	1128
GW 10 556 S	1/48	3744	793
GW 10 556 S	1/48	3744	1128
GW 10 557	4/48	7488	1156
GW 10 557 S	1/48	7488	793
GW 10 557 S	1/48	7488	1128
GW 10 558 S	1/48	3744	793
GW 10 558 S	1/48	3744	1128
GW 10 559	1/48	5616	1156
GW 10 564	1/12	1872	817
GW 10 567	1/12	1872	817
GW 10 568	1/12	2340	817
GW 10 572 A	1/12	1152	817
GW 10 572 AAB	1/12	768	979
GW 10 573 A	1/6	468	817
GW 10 575	1/12	1872	817
GW 10 581	1/2	156	816
GW 10 594	1/4	800	798
GW 10 595	1	300	798
GW 10 595	1	300	832
GW 10 595	1	300	866
GW 10 595	1	300	900
GW 10 595	1	300	934
GW 10 601	1/24	4872	815
GW 10 602	1/24	5400	815
GW 10 606	1/24	5400	815
GW 10 607	1/24	4872	815
GW 10 621	1/24	4224	813
GW 10 622	1/24	4224	813
GW 10 622 AB	1/24	3744	979
GW 10 623	1/24	3744	813
GW 10 623 AB	1/24	3744	979
GW 10 624	1/24	4224	813
GW 10 628	1/24	4224	813
GW 10 629	1/24	4224	813
GW 10 631	1/24	1152	813
GW 10 632	1/24	1152	813
GW 10 633	1/24	1344	813
GW 10 633 AB	1/24	1344	979
GW 10 634	1/24	1152	813
GW 10 641	2/48	8448	813
GW 10 642	2/48	8448	813
GW 10 643	2/48	8448	813
GW 10 644	2/48	8448	813
GW 10 651	1/24	1152	814
GW 10 656	1/2	246	814
GW 10 661	1/6	936	536
GW 10 661	1/6	936	814
GW 10 662	1/12	3744	814
GW 10 663	1/6	936	814

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 666	1/2	156	814
GW 10 671	1/12	1152	792
GW 10 671	1/12	1152	826
GW 10 671	1/12	1152	860
GW 10 671	1/12	1152	894
GW 10 671	1/12	1152	928
GW 10 672	1/6	468	792
GW 10 672	1/6	468	826
GW 10 672	1/6	468	860
GW 10 672	1/6	468	894
GW 10 672	1/6	468	928
GW 10 673	1/12	768	792
GW 10 673	1/12	768	826
GW 10 673	1/12	768	860
GW 10 673	1/12	768	894
GW 10 673	1/12	768	928
GW 10 674	1/6	468	792
GW 10 674	1/6	468	826
GW 10 674	1/6	468	860
GW 10 674	1/6	468	894
GW 10 674	1/6	468	928
GW 10 675	1/12	1152	792
GW 10 675	1/12	1152	826
GW 10 675	1/12	1152	860
GW 10 675	1/12	1152	894
GW 10 675	1/12	1152	928
GW 10 676	1/6	468	792
GW 10 676	1/6	468	826
GW 10 676	1/6	468	860
GW 10 676	1/6	468	894
GW 10 676	1/6	468	928
GW 10 677	1/12	1152	792
GW 10 677	1/12	1152	826
GW 10 677	1/12	1152	860
GW 10 677	1/12	1152	894
GW 10 677	1/12	1152	928
GW 10 677	1/12	1152	1127
GW 10 678	1/6	936	792
GW 10 678	1/6	936	826
GW 10 678	1/6	936	860
GW 10 678	1/6	936	894
GW 10 678	1/6	936	928
GW 10 678	1/6	936	1127
GW 10 679	1/12	1152	793
GW 10 679	1/12	1152	827
GW 10 679	1/12	1152	861
GW 10 679	1/12	1152	895
GW 10 679	1/12	1152	929
GW 10 679	1/12	1152	1127
GW 10 680	1/6	468	793
GW 10 680	1/6	468	827
GW 10 680	1/6	468	861
GW 10 680	1/6	468	895
GW 10 680	1/6	468	929
GW 10 680	1/6	468	1127
GW 10 705	1/2	312	816
GW 10 709	1/4	468	816
GW 10 709	1/4	468	1135
GW 10 711	1/2	156	818
GW 10 712	1/2	156	818
GW 10 720	1/10	3200	818
GW 10 720	1/10	3200	852
GW 10 720	1/10	3200	886
GW 10 720	1/10	3200	920
GW 10 720	1/10	3200	954
GW 10 720	1/10	3200	1167
GW 10 721	1/12	2340	798
GW 10 724	1/12	2340	798
GW 10 726	1/12	2340	798
GW 10 726 AB	1/12	1872	973
GW 10 731	4/48	5616	799
GW 10 732	4/48	5616	799
GW 10 733	4/48	5616	799
GW 10 736	1/24	2808	799
GW 10 738 AB	4/48	9600	973
GW 10 739 AB	4/48	9600	973
GW 10 750	1/12	1872	524
GW 10 750	1/12	1872	819
GW 10 750	1/12	1872	1135
GW 10 750	1/12	1872	1176
GW 10 751	5/200	10800	1154
GW 10 762 H	1	195	1166
GW 10 783 A	1	320	1155
GW 10 784 A	1	117	1155
GW 10 785 A	1	320	1155
GW 10 786	1	351	1159
GW 10 787	1	200	1155
GW 10 794 H	1	200	1165
GW 10 795 H	1	320	1165
GW 10 796	1	200	1160
GW 10 797	1	320	1161
GW 10 799	1	312	1165
GW 10 799 H	1	320	1166
GW 10 800	1	420	1166
GW 10 819	2/48	4608	1130
GW 10 820	1/48	3744	1130
GW 10 826	1/12	1152	1132
GW 10 840	1/2	320	1126
GW 10 856	1/12	400	1131
GW 10 881	50	17550	820
GW 10 881	50	17550	854
GW 10 881	50	17550	888
GW 10 881	50	17550	922
GW 10 881	50	17550	956
GW 10 881	50	17550	966
GW 10 881	50	17550	980
GW 10 881	50	17550	1025
GW 10 881	50	17550	1051
GW 10 882	50	17550	820
GW 10 882	50	17550	854
GW 10 882	50	17550	888
GW 10 882	50	17550	922
GW 10 882	50	17550	956
GW 10 882	50	17550	966
GW 10 882	50	17550	980
GW 10 882	50	17550	1025
GW 10 882	50	17550	1051
GW 10 883	50	17550	820
GW 10 883	50	17550	854
GW 10 883	50	17550	888
GW 10 883	50	17550	922
GW 10 883	50	17550	956
GW 10 883	50	17550	966
GW 10 883	50	17550	980
GW 10 883	50	17550	1025
GW 10 883	50	17550	1051
GW 10 884	50	17550	820
GW 10 884	50	17550	854
GW 10 884	50	17550	888
GW 10 884	50	17550	922
GW 10 884	50	17550	956
GW 10 884	50	17550	966
GW 10 884	50	17550	980
GW 10 884	50	17550	1025
GW 10 884	50	17550	1051
GW 10 885	50	17550	820
GW 10 885	50	17550	854
GW 10 885	50	17550	888
GW 10 885	50	17550	922
GW 10 885	50	17550	956
GW 10 885	50	17550	966
GW 10 885	50	17550	980
GW 10 885	50	17550	1025
GW 10 885	50	17550	1051
GW 10 886	50	15600	1154
GW 10 887	50	15600	1154
GW 10 888	50	10000	1154
GW 10 889	50	10000	1154
GW 10 890	50	14000	1154
GW 10 893	50	10000	226
GW 10 893	50	10000	1025
GW 10 893	50	10000	1051
GW 10 893	50	10000	1091
GW 10 894	50	15600	820
GW 10 894	50	15600	854
GW 10 894	50	15600	888
GW 10 894	50	15600	922
GW 10 894	50	15600	956
GW 10 894	50	15600	966
GW 10 894	50	15600	980
GW 10 894	50	15600	1025
GW 10 894	50	15600	1052
GW 10 900	1	160	1166
GW 10 912	1/12	720	795
GW 10 913	1/12	2400	795
GW 10 913	1/12	2400	1158
GW 10 914	1/12	2112	795
GW 10 914	1/12	2112	1158
GW 10 915	1/12	2400	795
GW 10 915	1/12	2400	1158
GW 10 916	1/12	2400	795
GW 10 916	1/12	2400	1158
GW 10 917	1/6	1200	795
GW 10 917	1/6	1200	1158

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 10 918	1/6	1200	795
GW 10 918	1/6	1200	1158
GW 10 921	1/12	768	796
GW 10 921	1/12	768	830
GW 10 921	1/12	768	864
GW 10 921	1/12	768	898
GW 10 921	1/12	768	932
GW 10 922	1/12	768	796
GW 10 922	1/12	768	830
GW 10 922	1/12	768	864
GW 10 922	1/12	768	898
GW 10 922	1/12	768	932
GW 10 923	1/12	384	796
GW 10 923	1/12	384	830
GW 10 923	1/12	384	864
GW 10 923	1/12	384	898
GW 10 923	1/12	384	932
GW 10 924	1/12	384	796
GW 10 924	1/12	384	830
GW 10 924	1/12	384	864
GW 10 924	1/12	384	898
GW 10 924	1/12	384	932
GW 10 925	1/12	384	796
GW 10 925	1/12	384	830
GW 10 925	1/12	384	864
GW 10 925	1/12	384	898
GW 10 925	1/12	384	932
GW 11			
GW 11 001	12/96	9216	958
GW 11 002	12/24	3840	958
GW 11 003	12/24	7680	958
GW 11 004	12/48	3744	958
GW 11 031	6/24	3744	958
GW 11 032	6/24	1872	958
GW 11 033	6/24	1872	958
GW 11 039	1/6	960	959
GW 11 051	12/96	9216	958
GW 11 052	12/24	3840	958
GW 11 053	12/24	3840	958
GW 11 071	6/24	1872	958
GW 11 072	6/24	1872	958
GW 11 073	6/24	1872	958
GW 11 091	12/48	3744	958
GW 11 092	12/24	3936	958
GW 11 101	6/12	1968	958
GW 11 102	6/12	1968	958
GW 11 121	12/24	3840	959
GW 11 123	6/24	1536	959
GW 11 131	12/96	4608	959
GW 11 132	12/24	3840	959
GW 11 133	12/24	3840	959
GW 11 136	1/12	1920	959
GW 11 140	12/24	3840	959
GW 11 153	12/24	3840	959
GW 11 171	6/24	1872	959
GW 11 172	6/24	1872	959
GW 11 173	6/24	1872	959
GW 11 195	10/200	18000	959

Code	Quantity		Page
	Pack/carton	Pallet	
GW 11 196	1/48	3072	960
GW 11 197	4/48	7488	959
GW 11 198	1/48	3072	959
GW 11 203	12/96	2400	960
GW 11 241	6/48	3600	960
GW 11 242	6/48	1200	960
GW 11 246	1/24	2304	961
GW 11 247	6/48	1200	961
GW 11 287	12/48	7488	961
GW 11 288	12/48	3744	961
GW 11 331	1/2	156	961
GW 11 361	1/48	3072	962
GW 11 371	1/48	3072	962
GW 11 381	1/24	1536	962
GW 11 383	1/24	1536	962
GW 11 401	1/24	1536	962
GW 11 421	1/24	2304	963
GW 11 422	1/24	1536	963
GW 11 423	1/24	1536	963
GW 11 424	1/24	1536	963
GW 11 431	1/48	3072	963
GW 11 564	1/12	1920	965
GW 11 567	1/12	1920	965
GW 11 573 A	1/6	468	965
GW 11 602	1/24	2784	964
GW 11 623	1/24	3840	964
GW 11 662	1/12	1920	964
GW 11 705	1/2	156	965
GW 12			
GW 12 001	12/96	9216	890
GW 12 002	12/24	6720	890
GW 12 003	12/24	7728	890
GW 12 004	12/48	7488	890
GW 12 005	12/24	5904	890
GW 12 006	1/12	3276	890
GW 12 007	12/24	4416	890
GW 12 021	12/24	8448	890
GW 12 022	6/24	6336	890
GW 12 031	6/24	3744	890
GW 12 031 F	6/24	1152	893
GW 12 032	6/24	1872	890
GW 12 032 F	6/24	1152	893
GW 12 033	6/24	1872	890
GW 12 033 F	6/24	1728	893
GW 12 034	6/24	1872	890
GW 12 034 F	6/24	1152	893
GW 12 035	6/24	1872	890
GW 12 035 F	6/24	1728	893
GW 12 039	1/6	1680	901
GW 12 051	12/96	9216	891
GW 12 052	12/24	7728	891
GW 12 053	12/24	4416	891
GW 12 054	1/12	2340	891
GW 12 061	6/24	6336	891
GW 12 071	6/24	3744	891
GW 12 071 F	6/24	1344	893
GW 12 072	6/24	1872	891
GW 12 072 F	6/24	1152	893

Code	Quantity		Page
	Pack/carton	Pallet	
GW 12 073	6/24	1872	891
GW 12 073 F	6/24	1728	893
GW 12 078 F	6/24	1728	894
GW 12 091	12/48	7488	891
GW 12 092	12/24	2952	891
GW 12 093	12/24	4416	891
GW 12 101	6/12	3312	891
GW 12 101 F	6/12	1620	893
GW 12 102	6/12	2208	891
GW 12 102 F	6/12	1620	893
GW 12 103	6/12	2208	891
GW 12 103 F	6/12	1620	893
GW 12 121	12/24	5400	891
GW 12 122	12/24	2952	891
GW 12 123	6/24	1536	891
GW 12 131	12/96	9216	892
GW 12 132	12/24	7728	892
GW 12 133	12/24	3744	892
GW 12 134	12/24	4416	892
GW 12 135	12/24	4416	892
GW 12 136	1/12	3744	892
GW 12 137	12/24	2808	892
GW 12 138	12/24	3240	892
GW 12 139	12/24	3240	892
GW 12 140	12/24	3240	892
GW 12 141	12/24	2952	892
GW 12 142	12/24	3240	892
GW 12 143	12/24	3240	892
GW 12 144	12/24	3240	892
GW 12 145	1/12	2340	892
GW 12 151	12/24	4416	892
GW 12 152	12/24	4416	892
GW 12 153	12/24	3744	892
GW 12 159 F	6/24	1728	894
GW 12 160 F	6/24	1344	894
GW 12 161	6/24	4800	892
GW 12 162	6/24	6336	892
GW 12 171	6/24	3744	892
GW 12 171 F	6/24	1152	893
GW 12 172	6/24	1872	892
GW 12 172 F	6/24	2304	893
GW 12 173	6/24	1872	892
GW 12 173 F	6/24	1152	893
GW 12 191	6/24	2304	892
GW 12 192	4/16	896	892
GW 12 194	6/48	1200	899
GW 12 195	10/200	18000	899
GW 12 196	1/48	3456	899
GW 12 197	4/48	14976	899
GW 12 198	1/48	3072	899
GW 12 199	1/48	2304	899
GW 12 201	12/96	7200	902
GW 12 203	12/96	7200	902
GW 12 204	6/48	3600	902
GW 12 205	6/48	3600	902
GW 12 208	6/24	1872	902
GW 12 209	4/12	936	902
GW 12 241	6/48	3600	903

Code	Quantity		Page
	Pack/carton	Pallet	
GW 12 241 F	6/12	1620	904
GW 12 242	6/48	4800	903
GW 12 246	1/24	2304	905
GW 12 247	6/48	3600	905
GW 12 247 F	6/12	1476	905
GW 12 248	6/12	1620	905
GW 12 281	1/24	2304	906
GW 12 282	1/48	3072	906
GW 12 286	12/48	3744	907
GW 12 287	12/48	7488	907
GW 12 288	12/48	7488	907
GW 12 296	6/48	1200	907
GW 12 297	6/48	1200	907
GW 12 298	6/48	1200	907
GW 12 299	12/240	5760	908
GW 12 301	6/48	1200	908
GW 12 306	6/48	1200	908
GW 12 307	6/48	1200	908
GW 12 310	10/40	3600	908
GW 12 311	1/6	1170	909
GW 12 312	1/4	880	909
GW 12 321	1/4	352	909
GW 12 322	1/2	246	909
GW 12 331	1/2	312	909
GW 12 341	6/12	3240	904
GW 12 361	1/48	4608	909
GW 12 362	1/24	4320	909
GW 12 363	1/24	3240	909
GW 12 367	1/24	1536	910
GW 12 371	1/48	4608	910
GW 12 372	1/24	3240	910
GW 12 373	1/24	3240	910
GW 12 377	1/24	1536	910
GW 12 381	1/24	1728	910
GW 12 382	1/24	1728	910
GW 12 383	1/24	1728	910
GW 12 386	1/24	1872	910
GW 12 387	1/24	1872	910
GW 12 391	6/48	1200	908
GW 12 392	6/48	1200	908
GW 12 401	1/24	2304	911
GW 12 406	1/24	3240	911
GW 12 409	1/24	720	911
GW 12 415	①		913
GW 12 417	②		913
GW 12 421	1/24	2304	911
GW 12 422	1/24	1152	911
GW 12 423	1/24	2304	911
GW 12 424	1/24	1536	911
GW 12 431	1/48	4608	912
GW 12 433	4/100	3000	912
GW 12 438	1/48	3072	912
GW 12 449	1/10	1800	913
GW 12 451	12/24	3240	912
GW 12 452	12/24	3240	912
GW 12 453	1/24	3480	913
GW 12 454	1/24	3240	913
GW 12 458	1/24	1536	913

Code	Quantity		Page
	Pack/carton	Pallet	
GW 12 459	1/24	1536	913
GW 12 461	1/12	3168	914
GW 12 462	1/12	3168	914
GW 12 463	1/12	3168	914
GW 12 466	1/12	3168	914
GW 12 467	1/12	1056	914
GW 12 468	1/12	1056	914
GW 12 482	1/6	1104	914
GW 12 483	1/6	1104	914
GW 12 485	1/6	1104	914
GW 12 486	1/6	1104	914
GW 12 488	1/6	1104	914
GW 12 489	1/6	1104	914
GW 12 491	1/12	2640	914
GW 12 492	1/12	2340	914
GW 12 541	4/48	17280	896
GW 12 543	4/48	17280	896
GW 12 544	4/48	17280	896
GW 12 545	4/48	17280	896
GW 12 546	4/48	17280	896
GW 12 551	4/48	7488	1156
GW 12 551 S	1/48	3744	895
GW 12 551 S	1/48	3744	1128
GW 12 552	4/48	7488	1156
GW 12 552 S	1/48	3744	895
GW 12 552 S	1/48	3744	1128
GW 12 553	4/48	15360	1156
GW 12 553 S	1/48	3744	895
GW 12 553 S	1/48	3744	1128
GW 12 554	4/48	7488	1156
GW 12 554 S	1/48	3744	895
GW 12 554 S	1/48	3744	1128
GW 12 555 S	1/48	7488	895
GW 12 555 S	1/48	7488	1128
GW 12 556 S	1/48	3744	895
GW 12 556 S	1/48	3744	1128
GW 12 557	4/48	7488	1156
GW 12 557 S	1/48	3744	895
GW 12 557 S	1/48	3744	1128
GW 12 558 S	1/48	3744	895
GW 12 558 S	1/48	3744	1128
GW 12 559	1/48	5616	1156
GW 12 564	1/12	2808	919
GW 12 567	1/12	2340	919
GW 12 568	1/12	1872	919
GW 12 572 A	1/12	1152	919
GW 12 573 A	1/6	468	919
GW 12 575	1/12		919
GW 12 581	1/2	156	918
GW 12 594	1/4	800	900
GW 12 601	1/24	2976	917
GW 12 602	1/24	4872	917
GW 12 606	1/24	5400	917
GW 12 607	1/24	4320	917
GW 12 621	1/24	4224	915
GW 12 622	1/24	4224	915
GW 12 623	1/24	4224	915
GW 12 624	1/24	4224	915

Code	Quantity		Page
	Pack/carton	Pallet	
GW 12 628	1/24	4224	915
GW 12 629	1/24	4224	915
GW 12 631	1/24	1152	915
GW 12 632	1/24	1344	915
GW 12 633	1/24	1152	915
GW 12 634	1/24	1152	915
GW 12 641	2/48	8448	915
GW 12 642	2/48	8448	915
GW 12 643	2/48	8448	915
GW 12 644	2/48	8448	915
GW 12 651	1/24	1536	916
GW 12 656	1/2	192	916
GW 12 661	1/6	936	916
GW 12 662	1/12	1872	916
GW 12 663	1/6	1170	916
GW 12 666	1/2	156	916
GW 12 705	1/2	312	918
GW 12 709	1/4	468	918
GW 12 709	1/4	468	1135
GW 12 711	1/2	312	920
GW 12 712	1/2	156	920
GW 12 721	1/12	2340	900
GW 12 724	1/12	2340	900
GW 12 726	1/12	2340	900
GW 12 731	4/48	5616	901
GW 12 732	4/48	5616	901
GW 12 733	4/48	5616	901
GW 12 736	1/24	2808	901
GW 12 750	1/12	1872	524
GW 12 750	1/12	1872	921
GW 12 750	1/12	1872	1135
GW 12 750	1/12	1872	1176
GW 12 751	5/200	10800	1154
GW 12 762 H	1	195	1166
GW 12 783 A	1	320	1155
GW 12 784 A	1	117	1155
GW 12 785 A	1	117	1155
GW 12 786	1	195	1159
GW 12 787	1	240	1155
GW 12 794 H	1	117	1165
GW 12 795 H	1	320	1165
GW 12 796	1	195	1160
GW 12 797	1	195	1161
GW 12 799	1	195	1165
GW 12 799 H	1	200	1166
GW 12 819	2/48	4608	1130
GW 12 820	1/48	3744	1130
GW 12 826	1/12	768	1132
GW 12 840	1/2	320	1126
GW 12 856	1/12	400	1131
GW 12 900	1	160	1166
GW 12 912	1/12	720	897
GW 12 913	1/12	720	897
GW 12 913	1/12	720	1158
GW 12 914	1/12	2112	897
GW 12 914	1/12	2112	1158
GW 12 915	1/12	2340	897
GW 12 915	1/12	2340	1158

Availability: ① July 2025 ② November 2025

Quick Reference

Code	Quantity Pack/carton	Pallet	Page
GW 12 916	1/12	2400	897
GW 12 916	1/12	2400	1158
GW 12 917	1/6	1200	897
GW 12 917	1/6	1200	1158
GW 12 918	1/6	1200	897
GW 12 918	1/6	1200	1158
GW 13			
GW 13 001	12/96	9216	856
GW 13 002	12/24	6552	856
GW 13 003	12/24	3744	856
GW 13 004	12/48	3744	856
GW 13 005	12/24	2952	856
GW 13 006	1/12	1872	856
GW 13 007	12/24	3744	856
GW 13 021	12/24	4800	856
GW 13 022	6/24	4800	856
GW 13 031	6/24	3744	856
GW 13 031 F	6/24	1344	859
GW 13 032	6/24	1872	856
GW 13 032 F	6/24	1344	859
GW 13 033	6/24	1872	856
GW 13 033 F	6/24	1344	859
GW 13 034	6/24	1872	856
GW 13 034 F	6/24	1344	859
GW 13 035	6/24	1872	856
GW 13 035 F	6/24	1344	859
GW 13 039	1/6	1200	867
GW 13 051	12/96	9216	857
GW 13 052	12/24	3744	857
GW 13 053	12/24	3744	857
GW 13 054	1/12	1872	857
GW 13 061	6/24	4800	857
GW 13 071	6/24	3744	857
GW 13 071 F	6/24	1344	859
GW 13 072	6/24	1872	857
GW 13 072 F	6/24	1344	859
GW 13 073	6/24	1872	857
GW 13 073 F	6/24	1344	859
GW 13 078 F	6/24	1344	860
GW 13 091	12/48	7488	857
GW 13 092	12/24	2952	857
GW 13 093	12/24	2952	857
GW 13 101	6/12	1476	857
GW 13 101 F	6/12	1476	859
GW 13 102	6/12	1476	857
GW 13 102 F	6/12	1476	859
GW 13 103	6/12	1476	857
GW 13 103 F	6/12	1476	859
GW 13 121	12/24	2952	857
GW 13 122	12/24	2952	857
GW 13 123	6/24	1344	857
GW 13 131	12/96	9216	858
GW 13 132	12/24	6552	858
GW 13 133	12/24	3744	858
GW 13 134	12/24	3744	858
GW 13 135	12/24	2952	858
GW 13 136	1/12	1872	858
GW 13 137	12/24	3744	858
GW 13 138	12/24	2952	858
GW 13 139	12/24	2952	858
GW 13 140	12/24	5904	858
GW 13 141	12/24	2952	858
GW 13 142	12/24	2952	858
GW 13 143	12/24	2952	858
GW 13 144	12/24	2952	858
GW 13 145	1/12	1872	858
GW 13 151	12/24	3744	858
GW 13 152	12/24	3744	858
GW 13 153	12/24	3744	858
GW 13 159 F	6/24	1344	860
GW 13 160 F	6/24	1344	860
GW 13 161	6/24	4800	858
GW 13 162	6/24	4800	858
GW 13 171	6/24	1872	858
GW 13 171 F	6/24	1344	859
GW 13 172	6/24	1872	858
GW 13 172 F	6/24	1344	859
GW 13 173	6/24	1872	858
GW 13 173 F	6/24	1344	859
GW 13 191	6/24	1344	858
GW 13 192	4/16	896	858
GW 13 194	6/48	1200	865
GW 13 195	10/200	18000	865
GW 13 196	1/48	3072	865
GW 13 197	4/48	9600	865
GW 13 198	1/48	3072	865
GW 13 199	1/48	2016	865
GW 13 201	12/96	2400	868
GW 13 203	12/96	7200	868
GW 13 204	6/48	3600	868
GW 13 205	6/48	3600	868
GW 13 208	6/24	1872	868
GW 13 209	4/12	936	868
GW 13 241	6/48	3600	869
GW 13 241 F	6/12	1476	870
GW 13 242	6/48	1200	869
GW 13 246	1/24	1536	871
GW 13 247	6/48	1200	871
GW 13 247 F	6/12	1476	871
GW 13 248	6/12	1476	871
GW 13 281	1/24	2304	872
GW 13 282	1/48	3072	872
GW 13 286	12/48	3744	873
GW 13 287	12/48	3744	873
GW 13 288	12/48	3744	873
GW 13 296	6/48	1200	873
GW 13 297	6/48	1200	873
GW 13 298	6/48	1200	873
GW 13 299	12/240	1920	874
GW 13 301	6/48	1200	874
GW 13 306	6/48	1200	874
GW 13 307	6/48	1200	874
GW 13 310	10/40	1800	874
GW 13 311	1/6	1200	875
GW 13 312	1/4	800	875
GW 13 321	1/4	800	875
GW 13 322	1/2	192	875
GW 13 331	1/2	156	875
GW 13 341	6/12	1476	870
GW 13 361	1/48	4608	875
GW 13 362	1/24	2976	875
GW 13 363	1/24	2976	875
GW 13 367	1/24	1536	876
GW 13 371	1/48	3072	876
GW 13 372	1/24	2976	876
GW 13 373	1/24	2976	876
GW 13 377	1/24	1536	876
GW 13 381	1/24	1536	876
GW 13 382	1/24	1536	876
GW 13 383	1/24	1536	876
GW 13 386	1/24	1872	876
GW 13 387	1/24	1872	876
GW 13 391	6/48	1200	874
GW 13 392	6/48	1200	874
GW 13 401	1/24	2304	877
GW 13 406	1/24	2976	877
GW 13 409	1/24	1536	877
GW 13 415	①		879
GW 13 417	②		879
GW 13 421	1/24	2304	877
GW 13 422	1/24	1536	877
GW 13 423	1/24	1536	877
GW 13 424	1/24	1536	877
GW 13 431	1/48	4608	878
GW 13 433	4/100	5400	878
GW 13 438	1/48	3072	878
GW 13 449	1/10	1800	879
GW 13 451	12/24	2952	878
GW 13 452	12/24	2952	878
GW 13 453	1/24	2976	879
GW 13 454	1/24	2976	879
GW 13 458	1/24	1536	879
GW 13 459	1/24	1536	879
GW 13 461	1/12	2400	880
GW 13 462	1/12	2400	880
GW 13 463	1/12	2400	880
GW 13 466	1/12	2400	880
GW 13 467	1/12	2400	880
GW 13 468	1/12	2400	880
GW 13 482	1/6	936	880
GW 13 483	1/6	936	880
GW 13 485	1/6	936	880
GW 13 486	1/6	936	880
GW 13 488	1/6	936	880
GW 13 489	1/6	936	880
GW 13 491	1/12	2400	880
GW 13 492	1/12	1872	880
GW 13 541	4/48	9600	862
GW 13 543	4/48	9600	862
GW 13 544	4/48	9600	862
GW 13 545	4/48	9600	862
GW 13 546	4/48	9600	862
GW 13 551	4/48	9600	1156
GW 13 551 S	1/48	3744	861

Availability: ① July 2025 ② November 2025

Code	Quantity		Page
	Pack/carton	Pallet	
GW 13 551 S	1/48	3744	1128
GW 13 552	4/48	9600	1156
GW 13 552 S	1/48	3744	861
GW 13 552 S	1/48	3744	1128
GW 13 553	4/48	9600	1156
GW 13 553 S	1/48	3744	861
GW 13 553 S	1/48	3744	1128
GW 13 554	4/48	9600	1156
GW 13 554 S	1/48	3744	861
GW 13 554 S	1/48	3744	1128
GW 13 555 S	1/48	7488	861
GW 13 555 S	1/48	7488	1128
GW 13 556 S	1/48	3744	861
GW 13 556 S	1/48	3744	1128
GW 13 557	4/48	9600	1156
GW 13 557 S	1/48	3744	861
GW 13 557 S	1/48	3744	1128
GW 13 558 S	1/48	3744	861
GW 13 558 S	1/48	3744	1128
GW 13 559	1/48	4608	1156
GW 13 564	1/12	1872	885
GW 13 567	1/12	1872	885
GW 13 568	1/12	1872	885
GW 13 572 A	1/12	768	885
GW 13 573 A	1/6	468	885
GW 13 575	1/12	1404	885
GW 13 594	1/4	800	866
GW 13 601	1/24	2976	883
GW 13 602	1/24	2976	883
GW 13 606	1/24	2976	883
GW 13 607	1/24	2976	883
GW 13 621	1/24	3744	881
GW 13 622	1/24	3744	881
GW 13 623	1/24	3744	881
GW 13 624	1/24	3744	881
GW 13 628	1/24	3744	881
GW 13 629	1/24	3744	881
GW 13 631	1/24	1344	881
GW 13 632	1/24	1344	881
GW 13 633	1/24	1344	881
GW 13 634	1/24	1344	881
GW 13 641	2/48	7488	881
GW 13 642	2/48	7488	881
GW 13 643	2/48	7488	881
GW 13 644	2/48	7488	881
GW 13 651	1/24	1536	882
GW 13 656	1/2	192	882
GW 13 661	1/6	936	882
GW 13 662	1/12	1872	882
GW 13 663	1/6	936	882
GW 13 666	1/2	156	882
GW 13 705	1/2	156	884
GW 13 709	1/4	468	884
GW 13 709	1/4	468	1135
GW 13 712	1/2	156	886
GW 13 721	1/12	1872	866
GW 13 724	1/12	1872	866
GW 13 726	1/12	1872	866
GW 13 731	4/48	9600	867
GW 13 732	4/48	9600	867
GW 13 733	4/48	9600	867
GW 13 736	1/24	3744	867
GW 13 750	1/12	2400	524
GW 13 750	1/12	2400	887
GW 13 750	1/12	2400	1135
GW 13 750	1/12	2400	1176
GW 13 751	5/200	10800	1154
GW 13 762 H	1	200	1166
GW 13 783 A	1	200	1155
GW 13 784 A	1	200	1155
GW 13 785 A	1	200	1155
GW 13 786	1	200	1159
GW 13 787	1	200	1155
GW 13 794 H	1	200	1165
GW 13 795 H	1	200	1165
GW 13 796	1	200	1160
GW 13 797	1	200	1161
GW 13 799	1	200	1165
GW 13 799 H	1	200	1166
GW 13 819	2/48	4608	1130
GW 13 820	1/48	3744	1130
GW 13 826	1/12	768	1132
GW 13 840	1/2	320	1126
GW 13 856	1/12	400	1131
GW 13 900	1	200	1166
GW 13 912	1/12	2400	863
GW 13 913	1/12	2400	863
GW 13 913	1/12	2400	1158
GW 13 914	1/12	1872	863
GW 13 914	1/12	1872	1158
GW 13 915	1/12	2400	863
GW 13 915	1/12	2400	1158
GW 13 916	1/12	2400	863
GW 13 916	1/12	2400	1158
GW 13 917	1/6	1200	863
GW 13 917	1/6	1200	1158
GW 13 918	1/6	1200	863
GW 13 918	1/6	1200	1158

GW 14

Code	Quantity		Page
	Pack/carton	Pallet	
GW 14 001	12/96	9216	924
GW 14 002	12/24	3744	924
GW 14 003	12/24	3744	924
GW 14 004	12/48	7488	924
GW 14 005	12/24	4416	924
GW 14 006	1/12	2340	924
GW 14 007	12/24	4416	924
GW 14 021	12/24	4800	924
GW 14 022	6/24	6336	924
GW 14 031	6/24	3744	924
GW 14 031 F	6/24	1728	927
GW 14 032	6/24	1872	924
GW 14 032 F	6/24	1152	927
GW 14 033	6/24	1872	924
GW 14 033 F	6/24	1728	927
GW 14 034	6/24	1872	924
GW 14 034 F	6/24	1728	927
GW 14 035	6/24	1872	924
GW 14 035 F	6/24	1728	927
GW 14 039	1/6	1200	935
GW 14 051	12/96	9216	925
GW 14 052	12/24	3744	925
GW 14 053	12/24	4416	925
GW 14 054	1/12	2340	925
GW 14 061	6/24	6336	925
GW 14 071	6/24	3744	925
GW 14 071 F	6/24	1152	927
GW 14 072	6/24	1872	925
GW 14 072 F	6/24	1152	927
GW 14 073	6/24	1872	925
GW 14 073 F	6/24	1728	927
GW 14 078 F	6/24	1728	928
GW 14 091	12/48	7488	925
GW 14 092	12/24	3312	925
GW 14 093	12/24	4416	925
GW 14 101	6/12	1476	925
GW 14 101 F	6/12	1620	927
GW 14 102	6/12	2208	925
GW 14 102 F	6/12	1620	927
GW 14 103	6/12	2208	925
GW 14 103 F	6/12	1620	927
GW 14 121	12/24	2952	925
GW 14 122	12/24	2952	925
GW 14 123	6/24	1872	925
GW 14 131	12/96	9216	926
GW 14 132	12/24	7728	926
GW 14 133	12/24	3744	926
GW 14 134	12/24	4416	926
GW 14 135	12/24	2952	926
GW 14 136	1/12	1872	926
GW 14 137	12/24	4416	926
GW 14 138	12/24	3240	926
GW 14 139	12/24	3240	926
GW 14 140	12/24	5904	926
GW 14 141	12/24	2952	926
GW 14 142	12/24	3240	926
GW 14 143	12/24	3240	926
GW 14 144	12/24	3240	926
GW 14 145	1/12	2340	926
GW 14 151	12/24	4416	926
GW 14 152	12/24	4416	926
GW 14 153	12/24	4416	926
GW 14 159 F	6/24	1728	928
GW 14 160 F	6/24	1728	928
GW 14 161	6/24	6336	926
GW 14 162	6/24	6336	926
GW 14 171	6/24	1872	926
GW 14 171 F	6/24	1728	927
GW 14 172	6/24	1872	926
GW 14 172 F	6/24	2304	927
GW 14 173	6/24	1872	926
GW 14 173 F	6/24	1152	927
GW 14 191	6/24	1344	926
GW 14 192	4/16	1152	926
GW 14 194	6/48	1200	933

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 14 195	10/200	18000	933
GW 14 196	1/48	3072	933
GW 14 197	4/48	9600	933
GW 14 198	1/48	3456	933
GW 14 199	1/48	2304	933
GW 14 201	12/96	2400	936
GW 14 203	12/96	7200	936
GW 14 204	6/48	3600	936
GW 14 205	6/48	1200	936
GW 14 208	6/24	1872	936
GW 14 209	4/12	936	936
GW 14 241	6/48	3600	937
GW 14 241 F	6/12	1620	938
GW 14 242	6/48	1200	937
GW 14 246	1/24	2304	939
GW 14 247	6/48	1200	939
GW 14 247 F	6/12	1476	939
GW 14 248	6/12	2700	939
GW 14 281	1/24	1536	940
GW 14 282	1/48	2688	940
GW 14 286	12/48	3744	941
GW 14 287	12/48	7488	941
GW 14 288	12/48	3744	941
GW 14 296	6/48	1200	941
GW 14 297	6/48	1200	941
GW 14 298	6/48	1200	941
GW 14 299	12/240	5760	942
GW 14 301	6/48	1200	942
GW 14 306	6/48	1200	942
GW 14 307	6/48	1200	942
GW 14 310	10/40	1800	942
GW 14 311	1/6	1170	943
GW 14 312	1/4	352	943
GW 14 321	1/4	352	943
GW 14 322	1/2	246	943
GW 14 331	1/2	156	943
GW 14 341	6/12	3240	938
GW 14 361	1/48	5760	943
GW 14 362	1/24	4320	943
GW 14 363	1/24	3240	943
GW 14 367	1/24	1536	944
GW 14 371	1/48	3072	944
GW 14 372	1/24	3240	944
GW 14 373	1/24	3240	944
GW 14 377	1/24	1536	944
GW 14 381	1/24	1152	944
GW 14 382	1/24	1728	944
GW 14 383	1/24	1536	944
GW 14 386	1/24	1872	944
GW 14 387	1/24	1872	944
GW 14 391	6/48	1200	942
GW 14 392	6/48	1200	942
GW 14 401	1/24	2304	945
GW 14 406	1/24	3240	945
GW 14 409	1/24	1536	945
GW 14 415	①		947
GW 14 417	②		947
GW 14 421	1/24	2304	945

Code	Quantity		Page
	Pack/carton	Pallet	
GW 14 422	1/24	1728	945
GW 14 423	1/24	1536	945
GW 14 424	1/24	1152	945
GW 14 431	1/48	3072	946
GW 14 433	4/100	3000	946
GW 14 438	1/48	3072	946
GW 14 449	1/10	1800	947
GW 14 451	12/24	3240	946
GW 14 452	12/24	3240	946
GW 14 453	1/24	3240	947
GW 14 454	1/24	3240	947
GW 14 458	1/24	1728	947
GW 14 459	1/24	1728	947
GW 14 461	1/12	3168	948
GW 14 462	1/12	3168	948
GW 14 463	1/12	3168	948
GW 14 466	1/12	3168	948
GW 14 467	1/12	1056	948
GW 14 468	1/12	1056	948
GW 14 482	1/6	1104	948
GW 14 483	1/6	1104	948
GW 14 485	1/6	1104	948
GW 14 486	1/6	1104	948
GW 14 488	1/6	1104	948
GW 14 489	1/6	1104	948
GW 14 491	1/12	2640	948
GW 14 492	1/12	2340	948
GW 14 541	4/48	17280	930
GW 14 543	4/48	17280	930
GW 14 544	4/48	17280	930
GW 14 545	4/48	17280	930
GW 14 546	4/48	17280	930
GW 14 551	4/48	768	1156
GW 14 551 S	1/48	3744	929
GW 14 551 S	1/48	3744	1128
GW 14 552	4/48	7488	1156
GW 14 552 S	1/48	3744	929
GW 14 552 S	1/48	3744	1128
GW 14 553	4/48	5760	1156
GW 14 553 S	1/48	3744	929
GW 14 553 S	1/48	3744	1128
GW 14 554	4/48	1248	1156
GW 14 554 S	1/48	3744	929
GW 14 554 S	1/48	3744	1128
GW 14 555 S	1/48	7488	929
GW 14 555 S	1/48	7488	1128
GW 14 556 S	1/48	3744	929
GW 14 556 S	1/48	3744	1128
GW 14 557	4/48	7680	1156
GW 14 557 S	1/48	3744	929
GW 14 557 S	1/48	3744	1128
GW 14 558 S	1/48	3744	929
GW 14 558 S	1/48	3744	1128
GW 14 559	1/48	5616	1156
GW 14 564	1/12	1872	953
GW 14 567	1/12	2340	953
GW 14 568	1/12	1872	953
GW 14 572 A	1/12	1152	953

Code	Quantity		Page
	Pack/carton	Pallet	
GW 14 573 A	1/6	468	953
GW 14 575	1/12	1872	953
GW 14 581	1/2	156	952
GW 14 594	1/4	800	934
GW 14 601	1/24	2976	951
GW 14 602	1/24	2976	951
GW 14 606	1/24	5400	951
GW 14 607	1/24	4320	951
GW 14 621	1/24	4224	949
GW 14 622	1/24	4224	949
GW 14 623	1/24	4224	949
GW 14 624	1/24	4224	949
GW 14 628	1/24	4224	949
GW 14 629	1/24	4224	949
GW 14 631	1/24	1152	949
GW 14 632	1/24	1152	949
GW 14 633	1/24	1152	949
GW 14 634	1/24	1152	949
GW 14 641	2/48	8448	949
GW 14 642	2/48	8448	949
GW 14 643	2/48	8448	949
GW 14 644	2/48	8448	949
GW 14 651	1/24	1536	950
GW 14 656	1/2	264	950
GW 14 661	1/6	936	950
GW 14 662	1/12	1872	950
GW 14 663	1/6	960	950
GW 14 666	1/2	156	950
GW 14 705	1/2	156	952
GW 14 709	1/4	468	952
GW 14 709	1/4	468	1135
GW 14 711	1/2	312	954
GW 14 712	1/2	156	954
GW 14 721	1/12	2340	934
GW 14 724	1/12	2340	934
GW 14 726	1/12	2340	934
GW 14 731	4/48	5616	935
GW 14 732	4/48	5616	935
GW 14 733	4/48	5616	935
GW 14 736	1/24	2808	935
GW 14 750	1/12	1872	524
GW 14 750	1/12	1872	955
GW 14 750	1/12	1872	1135
GW 14 750	1/12	1872	1176
GW 14 751	5/200	10800	1154
GW 14 762 H	1	195	1166
GW 14 783 A	1	117	1155
GW 14 784 A	1	200	1155
GW 14 785 A	1	200	1155
GW 14 786	1	195	1159
GW 14 787	1	320	1155
GW 14 794 H	1	156	1165
GW 14 795 H	1	156	1165
GW 14 796	1	195	1160
GW 14 797	1	200	1161
GW 14 799	1	200	1165
GW 14 799 H	1	200	1166
GW 14 819	2/48	4608	1130

Availability: ① July 2025 ② November 2025

Code	Quantity		Page
	Pack/carton	Pallet	
GW 14 820	1/48	3744	1130
GW 14 826	1/12	768	1132
GW 14 840	1/2	320	1126
GW 14 856	1/12	400	1131
GW 14 900	1	160	1166
GW 14 912	1/12	720	931
GW 14 913	1/12	4320	931
GW 14 913	1/12	4320	1158
GW 14 914	1/12	2112	931
GW 14 914	1/12	2112	1158
GW 14 915	1/12	2400	931
GW 14 915	1/12	2400	1158
GW 14 916	1/12	2400	931
GW 14 916	1/12	2400	1158
GW 14 917	1/6	1200	931
GW 14 917	1/6	1200	1158
GW 14 918	1/6	1200	931
GW 14 918	1/6	1200	1158

GW 15

Code	Quantity		Page
	Pack/carton	Pallet	
GW 15 001	12/96	9216	822
GW 15 002	12/24	3744	822
GW 15 003	12/24	3744	822
GW 15 004	12/48	3744	822
GW 15 005	12/24	2952	822
GW 15 006	1/12	1872	822
GW 15 007	12/24	3744	822
GW 15 021	12/24	4800	822
GW 15 022	6/24	4800	822
GW 15 031	6/24	3744	822
GW 15 031 F	6/24	1344	825
GW 15 032	6/24	1872	822
GW 15 032 F	6/24	1344	825
GW 15 033	6/24	1872	822
GW 15 033 F	6/24	1344	825
GW 15 034	6/24	1872	822
GW 15 034 F	6/24	1344	825
GW 15 035	6/24	1872	822
GW 15 035 F	6/24	1344	825
GW 15 039	1/6	1200	833
GW 15 051	12/96	9216	823
GW 15 052	12/24	3744	823
GW 15 053	12/24	3744	823
GW 15 054	1/12	1872	823
GW 15 061	6/24	4800	823
GW 15 071	6/24	3744	823
GW 15 071 F	6/24	1344	825
GW 15 072	6/24	1872	823
GW 15 072 F	6/24	1344	825
GW 15 073	6/24	1872	823
GW 15 073 F	6/24	1344	825
GW 15 078 F	6/24	1344	826
GW 15 091	12/48	7488	823
GW 15 092	12/24	2952	823
GW 15 093	12/24	2952	823
GW 15 101	6/12	1476	823
GW 15 101 F	6/12	1476	825
GW 15 102	6/12	1476	823
GW 15 102 F	6/12	1476	825
GW 15 103	6/12	1476	823
GW 15 103 F	6/12	1476	825
GW 15 121	12/24	5904	823
GW 15 122	12/24	2952	823
GW 15 123	6/24	1344	823
GW 15 131	12/96	9216	824
GW 15 132	12/24	3744	824
GW 15 133	12/24	3744	824
GW 15 134	12/24	3744	824
GW 15 135	12/24	2952	824
GW 15 136	1/12	1872	824
GW 15 137	12/24	3744	824
GW 15 138	12/24	2952	824
GW 15 139	12/24	2952	824
GW 15 140	12/24	5904	824
GW 15 141	12/24	2952	824
GW 15 142	12/24	2952	824
GW 15 143	12/24	2952	824
GW 15 144	12/24	2952	824
GW 15 145	1/12	1872	824
GW 15 151	12/24	3744	824
GW 15 152	12/24	3744	824
GW 15 153	12/24	3744	824
GW 15 159 F	6/24	1344	826
GW 15 160 F	6/24	1344	826
GW 15 161	6/24	4800	824
GW 15 162	6/24	4800	824
GW 15 171	6/24	1872	824
GW 15 171 F	6/24	1344	825
GW 15 172	6/24	1872	824
GW 15 172 F	6/24	1344	825
GW 15 173	6/24	1872	824
GW 15 173 F	6/24	1344	825
GW 15 191	6/24	1344	824
GW 15 192	4/16	896	824
GW 15 194	6/48	1200	831
GW 15 195	10/200	18000	831
GW 15 196	1/48	3072	831
GW 15 197	4/48	9600	831
GW 15 198	1/48	3072	831
GW 15 199	1/48	2016	831
GW 15 201	12/96	2400	834
GW 15 203	12/96	7200	834
GW 15 204	6/48	3600	834
GW 15 205	6/48	1200	834
GW 15 208	6/24	1872	834
GW 15 209	4/12	936	834
GW 15 241	6/48	3600	835
GW 15 241 F	6/12	1476	836
GW 15 242	6/48	1200	835
GW 15 246	1/24	2304	837
GW 15 247	6/48	3600	837
GW 15 247 F	6/12	1476	837
GW 15 248	6/12	1476	837
GW 15 281	1/24	2304	838
GW 15 282	1/48	3072	838
GW 15 286	12/48	3744	839
GW 15 287	12/48	7488	839
GW 15 288	12/48	3744	839
GW 15 296	6/48	1200	839
GW 15 297	6/48	1200	839
GW 15 298	6/48	1200	839
GW 15 299	12/240	1920	840
GW 15 301	6/48	1200	840
GW 15 306	6/48	1200	840
GW 15 307	6/48	1200	840
GW 15 310	10/40	3000	840
GW 15 311	1/6	1200	841
GW 15 312	1/4	800	841
GW 15 321	1/4	800	841
GW 15 322	1/2	192	841
GW 15 331	1/2	156	841
GW 15 341	6/12	2952	836
GW 15 361	1/48	4608	841
GW 15 362	1/24	2976	841
GW 15 363	1/24	2976	841
GW 15 367	1/24	1536	842
GW 15 371	1/48	3072	842
GW 15 372	1/24	2976	842
GW 15 373	1/24	2976	842
GW 15 377	1/24	1536	842
GW 15 381	1/24	1536	842
GW 15 382	1/24	1536	842
GW 15 383	1/24	1536	842
GW 15 386	1/24	1872	842
GW 15 387	1/24	1872	842
GW 15 391	6/48	1200	840
GW 15 392	6/48	1200	840
GW 15 401	1/24	2304	843
GW 15 406	1/24	2976	843
GW 15 409	1/24	1536	843
GW 15 415 ①			845
GW 15 417 ②			845
GW 15 421	1/24	2304	843
GW 15 422	1/24	1536	843
GW 15 423	1/24	1536	843
GW 15 424	1/24	1536	843
GW 15 431	1/48	4608	844
GW 15 433	4/100	5400	844
GW 15 438	1/48	3072	844
GW 15 449	1/10	1800	845
GW 15 451	12/24	2952	844
GW 15 452	12/24	2952	844
GW 15 453	1/24	2976	845
GW 15 454	1/24	2976	845
GW 15 458	1/24	1536	845
GW 15 459	1/24	1536	845
GW 15 461	1/12	2400	846
GW 15 462	1/12	2400	846
GW 15 463	1/12	2400	846
GW 15 466	1/12	2400	846
GW 15 467	1/12	2400	846
GW 15 468	1/12	2400	846
GW 15 482	1/6	936	846
GW 15 483	1/6	936	846
GW 15 485	1/6	936	846

Availability: ① July 2025 ② November 2025

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 15 486	1/6	936	846
GW 15 488	1/6	936	846
GW 15 489	1/6	936	846
GW 15 491	1/12	2400	846
GW 15 492	1/12	1872	846
GW 15 541	4/48	9600	828
GW 15 543	4/48	9600	828
GW 15 544	4/48	9600	828
GW 15 545	4/48	9600	828
GW 15 546	4/48	9600	828
GW 15 551	4/48	9600	1156
GW 15 551 S	1/48	3744	827
GW 15 551 S	1/48	3744	1128
GW 15 552	4/48	9600	1156
GW 15 552 S	1/48	3744	827
GW 15 552 S	1/48	3744	1128
GW 15 553	4/48	9600	1156
GW 15 553 S	1/48	3744	827
GW 15 553 S	1/48	3744	1128
GW 15 554	4/48	9600	1156
GW 15 554 S	1/48	3744	827
GW 15 554 S	1/48	3744	1128
GW 15 555 S	1/48	7488	827
GW 15 555 S	1/48	7488	1128
GW 15 556 S	1/48	3744	827
GW 15 556 S	1/48	3744	1128
GW 15 557	4/48	9600	1156
GW 15 557 S	1/48	7488	827
GW 15 557 S	1/48	7488	1128
GW 15 558 S	1/48	3744	827
GW 15 558 S	1/48	3744	1128
GW 15 559	1/48	4608	1156
GW 15 564	1/12	1872	851
GW 15 567	1/12	1872	851
GW 15 568	1/12	1872	851
GW 15 572 A	1/12	768	851
GW 15 573 A	1/6	468	851
GW 15 575	1/12	1404	851
GW 15 594	1/4	800	832
GW 15 601	1/24	2976	849
GW 15 602	1/24	2976	849
GW 15 606	1/24	2976	849
GW 15 607	1/24	2976	849
GW 15 621	1/24	3744	847
GW 15 622	1/24	3744	847
GW 15 623	1/24	3744	847
GW 15 624	1/24	3744	847
GW 15 628	1/24	3744	847
GW 15 629	1/24	3744	847
GW 15 631	1/24	1344	847
GW 15 632	1/24	1344	847
GW 15 633	1/24	1344	847
GW 15 634	1/24	1344	847
GW 15 641	2/48	7488	847
GW 15 642	2/48	7488	847
GW 15 643	2/48	7488	847
GW 15 644	2/48	7488	847
GW 15 651	1/24	1536	848

Code	Quantity		Page
	Pack/carton	Pallet	
GW 15 656	1/2	192	848
GW 15 662	1/12	1872	848
GW 15 663	1/6	936	848
GW 15 666	1/2	156	848
GW 15 705	1/2	156	850
GW 15 709	1/4	468	850
GW 15 709	1/4	468	1135
GW 15 712	1/2	156	852
GW 15 721	1/12	1872	832
GW 15 724	1/12	1872	832
GW 15 726	1/12	1872	832
GW 15 731	4/48	9600	833
GW 15 732	4/48	9600	833
GW 15 733	4/48	9600	833
GW 15 736	1/24	3744	833
GW 15 750	1/12	2400	524
GW 15 750	1/12	2400	853
GW 15 750	1/12	2400	1135
GW 15 750	1/12	2400	1176
GW 15 751	5/200	10800	1154
GW 15 762 H	1	200	1166
GW 15 783 A	1	200	1155
GW 15 784 A	1	200	1155
GW 15 785 A	1	200	1155
GW 15 786	1	200	1159
GW 15 787	1	320	1155
GW 15 794 H	1	200	1165
GW 15 795 H	1	200	1165
GW 15 796	1	200	1160
GW 15 797	1	200	1161
GW 15 799	1	200	1165
GW 15 799 H	1	200	1166
GW 15 819	2/48	4608	1130
GW 15 820	1/48	3744	1130
GW 15 826	1/12	1152	1132
GW 15 840	1/2	320	1126
GW 15 856	1/12	400	1131
GW 15 900	1	200	1166
GW 15 912	1/12	2400	829
GW 15 913	1/12	2400	829
GW 15 913	1/12	2400	1158
GW 15 914	1/12	1872	829
GW 15 914	1/12	1872	1158
GW 15 915	1/12	2400	829
GW 15 915	1/12	2400	1158
GW 15 916	1/12	2400	829
GW 15 916	1/12	2400	1158
GW 15 917	1/6	1200	829
GW 15 917	1/6	1200	1158
GW 15 918	1/6	1200	829
GW 15 918	1/6	1200	1158

GW 16

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 001 BR	12	1152	742
GW 16 001 BS	12	1152	744
GW 16 001 CP	12	1152	744
GW 16 001 CS	12	1152	743
GW 16 001 CY	12	1152	741
GW 16 001 DB	12	2304	742

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 001 DS	12	1152	741
GW 16 001 GR	12	1152	742
GW 16 001 NB	12	1152	741
GW 16 001 PW	12	1404	741
GW 16 001 SG	12	1152	743
GW 16 001 ST	12	1152	743
GW 16 002 BR	12	2304	742
GW 16 002 BS	12	1152	744
GW 16 002 CP	12	1152	744
GW 16 002 CS	12	1152	743
GW 16 002 CY	12	2304	741
GW 16 002 DB	12	2304	742
GW 16 002 DS	12	1152	741
GW 16 002 GR	12	2304	742
GW 16 002 NB	96	2304	741
GW 16 002 PW	96	2304	741
GW 16 002 SG	12	1152	743
GW 16 002 ST	12	2304	743
GW 16 003 BR	12	2304	742
GW 16 003 BS	12	2304	744
GW 16 003 CP	12	2304	744
GW 16 003 CS	12	2304	743
GW 16 003 CY	24	2304	741
GW 16 003 DB	24	2304	742
GW 16 003 DS	24	2304	741
GW 16 003 GR	24	2304	742
GW 16 003 NB	96	2304	741
GW 16 003 PW	96	2304	741
GW 16 003 SBR	1	342	749
GW 16 003 SBR	1	342	1137
GW 16 003 SBS	1	342	750
GW 16 003 SBS	1	342	1138
GW 16 003 SCP	1	342	750
GW 16 003 SCP	1	342	1138
GW 16 003 SCS	1	342	749
GW 16 003 SCS	1	342	1137
GW 16 003 SCY	1	342	747
GW 16 003 SCY	1	342	1136
GW 16 003 SDB	1	342	748
GW 16 003 SDB	1	342	1137
GW 16 003 SDS	1	342	748
GW 16 003 SDS	1	342	1136
GW 16 003 SG	12	2304	743
GW 16 003 SGR	1	342	748
GW 16 003 SGR	1	342	1137
GW 16 003 SNB	1	342	747
GW 16 003 SNB	1	342	1136
GW 16 003 SPW	1	570	747
GW 16 003 SPW	1	570	1136
GW 16 003 SSG	1	342	750
GW 16 003 SSG	1	342	1138
GW 16 003 SST	1	342	749
GW 16 003 SST	1	342	1137
GW 16 003 ST	12	2304	743
GW 16 004 BR	12	2304	742
GW 16 004 BS	12	1152	744
GW 16 004 CP	12	1152	744
GW 16 004 CS	12	1152	743

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 004 CY	12	2304	741
GW 16 004 DB	12	2304	742
GW 16 004 DS	12	1152	741
GW 16 004 GR	12	2304	742
GW 16 004 NB	12	2304	741
GW 16 004 PW	12	2304	741
GW 16 004 SBR	1	342	749
GW 16 004 SBR	1	342	1137
GW 16 004 SBS	1	342	750
GW 16 004 SBS	1	342	1138
GW 16 004 SCP	1	342	750
GW 16 004 SCP	1	342	1138
GW 16 004 SCS	1	342	749
GW 16 004 SCS	1	342	1137
GW 16 004 SCY	1	342	747
GW 16 004 SCY	1	342	1136
GW 16 004 SDB	1	342	748
GW 16 004 SDB	1	342	1137
GW 16 004 SDS	1	342	748
GW 16 004 SDS	1	342	1136
GW 16 004 SG	12	2304	743
GW 16 004 SGR	1	342	748
GW 16 004 SGR	1	342	1137
GW 16 004 SNB	1	342	747
GW 16 004 SNB	1	342	1136
GW 16 004 SPW	1	342	747
GW 16 004 SPW	1	342	1136
GW 16 004 SSG	1	342	750
GW 16 004 SSG	1	342	1138
GW 16 004 SST	1	342	749
GW 16 004 SST	1	342	1137
GW 16 004 ST	12	2304	743
GW 16 007 BR	6	1302	742
GW 16 007 BS	6	1302	744
GW 16 007 CP	6	744	744
GW 16 007 CS	6	744	743
GW 16 007 CY	6	1302	741
GW 16 007 DB	6	1302	742
GW 16 007 DS	6	744	741
GW 16 007 GR	6	1302	742
GW 16 007 NB	6	1302	741
GW 16 007 PW	6	1302	741
GW 16 007 SG	6	744	743
GW 16 007 ST	6	744	743
GW 16 022 BR	12	2304	711
GW 16 022 BS	12	1152	712
GW 16 022 CP	12	1152	712
GW 16 022 CS	12	1152	711
GW 16 022 CY	12	1152	709
GW 16 022 DB	12	2304	710
GW 16 022 DS	12	1152	710
GW 16 022 GR	12	2304	710
GW 16 022 NB	12	2304	709
GW 16 022 PW	12	2304	709
GW 16 022 SBR	1	256	717
GW 16 022 SBR	1	256	1140
GW 16 022 SBS	1	342	718
GW 16 022 SBS	1	342	1141

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 022 SCP	1	324	718
GW 16 022 SCP	1	324	1140
GW 16 022 SCS	1	324	717
GW 16 022 SCS	1	324	1140
GW 16 022 SCY	1	228	715
GW 16 022 SCY	1	228	1139
GW 16 022 SDB	1	252	716
GW 16 022 SDB	1	252	1139
GW 16 022 SDS	1	342	716
GW 16 022 SDS	1	342	1139
GW 16 022 SG	12	1152	712
GW 16 022 SGR	1	342	716
GW 16 022 SGR	1	342	1139
GW 16 022 SNB	1	256	715
GW 16 022 SNB	1	256	1139
GW 16 022 SPW	1	256	715
GW 16 022 SPW	1	256	1138
GW 16 022 SSG	1	256	718
GW 16 022 SSG	1	256	1140
GW 16 022 SST	1	342	717
GW 16 022 SST	1	342	1140
GW 16 022 ST	12	2304	711
GW 16 023 BR	12	936	711
GW 16 023 BS	12	936	712
GW 16 023 CP	12	936	712
GW 16 023 CS	12	936	711
GW 16 023 CY	12	936	709
GW 16 023 DB	12	936	710
GW 16 023 DS	12	936	710
GW 16 023 GR	12	936	710
GW 16 023 NB	12	936	709
GW 16 023 PW	12	1872	709
GW 16 023 SG	12	936	712
GW 16 023 ST	12	936	711
GW 16 024 BR	12	936	711
GW 16 024 BS	12	936	712
GW 16 024 CP	12	936	712
GW 16 024 CS	12	936	711
GW 16 024 CY	12	936	709
GW 16 024 DB	12	936	710
GW 16 024 DS	12	936	710
GW 16 024 GR	12	936	710
GW 16 024 NB	12	936	709
GW 16 024 PW	12	936	709
GW 16 024 SG	12	936	712
GW 16 024 ST	12	936	711
GW 16 026 BR	6	744	711
GW 16 026 BS	6	744	712
GW 16 026 CP	6	744	712
GW 16 026 CS	6	744	711
GW 16 026 CY	6	744	709
GW 16 026 DB	6	744	710
GW 16 026 DS	6	744	710
GW 16 026 GR	6	744	710
GW 16 026 NB	6	744	709
GW 16 026 PW	6	744	709
GW 16 026 SG	6	744	712
GW 16 026 ST	6	744	711

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 101 AB	12	2304	971
GW 16 101 TB	96	5760	729
GW 16 101 TC	12	2304	729
GW 16 101 TI	12	1152	729
GW 16 101 TN	12	1152	729
GW 16 101 VD	12	1152	731
GW 16 101 VL	12	2304	730
GW 16 101 VN	12	2304	730
GW 16 101 VO	12	1152	732
GW 16 101 VT	12	1152	731
GW 16 101 VW	96	2304	730
GW 16 101 VX	12	1152	732
GW 16 101 VZ	12	1152	731
GW 16 102 AB	12	2304	971
GW 16 102 TB	96	5760	729
GW 16 102 TC	12	2304	729
GW 16 102 TI	12	2304	729
GW 16 102 TN	12	2304	729
GW 16 102 VD	12	2304	731
GW 16 102 VL	12	2304	730
GW 16 102 VN	12	2304	730
GW 16 102 VO	12	1152	732
GW 16 102 VT	12	2304	731
GW 16 102 VW	96	2304	730
GW 16 102 VX	12	1152	732
GW 16 102 VZ	12	1152	731
GW 16 103 AB	12	2304	971
GW 16 103 TB	96	5760	729
GW 16 103 TC	24	2304	729
GW 16 103 TI	24	2304	729
GW 16 103 TN	24	2304	729
GW 16 103 VD	24	2304	731
GW 16 103 VL	24	2304	730
GW 16 103 VN	24	2304	730
GW 16 103 VO	12	1152	732
GW 16 103 VT	24	2304	731
GW 16 103 VW	96	2304	730
GW 16 103 VX	12	1152	732
GW 16 103 VZ	24	1536	731
GW 16 104 AB	12	2304	971
GW 16 104 TB	12	1920	729
GW 16 104 TC	12	1920	729
GW 16 104 TI	12	1920	729
GW 16 104 TN	12	1920	729
GW 16 104 VD	12	1152	731
GW 16 104 VL	12	2304	730
GW 16 104 VN	12	2304	730
GW 16 104 VO	12	936	732
GW 16 104 VT	12	1920	731
GW 16 104 VW	12	2304	730
GW 16 104 VX	12	936	732
GW 16 104 VZ	12	1152	731
GW 16 106 AB	6	1152	971
GW 16 106 TB	12	1152	729
GW 16 106 TC	6	1152	729
GW 16 106 TI	6	1152	729
GW 16 106 TN	6	1152	729
GW 16 106 VD	6	576	731

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 106 VL	6	1152	730
GW 16 106 VN	6	1152	730
GW 16 106 VO	6	576	732
GW 16 106 VT	6	1152	731
GW 16 106 VW	12	1152	730
GW 16 106 VX	6	576	732
GW 16 106 VZ	6	576	731
GW 16 108 TB	6	936	729
GW 16 108 VL	6	936	730
GW 16 108 VN	6	576	730
GW 16 108 VT	6	468	731
GW 16 108 VW	6	936	730
GW 16 109 TB	6	744	729
GW 16 112 TB	6	576	729
GW 16 112 VL	6	576	730
GW 16 112 VN	6	576	730
GW 16 112 VT	6	384	731
GW 16 112 VW	6	576	730
GW 16 122 AB	12	1920	971
GW 16 122 TB	12	1920	697
GW 16 122 TC	12	1920	697
GW 16 122 TI	12	1152	697
GW 16 122 TN	12	1920	697
GW 16 122 VD	12	1152	699
GW 16 122 VL	12	2304	698
GW 16 122 VN	12	1920	698
GW 16 122 VO	12	1152	700
GW 16 122 VT	12	2304	699
GW 16 122 VW	12	2304	698
GW 16 122 VX	12	1152	700
GW 16 122 VZ	12	1152	699
GW 16 123 AB	12	1152	971
GW 16 123 TB	12	1872	697
GW 16 123 TC	12	936	697
GW 16 123 TI	12	936	697
GW 16 123 TN	12	936	697
GW 16 123 VD	12	936	699
GW 16 123 VL	12	936	698
GW 16 123 VN	12	1872	698
GW 16 123 VO	12	936	700
GW 16 123 VT	12	936	699
GW 16 123 VW	12	936	698
GW 16 123 VX	12	936	700
GW 16 123 VZ	12	936	699
GW 16 124 AB	12	1152	971
GW 16 124 TB	12	936	697
GW 16 124 TC	12	936	697
GW 16 124 TI	12	936	697
GW 16 124 TN	12	1872	697
GW 16 124 VD	12	936	699
GW 16 124 VL	12	936	698
GW 16 124 VN	12	1872	698
GW 16 124 VO	12	936	700
GW 16 124 VT	12	936	699
GW 16 124 VW	12	936	698
GW 16 124 VX	12	936	700
GW 16 124 VZ	12	936	699
GW 16 126 AB	6	744	971

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 126 TB	6	930	697
GW 16 126 TC	6	486	697
GW 16 126 TI	6	648	697
GW 16 126 TN	6	744	697
GW 16 126 VD	6	744	699
GW 16 126 VL	6	744	698
GW 16 126 VN	6	1302	698
GW 16 126 VO	6	744	700
GW 16 126 VT	6	744	699
GW 16 126 VW	6	744	698
GW 16 126 VX	6	744	700
GW 16 126 VZ	6	744	699
GW 16 127 AB	6	744	971
GW 16 127 TB	6	900	697
GW 16 127 TC	6	486	697
GW 16 127 TI	6	450	697
GW 16 127 TN	6	900	697
GW 16 127 VD	6	744	699
GW 16 127 VL	6	744	698
GW 16 127 VN	6	744	698
GW 16 127 VO	6	744	700
GW 16 127 VT	6	900	699
GW 16 127 VW	6	744	698
GW 16 127 VX	6	744	700
GW 16 127 VZ	6	744	699
GW 16 128 TB	1	600	697
GW 16 128 TC	1	342	697
GW 16 128 TI	1	360	697
GW 16 128 TN	1	684	697
GW 16 128 VD	1	360	699
GW 16 128 VL	1	360	698
GW 16 128 VN	12	600	698
GW 16 128 VO	1	360	700
GW 16 128 VT	1	360	699
GW 16 128 VW	1	360	698
GW 16 128 VX	1	360	700
GW 16 128 VZ	1	360	699
GW 16 129 TB	1	570	697
GW 16 129 TC	1	342	697
GW 16 129 TI	1	342	697
GW 16 129 TN	1	570	697
GW 16 129 VD	1	360	699
GW 16 129 VL	1	360	698
GW 16 129 VN	6	300	698
GW 16 129 VO	1	360	700
GW 16 129 VT	1	342	699
GW 16 129 VW	1	360	698
GW 16 129 VX	1	360	700
GW 16 129 VZ	1	360	699
GW 16 202 GP	1	256	760
GW 16 202 GT	1	256	760
GW 16 202 TB	12	1152	754
GW 16 202 TN	12	1152	754
GW 16 202 VA	6	1476	755
GW 16 202 VT	12	1152	755
GW 16 202 WK	1	256	759
GW 16 202 WS	6	1230	758
GW 16 202 WU	1	256	759

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 202 XA	6	1476	757
GW 16 202 XE	6	1722	757
GW 16 202 XF	6	1230	757
GW 16 202 XG	6	738	758
GW 16 202 XL	6	1476	756
GW 16 202 XM	6	1476	756
GW 16 202 XP	6	738	756
GW 16 202 XQ	6	738	758
GW 16 202 XR	6	738	757
GW 16 202 XS	6	738	757
GW 16 202 XV	6	738	756
GW 16 202 XW	6	1722	756
GW 16 202 YA	12	1152	755
GW 16 202 YB	12	1152	754
GW 16 202 YN	12	768	754
GW 16 202 YT	12	1152	755
GW 16 203 GP	1	256	760
GW 16 203 GT	1	256	760
GW 16 203 TB	12	1152	754
GW 16 203 TN	12	1152	754
GW 16 203 VA	6	1230	755
GW 16 203 VT	12	1152	755
GW 16 203 WK	1	256	759
GW 16 203 WS	6	1476	758
GW 16 203 WU	1	256	759
GW 16 203 XA	6	1476	757
GW 16 203 XE	6	1476	757
GW 16 203 XF	6	1476	757
GW 16 203 XG	6	1476	758
GW 16 203 XL	6	1476	756
GW 16 203 XM	6	1476	756
GW 16 203 XP	6	1476	756
GW 16 203 XQ	6	738	758
GW 16 203 XR	6	738	757
GW 16 203 XS	6	738	757
GW 16 203 XV	6	738	756
GW 16 203 XW	6	1476	756
GW 16 203 YA	12	1152	755
GW 16 203 YB	12	1152	754
GW 16 203 YN	12	768	754
GW 16 203 YT	12	1152	755
GW 16 204 GP	1	256	760
GW 16 204 GT	1	256	760
GW 16 204 TB	12	1152	754
GW 16 204 TN	12	1152	754
GW 16 204 VA	6	1476	755
GW 16 204 VT	12	1152	755
GW 16 204 WK	1	256	759
GW 16 204 WS	6	1476	758
GW 16 204 WU	1	256	759
GW 16 204 XA	6	1476	757
GW 16 204 XE	6	738	757
GW 16 204 XF	6	1476	757
GW 16 204 XG	6	738	758
GW 16 204 XL	6	1476	756
GW 16 204 XM	6	1476	756
GW 16 204 XP	6	1476	756
GW 16 204 XQ	6	738	758

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 204 XR	6	738	757
GW 16 204 XS	6	738	757
GW 16 204 XV	6	738	756
GW 16 204 XW	6	1476	756
GW 16 204 YA	12		755
GW 16 204 YB	12	1152	754
GW 16 204 YN	12	768	754
GW 16 204 YT	12	1152	755
GW 16 206 GP	1	192	760
GW 16 206 GT	1	192	760
GW 16 206 TB	6	960	754
GW 16 206 TN	6	960	754
GW 16 206 VA	6	960	755
GW 16 206 VT	6	960	755
GW 16 206 WK	1	192	759
GW 16 206 WS	6	960	758
GW 16 206 WU	1	192	759
GW 16 206 XA	6	1152	757
GW 16 206 XE	6	576	757
GW 16 206 XF	6	1152	757
GW 16 206 XG	6	576	758
GW 16 206 XL	6	960	756
GW 16 206 XM	6	1152	756
GW 16 206 XP	6	576	756
GW 16 206 XQ	6	576	758
GW 16 206 XR	6	576	757
GW 16 206 XS	6	576	757
GW 16 206 XV	6	576	756
GW 16 206 XW	6	1152	756
GW 16 206 YA	6	702	755
GW 16 206 YB	6	1152	754
GW 16 206 YN	6	1152	754
GW 16 206 YT	6	1152	755
GW 16 222 TB	12	1920	722
GW 16 222 TN	12	1920	722
GW 16 222 VA	12	1920	723
GW 16 222 VT	12	1920	723
GW 16 222 WS	1	256	725
GW 16 222 XG	1	256	725
GW 16 222 XL	1	256	724
GW 16 222 XM	1	256	724
GW 16 222 XQ	1	256	726
GW 16 222 XS	1	256	725
GW 16 222 XW	1	256	724
GW 16 222 YA	12	1152	723
GW 16 222 YB	12	1152	722
GW 16 222 YN	12	1152	722
GW 16 222 YT	12	1152	723
GW 16 223 TB	6	960	722
GW 16 223 TN	6	576	722
GW 16 223 VA	6	576	723
GW 16 223 VT	6	576	723
GW 16 223 WS	1	192	725
GW 16 223 XG	1	192	725
GW 16 223 XL	1	192	724
GW 16 223 XM	1	192	724
GW 16 223 XQ	1	192	726
GW 16 223 XS	1	192	725
GW 16 223 XW	1	192	724
GW 16 223 YA	6	384	723
GW 16 223 YB	6	576	722
GW 16 223 YN	6	576	722
GW 16 223 YT	6	576	723
GW 16 224 TB	6	576	722
GW 16 224 TN	6	558	722
GW 16 224 VA	6	576	723
GW 16 224 VT	6	576	723
GW 16 224 WS	1	192	725
GW 16 224 XG	1	192	725
GW 16 224 XL	1	192	724
GW 16 224 XM	1	192	724
GW 16 224 XQ	1	192	726
GW 16 224 XS	1	192	725
GW 16 224 XW	1	192	724
GW 16 224 YA	6	576	723
GW 16 224 YB	6	576	722
GW 16 224 YN	6	576	722
GW 16 224 YT	6	576	723
GW 16 226 TB	1	360	722
GW 16 226 TN	1	486	722
GW 16 226 VA	1	360	723
GW 16 226 VT	1	360	723
GW 16 226 WS	1	160	725
GW 16 226 XG	1	160	725
GW 16 226 XL	1	160	724
GW 16 226 XM	1	128	724
GW 16 226 XQ	1	160	726
GW 16 226 XS	1	160	725
GW 16 226 XW	1	160	724
GW 16 226 YA	1	3600	723
GW 16 226 YB	1	360	722
GW 16 226 YN	1	360	722
GW 16 226 YT	1	360	723
GW 16 227 TB	1	360	722
GW 16 227 TN	1	720	722
GW 16 227 VA	1	720	723
GW 16 227 VT	1	810	723
GW 16 227 WS	1	160	725
GW 16 227 XG	1	160	725
GW 16 227 XL	1	160	724
GW 16 227 XM	1	128	724
GW 16 227 XQ	1	160	726
GW 16 227 XS	1	160	725
GW 16 227 XW	1	160	724
GW 16 227 YA	1	288	723
GW 16 227 YB	1	360	722
GW 16 227 YN	1	360	722
GW 16 227 YT	1	360	723
GW 16 228 TB	1	360	722
GW 16 228 TN	1	342	722
GW 16 228 VA	1	384	723
GW 16 228 VT	1	684	723
GW 16 228 WS	1	160	725
GW 16 228 XG	1	160	725
GW 16 228 XL	1	160	724
GW 16 228 XM	1	160	724
GW 16 228 XQ	1	160	726
GW 16 228 XS	1	160	725
GW 16 228 XW	1	160	724
GW 16 228 YA	1	288	723
GW 16 228 YB	1	360	722
GW 16 228 YN	1	360	722
GW 16 228 YT	1	360	723
GW 16 229 TB	1	570	722
GW 16 229 TN	1	570	722
GW 16 229 VA	1	570	723
GW 16 229 VT	1	570	723
GW 16 229 WS	1	160	725
GW 16 229 XG	1	160	725
GW 16 229 XL	1	160	724
GW 16 229 XM	1	160	724
GW 16 229 XQ	1	160	726
GW 16 229 XS	1	160	725
GW 16 229 XW	1	160	724
GW 16 229 YA	1	288	723
GW 16 229 YB	1	360	722
GW 16 229 YN	1	360	722
GW 16 229 YT	1	360	723
GW 16 401 TB	96	2304	735
GW 16 401 TC	24	1536	735
GW 16 401 TI	24	1536	735
GW 16 401 TN	24	2304	735
GW 16 401 VD	24	1536	737
GW 16 401 VL	12	2304	736
GW 16 401 VN	24	2304	736
GW 16 401 VO	12	1152	738
GW 16 401 VT	24	1536	737
GW 16 401 VW	96	2304	736
GW 16 401 VX	12	1152	738
GW 16 401 VZ	24	1536	737
GW 16 402 TB	96	5760	735
GW 16 402 TC	12	2304	735
GW 16 402 TI	12	2304	735
GW 16 402 TN	12	2304	735
GW 16 402 VD	12	1152	737
GW 16 402 VL	12	2304	736
GW 16 402 VN	12	1536	736
GW 16 402 VO	12	1152	738
GW 16 402 VT	12	2304	737
GW 16 402 VW	96	2304	736
GW 16 402 VX	12	1152	738
GW 16 402 VZ	12	2304	737
GW 16 403 TB	96	5760	735
GW 16 403 TC	24	2304	735
GW 16 403 TI	24	2304	735
GW 16 403 TN	24	2304	735
GW 16 403 VD	24	1536	737
GW 16 403 VL	12	2304	736
GW 16 403 VN	24	2304	736
GW 16 403 VO	12	2304	738
GW 16 403 VT	24	2304	737
GW 16 403 VW	96	2304	736
GW 16 403 VX	12	1152	738
GW 16 403 VZ	24	1536	737

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 404 TB	12	2304	735
GW 16 404 TC	12	2304	735
GW 16 404 TI	12	2304	735
GW 16 404 TN	12	2304	735
GW 16 404 VD	12	1152	737
GW 16 404 VL	12	2304	736
GW 16 404 VN	12	2304	736
GW 16 404 VO	12	1152	738
GW 16 404 VT	12	2304	737
GW 16 404 VW	12	2304	736
GW 16 404 VX	12	1152	738
GW 16 404 VZ	12	2304	737
GW 16 406 TB	12	1152	735
GW 16 406 TC	6	1152	735
GW 16 406 TI	6	1152	735
GW 16 406 TN	6	1152	735
GW 16 406 VD	6	576	737
GW 16 406 VL	6	1152	736
GW 16 406 VN	6	1152	736
GW 16 406 VO	6	576	738
GW 16 406 VT	6	1152	737
GW 16 406 VW	12	1152	736
GW 16 406 VX	6	576	738
GW 16 406 VZ	6	576	737
GW 16 422 TB	12	1920	703
GW 16 422 TC	12	1152	703
GW 16 422 TI	12	1920	703
GW 16 422 TN	12	1920	703
GW 16 422 VD	12	1152	705
GW 16 422 VL	12	2304	704
GW 16 422 VN	12	1920	704
GW 16 422 VO	12	1152	706
GW 16 422 VT	12	2304	705
GW 16 422 VW	12	2304	704
GW 16 422 VX	12	1152	706
GW 16 422 VZ	12	1152	705
GW 16 423 TB	12	1872	703
GW 16 423 TC	12	936	703
GW 16 423 TI	12	936	703
GW 16 423 TN	12	936	703
GW 16 423 VD	12	936	705
GW 16 423 VL	12	936	704
GW 16 423 VN	12	1872	704
GW 16 423 VO	12	936	706
GW 16 423 VT	12	936	705
GW 16 423 VW	12	936	704
GW 16 423 VX	12	936	706
GW 16 423 VZ	12	936	705
GW 16 424 TB	12	936	703
GW 16 424 TC	12	936	703
GW 16 424 TI	12	936	703
GW 16 424 TN	12	936	703
GW 16 424 VD	12	936	705
GW 16 424 VL	12	936	704
GW 16 424 VN	12	936	704
GW 16 424 VO	12	936	706
GW 16 424 VT	12	936	705
GW 16 424 VW	12	936	704
GW 16 424 VX	12	936	706
GW 16 424 VZ	12	936	705
GW 16 426 TB	6	558	703
GW 16 426 TC	6	486	703
GW 16 426 TI	6	900	703
GW 16 426 TN	6	744	703
GW 16 426 VD	6	744	705
GW 16 426 VL	6	744	704
GW 16 426 VN	6	486	704
GW 16 426 VO	6	744	706
GW 16 426 VT	6	744	705
GW 16 426 VW	6	744	704
GW 16 426 VX	6	744	706
GW 16 426 VZ	6	744	705
GW 16 427 TB	6	486	703
GW 16 427 TC	6	486	703
GW 16 427 TI	6	486	703
GW 16 427 TN	6	486	703
GW 16 427 VD	6	744	705
GW 16 427 VL	6	744	704
GW 16 427 VN	6	558	704
GW 16 427 VO	6	744	706
GW 16 427 VT	6	486	705
GW 16 427 VW	6	744	704
GW 16 427 VX	6	744	706
GW 16 427 VZ	6	744	705
GW 16 502	5/80	1200	771
GW 16 503	3/60	960	771
GW 16 504	1/40	600	771
GW 16 512	5/60	900	771
GW 16 513	2/40	600	771
GW 16 514	1/30	480	771
GW 16 702 TBN	1/24		769
GW 16 702 TNN	1/12		769
GW 16 702 VTN	1/12		769
GW 16 703 TBN	1/24		769
GW 16 703 TNN	1/12		769
GW 16 703 VTN	1/12		769
GW 16 704 TBN	1/24		769
GW 16 704 TNN	1/12		769
GW 16 704 VTN	1/12		769
GW 16 711 TB	1/48	768	769
GW 16 711 TN	1/24	768	769
GW 16 711 VT	1/12	900	769
GW 16 712 TB	1/24	576	769
GW 16 712 TN	1/24	288	769
GW 16 712 VT	1/12	504	769
GW 16 723 TB	1/24	2016	770
GW 16 723 TN	1/12	936	770
GW 16 724 TB	1/24	2304	770
GW 16 724 TN	1/12	1152	770
GW 16 743	3/60	900	321
GW 16 743	3/60	900	770
GW 16 744	1/30	240	321
GW 16 744	1/30	240	770
GW 16 752	1/30	960	321
GW 16 752	1/30	960	770
GW 16 753	1/15	240	321
GW 16 753	1/15	240	770
GW 16 754	1/15	180	321
GW 16 754	1/15	180	770
GW 16 773	3/30	480	321
GW 16 773	3/30	480	770
GW 16 774	1/30	480	321
GW 16 774	1/30	480	770
GW 16 782	1/30	480	321
GW 16 782	1/30	480	770
GW 16 783	1/15	360	321
GW 16 783	1/15	360	770
GW 16 784	1/15	240	321
GW 16 784	1/15	240	770
GW 16 802	12/120	7200	773
GW 16 803	12/240	8640	773
GW 16 803 N	6/240	2400	772
GW 16 803 N	6/240	2400	1141
GW 16 804	12/120	7200	773
GW 16 804 N	6/120	2160	772
GW 16 804 N	6/120	2160	1141
GW 16 806	12/72	2592	773
GW 16 807 N	12/72	720	773
GW 16 808	12/48	768	773
GW 16 812	12/48	768	773
GW 16 821	12/120	2880	772
GW 16 821 N	20/120	960	772
GW 16 821 N	20/120	960	1141
GW 16 822	20/120	6720	772
GW 16 822 N	20/120	960	772
GW 16 822 N	20/120	960	1141
GW 16 823	12/120	2880	772
GW 16 824	12/60	2340	772
GW 16 825	12/48	1152	772
GW 16 841	5/300	2400	536
GW 16 841	5/300	2400	774
GW 16 841	5/300	2400	1135
GW 16 842	5/150	1200	536
GW 16 842	5/150	1200	774
GW 16 842	5/150	1200	1135
GW 16 843	5/50	800	536
GW 16 843	5/50	800	774
GW 16 843	5/50	800	1135
GW 16 854	1/30	240	770
GW 16 856	1/15	180	770
GW 16 864	1/30	480	770
GW 16 866	1/15	180	770
GW 16 871	60/480	15360	773
GW 16 871	60/480	15360	1142
GW 16 873	120/480	9600	773
GW 16 873	120/480	9600	1142
GW 16 874	60/240	3840	773
GW 16 874	60/240	3840	1142
GW 16 876	60/240	3840	773
GW 16 877 N	60/240	2160	773
GW 16 891 CB	1	320	1168
GW 16 891 CL	1	400	1168
GW 16 891 CN	1		1168
GW 16 891 CT	1	200	1168

Code	Quantity		Page
	Pack/carton	Pallet	
GW 16 892 CB	1	320	1169
GW 16 892 CL	1	400	1169
GW 16 892 CN	1	100	1169
GW 16 892 CT	1	200	1169
GW 16 893 CN	1	40	1169
GW 16 899	10/40		1169
GW 16 902 CB	1	512	763
GW 16 902 CL	1	256	763
GW 16 902 CN	1	256	764
GW 16 902 CT	1	256	764
GW 16 903 CB	1	512	763
GW 16 903 CL	1	256	763
GW 16 903 CN	1	512	764
GW 16 903 CT	1	512	764
GW 16 904 CB	1	480	763
GW 16 904 CL	1	256	763
GW 16 904 CN	1	384	764
GW 16 904 CT	1	384	764
GW 16 906 CB			763
GW 16 906 CL	1	192	763
GW 16 906 CN	1	384	764
GW 16 906 CT	1	192	764
GW 16 946 CB	1	512	766
GW 16 946 CB	1	512	1153
GW 16 946 CL	1	384	766
GW 16 946 CL	1	384	1153
GW 16 946 CN	1	384	766
GW 16 946 CN	1	384	1153
GW 16 946 CT	1	256	766
GW 16 946 CT	1	256	1153
GW 16 950	12	936	1153
GW 16 955 CB	1	256	765
GW 16 955 CB	1	256	797
GW 16 955 CB	1	256	831
GW 16 955 CL	1	256	765
GW 16 955 CL	1	256	865
GW 16 955 CN	1	256	765
GW 16 955 CN	1	256	899
GW 16 955 CT	1	256	765
GW 16 955 CT	1	256	933
GW 16 970 CB	1	256	816
GW 16 970 CB	1	256	850
GW 16 970 CB	1	256	1019
GW 16 970 CB	1	256	1135
GW 16 970 CL	1/16		884
GW 16 970 CL	1/16		1135
GW 16 970 CN	1	256	918
GW 16 970 CN	1	256	1046
GW 16 970 CN	1	256	1135
GW 16 970 CT	1	256	952
GW 16 970 CT	1	256	1135
GW 16 974 CB	1	128	1166
GW 16 974 CL	1	128	1166
GW 16 974 CN	1	128	1166
GW 16 974 CT	1	128	1166
GW 16 976 CB	1	256	1167
GW 16 976 CL	1/16		1167
GW 16 976 CN	1	512	1167
GW 16 976 CT	1	512	1167

GW 20

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 005	15/30	2100	1004
GW 20 008	15/30	2100	1004
GW 20 024	20/40	4800	1005
GW 20 056	10/480	46080	1006
GW 20 058	60/120	4320	1006
GW 20 071	1/5	1560	1007
GW 20 072	1/5	780	1007
GW 20 073	30/60	2400	1006
GW 20 074	1/5	1560	1007
GW 20 076	1/5	1560	1007
GW 20 201	80/160	19200	1008
GW 20 203	80/320	19200	1008
GW 20 205	30/60	7200	1008
GW 20 206	30/60	3000	1009
GW 20 207	30/60	3000	1009
GW 20 208	30/60	2400	1009
GW 20 209	30/60	2400	1009
GW 20 212	30/60	4320	1009
GW 20 214	30/60	4320	1009
GW 20 216	30/60	2280	1009
GW 20 220	40/80	14560	1010
GW 20 228	30/60	4320	1012
GW 20 229	30/60	2280	1012
GW 20 230	30/60	2280	1012
GW 20 234	15/30	3240	1012
GW 20 235	15/30	1920	1013
GW 20 238	20/40	1200	1015
GW 20 239	15/30	1920	1012
GW 20 241	15/30	3840	1013
GW 20 243	15/30	2160	1014
GW 20 246	30/120	7200	536
GW 20 246	30/120	7200	1008
GW 20 248	30/60	2400	1010
GW 20 251	15/30	3360	1013
GW 20 265	30/120	7200	1008
GW 20 266	1/120	3600	1014
GW 20 267	1/120	6000	1014
GW 20 270	1/120	6000	1014
GW 20 271	15/30	2160	1014
GW 20 272	15/30	3780	1013
GW 20 277	50/200		807
GW 20 277	50/200		808
GW 20 277	50/200		841
GW 20 277	50/200		842
GW 20 277	50/200		875
GW 20 277	50/200		876
GW 20 277	50/200		909
GW 20 277	50/200		910
GW 20 277	50/200		943
GW 20 277	50/200		944
GW 20 277	50/200		1012
GW 20 277	50/200		1012
GW 20 277	50/200		1040
GW 20 277	50/200		1040
GW 20 277	50/200		1086
GW 20 277	50/200		1087

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 281	30/60	4560	1010
GW 20 281	30/60	4560	1039
GW 20 282	15/30	2160	1011
GW 20 282	15/30	2160	1039
GW 20 283	15/30	2160	1011
GW 20 283	15/30	2160	1039
GW 20 286	30/60	2160	1010
GW 20 286	30/60	2160	1039
GW 20 287	15/30	1140	1011
GW 20 287	15/30	1140	1039
GW 20 288	15/30	2160	1011
GW 20 288	15/30	2160	1039
GW 20 291	30/60	2400	1008
GW 20 295	80/320	6400	1010
GW 20 295	80/320	6400	1039
GW 20 296	30/60	3000	1011
GW 20 296	30/60	3000	1039
GW 20 297	15/30	2160	1011
GW 20 297	15/30	2160	1039
GW 20 298	40/80	4000	1011
GW 20 298	40/80	4000	1040
GW 20 299	40/80	2880	1011
GW 20 299	40/80	2880	1040
GW 20 312	15/30	2160	1011
GW 20 312	15/30	2160	1039
GW 20 320	30/60	4320	1010
GW 20 351	30/60	4320	1009
GW 20 356	30/60	2400	1010
GW 20 357	30/60	1200	1010
GW 20 363	1/10	1800	1015
GW 20 381	15/30	3360	1012
GW 20 382	15/30	3360	1012
GW 20 386	15/30	4320	1012
GW 20 391	15/30	3360	1012
GW 20 392	15/30	1920	1012
GW 20 396	15/30	1920	1012
GW 20 401	30/60	4320	1017
GW 20 423	1/14	4368	1017
GW 20 431	15/30	2100	1016
GW 20 432	15/30	2100	1016
GW 20 433	15/30	2700	1016
GW 20 434	15/30	2100	1016
GW 20 435	15/30	2700	1016
GW 20 436	15/30	2700	1016
GW 20 437	1/15	1080	1016
GW 20 438	1/15	2160	1016
GW 20 439	1/15	1890	1016
GW 20 448	1/15	1080	1016
GW 20 449	1/15	1890	1016
GW 20 450	1/15	1890	1016
GW 20 454	15/30	1260	1016
GW 20 454	15/30	1260	1044
GW 20 455	15/30	1260	1016
GW 20 455	15/30	1260	1044
GW 20 456	15/30	1260	1016
GW 20 456	15/30	1260	1044
GW 20 503	30/60	4320	1004
GW 20 504	30/60	4320	1004

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 510	80/160	8000	1005
GW 20 511	15/30	4320	1005
GW 20 512	30/60	4320	1005
GW 20 513	15/30	3780	1005
GW 20 514	15/30	2880	1005
GW 20 515	30/60	4320	1005
GW 20 516	30/60	4320	1005
GW 20 517	30/60	4320	1005
GW 20 518	20/40	2000	1005
GW 20 519	15/30	3780	1005
GW 20 520	15/30	4320	1005
GW 20 521	30/60	4320	1005
GW 20 522	30/60	4320	1005
GW 20 523	30/60	4320	1005
GW 20 527	15/30	2160	1006
GW 20 528	30/60	4320	1005
GW 20 529	30/60	4320	1005
GW 20 530	15/30	1260	1005
GW 20 531	15/30	3780	1005
GW 20 533	20	45600	1006
GW 20 533	20	45600	1034
GW 20 537	20	45600	1006
GW 20 537	20	45600	1034
GW 20 538	20	45600	1006
GW 20 538	20	45600	1034
GW 20 539	20	45600	1006
GW 20 539	20	45600	1034
GW 20 540	20	45600	1006
GW 20 540	20	45600	1034
GW 20 542	20	45600	1006
GW 20 542	20	45600	1034
GW 20 549	20	45600	1006
GW 20 549	20	45600	1034
GW 20 550	20	45600	1006
GW 20 550	20	45600	1034
GW 20 551	20	45600	1006
GW 20 551	20	45600	1034
GW 20 559	30/60	4320	1005
GW 20 560	30/60	4320	1005
GW 20 561	20	45600	1006
GW 20 561	20	45600	1034
GW 20 562	20	45600	1006
GW 20 562	20	45600	1034
GW 20 563	20	45600	1006
GW 20 563	20	45600	1034
GW 20 564	20	45600	1006
GW 20 564	20	45600	1034
GW 20 565	20	45600	1006
GW 20 565	20	45600	1034
GW 20 566	20	45600	1006
GW 20 566	20	45600	1034
GW 20 567	20	45600	1006
GW 20 567	20	45600	1034
GW 20 568	20	45600	1006
GW 20 568	20	45600	1034
GW 20 569	20	45600	1006
GW 20 569	20	45600	1034
GW 20 570	20	45600	1006

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 570	20	45600	1034
GW 20 571	80/320	19200	1004
GW 20 572	30/60	4320	1004
GW 20 576	80/320	19200	1004
GW 20 577	30/60	4320	1004
GW 20 579	30/60	4320	1004
GW 20 580	1/15	1890	1006
GW 20 583	30/60	2160	1004
GW 20 584	30/60	4320	1004
GW 20 585	15/30	2700	1004
GW 20 588	30/60	4320	1004
GW 20 589	15/30	2160	1006
GW 20 591	15/30	2160	1005
GW 20 592	20	45600	1006
GW 20 592	20	45600	1034
GW 20 593	20	45600	1006
GW 20 593	20	45600	1034
GW 20 594	20	45600	1006
GW 20 594	20	45600	1034
GW 20 595	20	45600	1006
GW 20 595	20	45600	1034
GW 20 596	20	45600	1006
GW 20 596	20	45600	1034
GW 20 597	20	45600	1006
GW 20 597	20	45600	1034
GW 20 601	15/30	900	1022
GW 20 601	15/30	900	1048
GW 20 602	1/12	684	1022
GW 20 602	1/12	684	1048
GW 20 603	30/60	4320	1021
GW 20 604	30/60	4320	1021
GW 20 605	30/60	2280	1021
GW 20 606	30/60	4320	1021
GW 20 607	15/30	1920	1021
GW 20 608	15/30	1920	1021
GW 20 613	15/30	2100	1021
GW 20 616	15/30	2100	1021
GW 20 617	15/30	2100	1021
GW 20 620	15/30	2100	1021
GW 20 622	15/30	3960	1022
GW 20 622	15/30	3960	1048
GW 20 623	15/30	900	1022
GW 20 623	15/30	900	1048
GW 20 626	15/30	900	1022
GW 20 626	15/30	900	1048
GW 20 627	1/12	432	1022
GW 20 627	1/12	432	1048
GW 20 628	1/12	432	1022
GW 20 628	1/12	432	1048
GW 20 631	30/60	2280	1021
GW 20 634	1/15	1080	1022
GW 20 651	30/60	2160	1024
GW 20 656	15/30	1140	1024
GW 20 684	1/15	1890	1014
GW 20 685	15/30	2160	1014
GW 20 686	15/30	2160	1014
GW 20 802	1/14	4368	1018
GW 20 803	1/14	3920	1018

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 810	1/4	1248	1018
GW 20 811	1/14	4368	1018
GW 20 820	1/2	624	1024
GW 20 821	1/6	1872	1007
GW 20 825	1/2	144	1018
GW 20 828	1/14	2184	1018
GW 20 833	1/4	1248	536
GW 20 833	1/4	1248	1020
GW 20 835	1/14	4368	1020
GW 20 841	1/4	448	1024
GW 20 852	1/2	272	1019
GW 20 853	1/2	144	1019
GW 20 901	1/100	19500	820
GW 20 901	1/100	19500	854
GW 20 901	1/100	19500	888
GW 20 901	1/100	19500	922
GW 20 901	1/100	19500	956
GW 20 901	1/100	19500	1026
GW 20 901	1/100	19500	1052
GW 20 901	1/100	19500	1092
GW 20 902	50	10000	820
GW 20 902	50	10000	854
GW 20 902	50	10000	888
GW 20 902	50	10000	922
GW 20 902	50	10000	956
GW 20 902	50	10000	1025
GW 20 902	50	10000	1052
GW 20 902	50	10000	1091
GW 20 903	50	15600	820
GW 20 903	50	15600	854
GW 20 903	50	15600	888
GW 20 903	50	15600	922
GW 20 903	50	15600	956
GW 20 903	50	15600	1025
GW 20 903	50	15600	1052
GW 20 903	50	15600	1091
GW 20 904	50	9750	1025
GW 20 904	50	9750	1052
GW 20 904	50	9750	1091
GW 20 905	50	9750	1025
GW 20 905	50	9750	1052
GW 20 905	50	9750	1091
GW 20 906	50	15600	1025
GW 20 906	50	15600	1052
GW 20 906	50	15600	1091
GW 20 908	50	15600	1025
GW 20 908	50	15600	1052
GW 20 908	50	15600	1091
GW 20 911	20/200	20000	1026
GW 20 911	20/200	20000	1052
GW 20 911	20/200	20000	1092
GW 20 921	10/200	20000	1026
GW 20 921	10/200	20000	1052
GW 20 921	10/200	20000	1092
GW 20 922	10/200	20000	1026
GW 20 922	10/200	20000	1052
GW 20 922	10/200	20000	1092
GW 20 923	10/200	20000	1026

Code	Quantity		Page
	Pack/carton	Pallet	
GW 20 923	10/200	20000	1052
GW 20 923	10/200	20000	1092
GW 20 924	10/200	20000	1026
GW 20 924	10/200	20000	1052
GW 20 924	10/200	20000	1092
GW 20 925	10/200	20000	1026
GW 20 925	10/200	20000	1052
GW 20 925	10/200	20000	1092
GW 21			
GW 21 005	15/30	1260	1032
GW 21 008	15/30	1260	1032
GW 21 024	20/40	1200	1033
GW 21 056	10/480	46080	1034
GW 21 058	60/120	2880	1034
GW 21 071	1/5	780	1035
GW 21 072	1/5	780	1035
GW 21 073	30/60	2400	1034
GW 21 074	1/5	780	1035
GW 21 076	1/5	780	1035
GW 21 201	80/160	8000	1036
GW 21 203	80/320	19200	1036
GW 21 205	30/60	3000	1036
GW 21 206	30/60	1800	1037
GW 21 207	30/60	3000	1037
GW 21 208	30/60	1200	1037
GW 21 209	30/60	2160	1037
GW 21 212	30/60	4320	1037
GW 21 214	30/60	4320	1038
GW 21 216	30/60	2280	1038
GW 21 220	30/60	3000	1038
GW 21 228	30/60	4320	1041
GW 21 229	30/60	2280	1041
GW 21 230	30/60	2280	1041
GW 21 234	15/30	1920	1041
GW 21 235	15/30	1920	1042
GW 21 238	20/40	1200	1043
GW 21 239	15/30	1920	1041
GW 21 241	15/30	1920	1041
GW 21 243	15/30	3780	1042
GW 21 246	30/120	7200	1036
GW 21 248	30/60	1200	1038
GW 21 251	15/30	3360	1041
GW 21 265	30/60	3000	1037
GW 21 266	1/120	3600	1042
GW 21 267	1/120	3600	1042
GW 21 270	1/120	6000	1042
GW 21 271	15/30	2160	1042
GW 21 272	15/30	1920	1042
GW 21 291	30/60	1200	1036
GW 21 351	30/60	2280	1037
GW 21 356	30/60	1200	1038
GW 21 357	30/60	1200	1038
GW 21 381	15/30	3360	1040
GW 21 382	15/30	3360	1040
GW 21 386	15/30	3360	1040
GW 21 391	15/30	1920	1040
GW 21 392	15/30	1920	1040
GW 21 396	15/30	1920	1040

Code	Quantity		Page
	Pack/carton	Pallet	
GW 21 401	30/60	4320	1044
GW 21 423	1/14	2184	1044
GW 21 431	15/30	1260	1043
GW 21 432	15/30	1260	1043
GW 21 433	15/30	1260	1043
GW 21 434	15/30	1260	1043
GW 21 435	15/30	2520	1043
GW 21 436	15/30	2100	1043
GW 21 437	1/15	1080	1044
GW 21 438	1/15	2160	1044
GW 21 439	1/15	1890	1044
GW 21 448	1/15	1080	1044
GW 21 449	1/15	1080	1044
GW 21 450	1/15	1080	1044
GW 21 503	30/60	4320	1032
GW 21 504	30/60	4320	1032
GW 21 510	80/160	8000	1033
GW 21 511	15/30	1920	1033
GW 21 512	15/30	3360	1033
GW 21 513	15/30	3360	1033
GW 21 514	15/30	1920	1033
GW 21 515	30/60	4320	1033
GW 21 516	30/60	2280	1033
GW 21 517	30/60	2280	1033
GW 21 518	20/40	2000	1033
GW 21 519	15/30	1920	1033
GW 21 520	15/30	1920	1033
GW 21 521	30/60	4320	1033
GW 21 522	30/60	2280	1033
GW 21 523	30/60	2280	1033
GW 21 527	15/30	2160	1033
GW 21 528	30/60	2280	1033
GW 21 529	30/60	2160	1033
GW 21 530	15/30	1260	1033
GW 21 531	15/30	1920	1033
GW 21 559	30/60	4320	1033
GW 21 571	80/320	19200	1032
GW 21 572	30/60	4320	1032
GW 21 576	80/320	6400	1032
GW 21 577	30/60	4320	1032
GW 21 579	30/60	4320	1032
GW 21 580	1/15	1080	1033
GW 21 583	30/60	2280	1032
GW 21 584	30/60	2280	1032
GW 21 585	15/30	1260	1032
GW 21 588	30/60	2280	1032
GW 21 589	15/30	2160	1033
GW 21 591	15/30	1080	1033
GW 21 603	30/60	4320	1047
GW 21 604	30/60	2280	1047
GW 21 605	30/60	2280	1047
GW 21 606	30/60	2280	1047
GW 21 607	15/30	1920	1048
GW 21 608	15/30	1920	1048
GW 21 613	15/30	1260	1047
GW 21 616	15/30	3360	1047
GW 21 617	15/30	2100	1047
GW 21 620	15/30	450	1047

Code	Quantity		Page
	Pack/carton	Pallet	
GW 21 631	30/60	2280	1047
GW 21 634	1/15	1080	1048
GW 21 684	1/15	1080	1042
GW 21 685	15/30	1140	1042
GW 21 686	15/30	1140	1042
GW 21 802	1/14	4368	1045
GW 21 803	1/14	4368	1045
GW 21 810	1/4	624	1045
GW 21 811	1/14	4368	1045
GW 21 820	1/2	312	1050
GW 21 821	1/6	936	1034
GW 21 825	1/2	256	1045
GW 21 828	1/14	2184	1045
GW 21 833	1/4	1248	1046
GW 21 835	1/14	4368	1047
GW 21 841	1/4	256	1050
GW 21 852	1/2	256	1046
GW 21 853	1/2	192	1046
GW 22			
GW 22 101	96	4032	991
GW 22 102	96	4032	991
GW 22 103	96	5184	991
GW 22 104	96	4032	991
GW 22 106	48	2592	991
GW 22 107	6	576	991
GW 22 108	6	576	991
GW 22 111	96	3456	991
GW 22 112	12	2304	991
GW 22 113	96	4032	991
GW 22 114	12	1152	991
GW 22 116	8	1280	991
GW 22 117	6	576	991
GW 22 121	24	1536	992
GW 22 122	12	2304	992
GW 22 123	24	2304	992
GW 22 124	12	1152	992
GW 22 126	8	720	992
GW 22 127	6	384	992
GW 22 131	24	2304	992
GW 22 132	12	2304	992
GW 22 133	24	2304	992
GW 22 134	12	1152	992
GW 22 136	8	768	992
GW 22 137	6	384	992
GW 22 141	24	2304	992
GW 22 142	12	1152	992
GW 22 143	24	2304	992
GW 22 144	12	768	992
GW 22 146	8	720	992
GW 22 147	6	384	992
GW 22 151	24	2304	992
GW 22 152	12	1152	992
GW 22 153	24	2304	992
GW 22 154	12	768	992
GW 22 156	8	720	992
GW 22 157	6	576	992
GW 22 161	24	1536	992
GW 22 162	12	2304	992

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 22 163	24	2304	992
GW 22 164	12	1152	992
GW 22 166	8	960	992
GW 22 167	6	576	992
GW 22 171	24	1536	993
GW 22 172	12	2304	993
GW 22 173	24	2304	993
GW 22 174	12	1152	993
GW 22 176	8	960	993
GW 22 177	6	576	993
GW 22 181	24	2304	993
GW 22 182	12	2304	993
GW 22 183	24	2304	993
GW 22 184	12	768	993
GW 22 186	8	768	993
GW 22 187	6	384	993
GW 22 251	12	2304	994
GW 22 252	12	2304	994
GW 22 253	24	1536	994
GW 22 254	12	1152	994
GW 22 256	8	960	994
GW 22 257	6	576	994
GW 22 261	12	1152	994
GW 22 262	12	1152	994
GW 22 263	24	1536	994
GW 22 264	12	768	994
GW 22 266	8	960	994
GW 22 267	6	384	994
GW 22 271	12	2304	994
GW 22 272	12	1152	994
GW 22 273	24	2304	994
GW 22 274	12	768	994
GW 22 276	8	960	994
GW 22 277	6	576	994
GW 22 281	12	1152	993
GW 22 282	12	2304	993
GW 22 283	24	2304	993
GW 22 284	12	1152	993
GW 22 286	8	1536	993
GW 22 287	6	384	993
GW 22 288	6	720	993
GW 22 291	12	2304	993
GW 22 292	12	2304	993
GW 22 293	24	2304	993
GW 22 294	12	1152	993
GW 22 296	8	1024	993
GW 22 297	6	384	993
GW 22 298	6	720	993
GW 22 451	30	3990	995
GW 22 451	30	3990	1064
GW 22 452	30	2700	995
GW 22 452	30	2700	1064
GW 22 453	30	2700	995
GW 22 453	30	2700	1064
GW 22 461	30	2700	995
GW 22 461	30	2700	1064
GW 22 462	30	900	995
GW 22 462	30	900	1064
GW 22 463	30	900	995
GW 22 463	30	900	1064
GW 22 471	3/60	720	321
GW 22 471	3/60	720	996
GW 22 472	3/30	540	321
GW 22 472	3/30	540	996
GW 22 501	96	5184	988
GW 22 502	96	5184	988
GW 22 503	96	5184	988
GW 22 504	96	5184	988
GW 22 506	48	2016	988
GW 22 507	6	576	988
GW 22 508	6	792	988
GW 22 511	96	1152	988
GW 22 512	12	2304	988
GW 22 513	96	4032	988
GW 22 514	12	1152	988
GW 22 516	8	1280	988
GW 22 517	6	576	988
GW 22 521	24	2304	988
GW 22 522	12	2304	988
GW 22 523	24	2304	988
GW 22 524	12	1152	988
GW 22 526	8	960	988
GW 22 527	6	576	988
GW 22 531	24	2304	989
GW 22 532	12	2304	989
GW 22 533	24	2304	989
GW 22 534	12	1152	989
GW 22 536	8	720	989
GW 22 537	6	384	989
GW 22 541	24	1536	989
GW 22 542	12	2304	989
GW 22 543	24	2304	989
GW 22 544	12	1152	989
GW 22 546	8	960	989
GW 22 547	6	576	989
GW 22 551	24	2304	989
GW 22 552	12	2304	989
GW 22 553	24	2304	989
GW 22 554	12	1152	989
GW 22 556	8	960	989
GW 22 557	6	576	989
GW 22 561	24	2304	989
GW 22 562	12	1152	989
GW 22 563	24	2304	989
GW 22 564	12	1152	989
GW 22 566	8	960	989
GW 22 567	6	384	989
GW 22 571	24	2304	989
GW 22 572	12	2304	989
GW 22 573	24	2304	989
GW 22 574	12	1152	989
GW 22 576	8	1920	989
GW 22 577	6	384	989
GW 22 581	24	2304	990
GW 22 582	12	2304	990
GW 22 583	24	2304	990
GW 22 584	12	1152	990
GW 22 586	8	768	990
GW 22 587	6	384	990
GW 22 601	12	2304	990
GW 22 602	12	2304	990
GW 22 603	12	2304	990
GW 22 604	12	1152	990
GW 22 606	8	768	990
GW 22 607	6	576	990
GW 22 608	6	720	990
GW 22 611	12	2304	990
GW 22 612	12	1152	990
GW 22 613	12	2304	990
GW 22 614	12	1152	990
GW 22 616	8	1024	990
GW 22 617	6	384	990
GW 22 618	6	720	990
GW 22 651	12	2304	991
GW 22 652	12	1152	991
GW 22 653	12	2304	991
GW 22 654	12	768	991
GW 22 656	8	960	991
GW 22 657	6	576	991
GW 22 661	12	1152	991
GW 22 662	12	1152	991
GW 22 663	12	2304	991
GW 22 664	12	768	991
GW 22 666	8	960	991
GW 22 667	6	384	991
GW 22 671	12	1152	990
GW 22 672	12	1152	990
GW 22 673	12	2304	990
GW 22 674	12	768	990
GW 22 676	8	960	990
GW 22 677	6	384	990

GW 24

Code	Quantity		Page
	Pack/carton	Pallet	
GW 24 001	1/120	2880	995
GW 24 002	1/120	2880	995
GW 24 003	1/120	2880	995
GW 24 004	1/60	1920	995
GW 24 005	1/60	480	995
GW 24 006	3/60	1200	322
GW 24 006	3/60	1200	996
GW 24 007	3/30	480	322
GW 24 007	3/30	480	996
GW 24 008	1/60	2400	996
GW 24 009	1/60	1200	996
GW 24 010	1/60	1440	996
GW 24 011	1/60	1440	996
GW 24 018	1/30	540	997
GW 24 019	1/30	540	997
GW 24 020	1/20	360	997
GW 24 021	1/20	360	997
GW 24 022	1/30	720	996
GW 24 023	1/30	720	996
GW 24 201	10/300	12000	998
GW 24 202	10/150	7200	998
GW 24 206	5/150	2400	318

Code	Quantity		Page
	Pack/carton	Pallet	
GW 24 208	270	5400	320
GW 24 209	312	16848	320
GW 24 210	152	8208	320
GW 24 211	1/120	2880	323
GW 24 211	1/120	2880	995
GW 24 212	1/120	480	323
GW 24 212	1/120	480	995
GW 24 213	1/60	960	323
GW 24 213	1/60	960	995
GW 24 214	1/60	480	323
GW 24 214	1/60	480	995
GW 24 215	1/60	480	323
GW 24 215	1/60	480	995
GW 24 216	1/60	1200	323
GW 24 216	1/60	1200	995
GW 24 218	50/400	8000	272
GW 24 218	50/400	8000	324
GW 24 220	50/600	9600	324
GW 24 221	280	4480	320
GW 24 224	500/7000		324
GW 24 224	500/7000		771
GW 24 225	300/4200		324
GW 24 225	300/4200		771
GW 24 227	5/50	1200	323
GW 24 228	5/50	2700	323
GW 24 229	300/4200		324
GW 24 229	300/4200		771
GW 24 230	10/100	3200	998
GW 24 231	5/200	4000	319
GW 24 232	5/200	6000	320
GW 24 233	20/200	14000	320
GW 24 234 PM	5/200	4000	271
GW 24 237	2/24	1296	318
GW 24 237 PM	2/24	288	271
GW 24 238	2/24	720	318
GW 24 239	2/16	192	318
GW 24 240	10/60	960	998
GW 24 241	10/40	640	998
GW 24 262	10/120	9600	998
GW 24 282 PM	2/108	648	271
GW 24 321	200	12800	272
GW 24 321	200	12800	319
GW 24 322	10/100	6400	323
GW 24 323	10/100	5400	323
GW 24 324	10/100	5400	323
GW 24 330	150	5700	319
GW 24 403	15/345	5175	318
GW 24 403 P	200	8000	319
GW 24 403 PM	9/180	5400	271
GW 24 404	5/135	2700	318
GW 24 404 P	50	2000	319
GW 24 404 PM	2/120	4080	271
GW 24 406	3/36	2160	318
GW 24 406 P	50	1000	319
GW 24 406 PM	2/60	1800	271
GW 24 601	1	120	316
GW 24 602	1	30	316
GW 24 606	1	50	317
GW 24 607	1	30	317
GW 24 611	1	50	316
GW 24 612	1	30	316
GW 24 616	1	50	317
GW 24 617	1	30	317
GW 24 621	1	50	318
GW 24 622	1	30	318
GW 24 633	1/30	480	318

GW 26

GW 26 222	5/40	720	1062
GW 26 223	5/40	720	1062
GW 26 406	25/250	12500	166
GW 26 406	25/250	12500	250
GW 26 406	25/250	12500	1065
GW 26 407	200/1600	60800	771
GW 26 407	200/1600	60800	1066
GW 26 409	5/300	10800	536
GW 26 409	5/300	10800	998
GW 26 410	5/150	5400	536
GW 26 410	5/150	5400	998
GW 26 417	1/12	240	1062
GW 26 420	1/20	360	1064
GW 26 421	1/20	360	1064
GW 26 427	1/12	720	1062

GW 27

GW 27 001	5/80	2880	1058
GW 27 002	5/80	2880	1058
GW 27 003	3/60	3000	1058
GW 27 004	2/40	2760	1058
GW 27 005	1/30	1080	1058
GW 27 006	1/20	1000	1058
GW 27 007	1/20	600	1058
GW 27 008	1/20	480	1058
GW 27 021	2/40	1680	1058
GW 27 022	1/30	1080	1058
GW 27 023	1/20	800	1058
GW 27 024	1/20	600	1058
GW 27 041	5/60	4140	1060
GW 27 042	5/60	4140	1060
GW 27 043	2/40	2760	1060
GW 27 044	3/30	2070	1060
GW 27 051	1/20	640	1060
GW 27 052	1/15	480	1060
GW 27 056	1/12	480	1060
GW 27 057	1/12	480	1060
GW 27 062	5/60	1080	1060
GW 27 071	1/8	560	1063
GW 27 072	1/6	288	1063
GW 27 073	1/4	192	1063
GW 27 101	5/60	960	165
GW 27 101	5/60	960	1064
GW 27 102	2/30	480	165
GW 27 102	2/30	480	1064
GW 27 103	1/20	480	165
GW 27 103	1/20	480	1064
GW 27 104	1/10	240	165
GW 27 104	1/10	240	1064
GW 27 105	1/10	120	165
GW 27 105	1/10	120	1064
GW 27 111	5/60	960	165
GW 27 111	5/60	960	1064
GW 27 201	1/30	360	165
GW 27 201	1/30	360	1065
GW 27 202	1/30	540	165
GW 27 202	1/30	540	1065
GW 27 203	1/10	240	165
GW 27 203	1/10	240	1065
GW 27 204	1/10	240	165
GW 27 204	1/10	240	1065
GW 27 401	3/60	5400	117
GW 27 401	3/60	5400	294
GW 27 401	3/60	5400	311
GW 27 401	3/60	5400	1063
GW 27 402	2/60	1440	166
GW 27 402	2/60	1440	1065
GW 27 403	3/60	5400	117
GW 27 403	3/60	5400	294
GW 27 403	3/60	5400	311
GW 27 403	3/60	5400	1064
GW 27 415	5/40	1680	1062
GW 27 416	5/40	720	1062
GW 27 417	5/40	720	1062
GW 27 418	5/40	720	1062
GW 27 419	5/40	720	1062
GW 27 421	1/12	384	1062
GW 27 422	1/12	384	1062
GW 27 423	1/12	240	1062
GW 27 424	1/12	180	1062
GW 27 431 B	1/10	240	1063
GW 27 432	1/24	432	1063
GW 27 441	10/100	15600	1065
GW 27 442	10/100	35100	1065
GW 27 443	10/100	6400	1066
GW 27 603	10	500	1059
GW 27 609	10	500	1059
GW 27 615	10	500	1059
GW 27 616	10	500	1059
GW 27 621	10	500	1059
GW 27 622	10	500	1059
GW 27 627	5	360	1059
GW 27 628	5	360	1059
GW 27 801	5/60	1080	1061
GW 27 802	5/60	360	1061
GW 27 803	5/60	360	1061
GW 27 804	5/60	360	1061
GW 27 805	5/60	360	1061
GW 27 811	5/80	960	1061
GW 27 812	5/80	960	1061
GW 27 813	5/80	480	1061
GW 27 814	5/80	480	1061
GW 27 815	5/80	480	1061
GW 27 831	5/60	1080	1061
GW 27 832	5/60	1080	1061
GW 27 833	5/60	1080	1061
GW 27 834	5/60	1080	1061

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 27 835	5/60	1080	1061
GW 27 836	2/40	240	1061
GW 27 841	5/60	1080	1061
GW 27 842	5/60	1080	1061
GW 27 843	5/60	1080	1061
GW 27 844	5/60	1080	1061
GW 27 845	5/60	720	1061
GW 28			
GW 28 003	25/250	18000	1189
GW 28 004	25/250	18000	1189
GW 28 005	25/150	10800	1189
GW 28 006	25/150	10800	1189
GW 28 007	25/150	7500	1189
GW 28 008	25/150	7500	1189
GW 28 009	25/250	6000	1189
GW 28 010	25/250	6000	1189
GW 28 011	25/175	4200	1189
GW 28 012	25/175	4200	1189
GW 28 013	25/175	4200	1189
GW 28 203	25/250	5000	1190
GW 28 204	25/250	5000	1190
GW 28 205	25/150	10800	1190
GW 28 206	25/150	10800	1190
GW 28 415	15/150	3600	1192
GW 28 416	50/200	1600	1191
GW 28 417	50/200	1600	1191
GW 28 418	40/160	1280	1191
GW 28 419	40/160	1280	1191
GW 28 421	50/200	2400	1191
GW 28 423	50/200	1600	1191
GW 28 509	50/200		1192
GW 28 510	50/200	3000	1192
GW 30			
GW 30 001	24/96	3840	1082
GW 30 002	24/48	2016	1082
GW 30 003	24/48	1920	1082
GW 30 004	24/48	3840	1082
GW 30 007	1/12	2340	1082
GW 30 011	24/96	3840	1082
GW 30 012	24/48	2016	1082
GW 30 013	24/48	1920	1082
GW 30 015	24/48	4032	1082
GW 30 016	24/48	1920	1082
GW 30 021	24/96	3840	1083
GW 30 022	12/24	1872	1083
GW 30 023	12/24	1872	1083
GW 30 024	12/24	1872	1083
GW 30 025	12/24	1872	1083
GW 30 026	12/24	1872	1083
GW 30 027	12/24	1872	1083
GW 30 030	24/48	1920	1083
GW 30 031	4/32	1280	1083
GW 30 032	1/24	1872	1083
GW 30 033	12/24	1872	1083
GW 30 034	12/24	3744	1083
GW 30 035	12/24	1872	1083
GW 30 036	12/24	1872	1083
GW 30 037	12/24	1872	1083
GW 30 038	12/36	864	1083
GW 30 121	1/6	1638	1083
GW 30 201	24/96	3840	1084
GW 30 203	24/96	3840	1084
GW 30 210	12/48	1920	1084
GW 30 211	12/48	1920	1085
GW 30 212	12/48	4800	1084
GW 30 214	12/24	1920	1084
GW 30 215	12/48	960	1085
GW 30 216	12/48	1920	1085
GW 30 219	12/48	960	1085
GW 30 220	12/48	960	1085
GW 30 227	24/48	4032	1086
GW 30 232	24/48	2016	1086
GW 30 234	24/48	3840	1085
GW 30 237	12/48	1920	1086
GW 30 261	1/24	3744	1087
GW 30 266	1/24	1872	1087
GW 30 267	1/24	3744	1087
GW 30 286	1/96	1440	1087
GW 30 287	1/96	5760	1087
GW 30 301	24/48	2016	1087
GW 30 306	1/24	1872	1087
GW 30 311	24/48	1920	1086
GW 30 316	1/24	1872	1086
GW 30 321	24/48	2016	1084
GW 30 322	12/24	1728	1085
GW 30 331	24/48	1920	1084
GW 30 360	24/48	1920	1088
GW 30 371	1/12	2340	1088
GW 30 372	1/12	2340	1088
GW 30 373	1/12	2340	1088
GW 30 374	1/12	2340	1088
GW 30 375	1/12	2340	1088
GW 30 376	1/12	2520	1088
GW 30 377	1/6	1170	1088
GW 30 378	1/6	1170	1088
GW 30 379	1/6	1170	1088
GW 30 401	1/6	1872	1090
GW 30 402	1/12	3276	1089
GW 30 403	1/12	2340	1090
GW 30 430	1/2	390	1091
GW 30 501	1/6	1638	1088
GW 30 522	1/2	312	819
GW 30 522	1/2	312	853
GW 30 522	1/2	312	887
GW 30 522	1/2	312	921
GW 30 522	1/2	312	955
GW 30 522	1/2	312	1023
GW 30 522	1/2	312	1049
GW 30 611	24/48	1920	1089
GW 30 612	24/48	3840	1089
GW 30 614	24/48	1920	1089
GW 30 633	12/24	1872	1089
GW 30 634	12/24	1872	1089
GW 30 635	12/24	1872	1089
GW 30 636	12/24	1872	1089
GW 30 685	1/12	900	1087
GW 30 686	1/12	300	1087
GW 30 702	2/4	624	1090
GW 30 703	2/12	576	1090
GW 30 706	1/2	156	1090
GW 30 711	2/4	312	1091
GW 30 901	5/200	12000	1083
GW 30 902	12/48	960	1083
GW 30 903	8/32	576	1083
GW 30 905	24/48	1920	1083
GW 30 912	1/100	19500	820
GW 30 912	1/100	19500	854
GW 30 912	1/100	19500	888
GW 30 912	1/100	19500	922
GW 30 912	1/100	19500	956
GW 30 912	1/100	19500	1026
GW 30 912	1/100	19500	1052
GW 30 912	1/100	19500	1092
GW 30 943	50	15600	226
GW 30 943	50	15600	1025
GW 30 943	50	15600	1051
GW 30 943	50	15600	1091
GW 30 944	50	9750	1025
GW 30 944	50	9750	1051
GW 30 944	50	9750	1091
GW 30 946	50	9750	1025
GW 30 946	50	9750	1051
GW 30 946	50	9750	1091
GW 30 947	50	9750	226
GW 30 947	50	9750	1025
GW 30 947	50	9750	1051
GW 30 947	50	9750	1091
GW 30 958	10	1560	227
GW 30 959	10	2730	227
GW 30 960	10	1560	227
GW 32			
GW 32 002	48	1344	1073
GW 32 003	48	1344	1073
GW 32 004	24	1200	1073
GW 32 006	24	720	1073
GW 32 007	12	576	1073
GW 32 008	12	1152	1073
GW 32 009	6	150	1073
GW 32 012	48	1344	1073
GW 32 013	48	1344	1073
GW 32 014	24	1728	1073
GW 32 016	24	1200	1073
GW 32 017	12	480	1073
GW 32 018	12	180	1073
GW 32 019	6	150	1073
GW 32 022	48	672	1073
GW 32 023	48	1344	1073
GW 32 024	24	1152	1073
GW 32 026	24	720	1073
GW 32 027	12	576	1073
GW 32 028	12	180	1073
GW 32 029	6	150	1073
GW 32 052	48	672	1073

Code	Quantity		Page
	Pack/carton	Pallet	
GW 32 053	48	1344	1073
GW 32 054	24	1200	1073
GW 32 056	24	1080	1073
GW 32 057	12	576	1073
GW 32 072	48	672	1074
GW 32 073	48	672	1074
GW 32 074	24	720	1074
GW 32 076	24	1080	1074
GW 32 077	12	576	1074
GW 32 121	1/30	450	1074
GW 32 123	1/30	720	1074
GW 32 131	1/30	1200	1074
GW 32 133	1/30	900	1074
GW 32 242	12	960	1072
GW 32 243	96	1152	1072
GW 32 244	12	1344	1072
GW 32 246	8	720	1072
GW 32 302	12	768	1072
GW 32 303	96	3456	1072
GW 32 304	12	1344	1072
GW 32 306	8	768	1072
GW 32 402	10/150	900	1076
GW 32 403	10/150	5400	1076
GW 32 404	10/100	2000	1076
GW 32 406	10/100	1200	1076
GW 32 407	5/50	800	1076
GW 32 408	5/50	800	1076
GW 32 409	5/25	450	1076
GW 32 411	2/24	192	1074
GW 32 412	2/12	192	1074
GW 32 421	5/200	1200	1076
GW 32 431	3/60	960	322
GW 32 431	3/60	960	322
GW 32 431	3/60	960	996
GW 32 431	3/60	960	1075
GW 32 432	3/60	480	322
GW 32 432	3/60	480	322
GW 32 432	3/60	480	996
GW 32 432	3/60	480	1075
GW 32 450	1/10	300	225
GW 32 450	1/10	300	1075
GW 32 451	1/10	500	225
GW 32 451	1/10	500	1075
GW 32 457	1/10	1950	226
GW 32 457	1/10	1950	1076
GW 32 461	1/60	720	1074
GW 32 462	1/60	780	1074
GW 32 466	1/30	600	1074
GW 32 467	1/30	540	1074
GW 32 752	12	240	1072
GW 32 753	12	1440	1072
GW 32 754	12	960	1072
GW 32 756	8	720	1072

GW 35

Code	Quantity		Page
	Pack/carton	Pallet	
GW 35 001 Y	10/100	1200	1112
GW 35 002 W	10/100	1400	1102
GW 35 002 Y	10/100	1400	1112
GW 35 003 W	10/100	1800	1102
GW 35 003 Y	10/100	1800	1112
GW 35 006 W	10/100	5200	1102
GW 35 006 Y	10/100	1200	1112
GW 35 011 Y	10/100	6000	1112
GW 35 012 W	10/100	5000	1102
GW 35 012 Y	10/100	1400	1112
GW 35 015 W	10/100	1800	1103
GW 35 015 Y	10/100	1800	1113
GW 35 016 W	10/100	5200	1102
GW 35 016 Y	10/100	1200	1112
GW 35 021 W	10/100	5200	1103
GW 35 021 Y	10/100	1200	1113
GW 35 022 W	10/100	1200	1103
GW 35 022 Y	10/100	1200	1113
GW 35 026 W	10/100	7200	1103
GW 35 026 Y	10/100	1200	1113
GW 35 031 W	10/100	6000	1102
GW 35 051 W	10/100	6000	1102
GW 35 051 Y	10/100	900	1112
GW 35 052 W	10/100	6000	1103
GW 35 052 Y	10/100	1200	1113
GW 35 071 W	10/100	6000	1102
GW 35 201 Y	10/100	1200	1114
GW 35 202 Y	10/100	5200	1114
GW 35 203 W	10/100	1200	1104
GW 35 203 Y	10/100	1200	1114
GW 35 204 W	6/60	3600	1104
GW 35 204 Y	6/60	1000	1114
GW 35 206 W	10/100	5200	1104
GW 35 207 W	10/100	6000	1104
GW 35 211 Y	10/100	1200	1114
GW 35 212 W	10/100	1200	1104
GW 35 212 Y	10/100	1200	1114
GW 35 213 W	10/100	1200	1104
GW 35 213 Y	10/100	1200	1114
GW 35 214 W	6/60	600	1104
GW 35 214 Y	6/60	540	1114
GW 35 216 W	10/100	5200	1104
GW 35 251 W	10/100	1400	1105
GW 35 251 Y	10/100	1400	1115
GW 35 261 W	10/100	1400	1105
GW 35 261 Y	10/100	1400	1115
GW 35 271 W	10/100	1400	1106
GW 35 271 Y	10/100	1400	1116
GW 35 272 W	10/100	1400	1106
GW 35 272 Y	10/100	1400	1116
GW 35 273 W	10/100	1400	1106
GW 35 273 Y	10/100	1400	1116
GW 35 274 W	10/100	1400	1106
GW 35 274 Y	10/100	1400	1116
GW 35 280 W	10/100	1800	1106
GW 35 280 Y	10/100	1800	1116
GW 35 301 W	6/60	960	1105
GW 35 301 Y	6/60	960	1115
GW 35 901 AD	240	1920	1098
GW 35 901 AG	240	1920	1098
GW 35 901 AH	240	1920	1097
GW 35 901 AM	240	1920	1097
GW 35 901 AN	240	1920	1098
GW 35 901 AW	240	7200	1097
GW 35 901 AY	240	7200	1097
GW 35 902 AD	120	960	1098
GW 35 902 AG	120	960	1098
GW 35 902 AH	120	960	1097
GW 35 902 AM	120	960	1097
GW 35 902 AN	120	960	1098
GW 35 902 AW	120	2880	1097
GW 35 902 AY	120	960	1097
GW 35 903 AD	100	1200	1098
GW 35 903 AG	100	1200	1098
GW 35 903 AH	100	1200	1097
GW 35 903 AM	100	1200	1097
GW 35 903 AN	100	800	1098
GW 35 903 AW	100	800	1097
GW 35 903 AY	100	1200	1097
GW 35 904 AD	80	960	1098
GW 35 904 AG	80	960	1098
GW 35 904 AH	80	960	1097
GW 35 904 AM	80	960	1097
GW 35 904 AN	80	960	1098
GW 35 904 AW	80	640	1097
GW 35 904 AY	80	960	1097
GW 35 905 AD	60	720	1098
GW 35 905 AG	60	720	1098
GW 35 905 AH	60	720	1097
GW 35 905 AM	60	720	1097
GW 35 905 AN	60	720	1098
GW 35 905 AW	60	720	1097
GW 35 905 AY	60	720	1097
GW 35 909 AD	120	960	1098
GW 35 909 AG	120	960	1098
GW 35 909 AH	120	960	1097
GW 35 909 AM	120	960	1097
GW 35 909 AN	120	960	1098
GW 35 909 AW	120	960	1097
GW 35 909 AY	120	960	1097
GW 35 911	10/80	4160	1108
GW 35 911	10/80	4160	1118
GW 35 912	5/40	2080	1108
GW 35 912	5/40	2080	1118
GW 35 981	50/500		1108
GW 35 981	50/500		1118
GW 35 986	1/50	3000	1108
GW 35 986	1/50	3000	1118
GW 35 991	20/200	10400	1107
GW 35 991	20/200	10400	1117
GW 35 996	50/800	12800	1108
GW 35 996	50/800	12800	1118

GW 38

Code	Quantity		Page
	Pack/carton	Pallet	
GW 38 031	10/50	3600	1182
GW 38 032	10/50	3600	1182
GW 38 033	10/50	3600	1182
GW 38 034	10/50	1800	1182
GW 38 035	10/50	3600	1182
GW 38 036	10/50	3600	1182
GW 38 056	1/48	6912	811

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 38 056	1/48	6912	845
GW 38 056	1/48	6912	879
GW 38 056	1/48	6912	913
GW 38 056	1/48	6912	947
GW 38 056	1/48	6912	963
GW 38 056	1/48	6912	1014
GW 38 056	1/48	6912	1043
GW 38 056	1/48	6912	1107
GW 38 056	1/48	6912	1117
GW 38 056	1/48	6912	1183
GW 38 057	1/48	6912	811
GW 38 057	1/48	6912	845
GW 38 057	1/48	6912	879
GW 38 057	1/48	6912	913
GW 38 057	1/48	6912	947
GW 38 057	1/48	6912	963
GW 38 057	1/48	6912	1014
GW 38 057	1/48	6912	1043
GW 38 057	1/48	6912	1107
GW 38 057	1/48	6912	1117
GW 38 057	1/48	6912	1183
GW 38 098	1	400	264
GW 38 098	1	400	296
GW 38 098	1	400	1210
GW 38 116	1/24	720	1182
GW 38 117	1/24	576	1182
GW 38 118	1/24	480	1182
GW 38 119	1/24	384	1182
GW 38 121	1/24	720	1183
GW 38 122	1/24	720	1183
GW 38 123	1/24	480	1183
GW 38 124	1/24	384	1183
GW 38 131	1/24	720	1182
GW 38 132	1/24	384	1182
GW 38 133	1/24	216	1182
GW 38 335	1/25	2400	810
GW 38 335	1/25	2400	844
GW 38 335	1/25	2400	878
GW 38 335	1/25	2400	912
GW 38 335	1/25	2400	946
GW 38 335	1/25	2400	963
GW 38 335	1/25	2400	1014
GW 38 335	1/25	2400	1043
GW 38 335	1/25	2400	1107
GW 38 335	1/25	2400	1117
GW 38 406	1	16	1183
GW 38 407	1	12	1183
GW 38 408	1	10	1183
GW 38 409	1	8	1183
GW 38 418	1	4	1183
GW 38 419	1	4	1183
GW 38 451	1	2	1184
GW 38 452	1	2	1184
GW 38 453	1	1	1184
GW 38 461	1	1	1184
GW 38 462	1	1	1184
GW 38 463	1	1	1184
GW 38 464	1	1	1184
GW 38 471	1/30	2520	1184
GW 38 472	1/5	420	1184
GW 38 473	1/30	2520	1186
GW 38 474	1	117	1185
GW 38 475	1	10	1185
GW 38 476	1	10	1185
GW 38 477	1/8	160	1185
GW 38 479	1/8	320	1185
GW 38 480	1	33	1185
GW 38 481	1	27	1185
GW 38 482	1	64	1185
GW 38 483	1/15	600	1185
GW 38 484	1	48	1185
GW 38 485	1	84	1184
GW 38 557	1/30	1200	1186
GW 38 558	1/30	2520	1185
GW 38 590	1	20	1183
GW 38 591	1	20	1183
GW 38 592	1	20	1183
GW 38 593	1	20	1183
GW 38 594	1	10	1184
GW 38 595	1	20	1184
GW 38 596	1	10	1184
GW 38 597	1	10	1184
GW 38 598	1	10	1184
GW 38 599	1	10	1184
GW 38 601	1/20	800	1186
GW 38 602	1/10	400	1186
GW 38 603	1/10	20	1185
GW 38 606	1/10	80	1186
GW 38 607	1/6	12	1186
GW 38 608	1/6	12	1186
GW 38 609	1/6	12	1186
GW 38 610	1/20	800	1186
GW 38 611	1/15	600	1186
GW 38 612	1	49	1185
GW 38 613	1	49	1185

GW 40

Code	Quantity		Page
	Pack/carton	Pallet	
GW 40 001	24	720	198
GW 40 003	24	480	198
GW 40 005	8	200	198
GW 40 007	6	96	198
GW 40 009	4	64	198
GW 40 022	84	2520	201
GW 40 023	36	1800	201
GW 40 024	34	850	201
GW 40 026	24	480	201
GW 40 028	12	288	201
GW 40 030	12	180	201
GW 40 032	9	108	201
GW 40 043	14	392	199
GW 40 043 BS	14	350	199
GW 40 045	9	270	199
GW 40 045 BS	9	225	199
GW 40 047	6	180	199
GW 40 047 BD	6	150	199
GW 40 047 BS	6	120	199
GW 40 049	2	56	199
GW 40 049 BD	2	50	199
GW 40 049 BS	2	56	199
GW 40 051	2	60	199
GW 40 051 BD	2	50	199
GW 40 053	1	24	199
GW 40 053 BD	1	19	199
GW 40 053 BQ	1	19	199
GW 40 063	14	252	200
GW 40 063 BS	14	252	200
GW 40 065	9	225	200
GW 40 065 BS	9	225	200
GW 40 067	6	150	200
GW 40 067 BD	6	150	200
GW 40 067 BS	6	150	200
GW 40 069	2	36	200
GW 40 069 BD	2	50	200
GW 40 069 BS	2	50	200
GW 40 071	2	50	200
GW 40 071 BD	2	50	200
GW 40 073	1	19	200
GW 40 073 BD	1	19	200
GW 40 073 BQ	1	19	200
GW 40 101	19	570	196
GW 40 102	12	360	196
GW 40 102 BS	12	288	196
GW 40 103	6	150	137
GW 40 103	6	150	196
GW 40 103 BS	6	120	196
GW 40 104	3	105	137
GW 40 104	3	105	197
GW 40 104 BD	3	75	197
GW 40 104 BS	3	75	197
GW 40 105	2	60	197
GW 40 105 BD	2	50	197
GW 40 105 UD	2	50	197
GW 40 106	3	105	137
GW 40 106	3	105	196
GW 40 106 BS	3	63	196
GW 40 107	2	56	197
GW 40 107 BD	2	50	197
GW 40 107 BS	2	50	197
GW 40 108	1	30	197
GW 40 108 BD	1	24	197
GW 40 108 BT	1	24	197
GW 40 109	1	24	197
GW 40 109 BD	1	19	197
GW 40 109 BQ	1	19	197
GW 40 112	1/12	84	208
GW 40 113	6	72	209
GW 40 114	3	63	209
GW 40 115	2	40	209
GW 40 116	1/3	18	208
GW 40 117	1/2	12	208
GW 40 118	1	7	208
GW 40 119	1	19	208
GW 40 123	6	120	209
GW 40 124	3	63	209
GW 40 125	2	40	209

Code	Quantity		Page
	Pack/carton	Pallet	
GW 40 151 N	1	84	215
GW 40 151 N	1	84	288
GW 40 152 N	1	84	215
GW 40 152 N	1	84	288
GW 40 153 N	1	70	215
GW 40 153 N	1	70	288
GW 40 154 N	1	36	215
GW 40 154 N	1	36	288
GW 40 155 N	1	28	215
GW 40 155 N	1	28	288
GW 40 161 N	1	72	215
GW 40 161 N	1	72	288
GW 40 162 N	1	60	215
GW 40 162 N	1	60	288
GW 40 163 N	1	48	215
GW 40 163 N	1	48	288
GW 40 164 N	1	36	215
GW 40 164 N	1	36	288
GW 40 165 N	1	28	215
GW 40 165 N	1	28	288
GW 40 173 N	1	48	215
GW 40 173 N	1	48	288
GW 40 174 N	1	36	215
GW 40 174 N	1	36	288
GW 40 178 N	1	48	215
GW 40 178 N	1	48	288
GW 40 179 N	1	36	215
GW 40 179 N	1	36	288
GW 40 225 TB	16	320	280
GW 40 225 TN	16	256	280
GW 40 225 VA	16	256	280
GW 40 225 VT	16	256	280
GW 40 229 TB	12	192	280
GW 40 229 TN	12	144	280
GW 40 229 VA	12	144	280
GW 40 229 VT	12	192	280
GW 40 233 TB	5	150	280
GW 40 233 TN	5	100	280
GW 40 233 VA	5	80	280
GW 40 233 VT	5	80	280
GW 40 237 TB	12	360	280
GW 40 237 TN	12	144	280
GW 40 237 VA	12	360	280
GW 40 237 VT	12	360	280
GW 40 239 TB	5	100	280
GW 40 239 TN	5	60	280
GW 40 239 VA	5	60	280
GW 40 239 VT	5	60	280
GW 40 285 TB	16	256	281
GW 40 287 TB	12	144	281
GW 40 289 TB	12	144	281
GW 40 293 TB	5	80	281
GW 40 299 TB	5	60	281
GW 40 336	10	150	208
GW 40 337	6	144	208
GW 40 390 C	1	40	263
GW 40 390 C	1	40	287
GW 40 390 F	1	20	263
GW 40 390 F	1	20	287
GW 40 401	10	3120	105
GW 40 401	10	3120	118
GW 40 401	10	3120	119
GW 40 401	10	3120	202
GW 40 401	10	3120	210
GW 40 401	10	3120	262
GW 40 401	10	3120	293
GW 40 402	10	1260	105
GW 40 402	10	1260	118
GW 40 402	10	1260	119
GW 40 402	10	1260	202
GW 40 402	10	1260	210
GW 40 402	10	1260	262
GW 40 402	10	1260	293
GW 40 404	10	600	202
GW 40 404	10	600	210
GW 40 404	10	600	262
GW 40 404	10	600	293
GW 40 408 B	1/10	3120	105
GW 40 408 B	1/10	3120	118
GW 40 408 B	1/10	3120	119
GW 40 408 B	1/10	3120	202
GW 40 408 B	1/10	3120	210
GW 40 408 B	1/10	3120	262
GW 40 408 B	1/10	3120	293
GW 40 408 U	1/10	3120	105
GW 40 408 U	1/10	3120	118
GW 40 408 U	1/10	3120	119
GW 40 408 U	1/10	3120	202
GW 40 408 U	1/10	3120	210
GW 40 408 U	1/10	3120	262
GW 40 408 U	1/10	3120	293
GW 40 412 B	1/10	1260	105
GW 40 412 B	1/10	1260	118
GW 40 412 B	1/10	1260	119
GW 40 412 B	1/10	1260	202
GW 40 412 B	1/10	1260	210
GW 40 412 B	1/10	1260	262
GW 40 412 B	1/10	1260	293
GW 40 412 U	1/10	1260	105
GW 40 412 U	1/10	1260	118
GW 40 412 U	1/10	1260	119
GW 40 412 U	1/10	1260	202
GW 40 412 U	1/10	1260	210
GW 40 412 U	1/10	1260	262
GW 40 412 U	1/10	1260	293
GW 40 413	20	1440	105
GW 40 413	20	1440	118
GW 40 413	20	1440	119
GW 40 413	20	1440	202
GW 40 413	20	1440	211
GW 40 413	20	1440	262
GW 40 413	20	1440	294
GW 40 418 B	1/10	600	202
GW 40 418 B	1/10	600	262
GW 40 418 B	1/10	600	293
GW 40 418 U	1/10	600	202
GW 40 418 U	1/10	600	262
GW 40 418 U	1/10	600	293
GW 40 421	10/100	40000	204
GW 40 421	10/100	40000	211
GW 40 421	10/100	40000	295
GW 40 422	1/10	1100	104
GW 40 422	1/10	1100	116
GW 40 422	1/10	1100	204
GW 40 422	1/10	1100	211
GW 40 422	1/10	1100	220
GW 40 422	1/10	1100	227
GW 40 422	1/10	1100	261
GW 40 422	1/10	1100	263
GW 40 422	1/10	1100	295
GW 40 422	1/10	1100	1075
GW 40 422 U	1/10	1260	105
GW 40 422 U	1/10	1260	118
GW 40 422 U	1/10	1260	119
GW 40 422 U	1/10	1260	202
GW 40 422 U	1/10	1260	210
GW 40 422 U	1/10	1260	262
GW 40 422 U	1/10	1260	293
GW 40 423	50	7200	183
GW 40 423	50	7200	189
GW 40 423	50	7200	204
GW 40 423	50	7200	210
GW 40 423	50	7200	228
GW 40 423	50	7200	295
GW 40 423	50	7200	312
GW 40 425	10	3360	261
GW 40 425	10	3360	264
GW 40 425	10	3360	292
GW 40 428	1/20	840	211
GW 40 451	20	1440	213
GW 40 452	20	1440	213
GW 40 453	20	1440	213
GW 40 454 N	1	4200	216
GW 40 454 N	1	4200	289
GW 40 455 N	1	4200	216
GW 40 455 N	1	4200	289
GW 40 461 N	1	8400	216
GW 40 461 N	1	8400	289
GW 40 463	1/10	3120	213
GW 40 463 N	1	8400	216
GW 40 463 N	1	8400	289
GW 40 467	50	6400	204
GW 40 467	50	6400	210
GW 40 467	50	6400	214
GW 40 467	50	6400	216
GW 40 467	50	6400	220
GW 40 467	50	6400	261
GW 40 467	50	6400	289
GW 40 467	50	6400	295
GW 40 467 TB	50	6400	292
GW 40 467 TB	50	6400	1209
GW 40 467 TN	50	6400	292
GW 40 467 VA	50	6400	292
GW 40 467 VT	50	6400	292

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 40 468	50	6400	295
GW 40 473	20	320	201
GW 40 473	20	320	210
GW 40 474	20	400	201
GW 40 474	20	400	210
GW 40 479	5	240	292
GW 40 487	10/100	2800	203
GW 40 487	10/100	2800	211
GW 40 487	10/100	2800	261
GW 40 487	10/100	2800	294
GW 40 488	10/100	1800	203
GW 40 488	10/100	1800	211
GW 40 488	10/100	1800	261
GW 40 488	10/100	1800	294
GW 40 492	20	800	203
GW 40 492	20	800	211
GW 40 493	20	400	203
GW 40 493	20	400	211
GW 40 495	20	800	262
GW 40 495	20	800	294
GW 40 496	20	400	262
GW 40 496	20	400	294
GW 40 501	8	144	217
GW 40 502	4	128	217
GW 40 503	4	60	217
GW 40 504	2	72	217
GW 40 506	4	144	217
GW 40 511	4	96	217
GW 40 512	3	180	217
GW 40 516	8	160	218
GW 40 517	4	80	218
GW 40 518	4	192	218
GW 40 519	2	72	218
GW 40 526	8	960	218
GW 40 527	4	576	218
GW 40 528	4	288	218
GW 40 529	2	144	218
GW 40 531	8	96	219
GW 40 532	4	160	219
GW 40 533	4	48	219
GW 40 534	2	36	219
GW 40 536	8	96	219
GW 40 537	4	80	219
GW 40 538	4	48	219
GW 40 539	2	40	219
GW 40 541	4	48	219
GW 40 542	4	72	219
GW 40 546	20	6240	218
GW 40 591	20	1920	219
GW 40 592	20	1920	219
GW 40 593	20	2560	219
GW 40 594	20	2560	219
GW 40 596	1/10	1280	217
GW 40 597	1/10	1280	217
GW 40 601	60	1200	283
GW 40 602	36	576	283
GW 40 603	21	336	283
GW 40 604	12	240	283
GW 40 604 BS	12	300	283
GW 40 605	8	200	283
GW 40 605 BS	8	160	283
GW 40 605 PM	8	128	260
GW 40 606	6	120	284
GW 40 606 BD	6	90	284
GW 40 606 BS	6	90	284
GW 40 606 PM	6	72	260
GW 40 608	4	80	283
GW 40 608 BS	4	80	283
GW 40 609	3	60	284
GW 40 609 BD	3	45	284
GW 40 609 BS	3	45	284
GW 40 609 PM	3	36	260
GW 40 610	2	48	284
GW 40 610 BD	2	36	284
GW 40 610 BT	2	36	284
GW 40 610 PM	3	24	260
GW 40 611	1	24	284
GW 40 611 BD	1	19	284
GW 40 611 BQ	1	19	284
GW 40 611 PM	1	19	260
GW 40 655	18	288	290
GW 40 657	8	128	290
GW 40 659	6	150	290
GW 40 661	3	48	290
GW 40 671	12	240	282
GW 40 673	16	256	282
GW 40 674	12	192	282
GW 40 677	5	120	282
GW 40 679	5	80	282
GW 40 685	1/12	96	286
GW 40 685 PM	1/12	180	261
GW 40 687	1/5	120	286
GW 40 687 PM	1/5	150	261
GW 40 688	1/5	80	286
GW 40 688	1/5	80	287
GW 40 688 PM	1/5	100	261
GW 40 688 PM	1/5	100	263
GW 40 689	1/3	72	286
GW 40 689	1/3	72	287
GW 40 689 PM	1/3	36	261
GW 40 689 PM	1/3	36	263
GW 40 690	1/2	48	286
GW 40 690 PM	1/2	38	261
GW 40 882	36	576	285
GW 40 883	21	336	285
GW 40 884	12	240	285
GW 40 884 BS	12	300	285
GW 40 885	8	128	285
GW 40 885 BS	8	128	285
GW 40 886	6	90	285
GW 40 886 BD	6	90	285
GW 40 886 BS	6	90	285
GW 40 888	4	80	285
GW 40 888 BS	4	100	285
GW 40 889	3	45	285
GW 40 889 BD	3	45	285
GW 40 889 BS	3	45	285
GW 40 890	2	48	285
GW 40 890 BD	2	36	285
GW 40 890 BT	2	36	285
GW 40 891	1	24	285
GW 40 891 BD	1	19	285
GW 40 891 BQ	1	19	285

GW 41

Code	Quantity		Page
	Pack/carton	Pallet	
GW 41 225 TB	16	128	281
GW 41 225 TN	16	128	281
GW 41 225 VA	16	128	281
GW 41 225 VT	16	128	281
GW 41 229 TB	12	192	281
GW 41 229 TN	12	192	281
GW 41 229 VA	12	96	281
GW 41 229 VT	12	96	281
GW 41 233 TB	5	125	281
GW 41 233 TN	5	80	281
GW 41 233 VA	5	40	281
GW 41 233 VT	5	40	281
GW 41 237 TB	12	240	281
GW 41 237 TN	12	240	281
GW 41 237 VA	12	240	281
GW 41 237 VT	12	240	281
GW 41 239 TB	5	60	281
GW 41 239 TN	5	60	281
GW 41 239 VA	5	60	281
GW 41 239 VT	5	60	281
GW 41 885 AB	12	144	260
GW 41 885 AB	12	144	286
GW 41 886 AB	5	75	260
GW 41 886 AB	5	75	286
GW 41 889 AB	3	36	260
GW 41 889 AB	3	36	286
GW 41 890 AB	2	54	260
GW 41 890 AB	2	54	286
GW 41 891 AB	1	19	260
GW 41 891 AB	1	19	286

GW 42

Code	Quantity		Page
	Pack/carton	Pallet	
GW 42 001	32	1024	249
GW 42 002	44	704	249
GW 42 003	32	512	249
GW 42 004	16	512	249
GW 42 005	21	336	249
GW 42 006	16	256	249
GW 42 007	10	160	249
GW 42 008	10	200	249
GW 42 009	8	128	249
GW 42 010	5	80	249
GW 42 201	1/10	1000	224
GW 42 202	1/10	200	225
GW 42 203	1/10	200	225
GW 42 204	1/10	400	224
GW 42 206	1/10	400	225
GW 42 207	1/10	160	225
GW 42 208	1/10	200	225
GW 42 211	1/10	1440	226

Code	Quantity		Page
	Pack/carton	Pallet	
GW 42 212	1/10	1280	226
GW 42 213	1/10	3120	226
GW 42 214	1/10	1440	226
GW 42 216	1/10	1560	226
GW 42 216	1/10	1560	1075
GW 42 231	1/10	240	225
GW 42 232	1/10	200	225
GW 43			
GW 43 021 S	1	120	212
GW 43 022 S	1	91	212
GW 43 023 S	1	48	212
GW 43 024 S	1	36	212
GW 43 040 S	100	31200	214
GW 43 042 S	2/20	6240	213
GW 43 044 S	10/100	3600	214
GW 43 052 S	1/10	1280	214
GW 43 071 S	1/4	364	213
GW 43 072 S	1/6	336	213
GW 43 073 S	1/2	120	213
GW 43 074 S	1/2	96	213
GW 43 111 S	1		213
GW 43 112 S	1	32	213
GW 43 113 S	1	20	213
GW 43 114 S	1	6	213
GW 43 122 S	1/10		214
GW 44			
GW 44 001	5/280	8400	233
GW 44 002	5/135	3780	233
GW 44 003	5/90	4050	233
GW 44 004	66	1980	233
GW 44 005	66	1980	233
GW 44 006	40	1000	233
GW 44 007	24	600	233
GW 44 008	12	300	233
GW 44 009	6	150	233
GW 44 010	4	100	233
GW 44 011	3	60	233
GW 44 024	66	1980	233
GW 44 026	40	1000	233
GW 44 051	5/280	5600	236
GW 44 051 R	5/280	5600	237
GW 44 052	5/135	2700	236
GW 44 053	5/90	1890	236
GW 44 053 R	5/90	2520	237
GW 44 054	66	1980	236
GW 44 054 R	66	1320	237
GW 44 055	66	528	238
GW 44 056	40	800	236
GW 44 056 R	40	640	237
GW 44 057	24	384	238
GW 44 058	12	192	238
GW 44 059	6	96	238
GW 44 060	4	64	238
GW 44 061	3	36	238
GW 44 114	1/45	900	235
GW 44 117	1/16	256	235
GW 44 118	1/12	144	235
GW 44 119	1/7	84	235
GW 44 120	1/3	60	235
GW 44 137	1/16	128	235
GW 44 138	1/12	144	235
GW 44 139	1/7	84	235
GW 44 140	1/3	60	235
GW 44 204	105	2625	234
GW 44 205	91	2730	234
GW 44 206	50	1250	234
GW 44 207	30	750	234
GW 44 208	14	350	234
GW 44 209	6	180	234
GW 44 210	4	100	234
GW 44 211	3	75	234
GW 44 214	45	900	234
GW 44 215	55	880	234
GW 44 216	24	600	234
GW 44 217	12	360	234
GW 44 218	12	240	234
GW 44 219	7	140	234
GW 44 220	3	75	234
GW 44 221	2	50	234
GW 44 234	105	2625	234
GW 44 236	50	1250	234
GW 44 254	45	360	239
GW 44 255	55	220	239
GW 44 256	24	96	239
GW 44 257	16	240	239
GW 44 258	12	144	239
GW 44 259	7	84	239
GW 44 260	3	48	239
GW 44 261	2	32	239
GW 44 274	105	1680	239
GW 44 275	91	1820	239
GW 44 276	50	800	239
GW 44 276 C	50	800	239
GW 44 277	30	480	239
GW 44 277 C	30	480	239
GW 44 278	14	224	239
GW 44 279	6	120	239
GW 44 280	4	64	239
GW 44 281	3	48	239
GW 44 404	108	1728	240
GW 44 405	108	1728	240
GW 44 406	50	800	240
GW 44 407	32	512	240
GW 44 408	14	224	240
GW 44 409	6	120	240
GW 44 410	4	64	240
GW 44 411	3	48	240
GW 44 414	45	360	240
GW 44 415	55	220	240
GW 44 416	24	384	240
GW 44 417	16	240	240
GW 44 418	12	144	240
GW 44 419	7	84	240
GW 44 420	3	48	240
GW 44 421	2	32	240
GW 44 426	50	800	241
GW 44 427	32	512	241
GW 44 428	14	224	241
GW 44 429	6	120	241
GW 44 430	4	100	241
GW 44 431	3	48	241
GW 44 436	24	384	241
GW 44 437	16	240	241
GW 44 438	12	144	241
GW 44 439	7	84	241
GW 44 440	3	48	241
GW 44 441	2	32	241
GW 44 601	10/480	14400	405
GW 44 602	10/240	7200	405
GW 44 603	10/160	4800	405
GW 44 604	10/120	2160	405
GW 44 605	3/36	1080	405
GW 44 606	10/100	7000	405
GW 44 607	10/100	7000	405
GW 44 608	10/100	7000	405
GW 44 609	10/100	4000	406
GW 44 610	10/100	4000	406
GW 44 610 C	10/100	4000	406
GW 44 611	10/100	2800	406
GW 44 612	10/100	2800	406
GW 44 613	1/10	1280	406
GW 44 614	1/10	1280	406
GW 44 615	20	2880	241
GW 44 615	20	2880	250
GW 44 616	20	1880	241
GW 44 616	20	1880	250
GW 44 617	20	1000	241
GW 44 617	20	1000	250
GW 44 618	5	520	241
GW 44 619	5	280	241
GW 44 620	10/160	2560	242
GW 44 621	40/480	13440	85
GW 44 621	40/480	13440	115
GW 44 621	40/480	13440	189
GW 44 621	40/480	13440	201
GW 44 621	40/480	13440	210
GW 44 621	40/480	13440	228
GW 44 621	40/480	13440	242
GW 44 622	10/100	14400	84
GW 44 622	10/100	14400	155
GW 44 622	10/100	14400	166
GW 44 622	10/100	14400	220
GW 44 622	10/100	14400	228
GW 44 622	10/100	14400	242
GW 44 622	10/100	14400	1066
GW 44 623	10/100	12800	84
GW 44 623	10/100	12800	155
GW 44 623	10/100	12800	204
GW 44 623	10/100	12800	210
GW 44 623	10/100	12800	228
GW 44 623	10/100	12800	242
GW 44 625	20	2560	241
GW 44 625	20	2560	250

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 44 626	20	1400	117
GW 44 626	20	1400	241
GW 44 626	20	1400	250
GW 44 627	20	1000	117
GW 44 627	20	1000	241
GW 44 627	20	1000	250
GW 44 628	4	320	117
GW 44 628	4	320	241
GW 44 629	5	430	241
GW 44 636	20	1620	188
GW 44 637	20	600	188
GW 44 638	5	260	188
GW 44 639	5	260	188
GW 44 646	20	1400	188
GW 44 647	20	1200	188
GW 44 648	4	272	188
GW 44 649	5	360	188
GW 44 661	10/450	13500	405
GW 44 662	10/450	10800	405
GW 44 663	10/300	4200	405
GW 44 664	10/240	8640	405
GW 44 665	10/450	12150	405
GW 44 666	5/150	6750	405
GW 44 667	5/150	6750	405
GW 44 671	10/100	7000	268
GW 44 671	10/100	7000	304
GW 44 671	10/100	7000	407
GW 44 672	10/100	7000	268
GW 44 672	10/100	7000	304
GW 44 672	10/100	7000	407
GW 44 673	10/50	4400	268
GW 44 673	10/50	4400	304
GW 44 673	10/50	4400	407
GW 44 674	10/50	3500	268
GW 44 674	10/50	3500	304
GW 44 674	10/50	3500	407
GW 44 675	5/25	2750	268
GW 44 675	5/25	2750	304
GW 44 675	5/25	2750	407
GW 44 676	1/10	1100	268
GW 44 676	1/10	1100	304
GW 44 676	1/10	1100	407
GW 44 681	100	16000	269
GW 44 681	100	16000	305
GW 44 681	100	16000	407
GW 44 682	200	62400	269
GW 44 682	200	62400	305
GW 44 682	200	62400	407
GW 44 683	1/50	2000	310
GW 44 683	1/50	2000	407
GW 44 691	1/40	2560	186
GW 44 691	1/40	2560	408
GW 44 691	1/40	2560	684
GW 44 693	1/12	768	186
GW 44 693	1/12	768	408
GW 44 693	1/12	768	684
GW 44 696	1/20	1280	186
GW 44 696	1/20	1280	408
GW 44 696	1/20	1280	684
GW 44 698	1/10	640	186
GW 44 698	1/10	640	408
GW 44 698	1/10	640	684
GW 44 699	1/12	192	186
GW 44 699	1/12	192	408
GW 44 699	1/12	192	684
GW 44 700	1/2	160	186
GW 44 700	1/2	160	684
GW 44 704	10/100	7000	268
GW 44 704	10/100	7000	304
GW 44 704	10/100	7000	406
GW 44 706	10/100	7000	268
GW 44 706	10/100	7000	304
GW 44 706	10/100	7000	406
GW 44 708	10/100	5000	268
GW 44 708	10/100	5000	304
GW 44 708	10/100	5000	406
GW 44 720	1/50	2000	268
GW 44 720	1/50	2000	304
GW 44 720	1/50	2000	406
GW 44 808	4	96	187
GW 44 809	4	80	187
GW 44 810	2	50	187
GW 44 811	2	40	187
GW 44 818	4	120	187
GW 44 819	4	80	187
GW 44 820	2	50	187
GW 44 821	2	24	187
GW 44 852	8	144	188
GW 44 853	8	96	188
GW 44 854	8	96	188
GW 44 855	8	192	188

GW 45

Code	Quantity		Page
	Pack/carton	Pallet	
GW 45 413	1	264	627
GW 45 413	1	264	649
GW 45 413	1	264	671
GW 45 414	1	264	627
GW 45 414	1	264	649
GW 45 414	1	264	671
GW 45 418	1	264	627
GW 45 418	1	264	649
GW 45 418	1	264	671
GW 45 419	1	264	627
GW 45 419	1	264	649
GW 45 419	1	264	671
GW 45 538	1	264	607
GW 45 545	1	50	684
GW 45 546	1	30	684
GW 45 547	1	70	684
GW 45 548	1	70	684
GW 45 551	1	340	685
GW 45 553	1	160	685
GW 45 554	1	80	685
GW 45 555	1	250	685
GW 45 557	1	175	685
GW 45 558	1	80	685
GW 45 559	1	100	629
GW 45 559	1	100	650
GW 45 560	1	100	672
GW 45 565	1	400	629
GW 45 565	1	400	650
GW 45 565	1	400	672
GW 45 566	1	40	629
GW 45 566	1	40	650
GW 45 566	1	40	672
GW 45 568	1	264	629
GW 45 568	1	264	650
GW 45 568	1	264	672
GW 45 569	1	264	629
GW 45 569	1	264	650
GW 45 569	1	264	672

GW 46

Code	Quantity		Page
	Pack/carton	Pallet	
GW 46 001 F	1	90	174
GW 46 002 F	1	84	174
GW 46 003 F	1	24	137
GW 46 003 F	1	24	174
GW 46 004 F	1	24	137
GW 46 004 F	1	24	174
GW 46 005 F	1	12	137
GW 46 005 F	1	12	174
GW 46 006 F	1	9	137
GW 46 006 F	1	9	174
GW 46 007 F	1	4	174
GW 46 031	1	90	176
GW 46 032	1	60	176
GW 46 033	1	28	176
GW 46 034	1	20	176
GW 46 035	1	18	176
GW 46 036	1	8	176
GW 46 037	1	4	176
GW 46 052	1	60	177
GW 46 054	1	20	177
GW 46 056	1	8	177
GW 46 201 F	1	90	175
GW 46 202 F	1	84	175
GW 46 203 F	1	24	137
GW 46 203 F	1	24	175
GW 46 204 F	1	24	137
GW 46 204 F	1	24	175
GW 46 205 F	1	12	137
GW 46 205 F	1	12	175
GW 46 206 F	1	9	137
GW 46 206 F	1	9	175
GW 46 207 F	1	4	175
GW 46 232	1	60	176
GW 46 233	1	28	176
GW 46 234	1	20	176
GW 46 235	1	18	176
GW 46 236	1	8	176
GW 46 237	1	4	176
GW 46 401	1/5	900	180
GW 46 402	1/5	480	180
GW 46 403	1/5	225	180
GW 46 404	1/4	200	180
GW 46 405	1/2	168	180

Code	Quantity		Page
	Pack/carton	Pallet	
GW 46 406	1/2	135	180
GW 46 407	1	20	180
GW 46 408	1/5	1350	180
GW 46 409	1/5	720	180
GW 46 410	1/5	400	180
GW 46 411	1/4	288	180
GW 46 412	1/3	138	180
GW 46 413	1/2	80	180
GW 46 414	1/5	120	178
GW 46 415	1/4	128	178
GW 46 416	1/5	80	178
GW 46 417	1/2	104	178
GW 46 418	1/2	104	178
GW 46 419	1	13	178
GW 46 420 F	1/10	480	178
GW 46 421 F	1/10	360	178
GW 46 422 F	1/10	240	178
GW 46 423 F	1/5	180	178
GW 46 424 F	1/5	90	178
GW 46 425 F	1/10	640	179
GW 46 426 F	1/10	500	179
GW 46 427 F	1/13	468	179
GW 46 428 F	1/5	400	179
GW 46 429 F	1/5	90	179
GW 46 430 F	1/10	500	179
GW 46 431 F	1/10	240	179
GW 46 432 F	1/10	320	179
GW 46 433 F	1/10	320	179
GW 46 434 F	1/10	220	179
GW 46 435 F	1/10	600	179
GW 46 436 F	1/10	550	179
GW 46 437 F	1/10	330	179
GW 46 438 F	1/10	150	179
GW 46 439 F	1/10	90	179
GW 46 445	10	1100	140
GW 46 445	10	1100	184
GW 46 445	10	1100	190
GW 46 446	20	1280	115
GW 46 446	20	1280	181
GW 46 446	20	1280	189
GW 46 447	1/10	200	140
GW 46 447	1/10	200	185
GW 46 447	1/10	200	597
GW 46 447	1/10	200	607
GW 46 447	1/10	200	629
GW 46 447	1/10	200	651
GW 46 447	1/10	200	673
GW 46 447	1/10	200	1186
GW 46 448	1/2	120	185
GW 46 448	1/2	120	628
GW 46 448	1/2	120	649
GW 46 448	1/2	120	671
GW 46 449	1/10	700	183
GW 46 450	10/100	39000	181
GW 46 451	20	1280	115
GW 46 451	20	1280	181
GW 46 451	20	1280	189
GW 46 461	1/5	1350	180

Code	Quantity		Page
	Pack/carton	Pallet	
GW 46 462	1/5	240	180
GW 46 463	1/5	360	180
GW 46 464	1/5	360	180
GW 46 465	1/4	168	180
GW 46 466	1/3	114	180
GW 46 467	1/2	40	180
GW 46 471	1/10	300	185
GW 46 471	1/10	300	628
GW 46 471	1/10	300	649
GW 46 471	1/10	300	672
GW 46 475 F	1/5	140	179
GW 46 476 F	1/5	90	179
GW 46 477 F	1/5	270	179
GW 46 478 F	1/5	140	179
GW 46 479 F	1	48	179
GW 46 501 F	1/6	180	175
GW 46 502 F	1/6	144	175
GW 46 503 F	1/8	72	175
GW 46 504 F	1/8	80	175
GW 46 505 F	1	22	175
GW 46 506 F	1	13	175
GW 46 507 F	1	10	175
GW 46 511 F	1/6	540	175
GW 46 512 F	1/6	144	175
GW 46 513 F	1/8	56	175
GW 46 514 F	1/8	160	175
GW 46 515 F	1	22	175
GW 46 516 F	1	13	175
GW 46 517 F	1	10	175
GW 46 521 F	1/20	1740	183
GW 46 522	10	3120	184
GW 46 522	10	3120	189
GW 46 523	10	1560	184
GW 46 523	10	1560	190
GW 46 524 F	1/4	812	182
GW 46 526	1/20	400	181
GW 46 530 F	1/10	400	179
GW 46 531 F	1/10	240	179
GW 46 532 F	1/10	240	179
GW 46 533 F	1/10	240	179
GW 46 534 F	1/10	120	179
GW 46 540	1/5	480	181
GW 46 541	1/5	360	181
GW 46 542	1/5	140	181
GW 46 543	1/5	120	181
GW 46 544	1/4	80	181
GW 46 551	1	80	182
GW 46 551	1	80	1230
GW 46 552	1	210	115
GW 46 552	1	210	182
GW 46 553	1	180	115
GW 46 553	1	180	182
GW 46 554	1	140	138
GW 46 554	1	140	182
GW 46 555	1	168	182
GW 46 557 F	1/10	700	182
GW 46 564	1/5	120	178
GW 46 565	1/4	56	178

Code	Quantity		Page
	Pack/carton	Pallet	
GW 46 566	1/5	100	178
GW 46 567	1/2	44	178
GW 46 568	1/2	44	178
GW 46 569	1	13	178
GW 46 570 F	1	50	180
GW 46 571 F	1	30	180
GW 46 572 F	1	30	180
GW 46 573 F	1	20	180
GW 46 577 F	1	55	180
GW 46 578 F	1	33	180
GW 46 579 F	1	22	180
GW 46 580	1/5	200	181
GW 46 581	1/5	140	181
GW 46 582	1/5	60	181
GW 46 583	1/5	60	181
GW 46 584	1/2	120	181
GW 46 591	1/10	880	182
GW 46 592 F	1/100	600	184

GW 47

Code	Quantity		Page
	Pack/carton	Pallet	
GW 47 001 E	1	12	602
GW 47 002 E	1	8	602
GW 47 003 E	1	10	602
GW 47 004 E	1	10	602
GW 47 011 E	1	10	602
GW 47 012 E	1	10	602
GW 47 013 E	1	8	602
GW 47 014 E	1	8	602
GW 47 021 E	1	11	602
GW 47 022 E	1	10	602
GW 47 023 E	1	8	602
GW 47 024 E	1	8	602
GW 47 031 E	1	10	603
GW 47 032 E	1	10	603
GW 47 033 E	1	8	603
GW 47 034 E	1	8	603
GW 47 041 E	1	10	603
GW 47 042 E	1	10	603
GW 47 043 E	1	8	603
GW 47 044 E	1	8	603
GW 47 062 E	1	10	603
GW 47 063 E	1	7	603
GW 47 064 E	1	9	603
GW 47 072	1	12	593
GW 47 073	1	11	593
GW 47 074	1	11	593
GW 47 082	1	10	593
GW 47 083	1	10	593
GW 47 084	1	10	593
GW 47 087	1	12	593
GW 47 088	1	10	593
GW 47 089	1	10	593
GW 47 116	1	10	598
GW 47 116	1	10	609
GW 47 117	1	10	598
GW 47 117	1	10	609
GW 47 118	1	10	598
GW 47 118	1	10	609
GW 47 119	1	10	609

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 47 121	1	12	598
GW 47 121	1	12	609
GW 47 122	1	12	598
GW 47 122	1	12	609
GW 47 123	1	10	598
GW 47 123	1	10	609
GW 47 124	1	10	609
GW 47 136	1	8	609
GW 47 137	1	8	609
GW 47 138	1	8	609
GW 47 139	1	8	609
GW 47 141	1	10	609
GW 47 142	1	10	609
GW 47 143	1	5	609
GW 47 144	1	10	609
GW 47 162	1	10	610
GW 47 163	1	10	610
GW 47 164	1	9	610
GW 47 171	1/10	240	604
GW 47 172	1/8	192	604
GW 47 173	1/10	360	594
GW 47 173	1/10	360	604
GW 47 174	1/10	180	594
GW 47 174	1/10	180	604
GW 47 175	1/10	360	594
GW 47 175	1/10	360	604
GW 47 177	1/10	250	1274
GW 47 178	1/10	300	594
GW 47 178	1/10	300	604
GW 47 179	1/10	300	594
GW 47 179	1/10	300	604
GW 47 181	1/10	480	605
GW 47 182	1/10	240	605
GW 47 183	1/10	240	605
GW 47 186	1/5	60	605
GW 47 187	1/5	80	605
GW 47 191	1/20	2880	596
GW 47 191	1/20	2880	606
GW 47 192	1/10	1440	597
GW 47 192	1/10	1440	608
GW 47 193	1/5	300	597
GW 47 193	1/5	300	607
GW 47 194 E	1/20	800	596
GW 47 194 E	1/20	800	606
GW 47 195	10/100	14400	597
GW 47 195	10/100	14400	608
GW 47 197	1/10	1280	597
GW 47 198	1/10	150	610
GW 47 251	1/10	480	595
GW 47 252	1/10	120	595
GW 47 253	1/10	180	595
GW 47 291	10	800	183
GW 47 291	10	800	596
GW 47 291	10	800	606
GW 47 297	1/5	35	604
GW 47 298	1/5	35	604
GW 47 299	1/5	35	604
GW 47 650	1	500	689
GW 47 652	1	500	689
GW 47 653	1	500	689
GW 47 654	1	50	689
GW 47 655	1	50	689
GW 47 691	1/5	200	627
GW 47 691	1/5	200	649
GW 47 691	1/5	200	671
GW 47 692	1/5	125	627
GW 47 692	1/5	125	649
GW 47 692	1/5	125	671

GW 48

Code	Quantity		Page
	Pack/carton	Pallet	
GW 48 001	162	3240	301
GW 48 002	114	2280	301
GW 48 003	84	1680	301
GW 48 004	64	1280	301
GW 48 005	49	980	301
GW 48 006	34	680	301
GW 48 006 P	70	840	266
GW 48 006 P	70	840	302
GW 48 006 PM	1/30	600	265
GW 48 007	22	440	301
GW 48 007 P	60	720	266
GW 48 007 P	60	720	302
GW 48 007 PM	1/21	420	265
GW 48 008	17	340	301
GW 48 008 P	50	800	266
GW 48 008 P	50	800	302
GW 48 008 PM	1/14	280	265
GW 48 009	17	204	301
GW 48 009 P	40	360	266
GW 48 009 P	40	360	302
GW 48 009 PM	1/12	240	265
GW 48 010	9	135	301
GW 48 010 P	30	270	302
GW 48 011	5	100	301
GW 48 011 P	25	175	302
GW 48 012	50/300	16200	267
GW 48 012	50/300	16200	303
GW 48 013	10/120	6480	303
GW 48 014	10/100	6400	303
GW 48 015	10/100	5000	303
GW 48 016	10/100	4000	303
GW 48 017	10/100	3600	267
GW 48 017	10/100	3600	303
GW 48 017 AB	1/50	900	266
GW 48 017 AB	1/50	900	302
GW 48 018	10/80	2400	267
GW 48 018	10/80	2400	303
GW 48 018 AB	80/40	200	266
GW 48 018 AB	80/40	200	302
GW 48 019	10/40	1600	267
GW 48 019	10/40	1600	303
GW 48 019 AB	1/20	640	266
GW 48 019 AB	1/20	640	302
GW 48 020	10/40	360	267
GW 48 020	10/40	360	303
GW 48 020 AB	1/20	140	266
GW 48 020 AB	1/20	140	302
GW 48 021	10/30	720	303
GW 48 022	10/20	220	303
GW 48 023	300/4200		267
GW 48 023	300/4200		303
GW 48 024	10/200	5600	310
GW 48 026	5/25	700	293
GW 48 026	5/25	700	310
GW 48 051	10	3120	266
GW 48 051	10	3120	302
GW 48 084	1/10	280	303
GW 48 085	1/8	128	303
GW 48 086	1/10	180	267
GW 48 086	1/10	180	303
GW 48 087	1/5	90	267
GW 48 087	1/5	90	303
GW 48 088	1/5	140	267
GW 48 088	1/5	140	303
GW 48 116	30	600	302
GW 48 116 PM	30	240	266
GW 48 117	20	240	302
GW 48 117 PM	20	80	266
GW 48 118	10	300	302
GW 48 118 PM	10	300	266
GW 48 119	10	800	302
GW 48 119 PM	10	40	266
GW 48 126 PM	1/30	360	265
GW 48 207	8	200	306
GW 48 207 PM	8	128	270
GW 48 211	6	120	306
GW 48 211 PM	6	96	270
GW 48 227	4	100	306
GW 48 231	4	64	306
GW 48 247	1/15	420	270
GW 48 247	1/15	420	307
GW 48 251	1/10	200	270
GW 48 251	1/10	200	307
GW 48 267	1/10	80	270
GW 48 267	1/10	80	307
GW 48 271	1/5	100	270
GW 48 271	1/5	100	307
GW 48 621	1/30	810	312
GW 48 622	1/20	540	312
GW 48 623	1/15	270	312
GW 48 643	1/100	12800	311
GW 48 644	1/10	1280	227
GW 48 644	1/10	1280	295
GW 48 644	1/10	1280	311
GW 48 645	1/100	7000	228
GW 48 645	1/100	7000	262
GW 48 645	1/100	7000	292
GW 48 645	1/100	7000	311
GW 48 651	1/30	810	312
GW 48 671	1/28	448	308
GW 48 672	1/14	224	308
GW 48 673	1/9	135	308
GW 48 681	1/6	252	291
GW 48 681	1/6	252	309
GW 48 682	1/4	96	291

Code	Quantity		Page
	Pack/carton	Pallet	
GW 48 682	1/4	96	309
GW 48 686	1/4	160	291
GW 48 686	1/4	160	309
GW 48 691	1/28	448	308
GW 49			
GW 49 678	1	90	685
GW 49 679	1	55	685
GW 49 680	1	27	685
GW 50			
GW 50 201	20/60	1920	337
GW 50 201	20/60	1920	394
GW 50 202	20/120	4560	337
GW 50 202	20/120	4560	394
GW 50 203	10/40	800	337
GW 50 203	10/40	800	394
GW 50 204	10/60	960	337
GW 50 204	10/60	960	394
GW 50 205	6/30	1080	337
GW 50 205	6/30	1080	394
GW 50 206	6/36	432	337
GW 50 206	6/36	432	394
GW 50 207	20/60	9000	337
GW 50 207	20/60	9000	394
GW 50 208	20/120	6000	337
GW 50 208	20/120	6000	394
GW 50 209	20/120	2880	337
GW 50 209	20/120	2880	394
GW 50 210	10/20	1280	337
GW 50 210	10/20	1280	394
GW 50 211	6/30	540	337
GW 50 211	6/30	540	394
GW 50 212	6/36	432	337
GW 50 212	6/36	432	394
GW 50 415	25/200	8000	352
GW 50 415	25/200	8000	381
GW 50 416	25/200	14400	352
GW 50 416	25/200	14400	381
GW 50 417	25/150	7500	352
GW 50 417	25/150	7500	381
GW 50 418	10/100	1800	352
GW 50 418	10/100	1800	381
GW 50 419	6/60	1080	352
GW 50 419	6/60	1080	381
GW 50 420	5/50	900	352
GW 50 420	5/50	900	381
GW 50 421	50/700	12600	381
GW 50 422	50/700	12600	381
GW 50 423	25/350	6300	381
GW 50 424	25/350	6300	381
GW 50 425	15/210	3360	381
GW 50 426	10/160	2560	381
GW 50 427	10/90	1440	381
GW 50 428	100/1000		242
GW 50 428	100/1000		381
GW 50 429	100/1000	50000	242
GW 50 429	100/1000	50000	381
GW 50 430	100/1000	30000	242

Code	Quantity		Page
	Pack/carton	Pallet	
GW 50 430	100/1000	30000	381
GW 50 431	50/500	21000	242
GW 50 431	50/500	21000	381
GW 50 432	35/350	11200	242
GW 50 432	35/350	11200	381
GW 50 601	100/1800	97200	386
GW 50 602	100/1600	86400	386
GW 50 603	100/900	54000	386
GW 50 604	100/900	32400	386
GW 50 605	100/900	54000	386
GW 50 606	100/900	54000	386
GW 50 607	100/600	36000	386
GW 50 608	50/450	27000	386
GW 50 609	50/350	18900	386
GW 50 610	100/8000		388
GW 50 611	100/8000		388
GW 50 612	100/8000		388
GW 50 613	100/6000		388
GW 50 614	100/6000		388
GW 50 615	100/6000		388
GW 50 616	100/3000		388
GW 50 617	100/1800	72000	388
GW 50 618	100/2000	12000	388
GW 50 619	50/900	36000	388
GW 50 620	50/1000	6000	388
GW 50 621	100/8000		388
GW 50 622	100/8000		388
GW 50 623	100/4000		388
GW 50 624	100/15000		388
GW 50 625	100/4800		388
GW 50 626	100/1000	16000	388
GW 50 627	100/1000	16000	388
GW 50 628	50/450	27000	386
GW 50 629	50/450	5400	386
GW 50 630	35/350	7000	386
GW 50 631	25/200	4000	386
GW 50 651	75/900	24000	386
GW 50 652	25/250	12000	386
GW 50 653	15/150	7200	386
GW 50 791	1/10	600	390
GW 50 792	10/100	1600	390
GW 50 798	1/10	200	390
GW 50 799	200/4000		390
GW 50 801	100/1600	38400	389
GW 50 802	100/800	24000	389
GW 50 803	100/800	38400	389
GW 50 804	100/800	28800	389
GW 50 805	100/800	26400	389
GW 50 806	100/600	12000	389
GW 50 807	100/600	14400	389
GW 50 808	100/600	14400	389
GW 50 809	100/300	9000	389
GW 50 810	50/300	7200	389
GW 50 811	100/2400	28800	389
GW 50 812	100/2000	36000	389
GW 50 813	100/2000	36000	389
GW 50 814	100/1600	38400	389
GW 50 815	100/1000	30000	389

Code	Quantity		Page
	Pack/carton	Pallet	
GW 50 816	50/1000	18000	389
GW 50 817	50/1000	18000	389
GW 50 818	50/600	14400	389
GW 50 819	50/600	7200	389
GW 50 820	50/300	7200	389
GW 50 821	100/2400		389
GW 50 822	100/3500	63000	389
GW 50 823	100/2000	56000	389
GW 50 824	100/1600	38400	389
GW 50 825	100/2000	24000	389
GW 50 826	50/1000	28000	389
GW 50 827	50/800	14400	389
GW 50 828	50/600	7200	389
GW 50 829	50/600	7200	389
GW 50 830	50/300	7200	389
GW 52			
GW 52 001	50/900	81000	378
GW 52 002	50/600	42000	378
GW 52 003	25/500	27000	378
GW 52 004	25/500	27000	378
GW 52 005	25/375	18750	378
GW 52 006	25/400	9600	378
GW 52 007	25/250	5000	378
GW 52 008	10/130	3120	378
GW 52 009	6/120	1440	378
GW 52 010	5/100	1200	378
GW 52 024	15/300	7200	379
GW 52 025	15/240	4320	379
GW 52 026	15/240	3840	379
GW 52 027	15/135	2160	379
GW 52 028	6/54	972	379
GW 52 029	4/80	480	379
GW 52 042	50/600	25200	378
GW 52 043	50/400	21600	378
GW 52 044	25/300	18000	378
GW 52 045	25/200	11200	378
GW 52 046	25/150	6750	378
GW 52 047	10/120	2400	378
GW 52 048	6/84	2016	378
GW 52 049	5/60	600	378
GW 52 071	50/600	24000	378
GW 52 072	50/400	38400	378
GW 52 073	50/600	36000	378
GW 52 074	25/300	18000	378
GW 52 075	25/300	18000	378
GW 52 076	25/200	11200	378
GW 52 077	25/150	6750	378
GW 52 078	10/120	2400	378
GW 52 079	6/84	2016	378
GW 52 080	5/60	1200	378
GW 52 201	100/4000	64000	404
GW 52 202	100/3000	48000	404
GW 52 203	100/1000	16000	404
GW 52 204	100/3000	24000	404
GW 52 205	100/1200	38400	404
GW 52 206	100/1000	24000	404
GW 52 207	100/500	12000	404
GW 52 208	100/500	4000	404

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 52 209	100/3000	54000	404
GW 52 210	100/3000	96000	404
GW 52 226	100/3000		402
GW 52 227	100/3000		402
GW 52 228	100/3000		403
GW 52 229	100/3000		403
GW 52 231	1000/20000		401
GW 52 232	1000/20000		401
GW 52 233	100/10000		401
GW 52 234	100/10000		401
GW 52 235	100/10000		401
GW 52 236	100/10000		401
GW 52 237	100/5000		401
GW 52 238	100/5000		401
GW 52 239	100/5000		401
GW 52 240	100/5000		401
GW 52 241	100/1000	50000	401
GW 52 242	50/500	35000	401
GW 52 243	50/500	7500	401
GW 52 251	1000/20000		401
GW 52 252	1000/20000		401
GW 52 253	100/10000		401
GW 52 254	100/10000		401
GW 52 255	100/10000		401
GW 52 256	100/10000		401
GW 52 257	100/5000		401
GW 52 258	100/5000		401
GW 52 259	100/5000		401
GW 52 260	100/5000		401
GW 52 261	100/1000	55000	401
GW 52 262	50/500	32500	401
GW 52 263	50/500	15000	401
GW 52 271	100/1000	64000	402
GW 52 272	100/1000	27000	402
GW 52 273	100/1000	27000	402
GW 52 281	100/5000		402
GW 52 282	100/2000	54000	402
GW 52 291	100/5000		402
GW 52 292	100/5000		402
GW 52 293	100/2000	54000	402
GW 52 294	100/2000	54000	402
GW 52 341	100/1000	50000	380
GW 52 342	100/1000	50000	380
GW 52 343	100/800	40000	380
GW 52 344	100/800	40000	380
GW 52 345	100/600	30000	380
GW 52 346	100/500	14000	380
GW 52 347	50/250	12500	380
GW 52 348	25/200	10000	380
GW 52 349	25/150	5400	380
GW 52 350	25/100	3600	380
GW 52 352	100/1000	50000	380
GW 52 353	100/1000	50000	380
GW 52 354	100/800	40000	380
GW 52 355	100/800	40000	380
GW 52 356	100/600	16800	380
GW 52 357	100/500	25000	380
GW 52 358	50/250	12500	380
GW 52 359	25/125	4500	380
GW 52 361	100/500		379
GW 52 362	100/500		379
GW 52 363	100/400	20000	379
GW 52 364	100/400	28000	379
GW 52 365	100/300	21000	379
GW 52 366	100/300	21000	379
GW 52 367	50/250	7000	379
GW 52 368	25/150	7500	379
GW 52 369	25/125	6250	379
GW 52 370	10/100	5000	379
GW 52 372	100/500		379
GW 52 373	100/500		379
GW 52 374	100/400	20000	379
GW 52 375	100/400	28000	379
GW 52 376	50/250	17500	379
GW 52 377	50/200	5600	379
GW 52 378	25/150	7500	379
GW 52 379	10/100	4000	379
GW 52 401	1/4	512	242
GW 52 401	1/4	512	391
GW 52 402	10	1280	250
GW 52 402	10	1280	391
GW 52 403	10	1280	391
GW 52 410	1/10	640	403
GW 52 411	1/10	640	404
GW 52 412	1/4	512	391
GW 52 420	1	24	390
GW 52 441	500/2500		379
GW 52 442	500/2500		379
GW 52 443	500/2000		379
GW 52 444	500/2000		379
GW 52 445	500/2000		379
GW 52 446	500/1500		379
GW 52 447	250/1250	87500	379
GW 52 448	100/1000	70000	379
GW 52 449	50/500		379
GW 52 450	50/400		379
GW 52 452	500/2500		379
GW 52 453	500/2500		379
GW 52 454	500/2000		379
GW 52 455	500/2000		379
GW 52 456	250/1250	87500	379
GW 52 457	50/1250	87500	379
GW 52 458	500/1000	70000	379
GW 52 459	50/500	35000	379

GW 60

Code	Quantity		Page
	Pack/carton	Pallet	
GW 60 001 FH	25	450	24
GW 60 001 H	50	1600	26
GW 60 002 FH	15	240	24
GW 60 002 H	50	800	26
GW 60 003 FH	50	200	24
GW 60 003 H	15	240	26
GW 60 004 FH	50	800	24
GW 60 004 H	50	2400	26
GW 60 005 FH	15	360	24
GW 60 005 H	25	450	26
GW 60 005 WH	15	240	28
GW 60 006 FH	15	240	24
GW 60 006 H	15	360	26
GW 60 006 WH	15	240	28
GW 60 007 FH	15	240	24
GW 60 007 H	15	360	26
GW 60 008 FH	25	450	24
GW 60 008 H	50	1700	26
GW 60 008 WH	15	360	28
GW 60 009 FH	50	400	24
GW 60 009 H	50	1200	26
GW 60 009 WH	15	960	28
GW 60 010 H	15	360	26
GW 60 011 H	15	360	26
GW 60 012 FH	15	240	24
GW 60 012 H	15	360	26
GW 60 013 FH	15	240	24
GW 60 013 H	15	360	26
GW 60 014 FH	15	240	24
GW 60 014 H	15	240	26
GW 60 015 FH	15	360	24
GW 60 015 H	25	1050	26
GW 60 016 FH	15	240	24
GW 60 016 H	50	400	26
GW 60 016 WH	15	240	28
GW 60 017 FH	15	240	24
GW 60 017 H	15	240	26
GW 60 017 WH	15	240	28
GW 60 018 FH	15	240	24
GW 60 018 H	15	360	26
GW 60 019 FH	15	360	24
GW 60 019 H	50	1200	26
GW 60 019 WH	15	360	28
GW 60 020 FH	15	360	24
GW 60 020 H	25	800	26
GW 60 020 WH	15	360	28
GW 60 021 H	15	360	26
GW 60 022 H	15	240	26
GW 60 023 FH	15	240	25
GW 60 023 H	25	450	27
GW 60 024 FH	15	240	25
GW 60 024 H	15	360	27
GW 60 025 FH	15	180	25
GW 60 025 H	15	180	27
GW 60 026 FH	50	1200	25
GW 60 026 H	50	1600	27
GW 60 027 FH	15	240	25
GW 60 027 H	15	360	27
GW 60 027 WH	15	240	29
GW 60 028 FH	15	270	25
GW 60 028 H	15	270	27
GW 60 028 WH	15	120	29
GW 60 029 FH	15	240	25
GW 60 029 H	15	240	27
GW 60 030 FH	15	360	25
GW 60 030 H	25	1050	27
GW 60 030 WH	15	360	29
GW 60 031 FH	25	200	25
GW 60 031 H	25	600	27

Code	Quantity		Page
	Pack/carton	Pallet	
GW 60 031 WH	15	270	29
GW 60 032 H	15	360	27
GW 60 033 H	15	180	27
GW 60 034 FH	15	180	25
GW 60 034 H	15	270	27
GW 60 035 FH	15	90	25
GW 60 035 H	15	270	27
GW 60 036 FH	15	180	25
GW 60 036 H	15	180	27
GW 60 037 FH	15	270	25
GW 60 037 H	15	270	27
GW 60 038 FH	15	180	25
GW 60 038 H	15	270	27
GW 60 038 WH	15	120	29
GW 60 039 FH	15	180	25
GW 60 039 H	15	180	27
GW 60 039 WH	15	120	29
GW 60 040 FH	15	180	25
GW 60 040 H	15	180	27
GW 60 041 FH	15	90	25
GW 60 041 H	15	270	27
GW 60 041 WH	15	270	29
GW 60 042 FH	15	270	25
GW 60 042 H	25	600	27
GW 60 042 WH	15	270	29
GW 60 043 H	15	270	27
GW 60 044 H	15	180	27
GW 60 056 H	1/2	48	31
GW 60 057 H	1/2	48	31
GW 60 058 H	1/2	48	31
GW 60 059 H	1/2	48	31
GW 60 060 H	1/2	128	31
GW 60 061 H	1/2	128	31
GW 60 062 H	1/2	48	31
GW 60 063 H	1/2	48	31
GW 60 064	10/40	2880	59
GW 60 065	10/20	720	59
GW 60 066	10/20	800	59
GW 60 067	10/20	800	59
GW 60 068	10/20	720	59
GW 60 069	10/20	960	59
GW 60 070	10/20	720	59
GW 60 071	10/20	960	59
GW 60 072	10/20	960	59
GW 60 073	10/20	960	59
GW 60 074	10/20	960	59
GW 60 075	10/20	800	59
GW 60 076	10/20	720	59
GW 60 077	10/20	960	59
GW 60 078	10/20	960	59
GW 60 079	10/20	960	59
GW 60 080	10/20	960	59
GW 60 081	10/20	960	59
GW 60 082	10/40	1440	32
GW 60 083	10/20	280	32
GW 60 084	10/20	280	32
GW 60 085	10/40	960	32
GW 60 086	10/20	280	32

Code	Quantity		Page
	Pack/carton	Pallet	
GW 60 087	10/20	280	32
GW 60 088	10/20	720	32
GW 60 089	10/40	800	32
GW 60 090	10/40	480	32
GW 60 091	10/20	280	32
GW 60 092	10/20	280	32
GW 60 093	8/16	512	32
GW 60 094	8/16	512	32
GW 60 095	8/16	512	32
GW 60 096	8/16	384	32
GW 60 097	8/16	512	32
GW 60 098	8/16	512	32
GW 60 099	8/16	384	32
GW 60 101	8/16	384	32
GW 60 102	8/16	384	32
GW 60 103	8/16	512	32
GW 60 104	8/16	384	32
GW 60 105	10/20	280	33
GW 60 106	10/20	640	33
GW 60 107	10/20	360	33
GW 60 108	10/40	480	33
GW 60 109	10/20	480	33
GW 60 110	10/20	320	33
GW 60 111	10/20	280	33
GW 60 112	10/40	640	33
GW 60 113	10/40	480	33
GW 60 114	10/20	480	33
GW 60 115	10/20	400	33
GW 60 116	8/16	288	33
GW 60 117	8/16	288	33
GW 60 118	8/16	288	33
GW 60 119	8/16	288	33
GW 60 120	8/16	288	33
GW 60 121	8/16	288	33
GW 60 122	8/16	288	33
GW 60 123	8/16	288	33
GW 60 124	8/16	288	33
GW 60 125	8/16	288	33
GW 60 126	8/16	288	33
GW 60 127	10/40	800	59
GW 60 128	10/20	280	59
GW 60 129	10/20	280	59
GW 60 130	10/20	280	59
GW 60 131	10/20	280	59
GW 60 132	10/20	280	59
GW 60 133	10/20	280	59
GW 60 134	10/20	280	59
GW 60 135	10/20	280	59
GW 60 136	10/20	280	59
GW 60 137	10/20	280	59
GW 60 138	10/20	280	59
GW 60 139	10/20	280	59
GW 60 140	10/20	280	59
GW 60 141	10/20	280	59
GW 60 142	10/20	280	59
GW 60 143	10/20	280	59
GW 60 144	10/20	280	59
GW 60 145 H	25	200	27

Code	Quantity		Page
	Pack/carton	Pallet	
GW 60 146	8/16	288	33
GW 60 201	10/20	480	34
GW 60 202	10/20	640	34
GW 60 203	10/20	640	34
GW 60 204	10/20	480	34
GW 60 205	10/20	480	34
GW 60 206	10/20	640	34
GW 60 207	10/20	480	34
GW 60 208	10/20	640	34
GW 60 209	10/20	400	34
GW 60 210	10/20	640	34
GW 60 211	10/20	480	34
GW 60 212	8/16	288	34
GW 60 213	8/16	288	34
GW 60 214	8/16	288	34
GW 60 215	8/16	288	34
GW 60 216	8/16	288	34
GW 60 217	8/16	288	34
GW 60 218	8/16	288	34
GW 60 219	8/16	288	34
GW 60 220	8/16	288	34
GW 60 221	8/16	288	34
GW 60 222	8/16	288	34
GW 60 223	10/20	400	35
GW 60 224	10/20	240	35
GW 60 225	10/20	400	35
GW 60 226	10/20	360	35
GW 60 227	10/20	360	35
GW 60 228	10/20	360	35
GW 60 229	10/20	400	35
GW 60 230	10/20	400	35
GW 60 231	10/20	400	35
GW 60 232	10/20	400	35
GW 60 233	10/20	400	35
GW 60 234	8/16	288	35
GW 60 235	8/16	288	35
GW 60 236	8/16	96	35
GW 60 237	8/16	192	35
GW 60 238	8/16	288	35
GW 60 239	8/16	128	35
GW 60 240	8/16	288	35
GW 60 241	8/16	288	35
GW 60 242	8/16	96	35
GW 60 243	8/16	288	35
GW 60 244	8/16	128	35
GW 60 263	10/120	1440	39
GW 60 264	10/120	1440	39
GW 60 265	10/80	880	39
GW 60 266	8/64	576	39
GW 60 267	8/64	576	39
GW 60 268	8/16	288	35
GW 60 269	5/40	960	39
GW 60 270	5/20	480	39
GW 60 401	10/20	840	36
GW 60 402	10/20	480	36
GW 60 403	10/20	400	36
GW 60 404	10/40	960	36
GW 60 405	10/20	640	36

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 60 406	10/20	400	36
GW 60 407	10/20	640	36
GW 60 408	10/40	960	36
GW 60 409	10/20	280	36
GW 60 410	10/20	640	36
GW 60 411	10/20	400	36
GW 60 412	8/16	512	36
GW 60 413	8/16	384	36
GW 60 414	8/16	320	36
GW 60 415	8/16	1024	36
GW 60 416	8/16	384	36
GW 60 417	8/16	320	36
GW 60 418	8/16	512	36
GW 60 419	8/16	384	36
GW 60 420	8/16	672	36
GW 60 421	8/16	512	36
GW 60 422	8/16	320	36
GW 60 423	10/20	400	37
GW 60 424	10/20	400	37
GW 60 425	10/20	240	37
GW 60 426	10/40	960	37
GW 60 427	10/20	400	37
GW 60 428	10/20	240	37
GW 60 429	10/20	400	37
GW 60 430	10/40	480	37
GW 60 431	10/20	680	37
GW 60 432	10/20	400	37
GW 60 433	10/20	240	37
GW 60 434	8/16	192	37
GW 60 435	8/16	192	37
GW 60 436	8/16	192	37
GW 60 437	8/16	544	37
GW 60 438	8/16	192	37
GW 60 439	8/16	192	37
GW 60 440	8/16	192	37
GW 60 441	8/16	224	37
GW 60 442	8/16	544	37
GW 60 443	8/16	192	37
GW 60 444	8/16	192	37
GW 60 456	1/2	36	38
GW 60 457	1/2	24	38
GW 60 458	1/2	36	38
GW 60 459	1/2	24	38
GW 60 460	1/2	48	38
GW 60 461	1/2	48	38
GW 60 462	1/2	32	38
GW 60 463	1/2	48	38
GW 60 464	10/40	800	60
GW 60 465	10/20	280	60
GW 60 466	10/20	280	60
GW 60 467	10/20	560	60
GW 60 468	10/20	280	60
GW 60 469	10/20	280	60
GW 60 470	10/20	280	60
GW 60 471	10/20	280	60
GW 60 472	10/20	280	60
GW 60 473	10/20	280	60
GW 60 474	10/20	280	60
GW 60 475	10/20	280	60
GW 60 476	10/20	280	60
GW 60 477	10/20	280	60
GW 60 478	10/20	280	60
GW 60 479	10/20	280	60
GW 60 480	10/20	280	60
GW 60 481	10/20	280	60
GW 60 482	8/16	192	37
GW 60 664 H	1/2	48	31
GW 60 665 H	1/2	48	31
GW 60 666 H	1/2	48	31
GW 60 667 H	1/2	48	31
GW 60 668 H	1/2	48	31
GW 60 669 H	1/2	48	31
GW 60 670 H	1/2	48	31
GW 60 671 H	1/2	48	31
GW 60 672 H	1/2	48	31
GW 60 673 H	1/2	48	31
GW 60 674 H	1/2	48	31
GW 60 675 H	1/2	48	31
GW 60 676 H	1/2	48	31
GW 60 677 H	1/2	48	31
GW 60 701 H	15	240	26
GW 60 702 H	15	240	26
GW 60 703 H	15	240	26
GW 60 704 H	15	240	26
GW 60 705 H	15	240	26
GW 60 706 H	15	240	26
GW 60 707 H	15	240	26
GW 60 708 H	15	240	26
GW 60 709 H	15	240	26
GW 60 710 H	15	240	26
GW 60 711 H	15	240	26
GW 60 712 H	15	240	26
GW 60 713 H	15	240	26
GW 60 714 H	15	240	26
GW 60 715 H	15	240	26
GW 60 716 H	15	240	26
GW 60 717 H	15	240	26
GW 60 718 H	15	240	26
GW 60 719 H	15	240	26
GW 60 720 H	15	240	26
GW 60 721 H	15	240	26
GW 60 722 H	15	240	26
GW 60 723 H	15	240	26
GW 60 724 H	15	240	26
GW 60 725 H	15	240	26
GW 60 726 H	15	240	26
GW 60 727 H	15	240	26
GW 60 728 H	15	240	26
GW 60 729 H	15	240	26
GW 60 730 H	15	240	26
GW 60 731 H	15	240	26
GW 60 732 H	15	240	26
GW 60 733 H	15	240	26
GW 60 734 H	15	240	26
GW 60 735 H	15	240	27
GW 60 736 H	15	240	27
GW 60 737 H	15	180	27
GW 60 738 H	15	240	27
GW 60 739 H	15	240	27
GW 60 740 H	15	180	27
GW 60 741 H	15	240	27
GW 60 742 H	15	240	27
GW 60 743 H	15	180	27
GW 60 744 H	15	240	27
GW 60 745 H	15	180	27
GW 60 746 H	15	240	27
GW 60 747 H	15	180	27
GW 60 748 H	15	240	27
GW 60 749 H	15	240	27
GW 60 750 H	15	240	27
GW 60 751 H	15	240	27
GW 60 752 H	15	180	27
GW 60 753 H	15	180	27
GW 60 754 H	15	180	27
GW 60 755 H	15	180	27
GW 60 756 H	15	180	27
GW 60 757 H	15	180	27
GW 60 758 H	15	180	27
GW 60 759 H	15	180	27
GW 60 760 H	15	180	27
GW 60 761 H	15	180	27
GW 60 762 H	15	180	27
GW 60 763 H	15	180	27
GW 60 764 H	15	180	27
GW 60 765 H	15	180	27
GW 60 766 H	15	180	27
GW 60 767 H	15	180	27

GW 61

GW 61 013 H	1/4	144	30
GW 61 014 H	1/4	144	30
GW 61 015 H	1/4	144	30
GW 61 016 H	1/4	144	30
GW 61 017 H	1/4	144	30
GW 61 018 H	1/4	144	30
GW 61 019 H	1/4	144	30
GW 61 020 H	1/4	144	30
GW 61 021 H	1/4	144	30
GW 61 045 H	1/4	144	31
GW 61 046 H	1/4	144	31
GW 61 047 H	1/4	144	31
GW 61 048 H	1/4	144	31
GW 61 049 H	1/4	144	31
GW 61 050 H	1/4	96	31
GW 61 051 H	1/4	144	31
GW 61 052 H	1/4	384	31
GW 61 053 H	1/4	384	31
GW 61 054 H	1/4	144	31
GW 61 055 H	1/4	144	31
GW 61 056 H	1/4	48	31
GW 61 057 H	1/4	144	31
GW 61 058 H	1/4	144	31
GW 61 059 H	1/4	144	31
GW 61 060 H	1/4	144	31
GW 61 061 H	1/4	144	31

Code	Quantity		Page
	Pack/carton	Pallet	
GW 61 062 H	1/4	144	31
GW 61 063 H	1/4	144	31
GW 61 064 H	1/4	144	31
GW 61 065 H	1/4	96	31
GW 61 066 H	1/4	144	31
GW 61 067 H	1/4	144	31
GW 61 068 H	1/4	144	31
GW 61 445	1/4	48	38
GW 61 446	1/4	48	38
GW 61 447	1/4	48	38
GW 61 448	1/4	96	38
GW 61 449	1/4	48	38
GW 61 450	1/4	48	38
GW 61 451	1/4	48	38
GW 61 452	1/4	96	38
GW 61 453	1/4	288	38
GW 61 454	1/4	48	38
GW 61 455	1/4	48	38

GW 62

Code	Quantity		Page
	Pack/carton	Pallet	
GW 62 001 FH	15	360	40
GW 62 001 H	50	1600	42
GW 62 002 FH	15	240	40
GW 62 002 H	50	400	42
GW 62 003 FH	15	240	40
GW 62 003 H	25	300	42
GW 62 004 FH	50	800	40
GW 62 004 H	50	2400	42
GW 62 005 FH	15	240	40
GW 62 005 H	15	360	42
GW 62 006 FH	15	240	40
GW 62 006 H	15	240	42
GW 62 007 FH	15	240	40
GW 62 007 H	15	240	42
GW 62 008 FH	15	360	40
GW 62 008 H	50	1600	42
GW 62 009 FH	15	360	40
GW 62 009 H	25	1050	42
GW 62 010 H	15	240	42
GW 62 011 H	15	240	42
GW 62 012 FH	15	240	40
GW 62 012 H	15	360	42
GW 62 013 FH	15	240	40
GW 62 013 H	15	240	42
GW 62 014 FH	15	180	40
GW 62 014 H	15	180	42
GW 62 015 FH	15	360	40
GW 62 015 H	25	800	42
GW 62 016 FH	15	240	40
GW 62 016 H	15	360	42
GW 62 017 FH	15	180	40
GW 62 017 H	15	180	42
GW 62 018 FH	15	360	40
GW 62 018 H	15	240	42
GW 62 019 FH	15	360	40
GW 62 019 H	25	800	42
GW 62 020 FH	15	270	40
GW 62 020 H	25	800	42
GW 62 021 H	15	240	42
GW 62 022 H	15	180	42
GW 62 023 FH	15	240	41
GW 62 023 H	50	400	43
GW 62 024 FH	25	300	41
GW 62 024 H	15	180	43
GW 62 025 FH	15	180	41
GW 62 025 H	15	180	43
GW 62 026 FH	50	400	41
GW 62 026 H	50	1200	43
GW 62 027 FH	15	180	41
GW 62 027 H	15	270	43
GW 62 028 FH	15	180	41
GW 62 028 H	15	90	43
GW 62 029 FH	15	240	41
GW 62 029 H	15	240	43
GW 62 030 FH	15	270	41
GW 62 030 H	25	450	43
GW 62 031 FH	25	200	41
GW 62 031 H	25	200	43
GW 62 032 H	15	90	43
GW 62 033 H	25	100	43
GW 62 034 FH	15	180	41
GW 62 034 H	15	270	43
GW 62 035 FH	15	180	41
GW 62 035 H	15	180	43
GW 62 036 FH	15	180	41
GW 62 036 H	15	180	43
GW 62 037 FH	15	270	41
GW 62 037 H	15	270	43
GW 62 038 FH	15	180	41
GW 62 038 H	15	270	43
GW 62 039 FH	15	180	41
GW 62 039 H	15	270	43
GW 62 040 FH	15	180	41
GW 62 040 H	15	180	43
GW 62 041 FH	15	270	41
GW 62 041 H	15	270	43
GW 62 042 FH	15	270	41
GW 62 042 H	15	630	43
GW 62 043 H	15	90	43
GW 62 044 H	15	270	43
GW 62 056 H	1/2	48	45
GW 62 057 H	1/2	32	45
GW 62 058 H	1/2	48	45
GW 62 059 H	1/2	32	45
GW 62 060 H	1/2	128	45
GW 62 060 PH	1/2	48	45
GW 62 061 H	1/2	128	45
GW 62 061 PH	1/2	48	45
GW 62 062 H	1/2	48	45
GW 62 062 PH	1/2	32	45
GW 62 063 H	1/2	48	45
GW 62 063 PH	1/2	32	45
GW 62 064	10/40	480	60
GW 62 065	10/20	280	60
GW 62 066	10/20	560	60
GW 62 067	10/20	280	60
GW 62 068	10/20	280	60
GW 62 069	10/20	280	60
GW 62 070	10/20	280	60
GW 62 071	10/20	280	60
GW 62 072	10/20	280	60
GW 62 073	10/20	280	60
GW 62 074	10/20	280	60
GW 62 075	10/20	560	60
GW 62 076	10/20	280	60
GW 62 077	10/20	280	60
GW 62 078	10/20	280	60
GW 62 079	10/20	280	60
GW 62 080	10/20	280	60
GW 62 081	10/20	280	60
GW 62 128 H	25	200	43
GW 62 201 FH	15	360	46
GW 62 201 H	50	800	48
GW 62 202 FH	15	240	46
GW 62 202 H	15	240	48
GW 62 203 FH	15	240	46
GW 62 203 H	15	240	48
GW 62 204	10/100	2000	56
GW 62 205 FH	25	450	46
GW 62 205 H	50	1700	48
GW 62 206 FH	15	240	46
GW 62 206 H	25	450	48
GW 62 207 FH	15	240	46
GW 62 207 H	15	240	48
GW 62 208 FH	15	240	46
GW 62 208 H	15	240	48
GW 62 209 FH	15	360	46
GW 62 209 H	50	800	48
GW 62 210 FH	15	360	46
GW 62 210 H	50	1600	48
GW 62 211 H	15	240	48
GW 62 212 H	15	240	48
GW 62 213 FH	15	120	46
GW 62 213 H	15	360	48
GW 62 214 FH	15	120	46
GW 62 214 H	15	240	48
GW 62 215 FH	15	120	46
GW 62 215 H	15	120	48
GW 62 216 FH	15	240	46
GW 62 216 H	25	450	48
GW 62 217 FH	15	120	46
GW 62 217 H	15	360	48
GW 62 218 FH	15	120	46
GW 62 218 H	15	120	48
GW 62 219 FH	15	120	46
GW 62 219 H	15	240	48
GW 62 220 FH	15	360	46
GW 62 220 H	15	360	48
GW 62 221 FH	15	240	46
GW 62 221 H	25	1050	48
GW 62 222 H	15	240	48
GW 62 223 H	15	120	48
GW 62 224 FH	15	240	47
GW 62 224 H	25	450	49
GW 62 225 FH	15	240	47

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 62 225 H	15	360	49
GW 62 226 FH	15	240	47
GW 62 226 H	15	240	49
GW 62 227 FH	25	450	47
GW 62 227 H	50	1700	49
GW 62 228 FH	15	240	47
GW 62 228 H	15	360	49
GW 62 229 FH	15	240	47
GW 62 229 H	15	240	49
GW 62 230 FH	15	240	47
GW 62 230 H	15	240	49
GW 62 231 FH	15	360	47
GW 62 231 H	25	450	49
GW 62 232 FH	15	360	47
GW 62 232 H	25	450	49
GW 62 233 H	15	240	49
GW 62 234 H	15	240	49
GW 62 235 FH	15	180	47
GW 62 235 H	25	200	49
GW 62 236 FH	15	180	47
GW 62 236 H	15	270	49
GW 62 237 FH	15	180	47
GW 62 237 H	15	180	49
GW 62 238 FH	15	90	47
GW 62 238 H	15	270	49
GW 62 239 FH	15	180	47
GW 62 239 H	15	270	49
GW 62 240 FH	15	180	47
GW 62 240 H	15	180	49
GW 62 241 FH	15	180	47
GW 62 241 H	15	180	49
GW 62 242 FH	15	270	47
GW 62 242 H	15	270	49
GW 62 243 FH	15	270	47
GW 62 243 H	15	270	49
GW 62 244 H	15	180	49
GW 62 245 H	15	180	49
GW 62 257 H	1/2	24	51
GW 62 257 PH	1/2	192	51
GW 62 258 H	1/2	72	51
GW 62 259 H	1/2	72	51
GW 62 260 H	1/2	72	51
GW 62 261 H	1/2	72	51
GW 62 261 PH	1/2	72	51
GW 62 262 H	1/2	72	51
GW 62 262 PH	1/2	48	51
GW 62 263 H	1/2	48	51
GW 62 263 PH	1/2	192	51
GW 62 264 H	1/2	72	51
GW 62 264 PH	1/2	72	51
GW 62 265	10/40	480	61
GW 62 266	10/20	280	61
GW 62 267	10/20	280	61
GW 62 268	10/20	280	61
GW 62 269	10/20	280	61
GW 62 270	10/20	280	61
GW 62 271	10/20	280	61
GW 62 272	10/20	280	61
GW 62 273	10/20	280	61
GW 62 274	10/20	280	61
GW 62 275	10/20	280	61
GW 62 276	10/20	280	61
GW 62 277	10/20	280	61
GW 62 278	10/20	280	61
GW 62 279	10/20	280	61
GW 62 280	10/20	280	61
GW 62 281	10/20	280	61
GW 62 282	10/20	560	61
GW 62 283 H	25	400	49
GW 62 365	10/40	800	61
GW 62 366	10/20	560	61
GW 62 392	1/12	840	56
GW 62 392	1/12	840	115
GW 62 393	1/20	2200	56
GW 62 393	1/20	2200	115
GW 62 394	1/20	2200	56
GW 62 394	1/20	2200	115
GW 62 401	40	240	52
GW 62 402	20	120	52
GW 62 403	20	120	52
GW 62 404	40	720	52
GW 62 405	20	240	52
GW 62 406	20	120	52
GW 62 407	20	120	52
GW 62 408	40	720	52
GW 62 409	40	720	52
GW 62 410	20	120	52
GW 62 411	20	120	52
GW 62 412	16	96	52
GW 62 413	16	96	52
GW 62 414	16	192	52
GW 62 415	16	576	52
GW 62 416	16	192	52
GW 62 417	16	96	52
GW 62 418	16	96	52
GW 62 419	16	192	52
GW 62 420	16	192	52
GW 62 421	14	84	52
GW 62 422	14	84	52
GW 62 423	20	240	53
GW 62 424	20	120	53
GW 62 425	20	120	53
GW 62 426	40	720	53
GW 62 427	20	120	53
GW 62 428	20	120	53
GW 62 429	20	120	53
GW 62 430	40	720	53
GW 62 431	40	720	53
GW 62 432	20	80	53
GW 62 433	20	120	53
GW 62 434	16	96	53
GW 62 435	16	96	53
GW 62 436	16	96	53
GW 62 437	16	192	53
GW 62 438	16	96	53
GW 62 439	16	96	53
GW 62 440	16	192	53
GW 62 441	16	192	53
GW 62 442	16	576	53
GW 62 443	14	84	53
GW 62 444	14	84	53
GW 62 456	10/40	240	62
GW 62 457	10/20	240	62
GW 62 458	10/20	240	62
GW 62 459	10/20	240	62
GW 62 460	10/20	240	62
GW 62 461	10/20	240	62
GW 62 462	10/20	240	62
GW 62 463	10/20	240	62
GW 62 464	10/20	240	62
GW 62 465	10/20	240	62
GW 62 466	10/20	240	62
GW 62 467	10/20	240	62
GW 62 468	10/20	240	62
GW 62 469	10/20	240	62
GW 62 470	10/20	240	62
GW 62 471	10/20	240	62
GW 62 472	10/20	240	62
GW 62 473	10/20	240	62
GW 62 474	20	760	54
GW 62 475	20	400	54
GW 62 476	20	160	54
GW 62 477	20	760	54
GW 62 478	20	280	54
GW 62 479	20	160	54
GW 62 480	20	280	54
GW 62 481	20	760	54
GW 62 482	20	560	54
GW 62 483	20	160	54
GW 62 484	20	160	54
GW 62 485	16	96	54
GW 62 486	16	96	54
GW 62 487	16	288	54
GW 62 488	16	288	54
GW 62 489	16	288	54
GW 62 490	16	96	54
GW 62 491	16	288	54
GW 62 492	16	288	54
GW 62 493	16	288	54
GW 62 494	16	96	54
GW 62 495	16	96	54
GW 62 496	20	240	55
GW 62 497	20	160	55
GW 62 498	20	160	55
GW 62 499	20	760	55
GW 62 501	20	240	55
GW 62 502	20	160	55
GW 62 503	20	240	55
GW 62 504	20	760	55
GW 62 505	20	560	55
GW 62 506	20	160	55
GW 62 507	20	160	55
GW 62 508	16	128	55
GW 62 509	16	128	55

Code	Quantity		Page
	Pack/carton	Pallet	
GW 62 510	16	128	55
GW 62 511	16	288	55
GW 62 512	16	96	55
GW 62 513	16	96	55
GW 62 514	16	128	55
GW 62 515	16	96	55
GW 62 516	16	288	55
GW 62 517	16	96	55
GW 62 518	16	96	55
GW 62 530	1/2	32	56
GW 62 531	1/2	48	56
GW 62 532	1/2	48	56
GW 62 533	1/2	32	56
GW 62 534	1/2	128	56
GW 62 535	1/2	128	56
GW 62 536	1/2	48	56
GW 62 537	1/2	48	56
GW 62 538	10/20	280	62
GW 62 539	10/20	240	62
GW 62 540	10/20	240	62
GW 62 541	10/20	240	62
GW 62 542	10/20	240	62
GW 62 543	10/20	240	62
GW 62 544	10/20	240	62
GW 62 545	10/20	240	62
GW 62 546	10/20	240	62
GW 62 547	10/20	240	62
GW 62 548	10/20	240	62
GW 62 549	10/20	240	62
GW 62 550	10/20	240	62
GW 62 551	10/20	240	62
GW 62 552	10/20	240	62
GW 62 553	10/20	240	62
GW 62 554	10/20	240	62
GW 62 555	10/20	240	62
GW 62 556	16	192	53
GW 62 557	16	128	55
GW 62 664 H	1/2	48	45
GW 62 665 H	1/2	48	45
GW 62 666 H	1/2	48	45
GW 62 667 H	1/2	48	45
GW 62 668 H	1/2	48	45
GW 62 669 H	1/2	48	45
GW 62 670 H	1/2	48	45
GW 62 671 H	1/2	48	45
GW 62 672 H	1/2	32	45
GW 62 673 H	1/2	48	45
GW 62 674 H	1/2	48	45
GW 62 675 H	1/2	32	45
GW 62 676 H	1/2	48	45
GW 62 677 H	1/2	32	45
GW 62 701 H	15	240	42
GW 62 702 H	15	240	42
GW 62 703 H	15	240	42
GW 62 704 H	15	240	42
GW 62 705 H	15	240	42
GW 62 706 H	15	240	42
GW 62 707 H	15	240	42
GW 62 708 H	15	240	42
GW 62 709 H	15	240	42
GW 62 710 H	15	240	42
GW 62 711 H	15	240	42
GW 62 712 H	15	240	42
GW 62 713 H	15	240	42
GW 62 714 H	15	240	42
GW 62 715 H	15	240	42
GW 62 716 H	15	240	42
GW 62 717 H	15	240	42
GW 62 718 H	15	240	42
GW 62 719 H	15	240	42
GW 62 720 H	15	180	42
GW 62 721 H	15	240	42
GW 62 722 H	15	240	42
GW 62 723 H	15	180	42
GW 62 724 H	15	240	42
GW 62 725 H	15	240	42
GW 62 726 H	15	180	42
GW 62 727 H	15	240	42
GW 62 728 H	15	180	42
GW 62 729 H	15	240	42
GW 62 730 H	15	180	42
GW 62 731 H	15	240	42
GW 62 732 H	15	240	42
GW 62 733 H	15	240	42
GW 62 734 H	15	240	42
GW 62 735 H	15	240	43
GW 62 736 H	15	180	43
GW 62 737 H	15	180	43
GW 62 738 H	15	240	43
GW 62 739 H	15	180	43
GW 62 740 H	15	180	43
GW 62 741 H	15	240	43
GW 62 742 H	15	180	43
GW 62 743 H	15	180	43
GW 62 744 H	15	180	43
GW 62 745 H	15	270	43
GW 62 746 H	15	180	43
GW 62 747 H	15	180	43
GW 62 748 H	15	240	43
GW 62 749 H	15	180	43
GW 62 750 H	15	240	43
GW 62 751 H	15	240	43
GW 62 752 H	15	180	43
GW 62 753 H	15	180	43
GW 62 754 H	15	180	43
GW 62 755 H	15	180	43
GW 62 756 H	15	180	43
GW 62 757 H	15	180	43
GW 62 758 H	15	180	43
GW 62 759 H	15	180	43
GW 62 760 H	15	180	43
GW 62 761 H	15	180	43
GW 62 762 H	15	180	43
GW 62 763 H	15	180	43
GW 62 764 H	15	180	43
GW 62 765 H	15	180	43
GW 62 766 H	15	180	43
GW 62 767 H	15	180	43
GW 62 801 H	15	240	48
GW 62 802 H	15	240	48
GW 62 803 H	15	240	48
GW 62 804 H	15	240	48
GW 62 805 H	15	240	48
GW 62 806 H	15	240	48
GW 62 807 H	15	240	48
GW 62 808 H	15	240	48
GW 62 809 H	15	240	48
GW 62 810 H	15	240	48
GW 62 811 H	15	240	48
GW 62 812 H	15	240	48
GW 62 813 H	15	240	48
GW 62 814 H	15	240	48
GW 62 815 H	15	240	48
GW 62 816 H	15	240	48
GW 62 817 H	15	240	48
GW 62 818 H	15	240	48
GW 62 819 H	15	240	48
GW 62 820 H	15	120	48
GW 62 821 H	15	240	48
GW 62 822 H	15	240	48
GW 62 823 H	15	120	48
GW 62 824 H	15	240	48
GW 62 825 H	15	240	48
GW 62 826 H	15	120	48
GW 62 827 H	15	240	48
GW 62 828 H	15	120	48
GW 62 829 H	15	240	48
GW 62 830 H	15	120	48
GW 62 831 H	15	240	48
GW 62 832 H	15	240	48
GW 62 833 H	15	240	48
GW 62 834 H	15	240	48
GW 62 835 H	15	240	49
GW 62 836 H	15	240	49
GW 62 837 H	15	240	49
GW 62 838 H	15	240	49
GW 62 839 H	15	240	49
GW 62 840 H	15	240	49
GW 62 841 H	15	240	49
GW 62 842 H	15	240	49
GW 62 843 H	15	240	49
GW 62 844 H	15	240	49
GW 62 845 H	15	240	49
GW 62 846 H	15	240	49
GW 62 847 H	15	240	49
GW 62 848 H	15	240	49
GW 62 849 H	15	240	49
GW 62 850 H	15	240	49
GW 62 851 H	15	240	49
GW 62 852 H	15	180	49
GW 62 853 H	15	180	49
GW 62 854 H	15	180	49
GW 62 855 H	15	180	49
GW 62 856 H	15	180	49

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 62 857 H	15	180	49
GW 62 858 H	15	180	49
GW 62 859 H	15	180	49
GW 62 860 H	15	180	49
GW 62 861 H	15	180	49
GW 62 862 H	15	180	49
GW 62 863 H	15	270	49
GW 62 864 H	15	180	49
GW 62 865 H	15	180	49
GW 62 866 H	15	240	49
GW 62 867 H	15	240	49
GW 62 965 H	1/2	72	51
GW 62 966 H	1/2	72	51
GW 62 967 H	1/2	72	51
GW 62 968 H	1/2	72	51
GW 62 969 H	1/2	72	51
GW 62 970 H	1/2	72	51
GW 62 971 H	1/2	72	51
GW 62 972 H	1/2	72	51
GW 62 973 H	1/2	72	51
GW 62 974 H	1/2	72	51
GW 62 975 H	1/2	72	51
GW 62 976 H	1/2	72	51
GW 62 977 H	1/2	72	51
GW 62 978 H	1/2	72	51

GW 63

Code	Quantity		Page
	Pack/carton	Pallet	
GW 63 013 H	1/4	56	44
GW 63 014 H	1/4	56	44
GW 63 015 H	1/4	56	44
GW 63 016 H	1/4	112	44
GW 63 017 H	1/4	56	44
GW 63 018 H	1/4	56	44
GW 63 019 H	1/4	56	44
GW 63 020 H	1/4	56	44
GW 63 021 H	1/4	112	44
GW 63 045 H	1/4	112	45
GW 63 046 H	1/4	56	45
GW 63 047 H	1/4	56	45
GW 63 048 H	1/4	112	45
GW 63 048 PH	1/4	112	45
GW 63 049 H	1/4	112	45
GW 63 050 H	1/4	56	45
GW 63 051 H	1/4	56	45
GW 63 052 H	1/4	280	45
GW 63 052 PH	1/4	112	45
GW 63 053 H	1/4	280	45
GW 63 053 PH	1/4	112	45
GW 63 054 H	1/4	112	45
GW 63 054 PH	1/4	56	45
GW 63 055 H	1/4	56	45
GW 63 056 H	1/4	56	45
GW 63 057 H	1/4	56	45
GW 63 058 H	1/4	56	45
GW 63 058 PH	1/4	96	45
GW 63 059 H	1/4	56	45
GW 63 060 H	1/4	56	45
GW 63 061 H	1/4	56	45
GW 63 062 H	1/4	56	45
GW 63 063 H	1/4	56	45
GW 63 064 H	1/4	56	45
GW 63 065 H	1/4	56	45
GW 63 066 H	1/4	112	45
GW 63 067 H	1/4	56	45
GW 63 068 H	1/4	56	45
GW 63 213 H	1/4	100	50
GW 63 214 H	1/4	100	50
GW 63 215 H	1/4	100	50
GW 63 216 H	1/4	100	50
GW 63 217 H	1/4	100	50
GW 63 218 H	1/4	100	50
GW 63 219 H	1/4	100	50
GW 63 220 H	1/4	100	50
GW 63 221 H	1/4	300	50
GW 63 246 H	1/4	100	51
GW 63 247 H	1/4	100	51
GW 63 248 H	1/4	100	51
GW 63 249 H	1/4	300	51
GW 63 249 PH	1/4	100	51
GW 63 250 H	1/4	100	51
GW 63 251 H	1/4	100	51
GW 63 252 H	1/4	100	51
GW 63 253 H	1/4	300	51
GW 63 253 PH	1/4	300	51
GW 63 254 H	1/4	300	51
GW 63 254 PH	1/4	300	51
GW 63 255 H	1/4	100	51
GW 63 255 PH	1/4	100	51
GW 63 256 H	1/4	100	51
GW 63 257 H	1/4	100	51
GW 63 258 H	1/4	100	51
GW 63 259 H	1/4	100	51
GW 63 260 H	1/4	100	51
GW 63 261 H	1/4	100	51
GW 63 262 H	1/4	100	51
GW 63 263 H	1/4	100	51
GW 63 264 H	1/4	100	51
GW 63 265 H	1/4	100	51
GW 63 266 H	1/4	100	51
GW 63 267 H	1/4	100	51
GW 63 268 H	1/4	100	51
GW 63 269 H	1/4	100	51
GW 63 445	2/4	64	53
GW 63 446	2/4	64	53
GW 63 447	2/4	64	53
GW 63 448	2/4	96	53
GW 63 449	2/4	64	53
GW 63 450	2/4	96	53
GW 63 451	2/4	64	53
GW 63 452	2/4	96	53
GW 63 453	2/4	256	53
GW 63 454	2/4	64	53
GW 63 455	2/4	64	53
GW 63 519	2/4	48	56
GW 63 520	2/4	96	56
GW 63 521	2/4	48	56
GW 63 522	2/4	96	56
GW 63 523	2/4	96	56
GW 63 524	2/4	96	56
GW 63 525	2/4	48	56
GW 63 526	2/4	216	56
GW 63 527	2/4	216	56
GW 63 528	2/4	96	56
GW 63 529	2/4	48	56

GW 64

Code	Quantity		Page
	Pack/carton	Pallet	
GW 64 008	5/20	240	66
GW 64 010	5/20	600	66
GW 64 011	5/10	120	66
GW 64 012	5/10	80	66
GW 64 013	5/10	280	66
GW 64 014	5/10	180	66
GW 64 022	5/10	180	66
GW 64 023	5/10	100	66
GW 64 024	5/10	180	66
GW 64 025	5/10	90	66
GW 64 026	5/10	80	66
GW 64 027	5/10	180	66
GW 64 028	5/10	240	66
GW 64 050	1/6	60	66
GW 64 052	1/6	144	66
GW 64 055	1/3	27	66
GW 64 056	1/3	84	66
GW 64 059	5/10	100	67
GW 64 060	5/10	100	67
GW 64 061	1/5	50	67
GW 64 062	5/10	240	67
GW 64 063	5/10	80	67
GW 64 064	1/5	60	67
GW 64 065	1/2	32	67
GW 64 066	10/20	480	68
GW 64 067	10/20	240	68
GW 64 068	1/4	200	66
GW 64 203	10/40	960	68
GW 64 204	10/40	960	68
GW 64 206	10/40	2880	68
GW 64 207	10/40	480	68
GW 64 208	10/40	1920	69
GW 64 209	10/40	720	69
GW 64 210	10/40	960	68
GW 64 211	10/40	2880	68
GW 64 212	10/40	2880	68
GW 64 216	10/40	480	68
GW 64 217	10/40	480	68
GW 64 221	5/20	320	69
GW 64 222	5/20	320	69
GW 64 223	5/20	320	69
GW 64 231	5/20	240	69
GW 64 232	5/20	240	70
GW 64 236	5/10	60	69
GW 64 237	5/10	60	70
GW 64 256	1/3	33	70
GW 64 263	1/6	60	70
GW 64 265	5/20	240	70

GW 66

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 001	1/12	192	96
GW 66 002	1/12	192	96
GW 66 003	1/12	192	96
GW 66 004	1/12	600	96
GW 66 005	1/12	192	96
GW 66 006	1/12	192	96
GW 66 007	1/12	192	96
GW 66 008	1/12	384	96
GW 66 009	1/12	384	96
GW 66 010	1/12	192	96
GW 66 011	1/12	192	96
GW 66 012	1/12	192	96
GW 66 013	1/12	192	96
GW 66 014	1/12	192	96
GW 66 015	1/12	384	96
GW 66 016	1/12	192	96
GW 66 017	1/12	192	96
GW 66 018	1/12	192	96
GW 66 019	1/12	384	96
GW 66 020	1/12	384	96
GW 66 021	1/12	192	96
GW 66 022	1/12	192	96
GW 66 023	1/12	96	97
GW 66 024	1/12	96	97
GW 66 025	1/12	96	97
GW 66 026	1/12	240	97
GW 66 027	1/12	96	97
GW 66 028	1/12	96	97
GW 66 029	1/12	96	97
GW 66 030	1/12	240	97
GW 66 031	1/12	240	97
GW 66 032	1/12	96	97
GW 66 033	1/12	96	97
GW 66 034	1/12	96	97
GW 66 035	1/12	96	97
GW 66 036	1/12	96	97
GW 66 037	1/12	96	97
GW 66 038	1/12	96	97
GW 66 039	1/12	96	97
GW 66 040	1/12	96	97
GW 66 041	1/12	96	97
GW 66 042	1/12	240	97
GW 66 043	1/12	96	97
GW 66 044	1/12	96	97
GW 66 051 N	1/12	96	79
GW 66 052 N	1/12	96	79
GW 66 053 N	1/12	96	79
GW 66 054 N	1/12	96	79
GW 66 055 N	1/12	96	79
GW 66 056 N	1/12	96	79
GW 66 057 N	1/12	96	79
GW 66 058 N	1/12	96	79
GW 66 059 N	1/12	96	79
GW 66 062 N	1/12	96	79
GW 66 063 N	1/12	96	79
GW 66 064 N	1/12	96	79
GW 66 065 N	1/12	96	79
GW 66 066 N	1/12	96	79
GW 66 067 N	1/12	96	79
GW 66 068 N	1/12	96	79
GW 66 069 N	1/12	96	79
GW 66 070 N	1/12	96	79
GW 66 101	1/12	192	96
GW 66 102	1/12	192	96
GW 66 103	1/12	192	96
GW 66 104	1/12	384	96
GW 66 105	1/12	192	96
GW 66 106	1/12	192	96
GW 66 107	1/12	192	96
GW 66 108	1/12	384	96
GW 66 109	1/12	384	96
GW 66 110	1/12	192	96
GW 66 111	1/12	192	96
GW 66 112	1/12	192	96
GW 66 113	1/12	192	96
GW 66 114	1/12	192	96
GW 66 115	1/12	192	96
GW 66 116	1/12	192	96
GW 66 117	1/12	192	96
GW 66 118	1/12	192	96
GW 66 119	1/12	384	96
GW 66 120	1/12	384	96
GW 66 121	1/12	192	96
GW 66 122	1/12	192	96
GW 66 123	1/12	96	97
GW 66 124	1/12	96	97
GW 66 125	1/12	96	97
GW 66 126	1/12	240	97
GW 66 127	1/12	96	97
GW 66 128	1/12	96	97
GW 66 129	1/12	96	97
GW 66 130	1/12	240	97
GW 66 131	1/12	240	97
GW 66 132	1/12	96	97
GW 66 133	1/12	96	97
GW 66 134	1/12	96	97
GW 66 135	1/12	96	97
GW 66 136	1/12	96	97
GW 66 137	1/12	240	97
GW 66 138	1/12	96	97
GW 66 139	1/12	96	97
GW 66 140	1/12	96	97
GW 66 141	1/12	240	97
GW 66 142	1/12	240	97
GW 66 143	1/12	96	97
GW 66 144	1/12	96	97
GW 66 151 N	1/12	96	78
GW 66 152 N	1/12	96	78
GW 66 153 N	1/12	96	78
GW 66 154 N	1/12	192	78
GW 66 155 N	1/12	96	78
GW 66 156 N	1/12	96	78
GW 66 157 N	1/12	96	78
GW 66 158 N	1/12	192	78
GW 66 159 N	1/12	192	78
GW 66 162 N	1/12	96	78
GW 66 163 N	1/12	96	78
GW 66 164 N	1/12	96	78
GW 66 165 N	1/12	96	78
GW 66 166 N	1/12	96	78
GW 66 167 N	1/12	96	78
GW 66 168 N	1/12	96	78
GW 66 169 N	1/12	96	78
GW 66 170 N	1/12	96	78
GW 66 201 N	1/12	96	81
GW 66 202 N	1/12	96	81
GW 66 203 N	1/12	96	81
GW 66 204 N	1/12	192	81
GW 66 205 N	1/12	96	81
GW 66 206 N	1/12	96	81
GW 66 207 N	1/12	96	81
GW 66 208 N	1/12	192	81
GW 66 209 N	1/12	192	81
GW 66 210 N	1/12	96	81
GW 66 211 N	1/12	96	81
GW 66 212 N	1/12	96	81
GW 66 213 N	1/12	96	81
GW 66 214 N	1/12	96	81
GW 66 215 N	1/12	192	81
GW 66 216 N	1/12	96	81
GW 66 217 N	1/12	96	81
GW 66 218 N	1/12	96	81
GW 66 219 N	1/12	192	81
GW 66 220 N	1/12	192	81
GW 66 221 N	1/12	96	81
GW 66 222 N	1/12	96	81
GW 66 223 N	1/12	96	83
GW 66 224 N	1/12	96	83
GW 66 225 N	1/12	96	83
GW 66 226 N	1/12	192	83
GW 66 227 N	1/12	96	83
GW 66 228 N	1/12	96	83
GW 66 229 N	1/12	96	83
GW 66 230 N	1/12	192	83
GW 66 231 N	1/12	192	83
GW 66 232 N	1/12	96	83
GW 66 233 N	1/12	96	83
GW 66 234 N	1/12	96	83
GW 66 235 N	1/12	96	83
GW 66 236 N	1/12	96	83
GW 66 237 N	1/12	96	83
GW 66 238 N	1/12	96	83
GW 66 239 N	1/12	96	83
GW 66 240 N	1/12	96	83
GW 66 241 N	1/12	192	83
GW 66 242 N	1/12	192	83
GW 66 243 N	1/12	96	83
GW 66 244 N	1/12	96	83
GW 66 257 N	1/12	192	81
GW 66 258 N	1/12	96	83
GW 66 259 N	1/4	128	81
GW 66 301 N	1/12	96	80
GW 66 302 N	1/12	96	80

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 303 N	1/12	96	80
GW 66 304 N	1/12	432	80
GW 66 305 N	1/12	96	80
GW 66 306 N	1/12	96	80
GW 66 307 N	1/12	96	80
GW 66 308 N	1/12	288	80
GW 66 309 N	1/12	288	80
GW 66 310 N	1/12	96	80
GW 66 311 N	1/12	96	80
GW 66 312 N	1/12	96	80
GW 66 313 N	1/12	96	80
GW 66 314 N	1/12	96	80
GW 66 315 N	1/12	288	80
GW 66 316 N	1/12	96	80
GW 66 317 N	1/12	96	80
GW 66 318 N	1/12	96	80
GW 66 319 N	1/12	288	80
GW 66 320 N	1/12	288	80
GW 66 321 N	1/12	96	80
GW 66 322 N	1/12	96	80
GW 66 323 N	1/12	96	82
GW 66 324 N	1/12	96	82
GW 66 325 N	1/12	96	82
GW 66 326 N	1/12	432	82
GW 66 327 N	1/12	96	82
GW 66 328 N	1/12	96	82
GW 66 329 N	1/12	96	82
GW 66 330 N	1/12	288	82
GW 66 331 N	1/12	288	82
GW 66 332 N	1/12	96	82
GW 66 333 N	1/12	96	82
GW 66 334 N	1/12	96	82
GW 66 335 N	1/12	96	82
GW 66 336 N	1/12	96	82
GW 66 337 N	1/12	288	82
GW 66 338 N	1/12	96	82
GW 66 339 N	1/12	96	82
GW 66 340 N	1/12	96	82
GW 66 341 N	1/12	288	82
GW 66 342 N	1/12	192	82
GW 66 343 N	1/12	96	82
GW 66 344 N	1/12	96	82
GW 66 345 N	1/4	64	82
GW 66 346 N	1/4	64	82
GW 66 347 N	1/4	64	82
GW 66 348 N	1/4	64	82
GW 66 349 N	1/4	64	82
GW 66 350 N	1/4	64	82
GW 66 351 N	1/4	64	82
GW 66 352 N	1/4	128	82
GW 66 353 N	1/4	128	82
GW 66 354 N	1/4	64	82
GW 66 355 N	1/4	64	82
GW 66 357 N	1/12	96	80
GW 66 358 N	1/12	96	82
GW 66 359 N	1/4	128	80
GW 66 388	1	6	136
GW 66 389	1	6	136

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 391	1/2	36	122
GW 66 392	1/2	24	122
GW 66 393	1/2	24	122
GW 66 394	1	18	122
GW 66 395	1	18	122
GW 66 396	1	18	122
GW 66 397	1	18	122
GW 66 401	1/12	192	102
GW 66 402	1/12	192	102
GW 66 403	1/12	192	102
GW 66 404	1/12	384	102
GW 66 405	1/12	192	102
GW 66 406	1/12	192	102
GW 66 407	1/12	192	102
GW 66 408	1/12	384	102
GW 66 409	1/12	192	102
GW 66 412	1/12	192	102
GW 66 413	1/12	192	102
GW 66 414	1/12	192	102
GW 66 415	1/12	192	102
GW 66 416	1/12	192	102
GW 66 417	1/12	192	102
GW 66 418	1/12	192	102
GW 66 419	1/12	192	102
GW 66 420	1/12	192	102
GW 66 423	1/12	192	102
GW 66 424	1/12	192	102
GW 66 425	1/12	192	102
GW 66 426	1/12	384	102
GW 66 427	1/12	192	102
GW 66 428	1/12	192	102
GW 66 429	1/12	192	102
GW 66 430	1/12	384	102
GW 66 431	1/12	192	102
GW 66 434	1/12	192	102
GW 66 435	1/12	192	102
GW 66 436	1/12	192	102
GW 66 437	1/12	384	102
GW 66 438	1/12	192	102
GW 66 439	1/12	192	102
GW 66 440	1/12	192	102
GW 66 441	1/12	192	102
GW 66 442	1/12	192	102
GW 66 445	1/12	192	103
GW 66 446	1/12	192	103
GW 66 447	1/12	192	103
GW 66 448	1/12	384	103
GW 66 449	1/12	96	103
GW 66 450	1/12	192	103
GW 66 451	1/12	192	103
GW 66 452	1/12	192	103
GW 66 453	1/12	192	103
GW 66 456	1/12	120	103
GW 66 457	1/12	120	103
GW 66 458	1/12	96	103
GW 66 459	1/12	96	103
GW 66 460	1/12	96	103
GW 66 461	1/12	96	103

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 462	1/12	96	103
GW 66 463	1/12	96	103
GW 66 464	1/12	96	103
GW 66 467	1/12	192	103
GW 66 468	1/12	384	103
GW 66 469	1/12	192	103
GW 66 470	1/12	384	103
GW 66 471	1/12	192	103
GW 66 472	1/12	192	103
GW 66 473	1/12	192	103
GW 66 474	1/12	384	103
GW 66 475	1/12	192	103
GW 66 478	1/12	96	103
GW 66 479	1/12	96	103
GW 66 480	1/12	96	103
GW 66 481	1/12	96	103
GW 66 482	1/12	96	103
GW 66 483	1/12	96	103
GW 66 484	1/12	96	103
GW 66 485	1/12	96	103
GW 66 486	1/12	96	103
GW 66 491	1/12	360	105
GW 66 491	1/12	360	118
GW 66 492	1/6	168	105
GW 66 492	1/6	168	118
GW 66 493	1/4	120	105
GW 66 493	1/4	120	118
GW 66 496	1/12	864	104
GW 66 498	1/12	432	104
GW 66 501	1/6	48	89
GW 66 502	1/6	24	89
GW 66 503	1/6	48	89
GW 66 504	1/6	48	89
GW 66 505	1/6	48	89
GW 66 506	1/6	48	89
GW 66 507	1/6	48	89
GW 66 508	1/6	48	89
GW 66 509	1/6	48	89
GW 66 510	1/6	48	89
GW 66 511	1/6	48	89
GW 66 512	1/6	48	89
GW 66 513	1/6	48	89
GW 66 514	1/6	48	89
GW 66 515	1/6	48	89
GW 66 516	1/6	48	89
GW 66 517	1/6	48	89
GW 66 518	1/6	48	89
GW 66 519	1/6	48	89
GW 66 520	1/6	48	89
GW 66 521	1/6	48	89
GW 66 522	1/6	48	89
GW 66 523	1/6	120	89
GW 66 524	1/3	18	89
GW 66 525	1/3	18	89
GW 66 526	1/3	135	89
GW 66 527	1/3	54	89
GW 66 528	1/3	18	89
GW 66 529	1/3	18	89

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 530	1/3	18	89
GW 66 531	1/3	54	89
GW 66 532	1/3	54	89
GW 66 533	1/3	18	89
GW 66 534	1/3	18	89
GW 66 535	1/6	48	88
GW 66 536	1/6	48	88
GW 66 537	1/6	48	88
GW 66 538	1/6	48	88
GW 66 539	1/6	48	88
GW 66 540	1/6	48	88
GW 66 541	1/6	48	88
GW 66 542	1/6	48	88
GW 66 543	1/6	48	88
GW 66 544	1/6	48	88
GW 66 545	1/6	48	88
GW 66 546	1/6	48	88
GW 66 547	1/6	48	88
GW 66 548	1/6	48	88
GW 66 549	1/6	48	88
GW 66 550	1/6	48	88
GW 66 551	1/6	48	88
GW 66 552	1/6	48	88
GW 66 553	1/6	48	88
GW 66 554	1/6	48	88
GW 66 555	1/6	48	88
GW 66 556	1/6	48	88
GW 66 557	1/6	48	88
GW 66 581	1	8	95
GW 66 582	1	8	95
GW 66 583	1	8	95
GW 66 584	1	8	95
GW 66 585	1	8	95
GW 66 586	1	12	95
GW 66 591	1	8	95
GW 66 592	1	8	95
GW 66 593	1	8	95
GW 66 594	1	8	95
GW 66 595	1	8	95
GW 66 596	1	8	95
GW 66 673	10/120	4800	118
GW 66 676	1/10	900	98
GW 66 677	1/10	540	100
GW 66 678 N	1/12	1080	84
GW 66 680 N	1/10	160	84
GW 66 681	1/10	420	98
GW 66 681 PM	1/10	360	98
GW 66 681 PM	1/10	360	273
GW 66 682	1/10	240	100
GW 66 682 PM	1/10	240	100
GW 66 682 PM	1/10	240	273
GW 66 683 N	1/10	360	85
GW 66 683 PM	1/10	250	86
GW 66 683 PM	1/10	250	273
GW 66 685	1/10	240	94
GW 66 686	1/10	160	84
GW 66 690	1/6	288	85
GW 66 691	1/6	144	85
GW 66 693	1/6	96	85
GW 66 694	1/6	96	85
GW 66 696	1/6	108	94
GW 66 697	1/2	40	94
GW 66 698	1/2	36	94
GW 66 700	1/6	72	94
GW 66 701	1/10	1280	98
GW 66 701	1/10	1280	116
GW 66 702	1/10	1100	100
GW 66 702	1/10	1100	116
GW 66 703 N	1/10	1100	86
GW 66 703 N	1/10	1100	116
GW 66 705 N	1/10	720	86
GW 66 705 N	1/10	720	116
GW 66 706	1/10	240	94
GW 66 707	1/10	240	95
GW 66 708	1/20	1400	117
GW 66 708	1/20	1400	165
GW 66 708	1/20	1400	294
GW 66 708	1/20	1400	311
GW 66 709 N	1/10	960	86
GW 66 709 N	1/10	960	117
GW 66 715 N	1/10	1000	87
GW 66 715 N	1/10	1000	117
GW 66 716 N	1/10	200	87
GW 66 716 N	1/10	200	117
GW 66 741 N	1/10	360	85
GW 66 742	1/10	120	85
GW 66 743 N	1/10	140	86
GW 66 745	1/20	1400	117
GW 66 745	1/20	1400	165
GW 66 745	1/20	1400	294
GW 66 745	1/20	1400	311
GW 66 781	1/6	108	94
GW 66 782	1/2	40	94
GW 66 783	1/2	36	94
GW 66 784	1/6	72	94
GW 66 801	1/6	48	92
GW 66 802	1/6	120	92
GW 66 803	1/6	120	92
GW 66 804	1/6	48	92
GW 66 805	1/6	48	92
GW 66 806	1/6	48	92
GW 66 807	1/6	48	92
GW 66 808	1/6	120	92
GW 66 809	1/6	120	92
GW 66 810	1/6	120	92
GW 66 811	1/6	120	92
GW 66 812	1/6	120	92
GW 66 813	1/6	120	92
GW 66 814	1/6	120	92
GW 66 815	1/6	48	92
GW 66 816	1/6	30	92
GW 66 817	1/6	48	92
GW 66 818	1/6	120	92
GW 66 819	1/6	60	92
GW 66 820	1/6	120	92
GW 66 821	1/6	120	92
GW 66 822	1/6	48	92
GW 66 823	1/6	120	92
GW 66 824	1/6	120	90
GW 66 825	1/6	120	90
GW 66 826	1/6	48	90
GW 66 827	1/6	120	90
GW 66 828	1/6	48	90
GW 66 829	1/6	120	90
GW 66 830	1/6	48	90
GW 66 831	1/6	48	90
GW 66 832	1/6	48	90
GW 66 833	1/6	120	90
GW 66 834	1/6	48	90
GW 66 835	1/6	48	90
GW 66 836	1/6	120	90
GW 66 837	1/6	120	90
GW 66 838	1/6	48	90
GW 66 839	1/6	48	90
GW 66 840	1/6	48	90
GW 66 841	1/6	96	90
GW 66 842	1/6	48	90
GW 66 843	1/6	48	90
GW 66 844	1/6	120	90
GW 66 845	1/6	120	90
GW 66 846	1/6	120	90
GW 66 847	1/3	24	93
GW 66 848	1/3	60	93
GW 66 849	1/3	18	93
GW 66 850	1/3	18	93
GW 66 851	1/3	48	93
GW 66 852	1/3	18	93
GW 66 853	1/3	18	93
GW 66 854	1/3	54	93
GW 66 855	1/3	54	93
GW 66 856	1/3	18	93
GW 66 857	1/3	24	93
GW 66 866	1/3	18	91
GW 66 867	1/3	18	91
GW 66 868	1/3	18	91
GW 66 869	1/3	18	91
GW 66 870	1/3	54	91
GW 66 871	1/3	18	91
GW 66 872	1/3	18	91
GW 66 873	1/3	18	91
GW 66 874	1/3	54	91
GW 66 875	1/3	18	91
GW 66 876	1/3	18	91
GW 66 886	1/4	48	92
GW 66 951	1/6	48	93
GW 66 952	1/6	48	93
GW 66 953	1/6	48	93
GW 66 954	1/6	48	93
GW 66 955	1/6	48	93
GW 66 956	1/6	48	93
GW 66 957	1/6	48	93
GW 66 958	1/6	48	93
GW 66 959	1/6	48	93
GW 66 960	1/6	48	93

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 66 961	1/6	48	93
GW 66 962	1/6	48	93
GW 66 963	1/6	48	93
GW 66 964	1/6	48	93
GW 66 965	1/6	48	93
GW 66 966	1/6	48	93
GW 66 967	1/6	48	93
GW 66 968	1/6	48	93
GW 66 969	1/6	48	93
GW 66 970	1/6	48	93
GW 66 971	1/6	240	93
GW 66 972	1/6	48	93
GW 66 973	1/6	72	93
GW 66 974	1/6	48	91
GW 66 975	1/6	48	91
GW 66 976	1/6	48	91
GW 66 977	1/6	48	91
GW 66 978	1/6	48	91
GW 66 979	1/6	48	91
GW 66 980	1/6	48	91
GW 66 981	1/6	48	91
GW 66 982	1/6	48	91
GW 66 983	1/6	48	91
GW 66 984	1/6	48	91
GW 66 985	1/6	48	91
GW 66 986	1/6	48	91
GW 66 987	1/6	48	91
GW 66 988	1/6	48	91
GW 66 989	1/6	48	91
GW 66 990	1/6	48	91
GW 66 991	1/6	48	91
GW 66 992	1/6	48	91
GW 66 993	1/6	48	91
GW 66 994	1/6	48	91
GW 66 995	1/6	48	91
GW 66 996	1/6	48	91
GW 66 998	1/4	48	93
GW 67			
GW 67 245 N	1/4	32	83
GW 67 246 N	1/4	32	83
GW 67 247 N	1/4	32	83
GW 67 248 N	1/4	32	83
GW 67 249 N	1/4	32	83
GW 67 250 N	1/4	32	83
GW 67 251 N	1/4	32	83
GW 67 252 N	1/4	64	83
GW 67 253 N	1/4	64	83
GW 67 254 N	1/4	32	83
GW 67 255 N	1/4	32	83
GW 67 256 N	1/4	64	81
GW 67 257 N	1/4	64	81
GW 67 258 N	1/4	64	81
GW 67 259 N	1/4	64	81
GW 67 260 N	1/4	64	81
GW 67 261 N	1/4	64	81
GW 67 262 N	1/4	64	81
GW 67 263 N	1/4	128	81
GW 67 264 N	1/4	128	81
GW 67 265 N	1/4	64	81
GW 67 266 N	1/4	64	81
GW 67 356 N	1/4	64	80
GW 67 357 N	1/4	64	80
GW 67 358 N	1/4	64	80
GW 67 359 N	1/4	64	80
GW 67 360 N	1/4	64	80
GW 67 361 N	1/4	64	80
GW 67 362 N	1/4	64	80
GW 67 363 N	1/4	64	80
GW 67 364 N	1/4	128	80
GW 67 365 N	1/4	64	80
GW 67 366 N	1/4	64	80
GW 68			
GW 68 001 N	8	320	112
GW 68 002 N	6	120	112
GW 68 003 N	6	168	112
GW 68 004 N	4	120	113
GW 68 005 N	4	120	113
GW 68 006 N	4	80	99
GW 68 006 N	4	80	113
GW 68 007 N	3	90	113
GW 68 008 N	3	90	113
GW 68 009 N	3	90	99
GW 68 009 N	3	90	113
GW 68 010 N	3	90	87
GW 68 010 N	3	90	113
GW 68 012 N	2	48	113
GW 68 013 N	2	48	113
GW 68 014 N	2	36	101
GW 68 014 N	2	36	113
GW 68 015 N	2	48	87
GW 68 015 N	2	48	114
GW 68 017 N	16	288	112
GW 68 018 N	12	288	112
GW 68 019 N	6	108	99
GW 68 019 N	6	108	112
GW 68 020 N	8	320	112
GW 68 021 N	2	36	113
GW 68 022 N	2	36	87
GW 68 022 N	2	36	114
GW 68 023 N	1/3	108	114
GW 68 024 N	1/3	72	114
GW 68 025 N	6	108	87
GW 68 025 N	6	108	112
GW 68 026 N	8	192	112
GW 68 027 N	6	108	112
GW 68 031 N	4	96	112
GW 68 202 N	1/3	30	120
GW 68 203 N	1	48	134
GW 68 204 N	1	48	134
GW 68 205 N	1/3	48	120
GW 68 206 N	1	28	121
GW 68 207 N	1	28	121
GW 68 208 N	1	18	121
GW 68 212 N	1/8	96	120
GW 68 216 N	1	48	134
GW 68 217 N	1	77	134
GW 68 223 N	1	28	134
GW 68 224 N	1/2	36	120
GW 68 225 N	1/6	48	120
GW 68 226 N	1/6	48	120
GW 68 227 N	1/8	96	120
GW 68 228 N	1/3	30	120
GW 68 229 N	1	28	121
GW 68 230 N	1	9	121
GW 68 231 N	1	9	121
GW 68 232 N	1/2	18	120
GW 68 233 N	1/2	12	120
GW 68 235 N	1/2	24	136
GW 68 236 N	1	28	136
GW 68 241 N	1	12	133
GW 68 242 N	1	28	134
GW 68 243 N	1	28	134
GW 68 244 N	1	12	134
GW 68 245 N	1	24	134
GW 68 246 N	1	24	134
GW 68 247 N	1	8	134
GW 68 248 N	1	8	135
GW 68 249 N	1	11	135
GW 68 250 N	1	12	135
GW 68 251 N	1	11	135
GW 68 281	1/10	720	117
GW 68 292	1/10	2760	116
GW 68 293	1/10	3120	116
GW 68 294	1/10	3120	116
GW 68 295	1/10	3120	104
GW 68 295	1/10	3120	105
GW 68 295	1/10	3120	119
GW 68 296	1/10	1320	116
GW 68 401 N	1	10	135
GW 68 411 N	1	6	135
GW 68 421 N	1	6	135
GW 68 424 N	1	6	136
GW 68 431	1	30	114
GW 68 432	1	15	115
GW 68 433	1	20	114
GW 68 436 N	1/10	960	116
GW 68 441	1/6	168	87
GW 68 441	1/6	168	99
GW 68 441	1/6	168	101
GW 68 441	1/6	168	104
GW 68 441	1/6	168	249
GW 68 463	1	10	139
GW 68 465	1	9	138
GW 68 466	1	9	138
GW 68 468	1	6	129
GW 68 469	1	6	129
GW 68 471	1	4	131
GW 68 471 F	1	4	133
GW 68 472	1	4	131
GW 68 472 F	1	4	133
GW 68 473	1	4	131
GW 68 473 F	1		133
GW 68 474	1	4	131
GW 68 481	1	6	131

Code	Quantity		Page
	Pack/carton	Pallet	
GW 68 481 F	1	6	133
GW 68 482	1	6	131
GW 68 482 F	1	6	133
GW 68 483	1	6	131
GW 68 483 F	1	6	133
GW 68 484	1	6	131
GW 68 484 F	1	6	133
GW 68 491	1	4	130
GW 68 491 F	1	4	132
GW 68 492	1	4	130
GW 68 493	1	4	130
GW 68 493 F	1	4	132
GW 68 494	1	4	130
GW 68 494 F	1	4	132
GW 68 495	1	4	130
GW 68 496	1	4	130
GW 68 497	1	4	130
GW 68 498 F	1	4	132
GW 68 503	1/8	80	139
GW 68 504	1/4	280	139
GW 68 505	1/10	1440	139
GW 68 511	1	6	129
GW 68 511 F	1	6	132
GW 68 512	1	6	129
GW 68 512 F	1	6	132
GW 68 513	1	6	129
GW 68 513 F	1		132
GW 68 514	1	6	129
GW 68 514 F	1	6	132
GW 68 521	1	6	128
GW 68 526	1	4	128
GW 68 531	1	6	128
GW 68 536	1	24	128
GW 68 537	1	24	128
GW 68 538	1	15	128
GW 68 539	1	15	128
GW 68 541	1	6	130
GW 68 542	1	6	129
GW 68 543	1	4	130
GW 68 544	1	4	130
GW 68 551	1	48	138
GW 68 552	1	48	138
GW 68 554	1	48	138
GW 68 556	1	48	138
GW 68 559	1	20	138
GW 68 561	1	6	129
GW 68 561 F	1	6	132
GW 68 562	1	6	129
GW 68 562 F	1	6	132
GW 68 563	1	4	129
GW 68 563 F	1	6	132
GW 68 564	1	6	129
GW 68 564 F	1	6	132
GW 68 565	1	6	129
GW 68 565 F	1		132
GW 68 566	1	6	129
GW 68 566 F	1	8	132
GW 68 567	1	9	129

Code	Quantity		Page
	Pack/carton	Pallet	
GW 68 567 F	1	4	132
GW 68 568	1	6	129
GW 68 568 F	1	6	132
GW 68 569	1	4	129
GW 68 569 F	1	4	132
GW 68 570	1	6	129
GW 68 570 F	1		132
GW 68 571	1	6	129
GW 68 571 F	1	6	132
GW 68 572	1	6	129
GW 68 572 F	1	6	132
GW 68 573	1	4	129
GW 68 573 F	1		132
GW 68 574	1	6	129
GW 68 574 F	1	4	132
GW 68 575	1	8	130
GW 68 575 F	1	4	132
GW 68 576	1	4	130
GW 68 576 F	1	4	132
GW 68 577	1	4	130
GW 68 577 F	1	4	132
GW 68 578	1	4	130
GW 68 578 F	1	4	132
GW 68 579	1	4	130
GW 68 579 F	1	4	132
GW 68 580	1	4	130
GW 68 580 F	1	4	132
GW 68 581	1	4	130
GW 68 582	1		130
GW 68 582 F	1	4	132
GW 68 583	1	4	130
GW 68 583 F	1	4	132
GW 68 584	1	6	131
GW 68 584 F	1	6	133
GW 68 585	1	6	131
GW 68 586	1	6	131
GW 68 586 F	1	6	133
GW 68 587	1	6	131
GW 68 587 F	1	6	133
GW 68 588	1		131
GW 68 588 F	1	4	133
GW 68 589	1		131
GW 68 589 F	1	6	133
GW 68 590	1		131
GW 68 590 F	1	6	133
GW 68 591	1/20	600	139
GW 68 592	1	6	131
GW 68 592 F	1	6	133
GW 68 593	1	6	131
GW 68 594	1	4	131
GW 68 594 F	1	6	133
GW 68 595	1	4	131
GW 68 595 F	1	4	133
GW 68 596	1		131
GW 68 596 F	1	2	133
GW 68 597	1	4	131
GW 68 597 F	1	4	133
GW 68 598	1	4	131

Code	Quantity		Page
	Pack/carton	Pallet	
GW 68 598 F	1	4	133
GW 68 599	1	4	131
GW 68 599 F	1	4	133
GW 68 600	1	4	131
GW 68 600 F	1	2	133
GW 68 701 A	1	10	1258
GW 68 701 W	1	10	1258
GW 68 711 A	1	10	1258
GW 68 711 W	1	10	1258
GW 68 712 A	1	10	1258
GW 68 712 W	1	10	1258
GW 68 713 A	1	6	1258
GW 68 713 G	1	6	1258
GW 68 713 W	1	6	1258
GW 68 714 A	1	8	1259
GW 68 714 W	1	6	1259
GW 68 715 A	1	3	1263
GW 68 715 W	1	3	1263
GW 68 716 A	1	6	1259
GW 68 716 W	1	6	1259
GW 68 717 A	1	2	1264
GW 68 717 W	1	2	1264
GW 68 731 W	1/2	112	1265
GW 68 732 W	1/2	112	1265
GW 68 733 W	1/2	110	1265
GW 68 734 W	1/2	80	1265
GW 68 735 W	1/2	110	1265
GW 68 736 W	1/2	24	1265
GW 68 737 A	1/2	48	1265
GW 68 737 W	1/2	48	1265
GW 68 741 A	1/2	48	1266
GW 68 741 W	1/2	48	1266
GW 68 745 A	1/2	100	1260
GW 68 745 G	1/2	80	1260
GW 68 745 W	1/2	100	1247
GW 68 745 W	1/2	100	1260
GW 68 746 A	1/2	100	1260
GW 68 746 W	1/2	100	1247
GW 68 746 W	1/2	100	1260
GW 68 747 A	1/2	100	1260
GW 68 747 W	1/2	48	1247
GW 68 747 W	1/2	48	1260
GW 68 748 A	1/2	100	1260
GW 68 748 G	1/2	80	1260
GW 68 748 W	1/2	100	1247
GW 68 748 W	1/2	100	1260
GW 68 749 A	1/2	100	1260
GW 68 749 W	1/2	100	1247
GW 68 749 W	1/2	100	1260
GW 68 750 A	1/2	100	1260
GW 68 750 G	1/2	80	1260
GW 68 750 W	1/2	100	1247
GW 68 750 W	1/2	100	1260
GW 68 751	1/4	48	1267
GW 68 752	1	42	1267
GW 68 753	1	24	1266
GW 68 758	1/5	1560	1267
GW 68 761	1	16	1267

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 68 762 A	1/2	32	1268
GW 68 762 W	1/2	32	1268
GW 68 763	1	40	1266
GW 68 764	1	21	1266
GW 68 765	1	108	1266
GW 68 766	1	72	1266
GW 68 767	1	72	1266
GW 68 768	1	72	1266
GW 68 769	1	72	1266
GW 68 770	1	110	1261
GW 68 770	1	110	1267
GW 68 776	1/5	1560	1261
GW 68 778	1/5	1560	1248
GW 68 781	1	176	1248
GW 68 781	1	176	1261
GW 68 782	1	16	1248
GW 68 782	1	16	1261
GW 68 785	1	72	52
GW 68 785	1	72	1266
GW 68 786	1	72	52
GW 68 786	1	72	1266
GW 68 788	1	312	1247
GW 68 788	1	312	1260
GW 68 789	1	312	1247
GW 68 789	1	312	1260
GW 68 790	1	50	1248
GW 68 790	1	50	1261
GW 68 791	1	50	1248
GW 68 791	1	50	1261
GW 68 792	1	110	1260
GW 68 793	1	110	1248
GW 68 793	1	110	1260
GW 68 794	1	72	1248
GW 68 794	1	72	1260
GW 68 795	1/10	1300	1268
GW 68 796	1	28	1248
GW 68 796	1	28	1261
GW 68 799	1	312	1262
GW 68 800	1	110	1247
GW 68 800	1	110	1260
GW 68 801 A	1	3	1262
GW 68 801 W	1	3	1262
GW 68 802 A	1	3	1262
GW 68 802 W	1	3	1262
GW 68 803 A	1	3	1262
GW 68 803 W	1	4	1262
GW 68 831 A	1	2	1263
GW 68 831 W	1	2	1263
GW 68 832 A	1	2	1263
GW 68 832 W	1	2	1263
GW 68 833 A	1	2	1263
GW 68 833 W	1	2	1263
GW 68 841 A	1	10	1254
GW 68 841 W	1	10	1254
GW 68 842 A	1	10	1254
GW 68 842 W	1	8	1254
GW 68 846 A	1	10	1254
GW 68 846 W	1	10	1254
GW 68 847 A	1	10	1254
GW 68 847 W	1	10	1254
GW 68 851 A	1	6	1255
GW 68 851 W	1	6	1255
GW 68 852 A	1	6	1255
GW 68 852 W	1	6	1255
GW 68 855 G	1	6	1255
GW 68 856 A	1	8	1255
GW 68 856 W	1	5	1255
GW 68 857 A	1	6	1256
GW 68 857 W	1	6	1256
GW 68 858 A	1	6	1256
GW 68 858 W	1	6	1256
GW 68 867 A	1	2	1263
GW 68 867 W	1	2	1263
GW 68 868 A	1		1264
GW 68 868 W	1	2	1264
GW 68 874 A	1	6	1257
GW 68 874 W	1	6	1257
GW 68 875 A	1		1257
GW 68 875 W	1	6	1257
GW 68 876 A	1	6	1257
GW 68 876 W	1	6	1257
GW 68 877 A	1	6	1257
GW 68 877 W	1	4	1257
GW 68 878 A	1	6	1257
GW 68 878 W	1	6	1257
GW 68 881 A	1	10	137
GW 68 883 A	1	10	137
GW 68 884 A	1	10	137
GW 68 901	1	6	1246
GW 68 902	1	6	1246
GW 68 903	1	8	1246
GW 68 904	1		1246
GW 68 905	1	6	1246
GW 68 931	1	8	1247
GW 68 990	1	50	1248
GW 68 990	1	50	1261
GW 68 991	1	280	1259
GW 68 991	1	280	1264
GW 68 992	1/10	3120	1259
GW 68 992	1/10	3120	1264
GW 68 994	1	110	1259
GW 68 994	1	110	1265
GW 68 995	1	128	1259
GW 68 995	1	128	1265
GW 68 998	1	48	1258

GW 70

Code	Quantity		Page
	Pack/carton	Pallet	
GW 70 001	1/10	240	152
GW 70 002	1/10	240	152
GW 70 003	1/10	600	152
GW 70 004	1/10	400	152
GW 70 005	1/10	240	152
GW 70 006	1/10	900	152
GW 70 007	1/5	300	152
GW 70 008	1/5	250	152
GW 70 009	1/10	1440	152
GW 70 009	1/10	1440	293
GW 70 009	1/10	1440	310
GW 70 026	1/12	1920	154
GW 70 027	1/12	1920	154
GW 70 028	1/12	1920	154
GW 70 029	1/12	1488	154
GW 70 035	1/12	3276	154
GW 70 036	1/12	3276	154
GW 70 040	1/20	720	154
GW 70 041	1/20	640	154
GW 70 052	1/10	240	152
GW 70 053	1/10	240	152
GW 70 055	1/10	240	152
GW 70 056	1/10	240	152
GW 70 058	1/5	250	152
GW 70 059	1/5	250	152
GW 70 061	1/6	216	152
GW 70 062	1/6	216	152
GW 70 064	1/6	216	152
GW 70 065	1/6	216	152
GW 70 067	1/6	144	152
GW 70 068	1/6	144	152
GW 70 070	1	75	153
GW 70 071	1		153
GW 70 073	1	90	153
GW 70 074	1	108	153
GW 70 076	1	48	153
GW 70 077	1	48	153
GW 70 079	1		153
GW 70 080	1	36	153
GW 70 085	1		153
GW 70 086	1	24	153
GW 70 088	1	24	153
GW 70 089	1	24	153
GW 70 091	1	24	153
GW 70 092	1	24	153
GW 70 171	1/20	720	154
GW 70 172	1/20		154
GW 70 173	1/20		154
GW 70 174	1/20		154
GW 70 175	1/20	480	154
GW 70 176	1/15		154
GW 70 181	1/20	720	155
GW 70 182	1/15		155
GW 70 183	1/10		155
GW 70 184	1/10		155
GW 70 185	1/8	128	155
GW 70 186	1/6		155
GW 70 201	1/24	1152	153
GW 70 202	1/24	1200	153
GW 70 203	1/24	1728	153
GW 70 204	1/24	960	153
GW 70 205	1/24	960	153
GW 70 206	1/24	864	153
GW 70 207	1/12	504	153
GW 70 208	1/12	504	153
GW 70 231	1/4	80	151
GW 70 235	1/4	80	151
GW 70 238	1/4	160	151

Code	Quantity		Page
	Pack/carton	Pallet	
GW 70 239	1/4	80	151
GW 70 242	1/4	80	151
GW 70 401 M	1	144	149
GW 70 401 P	1/16	512	147
GW 70 402 M	1	273	149
GW 70 402 NM	1	273	149
GW 70 402 NP	1/16	256	147
GW 70 402 P	1/16	512	147
GW 70 403 M	1	273	149
GW 70 403 P	1/16	512	147
GW 70 404 M	1	273	149
GW 70 404 P	1/16	256	147
GW 70 405 M	1	273	149
GW 70 405 NM	1	273	149
GW 70 405 NP	1/16	256	147
GW 70 405 P	1/16	256	147
GW 70 406 M	1	273	149
GW 70 406 P	1/16	512	147
GW 70 407 M	1	28	149
GW 70 407 NM	1	30	149
GW 70 407 NP	1/6	120	147
GW 70 407 P	1/6	120	147
GW 70 408 M	1	30	149
GW 70 408 P	1/6	240	147
GW 70 413 M	1	273	149
GW 70 413 P	1/16	256	147
GW 70 414 M	1	273	149
GW 70 414 NM	1	273	149
GW 70 414 NP	1/16	256	147
GW 70 414 P	1/16	256	147
GW 70 415 M	1	273	149
GW 70 415 P	1/16	256	147
GW 70 416 M	1	273	149
GW 70 416 P	1/16	256	147
GW 70 417 M	1	273	149
GW 70 417 NM	1	273	149
GW 70 417 NP	1/16	256	147
GW 70 417 P	1/16	256	147
GW 70 418 M	1	273	149
GW 70 418 P	1/16	256	147
GW 70 419 M	1	30	149
GW 70 419 NM	1	30	149
GW 70 419 NP	1/6	120	147
GW 70 419 P	1/6	120	147
GW 70 420 M	1	30	149
GW 70 420 P	1/6	120	147
GW 70 421 M	1	30	149
GW 70 421 NM	1	30	149
GW 70 421 NP	1	20	147
GW 70 421 P	1	20	147
GW 70 422 M	1	30	149
GW 70 422 P	1	20	147
GW 70 423 M	1	20	149
GW 70 423 NM	1	20	149
GW 70 423 NP	1	20	147
GW 70 423 P	1	20	147
GW 70 424 M	1	20	149
GW 70 424 P	1	20	147
GW 70 425 M	1	20	149
GW 70 425 NM	1	20	149
GW 70 425 NP	1	20	147
GW 70 425 P	1	20	147
GW 70 426 M	1	20	149
GW 70 426 P	1	20	147
GW 70 431 M	1	273	150
GW 70 431 P	1/16	512	148
GW 70 432 M	1	273	150
GW 70 432 NM	1	273	150
GW 70 432 NP	1/16	256	148
GW 70 432 P	1/16	512	148
GW 70 433 M	1	273	150
GW 70 433 P	1/16	512	148
GW 70 434 M	1	273	150
GW 70 434 P	1/16	512	148
GW 70 435 M	1	144	150
GW 70 435 NM	1	273	150
GW 70 435 NP	1/16	256	148
GW 70 435 P	1/16	512	148
GW 70 436 M	1	273	150
GW 70 436 P	1/16	512	148
GW 70 437 M	1	30	150
GW 70 437 NM	1	30	150
GW 70 437 NP	1/6	120	148
GW 70 437 P	1/6	240	148
GW 70 438 M	1	30	150
GW 70 438 P	1/6	240	148
GW 70 441 M	1	273	150
GW 70 441 P	1/16	256	148
GW 70 442 M	1	273	150
GW 70 442 NM	1	273	150
GW 70 442 NP	1/16	256	148
GW 70 442 P	1/16	256	148
GW 70 443 M	1	273	150
GW 70 443 P	1/16	256	148
GW 70 451	1	75	156
GW 70 452	1	75	156
GW 70 453	1	75	156
GW 70 454	1	75	156
GW 70 455	1	75	156
GW 70 456	1	75	156
GW 70 457	1	75	156
GW 70 458	1	75	156
GW 70 459	1	36	156
GW 70 460	1	36	156
GW 70 471	1	75	156
GW 70 472	1	75	156
GW 70 473	1	75	156
GW 70 474	1	75	156
GW 70 475	1	75	156
GW 70 476	1	75	156
GW 70 477	1	75	156
GW 70 478	1	75	156
GW 70 479	1	36	156
GW 70 480	1	36	156
GW 70 486 M	1	273	150
GW 70 486 P	1/16	256	148
GW 70 487 M	1	273	150
GW 70 487 NM	1	273	150
GW 70 487 NP	1/16	256	148
GW 70 487 P	1/16	256	148
GW 70 488 M	1	273	150
GW 70 488 P	1/16	256	148
GW 70 489 M	1	30	150
GW 70 489 NM	1	30	150
GW 70 489 NP	1/6	120	148
GW 70 489 P	1/6	120	148
GW 70 490 M	1	30	150
GW 70 490 P	1/6	120	148
GW 70 491 M	1	30	150
GW 70 491 NM	1	30	150
GW 70 491 NP	1	20	148
GW 70 491 P	1	20	148
GW 70 492 M	1	28	150
GW 70 492 P	1	20	148
GW 70 493 M	1	20	150
GW 70 493 NM	1	20	150
GW 70 493 NP	1	20	148
GW 70 493 P	1	20	148
GW 70 494 M	1	20	150
GW 70 494 P	1	60	148
GW 70 495 M	1	20	150
GW 70 495 NM	1	20	150
GW 70 495 NP	1	20	148
GW 70 495 P	1	20	148
GW 70 496 M	1	20	150
GW 70 496 P	1	20	148
GW 70 601 P	1/4	72	147
GW 70 602 P	1/4	72	147
GW 70 603 P	1/4	72	147
GW 70 604 P	1/4	72	147
GW 70 605 P	1	20	147
GW 70 607 P	1	20	147
GW 70 621 P	1/4		147
GW 70 622 P	1/4	72	147
GW 70 623 P	1/4		147
GW 70 624 P	1/4	72	147
GW 70 625 P	1	20	147
GW 70 627 P	1		147
GW 70 641 P	1/4	40	148
GW 70 642 P	1/4	64	148
GW 70 643 P	1/4	72	148
GW 70 644 P	1/4	72	148
GW 70 645 P	1	20	148
GW 70 647 P	1	20	148
GW 70 661 P	1/4	80	148
GW 70 662 P	1/4	80	148
GW 70 663 P	1/4	80	148
GW 70 664 P	1/4	80	148
GW 70 665 P	1		148
GW 70 667 P	1		148
GW 70 701 M	1	28	149
GW 70 702 M	1	28	149
GW 70 703 M	1	28	149
GW 70 704 M	1	28	149

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 70 705 M	1	28	149
GW 70 707 M	1	28	149
GW 70 721 M	1		149
GW 70 722 M	1	28	149
GW 70 723 M	1	28	149
GW 70 724 M	1	28	149
GW 70 725 M	1	28	149
GW 70 727 M	1		149
GW 70 741 M	1		150
GW 70 742 M	1	28	150
GW 70 743 M	1	28	150
GW 70 744 M	1	28	150
GW 70 745 M	1	28	150
GW 70 747 M	1	28	150
GW 70 761 M	1	28	150
GW 70 762 M	1		150
GW 70 763 M	1		150
GW 70 764 M	1		150
GW 70 765 M	1		150
GW 70 767 M	1		150
GW 72			
GW 72 001	10/100	5000	106
GW 72 003	10/100	12500	106
GW 72 005	10/100	12500	106
GW 72 013	10/100	10000	106
GW 72 015	10/100	10000	106
GW 72 021	10/50	5000	106
GW 72 023	10/50	5000	106
GW 72 065	5/20	2000	106
GW 72 092	5/20	2000	106
GW 72 095	5/20	2000	106
GW 72 101	10/100	10000	106
GW 72 101	10/100	10000	508
GW 72 103	10/30	3000	106
GW 72 103	10/30	3000	508
GW 72 104	10/100	10000	106
GW 72 104	10/100	10000	508
GW 72 105	10/100	10000	106
GW 72 105	10/100	10000	508
GW 72 107	10/100	10000	508
GW 72 108	10/100	10000	508
GW 72 109	10/100	10000	508
GW 72 110	10/100	10000	106
GW 72 110	10/100	10000	508
GW 72 111	10/100	19500	508
GW 72 112	10/100	19500	508
GW 72 113	10/100	19500	508
GW 72 114	10/100	19500	508
GW 72 115	10/100	19500	508
GW 72 116	10/100	19500	508
GW 72 117	10/100	19500	508
GW 72 121	10/100	19500	508
GW 72 122	10/100	19500	106
GW 72 122	10/100	19500	508
GW 72 123	10/100	19500	508
GW 72 124	10/100	4000	508
GW 72 131	10	32000	509
GW 72 131	10	32000	540
GW 72 132	10	32000	509
GW 72 132	10	32000	540
GW 72 133	10	32000	509
GW 72 133	10	32000	540
GW 72 134	10	32000	509
GW 72 134	10	32000	540
GW 72 135	10	32000	509
GW 72 135	10	32000	540
GW 72 136	10	32000	509
GW 72 136	10	32000	540
GW 74			
GW 74 201	10/60	7680	227
GW 74 202	10/60	3840	227
GW 74 301	10/60	1320	160
GW 74 302	10/60	1320	160
GW 74 303	10/60	1320	160
GW 74 304	10/60	1320	160
GW 74 305	10/60	1320	160
GW 74 306	10/60	1320	160
GW 74 311	10/60	1320	160
GW 74 312	10/60	1320	160
GW 74 313	10/60	1320	160
GW 74 314	10/60	1320	160
GW 74 315	10/60	1320	160
GW 74 316	10/60	1320	160
GW 74 341	10/60	1320	160
GW 74 342	10/60	1320	160
GW 74 343	10/60	1320	160
GW 74 344	10/60	1320	160
GW 74 345	10/60	1320	160
GW 74 361	10/60	2640	115
GW 74 361	10/60	2640	161
GW 74 362	10/60	1320	161
GW 74 363	10/60	1320	161
GW 74 364	10/60	1320	161
GW 74 365	10/60	1320	161
GW 74 366	10/60	1320	161
GW 74 367	10/60	2640	161
GW 74 401	10/60	1320	162
GW 74 402	10/60	1320	162
GW 74 411	10/60	1320	162
GW 74 412	10/60	2640	162
GW 74 421	10/60	1320	162
GW 74 422	10/60	1320	162
GW 74 451	10/60	1320	163
GW 74 452	10/60	1320	163
GW 74 453	10/60	1320	163
GW 74 454	10/60	1320	163
GW 74 455	10/60	1320	163
GW 74 501	1/30	13500	116
GW 74 501	1/30	13500	163
GW 74 501	1/30	13500	166
GW 74 502	1/30	13500	116
GW 74 502	1/30	13500	163
GW 74 502	1/30	13500	166
GW 74 503	1/30	9000	116
GW 74 503	1/30	9000	163
GW 74 504	1/30	9000	116
GW 74 504	1/30	9000	163
GW 74 505	1/30	9000	116
GW 74 505	1/30	9000	163
GW 74 511	1/30	13500	163
GW 74 515	10/100	30000	164
GW 74 516	10/100	30000	164
GW 74 517	10/100	30000	164
GW 74 518	10/100	30000	164
GW 74 521	10/100	13000	164
GW 74 522	5/100	1600	164
GW 74 523	10/100	13000	164
GW 74 524	10/100	1200	164
GW 74 525	10/100	13000	164
GW 76			
GW 76 261	1/40	1680	245
GW 76 262	1/32	1344	245
GW 76 263	1/24	672	245
GW 76 264	1/16	384	245
GW 76 265	1/8	224	245
GW 76 266	1/4	120	245
GW 76 267	1	60	245
GW 76 272	1/10	1950	246
GW 76 273	1/10	1600	246
GW 76 274	1/10	1200	246
GW 76 275	1/5	7200	246
GW 76 276	1/5	720	246
GW 76 277	1/5	360	246
GW 76 281	1/40	1680	245
GW 76 282	1/32	1344	245
GW 76 283	1/24	672	245
GW 76 284	1/16	384	245
GW 76 285	1/8	224	245
GW 76 286	1/4	120	245
GW 76 287	1	60	245
GW 76 291	1/40	1680	246
GW 76 292	1/32	1152	246
GW 76 293	1/24	720	246
GW 76 294	1/16	192	246
GW 76 295	1/8	224	246
GW 76 296	1/4	120	246
GW 76 297	1	60	246
GW 76 825	10/100	4800	383
GW 76 826	10/100	4800	383
GW 76 827	10/100	7200	383
GW 76 828	5/50	2400	383
GW 76 829	5/50	3600	383
GW 76 830	5/50	2400	383
GW 76 831	10/100	7200	383
GW 76 832	10/100	9000	383
GW 76 833	5/50	6000	383
GW 76 834	5/50	3600	383
GW 76 835	2/10	1200	383
GW 76 837	1/50	6000	382
GW 76 839	1/50	18000	382
GW 76 841	1/50	6000	382
GW 76 842	1/50	6000	382
GW 76 843	1/50	6000	382
GW 76 844	1/50	3600	382

Code	Quantity		Page
	Pack/carton	Pallet	
GW 76 845	1/10	2500	382
GW 76 846	1/10	960	382
GW 76 847	1/10	720	382
GW 76 848	1/50	12500	382
GW 76 849	1/50	4800	382
GW 76 850	1/10	3850	382
GW 76 851	1/10	2500	382
GW 76 852	1/10	720	382
GW 76 865	10/100	11000	383
GW 76 866	10/100		383
GW 76 867	10/100	12000	383
GW 76 868	5/50	13200	383
GW 76 869	5/50	1800	383
GW 76 870	10/100	4400	383
GW 76 871	10/100	4400	383
GW 76 872	5/50	2200	383
GW 76 873	5/50	2200	383
GW 76 894	50/250	2000	383
GW 76 895	5/40	360	383
GW 76 896	10/100	4800	383
GW 76 897	2/10	1440	383
GW 76 901	10/100	8700	385
GW 76 902	10/100	8700	385
GW 76 903	10/100	15600	385
GW 76 904	10/100	15600	385
GW 76 905	10/100	15600	385
GW 76 906	5/50	7800	385
GW 76 907	5/50	3200	385
GW 76 908	5/50	1500	385
GW 76 909	2/10	580	385
GW 76 910	2/10	1560	385
GW 76 921	10/100	8700	385
GW 76 922	10/100	8700	385
GW 76 923	10/100	15600	385
GW 76 924	10/100	3000	385
GW 76 925	5/50	400	385
GW 76 926	5/50	1500	385
GW 76 927	2/10	580	385
GW 76 928	2/10	1560	385
GW 76 941	25/100	19500	385
GW 76 942	25/100	19500	385
GW 76 943	10/50	7800	385
GW 76 949	25/100	19500	385
GW 76 950	10/50	1000	385
GW 76 951	25/100	21600	384
GW 76 951	25/100	21600	385
GW 76 952	25/100	19500	384
GW 76 952	25/100	19500	385
GW 76 953	25/100	19500	384
GW 76 953	25/100	19500	385
GW 76 954	25/100	19500	384
GW 76 954	25/100	19500	385
GW 76 955	10/50	9750	384
GW 76 955	10/50	9750	385
GW 76 956	10/50	9750	384
GW 76 956	10/50	9750	385
GW 76 957	25/100	19500	384
GW 76 957	25/100	19500	385
GW 76 958	25/100	19500	384
GW 76 958	25/100	19500	385
GW 76 959	25/100	19500	384
GW 76 959	25/100	19500	385
GW 76 960	25/100	19500	384
GW 76 960	25/100	19500	385
GW 76 961	25/100	19500	384
GW 76 961	25/100	19500	385
GW 76 962	10/50	6000	384
GW 76 962	10/50	6000	385
GW 76 963	10/50	3600	384
GW 76 963	10/50	3600	385
GW 76 966	100/500		384
GW 76 967	25/125	2250	384
GW 76 972	100/400	28800	384
GW 76 973	100/300	21600	384
GW 76 974	10/100	3000	384
GW 76 975	10/100	6600	384
GW 76 976	10/100	11000	384
GW 76 977	10/100	6600	384
GW 76 978	5/50	3300	384
GW 76 979	5/50	3300	384
GW 76 980	10/100	21600	384
GW 76 981	10/100	21600	384
GW 76 982	10/100	6600	384
GW 76 983	10/100	6600	384
GW 76 984	5/50	3300	384
GW 76 985	5/50	3300	384
GW 76 986	5/50	3300	384

GW 80

Code	Quantity		Page
	Pack/carton	Pallet	
GW 80 401	12	480	140
GW 80 403	12	480	140
GW 80 404	12	240	140
GW 80 409	36	720	140
GW 80 411	36	576	140
GW 80 412	36	144	140

GW 90

Code	Quantity		Page
	Pack/carton	Pallet	
GW 90 005	6/24	1536	438
GW 90 006	6/24	1536	438
GW 90 007	6/24	1536	438
GW 90 008	6/24	1536	438
GW 90 009	6/24	1536	438
GW 90 010	6/24	1536	438
GW 90 011	6/24		438
GW 90 022	6/24	1536	438
GW 90 025	6/24	3840	438
GW 90 026	6/24	3840	438
GW 90 027	6/24	3840	438
GW 90 028	6/24	3840	438
GW 90 029	6/24	3840	438
GW 90 030	6/24	3840	438
GW 90 031	6/24	1536	438
GW 90 045	6/24	2304	438
GW 90 046	6/24	3840	438
GW 90 047	6/24	3840	438
GW 90 048	6/24	2304	438
GW 90 049	6/24	2304	438
GW 90 050	6/24	1536	438
GW 90 051	6/24	1536	438
GW 90 065	3/12	768	438
GW 90 066	3/12	768	438
GW 90 067	3/12	768	438
GW 90 068	3/12	768	438
GW 90 069	3/12	768	438
GW 90 070	3/12	768	438
GW 90 071	3/12	768	438
GW 90 085	3/12	768	438
GW 90 086	3/12	768	438
GW 90 087	3/12	1152	438
GW 90 088	3/12	768	438
GW 90 089	3/12	768	438
GW 90 090	3/12	768	438
GW 90 091	3/12		438
GW 90 225	6/24	1536	439
GW 90 226	6/24	3840	439
GW 90 227	6/24	3840	439
GW 90 228	6/24	2304	439
GW 90 229	6/24	2304	439
GW 90 230	6/24	1536	439
GW 90 231	6/24	1536	439
GW 90 245	6/24	1536	439
GW 90 246	6/24	3840	439
GW 90 247	6/24	3840	439
GW 90 248	6/24	1536	439
GW 90 249	6/24	1536	439
GW 90 250	6/24	1536	439
GW 90 251	6/24	1536	439
GW 90 265	3/12	768	439
GW 90 266	3/12	768	439
GW 90 267	3/12	1152	439
GW 90 268	3/12	384	439
GW 90 269	3/12	768	439
GW 90 270	3/12	1152	439
GW 90 271	3/12	768	439
GW 90 285	3/12	768	439
GW 90 286	3/12	768	439
GW 90 287	3/12	1152	439
GW 90 288	3/12	768	439
GW 90 289	3/12	768	439
GW 90 290	3/12	1152	439
GW 90 291	3/12	768	439
GW 90 325	6/24	1536	440
GW 90 326	6/24	1536	440
GW 90 327	6/24	1536	440
GW 90 328	6/24	3840	440
GW 90 329	6/24	1536	440
GW 90 330	6/24	1536	440
GW 90 331	6/24	1536	440
GW 90 345	6/24		440
GW 90 346	6/24		440
GW 90 347	6/24		440
GW 90 348	6/24	1536	440
GW 90 349	6/24	1152	440
GW 90 350	6/24	1536	440
GW 90 351	6/24	1536	440

Quick Reference

Code	Quantity Pack/carton	Pallet	Page
GW 90 445	6/24	1536	440
GW 90 446	6/24	2304	440
GW 90 447	6/24	1536	440
GW 90 448	6/24	1536	440
GW 90 449	6/24	1536	440
GW 90 450	6/24	1536	440
GW 90 451	6/24	1536	440
GW 90 584	100	9800	1171
GW 90 585	100	8400	1171
GW 90 602	6/24	1536	438
GW 90 605	6/24	2304	438
GW 90 606	6/24	3840	438
GW 90 607	6/24	3840	438
GW 90 608	6/24	3840	438
GW 90 609	6/24	1536	438
GW 90 610	6/24	3840	438
GW 90 626	6/24	1536	439
GW 90 627	6/24	1536	439
GW 90 628	6/24	1536	439
GW 90 629	6/24	1536	439
GW 90 630	6/24	1536	439
GW 90 706 B	1	280	1151
GW 90 706 U	1	200	1152
GW 90 708 A	1/4	280	1151
GW 90 709	1	192	1151
GW 90 710	1	160	1151
GW 90 721 A	1	1248	1154
GW 90 727	1	1120	1154
GW 90 728	1	168	1154
GW 90 729	1	168	1154
GW 90 730	1	280	1162
GW 90 740 A	1	234	1160
GW 90 741	1	224	1160
GW 90 742	1	192	1161
GW 90 764	1	224	1163
GW 90 765	1	128	1163
GW 90 766	1/4	336	1164
GW 90 768 ①	1		1164
GW 90 800	1	42	1170
GW 90 802 A	1	168	1151
GW 90 807	50	7800	1171
GW 90 808	50	7800	1171
GW 90 856	1	224	1162
GW 90 857	1	224	1162
GW 90 871	1	156	1170
GW 90 873	1/4	168	1171
GW 90 876	1/5	960	531
GW 90 876	1/5	960	1168
GW 90 884	1	48	1170
GW 90 885	1	195	1170
GW 90 893	1/4	216	427
GW 90 896	1/4	168	427
GW 90 898	1/4	280	427
GW 90 901 N	1/4	216	422
GW 90 902 N	1/4	216	422
GW 90 911 B	1/2	114	422
GW 90 912 B	1/2	190	422
GW 90 913	1/4	132	422
GW 90 913 B	1/2	114	422
GW 90 917	1/4	72	422
GW 90 918	1/4	72	422
GW 90 919	1/4	228	422
GW 90 921	1/2	180	423
GW 90 921 B	1/2	190	423
GW 90 922	1/2	180	423
GW 90 922 B	1/2	190	423
GW 90 923	1/2	180	423
GW 90 923 B	1/2	114	423
GW 90 927	1/2	190	423
GW 90 927 B	1/2	114	423
GW 90 928	1/2	160	423
GW 90 928 B	1/2	114	423
GW 90 929	1/2	190	423
GW 90 929 B	1/2	114	423
GW 90 930	1/2	190	423
GW 90 967	1/4	216	424
GW 90 969	1/4	216	424
GW 90 986	1/4	216	426
GW 90 988	1/4	108	426
GW 90 992	1	280	428
GW 91			
GW 91 906	1/6	372	456
GW 91 907	1/6	372	456
GW 91 908	1/6	744	456
GW 91 909	1/6	744	456
GW 91 925	1/6	372	456
GW 91 926	1/6	372	456
GW 91 927	1/6	372	456
GW 91 928	1/6	372	456
GW 91 929	1/6		456
GW 92			
GW 92 001	6/24	1536	447
GW 92 002	6/24	1536	447
GW 92 003	6/24	1536	447
GW 92 004	6/24	1536	447
GW 92 005	6/24	3840	447
GW 92 006	6/24	3840	447
GW 92 007	6/24	3840	447
GW 92 008	6/24	3840	447
GW 92 009	6/24	3840	447
GW 92 010	6/24	3840	447
GW 92 011	6/24	3840	447
GW 92 012	6/24	3840	447
GW 92 013	6/24	3840	447
GW 92 014	6/24	1536	447
GW 92 021	3/12	768	447
GW 92 022	3/12	768	447
GW 92 023	3/12	768	447
GW 92 024	3/12	768	447
GW 92 025	3/12	768	447
GW 92 026	3/12	1920	447
GW 92 027	3/12	1920	447
GW 92 028	3/12	1920	447
GW 92 029	3/12	1920	447
GW 92 030	3/12	1920	447
GW 92 031	3/12	1920	447
GW 92 032	3/12	1920	447
GW 92 033	3/12	1920	447
GW 92 034	3/12	768	447
GW 92 041	3/12	768	447
GW 92 042	3/12	768	447
GW 92 043	3/12	768	447
GW 92 044	3/12	768	447
GW 92 045	3/12	1152	447
GW 92 046	3/12	1920	447
GW 92 047	3/12	1920	447
GW 92 048	3/12	1920	447
GW 92 049	3/12	1920	447
GW 92 050	3/12	1920	447
GW 92 051	3/12	1152	447
GW 92 052	3/12	1920	447
GW 92 053	3/12	1920	447
GW 92 054	3/12	768	447
GW 92 061	2/8	512	447
GW 92 062	2/8	512	447
GW 92 063	2/8	512	447
GW 92 064	2/8	512	447
GW 92 065	2/8	512	447
GW 92 066	2/8	1280	447
GW 92 067	2/8	1280	447
GW 92 068	2/8	1280	447
GW 92 069	2/8	1280	447
GW 92 070	2/8	1280	447
GW 92 071	2/8	1280	447
GW 92 072	2/8	1280	447
GW 92 073	2/8	1280	447
GW 92 074	2/8	512	447
GW 92 081	1/3	372	447
GW 92 082	1/3	348	447
GW 92 083	1/3	348	447
GW 92 084	1/3	348	447
GW 92 085	1/3	372	447
GW 92 086	1/3	651	447
GW 92 087	1/3	960	447
GW 92 088	1/3	960	447
GW 92 089	1/3	960	447
GW 92 090	1/3	960	447
GW 92 091	1/3	912	447
GW 92 092	1/3	912	447
GW 92 093	1/3	960	447
GW 92 094	1/3	372	447
GW 92 105	6/24	2304	445
GW 92 106	6/24	3840	445
GW 92 107	6/24	1536	445
GW 92 108	6/24	3840	445
GW 92 109	6/24	3840	445
GW 92 110	6/24	3840	445
GW 92 111	6/24	3840	445
GW 92 112	6/24	3840	445
GW 92 125	3/12	768	445
GW 92 126	3/12	1920	445
GW 92 127	3/12	768	445
GW 92 128	3/12	1920	445

Availability: ① July 2025

Code	Quantity		Page
	Pack/carton	Pallet	
GW 92 129	3/12	1152	445
GW 92 130	3/12	1152	445
GW 92 131	3/12	1152	445
GW 92 132	3/12	1152	445
GW 92 145	3/12	768	445
GW 92 146	3/12	768	445
GW 92 147	3/12	768	445
GW 92 148	3/12	1920	445
GW 92 149	3/12	1920	445
GW 92 150	3/12	1152	445
GW 92 151	3/12	1152	445
GW 92 152	3/12	1152	445
GW 92 165	2/8	512	445
GW 92 166	2/8	512	445
GW 92 167	2/8	512	445
GW 92 168	2/8	1280	445
GW 92 169	2/8	1280	445
GW 92 170	2/8	1280	445
GW 92 171	2/8	768	445
GW 92 172	2/8	768	445
GW 92 185	1/3	372	445
GW 92 186	1/3	372	445
GW 92 187	1/3	348	445
GW 92 188	1/3	651	445
GW 92 189	1/3	651	445
GW 92 190	1/3	651	445
GW 92 191	1/3	651	445
GW 92 192	1/3	651	445
GW 92 205	6/24	3840	448
GW 92 206	6/24	3840	448
GW 92 207	6/24	3840	448
GW 92 208	6/24	3840	448
GW 92 209	6/24	3840	448
GW 92 210	6/24	3840	448
GW 92 211	6/24	3840	448
GW 92 212	6/24	1536	448
GW 92 213	6/24	1536	448
GW 92 214	6/24	1536	448
GW 92 245	3/12	768	448
GW 92 246	3/12	768	448
GW 92 247	3/12	768	448
GW 92 248	3/12	768	448
GW 92 249	3/12	768	448
GW 92 250	3/12	768	448
GW 92 251	3/12	768	448
GW 92 252	3/12	768	448
GW 92 253	3/12	768	448
GW 92 254	3/12	768	448
GW 92 265	2/8	512	448
GW 92 266	2/8	512	448
GW 92 267	2/8	1280	448
GW 92 268	2/8	512	448
GW 92 269	2/8	512	448
GW 92 270	2/8	512	448
GW 92 271	2/8	512	448
GW 92 272	2/8	768	448
GW 92 273	2/8	512	448
GW 92 274	2/8	512	448

Code	Quantity		Page
	Pack/carton	Pallet	
GW 92 285	1/3	372	448
GW 92 286	1/3	372	448
GW 92 287	1/3	651	448
GW 92 288	1/3	372	448
GW 92 289	1/3	372	448
GW 92 290	1/3	372	448
GW 92 291	1/3	372	448
GW 92 292	1/3	372	448
GW 92 293	1/3	372	448
GW 92 294	1/3	372	448
GW 92 305	6/24	1536	446
GW 92 306	6/24	3840	446
GW 92 307	6/24	1536	446
GW 92 308	6/24	3840	446
GW 92 309	6/24	3840	446
GW 92 310	6/24	3840	446
GW 92 311	6/24	3840	446
GW 92 312	6/24	2304	446
GW 92 325	3/12	768	446
GW 92 326	3/12	768	446
GW 92 327	3/12	768	446
GW 92 328	3/12	768	446
GW 92 329	3/12	768	446
GW 92 330	3/12	768	446
GW 92 331	3/12	768	446
GW 92 332	3/12	768	446
GW 92 345	3/12	768	446
GW 92 346	3/12	768	446
GW 92 347	3/12	768	446
GW 92 348	3/12	768	446
GW 92 349	3/12	768	446
GW 92 350	3/12	768	446
GW 92 351	3/12	768	446
GW 92 352	3/12	768	446
GW 92 365	2/8	512	446
GW 92 366	2/8	512	446
GW 92 367	2/8	512	446
GW 92 368	2/8	512	446
GW 92 369	2/8	512	446
GW 92 370	2/8	512	446
GW 92 371	2/8	512	446
GW 92 372	2/8	512	446
GW 92 385	1/3	372	446
GW 92 386	1/3	372	446
GW 92 387	1/3	372	446
GW 92 388	1/3	372	446
GW 92 389	1/3	372	446
GW 92 390	1/3	372	446
GW 92 391	1/3	348	446
GW 92 392	1/3	348	446
GW 92 405	6/24	1536	449
GW 92 406	6/24	1536	449
GW 92 407	6/24	1536	449
GW 92 408	6/24	1536	449
GW 92 409	6/24	1536	449
GW 92 410	6/24	1536	449
GW 92 411	6/24	1536	449
GW 92 414	6/24	1536	449

Code	Quantity		Page
	Pack/carton	Pallet	
GW 92 445	3/12	768	449
GW 92 446	3/12	768	449
GW 92 447	3/12	768	449
GW 92 448	3/12	768	449
GW 92 449	3/12	768	449
GW 92 450	3/12	768	449
GW 92 451	3/12	768	449
GW 92 454	3/12		449
GW 92 465	2/8	512	449
GW 92 466	2/8	512	449
GW 92 467	2/8	512	449
GW 92 468	2/8	512	449
GW 92 469	2/8	512	449
GW 92 470	2/8	512	449
GW 92 471	2/8	512	449
GW 92 474	2/8		449
GW 92 485	1/3	279	449
GW 92 486	1/3	348	449
GW 92 487	1/3	651	449
GW 92 488	1/3	348	449
GW 92 489	1/3	348	449
GW 92 490	1/3	348	449
GW 92 491	1/3	372	449
GW 92 494	1/3	348	449
GW 92 505	6/24	1536	451
GW 92 506	6/24	2304	451
GW 92 507	6/24	2304	451
GW 92 508	6/24	3840	451
GW 92 509	6/24	2304	451
GW 92 510	6/24	2304	451
GW 92 511	6/24	3840	451
GW 92 512	6/24	1536	451
GW 92 513	6/24	1536	451
GW 92 514	6/24	1536	451
GW 92 545	3/12		451
GW 92 546	3/12	768	451
GW 92 547	3/12	768	451
GW 92 548	3/12	768	451
GW 92 549	3/12	768	451
GW 92 550	3/12	768	451
GW 92 551	3/12	768	451
GW 92 552	3/12	768	451
GW 92 553	3/12	768	451
GW 92 554	3/12	768	451
GW 92 565	2/8	512	451
GW 92 566	2/8	512	451
GW 92 567	2/8	512	451
GW 92 568	2/8	1280	451
GW 92 569	2/8	768	451
GW 92 570	2/8	768	451
GW 92 571	2/8	768	451
GW 92 572	2/8	512	451
GW 92 573	2/8	512	451
GW 92 574	2/8	512	451
GW 92 585	1/3	279	451
GW 92 586	1/3	279	451
GW 92 587	1/3	348	451
GW 92 588	1/3	348	451

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 92 589	1/3	279	451
GW 92 590	1/3	348	451
GW 92 591	1/3	348	451
GW 92 592	1/3	348	451
GW 92 593	1/3	279	451
GW 92 594	1/3	348	451
GW 92 605	6/24	1536	450
GW 92 606	6/24	3840	450
GW 92 607	6/24	3840	450
GW 92 608	6/24	3840	450
GW 92 609	6/24	1536	450
GW 92 610	6/24	1536	450
GW 92 611	6/24	1536	450
GW 92 612	6/24	1536	450
GW 92 613	6/24	1536	450
GW 92 614	6/24	1536	450
GW 92 645	3/12	768	450
GW 92 646	3/12	768	450
GW 92 647	3/12	768	450
GW 92 648	3/12	768	450
GW 92 649	3/12	768	450
GW 92 650	3/12	768	450
GW 92 651	3/12	1152	450
GW 92 652	3/12	768	450
GW 92 653	3/12	768	450
GW 92 654	3/12	768	450
GW 92 665	2/8	512	450
GW 92 666	2/8	512	450
GW 92 667	2/8	1280	450
GW 92 668	2/8	768	450
GW 92 669	2/8	768	450
GW 92 670	2/8	768	450
GW 92 671	2/8	512	450
GW 92 672	2/8	512	450
GW 92 673	2/8	512	450
GW 92 674	2/8	512	450
GW 92 685	1/3	348	450
GW 92 686	1/3	348	450
GW 92 687	1/3	651	450
GW 92 688	1/3	651	450
GW 92 689	1/3	348	450
GW 92 690	1/3	651	450
GW 92 691	1/3	651	450
GW 92 692	1/3	348	450
GW 92 693	1/3	651	450
GW 92 694	1/3	348	450
GW 92 701	6/24	1536	452
GW 92 702	6/24	1536	452
GW 92 703	6/24	1536	452
GW 92 704	6/24	1536	452
GW 92 705	6/24	1536	452
GW 92 706	6/24	1536	452
GW 92 707	6/24	1536	452
GW 92 708	6/24	1536	452
GW 92 709	6/24	1536	452
GW 92 710	6/24	1536	452
GW 92 711	6/24	1536	452
GW 92 714	6/24		452
GW 92 741	3/12	768	452
GW 92 742	3/12	768	452
GW 92 743	3/12	768	452
GW 92 744	3/12	768	452
GW 92 745	3/12	768	452
GW 92 746	3/12	768	452
GW 92 747	3/12	768	452
GW 92 748	3/12	768	452
GW 92 749	3/12	768	452
GW 92 750	3/12	768	452
GW 92 751	3/12	768	452
GW 92 754	3/12		452
GW 92 761	2/8	512	452
GW 92 762	2/8	512	452
GW 92 763	2/8	512	452
GW 92 764	2/8	512	452
GW 92 765	2/8	512	452
GW 92 766	2/8	512	452
GW 92 767	2/8	512	452
GW 92 768	2/8	512	452
GW 92 769	2/8	512	452
GW 92 770	2/8	512	452
GW 92 771	2/8	512	452
GW 92 774	2/8		452
GW 92 781	1/3	348	452
GW 92 782	1/3	348	452
GW 92 783	1/3	348	452
GW 92 784	1/3	348	452
GW 92 785	1/3	279	452
GW 92 786	1/3	348	452
GW 92 787	1/3	348	452
GW 92 788	1/3	348	452
GW 92 789	1/3	348	452
GW 92 790	1/3	348	452
GW 92 791	1/3	651	452
GW 92 794	1/3	348	452
GW 92 805	6/24	1536	453
GW 92 806	6/24	1536	453
GW 92 807	6/24	1536	453
GW 92 808	6/24	1536	453
GW 92 809	6/24	1536	453
GW 92 810	6/24	1536	453
GW 92 811	6/24	1536	453
GW 92 812	6/24	1536	453
GW 92 813	6/24	1536	453
GW 92 845	3/12	768	453
GW 92 846	3/12	768	453
GW 92 847	3/12	768	453
GW 92 848	3/12	768	453
GW 92 849	3/12	768	453
GW 92 850	3/12	768	453
GW 92 851	3/12	768	453
GW 92 852	3/12	768	453
GW 92 853	3/12	768	453
GW 92 865	2/8	512	453
GW 92 866	2/8	512	453
GW 92 867	2/8	512	453
GW 92 868	2/8	512	453
GW 92 869	2/8	512	453
GW 92 870	2/8	512	453
GW 92 871	2/8	512	453
GW 92 872	2/8	512	453
GW 92 873	2/8	512	453
GW 92 885	1/3	279	453
GW 92 886	1/3	348	453
GW 92 887	1/3	348	453
GW 92 888	1/3	348	453
GW 92 889	1/3	348	453
GW 92 890	1/3	372	453
GW 92 891	1/3	372	453
GW 92 892	1/3	348	453
GW 92 893	1/3	348	453

GW 93

Code	Quantity		Page
	Pack/carton	Pallet	
GW 93 201	1/12	768	455
GW 93 202	1/12	768	455
GW 93 203	1/12	768	455
GW 93 204	1/12	768	455
GW 93 205	1/12	768	455
GW 93 206	1/12	768	455
GW 93 221	1/4	224	455
GW 93 222	1/4	224	455
GW 93 223	1/4	224	455
GW 93 224	1/4	224	455
GW 93 225	1/4	224	455
GW 93 226	1/4	224	455
GW 93 231	1/4	120	455
GW 93 232	1/4	120	455
GW 93 233	1/4	120	455
GW 93 234	1/4	120	455
GW 93 235	1/4	120	455
GW 93 236	1/4	120	455
GW 93 241	1/4	72	455
GW 93 242	1/4	120	455
GW 93 243	1/4	72	455
GW 93 244	1/4	72	455
GW 93 245	1/4	72	455
GW 93 246	1/4	72	455
GW 93 307	1/12	1152	454
GW 93 308	1/12	384	454
GW 93 309	1/12	768	454
GW 93 327	1/4	280	454
GW 93 328	1/4	280	454
GW 93 329	1/4	280	454
GW 93 337	1/4	280	454
GW 93 338	1/4	240	454
GW 93 339	1/4	280	454
GW 93 347	1/4	216	454
GW 93 348	1/4	216	454
GW 93 349	1/4	216	454
GW 93 355	1/12	1152	454
GW 93 356	1/12	768	454
GW 93 357	1/12	768	454
GW 93 358	1/12	768	454
GW 93 375	1/4	168	454
GW 93 376	1/4	168	454
GW 93 377	1/4	168	454

Code	Quantity		Page
	Pack/carton	Pallet	
GW 93 378	1/4	168	454
GW 93 385	1/4	168	454
GW 93 386	1/4	120	454
GW 93 387	1/4	120	454
GW 93 388	1/4	120	454
GW 93 395	1/4	72	454
GW 93 396	1/4	72	454
GW 93 397	1/4	72	454
GW 93 398	1/4	72	454
GW 94			
GW 94 005	1/6	1302	467
GW 94 006	1/6	1302	467
GW 94 007	1/6	1302	467
GW 94 008	1/6	1302	467
GW 94 009	1/6	1302	467
GW 94 010	1/6	1302	467
GW 94 011	1/6	744	467
GW 94 015	1/6	744	467
GW 94 016	1/6	744	467
GW 94 017	1/6	744	467
GW 94 018	1/6	744	467
GW 94 019	1/6	744	467
GW 94 020	1/6	744	467
GW 94 025	1/6	744	467
GW 94 026	1/6	1302	467
GW 94 027	1/6	1302	467
GW 94 028	1/6	1302	467
GW 94 029	1/6	1302	467
GW 94 030	1/6	1302	467
GW 94 031	1/6	744	467
GW 94 035	1/6	744	467
GW 94 036	1/6	744	467
GW 94 037	1/6	744	467
GW 94 038	1/6	744	467
GW 94 039	1/6	744	467
GW 94 040	1/6	744	467
GW 94 045	1/4	464	467
GW 94 046	1/4	464	467
GW 94 047	1/4	464	467
GW 94 048	1/4	464	467
GW 94 049	1/4	464	467
GW 94 050	1/4	464	467
GW 94 051	1/4	464	467
GW 94 055	1/4	464	467
GW 94 056	1/4	464	467
GW 94 057	1/4	464	467
GW 94 058	1/4	464	467
GW 94 059	1/4	464	467
GW 94 060	1/4	464	467
GW 94 065	1/3	372	467
GW 94 066	1/3	348	467
GW 94 067	1/3	651	467
GW 94 068	1/3	348	467
GW 94 069	1/3	348	467
GW 94 070	1/3	651	467
GW 94 071	1/3	348	467
GW 94 075	1/3	348	467
GW 94 076	1/3	348	467
GW 94 077	1/3	348	467
GW 94 078	1/3	348	467
GW 94 079	1/3	348	467
GW 94 080	1/3	348	467
GW 94 105	1/6	744	470
GW 94 106	1/6	1302	470
GW 94 107	1/6	1302	470
GW 94 108	1/6	744	470
GW 94 109	1/6	744	470
GW 94 110	1/6	744	470
GW 94 111	1/6	744	470
GW 94 115	1/6	744	470
GW 94 116	1/6	744	470
GW 94 117	1/6	744	470
GW 94 118	1/6	744	470
GW 94 119	1/6	744	470
GW 94 120	1/6	744	470
GW 94 125	1/6	744	470
GW 94 126	1/6	1302	470
GW 94 127	1/6	1302	470
GW 94 128	1/6	744	470
GW 94 129	1/6	744	470
GW 94 130	1/6	744	470
GW 94 131	1/6	744	470
GW 94 135	1/6	744	470
GW 94 136	1/6	744	470
GW 94 137	1/6	744	470
GW 94 138	1/6	744	470
GW 94 139	1/6	744	470
GW 94 140	1/6	744	470
GW 94 145	1/4	464	470
GW 94 146	1/4	464	470
GW 94 147	1/4	464	470
GW 94 148	1/4	464	470
GW 94 149	1/4	464	470
GW 94 150	1/4	464	470
GW 94 151	1/4	464	470
GW 94 155	1/4	464	470
GW 94 156	1/4	464	470
GW 94 157	1/4	464	470
GW 94 158	1/4	464	470
GW 94 159	1/4	464	470
GW 94 160	1/4	464	470
GW 94 165	1/3	348	470
GW 94 166	1/3	348	470
GW 94 167	1/3	609	470
GW 94 168	1/3	348	470
GW 94 169	1/3	348	470
GW 94 170	1/3	651	470
GW 94 171	1/3	348	470
GW 94 175	1/3	348	470
GW 94 176	1/3	348	470
GW 94 177	1/3	348	470
GW 94 178	1/3	348	470
GW 94 179	1/3	348	470
GW 94 180	1/3	348	470
GW 94 205	1/6	744	469
GW 94 206	1/6	1302	469
GW 94 207	1/6	1302	469
GW 94 208	1/6	744	469
GW 94 209	1/6	1302	469
GW 94 210	1/6	744	469
GW 94 211	1/6	744	469
GW 94 215	1/6	744	469
GW 94 216	1/6	744	469
GW 94 217	1/6	744	469
GW 94 218	1/6	744	469
GW 94 219	1/6	744	469
GW 94 220	1/6	744	469
GW 94 225	1/6	744	469
GW 94 226	1/6	744	469
GW 94 227	1/6	744	469
GW 94 228	1/6	744	469
GW 94 229	1/6	744	469
GW 94 230	1/6	744	469
GW 94 231	1/6	744	469
GW 94 235	1/6	744	469
GW 94 236	1/6	744	469
GW 94 237	1/6	744	469
GW 94 238	1/6	744	469
GW 94 239	1/6	744	469
GW 94 240	1/6	744	469
GW 94 245	1/4	464	469
GW 94 246	1/4	464	469
GW 94 247	1/4	464	469
GW 94 248	1/4	464	469
GW 94 249	1/4	464	469
GW 94 250	1/4	464	469
GW 94 251	1/4	464	469
GW 94 255	1/4	464	469
GW 94 256	1/4	464	469
GW 94 257	1/4	464	469
GW 94 258	1/4	464	469
GW 94 259	1/4	464	469
GW 94 260	1/4	464	469
GW 94 265	1/3	348	469
GW 94 266	1/3	348	469
GW 94 267	1/3	348	469
GW 94 268	1/3	348	469
GW 94 269	1/3	348	469
GW 94 270	1/3	348	469
GW 94 271	1/3	348	469
GW 94 275	1/3	348	469
GW 94 276	1/3	348	469
GW 94 277	1/3	348	469
GW 94 278	1/3	348	469
GW 94 279	1/3	348	469
GW 94 280	1/3	348	469
GW 94 305	1/6	744	471
GW 94 306	1/6	1302	471
GW 94 307	1/6	1302	471
GW 94 308	1/6	744	471
GW 94 309	1/6	744	471
GW 94 310	1/6	1302	471
GW 94 311	1/6	744	471
GW 94 315	1/6	744	471

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 94 316	1/6	744	471
GW 94 317	1/6	744	471
GW 94 318	1/6	744	471
GW 94 319	1/6	744	471
GW 94 320	1/6	744	471
GW 94 325	1/6	744	471
GW 94 326	1/6	744	471
GW 94 327	1/6	1302	471
GW 94 328	1/6	744	471
GW 94 329	1/6	744	471
GW 94 330	1/6	744	471
GW 94 331	1/6	744	471
GW 94 335	1/6	744	471
GW 94 336	1/6	744	471
GW 94 337	1/6	744	471
GW 94 338	1/6	744	471
GW 94 339	1/6	744	471
GW 94 340	1/6	744	471
GW 94 345	1/4	464	471
GW 94 346	1/4	464	471
GW 94 347	1/4	464	471
GW 94 348	1/4	464	471
GW 94 349	1/4	464	471
GW 94 350	1/4	464	471
GW 94 351	1/4	464	471
GW 94 355	1/4	464	471
GW 94 356	1/4	464	471
GW 94 357	1/4	464	471
GW 94 358	1/4	464	471
GW 94 359	1/4	464	471
GW 94 360	1/4	464	471
GW 94 365	1/3	348	471
GW 94 366	1/3	348	471
GW 94 367	1/3	651	471
GW 94 368	1/3	348	471
GW 94 369	1/3	348	471
GW 94 370	1/3	651	471
GW 94 371	1/3	348	471
GW 94 375	1/3	348	471
GW 94 376	1/3	348	471
GW 94 377	1/3	348	471
GW 94 378	1/3	651	471
GW 94 379	1/3	348	471
GW 94 380	1/3	348	471
GW 94 401	1/2	216	481
GW 94 402	1/2	468	481
GW 94 403	1/2	246	481
GW 94 404	1/2	288	481
GW 94 412	1/2	216	481
GW 94 413	1/2	216	481
GW 94 414	1/2	288	481
GW 94 422	1/2	252	481
GW 94 423	1/2	228	481
GW 94 424	1/2	152	481
GW 94 432	1/2	252	481
GW 94 433	1/2	258	481
GW 94 434	1/2	152	481
GW 94 442	1/2	192	481
GW 94 443	1/2	192	481
GW 94 444	1/2	192	481
GW 94 448	1/2	192	481
GW 94 449	1/2	192	481
GW 94 450	1/2	192	481
GW 94 502	1/2	432	481
GW 94 503	1/2	492	481
GW 94 504	1/2	288	481
GW 94 512	1/2	288	481
GW 94 513	1/2	492	481
GW 94 514	1/2	288	481
GW 94 522	1/2	270	481
GW 94 523	1/2	270	481
GW 94 524	1/2	152	481
GW 94 532	1/2	270	481
GW 94 533	1/2	270	481
GW 94 534	1/2	152	481
GW 94 542	1/2	192	481
GW 94 543	1/2	192	481
GW 94 544	1/2	192	481
GW 94 547	1/2	192	481
GW 94 548	1/2	192	481
GW 94 549	1/2	192	481
GW 94 563	1/2	432	482
GW 94 565	1/2	288	482
GW 94 566	1/2	216	482
GW 94 583	1/2	228	482
GW 94 585	1/2	270	482
GW 94 586	1/2	192	482
GW 94 595	1/2	288	482
GW 94 598	1/2	192	482
GW 94 600	1/2	192	482
GW 94 662	1/4	464	485
GW 94 664	1/4	464	485
GW 94 667	1/4	496	485
GW 94 668	1/4	640	485
GW 94 669	1/4	464	485
GW 94 670	1/4	464	485
GW 94 761 K	1/3	348	485
GW 94 766 K	1/3	348	485
GW 94 777 K	1/3	348	485
GW 94 779 K	1/3	348	485
GW 94 867	1/4	464	486
GW 94 869	1/4	640	486
GW 94 885	1/4	464	486
GW 94 897	1/4	868	486
GW 94 898	1/4	640	486
GW 94 899	1/4	464	486
GW 94 900	1/4	464	486
GW 94 957 K	1/3	348	486
GW 94 959 K	1/3	348	486
GW 94 996 K	1/3	279	487

GW 95

Code	Quantity		Page
	Pack/carton	Pallet	
GW 95 025	1/6	744	476
GW 95 025 MA	1/6	744	477
GW 95 026	1/6	744	476
GW 95 026 MA	1/6	744	477
GW 95 027	1/6	744	476
GW 95 027 MA	1/6	744	477
GW 95 028	1/6	744	476
GW 95 028 MA	1/6	744	477
GW 95 029	1/6	744	476
GW 95 029 MA	1/6	744	477
GW 95 030	1/6	744	476
GW 95 030 MA	1/6	744	477
GW 95 031	1/6	744	476
GW 95 031 MA	1/6	744	477
GW 95 035	1/6	744	476
GW 95 036	1/6	744	476
GW 95 037	1/6	744	476
GW 95 038	1/6	744	476
GW 95 039	1/6	744	476
GW 95 040	1/6	744	476
GW 95 105	1/6	744	475
GW 95 106	1/6	744	475
GW 95 107	1/6	1302	475
GW 95 108	1/6	744	475
GW 95 109	1/6	744	475
GW 95 110	1/6	744	475
GW 95 111	1/6	744	475
GW 95 115	1/6	744	475
GW 95 116	1/6	744	475
GW 95 117	1/6	1302	475
GW 95 118	1/6	744	475
GW 95 119	1/6	744	475
GW 95 120	1/6	744	475
GW 95 125	1/6	744	475
GW 95 126	1/6	744	475
GW 95 127	1/6	744	475
GW 95 128	1/6	744	475
GW 95 129	1/6	744	475
GW 95 130	1/6	744	475
GW 95 131	1/6	744	475
GW 95 135	1/6	744	475
GW 95 136	1/6	744	475
GW 95 137	1/6	744	475
GW 95 138	1/6	744	475
GW 95 139	1/6	744	475
GW 95 140	1/6	744	475
GW 95 145	1/4		475
GW 95 146	1/4	464	475
GW 95 147	1/4	464	475
GW 95 148	1/4	496	475
GW 95 149	1/4		475
GW 95 150	1/4	512	475
GW 95 151	1/4		475
GW 95 155	1/4	464	475
GW 95 156	1/4	464	475
GW 95 157	1/4	464	475
GW 95 158	1/4		475
GW 95 159	1/4	624	475
GW 95 160	1/4	464	475
GW 95 165	1/3	651	475
GW 95 166	1/3	348	475
GW 95 167	1/3	651	475
GW 95 168	1/3	372	475

Code	Quantity		Page
	Pack/carton	Pallet	
GW 95 169	1/3	348	475
GW 95 170	1/3	348	475
GW 95 171	1/3	348	475
GW 95 175	1/3	348	475
GW 95 176	1/3	348	475
GW 95 177	1/3	651	475
GW 95 178	1/3	348	475
GW 95 179	1/3	372	475
GW 95 180	1/3	372	475
GW 95 225	1/6	744	477
GW 95 225 MA	1/6	744	478
GW 95 226	1/6	1302	477
GW 95 226 MA	1/6	744	478
GW 95 227	1/6	1302	477
GW 95 227 MA	1/6	744	478
GW 95 228	1/6	744	477
GW 95 228 MA	1/6	744	478
GW 95 229	1/6	744	477
GW 95 229 MA	1/6	744	478
GW 95 230	1/6	744	477
GW 95 230 MA	1/6	744	478
GW 95 231	1/6	744	477
GW 95 231 MA	1/6	744	478
GW 95 235	1/6	744	477
GW 95 236	1/6	744	477
GW 95 237	1/6	744	477
GW 95 238	1/6	744	477
GW 95 239	1/6	744	477
GW 95 240	1/6	744	477
GW 95 245	1/4	464	477
GW 95 246	1/4	464	477
GW 95 247	1/4	464	477
GW 95 248	1/4	464	477
GW 95 249	1/4	464	477
GW 95 250	1/4	464	477
GW 95 325	1/6	744	479
GW 95 326	1/6	744	479
GW 95 327	1/6	1302	479
GW 95 328	1/6	744	479
GW 95 329	1/6	744	479
GW 95 330	1/6	744	479
GW 95 331	1/6	744	479
GW 95 335	1/6		479
GW 95 336	1/6	744	479
GW 95 337	1/6	744	479
GW 95 338	1/6	744	479
GW 95 339	1/6	744	479
GW 95 340	1/6	744	479
GW 95 408	1/2	152	482
GW 95 416	1/2	128	482
GW 95 418	1/2	128	482
GW 95 426	1/2	128	482
GW 95 428	1/2	64	482
GW 95 436	1/2	152	1272
GW 95 438	1/2	152	483
GW 95 446	1/2	128	483
GW 95 448	1/2	128	483
GW 95 456	1/2	128	483

Code	Quantity		Page
	Pack/carton	Pallet	
GW 95 458	1/2	128	483
GW 95 468	1/2	152	483
GW 95 470	1/2	152	483
GW 95 478	1/2	128	483
GW 95 480	1/2	128	483
GW 95 488	1/2	128	483
GW 95 490	1/2	64	483
GW 95 512	1/2	128	483
GW 95 521	1/2	320	489
GW 95 521 N	1/2	312	490
GW 95 522	1/2	320	489
GW 95 522 N	1/2	312	490
GW 95 523	1/2	320	489
GW 95 523 N	1/2	312	490
GW 95 524	1/2	560	489
GW 95 524 N	1/2	312	490
GW 95 525	1/2	320	489
GW 95 525 N	1/2	312	490
GW 95 526	1/2	320	489
GW 95 526 N	1/2	312	490
GW 95 527	117	1170	489
GW 95 527 N	117	540	490
GW 95 604	1	320	1272
GW 95 606	1	320	1272
GW 95 609	1	320	1272
GW 95 631	1	480	485
GW 95 633	1	360	485
GW 95 636	1	480	486
GW 95 638	1	360	486
GW 95 639	1	360	486
GW 95 640	1	480	487
GW 95 696 K	1/3	348	487
GW 95 785	1/6		477
GW 95 786	1/6	744	477
GW 95 787	1/6	744	477
GW 95 788	1/6	744	477
GW 95 789	1/6	744	477
GW 95 790	1/6	744	477
GW 95 791	1/6	744	477
GW 95 795	1/6		479
GW 95 796	1/6	744	479
GW 95 797	1/6	744	479
GW 95 798	1/6	216	479
GW 95 799	1/6		479
GW 95 800	1/6	216	479
GW 95 801	1/6		479
GW 95 805	1/6	744	472
GW 95 806	1/6	744	472
GW 95 807	1/6	744	472
GW 95 808	1/6	744	472
GW 95 809	1/6	744	472
GW 95 810	1/6	744	472
GW 95 811	1/6	744	472
GW 95 815	1/3	348	472
GW 95 816	1/3	348	472
GW 95 817	1/3	348	472
GW 95 818	1/3	348	472
GW 95 819	1/3	348	472

Code	Quantity		Page
	Pack/carton	Pallet	
GW 95 820	1/3	348	472
GW 95 821	1/3	348	472
GW 95 825	1/6	558	478
GW 95 826	1/6	744	478
GW 95 827	1/6	744	478
GW 95 828	1/6	744	478
GW 95 829	1/6	744	478
GW 95 830	1/6	744	478
GW 95 831	1/6	744	478
GW 95 835	1/6	744	480
GW 95 836	1/6	744	480
GW 95 837	1/6	744	480
GW 95 838	1/6	744	480
GW 95 839	1/6	744	480
GW 95 840	1/6	744	480
GW 95 841	1/6	744	480
GW 95 847	1/6	744	473
GW 95 848	1/6	744	473
GW 95 849	1/6	744	473
GW 95 850	1/6	744	473
GW 95 857	1/3	348	473
GW 95 858	1/3	348	473
GW 95 859	1/3	348	473
GW 95 860	1/3	348	473
GW 95 935	1/6	558	474
GW 95 936	1/6	558	474
GW 95 937	1/6	744	474
GW 95 938	1/6	558	474
GW 95 939	1/6	558	474
GW 95 940	1/6	558	474
GW 95 941	1/6	744	474
GW 95 955	1/6	558	479
GW 95 956	1/6	558	479
GW 95 957	1/6	558	479
GW 95 958	1/6	744	479
GW 95 959	1/6	744	479
GW 95 960	1/6	558	479
GW 95 961	1/6	744	479
GW 95 965	1/6		480
GW 95 966	1/6	558	480
GW 95 967	1/6	558	480
GW 95 968	1/6	744	480
GW 95 969	1/6	744	480
GW 95 970	1/6	558	480
GW 95 971	1/6	744	480
GW 95 975	1/6	744	476
GW 95 976	1/6	744	476
GW 95 977	1/6	744	476
GW 95 978	1/6	558	476
GW 95 979	1/6	1302	476
GW 95 980	1/6	744	476
GW 95 981	1/6	744	476

GW 96

Code	Quantity		Page
	Pack/carton	Pallet	
GW 96 001	1/16	1824	501
GW 96 003	1/12	912	503
GW 96 004	1/12	1392	503
GW 96 006	1/16	2160	501
GW 96 008	1	1920	503

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW 96 009	1/16	1216	501
GW 96 011	1/8	1280	502
GW 96 012	1/8	1920	502
GW 96 014	1/6	744	427
GW 96 015	1/12	1152	503
GW 96 016	1/8	1280	502
GW 96 017	1/8	1280	502
GW 96 018	1/8	1280	502
GW 96 022	10/100	16000	502
GW 96 026	10/100	16000	502
GW 96 038	1/10	15600	503
GW 96 041	10/100	16000	505
GW 96 042	10/100	6400	502
GW 96 104	6/24	1488	514
GW 96 105	6/24	1536	514
GW 96 106	6/24	1536	514
GW 96 114	3/12	1152	514
GW 96 115	3/12	1152	514
GW 96 116	3/12	1152	514
GW 96 124	2/8	512	514
GW 96 125	2/8	512	514
GW 96 126	2/8	768	514
GW 96 134	1/3	372	514
GW 96 135	1/3	924	514
GW 96 136	1/3	651	514
GW 96 147	6/24	1536	514
GW 96 148	6/24	1536	514
GW 96 149	6/24	1536	514
GW 96 157	3/12	768	514
GW 96 158	3/12	768	514
GW 96 159	3/12	768	514
GW 96 167	2/8	512	514
GW 96 168	2/8	512	514
GW 96 169	2/8	512	514
GW 96 177	1/3	651	514
GW 96 178	1/3	372	514
GW 96 179	1/3	372	514
GW 96 182	1/6	744	514
GW 96 183	1/6	744	514
GW 96 186	1	336	515
GW 96 186	1	336	539
GW 96 187	1	480	515
GW 96 187	1	480	539
GW 96 192	1/3	279	514
GW 96 193	1/3	279	514
GW 96 194	1/3		514
GW 96 205	12	1404	508
GW 96 206	12	2808	508
GW 96 207	12	768	508
GW 96 215	6	768	508
GW 96 216	6	1404	508
GW 96 217	6	288	508
GW 96 218	2	360	508
GW 96 220	12	3240	508
GW 96 226	12	1404	508
GW 96 226	12	1404	540
GW 96 227	6	1404	508
GW 96 227	6	1404	540

Code	Quantity		Page
	Pack/carton	Pallet	
GW 96 301	6	864	508
GW 96 302	6	1404	508
GW 96 303	6	384	508
GW 96 306	4	512	508
GW 96 307	4	468	508
GW 96 308	4	256	508
GW 96 311	3	320	508
GW 96 312	3	702	508
GW 96 313	3	288	508
GW 96 314	1	192	508
GW 96 321	4	1148	535
GW 96 322	4	640	535
GW 96 323	1	495	535
GW 96 324	1	360	535
GW 96 325	1	480	535
GW 96 331	1/4	464	513
GW 96 331 B	1	336	513
GW 96 332	1	360	513
GW 96 332 B	1	96	513
GW 96 333	1	180	513
GW 96 333 B	1	96	513
GW 96 334	1	180	513
GW 96 334 B	1	72	513
GW 96 335	1	60	513
GW 96 335 B	1	36	513
GW 96 339	1/2	390	525
GW 96 340	1/5	780	525
GW 96 401	12	3168	534
GW 96 402	12	2220	534
GW 96 403	6	1584	534
GW 96 406	12	3168	534
GW 96 407	12	3168	534
GW 96 408	6	1584	534
GW 96 411	4	660	534
GW 96 421	6	1722	534
GW 96 422	6	1722	534
GW 96 423	6	1230	534
GW 96 424	6	1230	534
GW 96 425	6	1230	534
GW 96 426	6	1230	534
GW 96 431	4	656	534
GW 96 432	4	820	534
GW 96 433	4	984	534
GW 96 434	4	820	534
GW 96 441	1	448	532
GW 96 442	1	448	532
GW 96 443	1	384	532
GW 96 444	1	384	532
GW 96 445	1	384	532
GW 96 446	1	660	532
GW 96 447	1	384	532
GW 96 448	1	396	532
GW 96 449	1	384	532
GW 96 450	1	84	532
GW 96 451	1	108	532
GW 96 452	1	72	532
GW 96 453	1	90	532
GW 96 500	25	11000	506

Code	Quantity		Page
	Pack/carton	Pallet	
GW 96 501	25	11000	506
GW 96 503	50	22000	507
GW 96 507 F	1/10	1120	506
GW 96 522	2/8	768	535
GW 96 523	2/8	512	535
GW 96 524	2/8	768	535
GW 96 525	2/8	768	535
GW 96 526	2/8	768	535
GW 96 531	3/12	1392	515
GW 96 532	3/12	1044	515
GW 96 533	3/12	2088	515
GW 96 534	3/12	1440	515
GW 96 535	1/12	1392	515
GW 96 536	1/12	1392	515
GW 96 537	1/12	1392	515
GW 96 538	1/12	1392	515
GW 96 539	3/12	1392	515
GW 96 540	1/12	1044	515
GW 96 541	1/12	1392	515
GW 96 542	1/12	1392	515
GW 96 551	3/12	1392	516
GW 96 552	1/12	1488	516
GW 96 553	3/12	2604	516
GW 96 554	1/12	1392	516
GW 96 555	3/12	1620	516
GW 96 556	1/12	1392	516
GW 96 561	3/12	1044	533
GW 96 562	3/12	1044	533
GW 96 563	1/12	1044	533
GW 96 564	1/12	1044	533
GW 96 565	1/12	1044	533
GW 96 566	1/12	1044	533
GW 96 567	1/12	1044	533
GW 96 568	1/12	1392	533
GW 96 569	1/12	1044	533
GW 96 570	1/12	1044	533
GW 96 571	1/12	1044	533
GW 96 581	3/12	2436	533
GW 96 582	3/12	2604	533
GW 96 583	3/12	1044	533
GW 96 584	3/12	1044	533
GW 96 585	3/12	1044	533
GW 96 586	1/12	1044	533
GW 96 587	1/12	1044	533
GW 96 588	1/12	1044	533
GW 96 589	1/12	1044	533
GW 96 590	1/12	1044	533
GW 96 591	1/12	1044	533
GW 96 592	1/12	2604	533
GW 96 598	1/12	1044	533
GW 96 751	1/4	464	1273
GW 96 752	1/4	464	1273
GW 96 753	1/4	464	1273
GW 96 754	1/4	464	1273
GW 96 755	1/4	464	1273
GW 96 756	1/4	464	1273
GW 96 757	1/4	464	1273
GW 96 758	1/4	464	1273

Code	Quantity		Page
	Pack/carton	Pallet	
GW 96 759	1/4	464	1273
GW 96 760	1/4	464	1273
GW 96 761	1/4	464	1273
GW 96 762	1/4	464	1273
GW 96 763	1/4	464	1273
GW 96 764	1/12	1044	1273
GW 96 765	1/12	1392	1273
GW 96 767	1/6	744	1273
GW 96 769	1/6	744	1274
GW 96 770	1/6	744	1274
GW 96 771	1	64	1274
GW 96 781	1/6	1302	535
GW 96 809	1/8	1680	526
GW 96 814	1/8	1280	526
GW 96 815	1/8	1280	526
GW 96 832	1/4	464	1273
GW 96 851	1/4	464	516
GW 96 852	1/4	464	516
GW 96 853	1/4	348	516
GW 96 856	1/4	348	516
GW 96 867	1/4	640	530
GW 96 872	1/4	1056	530
GW 96 878	1/4	464	530
GW 96 879	1/4	640	530
GW 96 897	1/4	640	532
GW 96 899	1/2	360	532
GW 96 906	1/8	1280	522
GW 96 907	1/8	1280	522
GW 96 908	1/8	1280	522
GW 96 909	1/8	1280	522
GW 96 951	1/4	464	516
GW 96 952	1/4	464	516
GW 96 953	1/4	464	516
GW 96 961	50	3000	507
GW 96 962	50	30000	507
GW 96 963	10	58000	507
GW 96 964	10	58000	507
GW 96 965	10	58000	507
GW 96 966	10	58000	507
GW 96 967	10	8000	507
GW 96 971	1/10	11600	530
GW 96 972	1/10	11600	530
GW 96 973	1/10	11600	530
GW 96 974	1/10	11600	530
GW 96 975	1/10	11600	530
GW 96 976	1/10	11600	530
GW 96 977	1/10	11600	530
GW 96 978	1/10	11600	530
GW 96 979	1/10	11600	530
GW 96 980	1/10	32000	530
GW 96 981	1/10	32000	530
GW 96 984	50	12600	506
GW 96 985	25	5550	506
GW 96 986	25	5250	506
GW 96 987	20	3200	506
GW 96 988	50	3500	506
GW 96 988	50	3500	506
GW 96 989	20	1120	506
GW 96 990	20	1400	506
GW 96 991	15	420	506
GW 96 992	50	7200	506
GW 96 993	25	3600	506
GW 96 994	25	6300	506
GW 96 995	20	4200	506
GW 96 996	50	3150	506
GW 96 997	20	1400	506
GW 96 998	20	1120	506
GW 96 999	15	735	506
GW 97			
GW 97 721	1	228	583
GW 97 722	1	228	583
GW 97 723	1	456	583
GW 97 724	1	228	583
GW 97 725	1	228	583
GW 97 726	1	504	583
GW 97 727	1	224	583
GW 97 728	1	224	583
GW 97 729	1	126	583
GW 97 730	1	126	583
GW 97 731	1	48	584
GW 97 732	1	48	584
GW 97 733	1	48	584
GW 97 734	1	48	584
GW 97 758	1	32	584
GW 97 760	1	32	584
GW 97 761	1	72	584
GW 97 762	1	24	584
GW 97 764	1	24	584
GW 97 767	1	24	584
GW 97 772	1	150	586
GW 97 773	1	117	586
GW 97 774	1	117	585
GW 97 775	1	117	585
GW 98			
GW 98 508	1	960	586
GW 98 509	1	320	586
GW 98 510	1	320	586
GW 98 511	1	320	586
GW 98 512	1	320	586
GW 98 514	1	3900	585
GW 98 515	1	4680	585
GW 98 516	1	1560	585
GW 98 517	1	609	586
GW 98 521	1	1160	585
GW 98 522	1	300	585
GW 98 523	1	1160	585
GW 98 524	1	1160	585
GW 98 525	1	360	585
GW 98 526	1	660	586
GW 98 527	1	660	586
GW 98 528	1	660	586
GW 98 529	1	240	586
GW A1			
GW A1 201	1/12	1536	1126
GW A1 202	1/6	468	1126
GW A1 221	1/12	768	1126
GW A1 222	1/6	468	1126
GW A1 231	1/12	1536	1127
GW A1 232	1/6	468	1127
GW A1 241	1/12	1152	1127
GW A1 242	1/6	468	1127
GW A1 291	1	256	1130
GW A1 501	1/4	640	1131
GW A1 501	1/4	640	1172
GW A1 502	1/4	1280	1131
GW A1 502	1/4	1280	1172
GW A1 511	1/2	192	1131
GW A1 511	1/2	192	1174
GW A1 511 A	1		1131
GW A1 511 A	1		1174
GW A1 512	1/3	396	1132
GW A1 512	1/3	396	1175
GW A1 513	1/4	528	1131
GW A1 513	1/4	528	1174
GW A1 514	1/3	792	819
GW A1 514	1/3	792	853
GW A1 514	1/3	792	887
GW A1 514	1/3	792	921
GW A1 514	1/3	792	955
GW A1 514	1/3	792	1023
GW A1 514	1/3	792	1049
GW A1 514	1/3	792	1132
GW A1 514	1/3	792	1175
GW A1 521	1/4	1280	819
GW A1 521	1/4	1280	853
GW A1 521	1/4	1280	887
GW A1 521	1/4	1280	921
GW A1 521	1/4	1280	955
GW A1 521	1/4	1280	1023
GW A1 521	1/4	1280	1049
GW A1 521	1/4	1280	1133
GW A1 521	1/4	1280	1172
GW A1 522	1/4	800	1133
GW A1 522	1/4	800	1172
GW A1 523	1/4	1280	524
GW A1 523	1/4	1280	1133
GW A1 523	1/4	1280	1172
GW A1 526	1/2	1280	524
GW A1 526	1/2	1280	1134
GW A1 526	1/2	1280	1173
GW A1 531	1/4	800	1133
GW A1 531	1/4	800	1173
GW A1 541	1/4	800	819
GW A1 541	1/4	800	853
GW A1 541	1/4	800	887
GW A1 541	1/4	800	921
GW A1 541	1/4	800	955
GW A1 541	1/4	800	1023
GW A1 541	1/4	800	1049
GW A1 541	1/4	800	1132
GW A1 541	1/4	800	1175
GW A1 700	1/4	624	1141
GW A1 911	1	180	525

Quick Reference

Code	Quantity Pack/carton	Pallet	Page
GW A1 911	1	180	1173
GW A1 912	1	234	525
GW A1 912	1	234	1173
GW A1 916	1/6	540	523
GW A1 916	1/6	540	1134
GW A1 916	1/6	540	1173
GW A1 918	1/4	624	1134
GW A9			
GW A9 000	1	80	1150
GW A9 001	1	120	1150
GW A9 002	1	152	1150
GW A9 007 CB	1/16	64	1150
GW A9 103	1	128	1161
GW A9 108	1	224	1161
GW A9 126	1	90	1162
GW A9 140	1	432	1164
GW A9 141	1	432	1164
GW A9 145	1	810	1165
GW A9 151	1	280	1161
GW A9 181	1		1154
GW A9 301	1	168	1163
GW A9 302	1	168	1163
GW A9 303	1	2304	1163
GW A9 313	1	168	1162
GW A9 321	1		1163
GW A9 322	1		1163
GW A9 326	1	280	1164
GW A9 350	1/48	3072	1163
GW A9 421	1	320	1152
GW A9 531 A	1	384	1159
GW A9 543	1	432	1159
GW A9 545	1	450	1159
GW A9 705	1/8	2184	1152
GW A9 707	1/8	936	1152
GW A9 787	1	10	1169
GW A9 788	1	10	1169
GW A9 789	1	10	1169
GW A9 790	1	10	1169
GW A9 801	1/6	576	1167
GW A9 916	1/6	576	523
GW A9 916	1/6	576	1167
GW D0			
GW D0 951	1/4	280	428
GW D0 971	1/4	168	424
GW D0 976	1/4	280	424
GW D0 978	1/4	280	424
GW D0 991	1/4	280	426
GW D0 996	1/4	280	426
GW D0 998	1/4	280	426
GW D2			
GW D2 005 ①	6/24	2304	443
GW D2 006 ①	6/24	3840	443
GW D2 007 ①	6/24	3840	443
GW D2 008 ①	6/24	3840	443
GW D2 009 ①	6/24	3840	443
GW D2 010 ①	6/24	2304	443
GW D2 011 ①	6/24	2304	443
GW D2 012 ①	6/24	1536	443
GW D2 013 ①	6/24	1536	443
GW D2 014 ①	6/24	1536	443
GW D2 025 ①	3/12	768	443
GW D2 026 ①	3/12	768	443
GW D2 027 ①	3/12	768	443
GW D2 028 ①	3/12	768	443
GW D2 029 ①	3/12	768	443
GW D2 030 ①	3/12	768	443
GW D2 031 ①	3/12	768	443
GW D2 032 ①	3/12	768	443
GW D2 033 ①	3/12	768	443
GW D2 034 ①	3/12	768	443
GW D2 045 ①	3/12	768	443
GW D2 046 ①	3/12	768	443
GW D2 047 ①	3/12	768	443
GW D2 048 ①	3/12	768	443
GW D2 049 ①	3/12	768	443
GW D2 050 ①	3/12	768	443
GW D2 051 ①	3/12	1152	443
GW D2 052 ①	3/12	768	443
GW D2 053 ①	3/12	768	443
GW D2 054 ①	3/12	768	443
GW D2 065 ①	2/8	512	443
GW D2 066 ①	2/8	512	443
GW D2 067 ①	2/8	768	443
GW D2 068 ①	2/8	512	443
GW D2 069 ①	2/8	768	443
GW D2 070 ①	2/8	1280	443
GW D2 071 ①	2/8	768	443
GW D2 072 ①	2/8	768	443
GW D2 073 ①	2/8	1280	443
GW D2 074 ①	2/8	512	443
GW D2 085 ①	1/3	372	443
GW D2 086 ①	1/3	372	443
GW D2 087 ①	1/3	651	443
GW D2 088 ①	1/3	372	443
GW D2 089 ①	1/3	372	443
GW D2 090 ①	1/3	651	443
GW D2 091 ①	1/3	651	443
GW D2 092 ①	1/3	372	443
GW D2 093 ①	1/3	372	443
GW D2 094 ①	1/3	372	443
GW D2 105 ①	6/24	1536	441
GW D2 106 ①	6/24	1536	441
GW D2 107 ①	6/24	2304	441
GW D2 108 ①	6/24	2304	441
GW D2 109 ①	6/24	1536	441
GW D2 110 ①	6/24	1536	441
GW D2 111 ①	6/24	1536	441
GW D2 112 ①	6/24	1536	441
GW D2 113 ①	6/24	1536	441
GW D2 114 ①	6/24	1536	441
GW D2 125 ①	3/12	768	441
GW D2 126 ①	3/12	768	441
GW D2 127 ①	3/12	768	441
GW D2 128 ①	3/12	768	441
GW D2 129 ①	3/12	768	441
GW D2 130 ①	3/12	768	441
GW D2 131 ①	3/12	768	441
GW D2 132 ①	3/12	768	441
GW D2 133 ①	3/12	768	441
GW D2 134 ①	3/12	768	441
GW D2 145 ①	3/12	768	441
GW D2 146 ①	3/12	768	441
GW D2 147 ①	3/12	768	441
GW D2 148 ①	3/12	1920	441
GW D2 149 ①	3/12	1920	441
GW D2 150 ①	3/12	1152	441
GW D2 151 ①	3/12	768	441
GW D2 152 ①	3/12	1152	441
GW D2 153 ①	3/12	768	441
GW D2 154 ①	3/12	768	441
GW D2 165 ①	2/8	512	441
GW D2 166 ①	2/8	512	441
GW D2 167 ①	2/8	512	441
GW D2 168 ①	2/8	512	441
GW D2 169 ①	2/8	512	441
GW D2 170 ①	2/8	512	441
GW D2 171 ①	2/8	768	441
GW D2 172 ①	2/8	512	441
GW D2 173 ①	2/8	512	441
GW D2 174 ①	2/8	512	441
GW D2 185 ①	1/3	372	441
GW D2 186 ①	1/3	372	441
GW D2 187 ①	1/3	372	441
GW D2 188 ①	1/3	651	441
GW D2 189 ①	1/3	651	441
GW D2 190 ①	1/3	651	441
GW D2 191 ①	1/3	651	441
GW D2 192 ①	1/3	651	441
GW D2 193 ①	1/3	372	441
GW D2 194 ①	1/3	372	441
GW D2 205 ①	6/24	2304	444
GW D2 206 ①	6/24	1536	444
GW D2 207 ①	6/24	2304	444
GW D2 208 ①	6/24	1536	444
GW D2 209 ①	6/24	2304	444
GW D2 210 ①	6/24	1536	444
GW D2 211 ①	6/24	1536	444
GW D2 212 ①	6/24	1536	444
GW D2 213 ①	6/24	1536	444
GW D2 214 ①	6/24	1536	444
GW D2 225 ①	3/12		444
GW D2 226 ①	3/12		444
GW D2 227 ①	3/12		444
GW D2 228 ①	3/12		444
GW D2 229 ①	3/12		444
GW D2 230 ①	3/12		444
GW D2 231 ①	3/12		444
GW D2 232 ①	3/12		444
GW D2 233 ①	3/12		444
GW D2 234 ①	3/12		444
GW D2 245 ①	3/12		444
GW D2 246 ①	3/12		444
GW D2 247 ①	3/12		444

Availability: ① December 2025

Code		Quantity		Page
		Pack/carton	Pallet	
GW D2 248	①	3/12		444
GW D2 249	①	3/12		444
GW D2 250	①	3/12		444
GW D2 251	①	3/12		444
GW D2 252	①	3/12		444
GW D2 253	①	3/12		444
GW D2 254	①	3/12		444
GW D2 265	①	2/8		444
GW D2 266	①	2/8	512	444
GW D2 267	①	2/8	512	444
GW D2 268	①	2/8	512	444
GW D2 269	①	2/8	512	444
GW D2 270	①	2/8	512	444
GW D2 271	①	2/8		444
GW D2 272	①	2/8		444
GW D2 273	①	2/8		444
GW D2 274	①	2/8	512	444
GW D2 285	①	1/3		444
GW D2 286	①	1/3		444
GW D2 287	①	1/3		444
GW D2 288	①	1/3		444
GW D2 289	①	1/3		444
GW D2 290	①	1/3		444
GW D2 291	①	1/3		444
GW D2 292	①	1/3		444
GW D2 293	①	1/3		444
GW D2 294	①	1/3		444
GW D2 305	①	6/24	1536	442
GW D2 306	①	6/24	1536	442
GW D2 307	①	6/24	2304	442
GW D2 308	①	6/24	2304	442
GW D2 309	①	6/24	1536	442
GW D2 310	①	6/24	1536	442
GW D2 311	①	6/24	1536	442
GW D2 312	①	6/24	1536	442
GW D2 313	①	6/24	1536	442
GW D2 314	①	6/24	1536	442
GW D2 325	①	3/12	768	442
GW D2 326	①	3/12	768	442
GW D2 327	①	3/12	768	442
GW D2 328	①	3/12	768	442
GW D2 329	①	3/12	768	442
GW D2 330	①	3/12	768	442
GW D2 331	①	3/12	768	442
GW D2 332	①	3/12	768	442
GW D2 333	①	3/12	768	442
GW D2 334	①	3/12	768	442
GW D2 345	①	3/12	768	442
GW D2 346	①	3/12	768	442
GW D2 347	①	3/12	768	442
GW D2 348	①	3/12	768	442
GW D2 349	①	3/12	768	442
GW D2 350	①	3/12	768	442
GW D2 351	①	3/12	768	442
GW D2 352	①	3/12	768	442
GW D2 353	①	3/12	768	442
GW D2 354	①	3/12	768	442
GW D2 365	①	2/8	512	442
GW D2 366	①	2/8	512	442
GW D2 367	①	2/8	512	442
GW D2 368	①	2/8	512	442
GW D2 369	①	2/8	512	442
GW D2 370	①	2/8	512	442
GW D2 371	①	2/8	512	442
GW D2 372	①	2/8	512	442
GW D2 373	①	2/8	512	442
GW D2 374	①	2/8	512	442
GW D2 385	①	1/3	372	442
GW D2 386	①	1/3	372	442
GW D2 387	①	1/3	372	442
GW D2 388	①	1/3	372	442
GW D2 389	①	1/3	372	442
GW D2 390	①	1/3	372	442
GW D2 391	①	1/3	372	442
GW D2 392	①	1/3	372	442
GW D2 393	①	1/3	372	442
GW D2 394	①	1/3	372	442

GW D3

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 001	1	30	619
GW D3 002	1	18	619
GW D3 003	1	15	622
GW D3 004	1	15	619
GW D3 005	1	10	619
GW D3 006	1	15	622
GW D3 007	1	28	619
GW D3 008	1	36	619
GW D3 009	1	42	622
GW D3 010	1	42	622
GW D3 011	1	200	619
GW D3 012	1	68	619
GW D3 013	1	20	619
GW D3 014	1	20	619
GW D3 015	1	21	619
GW D3 016	1	23	619
GW D3 017	1	18	619
GW D3 018	1	18	619
GW D3 019	1	42	622
GW D3 020	1	42	622
GW D3 021	1	16	1275
GW D3 022	1	16	1275
GW D3 023	1	13	1275
GW D3 024	1	14	1275
GW D3 025	1	15	1275
GW D3 026	1	16	1275
GW D3 027	1	13	1275
GW D3 028	1	13	1275
GW D3 029	1	16	1276
GW D3 030	1	16	1276
GW D3 031	1	32	621
GW D3 032	1	20	621
GW D3 033	1	32	621
GW D3 034	1	20	621
GW D3 035	1	200	629
GW D3 041	1	30	1275
GW D3 042	1	18	1275
GW D3 043	1	18	1275
GW D3 044	1	12	1275
GW D3 045	1	25	1275
GW D3 046	1	18	1275
GW D3 047	1	36	620
GW D3 048	1	36	620
GW D3 049	1	36	620
GW D3 050	1	42	622
GW D3 051	1	42	622
GW D3 052	1	45	622
GW D3 053	1	68	620
GW D3 054	1	34	620
GW D3 055	1	54	620
GW D3 056	1	32	620
GW D3 057	1	51	620
GW D3 058	1	34	620
GW D3 059	1	21	620
GW D3 060	1	21	620
GW D3 061	1	21	620
GW D3 062	1	18	620
GW D3 063	1	18	620
GW D3 064	1	18	620
GW D3 065	1	36	622
GW D3 066	1	36	622
GW D3 067	1	36	622
GW D3 068	1	16	1275
GW D3 069	1	16	1275
GW D3 070	1	16	1275
GW D3 071	1	13	1275
GW D3 072	1	13	1275
GW D3 073	1	13	1275
GW D3 074	1	16	1275
GW D3 075	1	16	1275
GW D3 076	1	16	1275
GW D3 077	1	13	1275
GW D3 078	1	13	1275
GW D3 079	1	13	1275
GW D3 080	1	26	1276
GW D3 081	1	26	1276
GW D3 082	1	26	1276
GW D3 083	1	32	621
GW D3 084	1	32	621
GW D3 085	1	32	621
GW D3 086	1	32	621
GW D3 087	1	32	621
GW D3 088	1	32	621
GW D3 089	1	20	620
GW D3 090	1	20	620
GW D3 091	1	20	620
GW D3 101	1	7	639
GW D3 102	1	6	639
GW D3 103	1	6	639
GW D3 104	1	6	639
GW D3 105	1	6	639
GW D3 106	1	6	639
GW D3 107	1	5	639
GW D3 108	1	9	639
GW D3 109	1	5	639
GW D3 110	1	4	639

Availability: ① December 2025

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 111	1	4	639
GW D3 112	1	4	639
GW D3 113	1	24	1277
GW D3 114	1	25	1277
GW D3 115	1	20	1277
GW D3 116	1	20	1277
GW D3 117	1	8	1277
GW D3 118	1	24	1277
GW D3 119	1	25	1277
GW D3 120	1	20	1277
GW D3 121	1	50	650
GW D3 122	1	30	650
GW D3 123	1	30	650
GW D3 124	1	40	650
GW D3 125	1	50	650
GW D3 126	1	50	650
GW D3 131	1	30	1277
GW D3 132	1	18	1277
GW D3 133	1	5	1281
GW D3 134	1	5	1281
GW D3 135	1	18	1278
GW D3 136	1	12	1278
GW D3 137	1	5	1282
GW D3 138	1	5	1282
GW D3 139	1	18	1277
GW D3 140	1	12	1277
GW D3 141	1	5	1281
GW D3 142	1	5	1281
GW D3 143	1	15	1279
GW D3 144	1	18	1279
GW D3 145	1	10	1283
GW D3 146	1	10	1283
GW D3 147	1	28	640
GW D3 148	1	20	640
GW D3 149	1	28	640
GW D3 150	1	18	640
GW D3 152	1	28	640
GW D3 153	1	18	640
GW D3 156	1	27	641
GW D3 158	1	27	641
GW D3 159	1	40	662
GW D3 161	1	27	641
GW D3 162	1	48	662
GW D3 163	1	42	643
GW D3 164	1	42	643
GW D3 165	1	48	664
GW D3 166	1	42	643
GW D3 167	1	42	664
GW D3 168	1	16	660
GW D3 168 R	1	16	660
GW D3 169	1	16	660
GW D3 169 R6	1	24	660
GW D3 170	1	20	641
GW D3 171	1	20	641
GW D3 172	1	20	641
GW D3 173	1	20	641
GW D3 174	1	16	662
GW D3 174 R	1		662

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 175	1	14	641
GW D3 176	1	20	641
GW D3 177	1	16	662
GW D3 177 R6	1	20	662
GW D3 178	1	42	1277
GW D3 179	1	28	1277
GW D3 180	1	42	1277
GW D3 181	1	28	1277
GW D3 182	1	14	1282
GW D3 183	1	42	1277
GW D3 184	1	28	1277
GW D3 185	1	14	1282
GW D3 186	1	13	1282
GW D3 187	1	21	1278
GW D3 188	1	22	1278
GW D3 188	1	22	1282
GW D3 189	1	21	1278
GW D3 189	1	21	1282
GW D3 190	1	18	1278
GW D3 191	1	18	1278
GW D3 191	1	18	1282
GW D3 192	1	17	1278
GW D3 192	1	17	1282
GW D3 193	1	18	1278
GW D3 194	1	18	1278
GW D3 194	1	18	1282
GW D3 195	1	18	1278
GW D3 195	1	18	1282
GW D3 196	1	36	1279
GW D3 197	1	36	1279
GW D3 197	1	36	1283
GW D3 198	1	36	1279
GW D3 198	1	36	1283
GW D3 199	1	17	1279
GW D3 200	1	17	1279
GW D3 201	1	17	1279
GW D3 202	1	13	1279
GW D3 203	1	14	1279
GW D3 204	1	14	1279
GW D3 205	1	16	1279
GW D3 206	1	16	1279
GW D3 206	1	16	1283
GW D3 207	1	16	1279
GW D3 207	1	16	1283
GW D3 208	1	13	1279
GW D3 209	1	13	1279
GW D3 209	1	13	1283
GW D3 210	1	15	1279
GW D3 210	1	15	1283
GW D3 211	1	26	1280
GW D3 212	1	28	1280
GW D3 212	1	28	1284
GW D3 213	1	26	1280
GW D3 213	1	26	1284
GW D3 214	1	16	1278
GW D3 215	1	34	1278
GW D3 215	1	34	1283
GW D3 216	1	32	1278

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 216	1	32	1283
GW D3 217	1	100	650
GW D3 217	1	100	672
GW D3 218	1	20	1278
GW D3 219	1	20	1278
GW D3 220	1	20	1278
GW D3 221	1	10	1282
GW D3 222	1	13	1282
GW D3 223	1	10	1282
GW D3 224	1	225	648
GW D3 224	1	225	670
GW D3 225	1	225	648
GW D3 225	1	225	670
GW D3 226	1	50	648
GW D3 227	1	50	648
GW D3 227	1	50	670
GW D3 228	1	50	648
GW D3 228	1	50	670
GW D3 301	1	180	623
GW D3 301	1	180	644
GW D3 301	1	180	665
GW D3 302	1	200	623
GW D3 302	1	200	644
GW D3 302	1	200	665
GW D3 303	1	50	623
GW D3 303	1	50	644
GW D3 303	1	50	665
GW D3 304	1	120	623
GW D3 304	1	120	644
GW D3 304	1	120	665
GW D3 305	1	150	623
GW D3 305	1	150	644
GW D3 305	1	150	665
GW D3 306	1	60	623
GW D3 306	1	60	644
GW D3 306	1	60	665
GW D3 311	1	700	623
GW D3 311	1	700	644
GW D3 312	1	100	623
GW D3 312	1	100	644
GW D3 313	1	400	623
GW D3 313	1	400	644
GW D3 313	1	400	665
GW D3 314	1	200	623
GW D3 314	1	200	644
GW D3 314	1	200	665
GW D3 316	1	500	1276
GW D3 316	1	500	1280
GW D3 316	1	500	1284
GW D3 317	1	400	183
GW D3 317	1	400	596
GW D3 317	1	400	606
GW D3 317	1	400	627
GW D3 317	1	400	648
GW D3 317	1	400	670
GW D3 318	1	300	627
GW D3 318	1	300	648
GW D3 318	1	300	670

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 321	1	140	625
GW D3 321	1	140	646
GW D3 321	1	140	668
GW D3 322	1	50	625
GW D3 322	1	50	646
GW D3 322	1	50	668
GW D3 323	1	300	625
GW D3 323	1	300	646
GW D3 323	1	300	668
GW D3 324	1	60	625
GW D3 324	1	60	646
GW D3 324	1	60	668
GW D3 325	1	50	625
GW D3 325	1	50	646
GW D3 325	1	50	668
GW D3 326	1	40	625
GW D3 326	1	40	646
GW D3 326	1	40	668
GW D3 327	1	30	625
GW D3 327	1	30	646
GW D3 327	1	30	668
GW D3 328	1	30	625
GW D3 328	1	30	646
GW D3 328	1	30	668
GW D3 329	1	120	625
GW D3 329	1	120	646
GW D3 329	1	120	668
GW D3 330	1	50	625
GW D3 330	1	50	646
GW D3 330	1	50	668
GW D3 331	1	50	625
GW D3 331	1	50	646
GW D3 331	1	50	668
GW D3 332	1	50	625
GW D3 332	1	50	646
GW D3 332	1	50	668
GW D3 333	1	30	625
GW D3 333	1	30	646
GW D3 333	1	30	668
GW D3 334	1	30	625
GW D3 334	1	30	646
GW D3 334	1	30	668
GW D3 336	1	50	626
GW D3 336	1	50	647
GW D3 336	1	50	669
GW D3 337	1	50	626
GW D3 337	1	50	647
GW D3 337	1	50	669
GW D3 338	1	50	626
GW D3 338	1	50	647
GW D3 338	1	50	669
GW D3 339	1	20	626
GW D3 339	1	20	647
GW D3 339	1	20	669
GW D3 340	1	10	626
GW D3 340	1	10	647
GW D3 340	1	10	669
GW D3 341	1	64	626

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 341	1	64	647
GW D3 341	1	64	669
GW D3 342	1	20	626
GW D3 342	1	20	647
GW D3 342	1	20	669
GW D3 343	1	20	626
GW D3 343	1	20	647
GW D3 343	1	20	669
GW D3 344	1	20	626
GW D3 344	1	20	647
GW D3 344	1	20	669
GW D3 345	1	25	626
GW D3 345	1	25	647
GW D3 345	1	25	669
GW D3 346	1	10	647
GW D3 346	1	10	669
GW D3 347	1	10	647
GW D3 347	1	10	669
GW D3 348	1	10	647
GW D3 348	1	10	669
GW D3 349	1	10	647
GW D3 349	1	10	669
GW D3 351	1	50	626
GW D3 352	1	200	626
GW D3 353	1	60	626
GW D3 354	1	60	626
GW D3 355	1	20	626
GW D3 356	1	20	626
GW D3 357	1	200	626
GW D3 358	1	20	626
GW D3 359	1	20	626
GW D3 360	1	20	626
GW D3 361	1	240	626
GW D3 362	1	200	626
GW D3 363	1	120	626
GW D3 364	1	120	626
GW D3 365	1	20	647
GW D3 366	1	20	647
GW D3 367	1	20	647
GW D3 368	1	20	647
GW D3 369	1	200	647
GW D3 370	1	20	647
GW D3 371	1	30	669
GW D3 372	1	30	669
GW D3 374	1	30	669
GW D3 375	1	10	647
GW D3 376	1	24	647
GW D3 377	1	70	647
GW D3 377	1	70	669
GW D3 378	1	24	647
GW D3 378	1	24	669
GW D3 379	1		669
GW D3 380	1		669
GW D3 381	1		669
GW D3 382	1		669
GW D3 383	1		669
GW D3 384	1		669
GW D3 401	1	64	1276

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 402	1	64	1276
GW D3 403	1	32	1276
GW D3 404	1	44	1276
GW D3 405	1	28	1276
GW D3 406	1	72	1276
GW D3 407	1	96	1280
GW D3 408	1	40	1280
GW D3 409	1	32	1280
GW D3 410	1	28	1280
GW D3 411	1	48	1280
GW D3 412	1	48	1280
GW D3 413	1	40	1280
GW D3 414	1	28	1280
GW D3 415	1	48	1284
GW D3 416	1	48	1284
GW D3 417	1	40	1284
GW D3 418	1	50	1284
GW D3 419	1	40	1284
GW D3 420	1	40	1284
GW D3 421	1	40	1284
GW D3 422	1	40	1284
GW D3 426	1	200	628
GW D3 426	1	200	649
GW D3 426	1	200	671
GW D3 428	1	130	628
GW D3 428	1	130	649
GW D3 428	1	130	671
GW D3 431	1	20	1276
GW D3 432	1	50	1276
GW D3 434	1	50	1280
GW D3 435	1	50	1280
GW D3 437	1	500	1281
GW D3 437	1	500	1284
GW D3 438	1	88	1281
GW D3 438	1	88	1284
GW D3 439	1	1170	630
GW D3 439	1	1170	652
GW D3 439	1	1170	674
GW D3 440	1	1170	1276
GW D3 440	1	1170	1281
GW D3 440	1	1170	1285
GW D3 441	1	50	629
GW D3 442	1	50	629
GW D3 443	1	50	651
GW D3 444	1	50	651
GW D3 445	1	400	673
GW D3 451	1	50	652
GW D3 452	1	50	630
GW D3 453	1	50	630
GW D3 453	1	50	652
GW D3 454	1	50	630
GW D3 454	1	50	652
GW D3 454	1	50	674
GW D3 455	1	50	630
GW D3 455	1	50	652
GW D3 455	1	50	674
GW D3 456	1	50	1281
GW D3 456	1	50	1285

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 457	1	50	630
GW D3 457	1	50	652
GW D3 457	1	50	674
GW D3 458	1	50	652
GW D3 461	1	168	673
GW D3 462	1	144	673
GW D3 463	1	132	673
GW D3 464	1	108	673
GW D3 465	1	100	673
GW D3 466	1	120	673
GW D3 467	1	100	651
GW D3 468	1	100	651
GW D3 471	1	300	628
GW D3 471	1	300	649
GW D3 471	1	300	671
GW D3 472	1		671
GW D3 473	1	60	671
GW D3 501	1	80	623
GW D3 501	1	80	644
GW D3 501	1	80	665
GW D3 502	1	56	623
GW D3 502	1	56	644
GW D3 502	1	56	665
GW D3 503	1	80	623
GW D3 503	1	80	644
GW D3 503	1	80	665
GW D3 504	1	80	623
GW D3 504	1	80	644
GW D3 504	1	80	665
GW D3 505	1	60	623
GW D3 505	1	60	644
GW D3 505	1	60	665
GW D3 506	1	24	665
GW D3 507	1	28	665
GW D3 508	1	36	665
GW D3 509	1	50	623
GW D3 509	1	50	644
GW D3 509	1	50	665
GW D3 510	1	50	623
GW D3 510	1	50	644
GW D3 510	1	50	665
GW D3 511	1	60	623
GW D3 511	1	60	644
GW D3 511	1	60	665
GW D3 512	1	50	623
GW D3 512	1	50	644
GW D3 512	1	50	665
GW D3 513	1	40	623
GW D3 513	1	40	644
GW D3 513	1	40	665
GW D3 514	1	18	665
GW D3 515	1	21	665
GW D3 516	1	21	665
GW D3 517	1	60	623
GW D3 517	1	60	644
GW D3 517	1	60	666
GW D3 518	1	48	623
GW D3 518	1	48	644
GW D3 518	1	48	666
GW D3 519	1	26	623
GW D3 519	1	26	644
GW D3 519	1	26	666
GW D3 520	1	12	666
GW D3 521	1	8	666
GW D3 522	1	16	666
GW D3 523	1	60	623
GW D3 523	1	60	644
GW D3 523	1	60	666
GW D3 524	1	40	623
GW D3 524	1	40	644
GW D3 524	1	40	666
GW D3 525	1	30	623
GW D3 525	1	30	644
GW D3 525	1	30	666
GW D3 526	1	10	666
GW D3 527	1	10	666
GW D3 528	1	16	666
GW D3 531	1	64	624
GW D3 531	1	64	645
GW D3 531	1	64	666
GW D3 532	1	64	624
GW D3 532	1	64	645
GW D3 532	1	64	666
GW D3 533	1	64	624
GW D3 533	1	64	645
GW D3 533	1	64	666
GW D3 534	1	64	624
GW D3 534	1	64	645
GW D3 534	1	64	666
GW D3 535	1	64	624
GW D3 535	1	64	645
GW D3 535	1	64	666
GW D3 536	1	48	624
GW D3 536	1	48	645
GW D3 536	1	48	666
GW D3 537	1	16	667
GW D3 538	1	40	667
GW D3 539	1	20	667
GW D3 541	1	64	624
GW D3 541	1	64	645
GW D3 541	1	64	667
GW D3 542	1	64	624
GW D3 542	1	64	645
GW D3 542	1	64	667
GW D3 543	1	64	624
GW D3 543	1	64	645
GW D3 543	1	64	667
GW D3 544	1	48	624
GW D3 544	1	48	645
GW D3 544	1	48	667
GW D3 545	1	52	667
GW D3 546	1	40	667
GW D3 547	1	20	668
GW D3 551	1	40	625
GW D3 551	1	40	646
GW D3 551	1	40	668
GW D3 552	1	40	625
GW D3 552	1	40	646
GW D3 552	1	40	668
GW D3 553	1	40	625
GW D3 553	1	40	646
GW D3 553	1	40	668
GW D3 554	1	30	625
GW D3 554	1	30	646
GW D3 554	1	30	668
GW D3 555	1		623
GW D3 555	1		644
GW D3 555	1		666
GW D3 556	1		623
GW D3 556	1		644
GW D3 556	1		666
GW D3 557	1		624
GW D3 557	1		645
GW D3 557	1		667
GW D3 558	1		624
GW D3 558	1		645
GW D3 558	1		667
GW D3 559	1		624
GW D3 559	1		645
GW D3 559	1		667
GW D3 560	1		667
GW D3 561	1		668
GW D3 562	1		668
GW D3 563	1		667
GW D3 564	1		668
GW D3 565	1		668
GW D3 567	1		668
GW D3 568	1		624
GW D3 568	1		645
GW D3 568	1		666
GW D3 569	1		624
GW D3 569	1		645
GW D3 569	1		666
GW D3 570	1		624
GW D3 570	1		645
GW D3 570	1		666
GW D3 571	1		667
GW D3 572	1		667
GW D3 573	1		667
GW D3 574	1		667
GW D3 575	1		667
GW D3 576	1		667
GW D3 578	1		667
GW D3 605	1	16	621
GW D3 606	1	16	621
GW D3 607	1	13	621
GW D3 608	1	14	621
GW D3 609	1	15	621
GW D3 610	1	16	621
GW D3 611	1	13	621
GW D3 612	1	13	621
GW D3 613	1	16	622
GW D3 614	1	16	622
GW D3 615	1	30	620

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 616	1	18	620
GW D3 617	1	18	620
GW D3 618	1	12	620
GW D3 619	1	30	622
GW D3 620	1	18	622
GW D3 627	1	16	621
GW D3 628	1	16	621
GW D3 629	1	16	621
GW D3 630	1	13	621
GW D3 631	1	13	621
GW D3 632	1	13	621
GW D3 633	1	16	621
GW D3 634	1	16	621
GW D3 635	1	16	621
GW D3 636	1	13	621
GW D3 637	1	13	621
GW D3 638	1	13	621
GW D3 639	1	26	622
GW D3 640	1	26	622
GW D3 641	1	26	622
GW D3 651	1	24	639
GW D3 652	1	25	639
GW D3 653	1	20	639
GW D3 654	1	20	639
GW D3 655	1	8	639
GW D3 656	1	24	639
GW D3 657	1	25	639
GW D3 658	1	20	639
GW D3 659	1	30	640
GW D3 660	1	18	640
GW D3 661	1	5	660
GW D3 662	1	5	660
GW D3 663	1	18	641
GW D3 664	1	12	641
GW D3 665	1	5	662
GW D3 666	1	5	662
GW D3 667	1	18	640
GW D3 668	1	12	640
GW D3 669	1	5	660
GW D3 670	1	5	660
GW D3 671	1	15	643
GW D3 672	1	18	643
GW D3 673	1	10	664
GW D3 674			664
GW D3 675	1	42	640
GW D3 676			640
GW D3 677	1	42	640
GW D3 678			640
GW D3 679	1	14	661
GW D3 680	1	42	640
GW D3 681			640
GW D3 682	1	14	661
GW D3 683	1	13	661
GW D3 684	1	21	640
GW D3 685	1	22	640
GW D3 685	1	22	661
GW D3 686	1	21	640
GW D3 686	1	21	661

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 687	1	18	641
GW D3 688	1	18	641
GW D3 688	1	18	663
GW D3 689	1	17	641
GW D3 689	1	17	663
GW D3 690	1	18	640
GW D3 691	1	18	640
GW D3 691	1	18	661
GW D3 692	1	18	640
GW D3 692	1	18	661
GW D3 693	1	36	643
GW D3 694	1	36	643
GW D3 694	1	36	664
GW D3 695	1	36	643
GW D3 695	1	36	664
GW D3 696	1	17	642
GW D3 697	1	17	642
GW D3 697	1	17	663
GW D3 698	1	17	642
GW D3 698	1	17	663
GW D3 699	1	13	642
GW D3 701	1	80	685
GW D3 702	1	40	685
GW D3 702	1	40	685
GW D3 703	1	40	685
GW D3 704	1	40	685
GW D3 705	1	40	685
GW D3 706	1	40	685
GW D3 707	1	40	685
GW D3 708	1	40	685
GW D3 709	1	40	685
GW D3 711	1		690
GW D3 712	1	100	690
GW D3 713	1	40	690
GW D3 714	1	400	690
GW D3 715	1	40	690
GW D3 721	1	40	685
GW D3 721	1	40	685
GW D3 722	1	40	685
GW D3 722	1	40	685
GW D3 723	1	40	685
GW D3 724	1	40	685
GW D3 725	1	40	685
GW D3 726	1	40	685
GW D3 727	1	40	685
GW D3 728	1	40	685
GW D3 729	1	70	685
GW D3 730	1	90	685
GW D3 731	1	50	685
GW D3 732	1	50	685
GW D3 733	1	20	685
GW D3 734	1	60	685
GW D3 735	1	80	685
GW D3 736	1	60	685
GW D3 737	1	50	685
GW D3 738	1	50	685
GW D3 741	1	70	687
GW D3 742	1	50	687

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 743	1	70	687
GW D3 744	1	50	687
GW D3 745	1	20	686
GW D3 746	1	70	687
GW D3 747	1	20	686
GW D3 747	1	20	687
GW D3 748	1	140	686
GW D3 748	1	140	687
GW D3 749	1	30	686
GW D3 749	1	30	687
GW D3 751	1	40	688
GW D3 752	1	40	688
GW D3 753	1	40	688
GW D3 754	1	40	688
GW D3 754	1	40	688
GW D3 755	1	120	688
GW D3 756	1	50	688
GW D3 757	1	50	688
GW D3 758	1	50	688
GW D3 759	1	200	688
GW D3 760	1	50	688
GW D3 761	1	40	688
GW D3 762	1	40	688
GW D3 763	1	80	688
GW D3 764	1	60	688
GW D3 765	1	108	688
GW D3 766	1	30	688
GW D3 767	1	56	686
GW D3 767	1	56	687
GW D3 767	1	56	688
GW D3 768	1	48	686
GW D3 768	1	48	687
GW D3 768	1	48	688
GW D3 769	1	60	686
GW D3 769	1	60	687
GW D3 769	1	60	688
GW D3 771	1	88	689
GW D3 772	1	88	689
GW D3 773	1	88	689
GW D3 774	1	88	689
GW D3 775	1	40	689
GW D3 776	1	30	690
GW D3 777	1	30	690
GW D3 778	1	30	690
GW D3 779	1	30	690
GW D3 781	1	40	687
GW D3 782	1	60	687
GW D3 783	1	60	687
GW D3 791	1	50	688
GW D3 792	1	50	688
GW D3 793	1	30	688
GW D3 794	1	50	688
GW D3 801	1	14	642
GW D3 801	1	14	663
GW D3 802	1	14	642
GW D3 802	1	14	663
GW D3 803	1	16	642
GW D3 804	1	16	642

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW D3 804	1	16	663
GW D3 805	1	16	642
GW D3 805	1	16	663
GW D3 806	1	13	642
GW D3 807	1	13	642
GW D3 807	1	13	663
GW D3 808	1	15	642
GW D3 808	1	15	663
GW D3 809	1	26	643
GW D3 810	1	28	643
GW D3 810	1	28	664
GW D3 811	1	26	643
GW D3 811	1	26	664
GW D3 812	1	16	642
GW D3 813	1	34	642
GW D3 813	1	34	663
GW D3 814	1	32	642
GW D3 814	1	32	663
GW D3 815	1	20	640
GW D3 816	1	20	640
GW D3 817	1	20	640
GW D3 818	1	10	661
GW D3 819	1	13	661
GW D3 820	1	10	661
GW D3 821	1	500	627
GW D3 821	1	500	648
GW D3 821	1	500	670
GW D3 822	1	64	628
GW D3 823	1	64	628
GW D3 824	1	32	628
GW D3 825	1	44	628
GW D3 826	1	28	628
GW D3 827	1	72	628
GW D3 828	1	96	650
GW D3 829	1	40	650
GW D3 830	1	32	650
GW D3 831	1	28	650
GW D3 832	1	48	650
GW D3 833	1	48	650
GW D3 834	1	40	650
GW D3 835	1	28	650
GW D3 836	1	48	672
GW D3 837	1	48	672
GW D3 838	1	40	672
GW D3 839	1	50	672
GW D3 840	1	40	672
GW D3 841	1	40	672
GW D3 842	1	40	672
GW D3 843	1	40	672
GW D3 844	1	20	630
GW D3 845	1	50	630
GW D3 847	1	50	651
GW D3 848	1	50	651
GW D3 850	1	500	651
GW D3 850	1	500	674
GW D3 851	1	88	651
GW D3 851	1	88	674
GW D3 852	1/10	1170	630
GW D3 852	1/10	1170	652
GW D3 852	1/10	1170	674
GW D3 853	1	50	652
GW D3 853	1	50	674

GW D4

Code	Quantity		Page
	Pack/carton	Pallet	
GW D4 001	1/6	744	485
GW D4 002	1/6	1302	485
GW D4 003	1/6	744	485
GW D4 004	1/6	744	485
GW D4 011	1/6	744	486
GW D4 012	1/6	1302	486
GW D4 012 MA	1/6	744	486
GW D4 013	1/6	744	486
GW D4 014	1/6	744	486
GW D4 022	1/6	1302	485
GW D4 023	1/6	744	485
GW D4 024	1/6	744	485
GW D4 025	1/6	744	485
GW D4 032	1/6	1302	486
GW D4 032 MA	1/6		486
GW D4 033	1/6	744	486
GW D4 034	1/6	744	486
GW D4 035	1/6	744	486
GW D4 042	1/6	1302	485
GW D4 043	1/6	744	485
GW D4 044	1/6	744	485
GW D4 045	1/6	744	485
GW D4 052	1/6	1302	486
GW D4 052 MA	1/6		486
GW D4 053	1/6	744	486
GW D4 054	1/6	744	486
GW D4 055	1/6	744	486
GW D4 062	1/6	744	485
GW D4 072	1/6	744	486
GW D4 102	1/3	651	485
GW D4 103	1/3	348	485
GW D4 104	1/3	348	485
GW D4 111	1/3	348	486
GW D4 112	1/3	651	486
GW D4 113	1/3	348	486
GW D4 114	1/3	372	486
GW D4 122	1/3	651	485
GW D4 123	1/3	372	485
GW D4 124	1/3	651	485
GW D4 125	1/3	372	485
GW D4 132	1/3	651	486
GW D4 133	1/3	261	486
GW D4 134	1/3	651	486
GW D4 135	1/3	348	486
GW D4 142	1/3	651	485
GW D4 143	1/3	348	485
GW D4 144	1/3	372	485
GW D4 145	1/3	348	485
GW D4 152	1/3	651	486
GW D4 153	1/3	348	486
GW D4 154	1/3	651	486
GW D4 155	1/3	372	486
GW D4 202	1/6	744	487
GW D4 203	1/6	744	487
GW D4 205	1/6	1302	487
GW D4 206	1/6	744	487
GW D4 208	1/6	744	487
GW D4 209	1/6	744	487
GW D4 217	1/3	372	487
GW D4 218	1/3	348	487
GW D4 220	1/3	651	487
GW D4 221	1/3	348	487
GW D4 223	1/3	372	487
GW D4 224	1/3	348	487
GW D4 227 P	1/4	168	425
GW D4 227 R	1/4	280	425
GW D4 229 P	1/4	168	425
GW D4 229 R	1/4	280	425
GW D4 234	1/6	744	487
GW D4 235	1/6	744	487
GW D4 237	1/6	744	487
GW D4 238	1/6	744	487
GW D4 249	1/3	372	487
GW D4 250	1/3	348	487
GW D4 252	1/3	372	487
GW D4 253	1/3	348	487
GW D4 261	1/6	696	488
GW D4 265	1/6	696	488
GW D4 269	1/6	696	488
GW D4 281	1/3	348	488
GW D4 285	1/3	348	488
GW D4 289	1/3	348	488
GW D4 302	1/3	372	485
GW D4 304	1/3	372	485
GW D4 307	1/3	348	488
GW D4 312	1/3	348	486
GW D4 314	1/3	348	486
GW D4 317	1/3	351	487
GW D4 322	1/3	651	485
GW D4 324	1/3	348	485
GW D4 327	1/3	348	488
GW D4 332	1/3	651	486
GW D4 334	1/3	348	486
GW D4 337	1/3		487
GW D4 342	1/3	651	485
GW D4 344	1/3	348	485
GW D4 347	1/3	36	488
GW D4 352	1/3	372	486
GW D4 354	1/3	348	486
GW D4 357	1/3	348	487
GW D4 427	1/3	651	484
GW D4 429	1/3	651	484
GW D4 431	1/3	651	484
GW D4 433	1/3	651	484
GW D4 435	1/3	651	484
GW D4 437	1/3	372	484
GW D4 439	1/3	348	484
GW D4 441	1/3	372	484
GW D4 443	1/3	609	484
GW D4 445	1/3	372	484
GW D4 447	1/3	348	484

Code	Quantity		Page
	Pack/carton	Pallet	
GW D4 449	1/3	348	484
GW D4 502	1/3	372	488
GW D4 504	1/3	372	488
GW D4 507	1/3	372	488
GW D4 509	1/3	279	488
GW D4 512	1/3	372	488
GW D4 514	1/3	279	488
GW D4 527	1/3	372	488
GW D4 529	1/3	279	488
GW D4 532	1/3	651	488
GW D4 534	1/3	279	488
GW D4 537	1/3	372	488
GW D4 539	1/3	279	488
GW D4 617	1/6	1302	484
GW D4 627	1/6	1302	484
GW D4 817	1/6	1302	484
GW D4 817 P	1/4	280	423
GW D4 817 R	1/4	280	423
GW D4 827	1/6	1302	484
GW D4 827 P	1/4	280	423
GW D4 827 R	1/4	280	423

GW D6

Code	Quantity		Page
	Pack/carton	Pallet	
GW D6 002	1/16	928	503
GW D6 002	1/16	928	504
GW D6 007	1/16	928	503
GW D6 010	1/16	928	503
GW D6 013	1/8	928	503
GW D6 013	1/8	928	504
GW D6 015	1/8	1536	503
GW D6 015	1/8	1536	504
GW D6 019	1/8	1280	504
GW D6 020	1/8	768	504
GW D6 021	1/8	512	504
GW D6 026	1/50	6000	503
GW D6 026	1/50	6000	504
GW D6 027	1/10	1200	503
GW D6 027	1/10	1200	504
GW D6 401	1	744	511
GW D6 402	1	348	511
GW D6 404	1	348	511
GW D6 405	1	96	511
GW D6 407	1	744	511
GW D6 409	1	651	511
GW D6 411	1	1044	511
GW D6 412	1	1044	511
GW D6 413	1	1044	511
GW D6 417	1	744	511
GW D6 418	1	744	511
GW D6 419	1	651	511
GW D6 420	1	348	511
GW D6 426	1	480	511
GW D6 426	1	480	539
GW D6 428	1	496	511
GW D6 428	1	496	539
GW D6 429	1/4	496	511
GW D6 429	1/4	496	539
GW D6 430	1	1392	511
GW D6 433	1	1392	512
GW D6 434	1	696	512
GW D6 435	1	696	512
GW D6 436	1	756	512
GW D6 438	1	756	512
GW D6 441	1	696	512
GW D6 442	1	696	512
GW D6 443	1	420	512
GW D6 446	1	696	512
GW D6 446	1	696	540
GW D6 448	1	60	512
GW D6 448	1	60	540
GW D6 449	1	936	512
GW D6 449	1	936	540
GW D6 451	1	696	512
GW D6 452	1	696	512
GW D6 453	1	696	512
GW D6 461	1/6		512
GW D6 501	1		509
GW D6 502	1		509
GW D6 503	1		509
GW D6 504	1		509
GW D6 505	1		509
GW D6 506	1		509
GW D6 507	1		509
GW D6 508	1		509
GW D6 509	1		509
GW D6 510	1		509
GW D6 511	1		509
GW D6 512	1		509
GW D6 513	1		509
GW D6 514	1		509
GW D6 515	1		509
GW D6 516	1		510
GW D6 517	1	900	510
GW D6 518	1	900	510
GW D6 519	1	900	510
GW D6 520	1	900	510
GW D6 601	6/24	1920	518
GW D6 602	6/24	1920	518
GW D6 603	6/24	1920	518
GW D6 604	6/24	1920	518
GW D6 606	6/24	1920	518
GW D6 608	6/24	1920	518
GW D6 610	6/24	1920	518
GW D6 611	6/24	1920	518
GW D6 617	6/24	1920	518
GW D6 618	6/24	1920	518
GW D6 619	6/24	1920	518
GW D6 624	6/24	1920	518
GW D6 626	3/12	960	518
GW D6 627	3/12	960	518
GW D6 629	3/12	960	518
GW D6 630	3/12	960	518
GW D6 632	3/12	960	518
GW D6 633	3/12	960	518
GW D6 634	3/12	960	518
GW D6 641	6/24	1536	520
GW D6 642	6/24	1536	520
GW D6 643	6/24	1536	520
GW D6 644	6/24	2880	520
GW D6 646	6/24	1536	520
GW D6 647	6/24	1536	520
GW D6 648	6/24	1536	520
GW D6 649	6/24	1536	520
GW D6 650	6/24	1536	520
GW D6 652	6/24	1536	520
GW D6 653	6/24	1536	520
GW D6 654	6/24	1920	520
GW D6 657	6/24	1536	520
GW D6 658	6/24	1536	520
GW D6 659	6/24	1920	520
GW D6 663	3/12	768	520
GW D6 664	3/12	768	520
GW D6 667	3/12	768	520
GW D6 668	3/12	768	520
GW D6 669	3/12	768	520
GW D6 671	1/20	1280	521
GW D6 672	1/20	1600	521
GW D6 676	1/20	1600	521
GW D6 677	1/20	1600	521
GW D6 678	1/20	1600	521
GW D6 701	6/24	1920	517
GW D6 702	6/24	1920	517
GW D6 703	6/24	2800	517
GW D6 705	6/24	1920	517
GW D6 706	6/24	1920	517
GW D6 707	6/24	1920	517
GW D6 708	3/12	960	517
GW D6 709	3/12	480	517
GW D6 711	3/12	960	517
GW D6 712	3/12	1440	517
GW D6 713	3/12	960	517
GW D6 714	3/12	960	517
GW D6 715	3/12	1920	517
GW D6 716	3/12	960	517
GW D6 717	3/12	960	517
GW D6 718	3/12	960	517
GW D6 721	2/8	1600	517
GW D6 722	2/8	640	517
GW D6 723	2/8	640	517
GW D6 724	2/8	1280	517
GW D6 725	2/8	640	517
GW D6 726	2/8	768	517
GW D6 731	2/8	640	517
GW D6 732	2/8	640	517
GW D6 733	2/8	640	517
GW D6 734	2/8	1280	517
GW D6 735	2/8	640	517
GW D6 736	2/8	640	517
GW D6 741	6/24	1920	517
GW D6 742	6/24	2880	517
GW D6 743	6/24	1920	517
GW D6 744	6/24	1920	517
GW D6 751	3/12	960	517
GW D6 752	3/12	960	517
GW D6 753	3/12	960	517

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW D6 754	3/12	960	517
GW D6 755	3/12	960	517
GW D6 761	1/12	2592	519
GW D6 762	1/12	960	519
GW D6 763	1/10	1920	519
GW D6 764	1/10	960	519
GW D6 765	1/10	6400	519
GW D6 766	12	3276	505
GW D6 766	12	3276	519
GW D6 766	12	3276	521
GW D6 771	1/12	1488	527
GW D6 772	1/12	1488	527
GW D6 773	1/6	744	527
GW D6 776	1/4	496	527
GW D6 779	1/3	496	528
GW D6 780	1/4	496	528
GW D6 781	1/6	744	528
GW D6 782	1/3	372	528
GW D6 783	1/3	372	528
GW D6 785	1/4	496	529
GW D6 786	1/3	651	529
GW D6 788	1/3	186	529
GW D6 789	1/3	186	529
GW D6 801	1/5	580	531
GW D6 801	1/5	580	1168
GW D6 802	1/5	800	531
GW D6 802	1/5	800	1168
GW D6 803	1/5	800	531
GW D6 804	1/2	320	531
GW D6 805	1/2	320	531
GW D6 807	1/2	80	531
GW D6 807	1/2	80	1168
GW D6 809	1/2	80	531
GW D6 809	1/2	80	1168
GW D6 809	1/2	80	1222
GW D6 809	1/2	80	1230
GW D6 812	1/6	744	1290
GW D6 817	1/6	234	1290
GW D6 820	1/5	800	531
GW D6 821	1/5	800	531
GW D6 821	1/5	800	1222
GW D6 821	1/5	800	1230
GW D6 911	1/6	744	532
GW D6 916	1/6	540	523

GW D8

Code	Quantity		Page
	Pack/carton	Pallet	
GW D8 501	1		571
GW D8 502	1		571
GW D8 503	1		571
GW D8 504	1		571
GW D8 505	1	100	571
GW D8 510	1		571
GW D8 512	1		571
GW D8 513	1		571
GW D8 514	1		571
GW D8 519	1		571
GW D8 520	1		571
GW D8 522	1		571
GW D8 527	1	100	571
GW D8 528	1	100	571
GW D8 529	1	2000	571
GW D8 542	1		572
GW D8 544	1	372	572
GW D8 545	1		572
GW D8 546	1		572
GW D8 548	1	372	572
GW D8 552	1		572
GW D8 553	1		572
GW D8 554	1		572
GW D8 555	1	372	572
GW D8 557	1		572
GW D8 558	1	360	572
GW D8 564	1	2000	572
GW D8 565	1	100	572
GW D8 566	1	100	572
GW D8 567	1	100	572
GW D8 568	1		572
GW D8 569	1	100	572
GW D8 571	1	100	572
GW D8 572	1	100	572
GW D8 573	1	100	572
GW D8 581	1	48	572
GW D8 582	1	48	572
GW D8 584	1	96	572
GW D8 585	1	88	572
GW D8 590	1	48	572
GW D8 591	1	48	572
GW D8 595	1	36	572
GW D8 596	1	58	572
GW D8 598	1	26	572
GW D8 599	1	8	572
GW D8 602	1	20	572
GW D8 603	1	30	572
GW D8 618	1	120	573
GW D8 619	1	120	573
GW D8 620	1	87	573
GW D8 621	1	87	573
GW D8 622	1	24	573
GW D8 623	1	24	573
GW D8 624	1	20	573
GW D8 625	1	87	573
GW D8 626	1	87	573
GW D8 627	1	87	573
GW D8 628	1	100	573
GW D8 629	1	87	573
GW D8 630	1	87	573
GW D8 631	1	87	573
GW D8 632	1	87	573
GW D8 633	1	87	573
GW D8 634	1	24	573
GW D8 635	1	24	573
GW D8 636	1	24	573
GW D8 637	1	24	573
GW D8 641	1	87	574
GW D8 643	1	87	574
GW D8 644	1	87	574
GW D8 646	1	87	574
GW D8 647	1	87	574
GW D8 649	1	87	574
GW D8 650	1	87	574
GW D8 652	1	87	574
GW D8 653	1	360	574
GW D8 655	1	180	574
GW D8 661	1	224	574
GW D8 662	1	930	574
GW D8 663	1	840	574
GW D8 664	1		574
GW D8 665	1		574
GW D8 666	1	600	574
GW D8 668	1	600	574
GW D8 671	1		575
GW D8 672	1		575
GW D8 673	1		575
GW D8 674	1	87	575
GW D8 681	1	72	575
GW D8 682	1	66	575
GW D8 683	1	66	575
GW D8 684	1	66	575
GW D8 685	1	12	575
GW D8 686	1	12	575
GW D8 687	1	6	575
GW D8 688	1	100	575
GW D8 691	1	96	575
GW D8 692	1	96	575
GW D8 693	1	96	575
GW D8 694	1	108	575
GW D8 695	1	66	575
GW D8 696	1	66	575
GW D8 697	1	66	575
GW D8 698	1	66	575
GW D8 699	1	66	575
GW D8 700	1	66	575
GW D8 701	1	66	575
GW D8 702	1		575
GW D8 711	1		576
GW D8 712	1		576
GW D8 713	1		576
GW D8 714	1		576
GW D8 715	1		576
GW D8 716	1		576
GW D8 717	1		576
GW D8 718	1	20	576
GW D8 719	1	744	576
GW D8 720	1	372	576
GW D8 721	1		576
GW D8 722	1		576
GW D8 723	1		576
GW D8 724	1		576
GW D8 725	1		576
GW D8 726	1	50	576
GW D8 731	1		576
GW D8 733	1		576
GW D8 734	1		576
GW D8 735	1		576
GW D8 736	1	100	576

Code	Quantity		Page
	Pack/carton	Pallet	
GW D8 741	1		577
GW D8 742	1		577
GW D8 743	1		577
GW D8 744	1		577
GW D8 745	1		577
GW D8 746	1		577
GW D8 747	1		577
GW D8 748	1		577
GW D8 749	1		577
GW D8 750	1		577
GW D8 751	1		577
GW D8 752	1		577
GW D8 754	1	100	577
GW D8 756	1	100	577
GW D8 761	1		577
GW D8 762	1		577
GW D8 763	1		577
GW D8 764	1		577
GW D8 765	1		577
GW D8 766	1		577
GW D8 767	1		577
GW D8 768	1		577
GW D8 771	1		578
GW D8 772	1		578
GW D8 783	1		578
GW D8 784	1		578
GW D8 785	1		578
GW D8 786	1		578
GW D8 787	1		578
GW D8 788	1		578
GW D8 789	1		578
GW D8 790	1		578
GW D8 791	1		578
GW D8 792	1		578
GW D8 793	1		578
GW D8 794	1		578
GW D8 795	1		578
GW D8 796	1		578
GW D8 797	1	100	578
GW D8 798	1		578
GW D8 799	1	100	578
GW D8 800	1	248	578
GW D8 811	1		579
GW D8 812	1		579
GW D8 813	1		579
GW D8 814	1		579
GW D8 815	1		579
GW D8 816	1		579
GW D8 817	1		579
GW D8 818	1		579
GW D8 819	1		579
GW D8 820	1		579
GW D8 821	1		579
GW D8 822	1		579
GW D8 823	1		579
GW D8 824	1		579
GW D8 825	1	120	579
GW D8 826	1		579
GW D8 827	1		579
GW D8 828	1		579
GW D8 829	1		579
GW D8 830	1		579
GW D8 831	1		579
GW D8 832	1	336	579
GW D8 835	1		579
GW D8 836	1		579
GW D8 837	1		579
GW D8 838	1		579
GW D8 839	1		579
GW D8 840	1	100	579
GW D8 841	1		579
GW D8 842	1	936	579
GW D8 843	1		579
GW D8 844	1		579
GW D8 845	1	100	579
GW D8 846	1	50	579
GW D8 847	1	100	579
GW D8 848	1	100	579
GW D8 849	1	100	579
GW D8 850	1	50	579
GW D8 862	1		579
GW D8 863	1		579
GW D8 869	1		580
GW D8 870	1		580
GW D8 871	1	200	580
GW D8 872	1		580
GW D8 873	1		580
GW D8 874	1		580
GW D8 875	1		580
GW D8 876	1	840	580
GW D8 886	1	30	580
GW D8 887	1	30	580

GW D9

Code	Quantity		Page
	Pack/carton	Pallet	
GW D9 001	1	120	553
GW D9 002	1	120	553
GW D9 003	1	120	553
GW D9 004	1	120	553
GW D9 005	1	120	553
GW D9 011	1	120	553
GW D9 012	1	120	553
GW D9 013	1	120	553
GW D9 014	1	120	553
GW D9 015	1	120	553
GW D9 026	1	120	553
GW D9 027	1	120	553
GW D9 036	1	120	553
GW D9 037	1	120	553
GW D9 041	1	120	554
GW D9 042	1	120	554
GW D9 043	1	120	554
GW D9 044	1	120	554
GW D9 045	1	120	554
GW D9 051	1	96	554
GW D9 052	1	120	554
GW D9 053	1	120	554
GW D9 054	1	120	554
GW D9 055	1	120	554
GW D9 066	1	120	554
GW D9 067	1	120	554
GW D9 076	1	120	554
GW D9 077	1	120	554
GW D9 087	1	96	555
GW D9 088	1	96	555
GW D9 097	1	96	555
GW D9 098	1	84	555
GW D9 107	1	96	555
GW D9 108	1	96	555
GW D9 117	1	96	555
GW D9 118	1	96	555
GW D9 121	1	120	556
GW D9 122	1	212	556
GW D9 123	1	212	556
GW D9 124	1	212	556
GW D9 125	1	96	556
GW D9 126	1	96	556
GW D9 127	1	96	558
GW D9 128	1	96	559
GW D9 131	1		556
GW D9 132	1		556
GW D9 133	1		556
GW D9 134	1		556
GW D9 135	1		556
GW D9 136	1		556
GW D9 137	1		558
GW D9 138	1	96	559
GW D9 141	1	48	556
GW D9 142	1	120	556
GW D9 143	1	96	556
GW D9 144	1	96	556
GW D9 145	1	96	556
GW D9 146	1	96	556
GW D9 147	1	96	558
GW D9 148	1	60	559
GW D9 151	1		557
GW D9 152	1	165	557
GW D9 153	1	165	557
GW D9 154	1	165	557
GW D9 155	1	165	557
GW D9 156	1	165	557
GW D9 157	1	165	558
GW D9 158	1	165	559
GW D9 161	1	96	557
GW D9 162	1		557
GW D9 163	1		557
GW D9 164	1		557
GW D9 165	1		557
GW D9 166	1		557
GW D9 167	1		558
GW D9 168	1	84	559
GW D9 171	1	93	557
GW D9 172	1	84	557
GW D9 173	1	84	557
GW D9 174	1	84	557
GW D9 175	1	84	557

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW D9 176	1	84	557
GW D9 177	1	84	558
GW D9 178	1		559
GW D9 195	1	96	556
GW D9 196	1	96	556
GW D9 197	1	96	558
GW D9 198	1	60	559
GW D9 201	1	120	556
GW D9 202	1	160	556
GW D9 204	1	96	556
GW D9 205	1	87	556
GW D9 206	1	32	556
GW D9 207	1	120	558
GW D9 208	1	120	559
GW D9 211	1	150	556
GW D9 212	1	56	556
GW D9 214	1	150	556
GW D9 215	1	84	556
GW D9 216	1	54	556
GW D9 217	1	84	558
GW D9 218	1	120	559
GW D9 241	1		561
GW D9 242	1		561
GW D9 243	1		561
GW D9 244	1		561
GW D9 245	1		561
GW D9 246	1		561
GW D9 247	1		562
GW D9 248	1		562
GW D9 261	1		561
GW D9 262	1		561
GW D9 263	1		561
GW D9 264	1		561
GW D9 265	1		561
GW D9 266	1		561
GW D9 267	1		562
GW D9 268	1	117	562
GW D9 277	1	90	562
GW D9 278	1	96	562
GW D9 302	1		563
GW D9 306	1	96	563
GW D9 307	1	96	563
GW D9 308	1	96	564
GW D9 312	1	96	563
GW D9 316	1	96	563
GW D9 317	1	96	563
GW D9 318	1	96	564
GW D9 322	1	56	563
GW D9 326	1	96	563
GW D9 327	1	64	563
GW D9 328	1	96	564
GW D9 329	1	26	565
GW D9 332	1		563
GW D9 336	1	165	563
GW D9 337	1	165	563
GW D9 338	1	165	564
GW D9 342	1	32	563
GW D9 346	1	84	563

Code	Quantity		Page
	Pack/carton	Pallet	
GW D9 347	1	84	563
GW D9 348	1	84	564
GW D9 352	1		563
GW D9 356	1	84	563
GW D9 357	1	84	563
GW D9 358	1	84	564
GW D9 359	1	26	565
GW D9 361	1	32	560
GW D9 362	1	26	560
GW D9 363	1	26	560
GW D9 365	1	32	560
GW D9 366	1	26	560
GW D9 367	1	14	560
GW D9 368	1	14	560
GW D9 370	1	26	560
GW D9 371	1	32	565
GW D9 372	1	26	565
GW D9 373	1	26	565
GW D9 374	1	26	565
GW D9 375	1	32	565
GW D9 376	1	26	565
GW D9 377	1	26	565
GW D9 378	1	13	565
GW D9 381	1	32	566
GW D9 382	1	32	566
GW D9 383	1	39	566
GW D9 384	1	20	566
GW D9 385	1	32	566
GW D9 386	1	26	566
GW D9 387	1	26	566
GW D9 388	1	13	566
GW D9 389	1	12	565
GW D9 401	1	4	567
GW D9 402	1	10	567
GW D9 403	1	8	567
GW D9 404	1	8	567
GW D9 406	1	4	567
GW D9 407	1		567
GW D9 408	1	4	567
GW D9 409	1	8	567
GW D9 411	1	4	568
GW D9 411 B	1		568
GW D9 412	1	4	568
GW D9 412 B	1		568
GW D9 415	1	4	568
GW D9 415 B	1	10	568
GW D9 416	1	4	568
GW D9 416 B	1	4	568
GW D9 417	1	2	568
GW D9 417 B	1		568
GW D9 418	1	4	568
GW D9 418 B	1	4	568
GW D9 421	1	4	568
GW D9 421 B	1		568
GW D9 422	1	4	568
GW D9 422 B	1		568
GW D9 425	1	4	568
GW D9 425 B	1	10	568

Code	Quantity		Page
	Pack/carton	Pallet	
GW D9 426	1	4	568
GW D9 426 B	1	6	568
GW D9 427	1	4	568
GW D9 427 B	1		568
GW D9 428	1	4	568
GW D9 428 B	1	4	568
GW D9 441	1	120	569
GW D9 442	1	120	569
GW D9 443	1	96	569
GW D9 444	1	96	569
GW D9 445	1	32	569
GW D9 446	1	26	569
GW D9 447	1	32	570
GW D9 448	1	26	570
GW D9 449	1	4	570
GW D9 450	1	4	570
GW D9 451	1	4	570
GW D9 452	1	4	570
GW D9 453	1	4	570
GW D9 453 B	1		570
GW D9 454	1	4	570
GW D9 454 B	1	5	570
GW D9 455	1	4	570
GW D9 455 B	1		570
GW D9 456	1	4	570
GW D9 456 B	1		570
GW D9 457	1	4	570
GW D9 457 B	1		570
GW D9 458	1	4	570
GW D9 458 B	1		570
GW D9 459	1		570
GW D9 459 B	1		570
GW D9 460	1	4	570
GW D9 460 B	1		570
GW D9 502	1		563
GW D9 506	1		563
GW D9 507	1	72	563
GW D9 508	1	72	564
GW D9 522	1		563
GW D9 526	1		563
GW D9 527	1	60	563
GW D9 528	1	60	564
GW D9 531	1	14	565
GW D9 533	1	26	565
GW D9 534	1		565
GW D9 535	1	14	566
GW D9 537	1	26	566
GW D9 538	1		566
GW D9 551	1	120	561
GW D9 552	1	120	561
GW D9 553	1	96	561
GW D9 554	1	120	561
GW D9 555	1	96	561
GW D9 556	1	96	561
GW D9 557	1	96	562
GW D9 558	1	96	562
GW D9 561	1		567
GW D9 563	1	4	567

Code	Quantity		Page
	Pack/carton	Pallet	
GW D9 564	1		567
GW D9 565	1		567
GW D9 567	1	4	567
GW D9 568	1		567
GW D9 571	1	120	561
GW D9 572	1	96	561
GW D9 573	1	120	561
GW D9 574	1	120	561
GW D9 575	1	120	561
GW D9 576	1	120	561
GW D9 581	1		568
GW D9 583	1	4	568
GW D9 584	1		568
GW D9 585	1		568
GW D9 587	1	4	568
GW D9 588	1		568
GW D9 901	1	28	539
GW D9 902	1	20	1274
GW D9 903	1	20	1274
GW D9 906	1	28	539
GW D9 907	1	20	1274
GW D9 908	1	20	1274
GW J1			
GW J1 001 A	1	4	1290
GW J1 001 L	1	4	1291
GW J1 001 R	1	4	1290
GW J1 001 W	1	4	1291
GW J1 002 A	1	4	1290
GW J1 002 L	1	4	1291
GW J1 002 R	1	4	1290
GW J1 002 W	1	4	1291
GW J1 003 A	1	4	1290
GW J1 003 L	1	4	1291
GW J1 003 R	1	4	1290
GW J1 003 W	1	4	1291
GW J1 402 T	1		1226
GW J1 404 T	1	4	1226
GW J1 412 T	1		1226
GW J1 414 T	1	4	1226
GW J1 502 T	1		1226
GW J1 504 T	1	4	1226
GW J1 514 T	1	4	1226
GW J2			
GW J2 101 A	1	8	1290
GW J2 101 L	1	8	1291
GW J2 101 R	1	8	1291
GW J2 101 W	1	8	1291
GW J2 102 A	1	8	1290
GW J2 102 L	1	8	1291
GW J2 102 R	1	8	1291
GW J2 102 W	1	8	1291
GW J2 103 A	1	8	1290
GW J2 103 L	1	8	1291
GW J2 103 R	1	8	1291
GW J2 103 W	1	8	1291
GW J2 402 T	1		1228
GW J2 404 T	1	6	1228
GW J2 502 T	1		1228
GW J2 504 T	1	6	1228
GW J3			
GW J3 001 A	1	48	1286
GW J3 002 A	1	48	1286
GW J3 002 L	1	48	1288
GW J3 002 R	1	48	1287
GW J3 002 W	1	48	1288
GW J3 003 A	1	48	1286
GW J3 004 A	1	48	1286
GW J3 004 L	1	48	1288
GW J3 004 R	1	48	1287
GW J3 004 W	1	48	1288
GW J3 011 A	1	36	1286
GW J3 012 A	1	36	1286
GW J3 012 L	1	36	1288
GW J3 012 R	1	36	1287
GW J3 012 W	1	36	1288
GW J3 013 A	1	36	1286
GW J3 014 A	1	36	1286
GW J3 014 L	1	36	1288
GW J3 014 R	1	36	1287
GW J3 014 W	1	36	1288
GW J3 101 A	1	48	1286
GW J3 102 A	1	48	1286
GW J3 103 A	1	48	1286
GW J3 111 A	1	36	1286
GW J3 112 A	1	36	1286
GW J3 113 A	1	36	1286
GW J3 201 A	1	48	1287
GW J3 202 A	1	48	1287
GW J3 202 L	1	48	1289
GW J3 202 R	1	48	1288
GW J3 202 W	1	48	1289
GW J3 203 A	1	48	1287
GW J3 204 L	1	48	1289
GW J3 204 R	1	48	1288
GW J3 204 W	1	48	1289
GW J3 211 A	1	36	1287
GW J3 212 A	1	36	1287
GW J3 212 L	1	36	1289
GW J3 212 R	1	36	1288
GW J3 212 W	1	36	1289
GW J3 213 A	1	36	1287
GW J3 214 L	1	36	1289
GW J3 214 R	1	36	1288
GW J3 214 W	1	36	1289
GW J3 301 A	1	48	1287
GW J3 302 A	1	48	1287
GW J3 303 A	1	36	1287
GW J3 311 A	1	36	1287
GW J3 312 A	1	36	1287
GW J3 313 A	1	36	1287
GW J3 402 C	1	48	1218
GW J3 404 C	1	48	1218
GW J3 412 C	1	36	1218
GW J3 413 C	1	36	1218
GW J3 414 C	1	36	1218
GW J3 502 G	1	48	1219
GW J3 504 G	1	48	1219
GW J3 512 G	1	36	1219
GW J3 513 G	1	36	1219
GW J3 514 G	1	36	1219
GW J3 602 T	1	48	1220
GW J3 604 T	1	48	1220
GW J3 612 T	1	36	1220
GW J3 613 T	1	36	1220
GW J3 614 T	1	36	1220
GW J3 702 T	1	48	1220
GW J3 704 T	1	48	1220
GW J3 712 T	1	36	1220
GW J3 714 T	1	36	1220
GW J5			
GW J5 001 B	1/12	96	1239
GW J5 001 G	1/12	96	1239
GW J5 002 B	1/12	96	1239
GW J5 002 G	1/12	96	1239
GW J5 002 L	1/12		1239
GW J5 003 B	1/12	96	1239
GW J5 004 B	1/12	96	1239
GW J5 004 L	1/12	60	1239
GW J5 011 B	1/12	96	1239
GW J5 011 G	1/12	96	1239
GW J5 012 B	1/12	96	1239
GW J5 012 G	1/12	96	1239
GW J5 012 L	1/12	96	1239
GW J5 013 B	1/12	96	1239
GW J5 014 B	1/12	120	1239
GW J5 014 L	1/12	96	1239
GW J5 101 B	1	96	1240
GW J5 102 B	1	96	1240
GW J5 111 B	1	30	1240
GW J5 112 B	1	30	1240
GW J5 113 B	1	30	1240
GW J5 114 B	1	30	1240
GW J5 814 CT	1	30	1238
GW J5 815 BL	1	30	1237
GW J5 815 CL	1	30	1237
GW J5 818 BL	1	30	1237
GW J5 818 CL	1	30	1237
GW J5 834 CT	1	30	1238
GW J5 835 AL	1	30	1237
GW J5 835 CL	1	30	1237
GW J5 838 AL	1	30	1237
GW J5 838 CL	1	30	1237
GW J5 901	1/20	6240	1240
GW J5 912	1	84	1240
GW J5 913	10	180	1238
GW J8			
GW J8 001	1	3200	1289
GW J8 001	1	3200	1292
GW J8 002	1	16000	1222
GW J8 002	1	16000	1230
GW J8 002	1	16000	1234
GW J8 011	1	320	1292

Quick Reference

Code	Quantity		Page
	Pack/carton	Pallet	
GW J8 012	1	200	1292
GW J8 013	1	40	1230
GW J8 014	1	5000	1222
GW J8 014	1	5000	1230
GW J8 015	1/5	500	1292
GW J8 016	1/5	500	1292
GW J8 018	1/5	1560	1289
GW J8 018	1/5	1560	1292
GW J8 021	1	320	1230
GW J8 034	1	50	1222
GW J8 037	1	120	1222
GW J8 037	1	120	1230
GW J8 038	1	120	1222
GW J8 038	1	120	1230
GW J8 101	1	48	1222
GW J8 102	1	12	1222
GW J8 103	1	12	1222
GW J8 104	1	30	1222
GW J8 105	1/4	868	1222
GW J8 111	1		1222
GW J8 113	1/10	200	1222
GW J8 114	1/10	2000	1230
GW J8 115	1/10	2000	1234
GW J8 116	1/10		1234
GW J9			
GW J9 011 W	1	1	1233
GW J9 122 W	1	1	1293
GW J9 122 Y	1		1233
GW J9 232 W	1	1	1293
GW J9 232 Y	1		1233
GW J9 242 W	1		1293
GW J9 242 Y	1		1233
GW J9 252 W	1		1293
GW J9 252 Y	1		1233
GW J9 262 W	1		1293
GW J9 262 Y	1		1233
GW J9 902	1	16	1234
GW J9 911	1	1	1234
GW J9 912	1	1	1234
GW J9 921	1	24	1234
GW J9 922	1	10	1234
GW J9 923		1	1234
GW N1			
GW N1 002	1	8	1205
GW N1 003	1	8	1205
GW N1 012	1	15	1205
GW N1 014	1	30	1205
GW N1 022	1	15	1205
GW N1 024	1	30	1205
GW N1 031 F	1	30	1205
GW N1 042 XB	1	30	1206
GW N1 043 XB	1	30	1206
GW N1 051 XB	1	15	1206
GW N1 062 XB	1	30	1206
GW N1 064 XB	1	30	1206
GW N1 066 XB	1	10	1206
GW N1 101 CF	1	16	1207
GW N1 101 CP	1	16	1207
GW N1 101 XB	1	16	1207
GW N1 111 CF	1	16	1207
GW N1 111 CP	1	16	1207
GW N1 111 XB	1	16	1207
GW N1 121 XB	1	30	1207
GW N1 122 XB	1	20	1208
GW N1 124 XB	1	30	1208
GW N1 131	1	160	1208
GW N1 132	1	160	1208
GW N1 133	1	8	1208
GW N1 134	1	160	1209
GW N1 135	1/10	1600	1209
GW N1 141	1	60	1209
GW N1 142	1	18	1209
GW N1 201 XB	1	1	1202
GW N1 261 XB	1		1202
GW N1 401 XB	1	1	1202
GW N1 431 CP	1	15	1203
GW N1 461 XB	1	1	1203
GW N1 601 XB	1	1	1203
GW N1 661 XB	1		1204
GW N1 801 XB	1	1	1204
GW N1 831 CP	1	1	1204
GW N1 861 XB	1	1	1204

General sales conditions

1. Definitions

1.1 In these General Sales Conditions the terms hereunder have the meaning as specified for each one of them:

a) "Gewiss": the company GEWISS S.p.A.;

b) "Purchaser": the subject, natural person or legal entity requesting the purchase of Gewiss products;

c) "Party" or "Parties": Gewiss and/or the Purchaser, individually or jointly considered;

d) "Order" or "Orders": the purchase order or orders sent by the Purchaser to Gewiss;

e) "Order confirmation": the confirmation of the Order sent by Gewiss to the Purchaser;

f) "Products": all the products offered by Gewiss and described in catalogues, drawings, technical sheets or its brochures;

g) "General Conditions": the general sales conditions hereunder.

2 Scope of application

2.1 The General Conditions apply to all sales made between Gewiss and the Purchaser whose subject matter is the Products and form an integral part of all Contracts entered into between the Parties, regulating their relationship, even where not expressly referred to. These General Conditions replace Gewiss' previous general sales conditions.

2.2 The Purchaser cannot demand or take exception to conditions other than those contained in the General Conditions. Therefore, any conditions set out in writing by the Purchaser on the Order shall not be valid, or those in any other phase of the contractual negotiations as well as after the acceptance or knowledge of the General Conditions, as well as any general purchasing conditions of the Purchaser. To this end, the performance, even partial, of the Order by Gewiss or fulfilment of any other obligation in terms of the Purchaser are not valid and cannot be interpreted as tacit or implicit acceptance of any general condition which has not been explicitly signed by Gewiss.

2.3 The General Conditions are only valid for contractual relationships between Gewiss and professional operators, thus the Italian Legislative Decree no. 206 of 6th September 2005 (Consumer Law) is not applicable. The General Conditions are valid for the entire period necessary for complete and correct fulfilment of the Contract.

2.4 Any special conditions agreed between the Parties shall only be valid where indicated in the Order confirmation, and shall prevail over the General Conditions, constituting a derogation from these.

3 Procedure for finalising the sales contract

3.1 The Order sent by the Purchaser to Gewiss constitutes an irrevocable contractual proposal which is binding for 30 (thirty) days from the time Gewiss learns of it.

3.2 Within these 30 (thirty) days period Gewiss, at its sole discretion, reserves the right to accept the Order or not, and send to the Purchaser the Order confirmation.

3.3 The Contract shall be considered finalised following the transmission of the Order confirmation or, alternatively, with the performance of the Order by Gewiss; in this case, the Purchaser cannot cancel the Order without previous written approval from Gewiss and/or he cannot refuse the Products. Up to the time of finalising of the Contract under the above conditions, offers and/or estimates made by Gewiss or its agents, representatives and assistants, shall not be binding for Gewiss.

3.4 In the event that the Order confirmation differs from the Order, for example but not limited to, the quantity of Products, prices, discounts and delivery terms, such Order confirmation shall be considered as a counterproposal from GEWISS, and must be expressly accepted by the Purchaser, for the Contract to be considered finalised.

3.5 In any case, it is hereby understood that any oral agreement with the Purchaser related to the sale shall not be binding for Gewiss unless confirmed in writing by Gewiss.

3.6 In the event that the Order is cancelled by the Purchaser before it is accepted and/or performed by Gewiss, Gewiss may ask the Purchaser to reimburse any expenses or charges incurred to perform the Order and/or part of it as well as compensation for any sustained damages.

4 Prices

4.1 The prices indicated in Gewiss catalogues and price lists are considered VAT excluded for goods delivered EXW Incoterms® 2020 (ex works) of Gewiss, transportation, insurance, packing and assistance expenses excluded.

4.2 Such prices are merely given as a guideline and are not binding on Gewiss in any way, who reserves the right to make changes to the same proportionate to increases in labour, raw material and other cost items and for other causes which occur during the catalogue/price list validity period.

5 Deliveries

5.1 Unless otherwise agreed between the Parties, the Products are delivered to the Purchaser or third party assigned by the Purchaser as per EXW Incoterms® 2020 (ex works) at Gewiss warehouse. Order confirmations are purely indicative and not binding, and do not include transport times.

5.2 Gewiss is not liable for any indemnity or claim for compensation against Gewiss for direct or indirect damages due to delays and/or partial dispatch of the deliveries, if not attributable to fraud or gross negligence by Gewiss.

5.3 If performance of the Order is obstructed by the occurrence of force majeure events, lack of regular raw material supplies or sub-supplies or other unpredictable circumstances occurring when the Contract is finalised, the delivery dates shall be considered extended, without Gewiss being held liable for the delay and new dates shall be established by the Parties. The Purchaser shall not have the right to refuse the delivery of the Products.

5.4 If, once the Products are ready for shipping to the Purchaser, and delivery is not made due to circumstances not attributable to Gewiss or due to force majeure, the delivery shall be considered performed for all extents and purposes with a simple notice of goods ready for picking-up to be notified to the Purchaser by registered letter, fax or e-mail. From the day after sending the above notice, Gewiss shall be due in addition to the agreed upon price, a fee for storage at Gewiss' warehouse totalling 2% of the amount on the invoice for each entire week of delay; in the event of a delay less than a week the percentage shall be calculated in proportion to the days of delay. All risks related to the goods storage period at Gewiss' warehouse are the sole responsibility of the Purchaser. If the Purchaser's refusal to receive the goods lasts for more than 30 (thirty) days from the notice of goods ready for picking-up, Gewiss shall be entitled to terminate the Contract and claim for compensation of damages.

6 Risks

6.1 The risks of the delivery of the Products are regulated by Incoterms® 2020 terms which are agreed by the Parties.

6.2 The Purchaser, at the time of receiving the Products, must always, in their own interest, check the quantity and conditions before the acceptance and notify the carrier of any damage immediately and in writing. Otherwise, every dispute related to the quantity and conditions of the packed and delivered Products shall be refused.

7 Quantity and packing

7.1 The Orders must comply with the minimum packing quantities. In the event of Orders for lower quantities Gewiss reserves the right to charge the Purchaser, subject to notification, the lump sum of 5.00 Euro for each line of bulk Product Order.

7.2 Standard packing are considered included in the sales price, while the costs for any non-standard packing, unless otherwise established between the Parties, shall be charged by Gewiss to the Purchaser.

8 Compliance with product standards

8.1 Gewiss guarantees that all Products, which fall under the scope of application of European Directives and Regulations, comply with the essential requirements set out in them, in order to be put on the market and ordered in European Union. Compliance with the Directives and Regulations is indicated by affixing of the graphic symbol "CE".

8.2 The exportation in some UE or extra UE Countries can be forbidden or require specific documents, mark o certification. The Purchase shall contact Gewiss for the relevant information.

9 Modifications to Products

9.1 The indications, measurements, drawings and images of the Products and related components present in Gewiss catalogues, brochures and websites, and in general all Gewiss technical and informational documentation are given as a guideline and example and are not binding in any way.

9.2 Gewiss, at any time and with no obligation for prior notice, reserves the right to make all of the modifications that it, at its sole discretion, feels opportune for improving the Product features and performance as well as to meet its own technological and production needs.

9.3 The quality and certification marks mentioned on Gewiss paper material shall be considered in force at the date of the printing of the documents. The updated list of marks is available on the site www.gewiss.com or through the Technical Assistance Service. The updated certification list is available on www.gewiss.com or upon request to the Technical Assistance Service.

10 Quality, warranties and complaints

10.1 All of the Products have the qualities necessary for the normal intended use of products of the same type, as shown in the technical documentation in effect at the time of sale, which the Purchaser declares to know and accept. In addition, the Products are covered by warranty for their correct operation and warranty for design and manufacturing faults and/or defects for a period of 24 (twenty-four) months from the delivery date, except for normal wear and tear parts. Once this period has elapsed the warranty becomes null and void, even if the Products have not been put into operation for any reason.

10.2 The warranty is effective as long as the malfunctioning, faults and/or defects are not the result of: (i) assembly and/or installation errors, (ii) failure to perform or incorrect maintenance, (iii) failure to comply with and/or erroneous compliance with technical specifications contained in the Gewiss catalogue and in any instructions sheets, (iv) natural wear, (v) faults caused by inexperience and/or negligence (vi) poor care, (vii) failure to immediately adopt measures designed to limit inefficiencies, (viii) overloads compared to limits indicated in technical instructions, (ix) interruptions to or suspensions of electricity, (x) unauthorised activities, (xi) tampering by the Customer and/or third parties, (xii) acts of vandalism, (xiii) acts of terrorism, (xiv) atmospheric events, (xv) fortuitous events or (xvi) force majeure, (xvii) third party's act.

10.3 Moreover, the warranty is not effective in case of malfunctioning of the software installed on the Product, due to overloading, interruption and/or suspension of electric energy.

10.4 Any complaint due to quality defects, failure to operate or faulty operation or design and manufacturing faults and/or defects of the Products must be notified to Gewiss in writing, subject to forfeiture of the warranty:

- within 8 (eight) days from delivery of the Products in the event of clear faults and/or defects;
- within 8 (eight) days from discovery of the faults and/or defects becoming evident following delivery but within two years from the delivery.

10.5 For the complaint to be accepted, the Purchaser is required to prove in writing the validity of the warranty, the correct storage and installation of the Product, and to supply Gewiss with adequate documentation proving the faults/defects.

10.6 The warranty is limited, up to the sole discretion of Gewiss, to replacement of the defective Products or components (both with identical or similar products) or, alternatively, by repairing the defective Products or components. In any case the accessory expenses of the replacement and/or repair are excluded from the warranty.

10.7 Both in the case of replacement and repair of the defective Products the original warranty period will continue and shall not be considered renewed.

10.8 Gewiss shall not be held liable for any additional warranty obligation, including implicit, resulting from laws and/or regulations in favour of the Purchaser, including implicit warranties for non-compliance, non-saleable defects and/or the suitability of the Products for a special use.

11 Liability

11.1 Without prejudice to mandatory limits set by law and with the exclusion of fraud and gross negligence, is explicitly excluded any further liability by Gewiss - either contractual or extracontractual - that may arise from or be related, directly or indirectly, to the Contract, and/or to discrepancies, defects and/or faults in the Products, by means of example and not limited to loss of profit, loss of savings, loss of reputation, loss of goodwill and/or interruption of plants where the Products are intended to be used.

11.2 Gewiss shall not be held liable for Products sold and/or installed in Countries where there are regulations which do not allow their use, or for uses which they are not intended and/or for installations and uses not in compliance with the Products technical specifications indicated in the catalogues and instruction handbooks in effect at the time of the sale.

11.3 In the event of revision of the technical specifications and instruction handbook for Products already delivered and/or installed during the warranty period, the Purchaser shall not be covered under warranty for correct operation according to the new technical specifications.

11.4 The Purchaser agrees to establish in all contracts regarding the Products a clause limiting Gewiss' liability substantially identical to that envisaged by this article, assuming the complete and sole liability for the additional movement of Products supplied by Gewiss.

12 Returns

12.1 Return of the Products is not allowed without prior written authorisation from Gewiss, without which the Products shall be delivered again to the Purchaser at the Purchaser expenses and risk.

12.2 In the event of authorised return, the Products shall be returned carriage paid at the expense and risk of the Purchaser to Gewiss warehouses, within the term indicated by Gewiss. The Purchaser shall be credited for the purchase price of the Products, minus a minimum amount of 15% for administrative expenses. However, Gewiss reserves the right not to accept the return or to apply a higher percentage for administrative expenses if the goods are returned after the period indicated above.

12.3 In any case, the return of Products not included in the catalogue in effect at the time of the request to return and/or for which significant changes have been made to the technical specifications is prohibited.

13 Payment of the price

13.1 Payments shall be made in compliance with the "Supply Conditions" in the Gewiss catalogue in effect or according to what is otherwise agreed between the Parties in writing.

13.2 The delay, even partial of the payment of the invoices beyond their due date shall cause the immediate charging of interest in accordance with the legal measures in force, in addition to debiting of any bank expenses and fees.

13.3 Failure to pay for any reason, as well as failure to fulfil any other obligation by the Purchaser authorises Gewiss shall be entitled, pursuant to Article 1460 of the Italian Civil Code, to immediately suspend the delivery of the Products , as well as demand payment for the entire amount due, without prejudice to its right to withdraw from the Order being performed.

13.4 Gewiss also reserves the right to suspend supplies in the event of a significant modification in the Purchaser's economic situation, by means of example but not limited to transfer of the business or proven serious financial difficulty.

13.5 Possible collection expenses or stamp duty for payments received by bank transfer or other forms of payment are at the Purchaser charge.

13.6 Any discount agreed upon in writing between the Parties, is subject to complete compliance with payment due dates. Failure to pay within the agreed due dates shall result in forfeiture of the discount and the Purchaser who unduly withheld it shall be obligated to reimburse it immediately.

13.7 Any complaint from the Purchaser including for late delivery of incomplete supply, shall not give the Purchaser the right to suspend or delay payment of the supply.

13.8 The Purchaser cannot claim any non-fulfilment of Gewiss', nor claim the warranty as per article 10 above, if not up to date with payments.

13.9 The Parties undertake to act in compliance with the obligations set out in art. 3 of Law 136/2010 to ensure the traceability of financial movements relating to public services and supplies, with the clarification that the violation of these provisions determines the legal termination of the Contract.

14 Intellectual property

14.1 Gewiss shall remain the sole owner of the patents, drawings, designs and anything else used to create the Products, which, therefore, the Purchaser agrees not the give to third parties, reproduce or use, without prior authorization of Gewiss. If the creation of the Products is performed by Gewiss based on specific request and technical documentation of the Purchaser, Gewiss shall not be held liable for the violation of industrial property rights by third parties, which shall be the sole responsibility of the Purchaser, who agrees to guarantee and indemnify and hold Gewiss harmless from any claims made against it.

14.2 The Purchaser agrees to use Gewiss trademarks solely for the purposes of identifying, advertising and selling the Products, refraining from registering them of having them registered without prior written approval from Gewiss.

14.3 The Purchaser is prevented from registering "gewiss" as domain name as well as any domain which contains words which look like or recall Gewiss.

14.4 Possible links to Gewiss' website and the publication on the Purchaser's website of contents which refer to Gewiss shall be authorized in writing by the latter beforehand.

15 Confidentiality Obligation

15.1 The sales commercial conditions, particularly regarding the budget, incentive and discount conditions, as well as all other documentation or information classified by Gewiss as confidential, have a strictly confidential nature, therefore, the Purchaser agrees not to divulge them or communicate them to third parties, nor to use them for purposes other than the finalising and performance of the Contract, for the period of 5 (five) years after performance of the Order.

15.2 Gewiss reserves the right to pursue, including legally, any violations of the aforesaid confidentiality obligation.

16 Privacy

16.1 Gewiss agrees to collect and process the personal data it may learn of in relation to the execution of the Contract in compliance with the Italian Legislative Decree 196/2003 and subsequent amendments (Legislative Decree 101/2018 for the adaptation of the Italian legislation to EU Reg. no. 679/2016, so called GDPR), with the purposes therein permitted and to fulfil all legal requirements including of a tax or accounting nature. The information is available at www.gewiss.com.

17 Gewiss code of ethics and organization, management and control model - Anti-Corruption policy

17.1 The commercial relations governed by the General Conditions are based on the principles of legality, transparency, correctness and fairness, in accordance with the contents of the Code of Ethics, the Organisation Management and Control Framework adopted by Gewiss and with the principles of the Anti-Corruption Policy available on the www.gewiss.com website (Corporate governance documents).

17.2 Any notifications about the violation of the aforesaid Framework may be sent using the "Reporting Procedure", by filling in the appropriate form, both available on the www.gewiss.com website (Corporate Governance | Whistleblowing).

17.3 If, during the performance of the Contract, the Purchaser adopts a behaviour which does not comply with the aforesaid principles, Gewiss shall be entitled to take opportune measures, including to the termination of the Contract pursuant to Article 1456 of the Italian Civil Code and request compensation for damages.

18 Export restrictions to Russian Federation and to Belarus

18.1 The Purchaser shall not sell, export or re-export, directly or indirectly, to the Russian Federation or for use in the Russian Federation any Products supplied under or in connection with the Orders, that fall under the scope of Article 12g of Council Regulation (EU) No 833/2014.

18.2 The Purchaser shall not sell, export or re-export, directly or indirectly, to Belarus or for use in Belarus any Products supplied under or in connection with the Orders, that fall under the scope of Article 8g of Council Regulation (EC) No 765/2006.

18.3 The Purchaser shall undertake its best efforts to ensure that the purpose of art. 18.1 and art. 18.2 is not frustrated by any third parties further down the commercial chain, including by possible resellers.

18.4 The Purchaser shall set up and maintain an adequate monitoring mechanism to detect conduct by any third parties further down the commercial chain, including by possible resellers that would frustrate the purpose of art. 18.1 and of art. 18.2.

18.5 Any violation of articles 18.1, 18.2, 18.3 or 18.4 shall constitute a material breach of an essential element of the sales agreement, and Gewiss shall be entitled to seek appropriate remedies, including, but not limited to the cancellation of the Orders and the compensation for damages.

18.6 The Purchaser shall immediately inform Gewiss about any problems in applying paragraphs above, including any relevant activities by third parties that could frustrate the purpose of art. 18.1. The Purchaser shall make available to Gewiss information concerning compliance with the obligations under articles 18.1, 18.2, 18.3 and 18.4 within 2 (two) weeks of the simple request of such information.

19 Applicable law, court and language

19.1 All the Contracts finalised by Gewiss, regardless of the Purchaser's nationality and/or place of destination of the Products, are governed by Italian laws.

19.2 Application of the Vienna Convention on contracts for the international sale of goods of 11 April 1980 remains expressly excluded, as well as other statutory Conventions concerning international sales and governing conflicts between laws.

19.3 Any dispute arising between the Parties shall be submitted to the Italian court and solely to the Court of Gewiss' registered office, without prejudice to Gewiss' right to act at the Purchaser's address.

19.4 If these General Conditions are drafted in more than one language, in case of conflicts, the text in Italian shall be decisive.

Copyright
In compliance with copyright laws, the Italian Civil Code and further directives in effect in the markets where GEWISS operates, all information, data, images, photographs, drawings, tables and anything else included in the promotional and descriptive GEWISS material is the exclusive and sole property of GEWISS which holds all moral, commercial and economical rights to its use. Therefore, any reproduction of said material, using any means and whether total or partial is strictly prohibited without prior written authorisation from GEWISS. Any violation of the above will be prosecuted in compliance with law. The indications, measurements, drawings and photographs of the products and components are shown by way of information only and are not binding since they may be modified without any notification, safe for errors or omissions.

PB 11179 EN - 05.25

GEWISS S.p.A.
Registered Office: Via Domenico Bosatelli, 1
24069 Cenate Sotto (BG), Italy
T +39 035 946 111
E gewiss@gewiss.com
www.gewiss.com

Single shareholder company - Bergamo Business Register/VAT/Tax Code (IT) 00385040167
Economic and Administrative Index 107496 - Share Capital EUR 60,000,000.00 fully paid up