






Connected flush-mounted device with front rocker pushbutton, for switching on/off (short press) and for adjusting the brightness of the connected load (long press), with trailing-edge dimming control. The device can be paired and controlled via ZigBee by all connected ZigBee devices, including the connected 4-command rocker (GWA1391). The device operates as a ZigBee router, forwarding ZigBee messages to other devices. Equipped with 2 inputs (to which auxiliary controls, traditional pushbuttons and switches, sensors, etc. can be connected) to replicate the local control and dimming of the connected load or to send ZigBee commands and status information. The device must be completed with an interchangeable illuminated front key (codes from GWC2x048 to GWC2x052).

Category	Dimmers	LED colour	White
No. modules	1	Power supply	100 ÷ 240 V ac - 50/60 Hz
Radio connections	Zigbee (IEEE 802.15.4)	Power output Zigbee	10 dBm
Dispersible max power (W)	5,7	Local control	Via front rocker button (to be completed with key)
No. input channels	2 (for local command replication or sending additional Zigbee commands)	Input voltage	Mains supply voltage
Max. length of AUX input cables	50 m (single lenght)	No. output channels	1
240 V ac Incandescent-halogen lamps	4-150 W	240 V ac LED lamps	4-150 W (max 10 lamps)
Loads piloted from electronic transf. 240 V ac	4-150 VA	IP degree	IP20 (with button key)
Wiring terminals	With screw	Terminal tightening capacity stranded cables (mm ²)	Max. 1,5
Terminal tightening capacity solid cables (mm ²)	Max. 1,5	Working temperature	-5 ÷ +45 °C
Stocking temperature	-25 ÷ +70 °C	Relative humidity (non-condensative)	Max 93%
Standard	Directive RoHS, Directive RED, EN 60669-2-1, EN 60669-1, EN IEC 63000, EN 301 489-1, EN 301 489-17, EN 300 328	Power	4-150 W 240 V ac
Strip LED	4-150 W	Button key	To be completed (code from GWC2x048 to GWC2x052)

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 27/07/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice