






Connected flush-mounted device for controlling a motor for the movement of shutters, curtains, Venetian blinds, roller shutters, etc. via 2 interlocked voltage output contacts. The device is equipped with two relays that allow driving a 100-240 Vac, 50/60 Hz motor for controlling movement in the up and down directions. The device is equipped with a front rocker button for upward and downward movement and for adjusting the slat tilt. The device can be paired and controlled via ZigBee by all connected ZigBee devices, including the connected 4-command rocker (GWA1391). The device operates as a ZigBee router, forwarding ZigBee messages to other devices. Equipped with 2 inputs (to which auxiliary controls, traditional pushbuttons and switches, sensors, etc. can be connected) to replicate the local movement of the connected motor or to send ZigBee commands and status information. The device must be completed with an interchangeable illuminated front key (codes from GWC2x048 to GWC2x052).

Category	Comando tapparella connesso	LED colour	White
No. modules	1	Power supply	100 ÷ 240 V ac - 50/60 Hz
Radio connections	Zigbee (IEEE 802.15.4)	Power output Zigbee	10 dBm
Dispersible max power (W)	2	Local control	Via front rocker button (to be completed with key)
No. input channels	2 (for local command replication or sending additional Zigbee commands)	Input voltage	Mains supply voltage
Max. length of AUX input cables	50 m (single lenght)	No. output channels	1
Output contacts	2,3 A 240 V ac (as IEC 60669-2-1)	IP degree	IP20 (with button key)
Wiring terminals	With screw	Terminal tightening capacity stranded cables (mm ²)	Max. 1,5
Terminal tightening capacity solid cables (mm ²)	Max. 1,5	Working temperature	-5 ÷ +45 °C
Stocking temperature	-25 ÷ +70 °C	Relative humidity (non-condensative)	Max 93%
Standard	Directive RoHS, Directive RED, EN 60669-2-1, EN 60669-1, EN 301 489-1, EN 301 489-17, EN 300 328, EN IEC 63000	Button key	To be completed (code from GWC2x048 to GWC2x052)

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP20 (with button key)

STANDARDS/APPROVALS

