






A complete range of commands and protections, energy and signal sockets, temperature control units, comfort management solutions, and acoustic/visual signalling devices. The commands, available with two different buttons designs, are illuminated with LED light and feature elegant indicator icons. System Pura is available in two colours and two finishes: glossy white, satin black and satin white. The series proposes intuitive and modern solutions designed to enhance any space. These features make it ideal for both residential applications and special installations, where reliability and aesthetics must coexist harmoniously.

Category	Switch	Button key		With lens
Symbol	-	Description		1P - 16 AX illuminable
Colour	Satin black	Voltage		250 V ac
Type	Switch	Signalling unit		-
Standard	EN 60669-1	Resistance at test voltage		2000 V at 50 Hz for 1 minute
Rated power of 230V LED lamps	200 W	Insulation resistance		> 5 MOhm
Wiring terminals	With screw	Prolonged operation switch (no. of position changes)	40.000 at In 250 V ac cosφ=0,6	
Thermo-pressure with ball	125 °C	Glow Wire Test		850 °C
Terminal grip on cable traction	> 50 N	Terminal tightening capacity stranded cables (mm ²)		min. 0,75 - max. 2x4
Terminal tightening capacity solid cables (mm ²)	min. 0,5 - max. 2x2,5	No. modules		2
Material	Technopolymer	Halogen Free		Halogen-free in compliance with EN IEC 63355
Electrocod	0130			

DIMENSIONAL



TECHNICAL SYMBOLOGY



125 °C

850 °C

STANDARDS/APPROVALS

