





Wide range of surface-mounting and flush-mounting boxes for domestic ranges with high mechanical robustness and accessories supplied: dividers, junction elements, mortarguard shield, etc. Completing the range, the distribution outlet boxes for floor-mounting installations can be personalised in terms of capacity, external design finish, and internal fittings (they take both System range components and DIN rail devices).

No. gangs	2 modules sectional	IP degree	IP40
Type	For brick walls	Glow Wire Test	650 °C
Category	For domestic range	Thermo-pressure with ball	70 °C
Accordance with Standards	EN 60670-1 (CEI 23-48)	Outer dim. LxHxD (mm)	70x70x50
Material	GW PLAST Technopolymer	Fixing supports axles distance	60 mm
Halogen Free	Halogen-free in compliance with EN 60754-2	Cable entries	2 x Ø 16/20 + 8 x Ø 20/25 cut-outs
Colour	Orange RAL 2001	Type of cut-outs	Removable with tool
Installation temperature	-15 +60 °C		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY

GWT

650 °C



70 °C

HF

Halogen-free in compliance with EN 60754-2

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 27/07/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice