Product Data Sheet GW10921


CHORUSMART - domestic range



Flush-mounting roller shutter touch module. Device for commanding the motor that drives roller shutters, curtains, Venetian blinds, roller blinds, etc. via 2 interlocked output contacts with potential. There are two frontal touch areas for upward (UP) and downward (DOWN) movement, and for regulating the tilt of the slats. The device must be completed with one of the ICE Touch plates available. Inside the package of the plates is a sheet of interchangeable icons to customize the control symbol.

The device has n°3 DIP-switches, located on the back of the device, for feature configuration.

Description	Touch roller-shutter module	Power supply	100 ÷ 240 V ac - 50/60 Hz
No. modules	1	No. input channels	2
Local control	Via 2 frontal touch areas (must be completed with ICE Touch	Auxiliary input channel voltage	100 ÷ 240 V ac - 50/60 Hz
	plate)		
Stocking temperature	-25 ÷ +70 °C	No. output channels	2
Working temperature	-5 ÷ +45 °C	Output contacts	n. 2 x 2,3 A cosφ 0,6
Relative humidity (no	n-condensative) Max 93%	240 V ac Incandescent-halogen lamps	-
Front light signaling	Blue led	240 V ac LED lamps	-
Wiring terminals	With screw	Loads piloted from electronic transf. 240 V ac	-
Terminal tightening ca	pacity Max. 1,5	240 V Fluorescent lamps	-
stranded cables (mm)		
Terminal tightening ca	pacity Max. 1,5	Load control	-
solid cables (mm ²)			
Context	Dry indoor places	Acoustic signalling element Buzzer	
IP degree	IP20 (with plate fitted)	Standard 2014/35/EU (LVD), 2014/30/EU (EMC), 2011/65/EU + 2015/863	
		(RoHS), EN	60669-2-1, EN 60669-1, EN IEC 63000



22 48,25

TECHNICAL SYMBOLOGY



IP20 (with plate fitted)

STANDARDS/APPROVALS





GEWISS S.p.A. Via Domenico Bosatelli 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09 www.gewiss.com sat@gewiss.com Last update 30/04/2025 Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice