

No. DIN modules 4
 Supply voltage 12-24 V dc
 No. input channels 4
 Input channel type Comando per LED CVD
 Type of output loads 4 uscite per LED CVD, pilotate dal dimmer CVD collegato. Pilotaggio carico ad anodo comune

No. output channels	4	Max current per channel	16 A
Rated power	768 W max. a 12Vdc - 1536 W max. a 24Vdc	Dispersible max power (W)	6 W
Max power supply cable length (m)	3 m	Wiring terminals	With screw
Terminal tightening capacity stranded cables (mm ²)	Max. 4	Working temperature	-5 ÷ +45 °C
Stocking temperature	-25 ÷ +55 °C	IP degree	IP20
Relative humidity (non-condensative)	Max 93%	Standard	Low Voltage Directive 2014/35/EU - Electromagnetic Compatibility Directive 2014/30/ EU - EN50428, EN50090-2-2

DIMENSIONAL

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
 24069 Cenate Sotto - Bergamo - Italy
 tel. +39 035 94 61 11 fax +39 035 94 69 09
 Company subject to the management and
 coordination of Polifin S.p.A.

www.gewiss.com
 sat@gewiss.com
 Last update 27/07/2026

Data, measures, designs and pictures are shown
 only as informative purposes,
 and could be changed without previous notice