



Communication KNX Secure

No. DIN modules 4

Power supply Via KNX BUS, 29 V DC SELV

Supply voltage 230 V ac - 50/60 Hz

Interfaces KNX TP1

Current absorbed by KNX bus (mA)	Max 10 mA a 29 V	Dispersible max power (W)	5 W
Power max.	500 VA	No. output channels	1
Wiring terminals	With screw	Terminal tightening capacity stranded cables (mm ²)	Max. 2,5
Connection to the KNX bus	KNX bus terminal	240 V ac Incandescent-halogen lamps	500 W
Low voltage halogen lamps with electronic transformers	500 VA	Low voltage halogen lamps with ferromagnetic transformers	500 VA
230V AC LED lamps with dimmer function	200 W	CFL lamps with dimmer function	150 W
Working temperature	-5 ÷ +45 °C	Stocking temperature	-25 ÷ +55 °C
IP degree	IP20	Relative humidity (non-condensative)	Max 93%
Standard	Low Voltage Directive 2014/35/EU - Electromagnetic Compatibility Directive 2014/30/ EU - EN50428, EN50090-2-2		

DIMENSIONAL

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09
Company subject to the management and coordination of Polifin S.p.A.

www.gewiss.com
sat@gewiss.com
Last update 28/07/2026

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice