



Description Interruttore automatico scatolato
 Code MSX 125
 No. of poles 3P
 Rated current 125 A
 Release Elettromeccanico

ELECTRICAL CHARACTERISTICS

Standard	IEC/EN 60947-2
Use category	A
Rated frequency (Hz)	50 / 60
Rated operating voltage (Ue)	690 Vac - 250 Vdc
Rated impulse withstand voltage (Uimp)	8 kV
Overvoltage category	IV
Insulation voltage (Ui)	800 V
Thermal regulation	-
Magnetic regulation	6 - 8 - 10 x In
Neutral protection	-
Total power loss	29.52 W
Rated short-circuit current making capacity (Icm)	-
Rated short-time withstand current for 0,3s (Icw)	-
I _{dn} regulation	-
DT regulation	-

SERVICE BREAKING CAPACITY (ICU)

220/240Vac	50 kA
400/415Vac	36 kA
440Vac	25 kA
525Vac	22 kA
690Vac	6 kA
250Vdc	25 kA


MECHANICAL CHARACTERISTICS

Execution	Fisso - Rimovibile
DIN rail mounting	Sì, tramite accessorio
Accessoriabile con comando motore	Sì
Compatible interlock	Lever - Cable
Terminals supplied	Front FC
Assembly position	Any
Upline/downline power supply	Sì
Electrical life (415Vac)	30.000 cycles
Mechanical life	30.000 cycles
Operating temperature	-5°C +65°C
Stocking temperature	-20° +65°
Weight (kg)	1.1
Width	90 mm
Height	155 mm
Depth	68 mm

RATED BREAKING CAPACITY (ICS)

220/240Vac	50 kA	220/240Vac	50 kA
400/415Vac	36 kA	400/415Vac	36 / 30 kA
440Vac	25 kA	440Vac	25 kA
525Vac	22 kA	525Vac	22 kA
690Vac	6 kA	690Vac	6 kA
250Vdc	25 kA	250Vdc	19 kA

DIMENSIONAL





Product Data Sheet

GWD9206

MSX Range

STANDARDS/APPROVALS

