



Description Interruttore automatico scatolato  
 Code MSXD 125  
 No. of poles 3P+N  
 Rated current 50 A  
 Release Elettromeccanico

#### ELECTRICAL CHARACTERISTICS

Standard	IEC/EN 60947-2
Use category	A
Rated frequency (Hz)	50 / 60
Rated operating voltage (Ue)	525 Vac
Rated impulse withstand voltage (Uimp)	8 kV
Overvoltage category	IV
Insulation voltage (Ui)	525 V
Thermal regulation	0,63 - 0,8 - 1 x In
Magnetic regulation	Fixed - 500 A
Neutral protection	Non protetto
Total power loss	19,92 W
Rated short-circuit current making capacity (Icm)	-
Rated short-time withstand current for 0,3s (Icw)	-
I <sub>dn</sub> regulation	0,03 - 0,1 - 0,3 - 0,5 - 1 - 3 A
DT regulation	0 - 60 - 200 - 400 - 700 ms

#### SERVICE BREAKING CAPACITY (ICU)

220/240Vac	35 kA
400/415Vac	25 kA
440Vac	15 kA
525Vac	8 kA
690Vac	-
250Vdc	-


#### MECHANICAL CHARACTERISTICS

Execution	Fixed
DIN rail mounting	Si, tramite accessorio
Accessoriabile con comando motore	Si
Compatible interlock	-
Terminals supplied	Front FC
Assembly position	Any
Upline/downline power supply	Si
Electrical life (415Vac)	30.000 cycles
Mechanical life	30.000 cycles
Operating temperature	-5°C +65°C
Stocking temperature	-20° +65°
Weight (kg)	1.4
Width	120 mm
Height	155 mm
Depth	68 mm

#### RATED BREAKING CAPACITY (ICS)

220/240Vac	27 kA
400/415Vac	19 kA
440Vac	12 kA
525Vac	6 kA
690Vac	-
250Vdc	-

### DIMENSIONAL





Product Data Sheet

**GWD9553**

MSX Range

STANDARDS/APPROVALS

