



Beschreibung Interruttore automatico scatolato

Artikelnr. MSX 125

Anz. Pole 4P

Bemessungs- strom 125 A

Auslöser Elettromeccanico


ELECTRICAL CHARACTERISTICS

Norm	IEC/EN 60947-2	Ausführung	Fisso - Rimovibile
Kategorie	A	DIN rail mounting	Si, tramite accessorio
Bemessungs- frequenz (Hz)	50 / 60	Accessoriabile con comando motore	Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever - Cable
Bemessungsstoß- spannungsfestigkeit (Uimp)	8 kV	Terminals supplied	Vorderseitige FC
Überspannungs- kategorie	IV	Position Montage	Jeder
Isolationsspannung (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	30.000 cycles
Magnetic regulation	6 - 8 - 10 x In	Mechanical life	30.000 cycles
Neutral protection	100% x Ir	Betriebstemperatur	-5°C +65°C
Total power loss	39.36 W	Lagertemperatur	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Gewicht (kg)	1.4
Rated short-time withstand current for 0,3s (Icw)	-	Breite	120 mm
I _{dn} regulation	-	Höhe	155 mm
DT regulation	-	Tiefe	68 mm

SERVICE BREAKING CAPACITY (ICU)

220/240Vac	50 kA	220/240Vac	50 kA
400/415Vac	36 kA	400/415Vac	36 / 30 kA
440Vac	25 kA	440Vac	25 kA
525Vac	22 kA	525Vac	22 kA
690Vac	6 kA	690Vac	6 kA
250Vdc	25 kA	250Vdc	19 kA

Abmessungen





Produktdatenblatt

GWD9146

Baureihe MSX

Normen / Richtlinien

