



Descripción Interruttore automatico scatolato
 Código MSXE 250
 N° polos 4P
 Corriente nominal 250 A
 Disparador Electrónico

ELECTRICAL CHARACTERISTICS

| | |
|---|--|
| Norma de referencia | IEC/EN 60947-2 |
| Categoría de uso | A |
| Frecuencia nominal (Hz) | 50 / 60 |
| Rated operating voltage (Ue) | 690 Vac |
| Tensión nominal de tensión soportada (Uimp) | 8 kV |
| Categoría de sobretensiones | IV |
| Tensión de aislamiento (Ui) | 800 V |
| Thermal regulation | 0,4 - 0,5 - 0,63 - 0,8 - 0,9 - 0,95 - 1 x In |
| Magnetic regulation | Electronic LSI |

MECHANICAL CHARACTERISTICS


| | |
|-----------------------------------|--------------------|
| Ejecución | Fisso - Rimovibile |
| DIN rail mounting | No |
| Accessoriabile con comando motore | Si |
| Compatible interlock | Lever - Cable |
| Terminals supplied | Delantero FC |
| Posición de montaje | Cualquier |
| Upline/downline power supply | Si |
| Electrical life (415Vac) | 10.000 cycles |
| Mechanical life | 30.000 cycles |
| Temperatura de empleo | -5°C +65°C |
| Temperatura de almacenaje | -20° +65° |
| Peso (kg) | 3.1 |
| Ancho | 140 mm |
| Altura | 165 mm |
| Profundidad | 103 mm |

| | |
|---|---------------------|
| Neutral protection | 100% x Ir |
| Total power loss | 87.59999999999999 W |
| Rated short-circuit current making capacity (Icm) | - |
| Rated short-time withstand current for 0,3s (Icw) | - |
| I _{dn} regulation | - |
| DT regulation | - |

SERVICE BREAKING CAPACITY (ICU)

| | | | |
|------------|--------|------------|--------|
| 220/240Vac | 85 kA | 220/240Vac | 85 kA |
| 400/415Vac | 65 kA | 400/415Vac | 36 kA |
| 440Vac | 50 kA | 440Vac | 25 kA |
| 525Vac | 25 kA | 525Vac | 25 kA |
| 690Vac | 7,5 kA | 690Vac | 7,5 kA |
| 250Vdc | - | 250Vdc | - |

DIMENSIONAL





Ficha Técnica Producto

GWD9358

Gama MSX

MARCAS/APROBACIONES

