





Wide range of surface-mounting and flush-mounting boxes for domestic ranges with high mechanical robustness and accessories supplied: dividers, junction elements, mortarguard shield, etc. Completing the range, the distribution outlet boxes for floor-mounting installations can be personalised in terms of capacity, external design finish, and internal fittings (they take both System range components and DIN rail devices).

Počet modulů	2 moduly sekční	Stupeň krytí IP	IP40
Typ	Pro zděné stěny	Zkouška žhavou smyčkou	650 °C
Kategorie	Pro řadu Domestic	Tepelné zatížení s kuličkou	70 °C
Soulad s normami	EN 60670-1 (CEI 23-48)	Vnější rozměry DxVxH (mm)	70x70x50
Materiál	GW PLAST Technopolymer	Osová vzdálenost upevňovacích podpěr	60 mm
Bez halogenů	Bez halogenů v souladu s normou EN 60754-2	Cable entries	2 x Ø 16/20 + 8 x Ø 20/25 cut-outs
Barva	Orange RAL 2001	Type of cut-outs	Odnímatelné pomocí nástroje
Instalační teplota	-15 +60 °C		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY

GWT

650 °C



70 °C

HF

Bez halogenů v souladu s normou EN 60754-2

STANDARDS/APPROVALS

