



Beschreibung Interruttore automatico scatolato

Artikelnr. MSX 160c

Anz. Pole 3P+N

Bemessungs- strom 25 A


Auslöser Elettromeccanico

ELECTRICAL CHARACTERISTICS

MECHANICAL CHARACTERISTICS

Norm	IEC/EN 60947-2	Ausführung	Fest
Kategorie	A	DIN rail mounting	Si, tramite accessorio
Bemessungs- frequenz (Hz)	50 / 60	Accessoriabile con comando motore	Nein
Rated operating voltage (Ue)	525 Vac - 250 Vdc	Compatible interlock	-
Bemessungsstoß- spannungsfestigkeit (Uimp)	8 kV	Terminals supplied	Vorderseitige für Kabel FW
Überspannungs- kategorie	IV	Position Montage	Jeder
Isolationsspannung (Ui)	690 V	Upline/downline power supply	Si
Thermal regulation	0,63 - 0,8 - 1 x In	Electrical life (415Vac)	14.000 cicli
Magnetic regulation	Fisso - 600A	Mechanical life	20.000 cicli
Neutral protection	Non protetto	Betriebstemperatur	-5°C +65°C
Total power loss	18.4 W	Lagertemperatur	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Gewicht (kg)	1
Rated short-time withstand current for 0,3s (Icw)	-	Breite	100 mm
I _{dn} regulation	-	Höhe	130 mm
DT regulation	-	Tiefe	68 mm
SERVICE BREAKING CAPACITY (ICU)		RATED BREAKING CAPACITY (ICS)	
220/240Vac	25 kA	220/240Vac	13 kA
400/415Vac	16 kA	400/415Vac	8 kA
440Vac	10 kA	440Vac	5 kA
525Vac	6 kA	525Vac	3 kA
690Vac	-	690Vac	-
250Vdc	13 kA	250Vdc	7 kA

Abmessungen





Produktdatenblatt

GWD9011

Baureihe MSX

Normen / Richtlinien

