



Beschreibung Interruttore automatico scatolato

Artikelnr. MSX 160

Anz. Pole 4P

Bemessungs- strom 160 A

Auslöser Elettromeccanico

#### ELECTRICAL CHARACTERISTICS


Norm	IEC/EN 60947-2	Ausführung	Fisso - Rimovibile
Kategorie	A	DIN rail mounting	Si, tramite accessorio
Bemessungs- frequenz (Hz)	50 / 60	Accessoriabile con comando motore	Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever – Cable
Bemessungsstoß- spannungsfestigkeit (Uimp)	8 kV	Terminals supplied	Vorderseitige FC
Überspannungs- kategorie	IV	Position Montage	Jeder
Isolationsspannung (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	-	Electrical life (415Vac)	20.000 cicli
Magnetic regulation	6 - 8 - 10 - 13 x In	Mechanical life	30.000 cycles
Neutral protection	-	Betriebstemperatur	-5°C +65°C
Total power loss	48.12 W	Lagertemperatur	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Gewicht (kg)	1.9
Rated short-time withstand current for 0,3s (Icw)	-	Breite	140 mm
Idn regulation	-	Höhe	165 mm
DT regulation	-	Tiefe	68 mm

#### SERVICE BREAKING CAPACITY (ICU)

220/240Vac	65 kA	220/240Vac	65 kA
400/415Vac	36 kA	400/415Vac	36 kA
440Vac	25 kA	440Vac	25 kA
525Vac	25 kA	525Vac	25 kA
690Vac	7,5 kA	690Vac	7,5 kA
250Vdc	40 kA	250Vdc	40 kA

#### RATED BREAKING CAPACITY (ICS)

### Abmessungen



Normen / Richtlinien

