



Beschreibung Interruttore automatico scatolato

Artikelnr. MSX 250

Anz. Pole 4P

Bemessungs- strom 250 A

Auslöser Elettromeccanico


ELECTRICAL CHARACTERISTICS

Norm	IEC/EN 60947-2	Ausführung	Fisso - Rimovibile
Kategorie	A	DIN rail mounting	Si, tramite accessorio
Bemessungs- frequenz (Hz)	50 / 60	Accessoriabile con comando motore	Si
Rated operating voltage (Ue)	690 Vac - 250 Vdc	Compatible interlock	Lever - Cable
Bemessungsstoß- spannungsfestigkeit (Uimp)	8 kV	Terminals supplied	Vorderseitige FC
Überspannungs- kategorie	IV	Position Montage	Jeder
Isolationsspannung (Ui)	800 V	Upline/downline power supply	Si
Thermal regulation	-	Electrical life (415Vac)	10.000 cycles
Magnetic regulation	6 - 8 - 10 x In	Mechanical life	30.000 cycles
Neutral protection	-	Betriebstemperatur	-5°C +65°C
Total power loss	65 W	Lagertemperatur	-20° +65°
Rated short-circuit current making capacity (Icm)	-	Gewicht (kg)	1.9
Rated short-time withstand current for 0,3s (Icw)	-	Breite	140 mm
I _{dn} regulation	-	Höhe	165 mm
DT regulation	-	Tiefe	68 mm

SERVICE BREAKING CAPACITY (ICU)

220/240Vac	65 kA	220/240Vac	65 kA
400/415Vac	36 kA	400/415Vac	36 kA
440Vac	25 kA	440Vac	25 kA
525Vac	25 kA	525Vac	25 kA
690Vac	7,5 kA	690Vac	7,5 kA
250Vdc	40 kA	250Vdc	40 kA

Abmessungen





Produktdatenblatt

GWD9218

Baureihe MSX

Normen / Richtlinien

