



Beschreibung Interruttore non automatico scatolato

Artikelnr. MSXM 250c

Anz. Pole 4P

Bemessungs- strom 250 A

Auslöser -

ELECTRICAL CHARACTERISTICS

Norm	IEC/EN 60947-2
Kategorie	AC-23A, DC-22A
Bemessungs- frequenz (Hz)	50 / 60
Rated operating voltage (Ue)	690 Vac - 250 Vdc
Bemessungsstoß- spannungsfestigkeit (Uimp)	8 kV
Überspannungs- kategorie	IV
Isolationsspannung (Ui)	800 V
Thermal regulation	-
Magnetic regulation	-
Neutral protection	-
Total power loss	76.83 W
Rated short-circuit current making capacity (Icm)	6
Rated short-time withstand current for 0,3s (Icw)	3 kA
I _{dn} regulation	-
DT regulation	-

MECHANICAL CHARACTERISTICS

Ausführung	Fest
DIN rail mounting	Si, tramite accessorio
Accessoriabile con comando motore	Si
Compatible interlock	Lever - Cable
Terminals supplied	Vorderseitige FC
Position Montage	Jeder
Upline/downline power supply	Si
Electrical life (415Vac)	6.000 cycles
Mechanical life	18.000 cycles
Betriebstemperatur	-5°C +65°C
Lagertemperatur	-20° +65°
Gewicht (kg)	1.9
Breite	140 mm
Höhe	165 mm
Tiefe	68 mm


SERVICE BREAKING CAPACITY (ICU)

220/240Vac	-
400/415Vac	-
440Vac	-
525Vac	-
690Vac	-
250Vdc	-

RATED BREAKING CAPACITY (ICS)

220/240Vac	-
400/415Vac	-
440Vac	-
525Vac	-
690Vac	-
250Vdc	-

Abmessungen





Produktdatenblatt

GWD9444

Baureihe MSX

Normen / Richtlinien

